

ConTeXt

commands

EN

ConTeXt

commands

en / english

September 27, 2016

<code>\AfterPar {...}</code> * COMMAND
<code>\Alphabeticnumerals {...}</code> * NUMBER
<code>\AMSTEX</code>
<code>\AmSTeX</code>
<code>\And</code>
<code>\abbreviation [...]¹ {...}² {...}³</code> 1 NAME 2 TEXT 3 CONTENT
<code>\abjadnaivenumerals {...}</code> * NUMBER
<code>\abjadnodotnumerals {...}</code> * NUMBER
<code>\abjadnumerals {...}</code> * NUMBER
<code>\about [...]</code> * REFERENCE
<code>\activatespacehandler {...}</code> * on <u>off</u> yes fixed
<code>\acute {...}</code> * CHARACTER
<code>\adaptcollector [...]¹ [...,...²...,...]</code> 1 NAME 2 inherits: \setupcollector
<code>\adaptfontfeature [...]¹ [...,...²...,...]</code> 1 NAME 2 inherits: \definefontfeature
<code>\adaptlayout [...,¹...] [...,...²...,...]</code> 1 NUMBER 2 height = max DIMENSION lines = NUMBER

`\adaptpapersize [...1,...] [...2,...]`

1 inherits: \setuppapersize

2 inherits: \setuppapersize

`\addfeature [...]`

* NAME

`\addfeature {...}`

* NAME

`\addtocommalist {...} \2..`

1 TEXT

2 CSNAME

`\addtoJSreamble {...} {...}`

1 NAME

2 CONTENT

`\addvalue {...} {...}`

1 NAME

2 TEXT

`\aftersplitstring ... \at ... \to \3..`

1 TEXT

2 TEXT

3 CSNAME

`\aftertestandsplitstring ... \at ... \to \3..`

1 TEXT

2 TEXT

3 CSNAME

`\alignbottom`

`\aligned [...1,...] {...2}`

1

2 CONTENT

`\alignedbox [...1,...] \2.. {...3}`

1

2 CSNAME

3 CONTENT

`\alignedline {...1} {...2} {...3}`

1

2

3 CONTENT

<code>\alignmentcharacter</code>
<code>\allinputpaths</code>
<code>\alphabeticnumerals {...}</code> <code>* NUMBER</code>
<code>\alwayscitation [...¹...,...] [...²...]</code> <code>1 reference = REFERENCE</code> <code> alternative =</code> <code> before = COMMAND</code> <code> after = COMMAND</code> <code> left = COMMAND</code> <code> right = COMMAND</code> <code> inherits: \setupbtx</code> <code>2 REFERENCE</code>
<code>\alwayscitation [...¹...,...] [...²...,...]</code> <code>1 reference = REFERENCE</code> <code> alternative =</code> <code> before = COMMAND</code> <code> after = COMMAND</code> <code> left = COMMAND</code> <code> right = COMMAND</code> <code> inherits: \setupbtx</code> <code>2 KEY = VALUE</code>
<code>\alwayscitation [...¹...] [...²...]</code> <code>1</code> <code>2 REFERENCE</code>
<code>\alwayscite [...¹...,...] [...²...]</code> <code>1 reference = REFERENCE</code> <code> alternative =</code> <code> before = COMMAND</code> <code> after = COMMAND</code> <code> left = COMMAND</code> <code> right = COMMAND</code> <code> inherits: \setupbtx</code> <code>2 REFERENCE</code>
<code>\alwayscite [...¹...,...] [...²...,...]</code> <code>1 reference = REFERENCE</code> <code> alternative =</code> <code> before = COMMAND</code> <code> after = COMMAND</code> <code> left = COMMAND</code> <code> right = COMMAND</code> <code> inherits: \setupbtx</code> <code>2 KEY = VALUE</code>
<code>\alwayscite [...¹...] [...²...]</code> <code>1</code> <code>2 REFERENCE</code>
<code>\ampersand</code>

\anchor [¹...] [²...₂...] [³...₃...] {...⁴}

- 1 NAME
- 2 inherits: \setupplayer
- 3 inherits: \setupplayerinherits: \setupframed
- 4 CONTENT

\appendetoks ¹... \to \²...

- 1 COMMAND
- 2 CSNAME

\appendgvalue {...¹} {...²}

- 1 NAME
- 2 COMMAND

\appendtocommalist {...¹} \²...

- 1 TEXT
- 2 CSNAME

\appendtoks ¹... \to \²...

- 1 COMMAND
- 2 CSNAME

\appendtoksonce ¹... \to \²...

- 1 COMMAND
- 2 CSNAME

\appendvalue {...¹} {...²}

- 1 NAME
- 2 COMMAND

\apply {...¹} {...²}

- 1 CONTENT
- 2 CONTENT

\applyalternativestyle {...^{*}}

- * NAME

\applyprocessor {...¹} {...²}

- 1 NAME
- 2 CONTENT

\applytocharacters \¹... {...²}

- 1 CSNAME
- 2 TEXT

`\applytofirstcharacter \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringchar \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringcharspaced \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringline \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringlinespaced \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringword \1... {2...}`

1 CSNAME

2 TEXT

`\applytosplitstringwordspaced \1... {2...}`

1 CSNAME

2 TEXT

`\applytowords \1... {2...}`

1 CSNAME

2 TEXT

`\arabicdecimals {*...}`

* NUMBER

`\arabicexnumerals {*...}`

* NUMBER

`\arabicnumerals {*...}`

* NUMBER

`\arg {*...}`

* CONTENT

`\asciistr {*...}`

* CONTENT

`\assignalfadimension {...} \^... {...} {...} {...}`

1 small medium big none DIMENSION
2 CSNAME
3 DIMENSION
4 DIMENSION
5 DIMENSION

`\assigndimen \^... {...}`

1 CSNAME
2 DIMENSION

`\assigndimension {...} \^... {...} {...} {...}`

1 [-+]small [-+]medium [-+]big none DIMENSION
2 CSNAME
3 DIMENSION
4 DIMENSION
5 DIMENSION

`\assignifempty \^... {...}`

1 CSNAME
2 COMMAND

`\assigntranslation [...,\^...,...] \to \^...`

1 LANGUAGE = TEXT
2 CSNAME

`\assignvalue {...} \^... {...} {...} {...}`

1 small medium big TEXT
2 CSNAME
3 COMMAND
4 COMMAND
5 COMMAND

`\assignwidth {...} \^... {...} {...}`

1 fit broad DIMENSION
2 CSNAME
3 TEXT
4 DIMENSION

`\assumelongusagecs \^... {...}`

1 CSNAME
2 CONTENT

`\astype {...}`

* CONTENT

`\at {...} {...} [...]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\atleftmargin [...]\atleftmargin [...] {...}`

- 1 reference = REFERENCE
inherits: \setupmargindata
- 2 inherits: \setupmarginframed
- 3 CONTENT

`\atpage [...]`

- * REFERENCE

`\atrighmargin [...]\atrighmargin [...] {...}`

- 1 reference = REFERENCE
inherits: \setupmargindata
- 2 inherits: \setupmarginframed
- 3 CONTENT

`\attachment [...] [...]\attachment [...]`

- 1 NAME
- 2 inherits: \setupattachment

`\attachment [...] [...]\attachment [...]`

- 1 NAME
- 2 inherits: \setupattachment

`\autocap {...}`

- * TEXT

`\autodirhbox ... {...}`

- 1 TEXT
- 2 CONTENT

`\autodirvbox ... {...}`

- 1 TEXT
- 2 CONTENT

`\autodirvtop ... {...}`

- 1 TEXT
- 2 CONTENT

`\autoinsertnextspace`

`\automathematics {...}`

- * CONTENT

$\backslash\text{autosetups } \{ \dots, \dots \}$ * NAME
$\backslash\text{autostarttext } \dots \backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$
$\backslash\text{BeforePar } \{ \dots \}$ * COMMAND
$\backslash\text{Big } \dots$ * CHARACTER
$\backslash\text{Bigg } \dots$ * CHARACTER
$\backslash\text{Biggl } \dots$ * CHARACTER
$\backslash\text{Biggm } \dots$ * CHARACTER
$\backslash\text{Biggr } \dots$ * CHARACTER
$\backslash\text{Bigl } \dots$ * CHARACTER
$\backslash\text{Bigm } \dots$ * CHARACTER
$\backslash\text{Bigr } \dots$ * CHARACTER
$\backslash\text{background } \{ \dots \}$ * CONTENT
$\backslash\text{backgroundimage } \{ \dots^1 \} \{ \dots^2 \} \{ \dots^3 \} \{ \dots^4 \}$ 1 NUMBER 2 DIMENSION 3 DIMENSION 4 COMMAND

`\backgroundimagefill {...} {...} {...} {...}`

- 1 NUMBER
- 2 DIMENSION
- 3 DIMENSION
- 4 COMMAND

`\backgroundline [...] {...}`

- 1 COLOR
- 2 CONTENT

`\background {...}`

- * CONTENT

`\bar {...}`

- * CHARACTER

`\bar {...}`

- * CONTENT

`\basegrid [..., ...*=..., ...]`

- * nx = NUMBER
- ny = NUMBER
- dx = NUMBER
- dy = NUMBER
- factor = NUMBER
- scale = NUMBER
- xstep = NUMBER
- ystep = NUMBER
- offset = DIMENSION
- xoffset = DIMENSION
- yoffset = DIMENSION
- align = middle
- unit = cm mm in pc pt bp
- style =
- color = COLOR

`\baselinebottom`

`\baselineleftbox {...}`

- * CONTENT

`\baselinemiddlebox {...}`

- * CONTENT

`\baselinerrightbox {...}`

- * CONTENT

`\bbox {...}`

- * CONTENT

$\backslash\text{beforesplitstring}$ ¹ ... $\backslash\text{at}$ ² ... $\backslash\text{to}$ ³ ... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{beforetestandsplitstring}$ ¹ ... $\backslash\text{at}$ ² ... $\backslash\text{to}$ ³ ... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{beginblock}$ [...*,...] ... $\backslash\text{endblock}$ * + -
$\backslash\text{beginhbox}$
$\backslash\text{beginofshapebox}$... $\backslash\text{endofshapebox}$
$\backslash\text{beginvbox}$
$\backslash\text{begstrut}$... $\backslash\text{endstrut}$
$\backslash\text{big}$... * CHARACTER
$\backslash\text{bigbodyfont}$
$\backslash\text{bigg}$... * CHARACTER
$\backslash\text{bigger}$
$\backslash\text{biggl}$... * CHARACTER
$\backslash\text{biggm}$... * CHARACTER
$\backslash\text{biggr}$... * CHARACTER
$\backslash\text{bigl}$... * CHARACTER
$\backslash\text{bigm}$... * CHARACTER
$\backslash\text{bigr}$... * CHARACTER

<code>\bigskip</code>
<code>\binom {¹.} {².}</code> 1 CONTENT 2 CONTENT
<code>\bitmapimage [...,¹...,...] {².}</code> 1 color = rgb cmyk gray width = DIMENSION height = DIMENSION x = NUMBER y = NUMBER 2 NUMBER
<code>\blackrule [...,[*]...,...]</code> * inherits: \setupblackrules
<code>\blackrules [...,[*]...,...]</code> * inherits: \setupblackrules
<code>\blank [...,[*]...,...]</code> * inherits: \vspacing
<code>\blap {[*].}</code> * CONTENT
<code>\bleed [...,¹...,...] {².}</code> 1 inherits: \setupbleeding 2 CONTENT
<code>\bleedheight</code>
<code>\bleedwidth</code>
<code>\blockquote {[*].}</code> * CONTENT
<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\bold</code>
<code>\boldface</code>
<code>\bolditalic</code>
<code>\boldslanted</code>

<code>\bookmark [...] {...}</code> 1 SECTION LIST 2 TEXT
<code>\booleanmodevalue {...}</code> * NAME
<code>\bottombox {...}</code> * CONTENT
<code>\bottomleftbox {...}</code> * CONTENT
<code>\bottomrightbox {...}</code> * CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...} {...}</code> 1 NAME 2 NUMBER
<code>\boxofsize \^1... .. ^2... .. {...}</code> 1 CSNAME 2 DIMENSION 3 CONTENT
<code>\boxreference [...,^1,...] \^2... {...}</code> 1 REFERENCE 2 CSNAME 3 CONTENT
<code>\bpar ... \epar</code>
<code>\bpos {...}</code> * NAME
<code>\breve {...}</code> * CHARACTER
<code>\bTABLE [...,...^*...,...] ... \eTABLE</code> * inherits: \setupTABLE
<code>\bTABLEbody [...,...^*...,...] ... \eTABLEbody</code> * inherits: \setupTABLE
<code>\bTABLEfoot [...,...^*...,...] ... \eTABLEfoot</code> * inherits: \setupTABLE

<p><code>\bTABLEhead [...,.*=...,...] ... \eTABLEhead</code></p> <p>* inherits: \setupTABLE</p>
<p><code>\bTABLEnext [...,.*=...,...] ... \eTABLEnext</code></p> <p>* inherits: \setupTABLE</p>
<p><code>\bTC [...,.*=...,...] ... \eTC</code></p> <p>* inherits: \bTD</p>
<p><code>\bTD [...,.*=...,...] ... \eTD</code></p> <p>* nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER n = NUMBER m = NUMBER action = REFERENCE inherits: \setupTABLE</p>
<p><code>\bTDs [...*] ... \eTDs</code></p> <p>* NAME</p>
<p><code>\bTH [...,.*=...,...] ... \eTH</code></p> <p>* inherits: \bTD</p>
<p><code>\bTN [...,.*=...,...] ... \eTN</code></p> <p>* inherits: \bTD</p>
<p><code>\bTR [...,.*=...,...] ... \eTR</code></p> <p>* inherits: \setupTABLE</p>
<p><code>\bTRs [...*] ... \eTRs</code></p> <p>* NAME</p>
<p><code>\bTX [...,.*=...,...] ... \eTX</code></p> <p>* inherits: \bTD</p>
<p><code>\bTY [...,.*=...,...] ... \eTY</code></p> <p>* inherits: \setupTABLE</p>
<p><code>\bthiddencitation [...*]</code></p> <p>* REFERENCE</p>
<p><code>\btxabbreviatedjournal {...*}</code></p> <p>* NAME</p>
<p><code>\btxaddjournal [...¹.] [...².]</code></p> <p>1 NAME 2 NAME</p>

```
\btxfalwayscitation [...1...] [...2]
```

```
1  reference    = REFERENCE
   alternative  =
   before      = COMMAND
   after       = COMMAND
   left        = COMMAND
   right       = COMMAND
   inherits: \setupbtx
```

```
2  REFERENCE
```

```
\btxfalwayscitation [...1...] [...2...]
```

```
1  reference    = REFERENCE
   alternative  =
   before      = COMMAND
   after       = COMMAND
   left        = COMMAND
   right       = COMMAND
   inherits: \setupbtx
```

```
2  KEY = VALUE
```

```
\btxfalwayscitation [...1] [...2]
```

```
1
```

```
2  REFERENCE
```

```
\btxauthorfield {...}
```

```
*  initials firstnames vons surnames juniors
```

```
\btxdetail {...}
```

```
*
```

```
\btxdirect {...}
```

```
*
```

```
\btxdoif {...} {...}
```

```
1
```

```
2  TRUE
```

```
\btxdoifcombiinlistelse {...1} {...2} {...3} {...4}
```

```
1  NAME
```

```
2  NAME
```

```
3  TRUE
```

```
4  FALSE
```

```
\btxdoifelse {...1} {...2} {...3}
```

```
1
```

```
2  TRUE
```

```
3  FALSE
```

\btxdoifelsecombiinlist {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdoifelsesameasprevious {...} {...} {...}

- 1
- 2 TRUE
- 3 FALSE

\btxdoifelsesameaspreviouschecked {...} {...} {...} {...}

- 1 always doublesided
- 2
- 3 TRUE
- 4 FALSE

\btxdoifelseuservariable {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxdoifnot {...} {...}

- 1
- 2 TRUE

\btxdoifsameaspreviouscheckedelse {...} {...} {...} {...}

- 1 always doublesided
- 2
- 3 TRUE
- 4 FALSE

\btxdoifsameaspreviouselse {...} {...} {...}

- 1
- 2 TRUE
- 3 FALSE

\btxdoifuservariableelse {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxexpandedjournal {...}

- * NAME

\btxfield {...}

- *

\btxfielddname {...} *
\btxfielddtype {...} *
\btxfirstofrange {...} * volume pages
\btxflush {...} *
\btxflushauthor [...] ¹ {...} ² 1 num normal normalshort inverted invertedshort 2
\btxflushauthorinverted {...} *
\btxflushauthorinvertedshort {...} *
\btxflushauthorname {...} *
\btxflushauthornormal {...} *
\btxflushauthornormalshort {...} *
\btxflushsuffix
\btxfoundname {...} *
\btxfoundtype {...} *
\btxhybridcite [..., ¹ ...,...] ² [...] 1 reference = REFERENCE alternative = before = COMMAND after = COMMAND left = COMMAND right = COMMAND inherits: \setupbtx 2 REFERENCE

`\btxhybridcite [...1...] [...2...]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 KEY = VALUE

`\btxhybridcite [...1] [...2]`

1

2 REFERENCE

`\btxhybridcite {...}`

* REFERENCE

`\btxlabellanguage`

`\btxlabeltext {...}`

* KEY

`\btxlistcitation [...1...] [...2]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 REFERENCE

`\btxlistcitation [...1...] [...2...]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 KEY = VALUE

`\btxlistcitation [...1] [...2]`

1

2 REFERENCE

`\btxloadjournalist [...*]`

* FILE

`\btxoneorrange {...1} {...2} {...3}`

1 volume pages

2 TRUE

3 FALSE

`\btxremapauthor [...]1 [...]2`

1 TEXT

2 TEXT

`\btxsavejournalist [...]*`

* FILE

`\btxsetup {...}`

* NAME

`\btxsingularorplural {...}1 {...}2 {...}3`

1 editor producer director

2 TRUE

3 FALSE

`\btxsingularplural {...}1 {...}2 {...}3`

1 editor producer director

2 TRUE

3 FALSE

`\btxttextcitation [...]1 [...]2`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 REFERENCE

`\btxttextcitation [...]1 [...]2`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 KEY = VALUE

`\btxttextcitation [...]1 [...]2`

1

2 REFERENCE

`\buildmathaccent {...}1 {...}2`

1 CHARACTER

2 CHARACTER

`\buildtextaccent {...}1 {...}2`

1 CHARACTER

2 CHARACTER

<code>\buildtextbottomcomma {...}</code> * CHARACTER
<code>\buildtextbottomdot {...}</code> * CHARACTER
<code>\buildtextcedilla {...}</code> * CHARACTER
<code>\buildtextgrave {...}</code> * CHARACTER
<code>\buildtextmacron {...}</code> * CHARACTER
<code>\buildtextognek {...}</code> * CHARACTER
<code>\button [...,¹...,²...,³...] {...} [...]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\button [...,¹...,²...,³...] {...} [...]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\but [¹...] ²... \\\</code> 1 REFERENCE 2 TEXT
<code>\but [¹...] [...,²...]</code> 1 REFERENCE 2 REFERENCE
<code>\Caps {...}</code> * TEXT
<code>\Character {...}</code> * NUMBER
<code>\Characters {...}</code> * NUMBER
<code>\CONTEXT</code>
<code>\ConTeXt</code>

<code>\Context</code>
<code>\ConvertConstantAfter \¹... {\²...} {\³...}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\ConvertToConstant \¹... {\²...} {\³...}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\calligraphic</code>
<code>\camel {\[*]...}</code> * TEXT
<code>\catcodetablename</code>
<code>\cbox \¹... {\²...}</code> 1 TEXT 2 CONTENT
<code>\centeraligned {\[*]...}</code> * CONTENT
<code>\centerbox \¹... {\²...}</code> 1 TEXT 2 CONTENT
<code>\centeredbox \¹... {\²...}</code> 1 TEXT 2 CONTENT
<code>\centeredlastline</code>
<code>\centerednextbox \¹... {\²...}</code> 1 TEXT 2 CONTENT
<code>\centerline {\[*]...}</code> * CONTENT
<code>\cfrac [\¹...] {\²...} {\³...}</code> 1 l c r ll lc lr cl cc cr rl rc rr 2 CONTENT 3 CONTENT

<code>\chapter [...¹,...] {...²}</code> 1 REFERENCE 2 TEXT
<code>\character {...}</code> * NUMBER
<code>\characterkerning [...¹] {...²}</code> 1 NUMBER 2 TEXT
<code>\characters {...}</code> * NUMBER
<code>\chardescription {...}</code> * NUMBER
<code>\charwidthlanguage</code>
<code>\check {...}</code> * CHARACTER
<code>\checkcharacteralign {...}</code> * CONTENT
<code>\checkedchar {...¹} {...²}</code> 1 NUMBER 2 CHARACTER
<code>\checkedfiller {...}</code> * sym symbol rule width space NAME COMMAND
<code>\checkedstrippedcsname \...</code> * CSNAME
<code>\checkedstrippedcsname ...</code> * TEXT
<code>\checkinjector [...]</code> * NAME
<code>\checknextindentation [...]</code> * yes no auto
<code>\checknextinjector [...]</code> * NAME

$\backslash\text{checkpage}$ [¹ ...] [² ...,...] 1 NAME 2 inherits: \setuppagechecker
$\backslash\text{checkparameters}$ [...] * TEXT
$\backslash\text{checkpreviousinjector}$ [...] * NAME
$\backslash\text{checksoundtrack}$ {...} * NAME
$\backslash\text{checktwopassdata}$ {...} * NAME
$\backslash\text{chem}$ { ¹ ...} { ² ...} { ³ ...} 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{chemical}$ [¹ ...] [..., ² ...] [..., ³ ...] 1 NAME 2 TEXT 3 TEXT
$\backslash\text{chemicalbottext}$ {...} * TEXT
$\backslash\text{chemicalmidtext}$ {...} * TEXT
$\backslash\text{chemicalsymbol}$ [...] * NAME
$\backslash\text{chemicaltext}$ {...} * TEXT
$\backslash\text{chemicaltoptext}$ {...} * TEXT
$\backslash\text{chineseallnumerals}$ {...} * NUMBER
$\backslash\text{chinesecapnumerals}$ {...} * NUMBER

`\chinesenumerals {...}`

* NUMBER

`\citation [...,\stackrel{1}{=},...] [\stackrel{2}{=}]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 REFERENCE

`\citation [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 KEY = VALUE

`\citation [\stackrel{1}{=}] [\stackrel{2}{=}]`

1

2 REFERENCE

`\citation {...}`

* REFERENCE

`\cite [...,\stackrel{1}{=},...] [\stackrel{2}{=}]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 REFERENCE

`\cite [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 KEY = VALUE

`\cite [\stackrel{1}{=}] [\stackrel{2}{=}]`

1

2 REFERENCE

`\cite {...}`

* REFERENCE

<code>\clap {...}</code> * CONTENT
<code>\classfont {...} {...}</code> 1 NAME 2 FONT
<code>\cldcommand {...}</code> * COMMAND
<code>\cldcontext {...}</code> * COMMAND
<code>\cldloadfile {...}</code> * FILE
<code>\cldprocessfile {...}</code> * FILE
<code>\cleftarrow {...} {...}</code> 1 TEXT 2 TEXT
<code>\clip [...,\u{1}...,...] {...}</code> 1 inherits: \setupclipping 2 CONTENT
<code>\clonefield [...]\u{1} [...] [\u{2}...] [\u{3}...] [...,\u{4}...]</code> 1 NAME 2 NAME 3 NAME 4 NAME
<code>\collect {...}</code> * CONTENT
<code>\collectedtext [...,\u{1}...,...] [...,\u{2}...,...] {\u{3}} {\u{4}}</code> 1 inherits: \setupcollector 2 style = color = COLOR inherits: \setupframed 3 TEXT 4 CONTENT
<code>\collectexpanded {...}</code> * CONTENT

<code>\color [...]{...}</code> 1 COLOR 2 CONTENT
<code>\colorbar [...*,...]</code> * COLOR
<code>\colorcomponents {...}</code> * COLOR
<code>\colored [...¹]{...²}</code> 1 COLOR 2 CONTENT
<code>\colored [...,...¹,...]{...²}</code> 1 inherits: \definecolor 2 CONTENT
<code>\coloronly [...¹]{...²}</code> 1 COLOR 2 CONTENT
<code>\colorvalue {...}</code> * COLOR
<code>\column [...*,...]</code> * inherits: \columnbreak
<code>\columnbreak [...*,...]</code> * NAME
<code>\combinepages [...¹][...,...²,...]</code> 1 FILE 2 alternative = a b c horizontal vertical n = NUMBER nx = NUMBER ny = NUMBER start = NUMBER stop = NUMBER distance = DIMENSION top = COMMAND bottom = COMMAND left = COMMAND right = COMMAND before = COMMAND after = COMMAND inbetween = COMMAND frame = on <u>off</u> background = foreground color NAME backgroundcolor = COLOR
<code>\commalistelement</code>

$\backslash\text{commalistsentence}$ [... ¹ ,...] [... ² ,...] 1 TEXT 2 TEXT
$\backslash\text{commalistsize}$
$\backslash\text{comment}$ [... ¹] [... ² ,... ² ,...] {... ³ .} 1 TEXT 2 inherits: $\backslash\text{setupcomment}$ 3 TEXT
$\backslash\text{comment}$ [... ¹] [... ² ,... ² ,...] {... ³ .} 1 TEXT 2 inherits: $\backslash\text{setupcomment}$ 3 TEXT
$\backslash\text{comparecolorgroup}$ [...*] * NAME
$\backslash\text{comparedimension}$ {... ¹ .} {... ² .} 1 DIMENSION 2 DIMENSION
$\backslash\text{comparedimensioneps}$ {... ¹ .} {... ² .} 1 DIMENSION 2 DIMENSION
$\backslash\text{comparepalet}$ [...*] * NAME
$\backslash\text{completebtxrendering}$ [... ¹ .] [... ² ,... ² ,...] 1 NAME 2 inherits: $\backslash\text{setupbtxrendering}$
$\backslash\text{completecombinedlist}$ [... [*] ,... [*] ,...] * inherits: $\backslash\text{setuplist}$
$\backslash\text{completecontent}$ [... [*] ,... [*] ,...] * inherits: $\backslash\text{setuplist}$
$\backslash\text{completeindex}$ [... [*] ,... [*] ,...] * inherits: $\backslash\text{setupregister}$
$\backslash\text{completelist}$ [... ¹ .] [... ² ,... ² ,...] 1 LIST 2 inherits: $\backslash\text{setuplist}$

<code>\completelistofabbreviations [...,..[*]...,...]</code> <code>* inherits: \setupsynonyms</code>
<code>\completelistofchemicals [...,..[*]...,...]</code> <code>* inherits: \setuplist</code>
<code>\completelistoffigures [...,..[*]...,...]</code> <code>* inherits: \setuplist</code>
<code>\completelistoffloats [...,..[*]...,...]</code> <code>* inherits: \setuplist</code>
<code>\completelistofgraphics [...,..[*]...,...]</code> <code>* inherits: \setuplist</code>
<code>\completelistofintermezzi [...,..[*]...,...]</code> <code>* inherits: \setuplist</code>
<code>\completelistoflogos [...,..[*]...,...]</code> <code>* inherits: \setupsorting</code>
<code>\completelistofpublications [...¹.] [...,..²...,...]</code> <code>1 NAME</code> <code>2 inherits: \setupbtxrendering</code>
<code>\completelistofsorts [...¹.] [...,..²...,...]</code> <code>1 SINGULAR</code> <code>2 inherits: \setupsorting</code>
<code>\completelistofsorts [...,..[*]...,...]</code> <code>* inherits: \setupsorting</code>
<code>\completelistofsynonyms [...¹.] [...,..²...,...]</code> <code>1 SINGULAR</code> <code>2 inherits: \setupsynonyms</code>
<code>\completelistofsynonyms [...,..[*]...,...]</code> <code>* inherits: \setupsynonyms</code>
<code>\completelistoftables [...,..[*]...,...]</code> <code>* inherits: \setuplist</code>
<code>\completepagenumber</code>
<code>\completeregister [...¹.] [...,..²...,...]</code> <code>1 NAME</code> <code>2 inherits: \setupregister</code>

\completeregister [...,.*=...,...] * inherits: \setupregister
\complexorsimpleempty *... * CSNAME
\complexorsimpleempty {...} * TEXT CSNAME
\complexorsimple *... * CSNAME
\complexorsimple {...} * TEXT CSNAME
\component [...] * FILE
\component ... * FILE
\composedcollector {...} * NAME
\composedlayer {...} * NAME
\compresult
\com ... \\ * TEXT
\constantdimen *... * CSNAME
\constantdimenargument *... * CSNAME
\constantemptyargument *... * CSNAME
\constantnumber *... * CSNAME
\constantnumberargument *... * CSNAME

\backslash contentreference [... ¹ ,...] [... ² ,... ² ,...] {... ³ } 1 REFERENCE 2 inherits: \setupframed 3 CONTENT
\backslash continuednumber {...} * NUMBER
\backslash continueifinputfile {...} * FILE
\backslash convertargument ... ¹ \to ... ² 1 TEXT 2 CSNAME
\backslash convertcommand \... ¹ \to \... ² 1 CSNAME 2 CSNAME
\backslash convertedcounter [... ¹] [... ² ,... ² ,...] 1 NAME 2 inherits: \setupcounter
\backslash convertedddimen {... ¹ } {... ² } 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc
\backslash convertedsubcounter [... ¹] [... ²] [... ³ ,... ³ ,...] 1 NAME 2 3 inherits: \setupcounter
\backslash convertmonth {...} * NUMBER
\backslash convertnumber {... ¹ } {... ² } 1 empty default none month:mnem character Character characters Characters a A Numbers word words Word Words n N romannumerals Romannumerals i I r R KR RK greek Greek g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmukhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirlenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set ₀ set ₁ set ₂ set ₃ continued NAME 2 NUMBER
\backslash convertvalue ... ¹ \to ... ² 1 NAME 2 CSNAME
\backslash convertvboxtohbox

`\copybtxlabeltext [...]1 [...,...2...,...]`

1 LANGUAGE
2 KEY = KEY

`\copyfield [...]1 [...]2`

1 NAME
2 NAME

`\copyheadtext [...]1 [...,...2...,...]`

1 LANGUAGE
2 KEY = KEY

`\copylabeltext [...]1 [...,...2...,...]`

1 LANGUAGE
2 KEY = KEY

`\copylabeltext [...]1 [...,...2...,...]`

1 LANGUAGE
2 KEY = KEY

`\copymathlabeltext [...]1 [...,...2...,...]`

1 LANGUAGE
2 KEY = KEY

`\copyoperatortext [...]1 [...,...2...,...]`

1 LANGUAGE
2 KEY = KEY

`\coppages [...]1 [...,...2...,...]3 [...,...3...,...]`

1 FILE
2 marking = on *off*
offset = DIMENSION
n = NUMBER
3 inherits: \setupexternalfigure

`\copyparameters [...]1 [...]2 [...,...3...,...]`

1 TEXT
2 TEXT
3 KEY

`\copyposition {...}1 {...}2`

1 NAME
2 NAME

`\copyprefixtext [...]1 [...,...2...,...]`

1 LANGUAGE
2 KEY = KEY

$\backslash\text{copytaglabeltext}$ [¹ ...] [² ...,...] 1 LANGUAGE 2 KEY = KEY
$\backslash\text{copyunittext}$ [¹ ...] [² ...,...] 1 LANGUAGE 2 KEY = KEY
$\backslash\text{correctwhitespace}$ {...} * CONTENT
$\backslash\text{countersubs}$ [¹ ...] [² ...] 1 NAME 2 NUMBER
$\backslash\text{counttoken}$ ¹ ... \in ² ... \to \sup{3}... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{counttokens}$ ¹ ... \to \sup{2}... 1 TEXT 2 CSNAME
$\backslash\text{cramped}$ {...} * CONTENT
$\backslash\text{crampedclap}$ {...} * CONTENT
$\backslash\text{crampedllap}$ {...} * CONTENT
$\backslash\text{crampedrlap}$ {...} * CONTENT
$\backslash\text{crightarrow}$ { ¹ ...} { ² ...} 1 TEXT 2 TEXT
$\backslash\text{crightoverleftarrow}$ { ¹ ...} { ² ...} 1 TEXT 2 TEXT
$\backslash\text{ctop}$ ¹ ... { ² ...} 1 TEXT 2 CONTENT

\ctxcommand {...} * COMMAND
\ctxdirectcommand {...} * COMMAND
\ctxdirectlua {...} * COMMAND
\ctxfunction {...} * NAME
\ctxfunctiondefinition
\ctxfunction
\ctxlatecommand {...} * COMMAND
\ctxlatelua {...} * COMMAND
\ctxloadluafile {...} * FILE
\ctxlua {...} * COMMAND
\ctxluabuffer [...] * BUFFER
\ctxluacode {...} * COMMAND
\ctxreport {...} * COMMAND
\ctxsprint {...} * COMMAND
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} * KEY
\currentcommalistitem

<code>\currentcomponent</code>
<code>\currentdate [...*,...]</code> * yes moth day weekday y yy Y m mm M d dd D w W space _ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT
<code>\currentenvironment</code>
<code>\currentfeaturetest</code>
<code>\currentheadnumber</code>
<code>\currentinterface</code>
<code>\currentlabel [...¹,...]{...²}</code> 1 REFERENCE 2 TEXT
<code>\currentlanguage</code>
<code>\currentlistentrydestinationattribute</code>
<code>\currentlistentrylimitedtext {...}</code> * TEXT
<code>\currentlistentrynumber</code>
<code>\currentlistentrypagenumber</code>
<code>\currentlistentryreferenceattribute {...}</code> * number text pagenumber all
<code>\currentlistentrytitle</code>
<code>\currentlistentrytitlerendered</code>
<code>\currentlistsymbol</code>
<code>\currentmainlanguage</code>
<code>\currentmessagetext</code>
<code>\currentmoduleparameter {...}</code> * KEY
<code>\currentoutputstream</code>
<code>\currentproduct</code>
<code>\currentproject</code>

<code>\currentregime</code>
<code>\currentregisterpageuserdata {...}</code> * KEY
<code>\currentresponses</code>
<code>\currenttime [...,*,...]</code> * h m TEXT
<code>\currentvalue</code>
<code>\currentxtablecolumn</code>
<code>\currentxtablerow</code>
<code>\d {...}</code> * CHARACTER
<code>\datasetvariable {...} {...} {...}</code> 1 NAME 2 NAME NUMBER 3 KEY realpage
<code>\date [...,...¹...,...] [...,...²...,...]</code> 1 d = NUMBER m = NUMBER y = NUMBER 2 inherits: \currentdate
<code>\dayoftheweek {...} {...} {...}</code> 1 NUMBER 2 NUMBER 3 NUMBER
<code>\dayspermonth {...} {...}</code> 1 NUMBER 2 NUMBER
<code>\dbinom {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\ddot {...}</code> * CHARACTER
<code>\decrementcounter [...¹] [...²]</code> 1 NAME 2 NUMBER

<code>\decrementedcounter [...]</code> * NAME
<code>\decrementpagenumber</code>
<code>\decrementsubpagenumber</code>
<code>\decrementvalue {...}</code> * NAME
<code>\decrement *...</code> * CSNAME
<code>\decrement cd:parentheses-1</code> * CSNAME NUMBER
<code>\defaultinterface</code>
<code>\defaultobjectpage</code>
<code>\defaultobjectreference</code>
<code>\defcatcodecommand \¹... \²... {...}</code> 1 CSNAME 2 CHARACTER NUMBER 3 COMMAND
<code>\defconvertedargument \¹... {...}</code> 1 CSNAME 2 TEXT
<code>\defconvertedcommand \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\defconvertedvalue \¹... {...}</code> 1 CSNAME 2 NAME
<code>\define [¹] \²... {...}</code> 1 NUMBER 2 CSNAME 3 CONTENT
<code>\defineaccent ¹... ²... ³...</code> 1 CHARACTER 2 CHARACTER 3 CHARACTER

`\defineactivecharacter 1... {2...}`

1 CHARACTER

2 COMMAND

`\definealternativestyle [...1,...] [2...] [3...]`

1 NAME

2 COMMAND

3 COMMAND

`\defineanchor [1...] [2...] [...,3...,...] [...,4...,...]`

1 NAME

2 NAME

3 inherits: \setupplayer

4 inherits: \setupplayerinherits: \setupframed

`\defineattachment [1...] [2...] [...,3...,...]`

1 NAME

2 NAME

3 inherits: \setupattachment

`\defineattribute [1...] [...2,...]`

1 NAME

2 local global public private

`\definebackground [1...] [2...] [...,3...,...]`

1 NAME

2 NAME

3 inherits: \setupbackground

`\definebar [1...] [2...] [...,3...,...]`

1 NAME

2 NAME

3 inherits: \setupbar

`\defineblock [1...] [2...] [...,3...,...]`

1 NAME

2 NAME

3 inherits: \setupblock


```
\definebodyfontenvironment [...]1 [...]2 [...,...3...,...]
```

```
1  NAME
2  default DIMENSION
3  big          = DIMENSION NUMBER
   small       = DIMENSION NUMBER
   a           = DIMENSION NUMBER
   b           = DIMENSION NUMBER
   c           = DIMENSION NUMBER
   d           = DIMENSION NUMBER
   text        = DIMENSION NUMBER
   x           = DIMENSION NUMBER
   xx          = DIMENSION NUMBER
   script      = DIMENSION NUMBER
   scriptscript = DIMENSION NUMBER
   interlinespace = DIMENSION
   em          = slanted italic
   *           = NUMBER
```

```
\definebodyfontswitch [...]1 [...,2...]
```

```
1  NAME
2  inherits: \setupbodyfont
```

```
\definebodyfont [...]1,... [...]2,... [...]3,... [...,...4...,...]
```

```
1  NAME default
2  NAME DIMENSION
3  rm ss tt hw cg
4  tf    = FILE
   bf    = FILE
   it    = FILE
   sl    = FILE
   bi    = FILE
   bs    = FILE
   sc    = FILE
   mr    = FILE
   mrlr  = FILE
   mrrl  = FILE
   mb    = FILE
   mblr  = FILE
   mbrl  = FILE
```

```
\definebodyfont [...]1,... [...]2,... [...]3,... [...]4,
```

```
1  NAME default
2  NAME DIMENSION
3  rm ss tt hw cg
4  NAME
```

```
\definebreakpoint [...]1 [...]2 [...,...3...,...]
```

```
1  NAME
2  CHARACTER
3  type      = 1 2 3 4 5
   nleft     = NUMBER
   nright    = NUMBER
   left      = COMMAND
   middle    = COMMAND
   right     = COMMAND
   language  = LANGUAGE
```

```
\definebreakpoints [...]*
```

```
*  NAME
```

```
\definebtx [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtx

```
\definebtxdataset [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtxdataset

```
\definebtxregister [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtxregister

```
\definebtxrendering [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupbtxrendering

```
\definebuffer [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 BUFFER
- 3 inherits: \setupbuffer

```
\definebutton [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupbutton

```
\definecapitals [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupcapitals

```
\definecharacter 1... 2...
```

- 1 CHARACTER
- 2 NUMBER

```
\definecharacterkerning [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupcharacterkerning

```
\definecharacterspacing [...]
```

- * NAME

`\definechemical [...]{...}`

- 1 NAME
- 2 CONTENT

`\definechemicals [...][...][...3...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupchemical

`\definechemicalsymbol [...][...]`

- 1 NAME
- 2 TEXT

`\definecollector [...][...][...3...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupcollector

`\definecolorgroup [...][...][x:y:3z,...]`

- 1 NAME
- 2 gray rgb cmyk spot
- 3 TRIPLET

`\definecolor [...][...2...]`

- 1 NAME
- 2 r = NUMBER
g = NUMBER
b = NUMBER
c = NUMBER
m = NUMBER
y = NUMBER
k = NUMBER
h = NUMBER
s = NUMBER
v = NUMBER
x = NUMBER
a =
t = NUMBER

`\definecolor [...][...]`

- 1 NAME
- 2 COLOR

`\definecolumnbreak [...][...2,...]`

- 1 NAME
- 2

`\definecombination [...][...][...3...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupcombination

```
\definecombinedlist [...]1 [...,2...] [...,3...,...]
```

```
1 NAME
2 LIST
3 inherits: \setuplist
```

```
\definecommand ...1 ...2
```

```
1 CHARACTER
2 COMMAND
```

```
\definecomment [...]1 [...]2 [...,3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupcomment
```

```
\definecomplexorsimpleempty \...
```

```
* CSNAME
```

```
\definecomplexorsimpleempty {...}
```

```
* TEXT CSNAME
```

```
\definecomplexorsimple \...
```

```
* CSNAME
```

```
\definecomplexorsimple {...}
```

```
* TEXT CSNAME
```

```
\defineconversionset [...]1 [...,2...] [...]3
```

```
1 NAME SECTIONBLOCK:NAME
2 NAME PROCESSOR->NAME
3 NAME PROCESSOR->NAME
```

```
\defineconversion [...]1 [...]2 [...]3
```

```
1 LANGUAGE
2 NAME
3 CSNAME
```

```
\defineconversion [...]1 [...]2 [...,3...]
```

```
1 LANGUAGE
2 NAME
3 TEXT
```

```
\definecounter [...]1 [...]2 [...,3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupcounter
```

`\definedataset [.1.] [.2.] [.,.,.3.,.,.]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupdataset

`\definedelimitedtext [.1.] [.2.] [.,.,.3.,.,.]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupdelimitedtext

`\definedescription [.1.] [.2.] [.,.,.3.,.,.]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupdescription

`\definedfont [.*.]`

- * FONT

`\defineeffect [.1.] [.2.] [.,.,.3.,.,.]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupeffect

`\defineenumerations [.1.] [.2.] [.,.,.3.,.,.]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupenumeration

`\defineexpandable [.1.] \.2. {.3.}`

- 1 NUMBER
- 2 CSNAME
- 3 CONTENT

`\defineexternalfigure [.1.] [.2.] [.,.,.3.,.,.]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupexternalfigure

```
\definefallbackfamily [.1.] [..2.] [...3.] [...,4...,...]
```

```
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
  mathematics
3 FONT
4 rscale      = NUMBER
  designsizes = default auto
  goodies     = FILE
  range       = NUMBER NAME
  offset      = NUMBER NAME
  check       = yes no
  force       = yes no
  features    = NAME
  tf          = TEXT
  bf          = TEXT
  it          = TEXT
  sl          = TEXT
  bi          = TEXT
  bs          = TEXT
  sc          = TEXT
```

```
\definefallbackfamily [.1.] [..2.] [...3.] [...,4...,...]
```

```
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
  mathematics
3 FONT
4 NAME
```

```
\definefield [.1.] [..2.] [...3.] [...,4...,...] [...5.]
```

```
1 NAME
2 radio sub text line push check signature
3 NAME
4 NAME
5 NAME
```

```
\definefieldbody [..1.] [...2.] [...,3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupfieldbody
```

```
\definefieldbodyset [..1.] [...,2...,...]
```

```
1 NAME
2 NAME
```

```
\definefieldcategory [...1.] [...2.] [...,3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupfieldcategory
```

```
\definefieldstack [...1.] [...,2...,...] [...,3...,...]
```

```
1 NAME
2 NAME
3 inherits: \setupfieldcategory
```

```
\definefiguresymbol [...]1 [...]2 [...,...3...,...]
```

1 NAME

2 FILE NAME

3 inherits: \externalfigure

```
\definefileconstant {...}1 {...}2
```

1 NAME

2 NAME

```
\definefilefallback [...]1 [...,2...,...]
```

1 NAME

2 FILE

```
\definefilesynonym [...]1 [...]2
```

1 NAME

2 FILE

```
\definefiller [...]1 [...]2 [...,...3...,...]
```

1 NAME

2 NAME

3 inherits: \setupfiller

```
\definefirstline [...]1 [...]2 [...,...3...,...]
```

1 NAME

2 NAME

3 inherits: \setupfirstline

```
\definefittingpage [...]1 [...]2 [...,...3...,...]
```

1 NAME

2 NAME

3 inherits: \setupfittingpage

```
\definefloat [...]1 [...]2 [...,...3...,...]
```

1 SINGULAR

2 PLURAL

3 inherits: \setupfloat

```
\definefloat [...]1 [...]2 [...]3
```

1 SINGULAR

2 PLURAL

3 SINGULAR

```
\definefontalternative [...]*
```

* NAME

```
\definefontfallback [1...] [2] [...,3...] [...,4...,...]
```

```
1  NAME
2  FONT NAME
3  NAME NUMBER
4  rscale = NUMBER
    force = yes no
    check = yes no
    offset = NUMBER NAME
```

```
\definefontfamilypreset [1...] [...,2...,...]
```

```
1  NAME
2  inherits: \definefontfamily
```

```
\definefontfamilypreset [1...] [2]
```

```
1  NAME
2  NAME
```

```
\definefontfamily [1...] [2] [3] [...,4...,...]
```

```
1  NAME
2  rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
    mathematics
3  FONT
4  rscale      = NUMBER
    designsize = default auto
    goodies    = FILE
    features   = NAME
    tf         = TEXT
    bf         = TEXT
    it         = TEXT
    sl         = TEXT
    bi         = TEXT
    bs         = TEXT
    sc         = TEXT
```

```
\definefontfamily [1...] [2] [3] [...,4...,...]
```

```
1  NAME
2  rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
    mathematics
3  FONT
4  NAME
```


`\definefontfeature [...]1 [...]2 [...,...3...,...]`

```
1  NAME
2  NAME
3  language      = NAME
   script        = NAME auto
   mode          = node base auto none
   liga          = yes no
   kern          = yes no
   extrakerns    = yes no
   tlig          = yes no
   trep          = yes no
   missing       = yes no
   dummies       = yes no
   analyze       = yes no
   unicoding     = yes no
   expansion     = NAME
   protrusion    = NAME
   nostackmath   = yes no
   realdimensions = yes no
   itlc          = yes no
   textitalics   = yes no
   mathitalics   = yes no
   slant         = NUMBER
   extend        = NUMBER
   dimensions    = NUMBER
   boundingbox    = yes no
   compose       = yes no
   char-ligatures = yes no
   compat-ligatures = yes no
   goodies       = FILE
   extrafeatures = yes no
   featureset    = NAME
   colorsheme    = NAME
   postprocessor = NAME
   mathdimensions = NAME
   keepligatures = yes no auto
   devanagari    = yes no
   features      = yes no
   tcom          = yes no
   anum         = yes no
   mathsize      = yes no
   decomposehangul = yes no
   mathalternatives = yes no
   mathgaps      = yes no
   NAME         = yes no
   CD:MATHNOLIMITSMODE = NUMBER
```

`\definefontfile [...]1 [...]2 [...,...3...,...]`

```
1  NAME
2  FILE
3  features      = NAME
   fallbacks     = NAME
   goodies       = NAME
   designsize    = auto default
```

`\definefontsize [...]`

```
*  NAME
```

`\definefontsolution [...]1 [...]2 [...,...3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupfontsolution
```

`\definefontstyle [...,1...] [...]2`

```
1  NAME
2  NAME
```

`\definefontsynonym [1...] [2...] [...,3...,...]`

```
1  NAME
2  FONT
3  features    = NAME
   fallbacks  = NAME
   goodies    = NAME
   designsize = auto default
```

`\definefont [1...] [2...] [...,3...,...]`

```
1  NAME
2  FONT
3  inherits: \setupinterlinespace
```

`\definefont [1...] [2...] [3...]`

```
1  NAME
2  FONT
3  NAME
```

`\defineformula [1...] [2...] [...,3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupformula
```

`\defineformulaalternative [1...] [2...] [3...]`

```
1  NAME
2  CSNAME
3  CSNAME
```

`\defineframed [1...] [2...] [...,3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupframed
```

`\defineframedcontent [1...] [2...] [...,3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupframedcontent
```

`\defineframedtext [1...] [2...] [...,3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupframedtext
```

`\definefrozenfont [1...] [2...]`

```
1  NAME
2  FONT
```

`\defineglobalcolor [...]1 [...,...2...,...]`

1 NAME

2 inherits: \definecolor

`\defineglobalcolor [...]1 [...]2`

1 NAME

2 COLOR

`\definegraphictypesynonym [...]1 [...]2`

1 NAME

2 NAME

`\definegridsnapping [...]1 [...,...2...,...]`

1 NAME

2 local global noheight nodepth box max min none line halflines first last minheight maxheight mindepth maxdepth
top bottom strut NUMBER minheight:NUMBER maxheight:NUMBER mindepth:NUMBER maxdepth:NUMBER box:NUMBER top:NUMBER
bottom:NUMBER offset:NUMBER

`\definehbox [...]1 [...]2`

1 NAME

2 DIMENSION

`\definehead [...]1 [...]2 [...,...3...,...]`

1 NAME

2 SECTION

3 inherits: \setuphead

`\defineheadalternative [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 inherits: \setupheadalternative

`\definehelp [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 inherits: \setuphelp

`\definehigh [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 inherits: \setuphigh

`\definehighlight [...]1 [...]2 [...,...3...,...]`

1 NAME

2 NAME

3 inherits: \setuphighlight

```
\definehspace [...] [...] [...]
```

```
1  NAME
2  NAME
3  DIMENSION
```

```
\definehyphenationfeatures [...] [...,...2...,...]
```

```
1  NAME
2  characters      = TEXT
   hyphens        = yes all TEXT
   joiners        = yes all TEXT
   rightwords     = NUMBER
   hyphenmin      = NUMBER
   lefthyphenmin  = NUMBER
   righthyphenmin = NUMBER
   lefthyphenchar = NUMBER
   righthyphenchar = NUMBER
   alternative    = original tex hyphenate expanded traditional none
   rightedge      = tex
   rightchars     = word NUMBER
```

```
\defineindentedtext [...] [...] [...,...3...,...]
```

```
1  NAME
2  NAME
3  inherits: \setupindentedtext
```

```
\defineindenting [...] [...,2...,...]
```

```
1  NAME
2  [-+]small [-+]medium [-+]big none no not first next yes always never odd even normal reset toggle DIMENSION
```

```
\defineinitial [...] [...] [...,...3...,...]
```

```
1  NAME
2  NAME
3  inherits: \setupinitial
```

```
\defineinsertion [...] [...] [...,...3...,...]
```

```
1  NAME
2  NAME
3  inherits: \setupinsertion
```

```
\defineinteraction [...] [...] [...,...3...,...]
```

```
1  NAME
2  NAME
3  inherits: \setupinteraction
```

```
\defineinteractionbar [...] [...] [...,...3...,...]
```

```
1  NAME
2  NAME
3  inherits: \setupinteractionbar
```

```
\defineinteractionmenu [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupinteractionmenu
```

```
\defineinterfaceconstant {...}1 {...}2
```

```
1 NAME
```

```
2 NAME
```

```
\defineinterfaceelement {...}1 {...}2
```

```
1 NAME
```

```
2 NAME
```

```
\defineinterfacevariable {...}1 {...}2
```

```
1 NAME
```

```
2 NAME
```

```
\defineinterlinespace [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupinterlinespace
```

```
\defineintermediatecolor [...]1 [...,2...] [...,...3...,...]
```

```
1 NAME
```

```
2 COLOR NUMBER
```

```
3 a = NUMBER  
t = NUMBER
```

```
\defineitemgroup [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupitemgroup
```

```
\defineitems [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupitems
```

```
\definelabel [...]1 [...]2 [...,...3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setuplabel
```

```
\definelabelclass [...]1 [...]2
```

```
1 NAME
```

```
2 NUMBER
```

\definelayer [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayer

\definelayerpreset [¹...] [...,²...,...]

- 1 NAME
- 2 inherits: \setuplayer

\definelayerpreset [¹...] [²...]

- 1 NAME
- 2 NAME

\definelayout [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayout

\definelinenote [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinenote

\definelinenumbering [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinenumbering

\definelines [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplines

\definelist [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 LIST
- 3 inherits: \setuplist

\definelistalternative [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplistalternative

\definelistextra [¹...] [²...] [...,³...,...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplistextra

`\definelow [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuplow

`\definelowhigh [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuplowhigh

`\definelowmidhigh [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuplowmidhigh

`\defineMPinstance [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupMPinstance

`\definemakeup [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupmakeup

`\definemarginblock [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupmarginblock

`\definemargindata [1] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupmargindata

`\definemarker [...]`

- * NAME

`\definemarking [1] [2] [...,3...,...]`

- 1 NAME
- 2 MARK
- 3 inherits: \setupmarking

`\definemathaccent 1. 2.`

- 1 NAME
- 2 CHARACTER

```
\definemathalignment [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathalignment
```

```
\definemathcases [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathcases
```

```
\definemathcommand [...1] [...2] [...3] {...4}
```

```
1 NAME
```

```
2 ord op bin rel open close punct alpha inner nothing limop nolog box
```

```
3 one two
```

```
4 COMMAND CD:ONEARGUMENT CD:TWOARGUMENTS
```

```
\definemathdoubleextensible [...1] [...2] [...3] [...4]
```

```
1 both vfenced
```

```
2 NAME
```

```
3 NUMBER
```

```
4 NUMBER
```

```
\definematheconomics [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathematics
```

```
\definemathextensible [...1] [...2] [...3]
```

```
1 reverse mathematics text chemistry
```

```
2 NAME
```

```
3 NUMBER
```

```
\definemathfence [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathfence
```

```
\definemathfraction [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathfraction
```

```
\definemathframed [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathframed
```



```
\definemathmatrix [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathmatrix
```

```
\definemathornament [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathornament
```

```
\definemathoverextensible [...1] [...2] [...3]
```

```
1 top vfenced
```

```
2 NAME
```

```
3 NUMBER
```

```
\definemathovertextextensible [...1] [...2] [...3]
```

```
1 bothtext
```

```
2 NAME
```

```
3 NUMBER
```

```
\definemathradical [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathradical
```

```
\definemathstackers [...1] [...2] [...,3...,...]
```

```
1 NAME
```

```
2 NAME
```

```
3 inherits: \setupmathstackers
```

```
\definemathstyle [...1] [...,2...]
```

```
1 NAME
```

```
2
```

```
\definemathtriplet [...1] [...2] [...3]
```

```
1 NAME
```

```
2 NAME
```

```
3 TEXT
```

```
\definemathunderextensible [...1] [...2] [...3]
```

```
1 bottom vfenced
```

```
2 NAME
```

```
3 NUMBER
```

```
\definemathundertexttextensible [1...] [2...] [3]
```

- 1 bothtext
- 2 NAME
- 3 NUMBER

```
\definemathunstacked [1] [2] [3]
```

- 1 wide
- 2 NAME
- 3 NUMBER

```
\definemeasure [1] [2]
```

- 1 NAME
- 2 DIMENSION

```
\definemessageconstant {.*}
```

- * NAME

```
\definemixedcolumns [1] [2] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupmixedcolumns

```
\definemode [...,1...] [2]
```

- 1 NAME
- 2 yes no keep

```
\definemultitonecolor [1] [...,2...,...] [...,3...,...] [...,4...,...]
```

- 1 NAME
- 2 COLOR = NUMBER
- 3 inherits: \definecolor
- 4 inherits: \definespotcolor

```
\definenamecolor [1] [...,2...,...]
```

- 1 NAME
- 2 inherits: \definecolor

```
\definenamecolor [1] [2]
```

- 1 NAME
- 2 COLOR

```
\definenamespace [1] [...,2...,...]
```

- 1 NAME
- 2 name = TEXT
parent = TEXT
style = yes no
command = yes no list
setup = yes no list
set = yes no list
frame = yes no

`\definenarrower [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupnarrower

`\definernote [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupnote

`\defineornament [...]1 [...,...2...,...]2 [...,...3...,...]3`

- 1 NAME
- 2 alternative = a b
inherits: \setupcollector
- 3 style =
color = COLOR
inherits: \setupframed

`\defineornament [...]1 [...,...2...,...]2 [...,...3...,...]3`

- 1 NAME
- 2 alternative = a b
inherits: \setuplayer
- 3 inherits: \setuplayeredtext

`\defineoutputroutine [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupoutputroutine

`\defineoutputroutinecommand [...,*,...]`

- * KEY

`\defineoverlay [...,1...] [...]2 [...]3`

- 1 NAME
- 2 NAME
- 3 COMMAND

`\definepage [...]1 [...]2`

- 1 NAME
- 2 REFERENCE

`\definepagebreak [...]1 [...,2...]`

- 1 NAME
- 2

`\definepagechecker [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagechecker

```
\definepagegrid [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagegrid

```
\definepagegridarea [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagegridarea

```
\definepagegridspan [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagegridspan

```
\definepageinjection [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppageinjection

```
\definepageinjectionalternative [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppageinjectionalternative

```
\definepageshift [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 horizontal vertical
- 3 DIMENSION

```
\definepagestate [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppagestate

```
\definepairedbox [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuppairedbox

```
\definepalet [1...] [...,2...,...]
```

- 1 NAME
- 2 NAME = COLOR

```
\definepalet [1...] [2...]
```

- 1 NAME
- 2 NAME

`\definepapersize [1.] [2...2...]`

```
1  NAME
2  width    = DIMENSION
   height   = DIMENSION
   top      = COMMAND
   bottom   = COMMAND
   left     = COMMAND
   right    = COMMAND
   distance = DIMENSION
   page     = inherits: \setuppapersize
   paper    = inherits: \setuppapersize
```

`\definepapersize [1.] [2...2...] [3...3...]`

```
1  NAME
2  inherits: \setuppapersize
3  inherits: \setuppapersize
```

`\defineparagraph [1.] [2.] [3...3...]`

```
1  NAME
2  NAME
3  inherits: \setupparagraph
```

`\defineparagraphs [1.] [2.] [3...3...]`

```
1  NAME
2  NAME
3  inherits: \setupparagraphs
```

`\defineparallel [1.] [2...2...]`

```
1  NAME
2  NAME
```

`\defineparbuilder [*.]`

```
*  NAME
```

`\defineplacement [1.] [2.] [3...3...]`

```
1  NAME
2  NAME
3  inherits: \setupplacement
```

`\definepositioning [1.] [2.] [3...3...]`

```
1  NAME
2  NAME
3  inherits: \setuppositioning
```

`\defineprefixset [1.] [2...2...] [3.]`

```
1  NAME SECTIONBLOCK:NAME
2  SECTION
3  SECTION
```

`\defineprocesscolor [1...] [2] [...,3...,...]`

- 1 NAME
- 2 COLOR
- 3 inherits: \definecolor

`\defineprocessor [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupprocessor

`\defineprofile [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupprofile

`\defineprogram [1...] [2] [3]`

- 1 NAME
- 2 TEXT
- 3 TEXT

`\definepushbutton [1...] [...,2...,...]`

- 1 NAME
- 2 inherits: \setupfieldcontentframed

`\definepushsymbol [1...] [2]`

- 1 NAME
- 2 n r d

`\definereference [1...] [...,2...,...]`

- 1 NAME
- 2 REFERENCE

`\definereferenceformat [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupreferenceformat

`\defineregister [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupregister

`\definerenderingwindow [1...] [2] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuprenderingwindow

`\defineresetset [1...] [2...,...] [3...]`

- 1 NAME SECTIONBLOCK:NAME
- 2 NUMBER
- 3 NUMBER

`\definescale [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupscale

`\definescript [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupscript

`\definesection [...]`

- * NAME

`\definesectionblock [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupsectionblock

`\definesectionlevels [1...] [2...,...]`

- 1 NAME
- 2 SECTION

`\defineselector [1...] [2...,...]`

- 1 NAME
- 2 inherits: \setupselector

`\defineseparatorset [1...] [2...,...] [3...]`

- 1 NAME SECTIONBLOCK:NAME
- 2
- 3

`\defineshift [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupshift

`\definesidebar [1...] [2...] [3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupsidebar

`\definesort [...1] [...2] [...3] {...4}`

1 yes no
2 SINGULAR
3 NAME
4 CONTENT

`\definesorting [...1] [...2] [...3]`

1 SINGULAR
2 PLURAL
3 none CSNAME

`\definespotcolor [...1] [...2] [...,3...,...]`

1 NAME
2 COLOR
3 a =
 t = NUMBER
 e = TEXT
 p = NUMBER

`\definestartstop [...1] [...2] [...,3...,...]`

1 NAME
2 NAME
3 inherits: \setupstartstop

`\definestyle [...1] [...2] [...,3...,...]`

1 NAME
2 NAME
3 inherits: \setupstyle

`\definestyleinstance [...1] [...2] [...3] [...4]`

1 NAME
2 rm ss tt mm hw cg
3 tf bf it sl bi bs sc
4 COMMAND

`\definesubfield [...1] [...2] [...,3...]`

1 NAME
2 NAME
3 NAME

`\definesubformula [...1] [...2] [...,3...,...]`

1 NAME
2 NAME
3 inherits: \setupsbformula

`\definesymbol [1...] [2...] [3...]`

- 1 NAME
- 2 NAME
- 3 COMMAND

`\definesynonym [1...] [2...] [3...] {4...} {5...}`

- 1 yes no
- 2 SINGULAR
- 3 NAME
- 4 TEXT
- 5 CONTENT

`\definesynonyms [1...] [2...] [3...] [4...]`

- 1 SINGULAR
- 2 PLURAL
- 3 CSNAME
- 4 CSNAME

`\definesystemattribute [1...] [2...,...]`

- 1 NAME
- 2 local global public private

`\definesystemconstant {.*}`

- * NAME

`\definesystemvariable {.*}`

- * NAME

`\defineTABLEsetup [1...] [...,2...,...]`

- 1 NAME
- 2 inherits: \setupTABLE

`\definetabletemplate [1...] [|2...|] [3...] [4...]`

- 1 NAME
- 2 TEMPLATE
- 3 NAME
- 4 NAME

`\definetabulate [1...] [2...] [|3...|]`

- 1 NAME
- 2 NAME
- 3 TEMPLATE

`\definetabulation [1...] [2...] [...,3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuptabulation

```
\definetext [1...] [2...] [3...] [4...] [5...] [6...] [7]
```

- 1 NAME
- 2 top header text footer bottom
- 3 text margin edge
- 4 date pagenumber MARK TEXT COMMAND
- 5 date pagenumber MARK TEXT COMMAND
- 6 date pagenumber MARK TEXT COMMAND
- 7 date pagenumber MARK TEXT COMMAND

```
\definetextbackground [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextbackground

```
\definetextflow [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextflow

```
\definetooltip [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuptooltip

```
\definetransparency [1...] [2...]
```

- 1 NAME
- 2 NUMBER

```
\definetransparency [1...] [...,2...,...]
```

- 1 NAME
- 2 a =
t = NUMBER

```
\definetransparency [1...] [2...]
```

- 1 NAME
- 2 NAME

```
\definetwopasslist {...}
```

- * NAME

```
\definetype [1...] [2...] [...,3...,...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuptype

`\definetypeface [...]1 [...]2 [...]3 [...]4 [...]5 [...]6...,...]`

```
1  NAME
2  rm ss tt mm hw cg
3  serif sans mono math handwriting calligraphy
4  NAME
5  default dtp
6  rscale      = auto NUMBER
   features    = NAME
   fallbacks   = NAME
   goodies     = NAME
   designsizes = auto default
   direction   = both
```

`\definetypecriptprefix [...]1 [...]2`

```
1  NAME
2  TEXT
```

`\definetypecriptsynonym [...]1 [...]2`

```
1  NAME
2  TEXT
```

`\definetypesetting [...]1 [...]2 [...]3...,...]`

```
1  NAME
2  TEXT
3  inherits: \setuexternalfigure
```

`\definetying [...]1 [...]2 [...]3...,...]`

```
1  NAME
2  NAME
3  inherits: \setuptying
```

`\defineunit [...]1 [...]2 [...]3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupunit
```

`\defineviewerlayer [...]1 [...]2 [...]3...,...]`

```
1  NAME
2  NAME
3  inherits: \setupviewerlayer
```

`\definevspace [...]1 [...]2 [...]3`

```
1  NAME
2  NAME
3  DIMENSION
```

`\definevspacing [...]1 [...]2`

```
1  NAME
2  inherits: \vspacing
```

`\definevspacingamount [...]1 [...]2 [...]3`

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION

`\definetable [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupxtable

`\delimited [...]1 {...}2`

- 1 NAME
- 2 CONTENT

`\delimitedtext [...]1 {...}2`

- 1 NAME
- 2 CONTENT

`\delimitedtext {...}*`

- * CONTENT

`\depthofstring {...}*`

- * TEXT

`\depthonlybox {...}*`

- * CONTENT

`\depthspanningtext {...}1 {...}2 {...}3`

- 1 TEXT
- 2 DIMENSION
- 3 FONT

`\description [...,1...] {...}2 ...3 \par`

- 1 REFERENCE
- 2 TEXT
- 3 CONTENT

`\determineheadnumber [...]*`

- * SECTION

`\determinelistcharacteristics [...,1...] [...,...2...,...]`

- 1 LIST
- 2 inherits: \setuplist

`\determinenoflines {...}*`

- * CONTENT

`\determineregistercharacteristics [...]1 [...,...2...,...]`

1 NAME
2 language =
method =
numberorder = numbers
compress = yes no all
criterium = local text current previous all SECTION

`\devanagarinumerals {...}`

* NUMBER

`\dfrac {...}1 {...}2`

1 CONTENT
2 CONTENT

`\digits {...}`

* NUMBER

`\digits ...`

* NUMBER

`\dimensiontocount {...}1 \...2`

1 DIMENSION
2 CSNAME

`\directcolor [...]`

* COLOR

`\directcolored [...]`

* COLOR

`\directcolored [...,...*...,...]`

* inherits: \definecolor

`\directconvertedcounter {...}1 {...}2`

1 NAME
2 first previous next last number

`\directdummyparameter {...}`

* KEY

`\directgetboxllx ...`

* CSNAME NUMBER

`\directgetboxlly ...`

* CSNAME NUMBER

<code>\directhighlight {...} {...}</code> 1 NAME 2 TEXT
<code>\directlocalframed [...] {...}</code> 1 NAME 2 CONTENT
<code>\directluacode {...}</code> * COMMAND
<code>\directselect {...} {...} {...} {...} {...} {...}</code> 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\directsetbar {...}</code> * NAME
<code>\directsetup {...}</code> * NAME
<code>\directsymbol {...} {...}</code> 1 NAME 2 NAME
<code>\directvspacing {...,*...}</code> * inherits: \vspacing
<code>\dis {...}</code> * CONTENT
<code>\disabledirectives [...,*...]</code> * NAME
<code>\disableexperiments [...,*...]</code> * NAME
<code>\disablemode [...,*...]</code> * NAME
<code>\disableoutputstream</code>
<code>\disableparpositions</code>

<code>\disableregime</code>
<code>\disabletrackers [...]*...]</code> * NAME
<code>\displaymath {...}</code> * CONTENT
<code>\displaymathematics {...}</code> * CONTENT
<code>\displaymessage {...}</code> * TEXT
<code>\distributedhsize {...}^{1.} {...}^{2.} {...}^{3.}</code> 1 DIMENSION 2 DIMENSION 3 NUMBER
<code>\dividedsize {...}^{1.} {...}^{2.} {...}^{3.}</code> 1 DIMENSION 2 DIMENSION 3 NUMBER
<code>\doadaptleftskip {...}</code> *
<code>\doadaptrightskip {...}</code> *
<code>\doaddfeature {...}</code> * NAME
<code>\doassign [...] [...²..]</code> 1 TEXT 2 KEY = VALUE
<code>\doassignempty [...] [...²..]</code> 1 TEXT 2 KEY = VALUE
<code>\doboundtext {...}^{1.} {...}^{2.} {...}^{3.}</code> 1 TEXT 2 DIMENSION 3 COMMAND
<code>\docheckassignment {...}</code> * TEXT

\docheckedpagestate {...} {...} {...} {...} {...} {...} {...}

- 1 REFERENCE
- 2 COMMAND
- 3 COMMAND
- 4 COMMAND
- 5 COMMAND
- 6 COMMAND
- 7 COMMAND

\docheckedpair {...,*,...}

- * TEXT

\documentvariable {...}

- * KEY

\dodoubleargument \¹... [²...] [³...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleargumentwithset \¹... [...,²...] [³...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleempty \¹... [²...] [³...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleemptywithset \¹... [...,²...] [³...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoublegroupempty \¹... {...²} {...³}

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\doeassign [...¹] [...²...]

- 1 TEXT
- 2 KEY = VALUE

\doexpandedrecurse {...¹} {...²}

- 1 NUMBER
- 2 COMMAND

`\dogetattribute {...}`

* NAME

`\dogetattributeid {...}`

* NAME

`\dogetcommacommandelement 1... \from 2... \to 3...`

1 NUMBER

2 TEXT

3 CSNAME

`\dogobbledoubleempty [1...] [2...]`

1 TEXT

2 TEXT

`\dogobblesingleempty [...]`

* TEXT

`\doif {1...} {2...} {3...}`

1 CONTENT

2 CONTENT

3 TRUE

`\doifallcommon {...}`

* TRUE

`\doifallcommonelse {1...} {2...}`

1 TRUE

2 FALSE

`\doifalldefinedelse {...,1...} {2...} {3...}`

1 NAME

2 TRUE

3 FALSE

`\doifallmodes {...,1...} {2...} {3...}`

1 NAME

2 TRUE

3 FALSE

`\doifallmodeselse {...,1...} {2...} {3...}`

1 NAME

2 TRUE

3 FALSE

`\doifassignmentelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifblackelse {...} {...} {...}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifbothsides {...} {...} {...}`

- 1 COMMAND
- 2 COMMAND
- 3 COMMAND

`\doifbothsidesoverruled {...} {...} {...}`

- 1 COMMAND
- 2 COMMAND
- 3 COMMAND

`\doifboxelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifbufferelse {...} {...} {...}`

- 1 BUFFER
- 2 TRUE
- 3 FALSE

`\doifcolor {...} {...}`

- 1 COLOR
- 2 TRUE

`\doifcolorelse {...} {...} {...}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifcommandhandler \... {...} {...}`

- 1 CSNAME
- 2 NAME
- 3 TRUE

```
\doifcommandhandlerelse \1... {2...} {3...} {4...}
```

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

```
\doifcommon {*...}
```

- * TRUE

```
\doifcommonelse {1...} {2...}
```

- 1 TRUE
- 2 FALSE

```
\doifcontent {1...} {2...} {3...} \4... {5...}
```

- 1 COMMAND
- 2 COMMAND
- 3 COMMAND
- 4 CSNAME
- 5 CONTENT

```
\doifconversiondefinedelse {1...} {2...} {3...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifconversionnumberelse {1...} {2...} {3...} {4...}
```

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

```
\doifcounter {1...} {2...}
```

- 1 NAME
- 2 TRUE

```
\doifcounterelse {1...} {2...} {3...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

```
\doifcurrentfonthasfeatureelse {1...} {2...} {3...}
```

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefined {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounter {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdimensionelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdimenstringelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdocumentargument {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdocumentargumentelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdocumentfilename {...} {...}`

- 1 NUMBER
- 2 TRUE

`\doifdocumentfilenameelse {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifdrawingblackelse {...} {...}`

1 TRUE
2 FALSE

`\doifelse {...} {...} {...} {...}`

1 CONTENT
2 CONTENT
3 TRUE
4 FALSE

`\doifelseallcommon {...} {...}`

1 TRUE
2 FALSE

`\doifelsealldefined {...,1...} {...2} {...3}`

1 NAME
2 TRUE
3 FALSE

`\doifelseallmodes {...,1...} {...2} {...3}`

1 NAME
2 TRUE
3 FALSE

`\doifelseassignment {...} {...2} {...3}`

1 TEXT
2 TRUE
3 FALSE

`\doifelseblack {...} {...2} {...3}`

1 COLOR
2 TRUE
3 FALSE

`\doifelsebox {...} {...2} {...3} {...4}`

1 NAME
2 NAME
3 TRUE
4 FALSE

`\doifelsebuffer {...} {...2} {...3}`

1 BUFFER
2 TRUE
3 FALSE

\doifelsecolor {...} {...} {...}

- 1 COLOR
- 2 TRUE
- 3 FALSE

\doifelsecommandhandler ^{1} {...} {...} {...}

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelsecommon {...} {...}

- 1 TRUE
- 2 FALSE

\doifelseconversiondefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseconversionnumber {...} {...} {...} {...}

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

\doifelsecounter {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentsortingtongused {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymshown {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymused {...} {...}

- 1 TRUE
- 2 FALSE

`\doifelsedefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedefinedcounter {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedimension {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsedimenstring {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsedocumentargument {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsedocumentfilename {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelsedrawingblack {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelseempty {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifelseemptyvalue {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseemptyvariable {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doifelseenv {...} {...} {...}`

- 1 KEY
- 2 TRUE
- 3 FALSE

`\doifelsefastoptionalcheck {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsefastoptionalcheckcs \^1 \^2`

- 1 CSNAME
- 2 CSNAME

`\doifelsefieldbody {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefieldcategory {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefigure {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsefile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsefiledefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefileexists {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsefirstchar {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelseflagged {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsefontchar {...} {...} {...} {...}`

- 1 FONT
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsefontpresent {...} {...} {...}`

- 1 FONT
- 2 TRUE
- 3 FALSE

`\doifelsefontsynonym {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsehasspace {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsehelp {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelseincsname {...} {...} {...} {...}`

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifelseinelement {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseinputfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseinsertion {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseinset {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifelseinstring {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelseinsymbolset {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseintoks {...} {...} {...} {...}`

- 1 COMMAND
- 2 COMMAND
- 3 TRUE
- 4 FALSE

`\doifelseintwopassdata {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseitalic {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelselanguage {...} {...} {...}`

- 1 LANGUAGE
- 2 TRUE
- 3 FALSE

`\doifelselayerdata {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayoutdefined {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayoutsomeline {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayouttextline {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseleapyear {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelselist {...} {...} {...}`

- 1 LIST
- 2 TRUE
- 3 FALSE

`\doifelselocation {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelselocfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseMPgraphic {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsemainfloatbody {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsemarking {...} {...} {...}`

- 1 MARK
- 2 TRUE
- 3 FALSE

`\doifelsemeaning \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifelsemessage {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsemode {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenextbgroup {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextbgroupcs \1... \2...`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextchar {...1} {...2} {...3}`

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

`\doifelsenextoptional {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextoptionalcs \1... \2...`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextparenthesis {\1...} {\2...}`

- 1 TRUE
- 2 FALSE

`\doifelsenonzeropositive {\1...} {\2...} {\3...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelsenoteonsamepage {\1...} {\2...} {\3...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenothing {\1...} {\2...} {\3...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsenumber {\1...} {\2...} {\3...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelseobjectfound {\1...} {\2...} {\3...} {\4...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseobjectreferencefound {\1...} {\2...} {\3...} {\4...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseoddpage {\1...} {\2...}`

- 1 COMMAND
- 2 COMMAND

`\doifelseoddpagefloat {\1...} {\2...}`

- 1 TRUE
- 2 FALSE

\doifelseoldercontext {...} {...} {...}

- 1 NUMBER
- 2 TRUE
- 3 FALSE

\doifelseolderversion {...} {...} {...} {...}

- 1 NUMBER
- 2 NUMBER
- 3 TRUE
- 4 FALSE

\doifelseoverlapping {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseoverlay {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseparallel {...} {...,²...} {...} {...}

- 1 NAME
- 2 NAME all
- 3 TRUE
- 4 FALSE

\doifelseparentfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsepath {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsepathexists {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsepatterns {...} {...} {...}

- 1 LANGUAGE
- 2 TRUE
- 3 FALSE

`\doifelseposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositiononpage {...} {...} {...} {...}`

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsepositionsonsamepage {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionsontthispage {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionsused {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelserreferencefound {...} {...} {...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifelserightpagefloat {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelserighttoleftinbox ...1 {...2} {...3}`

- 1 CSNAME NUMBER
- 2 TRUE
- 3 FALSE

\doifelsesamelinereference {...} {...} {...}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

\doifelsesamestring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsesetups {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomebackground {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomespace {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesomething {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesometoks \.^{1..} {...} {...}

- 1 CSNAME
- 2 TRUE
- 3 FALSE

\doifelsestringinstring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsestructurelisthasnumber {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsestructurelisthaspage {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsesymboldefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesymbolset {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetext {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsetextflow {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetextflowcollector {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetypingfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelseundefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseurldefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsevalue {...} {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifelsevaluenothing {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsevariable {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doifempty {...} {...}`

- 1 CONTENT
- 2 TRUE

`\doifemptyelse {...} {...} {...}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifemptytoks \^1... {...}`

- 1 CSNAME
- 2 TRUE

`\doifemptyvalue {...} {...}`

- 1 NAME
- 2 TRUE

`\doifemptyvalueelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifemptyvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifemptyvariableelse {...} {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

`\doifenv {...} {...}`

- 1 KEY
- 2 TRUE

`\doifenvelse {...} {...} {...}`

- 1 KEY
- 2 TRUE
- 3 FALSE

`\doiffastoptionalcheckcseelse \1 \2`

- 1 CSNAME
- 2 CSNAME

`\doiffastoptionalcheckelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiffielddbbodyelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffielddcategoryelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffigureelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffile {...} {...}`

- 1 FILE
- 2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffileexistselse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifflaggedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffontcharelse {...} {...} {...} {...}`

- 1 FONT
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doiffontpresentelse {...} {...} {...}`

- 1 FONT
- 2 TRUE
- 3 FALSE

`\doiffontsynonymelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifhasspaceelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifhelpelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifincsnameelse {1..} {2..} {3..} {4..}`

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifinelementelse {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifinputfileelse {1..} {2..} {3..}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifinsetionelse {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifinset {1..} {2..}`

- 1 CONTENT
- 2 TRUE

`\doifinsetelse {1..} {2..} {3..}`

- 1 CONTENT
- 2 TRUE
- 3 FALSE

`\doifinstring {1..} {2..} {3..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifinstringelse {1..} {2..} {3..} {4..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifinsymbolset {1..} {2..} {3..} {4..}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifinsymbolsetelse {...} {...} {...} {...}`

1 NAME
2 NAME
3 TRUE
4 FALSE

`\doifintokselse {...} {...} {...} {...}`

1 COMMAND
2 COMMAND
3 TRUE
4 FALSE

`\doifintwopassdataelse {...} {...} {...} {...}`

1 NAME
2 NAME
3 TRUE
4 FALSE

`\doifitalicelse {...} {...}`

1 TRUE
2 FALSE

`\doiflanguageelse {...} {...} {...}`

1 LANGUAGE
2 TRUE
3 FALSE

`\doiflayerdataelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayoutdefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayoutsomelineelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayouttextlineelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifleapyearelse {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doiflistelse {...} {...} {...}`

- 1 LIST
- 2 TRUE
- 3 FALSE

`\doiflocationelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiflocfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifMPgraphicelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifmainfloatbodyelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifmarkingelse {...} {...} {...}`

- 1 MARK
- 2 TRUE
- 3 FALSE

`\doifmeaningelse \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifmessageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

\doifmode {...,¹...} {...²}

- 1 NAME
- 2 TRUE

\doifmodeelse {...,¹...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifnextbgroupcselse \¹... \²...

- 1 CSNAME
- 2 CSNAME

\doifnextbgroupelse {...¹} {...²}

- 1 TRUE
- 2 FALSE

\doifnextcharelse {...¹} {...²} {...³}

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

\doifnextoptionalcselse \¹... \²...

- 1 CSNAME
- 2 CSNAME

\doifnextoptionalelse {...¹} {...²}

- 1 TRUE
- 2 FALSE

\doifnextparenthesiselse {...¹} {...²}

- 1 TRUE
- 2 FALSE

\doifnonzeropositiveelse {...¹} {...²} {...³}

- 1 NUMBER
- 2 TRUE
- 3 FALSE

\doifnot {...¹} {...²} {...³}

- 1 CONTENT
- 2 CONTENT
- 3 TRUE

\doifnotallcommon {...^{*}}

- * TRUE

`\doifnotallmodes {...1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifnotcommandhandler \...1 {...2} {...3}`

- 1 CSNAME
- 2 NAME
- 3 TRUE

`\doifnotcommon {...*}`

- * TRUE

`\doifnotcounter {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotdocumentargument {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotdocumentfilename {...1} {...2}`

- 1 NUMBER
- 2 TRUE

`\doifnotempty {...1} {...2}`

- 1 CONTENT
- 2 TRUE

`\doifnotemptyvalue {...1} {...2}`

- 1 NAME
- 2 TRUE

`\doifnotemptyvariable {...1} {...2} {...3}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifnotenv {...1} {...2}`

- 1 KEY
- 2 TRUE

`\doifnoteonsamepageelse {...1} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifnotescollected {...} {...}

- 1 NAME
- 2 TRUE

\doifnotfile {...} {...}

- 1 FILE
- 2 TRUE

\doifnotflagged {...} {...}

- 1 NAME
- 2 TRUE

\doifnothing {...} {...}

- 1 TEXT
- 2 TRUE

\doifnothingelse {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifnotinset {...} {...}

- 1 CONTENT
- 2 TRUE

\doifnotinsidesplitfloat {...}

- * TRUE

\doifnotinstring {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE

\doifnotmode {...,¹...} {...²}

- 1 NAME
- 2 TRUE

\doifnotnumber {...} {...}

- 1 TEXT
- 2 TRUE

\doifnotsamestring {...} {...²} {...³}

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifnotsetups {...} {...}`

- 1 NAME
- 2 TRUE

`\doifnotvalue {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifnotvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifnumber {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifnumberelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifobjectfoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifobjectreferencefoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoddpagelse {...} {...}`

- 1 COMMAND
- 2 COMMAND

`\doifoddpagefloatelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifoldercontextelse {...} {...} {...}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifolderversionelse {...} {...} {...} {...}`

- 1 NUMBER
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifoverlappingelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoverlayelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifparallelelse {...} {...,2...} {...} {...}`

- 1 NAME
- 2 NAME all
- 3 TRUE
- 4 FALSE

`\doifparentfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifpathelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifpathexistselse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifpatternseelse {...} {...} {...}`

- 1 LANGUAGE
- 2 TRUE
- 3 FALSE

`\doifposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionactionelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositiononpageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NUMBER
- 3 TRUE
- 4 FALSE

`\doifpositionsonsamepageelse {...,1...} {...2...} {...3...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionsonthispageelse {...,1...} {...2...} {...3...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionsusedelse {...1...} {...2...}`

- 1 TRUE
- 2 FALSE

`\doifreferencefoundelse {...1...} {...2...} {...3...}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifrightpagefloatelse {...1...} {...2...}`

- 1 TRUE
- 2 FALSE

`\doifrighttoleftinboxedelse 1. {2..} {3..}`

- 1 CSNAME NUMBER
- 2 TRUE
- 3 FALSE

`\doifsamelinereferenceelse {1..} {2..} {3..}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifsamestring {1..} {2..} {3..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifsamestringelse {1..} {2..} {3..} {4..}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifsetups {1..} {2..}`

- 1 NAME
- 2 TRUE

`\doifsetupself {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackground {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackgroundelse {1..} {2..} {3..}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomespaceelse {1..} {2..} {3..}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsomething {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifsomethingelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsometoks \... {...}`

- 1 CSNAME
- 2 TRUE

`\doifsometokselse \... {...} {...}`

- 1 CSNAME
- 2 TRUE
- 3 FALSE

`\doifstringinstringelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifstructurelisthasnumberelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifstructurelisthaspageelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifsymboldefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsymbolsetelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiftext {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doiftextelse {1.} {2.} {3.}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doiftextflowcollectorelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiftextflowelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiftypingfileelse {1.} {2.} {3.}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifundefined {1.} {2.}`

- 1 NAME
- 2 TRUE

`\doifundefinedcounter {1.} {2.}`

- 1 NAME
- 2 TRUE

`\doifundefinedelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifurldefinedelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifvalue {1.} {2.} {3.}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifvalueelse {...} {...} {...} {...}`

1 NAME
2 TEXT
3 TRUE
4 FALSE

`\doifvaluenothing {...} {...}`

1 NAME
2 TRUE

`\doifvaluenothingelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifvaluesomething {...} {...}`

1 NAME
2 TRUE

`\doifvariable {...} {...} {...}`

1 NAME
2 KEY
3 TRUE

`\doifvariableelse {...} {...} {...} {...}`

1 NAME
2 KEY
3 TRUE
4 FALSE

`\doindentation`

`\dollar`

`\doloop {...}`

* COMMAND

`\doloopoverlist {...,1...} {...2}`

1 TEXT
2 COMMAND

`\donothing`

`\dontconvertfont`

`\dontleavehmode`

`\dontpermitspacesbetweenegroups`

`\dopositionaction {...}`

* NAME

`\doprocesslocalsetups {...,*...}`

* NAME

`\doquadrupleargument \1... [2...] [3...] [4...] [5...]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\doquadrupleempty \1... [2...] [3...] [4...] [5...]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\doquadruplegroupempty \1... {2...} {3...} {4...} {5...}`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\doquintupleargument \1... [2...] [3...] [4...] [5...] [6...]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

6 TEXT

`\doquintupleempty \1... [2...] [3...] [4...] [5...] [6...]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

6 TEXT

`\doquintuplegrouplempty \1... {\2...} {\3...} {\4...} {\5...} {\6...}`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT

`\dorechecknextindentation`

`\dorecurse {\1...} {\2...}`

1 NUMBER
2 COMMAND

`\dorepeatwithcommand [\1...] \2...`

1 TEXT NUMBER*TEXT
2 CSNAME

`\doreplacefeature {*...}`

* NAME

`\doresetandafffeature {*...}`

* NAME

`\doresetattribute {*...}`

* NAME

`\dorotatebox {\1...} \2... {\3...}`

1 NUMBER
2 CSNAME
3 CONTENT

`\dosetattribute {\1...} {\2...}`

1 NAME
2 NUMBER

`\dosetleftskipadaption {*...}`

*

`\dosetrighskipadaption {*...}`

*

`\dosetupcheckedinterlinespace {...,*=...,...}`

* inherits: \setupinterlinespace

`\dosetupcheckedinterlinespace {...,*...}`

* on off reset auto small medium big NUMBER DIMENSION

```
\dosetupcheckedinterlinespace {...}
```

```
* NAME
```

```
\doseventupleargument \1... [2...] [3...] [4...] [5...] [6...] [7...] [8...]
```

```
1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT  
8 TEXT
```

```
\doseventupleempty \1... [2...] [3...] [4...] [5...] [6...] [7...] [8...]
```

```
1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT  
8 TEXT
```

```
\dosingleargument \1... [2...]
```

```
1 CSNAME  
2 TEXT
```

```
\dosingleempty \1... [2...]
```

```
1 CSNAME  
2 TEXT
```

```
\dosinglegroupempty \1... {2...}
```

```
1 CSNAME  
2 TEXT
```

```
\dosixtupleargument \1... [2...] [3...] [4...] [5...] [6...] [7...]
```

```
1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT
```

`\dosixtupleempty \1... [2...] [3] [4] [5] [6] [7]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

`\dostarttagged {1...} {2...} ... \dostoptagged`

- 1 NAME
- 2 NAME

`\dostepwiserecurse {1...} {2...} {3...} {4...}`

- 1 NUMBER
- 2 NUMBER
- 3 [-+]NUMBER
- 4 COMMAND

`\dosubtractfeature {*...}`

- * NAME

`\dot {*...}`

- * CHARACTER

`\dotfskip {*...}`

- * DIMENSION

`\dotoks *...`

- * CSNAME

`\dotripleargument \1... [2...] [3] [4]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleargumentwithset \1... [2...,...] [3] [4]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleempty \1... [2...] [3] [4]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleemptywithset \1... [2...,...] [3] [4]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotriplegroupempty \1... {2...} {3...} {4...}`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\doublebar {*...}`

- * TEXT

`\doublebond`

`\doublebrace {*...}`

- * TEXT

`\doublebracket {*...}`

- * TEXT

`\doubleparent {*...}`

- * TEXT

`\dowith {1...,...} {2...}`

- 1 COMMAND
- 2 COMMAND

`\dowithnextbox {1...} \2... {3...}`

- 1 COMMAND
- 2 CSNAME
- 3 CONTENT

`\dowithnextboxcontent {1...} {2...} \3... {4...}`

- 1 COMMAND
- 2 COMMAND
- 3 CSNAME
- 4 CONTENT

`\dowithnextboxcontentcs \1... \2... \3... {4...}`

- 1 CSNAME
- 2 CSNAME
- 3 CSNAME
- 4 CONTENT

`\dowithnextboxcs \1... \2... {3...}`

- 1 CSNAME
- 2 CSNAME
- 3 CONTENT

`\dowithpargument *...`

- * CSNAME

`\dowithrange {...,1...} \2...`

- 1 NUMBER NUMBER:NUMBER
- 2 CSNAME

`\dowithwargument *...`

- * CSNAME

`\dpofstring {*...}`

- * TEXT

`\dummydigit`

`\dummyparameter {*...}`

- * KEY

`\ETEX`

`\EveryLine {*...}`

- * COMMAND

`\EveryPar {*...}`

- * COMMAND

`\edefconvertedargument \1... {2...}`

- 1 CSNAME
- 2 TEXT

`\efcmaxheight {*...}`

- * NAME

`\efcmaxwidth {*...}`

- * NAME

<code>\efcminheight {...}</code> * NAME
<code>\efcminwidth {...}</code> * NAME
<code>\efcparameter {...} {...}</code> 1 NAME 2 KEY
<code>\effect [...] {...}</code> 1 NAME 2 CONTENT
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\leftarrowfill {...} {...}</code> 1 TEXT 2 TEXT
<code>\leftharpoondownfill {...} {...}</code> 1 TEXT 2 TEXT
<code>\leftharpoonupfill {...} {...}</code> 1 TEXT 2 TEXT
<code>\leftrightarrowfill {...} {...}</code> 1 TEXT 2 TEXT
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...]</code> * NUMBER
<code>\emspace</code>
<code>\enabledirectives [...,*,...]</code> * NAME
<code>\enableexperiments [...,*,...]</code> * NAME

<p><code>\enablemode [...,*,...]</code></p> <p>* NAME</p>
<p><code>\enableoutputstream [...]</code></p> <p>* NAME</p>
<p><code>\enableparpositions</code></p>
<p><code>\enableregime [...]</code></p> <p>* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows</p>
<p><code>\enabletrackers [...,*,...]</code></p> <p>* NAME</p>
<p><code>\endhbox</code></p>
<p><code>\endnote [...,¹,...] {²...}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\endnote [...,.*=...,...]</code></p> <p>* title = TEXT</p> <p>bookmark = TEXT</p> <p>list = TEXT</p> <p>reference = REFERENCE</p>
<p><code>\endvbox</code></p>
<p><code>\enskip</code></p>
<p><code>\enspace</code></p>
<p><code>\enumeration [...,¹,...] {²...} ³. \par</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p><code>\env {...}</code></p> <p>* KEY</p>
<p><code>\environment [...]</code></p> <p>* FILE</p>
<p><code>\environment ...</code></p> <p>* FILE</p>

`\envvar {...} {...}`

- 1 KEY
- 2 COMMAND

`\eoverbarfill {...} {...}`

- 1 TEXT
- 2 TEXT

`\eoverbracefill {...} {...}`

- 1 TEXT
- 2 TEXT

`\eoverbracketfill {...} {...}`

- 1 TEXT
- 2 TEXT

`\eoverparentfill {...} {...}`

- 1 TEXT
- 2 TEXT

`\epos {...}`

- * NAME

`\equaldigits {...}`

- * TEXT

`\erightarrowfill {...} {...}`

- 1 TEXT
- 2 TEXT

`\erightharpoondownfill {...} {...}`

- 1 TEXT
- 2 TEXT

`\erightharpoonupfill {...} {...}`

- 1 TEXT
- 2 TEXT

`\eTeX`

`\ethiopic`

`\etwoheadrightarrowfill {...} {...}`

- 1 TEXT
- 2 TEXT

`\eunderbarfill {...} {...}`

1 TEXT

2 TEXT

`\eunderbracefill {...} {...}`

1 TEXT

2 TEXT

`\eunderbracketfill {...} {...}`

1 TEXT

2 TEXT

`\eunderparentfill {...} {...}`

1 TEXT

2 TEXT

`\executeifdefined {...} {...}`

1 NAME

2 COMMAND

`\exitloop`

`\exitloopnow`

`\expandcheckedcsname \... {...} {...}`

1 CSNAME

2 KEY

3 TEXT

`\expanded {...}`

* CONTENT

`\expandfontsynonym \... {...}`

1 CSNAME

2 NAME

`\externalfigure [...] [...] [..., ...3..., ...]`

1 FILE

2 NAME

3 inherits: \setupexternalfigure

`\externalfigurecollectionmaxheight {...}`

* NAME

`\externalfigurecollectionmaxwidth {...}`

* NAME

<code>\externalfigurecollectionminheight {...}</code> * NAME
<code>\externalfigurecollectionminwidth {...}</code> * NAME
<code>\externalfigurecollectionparameter {...} {...}</code> 1 NAME 2 KEY
<code>\fakebox ...</code> * CSNAME NUMBER
<code>\fastdecrement \...</code> * CSNAME
<code>\fastincrement \...</code> * CSNAME
<code>\fastlocalframed [...]¹ [...,²...,...]³ {...}</code> 1 NAME 2 inherits: \setupframed 3 CONTENT
<code>\fastscale {...}¹ {...}²</code> 1 NUMBER 2 CONTENT
<code>\fastsetup {...}</code> * NAME
<code>\fastsetupwithargument {...}¹ {...}²</code> 1 NAME 2 CONTENT
<code>\fastsetupwithargumentswapped {...}¹ {...}²</code> 1 CONTENT 2 NAME
<code>\fastswitchtobodyfont {...}</code> * x xx small big script scriptscript
<code>\fastsxsy {...}¹ {...}² {...}³</code> 1 NUMBER 2 NUMBER 3 CONTENT

<pre> \feature [...] [...] 1 + - = ! > < more less new reset default old local 2 NAME </pre>
<pre> \feature {...} {...} 1 + - = ! > < more less new reset default old local 2 NAME </pre>
<pre> \fence </pre>
<pre> \fenced [...] {...} 1 NAME 2 CONTENT </pre>
<pre> \fence {...} * CONTENT </pre>
<pre> \fetchallmarkings [...] [...] 1 MARK 2 page NAME </pre>
<pre> \fetchallmarks [...] * MARK </pre>
<pre> \fetchmark [...] [...] 1 MARK 2 </pre>
<pre> \fetchmarking [...] [...] [...] 1 MARK 2 page NAME 3 </pre>
<pre> \fetchonemark [...] [...] 1 MARK 2 </pre>
<pre> \fetchonemarking [...] [...] [...] 1 MARK 2 page NAME 3 </pre>
<pre> \fetchruntinecommand \... {...} 1 CSNAME 2 FILE </pre>

<code>\fetchtwomarkings [...]¹ [...]²</code> 1 MARK 2 page NAME
<code>\fetchtwomarks [...]</code> * MARK
<code>\field [...]¹ [...]²</code> 1 NAME 2 TEXT
<code>\fieldbody [...]¹ [...]²...]</code> 1 NAME 2 inherits: \setupfieldbody
<code>\fieldstack [...]¹ [...]²...] [...]³...]</code> 1 NAME 2 NAME 3 inherits: \setupfieldcategory
<code>\fifthoffivearguments {...}¹ {...}² {...}³ {...}⁴ {...}⁵</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\fifthofsixarguments {...}¹ {...}² {...}³ {...}⁴ {...}⁵ {...}⁶</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\figurefilename</code>
<code>\figurefilepath</code>
<code>\figurefiletype</code>
<code>\figurefullname</code>
<code>\figureheight</code>
<code>\figurenaturalheight</code>
<code>\figurenaturalwidth</code>

<code>\figuresymbol [...]¹ [...,...²...,...]</code> 1 FILE NAME 2 inherits: \externalfigure
<code>\figurewidth</code>
<code>\filename {...}</code> * FILE
<code>\filledhboxb ...¹ {...²}</code> 1 TEXT 2 CONTENT
<code>\filledhboxc ...¹ {...²}</code> 1 TEXT 2 CONTENT
<code>\filledhboxg ...¹ {...²}</code> 1 TEXT 2 CONTENT
<code>\filledhboxk ...¹ {...²}</code> 1 TEXT 2 CONTENT
<code>\filledhboxm ...¹ {...²}</code> 1 TEXT 2 CONTENT
<code>\filledhboxr ...¹ {...²}</code> 1 TEXT 2 CONTENT
<code>\filledhboxy ...¹ {...²}</code> 1 TEXT 2 CONTENT
<code>\filler [...]</code> * sym symbol rule width space NAME
<code>\fillinline [...,...[*]...,...]</code> * inherits: \setupfillinlines
<code>\fillinrules [...,...¹...,...] {...².} {...³.}</code> 1 inherits: \setupfillinrules 2 TEXT 3 TEXT

\fillintext [...¹...] {...} {...}

1 inherits: \setupfillinrules
2 TEXT
3 TEXT

\filterfromnext {...} {...}

1 NUMBER
2 NUMBER

\filterfromvalue {...} {...} {...}

1 NAME
2 NUMBER
3 NUMBER

\filterpages [...¹] [...²...] [...³...] [...⁴...]

1 FILE
2 even odd NUMBER NUMBER:NUMBER
3 width = DIMENSION
category = CD:STRING
n = NUMBER

\filterreference {...}

*

\findtwopassdata {...} {...}

1 NAME
2 NAME

\finishregisterentry [...¹] [...²...] [...³...]

1 NAME
2 label = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
alternative = TEXT
3 KEY = VALUE

\firstcharacter

\firstcounter [...¹] [...²]

1 NAME
2 NUMBER

\firstcountervalue [...^{*}]

* NAME

\firstoffivearguments {...} {...} {...} {...} {...}

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT

\firstoffourarguments {...} {...} {...} {...}

1 TEXT
2 TEXT
3 TEXT
4 TEXT

\firstofoneargument {...}

* TEXT

\firstofoneunexpanded {...}

* TEXT

\firstofsixarguments {...} {...} {...} {...} {...} {...}

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT

\firstofthreearguments {...} {...} {...}

1 TEXT
2 TEXT
3 TEXT

\firstofthreeunexpanded {...} {...} {...}

1 TEXT
2 TEXT
3 TEXT

\firstoftwoarguments {...} {...}

1 TEXT
2 TEXT

\firstoftwounexpanded {...} {...}

1 TEXT
2 TEXT

\firstrealpage

<code>\firstrealpagenumber</code>
<code>\firstsubcountervalue</code> [¹ ...] [² ...] <ul style="list-style-type: none"> 1 NAME 2 NUMBER
<code>\firstsubpage</code>
<code>\firstsubpagenumber</code>
<code>\firstuserpage</code>
<code>\firstuserpagenumber</code>
<code>\fitfield</code> [¹ ...] [..., ² ...,...] <ul style="list-style-type: none"> 1 NAME 2 inherits: \setupfieldbody
<code>\fitfieldframed</code> [..., ¹ ...,...] { ² ...} <ul style="list-style-type: none"> 1 inherits: \setupframed 2 CONTENT
<code>\fittopbaselinegrid</code> { [*] ...} <ul style="list-style-type: none"> * CONTENT
<code>\fixedspace</code>
<code>\fixedspaces</code>
<code>\flag</code> { [*] ...} <ul style="list-style-type: none"> * NAME
<code>\floatuserdataparameter</code> { [*] ...} <ul style="list-style-type: none"> * KEY
<code>\flushcollector</code> [...] <ul style="list-style-type: none"> * NAME
<code>\flushedrightlastline</code>
<code>\flushlayer</code> [...] <ul style="list-style-type: none"> * NAME
<code>\flushlocalfloats</code>
<code>\flushnextbox</code>
<code>\flushnotes</code>

\flushoutputstream [...] * NAME
\flushshapebox
\flushtextflow {...} * NAME
\flushtokens [...] * NAME
\flushtoks *... * CSNAME
\fontalternative
\fontbody
\fontchar {...} * NAME
\fontcharbyindex {...} * NUMBER
\fontclass
\fontclassname {...} {...} 1 NAME 2 FONT
\fontface
\fontfeaturelist [... ¹] [... ²] 1 NAME 2 TEXT
\fontsize
\fontstyle
\footnotetext [..., ¹ ...] {... ² } 1 REFERENCE 2 TEXT
\footnotetext [..., [*] ...,...] * title = TEXT * bookmark = TEXT * list = TEXT * reference = REFERENCE

`\footnote [...1,...] {...}`

1 REFERENCE

2 TEXT

`\footnote [...*...,...]`

* title = TEXT
bookmark = TEXT
list = TEXT
reference = REFERENCE

`\forcecharacterstripping`

`\forcelocalfloats`

`\forgeteverypar`

`\forgetparameters [...1] [...2...,...]`

1 TEXT

2 KEY = VALUE

`\forgetragged`

`\formula [...1,...] {...2...}`

1 packed tight middle frame inherits: \setupbodyfont

2 CONTENT

`\formulanumber [...*,...]`

* REFERENCE

`\foundbox {...1} {...2...}`

1 NAME

2 NAME

`\fourthoffivearguments {...1} {...2} {...3} {...4} {...5}`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\fourthoffourarguments {...1} {...2} {...3} {...4}`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

`\fourthofsixarguments {...} {...} {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT

`\frac {...} {...}`

1 CONTENT
2 CONTENT

`\fraction {...} {...}`

1 CONTENT
2 CONTENT

`\framed [...,\stackrel{1}{...}] {...}`

1 inherits: \setupframed
2 CONTENT

`\frameddimension {...}`

* KEY

`\framedparameter {...}`

* KEY

`\framedtext [...,\stackrel{1}{...}] {...}`

1 inherits: \setupframedtext
2 CONTENT

`\framedtext [...,\stackrel{1}{...}] {...}`

1 inherits: \setupframedtext
2 CONTENT

`\framed [...,\stackrel{1}{...}] {...}`

1 inherits: \setupframed
2 CONTENT

`\freezedimenmacro \stackrel{1}{...} \stackrel{2}{...}`

1 CSNAME
2 CSNAME

`\freezemeasure [\stackrel{1}{...}] [\stackrel{2}{...}]`

1 NAME
2 DIMENSION

`\frenchspacing`

<code>\from [...]</code> * REFERENCE
<code>\fromlinenote [...]¹ {...}²</code> 1 REFERENCE 2 TEXT
<code>\frozenhbox {...}</code> * CONTENT
<code>\GetPar</code>
<code>\GotoPar</code>
<code>\Greeknumpals {...}</code> * NUMBER
<code>\gdefconvertedargument \...¹ {...}²</code> 1 CSNAME 2 TEXT
<code>\gdefconvertedcommand \...¹ \...²</code> 1 CSNAME 2 CSNAME
<code>\getboxllx ...</code> * CSNAME NUMBER
<code>\getboxlly ...</code> * CSNAME NUMBER
<code>\getbuffer [...]</code> * BUFFER
<code>\getbufferdata [...]</code> * BUFFER
<code>\getbuffer</code>
<code>\getcommacommandsize [...,*,...]</code> * COMMAND
<code>\getcommalistsize [...,*,...]</code> * COMMAND

`\getdayoftheweek {...} {...} {...}`

- 1 NUMBER
- 2 NUMBER
- 3 NUMBER

`\getdayspermonth {...} {...}`

- 1 NUMBER
- 2 NUMBER

`\getdefinedbuffer [...]`

- * BUFFER

`\getdocumentargument {...}`

- * NAME

`\getdocumentargumentdefault {...} {...}`

- 1 NAME
- 2 TEXT

`\getdocumentfilename {...}`

- * NUMBER

`\getdummyparameters [...,...1...,...]`

- * KEY = VALUE

`\getemptyparameters [...1] [...,...2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getparameters [...1] [...,...2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getexpandedparameters [...1] [...,...2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getfiguredimensions [...1] [...,...2...,...]`

- 1 FILE
- 2 inherits: \setupexternalfigure

`\getfirstcharacter {...}`

- * TEXT

`\getfirsttwopassdata {...}`

- * NAME

`\getfromcommand [..1...] [2..]`

1 COMMAND

2 NUMBER

`\getfromcommalist [..1...] [2..]`

1 COMMAND

2 NUMBER

`\getfromtwopassdata {..1.} {..2.}`

1 NAME

2 NAME

`\getglyphdirect {..1.} {..2.}`

1 FONT

2 NUMBER CHARACTER

`\getglyphstyled {..1.} {..2.}`

1 FONT

2 NUMBER CHARACTER

`\getgparameters [1..] [2..,..2..,..2..]`

1 TEXT

2 KEY = VALUE

`\getlasttwopassdata {.*.}`

* NAME

`\getlocalfloat {.*.}`

* NUMBER

`\getlocalfloats`

`\getMPdrawing`

`\getMPlayer [1..] [2..,..2..,..2..] {3..}`

1 NAME

2 inherits: \setupframed

3 CONTENT

`\getmarking [1..] [2..] [3..]`

1 MARK

2 page NAME

3

`\getmessage {..1.} {..2.}`

1 NAME

2 NAME NUMBER

`\getnamedglyphdirect {...} {...}`

- 1 FONT
- 2 NAME

`\getnamedglyphstyled {...} {...}`

- 1 FONT
- 2 NAME

`\getnamedtwopassdatalist \1... {...}`

- 1 CSNAME
- 2 NAME

`\getnaturaldimensions ...`

- * CSNAME NUMBER

`\getnoflines {...}`

- * DIMENSION

`\getobject {...} {...}`

- 1 NAME
- 2 NAME

`\getobjectdimensions {...} {...}`

- 1 NAME
- 2 NAME

`\getpaletsize [...]`

- * NAME

`\getparameters [...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getprivatechar {...}`

- * NAME

`\getprivateslot {...}`

- * NAME

`\getrandomcount \1... {...} {...}`

- 1 CSNAME
- 2 NUMBER
- 3 NUMBER

`\getrandomdimen \1... {2...} {3...}`

- 1 CSNAME
- 2 DIMENSION
- 3 DIMENSION

`\getrandomfloat \1... {2...} {3...}`

- 1 CSNAME
- 2 NUMBER
- 3 NUMBER

`\getrandomnumber \1... {2...} {3...}`

- 1 CSNAME
- 2 NUMBER
- 3 NUMBER

`\getrandomseed *...`

- * CSNAME

`\getraweparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawgparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawnoflines {*...}`

- * DIMENSION

`\getrawparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawxparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getreference [1...] [2...]`

- 1
- 2 REFERENCE

`\getreferenceentry {*...}`

- *

`\getroundednoflines {*...}`

- * DIMENSION

`\getsubstring {...} {...} {...}`

- 1 NUMBER
- 2 NUMBER
- 3 TEXT

`\gettwopassdata {...}`

- * NAME

`\gettwopassdatalist {...}`

- * NAME

`\getuvalue {...}`

- * NAME

`\getvalue {...}`

- * NAME

`\getvariable {...} {...}`

- 1 NAME
- 2 KEY

`\getvariabledefault {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 COMMAND

`\getxparameters [...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\globaldisablemode [...,*,...]`

- * NAME

`\globalenablemode [...,*,...]`

- * NAME

`\globalletempty \.*...`

- * CSNAME

`\globalpopbox \.*...`

- * CSNAME NUMBER

`\globalpopmacro \.*...`

- * CSNAME

`\globalpreventmode [...,*,...]`

- * NAME

`\globalprocesscommalist [...] \^...`

1 COMMAND

2 CSNAME

`\globalpushbox ...`

* CSNAME NUMBER

`\globalpushmacro \^...`

* CSNAME

`\globalpushreferenceprefix {...} ... \globalpopreferenceprefix`

*

`\globalswapcounts \^... \^...`

1 CSNAME

2 CSNAME

`\globalswapdimens \^... \^...`

1 CSNAME

2 CSNAME

`\globalswapmacros \^... \^...`

1 CSNAME

2 CSNAME

`\globalundefine {...}`

* NAME

`\glyphfontfile {...}`

* FONT

`\gobbledoubleempty [...^] [...^]`

1 TEXT

2 TEXT

`\gobbleeightarguments {...^} {...^} {...^} {...^} {...^} {...^} {...^} {...^}`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

7 CONTENT

8 CONTENT

`\gobblefivearguments {...} {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT

`\gobblefiveoptionals [...] [...] [...] [...] [...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\gobblefourarguments {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT

`\gobblefouroptionals [...] [...] [...] [...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT
- 8 CONTENT
- 9 CONTENT

`\gobbleoneargument {...}`

- * CONTENT

`\gobbleoneoptional [...]`

- * TEXT

`\gobblesevenarguments {1.} {2.} {3.} {4.} {5.} {6.} {7.}`

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT

`\gobblesingleempty [...]`

* TEXT

`\gobblesixarguments {1.} {2.} {3.} {4.} {5.} {6.}`

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT

`\gobblespacetokens`

`\gobbletenarguments {1.} {2.} {3.} {4.} {5.} {6.} {7.} {8.} {9.} {10.}`

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT
8 CONTENT
9 CONTENT
10 CONTENT

`\gobblethreearguments {1.} {2.} {3.}`

1 CONTENT
2 CONTENT
3 CONTENT

`\gobblethreeoptionals [1.] [2.] [3.]`

1 TEXT
2 TEXT
3 TEXT

`\gobbletwoarguments {1.} {2.}`

1 CONTENT
2 CONTENT

<p><code>\gobbletwooptionals [...] [...]</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\gobbleuntil *</code></p> <p>* CSNAME</p>
<p><code>\gobbleuntilrelax ... \relax</code></p> <p>* CONTENT</p>
<p><code>\godown [...]</code></p> <p>* DIMENSION</p>
<p><code>\goto {...} [...]</code></p> <p>1 CONTENT</p> <p>2 REFERENCE</p>
<p><code>\gotobox {...} [...]</code></p> <p>1 CONTENT</p> <p>2 REFERENCE</p>
<p><code>\gotopage {...} [...]</code></p> <p>1 TEXT</p> <p>2 REFERENCE</p>
<p><code>\got [...] ... \</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\grabbufferdata [...] [...] [...] [...]</code></p> <p>1 CATEGORY</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p>
<p><code>\grabbufferdatadirect {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p>
<p><code>\grabuntil {...} *</code></p> <p>1 NAME</p> <p>2 CSNAME</p>
<p><code>\grave {...}</code></p> <p>* CHARACTER</p>

<code>\graycolor [...]{...}</code> 1 COLOR 2 CONTENT
<code>\grayvalue {...}</code> * COLOR
<code>\greedystring \at ... \to ... \and ...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\greeknumerals {...}</code> * NUMBER
<code>\grid [..., ...=..., ...]</code> * inherits: \basegrid
<code>\groupedcommand {...}{...}</code> 1 COMMAND 2 COMMAND
<code>\gsetboxllx ...{...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gsetboxlly ...{...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gujaratinumerals {...}</code> * NUMBER
<code>\gurmukhinumerals {...}</code> * NUMBER
<code>\hairline</code>
<code>\hairspace</code>
<code>\halfwaybox {...}</code> * CONTENT
<code>\handletokens ... \with ...</code> 1 TEXT 2 CSNAME

<code>\handwritten</code>
<code>\hangul</code>
<code>\hanzi</code>
<code>\hash</code>
<code>\hat {...}</code> * CHARACTER
<code>\hboxofvbox ...</code> * CSNAME NUMBER
<code>\hboxreference [...¹,...] {...²}</code> 1 REFERENCE 2 CONTENT
<code>\hboxbox {...}</code> * CONTENT
<code>\hdofstring {...}</code> * TEXT
<code>\headhbox ...¹ {...²}</code> 1 TEXT 2 CONTENT
<code>\headlanguage</code>
<code>\headnumber [...¹] [...²]</code> 1 SECTION 2 previous <u>current</u> next first last
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsym {...¹} [...²,...] {...³}</code> 1 TEXT 2 REFERENCE 3 TEXT
<code>\headtext {...}</code> * KEY

<code>\headtextcontent</code>
<code>\headtexts {...} {...}</code> 1 KEY 2 TEXT
<code>\headtextwidth</code>
<code>\headvbox ... {...}</code> 1 TEXT 2 CONTENT
<code>\headwidth</code>
<code>\head ... \par</code> * TEXT
<code>\heightanddepthofstring {...}</code> * TEXT
<code>\heightofstring {...}</code> * TEXT
<code>\heightspanningtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\helptext [...] {...} {...}</code> 1 REFERENCE 2 TEXT 3 TEXT
<code>\help [...] {...} {...}</code> 1 REFERENCE 2 TEXT 3 TEXT
<code>\hglue ...</code> * DIMENSION
<code>\hiddenbar {...}</code> * CONTENT
<code>\hiddencitation [...]</code> * REFERENCE

<code>\hiddencite [...]</code> * REFERENCE
<code>\hideblocks [...¹,...] [...²,...]</code> 1 NAME 2 + -
<code>\high {...}</code> * CONTENT
<code>\highlight [...¹] {...²}</code> 1 NAME 2 TEXT
<code>\highlight {...}</code> * TEXT
<code>\highordinalstr {...}</code> * TEXT
<code>\high {...}</code> * CONTENT
<code>\hilo [...¹] {...²} {...³}</code> 1 left <u>right</u> 2 CONTENT 3 CONTENT
<code>\himilo {...¹} {...²} {...³}</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\hl [...]</code> * NUMBER
<code>\horizontalgrowingbar [...,[*]...,...]</code> * inherits: \setuppositionbar
<code>\horizontalpositionbar [...,[*]...,...]</code> * inherits: \setuppositionbar
<code>\hphantom {...}</code> * CONTENT
<code>\hpos {...¹} {...²}</code> 1 NAME 2 CONTENT

\backslash hsizelfraction {...} {...} 1 DIMENSION 2 NUMBER
\backslash hsmash {...} * CONTENT
\backslash hsmashbox ... * CSNAME NUMBER
\backslash hsmashed {...} * CONTENT
\backslash hspace [...] [...] 1 NAME 2 small medium big normal <u>default</u> none .5 1 2 3 speech quote interquotation quotation sentence intersentence NAME
\backslash htdpofstring {...} * TEXT
\backslash htofstring {...} * TEXT
\backslash hyphen
\backslash hyphenatedcoloredword {...} * TEXT
\backslash hyphenatedfile {...} * FILE
\backslash hyphenatedfilename {...} * TEXT
\backslash hyphenatedhbox {...} * CONTENT
\backslash hyphenatedpar {...} * TEXT
\backslash hyphenatedurl {...} * TEXT
\backslash hyphenatedword {...} * TEXT
\backslash INRSTEX

<code>\ibox {...}</code> * CONTENT
<code>\ifassignment ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\iff</code>
<code>\ifinobject ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\ifinoutputstream ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\iftrialssetting ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignorevalue {...}</code> * NAME
<code>\immediatesavetwopassdata ¹{...} ²{...} ³{...}</code> 1 NAME 2 NUMBER 3 CONTENT
<code>\impliedby</code>
<code>\implies</code>
<code>\in ¹{...} ²{...} [³...]</code> 1 TEXT 2 TEXT 3 REFERENCE
<code>\includemenu [...]</code> * NAME

<code>\includeversioninfo {...}</code> * NAME
<code>\incrementcounter [...]¹ [...]²</code> 1 NAME 2 NUMBER
<code>\incrementedcounter [...]</code> * NAME
<code>\incrementpagenumber</code>
<code>\incrementsubpagenumber</code>
<code>\incrementvalue {...}</code> * NAME
<code>\increment *...</code> * CSNAME
<code>\increment cd:parentheses-1</code> * CSNAME NUMBER
<code>\indentation</code>
<code>\index [...]¹ [...+...+...]</code> 1 TEXT PROCESSOR->TEXT 2 INDEX
<code>\index [...]¹ {...}² [...+...+...]³</code> 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX
<code>\infofont</code>
<code>\infofontbold</code>
<code>\inframed [...,...¹...,...]² {...}</code> 1 inherits: \setupframed 2 CONTENT
<code>\infull {...}</code> * NAME

<code>\inheritparameter [...]¹ [...]² [...]³</code> 1 TEXT 2 TEXT 3 KEY
<code>\inhibitblank</code>
<code>\ininner [...]¹ [...]² {...}³</code> 1 reference = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inneredge [...]¹ [...]² {...}³</code> 1 reference = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\innermargin [...]¹ [...]² {...}³</code> 1 reference = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\initializeboxstack {...}</code> * NAME
<code>\inleft [...]¹ [...]² {...}³</code> 1 reference = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inleftedge [...]¹ [...]² {...}³</code> 1 reference = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inleftmargin [...]¹ [...]² {...}³</code> 1 reference = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inline {...}¹ [...]²</code> 1 TEXT 2 REFERENCE

<code>\inlinebuffer [...,*...]</code> * BUFFER
<code>\inlinedbox {...}</code> * CONTENT
<code>\inlinemath {...}</code> * CONTENT
<code>\inlinemathematics {...}</code> * CONTENT
<code>\inlinemessage {...}</code> * TEXT
<code>\inlineordisplaymath {...}^1 {...}^2 {...}</code> 1 CONTENT 2 CONTENT
<code>\inlinorange [...]</code> * REFERENCE
<code>\inmargin [...,\stackrel{1}{=}\dots,] [...,\stackrel{2}{=}\dots,] {...}^3</code> 1 reference = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inmframed [...,\stackrel{1}{=}\dots,] {...}^2</code> 1 inherits: \setupmathframed 2 CONTENT
<code>\innerflushshapebox</code>
<code>\inotherv [...,\stackrel{1}{=}\dots,] [...,\stackrel{2}{=}\dots,] {...}^3</code> 1 reference = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inouter [...,\stackrel{1}{=}\dots,] [...,\stackrel{2}{=}\dots,] {...}^3</code> 1 reference = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT

$\backslash\text{inouteredge}$ [$\dots\overset{1}{=}\dots$] [$\dots\overset{2}{=}\dots$] $\{\dots\}$ 1 <code>reference = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 <code>inherits: \setupmarginframed</code> 3 <code>CONTENT</code>
$\backslash\text{inoutermargin}$ [$\dots\overset{1}{=}\dots$] [$\dots\overset{2}{=}\dots$] $\{\dots\}$ 1 <code>reference = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 <code>inherits: \setupmarginframed</code> 3 <code>CONTENT</code>
$\backslash\text{inputfilebarename}$
$\backslash\text{inputfilename}$
$\backslash\text{inputfilerealsuffix}$
$\backslash\text{inputfilesuffix}$
$\backslash\text{inputgivenfile}$ $\{\dots\}$ * <code>FILE</code>
$\backslash\text{input}$ $\{\dots\}$ * <code>FILE</code>
$\backslash\text{input}$ \dots * <code>FILE</code>
$\backslash\text{inright}$ [$\dots\overset{1}{=}\dots$] [$\dots\overset{2}{=}\dots$] $\{\dots\}$ 1 <code>reference = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 <code>inherits: \setupmarginframed</code> 3 <code>CONTENT</code>
$\backslash\text{inrightedge}$ [$\dots\overset{1}{=}\dots$] [$\dots\overset{2}{=}\dots$] $\{\dots\}$ 1 <code>reference = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 <code>inherits: \setupmarginframed</code> 3 <code>CONTENT</code>
$\backslash\text{inrightmargin}$ [$\dots\overset{1}{=}\dots$] [$\dots\overset{2}{=}\dots$] $\{\dots\}$ 1 <code>reference = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 <code>inherits: \setupmarginframed</code> 3 <code>CONTENT</code>

\insertpages [...]¹ [...]²,... [...]³,...]

1 FILE
2 NUMBER
3 width = DIMENSION
n = NUMBER

\installactionhandler {...}

* NAME

\installactivecharacter ...

* CHARACTER

\installanddefineactivecharacter ...¹ {...}²

1 CHARACTER
2 COMMAND

\installattributestack \...

* CSNAME

\installautocommandhandler \...¹ {...}² \...³

1 CSNAME
2 NAME
3 CSNAME

\installautosetuphandler \...¹ {...}²

1 CSNAME
2 NAME

\installbasicautosetuphandler \...¹ {...}² \...³

1 CSNAME
2 NAME
3 CSNAME

\installbasicparameterhandler \...¹ {...}²

1 CSNAME
2 NAME

\installbottomframerenderer {...}¹ {...}²

1 NAME
2 COMMAND

\installcommandhandler \...¹ {...}² \...³

1 CSNAME
2 NAME
3 CSNAME

\installcorenamespace {...}

* NAME

\installdefinehandler \¹... {²...} \³...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installdefinitionset \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdefinitionsetmember \¹... {²...} \³... {⁴...}

- 1 CSNAME
- 2 NAME
- 3 CSNAME
- 4 NAME

\installdirectcommandhandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdirectparameterhandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdirectparametersethandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdirectsetuphandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdirectstyleandcolorhandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installframedautocommandhandler \¹... {²...} \³...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installframedcommandhandler \¹... {²...} \³...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installlanguage [...]¹ [...,²...,...]

1 NAME

2 inherits: \setuplanguage

\installlanguage [...]¹ [...]²

1 NAME

2 LANGUAGE

\installleftframerenderer {...}¹ {...}²

1 NAME

2 COMMAND

\installnamespace {...}^{*}

* NAME

\installoutputroutine \...¹ {...}²

1 CSNAME

2 COMMAND

\installpagearrangement ...¹ {...}²

1 NAME

2 COMMAND

\installparameterhandler \...¹ {...}²

1 CSNAME

2 NAME

\installparameterhashhandler \...¹ {...}²

1 CSNAME

2 NAME

\installparametersethandler \...¹ {...}²

1 CSNAME

2 NAME

\installparentinjector \...¹ {...}²

1 CSNAME

2 NAME

\installrightframerenderer {...}¹ {...}²

1 NAME

2 COMMAND

\installrootparameterhandler \...¹ {...}²

1 CSNAME

2 NAME

\installsetuphandler \.¹ {..²}

1 CSNAME

2 NAME

\installsetuponlycommandhandler \.¹ {..²}

1 CSNAME

2 NAME

\installshipoutmethod {..¹} {..²}

1 NAME

2 COMMAND

\installsimplecommandhandler \.¹ {..²} \.³..

1 CSNAME

2 NAME

3 CSNAME

\installsimpleframedcommandhandler \.¹ {..²} \.³..

1 CSNAME

2 NAME

3 CSNAME

\installstyleandcolorhandler \.¹ {..²}

1 CSNAME

2 NAME

\installswitchcommandhandler \.¹ {..²} \.³..

1 CSNAME

2 NAME

3 CSNAME

\installswitchsetuphandler \.¹ {..²}

1 CSNAME

2 NAME

\installtexdirective {..¹} {..²} {..³}

1 NAME

2 COMMAND

3 COMMAND

\installtextracker {..¹} {..²} {..³}

1 NAME

2 COMMAND

3 COMMAND

<code>\installtopframerenderer {...} {...}</code> 1 NAME 2 COMMAND
<code>\installunitsseparator {...} {...}</code> 1 NAME 2 COMMAND
<code>\installunitsspace {...} {...}</code> 1 NAME 2 COMMAND
<code>\installversioninfo {...} {...}</code> 1 NAME 2 COMMAND
<code>\integerrounding {...}</code> * NUMBER
<code>\interactionbar [...]¹ [...,...²...,...]</code> 1 NAME 2 inherits: \setupinteractionbar
<code>\interactionbuttons [...,...¹...,...]² [...²,...]</code> 1 inherits: \setupinteractionbar 2 page subpage REFERENCE
<code>\interactionmenu [...]¹ [...,...²...,...]</code> 1 NAME 2 inherits: \setupinteractionmenu
<code>\intertext {...}</code> * TEXT
<code>\invokepagehandler {...} {...}</code> 1 normal none NAME 2 CONTENT
<code>\istltdir ...</code> * TLT TRT
<code>\istrtdir ...</code> * TLT TRT
<code>\italic</code>
<code>\italicbold</code>

<code>\italiccorrection</code>
<code>\items [...,\¹...,...] {\²...}</code> 1 inherits: \setupitems 2 TEXT
<code>\itemtag [...,*,...]</code> * REFERENCE
<code>\item [...,*,...]</code> * REFERENCE
<code>\itm [...,*,...]</code> * REFERENCE
<code>\its</code>
<code>\jobfilename</code>
<code>\jobfilesuffix</code>
<code>\kap {...}</code> * TEXT
<code>\keepblocks [...,\¹...,...] [...,\²...,...]</code> 1 NAME 2 + -
<code>\keeplinestogether {...}</code> * NUMBER
<code>\keepunwantedspaces</code>
<code>\kerncharacters [...]\¹...] {\²...}</code> 1 NUMBER 2 TEXT
<code>\koreancirclenumerals {...}</code> * NUMBER
<code>\koreannumerals {...}</code> * NUMBER
<code>\koreannumeralsc {...}</code> * NUMBER
<code>\koreannumeralsp {...}</code> * NUMBER

<code>\koreanparentnumerals {...}</code> * NUMBER
<code>\LAMSTEX</code>
<code>\LATEX</code>
<code>\LamSTeX</code>
<code>\LaTeX</code>
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\labellanguage</code>
<code>\labellanguage</code>
<code>\labeltext {...}</code> * KEY
<code>\labeltexts {...¹} {...²}</code> 1 KEY 2 TEXT
<code>\labeltexts {...¹} {...²}</code> 1 KEY 2 TEXT
<code>\labeltext {...}</code> * KEY
<code>\label [...¹,...] {...²}</code> 1 REFERENCE 2 TEXT
<code>\language [...]</code> * LANGUAGE
<code>\languageCharacters {...}</code> * NUMBER

<code>\languagecharacters {...}</code> * NUMBER
<code>\languagecharwidth {...}</code> * LANGUAGE
<code>\language</code>
<code>\lastcounter [...] [...]</code> 1 NAME 2 NUMBER
<code>\lastcountervalue [...]</code> * NAME
<code>\lastdigit {...}</code> * NUMBER
<code>\lastnaturalboxdp</code>
<code>\lastnaturalboxht</code>
<code>\lastnaturalboxwd</code>
<code>\lastpredefinedsymbol</code>
<code>\lastrealpage</code>
<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue [...] [...]</code> 1 NAME 2 NUMBER
<code>\lastsubpage</code>
<code>\lastsubpagenumber</code>
<code>\lasttwodigits {...}</code> * NUMBER
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode {...}</code> * COMMAND
<code>\latin</code>

<p><code>\layeredtext [...¹... [...²... {³...} {⁴...}</code></p> <p>1 inherits: \setuplayer</p> <p>2 inherits: \setuplayeredtext</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\layerheight</code></p>
<p><code>\layerwidth</code></p>
<p><code>\lazysavetaggedtwopassdata {¹...} {²...} {³...} {⁴...}</code></p> <p>1 NAME</p> <p>2 NUMBER</p> <p>3 NAME</p> <p>4 CONTENT</p>
<p><code>\lazysavetwopassdata {¹...} {²...} {³...}</code></p> <p>1 NAME</p> <p>2 NUMBER</p> <p>3 CONTENT</p>
<p><code>\lbox ¹... {²...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\left ...</code></p> <p>* CHARACTER</p>
<p><code>\leftaligned {[*]...}</code></p> <p>* CONTENT</p>
<p><code>\leftbottombox {[*]...}</code></p> <p>* CONTENT</p>
<p><code>\leftbox {[*]...}</code></p> <p>* CONTENT</p>
<p><code>\lefthbox {[*]...}</code></p> <p>* CONTENT</p>
<p><code>\leftheadtext {[*]...}</code></p> <p>* KEY</p>
<p><code>\leftlabeltext {[*]...}</code></p> <p>* KEY</p>
<p><code>\leftlabeltext {[*]...}</code></p> <p>* KEY</p>

<code>\leftline {...}</code> * CONTENT
<code>\leftmathlabeltext {...}</code> * KEY
<code>\lefttorrighthbox .¹. {...}</code> 1 TEXT 2 CONTENT
<code>\lefttorrightvbox .¹. {...}</code> 1 TEXT 2 CONTENT
<code>\lefttorrightvtop .¹. {...}</code> 1 TEXT 2 CONTENT
<code>\leftskipadaption</code>
<code>\leftsubguillemot</code>
<code>\leftttopbox {...}</code> * CONTENT
<code>\lefttoright</code>
<code>\lefttorrighthbox .¹. {...}</code> 1 TEXT 2 CONTENT
<code>\lefttorrightvbox .¹. {...}</code> 1 TEXT 2 CONTENT
<code>\lefttorrightvtop .¹. {...}</code> 1 TEXT 2 CONTENT
<code>\letbeundefined {...}</code> * NAME
<code>\letcatcodecommand \¹... \²... \³...</code> 1 CSNAME 2 CHARACTER NUMBER 3 CSNAME

<pre>\letcscsname \.^1. \csname .^2. \endcsname</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\letcsnamecs \csname .^1. \endcsname \.^2.</pre> <pre>1 NAME</pre> <pre>2 CSNAME</pre>
<pre>\letcsnamecsname \csname .^1. \endcsname \csname .^2. \endcsname</pre> <pre>1 NAME</pre> <pre>2 NAME</pre>
<pre>\letdummyparameter {...} \.^2.</pre> <pre>1 KEY</pre> <pre>2 CSNAME</pre>
<pre>\letempty \.*.</pre> <pre>* CSNAME</pre>
<pre>\letgvalue {...} \.^2.</pre> <pre>1 NAME</pre> <pre>2 CSNAME</pre>
<pre>\letgvalueempty {...}</pre> <pre>* NAME</pre>
<pre>\letgvalurelax {...}</pre> <pre>* NAME</pre>
<pre>\letterampersand</pre>
<pre>\letterat</pre>
<pre>\letterbackslash</pre>
<pre>\letterbar</pre>
<pre>\letterbgroup</pre>
<pre>\letterclosebrace</pre>
<pre>\lettercolon</pre>
<pre>\letterdollar</pre>
<pre>\letterdoublequote</pre>
<pre>\letteregroup</pre>

<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing [...]{...}</code> 1 NUMBER 2 TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue {...}\...</code> 1 NAME 2 CSNAME
<code>\letvalueempty {...}</code> * NAME
<code>\letvaluerelax {...}</code> * NAME
<code>\lfence {...}</code> * CHARACTER
<code>\lhbox {...}</code> * CONTENT

`\limitatelines {...} {...} {...}`

- 1 NUMBER
- 2 COMMAND
- 3 TEXT

`\limitatetext {...} {...} {...}`

- 1 TEXT
- 2 [-+]DIMENSION
- 3 COMMAND

`\limitatetext {...} {...,2...} {...}`

- 1 TEXT
- 2 [-+]DIMENSION
- 3 COMMAND

`\limtatefirstline {...} {...} {...}`

- 1 TEXT
- 2 DIMENSION
- 3 COMMAND

`\line {...}`

- * CONTENT

`\linenote {...}`

- * TEXT

`\linenote {...}`

- * TEXT

`\linespanningtext {...} {...} {...}`

- 1 TEXT
- 2 DIMENSION
- 3 FONT

`\linewidth`

`\listcitation [...,1...,...] [...2]`

- 1 reference = REFERENCE
- alternative =
- before = COMMAND
- after = COMMAND
- left = COMMAND
- right = COMMAND
- inherits: \setupbtx
- 2 REFERENCE

`\listcitation [...1...] [...2...]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 KEY = VALUE

`\listcitation [...1] [...2]`

1

2 REFERENCE

`\listcite [...1...] [...2...]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 REFERENCE

`\listcite [...1...] [...2...]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 KEY = VALUE

`\listcite [...1] [...2]`

1

2 REFERENCE

`\listlength`

`\listnamespaces`

`\llap {...}`

* CONTENT

`\loadanyfile [...]`

* FILE

`\loadanyfileonce [...]`

* FILE

`\loadbtxdefinitionfile [...]`

* FILE

\loadbtxreplacementfile [...] * FILE
\loadcldfile [...] * FILE
\loadcldfileonce [...] * FILE
\loadfontgoodies [...] * FILE
\loadluafile [...] * FILE
\loadluafileonce [...] * FILE
\loadspellchecklist [¹ ...] [² ...] 1 NAME 2 FILE
\loadtexfile [...] * FILE
\loadtexfileonce [...] * FILE
\loadtypescriptfile [...] * FILE
\localframed [¹] [..., ² ...,...] { ³ ...} 1 NAME 2 inherits: \setupframed 3 CONTENT
\localframedwithsettings [¹] [..., ² ...,...] { ³ ...} 1 NAME 2 inherits: \setupframed 3 CONTENT
\localhsize
\localpopbox ... * CSNAME NUMBER
\localpopmacro *... * CSNAME

<code>\localpushbox ...</code> * CSNAME NUMBER
<code>\localpushmacro \...</code> * CSNAME
<code>\localundefine {...}</code> * NAME
<code>\locatedfilepath</code>
<code>\locatefilepath {...}</code> * FILE
<code>\locfilename {...}</code> * FILE
<code>\logo [...]¹ {...}²</code> 1 NAME 2 CONTENT
<code>\lohi [...]¹ {...}² {...}³</code> 1 left <u>right</u> 2 CONTENT 3 CONTENT
<code>\lomihi {...}¹ {...}² {...}³</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\low {...}</code> * CONTENT
<code>\lowerbox {...}¹ \...² {...}³</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\lowercased {...}</code> * TEXT
<code>\lowercasestring ...¹ \to \...²</code> 1 TEXT 2 CSNAME
<code>\lowerlefthdoubleninequote</code>

<code>\lowerleftsingleninequote</code>
<code>\lowerrightdoubleninequote</code>
<code>\lowerrightsingleninequote</code>
<code>\lowhigh [.¹.] {..².} {..³.}</code> 1 left <u>right</u> 2 CONTENT 3 CONTENT
<code>\lowmidhigh {..¹.} {..².} {..³.}</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\low {..[*].}</code> * CONTENT
<code>\lrbbox {..¹.} {..².} {..³.} {..⁴.} {..⁵.}</code> 1 DIMENSION 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 CONTENT
<code>\ltop ..¹. {..².}</code> 1 TEXT 2 CONTENT
<code>\luacode {..[*].}</code> * COMMAND
<code>\luaconditional \..[*].</code> * CSNAME
<code>\luaenvironment ..[*].</code> * FILE
<code>\luaexpanded {..[*].}</code> * COMMAND
<code>\luafunction {..[*].}</code> * COMMAND
<code>\luajitTeX</code>
<code>\luamajorversion</code>

<code>\luaminorversion</code>
<code>\luaparameterset {¹...} {²...}</code> 1 NAME 2 CONTENT
<code>\luasetup {...}</code> * NAME
<code>\luaTeX</code>
<code>\luaversion</code>
<code>\METAFONT</code>
<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTH {...}</code> * NUMBER
<code>\MONTHLONG {...}</code> * NUMBER
<code>\MONTHSHORT {...}</code> * NUMBER
<code>\MPanchor {...}</code> * NAME
<code>\MPbetex {...}</code> * NAME

\MPc {...} * NAME
\MPcode {...} {...} 1 NAME 2 CONTENT
\MPcolor {...} * COLOR
\MPcoloronly {...} * COLOR
\MPcolumn {...} * NAME
\MPd {...} * NAME
\MPdrawing {...} * CONTENT
\MPfontsizehskip {...} * FONT
\MPgetmultipars {...} {...} 1 NAME 2 NAME
\MPgetmultishape {...} {...} 1 NAME 2 NAME
\MPgetposboxes {... ¹ ,...} {... ² } 1 NAME 2 NAME
\MPh {...} * NAME
\MPII
\MPIV
\MPinclusions [... ¹] [... ²] [... ³] 1 + 2 NAME 3 CONTENT

\MPleftskip {...} * NAME
\MPll {...} * NAME
\MPlr {...} * NAME
\MPls {...} * NAME
\MPmenubuttons {...} * NAME
\MPn {...} * NAME
\MPoptions {...} * COLOR
\MPoverlayanchor {...} * NAME
\MPp {...} * NAME
\MPpage {...} * NAME
\MPpardata {...} * NAME
\MPplus {... ¹ } {... ² } {... ³ } 1 NAME 2 NUMBER 3 CONTENT
\MPpos {...} * NAME
\MPpositiongraphic {... ¹ } {..., ² ...,...} 1 NAME 2 KEY = VALUE
\MPposset {...} * NAME

\MP _r {...} * NAME
\MP _r awvar {...} {...} 1 NAME 2 KEY
\MP _r egion {...} * NAME
\MP _r est {...} {...} 1 NAME 2 CONTENT
\MP _r ightskip {...} * NAME
\MP _r s {...} * NAME
\MP _s tring {...} * NAME
\MP _t ext {...} * NAME
\MP _t ransparency {...} * COLOR
\MP _u l {...} * NAME
\MP _u r {...} * NAME
\MP _V I
\MP _v {...} {...} {...} 1 NAME 2 NUMBER 3 CONTENT
\MP _v ar {...} * KEY
\MP _v ariable {...} * KEY

<code>\MPvv {...} {...}</code> 1 NAME 2 CONTENT
<code>\MPw {...}</code> * NAME
<code>\MPwhd {...}</code> * NAME
<code>\MPx {...}</code> * NAME
<code>\MPxy {...}</code> * NAME
<code>\MPxywhd {...}</code> * NAME
<code>\MPy {...}</code> * NAME
<code>\m [...] {...}</code> 1 NAME 2 CONTENT
<code>\mainlanguage [...]</code> * LANGUAGE
<code>\makecharacteractive ...</code> * CHARACTER
<code>\makerawcommalist [...¹,...] \...²</code> 1 COMMAND 2 CSNAME
<code>\makestrutofbox ...</code> * CSNAME NUMBER
<code>\mapfontsize [...]¹ [...]²</code> 1 DIMENSION 2 DIMENSION

`\margindata [...1] [...2...] [...3...] {...4}`

1 NAME
2 reference = REFERENCE
inherits: \setupmargindata
3 inherits: \setupmarginframed
4 CONTENT

`\margindata [...1...] [...2...] {...3}`

1 reference = REFERENCE
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

`\margintext [...1...] [...2...] {...3}`

1 reference = REFERENCE
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

`\margintitle [...1...] [...2...] {...3}`

1 reference = REFERENCE
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

`\marginword [...1...] [...2...] {...3}`

1 reference = REFERENCE
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

`\markcontent [...1] {...2}`

1 reset all NAME
2 CONTENT

`\marking (...1,...) (...2,...) [...3]`

1 POSITION
2 POSITION
3 REFERENCE

`\markinjector [...*]`

* NAME

`\mar {...*}`

* TEXT

`\mat {...*}`

* CONTENT

$\backslash\mathrm{math} [\dots] \{\dots\}$ 1 NAME 2 CONTENT
$\backslash\mathrm{mathbf}$
$\backslash\mathrm{mathbi}$
$\backslash\mathrm{mathblackboard}$
$\backslash\mathrm{mathbs}$
$\backslash\mathrm{mathcommand} \{.*\}$ * NAME
$\backslash\mathrm{mathcommand} [\dots] \{\dots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mathdefault}$
$\backslash\mathrm{mathdoubleextensible} \{.*\}$ * TEXT
$\backslash\mathrm{mathematics} [\dots] \{\dots\}$ 1 NAME 2 CONTENT
$\backslash\mathrm{mathextensible} [\dots] \{\dots\} \{\dots\}$ 1 reverse mathematics text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{mathfraktur}$
$\backslash\mathrm{mathframed} [\dots, \dots^1 \dots] \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathframed}$ 2 CONTENT
$\backslash\mathrm{mathfunction} \{.*\}$ * CONTENT
$\backslash\mathrm{mathit}$
$\backslash\mathrm{mathitalic}$
$\backslash\mathrm{mathlabellanguage}$

$\backslash\mathrm{mathlabeltext}\{...\}$ * KEY
$\backslash\mathrm{mathlabeltexts}\{...\}\{...\}$ 1 KEY 2 TEXT
$\backslash\mathrm{mathop}\{...\}$ * CONTENT
$\backslash\mathrm{mathornament}\{...\}$ * CONTENT
$\backslash\mathrm{mathoverextensible}\{...\}$ * TEXT
$\backslash\mathrm{mathovertextextensible}\{...\}\{...\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mathradical}\left[...\right]\{...\}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{mathrm}$
$\backslash\mathrm{mathscript}$
$\backslash\mathrm{mathsl}$
$\backslash\mathrm{mathss}$
$\backslash\mathrm{mathtext}\{...\}$ * TEXT
$\backslash\mathrm{mathtextbf}\{...\}$ * TEXT
$\backslash\mathrm{mathtextbi}\{...\}$ * TEXT
$\backslash\mathrm{mathtextbs}\{...\}$ * TEXT
$\backslash\mathrm{mathtextit}\{...\}$ * TEXT

$\backslash\mathtextsl {...}$ * TEXT
$\backslash\mathtexttf {...}$ * TEXT
$\backslash\mathtf$
$\backslash\mathtriplet [^{1..}] \{^{2..}\} \{^{3..}\} \{^{4..}\}$ 1 NAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\mathtriplet [^{1..}] \{^{2..}\} \{^{3..}\} \{^{4..}\}$ 1 NAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\mathtt$
$\backslash\mathunderextensible {...}$ * TEXT
$\backslash\mathundertextextensible \{^{1..}\} \{^{2..}\}$ 1 TEXT 2 TEXT
$\backslash\mathunstacked$
$\backslash\mathupright$
$\backslash\mathword {...}$ * TEXT
$\backslash\mathwordbf {...}$ * TEXT
$\backslash\mathwordbi {...}$ * TEXT
$\backslash\mathwordbs {...}$ * TEXT
$\backslash\mathwordit {...}$ * TEXT

$\backslash\mathrm{mathwordsl}\{...\}$ * TEXT
$\backslash\mathrm{mathwordtf}\{...\}$ * TEXT
$\backslash\mathrm{maxaligned}\{...\}$ * CONTENT
$\backslash\mathrm{mbox}\{...\}$ * CONTENT
$\backslash\mathrm{mcframed}[\dots,\dots,\overset{1}{\dots},\dots]\{\overset{2}{\dots}\}$ 1 inherits: $\backslash\mathrm{setupmathframed}$ 2 CONTENT
$\backslash\mathrm{measure}\{...\}$ * NAME
$\backslash\mathrm{measured}\{...\}$ * NAME
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$
$\backslash\mathrm{menubutton}[\overset{1}{\dots}][\dots,\dots,\overset{2}{\dots},\dots]\{\overset{3}{\dots}\}\{\overset{4}{\dots}\}$ 1 NAME 2 inherits: $\backslash\mathrm{setupinteractionmenu}$ 3 TEXT 4 REFERENCE
$\backslash\mathrm{menubutton}[\dots,\dots,\overset{1}{\dots},\dots]\{\overset{2}{\dots}\}\{\overset{3}{\dots}\}$ 1 inherits: $\backslash\mathrm{setupbutton}$ 2 TEXT 3 REFERENCE
$\backslash\mathrm{mequal}\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{message}\{...\}$ * TEXT
$\backslash\mathrm{metaTeX}$
$\backslash\mathrm{mfence}\{...\}$ * CHARACTER

$\backslash\mathrm{mframed} [\dots,\dots^1,\dots] \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathframed}$ 2 CONTENT
$\backslash\mathrm{mfunction} \{\dots\}$ * CONTENT
$\backslash\mathrm{mfunctionlabeltext} \{\dots\}$ * NAME
$\backslash\mathrm{mhbox} \{\dots\}$ * CONTENT
$\backslash\mathrm{mhookleftarrow} \{\dots\} \{\dots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mhookrightarrow} \{\dots\} \{\dots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{midaligned} \{\dots\}$ * CONTENT
$\backslash\mathrm{middle} \dots$ * CHARACTER
$\backslash\mathrm{middlealigned} \{\dots\}$ * CONTENT
$\backslash\mathrm{middlebox} \{\dots\}$ * CONTENT
$\backslash\mathrm{midhbox} \{\dots\}$ * CONTENT
$\backslash\mathrm{minimalhbox} \dots^1 \{\dots\}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{mirror} \{\dots\}$ * CONTENT
$\backslash\mathrm{mixedcaps} \{\dots\}$ * TEXT
$\backslash\mathrm{mkvibuffer} [\dots]$ * BUFFER

\mLeftarrow $\{...\} \{...\}$ 1 TEXT 2 TEXT
\mLeftrightarrow $\{...\} \{...\}$ 1 TEXT 2 TEXT
\mleftarrow $\{...\} \{...\}$ 1 TEXT 2 TEXT
\mleftharpoondown $\{...\} \{...\}$ 1 TEXT 2 TEXT
\mleftharpoonup $\{...\} \{...\}$ 1 TEXT 2 TEXT
\mleftrightharpoonup $\{...\} \{...\}$ 1 TEXT 2 TEXT
\mleftrightharpoons $\{...\} \{...\}$ 1 TEXT 2 TEXT
\mmapsto $\{...\} \{...\}$ 1 TEXT 2 TEXT
\moduleparameter $\{...\} \{...\}$ 1 FILE 2 KEY
\molecule $\{...\}$ * CONTENT
\mono
\monobold
\mononormal
\month $\{...\}$ * NUMBER

$\backslash\text{monthlong}\{...\}$ * NUMBER
$\backslash\text{monthshort}\{...\}$ * NUMBER
$\backslash\text{mprandomnumber}$
$\backslash\text{mRightarrow}\{...\}^{1}\{...\}^{2}$ 1 TEXT 2 TEXT
$\backslash\text{mrel}\{...\}^{1}\{...\}^{2}$ 1 TEXT 2 TEXT
$\backslash\text{mrightarrow}\{...\}^{1}\{...\}^{2}$ 1 TEXT 2 TEXT
$\backslash\text{mrightharpoondown}\{...\}^{1}\{...\}^{2}$ 1 TEXT 2 TEXT
$\backslash\text{mrightharpoonup}\{...\}^{1}\{...\}^{2}$ 1 TEXT 2 TEXT
$\backslash\text{mrightharpoons}\{...\}^{1}\{...\}^{2}$ 1 TEXT 2 TEXT
$\backslash\text{mrightoverleftarrow}\{...\}^{1}\{...\}^{2}$ 1 TEXT 2 TEXT
$\backslash\text{mtext}\{...\}$ * CONTENT
$\backslash\text{mtriplerel}\{...\}^{1}\{...\}^{2}$ 1 TEXT 2 TEXT
$\backslash\text{mtwoheadleftarrow}\{...\}^{1}\{...\}^{2}$ 1 TEXT 2 TEXT

`\mtwoheadrightarrow {...} {...}`

1 TEXT

2 TEXT

`\NormalizeFontHeight \.^{.1} {...} {...} {...} {...}`

1 CSNAME

2 TEXT

3 DIMENSION

4 FONT

`\NormalizeFontWidth \.^{.1} {...} {...} {...} {...}`

1 CSNAME

2 TEXT

3 DIMENSION

4 FONT

`\NormalizeTextHeight {...} {...} {...}`

1 FONT

2 DIMENSION

3 TEXT

`\NormalizeTextWidth {...} {...} {...}`

1 FONT

2 DIMENSION

3 TEXT

`\Numbers {...}`

* NUMBER

`\namedheadnumber {...}`

* SECTION

`\namedstructureheadlocation {...}`

* SECTION

`\namedstructureuservariable {...} {...}`

1 SECTION

2 KEY

`\namedstructurevariable {...} {...}`

1 SECTION

2 KEY

<p><code>\namedtaggedlabeltexts {...} {...} {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p> <p>5 CONTENT</p>
<p><code>\naturalhbox ... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\naturalhpack ... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\naturalvbox ... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\naturalvcenter ... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\naturalvpack ... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\naturalvtop ... {...}</code></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\naturalwd ...</code></p> <p>* CSNAME NUMBER</p>
<p><code>\negatecolorbox ...</code></p> <p>* CSNAME NUMBER</p>
<p><code>\negated {...}</code></p> <p>* TEXT</p>
<p><code>\negthinspace</code></p>
<p><code>\newattribute \...</code></p> <p>* CSNAME</p>
<p><code>\newcatcodetable \...</code></p> <p>* CSNAME</p>

<code>\newcounter *...</code> <code>* CSNAME</code>
<code>\newevery \¹... \²...</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\newfrenchspacing</code>
<code>\newmode {...}</code> <code>* NAME</code>
<code>\newsignal *...</code> <code>* CSNAME</code>
<code>\newsystemmode {...}</code> <code>* NAME</code>
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...]¹ [...]²</code> <code>1 NAME</code> <code>2 NUMBER</code>
<code>\nextcountervalue [...][*]</code> <code>* NAME</code>
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\nextparagraphs</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...]¹ [...]²</code> <code>1 NAME</code> <code>2 NUMBER</code>

<code>\nextsubpage</code>
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\nihongo</code>
<code>\nobar {...}</code> * CONTENT
<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE
<code>\nodetostring \¹... {²...}</code> 1 CSNAME 2 CONTENT
<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noheaderandfooterlines</code>
<code>\noindentation</code>
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> * CONTENT
<code>\nop ... \\\</code> * TEXT
<code>\nop</code>

<code>\normal</code>
<code>\normalboldface</code>
<code>\normalframedwithsettings [...¹...²] {...}</code> 1 inherits: \setupframed 2 CONTENT
<code>\normalizebodyfontsize \...¹ {...}</code> 1 CSNAME 2 DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \...¹ {...²} {...³} {...⁴}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontheight \...¹ {...²} {...³} {...⁴}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontline \...¹ {...²} {...³} {...⁴}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontwidth \...¹ {...²} {...³} {...⁴}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizetextdepth {...¹} {...²} {...³}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextheight {...¹} {...²} {...³}</code> 1 FONT 2 DIMENSION 3 TEXT

`\normalizetextline {...} {...} {...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextwidth {...} {...} {...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normaltypeface`

`\nospace`

`\note [...]1 [...]2`

- 1 NAME
- 2 REFERENCE

`\notesymbol [...]1 [...]2`

- 1 NAME
- 2 REFERENCE

`\note [...]1, [...]2`

- 1 REFERENCE
- 2 TEXT

`\note [...]*, [...]`

- * title = TEXT
- bookmark = TEXT
- list = TEXT
- reference = REFERENCE

`\notopandbottomlines`

`\notragged`

`\notsmallcapped {...}`

- * TEXT

`\ntimes {...}1 {...}2`

- 1 TEXT
- 2 NUMBER

`\numberofpoints {...}`

- * DIMENSION

`\numbers {...}`

- * NUMBER

<code>\obeydepth</code>
<code>\objectdepth</code>
<code>\objectheight</code>
<code>\objectmargin</code>
<code>\objectwidth</code>
<code>\obox {...}</code> * CONTENT
<code>\offset [...,\stackrel{1}{...}] {...}</code> 1 inherits: \setupoffset 2 CONTENT
<code>\offsetbox [...,\stackrel{1}{...}] \stackrel{2}{...} {...}</code> 1 inherits: \setupoffsetbox 2 CSNAME 3 CONTENT
<code>\onedigitrounding {...}</code> * NUMBER
<code>\operatorlanguage</code>
<code>\operatorortext {...}</code> * KEY
<code>\ordinaldaynumber {...}</code> * NUMBER
<code>\ordinalstr {...}</code> * TEXT
<code>\ornamenttext [...,\stackrel{1}{...}] [...,\stackrel{2}{...}] {...} {...}</code> 1 alternative = <code>a b</code> inherits: \setupcollector 2 style = color = COLOR inherits: \setupframed 3 TEXT 4 CONTENT

$\backslash\text{ornamenttext} [\dots]^1 [\dots]^2 \{\dots\} \{\dots\}$ 1 <code>alternative = a b</code> <code>inherits: \setupplayer</code> 2 <code>inherits: \setuplayeredtext</code> 3 <code>TEXT</code> 4 <code>CONTENT</code>
$\backslash\text{ornamenttext} [.^1] \{.^2\} \{.^3\}$ 1 <code>NAME</code> 2 <code>TEXT</code> 3 <code>CONTENT</code>
$\backslash\text{ornament} \{\dots\} \{\dots\}$ 1 <code>TEXT</code> 2 <code>CONTENT</code>
$\backslash\text{outputfilename}$
$\backslash\text{outputstreambox} [.^*]$ * <code>NAME</code>
$\backslash\text{outputstreamcopy} [.^*]$ * <code>NAME</code>
$\backslash\text{outputstreamunvbox} [.^*]$ * <code>NAME</code>
$\backslash\text{outputstreamunvcopy} [.^*]$ * <code>NAME</code>
$\backslash\text{over} [.^*]$ * <code>REFERENCE</code>
$\backslash\text{overbar} \{\dots\}$ * <code>CONTENT</code>
$\backslash\text{overbars} \{\dots\}$ * <code>CONTENT</code>
$\backslash\text{overbartext} \{\dots\} \{\dots\}$ 1 <code>TEXT</code> 2 <code>TEXT</code>
$\backslash\text{overbarunderbar} \{\dots\}$ * <code>TEXT</code>
$\backslash\text{overbrace} \{\dots\}$ * <code>TEXT</code>

<code>\overbracetext {...} {...}</code> 1 TEXT 2 TEXT
<code>\overbraceunderbrace {...}</code> * TEXT
<code>\overbracket {...}</code> * TEXT
<code>\overbrackettext {...} {...}</code> 1 TEXT 2 TEXT
<code>\overbracketunderbracket {...}</code> * TEXT
<code>\overlaybutton [...]</code> * REFERENCE
<code>\overlaybutton {...}</code> * REFERENCE
<code>\overlaycolor</code>
<code>\overlaydepth</code>
<code>\overlayfigure {...}</code> * FILE
<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [...] [...]</code> 1 REFERENCE 2 REFERENCE
<code>\overlaywidth</code>
<code>\overleftarrow {...}</code> * TEXT
<code>\overleftharpoontdown {...}</code> * TEXT

$\overleftarrow{\text{harpoonup}}$ {...} * TEXT
$\overleftrightarrow{\text{harpoonright}}$ {...} * TEXT
\overloaderror
\overparent {...} * TEXT
\overparenttext {...} {...} 1 TEXT 2 TEXT
\overparentunderparent {...} * TEXT
$\overrightarrow{\text{harpoonright}}$ {...} * TEXT
$\overrightarrow{\text{harpoonup}}$ {...} * TEXT
$\overrightarrow{\text{harpoonright}}$ {...} * TEXT
$\overrightarrow{\text{harpoonup}}$ {...} * TEXT
$\overset{1}{\text{set}}$ {...} {...} 1 TEXT 2 TEXT
\overstrike {...} * CONTENT
\overstrikes {...} * CONTENT
\overtwoheadleftarrow {...} * TEXT
\overtwoheadrightarrow {...} * TEXT
\PDFcolor {...} * NAME
\PDFETEX

<code>\PDFTEX</code>
<code>\PICTEX</code>
<code>\PiCTeX</code>
<code>\PointsToBigPoints {¹. .} \². .</code> 1 DIMENSION 2 CSNAME
<code>\PointsToReal {¹. .} \². .</code> 1 DIMENSION 2 CSNAME
<code>\PointsToWholeBigPoints {¹. .} \². .</code> 1 DIMENSION 2 CSNAME
<code>\PPCHTEX</code>
<code>\PPCHTeX</code>
<code>\PRAGMA</code>
<code>\PtToCm {[*]. .}</code> * DIMENSION
<code>\page [...[*],...]</code> * inherits: \pagebreak
<code>\pagearea [¹. .] [². .] [³. .]</code> 1 top header text footer bottom 2 text margin edge 3 left right lefttext <u>middletext</u> righttext
<code>\pagebreak [...[*],...]</code> * NAME
<code>\pagefigure [¹. .] [...,². .,...]</code> 1 FILE 2 inherits: \setupexternalfigure
<code>\pagegridspanwidth {[*]. .}</code> * NUMBER
<code>\pageinjection [¹. .] [...,². .,...]</code> 1 NAME 2 KEY = VALUE

\pageinjection [...,¹...]² [...,²...]

1 inherits: \setuppageinjection
2 KEY = VALUE

\pagenumber

\pagereference [...,*,...]

* REFERENCE

\pagestaterealpage {...¹.} {...².}

1 NAME
2 NAME NUMBER

\paletsize

\paragraphs

\part [...,¹...]² {...}

1 REFERENCE
2 TEXT

\pdfactualtext {...¹.} {...².}

1 CONTENT
2 TEXT

\pdfbackendactualtext {...¹.} {...².}

1 CONTENT
2 TEXT

\pdfbackendcurrentresources

\pdfbackendsetcatalog {...¹.} {...².}

1 NAME
2 TEXT

\pdfbackendsetcolorspace {...¹.} {...².}

1 NAME
2 TEXT

\pdfbackendsettextgstate {...¹.} {...².}

1 NAME
2 TEXT

\pdfbackendsetinfo {...¹.} {...².}

1 NAME
2 TEXT

<p><code>\pdfbackendsetname {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageresource {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpagesattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpattern {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetshade {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfcolor {...}</code></p> <p>* NAME</p>
<p><code>\pdfeTeX</code></p>
<p><code>\pdfTeX</code></p>
<p><code>\percent</code></p>
<p><code>\percentdimen {...} {...}</code></p> <p>1 DIMENSION CSNAME</p> <p>2 DIMENSION NUMBER</p>
<p><code>\periods [...]</code></p> <p>* NUMBER</p>
<p><code>\periods [..., ...*=..., ...]</code></p> <p>* inherits: \setupperiods</p>
<p><code>\permitcaretescape</code></p>
<p><code>\permitcircumflexescape</code></p>
<p><code>\permitspacesbetweengroups</code></p>

<p><code>\persiandecimals {...}</code></p> <p>* NUMBER</p>
<p><code>\persiannumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\phantom {...}</code></p> <p>* CONTENT</p>
<p><code>\phantombox [...,..[*]...,...]</code></p> <p>* width = DIMENSION height = DIMENSION depth = DIMENSION</p>
<p><code>\pickupgroupedcommand {...¹} {...²} {...³}</code></p> <p>1 COMMAND 2 COMMAND 3 COMMAND</p>
<p><code>\placeattachments</code></p>
<p><code>\placebookmarks [...,¹...] [...,²...] [...,³...,...]</code></p> <p>1 SECTION LIST 2 SECTION LIST 3 inherits: \setupbookmark</p>
<p><code>\placebtxrendering [...¹] [...,²...,...]</code></p> <p>1 NAME 2 inherits: \setupbtxrendering</p>
<p><code>\placechemical [...,¹...] [...,²...] {...³} {...⁴}</code></p> <p>1 2 REFERENCE 3 TEXT 4 CONTENT</p>
<p><code>\placecitation [...]</code></p> <p>* REFERENCE</p>
<p><code>\placecombinedlist [...¹] [...,²...,...]</code></p> <p>1 LIST 2 inherits: \setuplist</p>
<p><code>\placecombinedlist [...,[*]...,...]</code></p> <p>* inherits: \setuplist</p>
<p><code>\placecomments</code></p>

<p><code>\placecontent [...,..[*]...]</code></p> <p>* inherits: \setuplist</p>
<p><code>\placecurrentformulanumber</code></p>
<p><code>\placedbox {...}</code></p> <p>* CONTENT</p>
<p><code>\placefigure [...,¹...] [...,²...] {...³} {...⁴}</code></p> <p>1</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\placefloat [...¹] [...,²...] [...,³...] {...⁴} {...⁵}</code></p> <p>1 SINGULAR</p> <p>2</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placefloatwithsetups [...¹] [...,²...] [...,³...] {...⁴} {...⁵}</code></p> <p>1 NAME</p> <p>2</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placefloat [...,¹...] [...,²...] {...³} {...⁴}</code></p> <p>1</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\placefootnotes [...,..[*]...]</code></p> <p>* inherits: \setupnote</p>
<p><code>\placeformula [...,[*]...]</code></p> <p>* + - REFERENCE</p>
<p><code>\placeframed [...¹] [...,..²...] {...³}</code></p> <p>1 NAME</p> <p>2 inherits: \setupframed</p> <p>3 CONTENT</p>

<p><code>\placegraphic [...,¹...] [...,²...] {...} {...}</code></p> <p>1</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\placeheadnumber [...]</code></p> <p>* SECTION</p>
<p><code>\placeheadtext [...]</code></p> <p>* SECTION</p>
<p><code>\placehelp</code></p>
<p><code>\placeindex [...,[*]...]</code></p> <p>* inherits: \setupregister</p>
<p><code>\placeinitial [...]</code></p> <p>* NAME</p>
<p><code>\placeintermezzo [...,¹...] [...,²...] {...} {...}</code></p> <p>1</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\placelayer [...]</code></p> <p>* NAME</p>
<p><code>\placelayeredtext [...,¹...] [...,²...], [...,³...], {...} {...}</code></p> <p>1 NAME</p> <p>2 inherits: \setuplayer</p> <p>3 inherits: \setuplayeredtext</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placelegend [...,¹...] {...} {...}</code></p> <p>1 inherits: \setuppairedbox</p> <p>2 CONTENT</p> <p>3 TEXT</p>
<p><code>\placelist [...,¹...] [...,²...]</code></p> <p>1 LIST</p> <p>2 inherits: \setuplist</p>
<p><code>\placelistofabbreviations [...,[*]...]</code></p> <p>* inherits: \setupsynonyms</p>

<p><code>\placelistofchemicals [...]\symboldot...</code></p> <p>* inherits: \setuplist</p>
<p><code>\placelistoffigures [...]\symboldot...</code></p> <p>* inherits: \setuplist</p>
<p><code>\placelistoffloats [...]\symboldot...</code></p> <p>* inherits: \setuplist</p>
<p><code>\placelistofgraphics [...]\symboldot...</code></p> <p>* inherits: \setuplist</p>
<p><code>\placelistofintermezzi [...]\symboldot...</code></p> <p>* inherits: \setuplist</p>
<p><code>\placelistoflogos [...]\symboldot...</code></p> <p>* inherits: \setupsorting</p>
<p><code>\placelistofpublications [...]\superscript1 [...]\superscript2...</code></p> <p>1 NAME</p> <p>2 inherits: \setupbt rendering</p>
<p><code>\placelistofsorts [...]\superscript1 [...]\superscript2...</code></p> <p>1 SINGULAR</p> <p>2 inherits: \setupsorting</p>
<p><code>\placelistofsorts [...]\symboldot...</code></p> <p>* inherits: \setupsorting</p>
<p><code>\placelistofsynonyms [...]\superscript1 [...]\superscript2...</code></p> <p>1 SINGULAR</p> <p>2 inherits: \setupsynonyms</p>
<p><code>\placelistofsynonyms [...]\symboldot...</code></p> <p>* inherits: \setupsynonyms</p>
<p><code>\placelistoftables [...]\symboldot...</code></p> <p>* inherits: \setuplist</p>
<p><code>\placelocalfootnotes [...]\symboldot...</code></p> <p>* inherits: \setupnote</p>
<p><code>\placelocalnotes [...]\superscript1 [...]\superscript2...</code></p> <p>1 NAME</p> <p>2 inherits: \setupnote</p>

`\placement [...1] [...2...] {...3}`

1 NAME

2 inherits: \setupplacement

3 CONTENT

`\placement [...1...] {...2}`

1 inherits: \setupplacement

2 CONTENT

`\placenamefloat [...1] [...2]`

1 NAME

2 REFERENCE

`\placenameformula [...1...] {...2}`

1 + - REFERENCE

2 TEXT

`\placenotes [...1...] [...2...] {...}`

1 NAME

2 inherits: \setupnote

`\placeongrid [...1] {...2}`

1

2 CONTENT

`\placeongrid [...1...] {...2}`

1 inherits: \definegridsnapping

2 CONTENT

`\placeontopofeachother {...1} {...2}`

1 CONTENT

2 CONTENT

`\placepagenumber`

`\placepairedbox [...1] [...2...] {...3} {...4}`

1 NAME

2 inherits: \setuppairedbox

3 CONTENT

4 TEXT

`\placepairedbox [...1...] {...2} {...3}`

1 inherits: \setuppairedbox

2 CONTENT

3 TEXT

`\placeparallel [...]1 [...,2...] [...,3...,...]`

1 NAME

2 NAME

3 inherits: \setupparallel

`\placerawlist [...]1 [...,2...,...]`

1 LIST

2 inherits: \setuplist

`\placeregister [...]1 [...,2...,...]`

1 NAME

2 inherits: \setupregister

`\placeregister [...]*...,...]`

* inherits: \setupregister

`\placereadingwindow [...]1 [...]2]`

1 NAME

2 NAME

`\placesidebyside {...}1 {...}2`

1 CONTENT

2 CONTENT

`\placesubformula [...]*...`

* + - REFERENCE

`\placetable [...]1 [...]2 {...}3 {...}4`

1

2 REFERENCE

3 TEXT

4 CONTENT

`\popattribute *...`

* CSNAME

`\popmacro *...`

* CSNAME

`\popmode [...]*`

* NAME

`\popsystemmode {...}*`

* NAME

`\position [...,1...,...] (...2,...) {...3}`

1 inherits: \setuppositioning

2 POSITION

3 CONTENT

`\positionoverlay {...}`

* NAME

`\positionregionoverlay {...1} {...2}`

1 NAME

2 NAME

`\postponenotes`

`\predefinedfont [...]`

* FONT

`\predefinefont [...1] [...2]`

1 NAME

2 FONT

`\predefinesymbol [...]`

* NAME

`\prefixedpagenumber`

`\prefixlanguage`

`\prefixtext {...}`

* KEY

`\prependetoks ... \to \2...`

1 COMMAND

2 CSNAME

`\prependgvalue {...1} {...2}`

1 NAME

2 COMMAND

`\prependtocommalist {...1} \2...`

1 TEXT

2 CSNAME

`\prependtoks ... \to \2...`

1 COMMAND

2 CSNAME

`\prependtoksonce 1... \to 2...`

1 COMMAND

2 CSNAME

`\prependvalue {1...} {2...}`

1 NAME

2 COMMAND

`\presetbtxlabeltext [1...] [...,2...,...]`

1 LANGUAGE

2 KEY = VALUE

`\presetdocument [...,*...,...]`

* inherits: \setupdocument

`\presetfieldsymbols [...,*...,...]`

* NAME

`\presetheadtext [1...] [...,2...,...]`

1 LANGUAGE

2 KEY = VALUE

`\presetlabeltext [1...] [...,2...,...]`

1 LANGUAGE

2 KEY = VALUE

`\presetlabeltext [1...] [...,2...,...]`

1 LANGUAGE

2 KEY = VALUE

`\presetmathlabeltext [1...] [...,2...,...]`

1 LANGUAGE

2 KEY = VALUE

`\presetoperatortext [1...] [...,2...,...]`

1 LANGUAGE

2 KEY = VALUE

`\presetprefixtext [1...] [...,2...,...]`

1 LANGUAGE

2 KEY = VALUE

`\presettaglabeltext [1...] [...,2...,...]`

1 LANGUAGE

2 KEY = VALUE

<pre>\presetunittext [...]¹ [...,...²...,...]</pre> <pre>1 LANGUAGE</pre> <pre>2 KEY = VALUE</pre>
<pre>\pretocommalist {...}¹ \...²</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\prevcounter [...]¹ [...]²</pre> <pre>1 NAME</pre> <pre>2 NUMBER</pre>
<pre>\prevcountervalue [...][*]</pre> <pre>* NAME</pre>
<pre>\preventmode [...][*],...]</pre> <pre>* NAME</pre>
<pre>\prevrealpage</pre>
<pre>\prevrealpagenumber</pre>
<pre>\prevsubcountervalue [...]¹ [...]²</pre> <pre>1 NAME</pre> <pre>2 NUMBER</pre>
<pre>\prevsubpage</pre>
<pre>\prevsubpagenumber</pre>
<pre>\prevuserpage</pre>
<pre>\prevuserpagenumber</pre>
<pre>\procent</pre>
<pre>\processaction [...]¹ [...,...²>...,...]</pre> <pre>1 COMMAND</pre> <pre>2 APPLY</pre>
<pre>\processallactionsinset [...]¹ [...,...²>...,...]</pre> <pre>1 COMMAND</pre> <pre>2 APPLY</pre>
<pre>\processassignlist [...]¹,... \...²</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>

`\processassignmentcommand [...,1...,...] \2...`

1 KEY = VALUE

2 CSNAME

`\processassignmentlist [...,1...,...] \2...`

1 KEY = VALUE

2 CSNAME

`\processbetween {1...} \2...`

1 NAME

2 CSNAME

`\processblocks [...,1...] [...,2...] [...,3...,...]`

1 NAME

2 + -

3 criterium = text SECTION

`\processbodyfontenvironmentlist *`

* CSNAME

`\processcolorcomponents {*...}`

* COLOR

`\processcommacommand [...,1...] \2...`

1 COMMAND

2 CSNAME

`\processcommalist [...,1...] \2...`

1 COMMAND

2 CSNAME

`\processcommalistwithparameters [...,1...] \2...`

1 COMMAND

2 CSNAME

`\processcontent {1...} \2...`

1 NAME

2 CSNAME

`\processfile {*...}`

* FILE

`\processfilemany {*...}`

* FILE

`\processfilenone {*...}`

* FILE

<pre>\processfileonce {...}</pre> <pre>* FILE</pre>
<pre>\processfirstactioninset [...]¹ [...,...=>...,...]</pre> <pre>1 COMMAND</pre> <pre>2 APPLY</pre>
<pre>\processisolatedchars {...}¹ \...²</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\processisolatedwords {...}¹ \...²</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\processlinetablebuffer [...][*]</pre> <pre>* BUFFER</pre>
<pre>\processlinetablefile {...}[*]</pre> <pre>* FILE</pre>
<pre>\processlist {...}¹ {...}² {...}³ \...⁴</pre> <pre>1 CHARACTER</pre> <pre>2 CHARACTER</pre> <pre>3 TEXT</pre> <pre>4 CSNAME</pre>
<pre>\processMPbuffer [...,][*]...</pre> <pre>* NAME</pre>
<pre>\processMPfigurefile {...}[*]</pre> <pre>* FILE</pre>
<pre>\processmonth {...}¹ {...}² {...}³</pre> <pre>1 NUMBER</pre> <pre>2 NUMBER</pre> <pre>3 COMMAND</pre>
<pre>\processranges [...,]¹... \...²</pre> <pre>1 NUMBER NUMBER:NUMBER</pre> <pre>2 CSNAME</pre>
<pre>\processseparatedlist [...]¹ [...]² {...}³</pre> <pre>1 TEXT</pre> <pre>2 TEXT</pre> <pre>3 CSNAME COMMAND</pre>

`\processTEXbuffer [...]`

* BUFFER

`\processtokens {1.} {2.} {3.} {4.} {5.}`

1 COMMAND

2 COMMAND

3 COMMAND

4 COMMAND

5 TEXT

`\processuntil \...`

* CSNAME

`\processxtablebuffer [...]`

* NAME

`\processyear {1.} {2.} {3.} {4.}`

1 NUMBER

2 COMMAND

3 COMMAND

4 COMMAND

`\product [...]`

* FILE

`\product ...`

* FILE

`\profiledbox [...] [...2...2...] {3.}`

1 none fixed strict halfixed quarterfixed eightsfixed NAME

2 inherits: \setupprofile

3 CONTENT

`\profilegivenbox {1.} 2.`

1 none fixed strict halfixed quarterfixed eightsfixed NAME

2 CSNAME NUMBER

`\program [...]`

* NAME

`\project [...]`

* FILE

`\project ...`

* FILE

<p><code>\pseudoMixedCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudosmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\psh [...]¹ ...² \\</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\purenumber {...}</code></p> <p>* NUMBER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute *...</code></p> <p>* CSNAME</p>
<p><code>\pushbackground [...][*] ... \popbackground</code></p> <p>* NAME</p>
<p><code>\pushbar [...][*] ... \popbar</code></p> <p>* NAME</p>
<p><code>\pushbutton [...]¹ [...]²</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushcolor [...][*] ... \popcolor</code></p> <p>* COLOR</p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro *...</code></p> <p>* CSNAME</p>

<code>\pushmathstyle ... \popmathstyle</code>
<code>\pushmode [...]</code> * NAME
<code>\pushoutputstream [...]</code> * NAME
<code>\pushpath [...] ... \poppath</code> * FILE
<code>\pushpunctuation ... \poppunctuation</code>
<code>\pushrandomseed ... \poprandomseed</code>
<code>\pushreferenceprefix {...} ... \popreferenceprefix</code> *
<code>\pushsystemmode {...}</code> * NAME
<code>\qqquad</code>
<code>\quad</code>
<code>\quads [...]</code> * NUMBER
<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\quotation {...}</code> * CONTENT
<code>\quote {...}</code> * CONTENT
<code>\ReadFile {...}</code> * FILE
<code>\Romannumerals {...}</code> * NUMBER
<code>\raggedbottom</code>
<code>\raggedcenter</code>

<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {¹.} \². {³.}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\randomizetext {[*].}</code> * TEXT
<code>\randomnumber {¹.} {².}</code> 1 NUMBER 2 NUMBER
<code>\ran {[*].}</code> * TEXT
<code>\rawcounter [¹.] [².]</code> 1 NAME 2 NUMBER
<code>\rawcountervalue [[*].]</code> * NAME
<code>\rawdate [...,[*]...]</code> * inherits: \currentdate
<code>\rawdoifelseinset {¹.} {².} {³.}</code> 1 CONTENT 2 TRUE 3 FALSE
<code>\rawdoifinset {¹.} {².}</code> 1 CONTENT 2 TRUE
<code>\rawdoifinsetelse {¹.} {².} {³.}</code> 1 CONTENT 2 TRUE 3 FALSE
<code>\rawgetparameters [¹.] [...,²...,...]</code> 1 TEXT 2 KEY = VALUE

`\rawprocessaction [...]1 [...,...=>...,...]`

- 1 COMMAND
- 2 APPLY

`\rawprocesscommaccommand [...,1...] \...2`

- 1 COMMAND
- 2 CSNAME

`\rawprocesscommalist [...,1...] \...2`

- 1 COMMAND
- 2 CSNAME

`\rawstructurelistuservariable {...}`

- * KEY

`\rawsubcountervalue [...]1 [...]2`

- 1 NAME
- 2 NUMBER

`\raw [...]1 ... \\2`

- 1 REFERENCE
- 2 TEXT

`\rbox ... {...}1 {...}2`

- 1 TEXT
- 2 CONTENT

`\readfile {...}1 {...}2 {...}3`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readfixfile {...}1 {...}2 {...}3 {...}4`

- 1 FILE
- 2 FILE
- 3 TRUE
- 4 FALSE

`\readjobfile {...}1 {...}2 {...}3`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readlocfile {...}1 {...}2 {...}3`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readsetfile {1..} {2..} {3..} {4..}`

- 1 FILE
- 2 FILE
- 3 TRUE
- 4 FALSE

`\readsysfile {1..} {2..} {3..}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readtexfile {1..} {2..} {3..}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\readxmlfile {1..} {2..} {3..}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\realpagenumber`

`\realSmallCapped {*..}`

- * TEXT

`\realSmallcapped {*..}`

- * TEXT

`\realsmallcapped {*..}`

- * TEXT

`\recursedepth`

`\recurselevel`

`\recursestring`

`\redoconvertfont`

`\ref [1..] [2..]`

- 1
- 2 REFERENCE

`\reference [...,1...] {2..}`

- 1 REFERENCE
- 2 TEXT

`\referenceformat {...} {...} [...]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\referenceprefix`

`\referring (...1,...) (...2,...) [...3]`

- 1 POSITION
- 2 POSITION
- 3 REFERENCE

`\registerattachment [...]1 [...,...2...,...]`

- 1 NAME
- 2 inherits: \setupattachment

`\registerctxluafile {...}1 {...}2`

- 1 FILE
- 2 NUMBER

`\registerexternalfigure [...]1 [...]2 [...,...3...,...]`

- 1 FILE
- 2 NAME
- 3 inherits: \setuexternalfigure

`\registerfontclass {...}*`

- * NAME

`\registerhyphenationexception [...]1 [...]2`

- 1 LANGUAGE
- 2 TEXT

`\registerhyphenationpattern [...]1 [...]2`

- 1 LANGUAGE
- 2 TEXT

`\registermenubuttons [...]1 [...]2`

- 1 NAME
- 2 TEXT

`\registersort [...]1 [...]2`

- 1 SINGULAR
- 2 NAME

`\registersynonym [...]1 [...]2`

- 1 SINGULAR
- 2 NAME

\registerunit [¹...] [²...₌...]

1 prefix **unit** operator suffixe symbol packaged
2 KEY = VALUE

\register [¹...] [²...+...+...]

1 TEXT PROCESSOR->TEXT
2 INDEX

\register [¹...] {²...} [³...+...+...]

1 TEXT PROCESSOR->TEXT
2 TEXT
3 INDEX

\regular

\relatemarking [¹...] [²...]

1 MARK
2 MARK

\relateparameterhandlers {¹...} {²...} {³...} {⁴...}

1 NAME
2 NAME
3 NAME
4 NAME

\relaxvalueifundefined {^{*}...}

* NAME

\remainingcharacters

\remark (...¹,...) (...²,...) [...³...₌...]⁴ {...}

1 POSITION
2 POSITION
3 inherits: \setupframed
4 TEXT

\removebottomthings

\removedepth

\removefromcommalist {¹...} \²...

1 TEXT
2 CSNAME

\removelastskip

\removelastspace

\removemarkedcontent [...] * NAME
\removepunctuation
\removesubstring . ¹ . \from . ² . \to \ ³ . 1 TEXT 2 TEXT 3 CSNAME
\removetoks . ¹ . \from \ ² . 1 COMMAND 2 CSNAME
\removeunwantedspaces
\replacefeature [...] * NAME
\replacefeature {...} * NAME
\replaceincommalist \ ¹ . {...} 1 CSNAME 2 NUMBER
\replaceword [...] ¹ [...] ² [...] ³ 1 NAME 2 TEXT 3 TEXT
\rescan {...} * CONTENT
\rescanwithsetup {...} ¹ {...} ² 1 NAME 2 CONTENT
\resetallattributes
\resetandaddfeature [...] * NAME
\resetandaddfeature {...} * NAME
\resetbar

<code>\resetbreakpoints</code>
<code>\resetbuffer [...]</code> * BUFFER
<code>\resetcharacteralign</code>
<code>\resetcharacterkerning</code>
<code>\resetcharacterspacing</code>
<code>\resetcharacterstripping</code>
<code>\resetcollector [...]</code> * NAME
<code>\resetcounter [...]¹ [...]²</code> 1 NAME 2 NUMBER
<code>\resetdigitsmanipulation</code>
<code>\resetdirection</code>
<code>\resetfeature</code>
<code>\resetflag {...}</code> * NAME
<code>\resetfontcolorsheme</code>
<code>\resetfontfallback [...]¹ [...]²</code> 1 NAME 2 FONT
<code>\resetfontsolution</code>
<code>\resethyphenationfeatures</code>
<code>\resetinjector [...]</code> * NAME
<code>\resetinteractionmenu [...]</code> * NAME
<code>\resetitaliccorrection</code>
<code>\resetlayer [...]</code> * NAME

<code>\resetlocalfloats</code>
<code>\resetMPdrawing</code>
<code>\resetMPenvironment</code>
<code>\resetMPinstance [...]</code> * NAME
<code>\resetmarker [...]</code> * NAME
<code>\resetmarking [...]</code> * MARK
<code>\resetmode {...}</code> * NAME
<code>\resetpagenumber</code>
<code>\resetparallel [...]¹ [...]²,...]</code> 1 NAME 2 NAME <u>all</u>
<code>\resetpath</code>
<code>\resetpenalties \...</code> * CSNAME
<code>\resetprofile</code>
<code>\resetreference [...]</code> * NAME
<code>\resetreplacement</code>
<code>\resetscript</code>
<code>\resetsetups [...]</code> * NAME
<code>\resetshownsynonyms [...]</code> * SINGULAR
<code>\resetsubpagenumber</code>
<code>\resetsymbolset</code>

\resetsystemmode {...} * NAME
\resettimer
\resettrackers
\resettrialtypesetting
\resetusedsortings [...] * SINGULAR
\resetusedsynonyms [...] * SINGULAR
\resetuserpagenumber
\resetvalue {...} * NAME
\resetvisualizers
\reshapebox {...} * COMMAND
\restartcounter [... ¹] [... ²] [... ³] 1 NAME 2 NUMBER 3 NUMBER
\restorebox {... ¹ } {... ² } 1 NAME 2 NAME
\restorecatcodes
\restorecounter [...] * NAME
\restorecurrentattributes {...} * NAME
\restoreendofline
\restoreglobalbodyfont
\reusableMPgraphic {... ¹ } {..., ² ...} 1 NAME 2 KEY = VALUE

\backslash reuseMPgraphic {...} {..., ² ...,...} 1 NAME 2 KEY = VALUE
\backslash reuserandomseed
\backslash revivefeature
\backslash rfence {...} * CHARACTER
\backslash rhbox {...} * CONTENT
\backslash right ... * CHARACTER
\backslash rightaligned {...} * CONTENT
\backslash rightbottombox {...} * CONTENT
\backslash rightbox {...} * CONTENT
\backslash right hbox {...} * CONTENT
\backslash rightheadtext {...} * KEY
\backslash rightlabeltext {...} * KEY
\backslash rightlabeltext {...} * KEY
\backslash rightline {...} * CONTENT
\backslash rightmathlabeltext {...} * KEY
\backslash rightorleftpageaction {...} {...} 1 COMMAND 2 COMMAND

<code>\rightskipadaption</code>
<code>\rightsubguillemot</code>
<code>\righttopleft</code>
<code>\righttopleftthbox .¹. {..².}</code> 1 TEXT 2 CONTENT
<code>\righttopleftvbox .¹. {..².}</code> 1 TEXT 2 CONTENT
<code>\righttopleftvtop .¹. {..².}</code> 1 TEXT 2 CONTENT
<code>\righttopbox {...}</code> * CONTENT
<code>\rlap {...}</code> * CONTENT
<code>\robustaddtocommalist {...} \..².</code> 1 TEXT 2 CSNAME
<code>\robustdoifelseinset {...} {...}</code> 1 TRUE 2 FALSE
<code>\robustdoifinsetelse {...} {...}</code> 1 TRUE 2 FALSE
<code>\robustpretocommalist {...} \..².</code> 1 TEXT 2 CSNAME
<code>\rob [...¹] .². \\\</code> 1 REFERENCE 2 TEXT

`\rollbutton [...]1 [...,...2...,...] ...3 [...]4`

- 1 NAME
- 2 inherits: \setupinteractionmenu
- 3 TEXT
- 4 REFERENCE

`\rollbutton [...,...1...,...] ...2 [...]3`

- 1 inherits: \setupbutton
- 2 TEXT
- 3 REFERENCE

`\roman`

`\romannumerals {...}`

- * NUMBER

`\rotate [...,...1...,...] {...}2`

- 1 inherits: \setuprotate
- 2 CONTENT

`\rtop ...1 {...}2`

- 1 TEXT
- 2 CONTENT

`\ruledhbox ...1 {...}2`

- 1 TEXT
- 2 CONTENT

`\ruledhpack ...1 {...}2`

- 1 TEXT
- 2 CONTENT

`\ruledmbox {...}`

- * CONTENT

`\ruledtopv ...1 {...}2`

- 1 TEXT
- 2 CONTENT

`\ruledtpack ...1 {...}2`

- 1 TEXT
- 2 CONTENT

`\ruledvbox ...1 {...}2`

- 1 TEXT
- 2 CONTENT

<code>\ruledvpack ¹ {²}</code> 1 TEXT 2 CONTENT
<code>\ruledvtop ¹ {²}</code> 1 TEXT 2 CONTENT
<code>\rul [*] \\\</code> * TEXT
<code>\runMPbuffer [...[*]...]</code> * NAME
<code>\ScaledPointsToBigPoints {¹} \²..</code> 1 DIMENSION 2 CSNAME
<code>\ScaledPointsToWholeBigPoints {¹} \²..</code> 1 DIMENSION 2 CSNAME
<code>\SmallCapped {[*]}</code> * TEXT
<code>\Smallcapped {[*]}</code> * TEXT
<code>\safechar {[*]}</code> * NUMBER
<code>\sans</code>
<code>\sansbold</code>
<code>\sansnormal</code>
<code>\sansserif</code>
<code>\savebox {¹} {²} {³}</code> 1 NAME 2 NAME 3 CONTENT

\savebtxdataset [...¹] [...²] [...,³...,...]

1 NAME

2 FILE

3 dataset = NAME

type = bib lua xml

file = FILE

criterion = all text intro reference current here previous local component SECTIONBLOCK:all SECTIONBLOCK:reference
SECTIONBLOCK:current SECTIONBLOCK:previous

\savebuffer [...¹,...] [...²]

1 BUFFER

2 FILE

\savebuffer [...,^{*}...,...]

* list = NAME

file = FILE

prefix = yes no

\savecolor ... \restorecolor

\savecounter [...]

* NAME

\savecurrentattributes {...}

* NAME

\savenormalmeaning *...

* CSNAME

\savetaggedtwopassdata {...¹} {...²} {...³} {...⁴}

1 NAME

2 NUMBER

3 NAME

4 CONTENT

\savetwopassdata {...¹} {...²} {...³}

1 NAME

2 NUMBER

3 CONTENT

\sbox {...}

* CONTENT

\scale [...¹] [...,²...,...] {...³}

1 NAME

2 inherits: \setupscale

3 CONTENT

\screen [...,^{*}...]

* inherits: \page

`\script`

`\secondoffivearguments {1...} {2...} {3...} {4...} {5...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\secondoffourarguments {1...} {2...} {3...} {4...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\secondofsixarguments {1...} {2...} {3...} {4...} {5...} {6...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\secondofthreearguments {1...} {2...} {3...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\secondofthreeunexpanded {1...} {2...} {3...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\secondoftwoarguments {1...} {2...}`

- 1 TEXT
- 2 TEXT

`\secondoftwounexpanded {1...} {2...}`

- 1 TEXT
- 2 TEXT

`\section [...,1...] {2...}`

- 1 REFERENCE
- 2 TEXT

`\section [...1,...] {...2}`

1 REFERENCE

2 TEXT

`\section [...1,...] {...2} {...3}`

1 REFERENCE

2 NUMBER

3 TEXT

`\section [...,*...,...]`

* title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
reference = REFERENCE
ownnumber = TEXT

`\seeindex [...1] [...+...2+...] {...3}`

1 TEXT PROCESSOR->TEXT

2 INDEX

3 TEXT PROCESSOR->TEXT

`\seeregister [...1] [...+...2+...] {...3}`

1 TEXT PROCESSOR->TEXT

2 INDEX

3 TEXT PROCESSOR->TEXT

`\select {...1} {...2} {...3} {...4} {...5} {...6}`

1 NAME

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

`\selectblocks [...1,...] [...2,...] [...,3...,...]`

1 NAME

2 + -

3 criterium = text SECTION

`\serializecommalist [...,*...,...]`

* COMMAND

`\serializedcommalist`

`\serif`

`\serifbold`

`\serifnormal`

\setbar [...] * NAME
\setbigbodyfont
\setboxllx ¹ ... { ² ...} 1 CSNAME NUMBER 2 DIMENSION
\setboxlly ¹ ... { ² ...} 1 CSNAME NUMBER 2 DIMENSION
\setbreakpoints [...] * reset NAME
\setbuffer [...] ... \endbuffer * NAME
\setcapstrut
\setcatcodetable *... * CSNAME
\setcharacteralign {...} {...} 1 NUMBER 2 TEXT number->TEXT text->TEXT
\setcharactercasing [...] * reset WORD word Word Words capital Capital none random mixed camel cap Cap
\setcharactercleaning [...] * reset 1
\setcharacterkerning [...] * reset NAME
\setcharacterspacing [...] * reset NAME
\setcharacterstripping [...] * reset 1
\setcharstrut {...} * TEXT

`\setcollector [...]1 [...,...2...] {...}3`

1 NAME

2 inherits: \setupcollector

3 CONTENT

`\setcolormodel [...]`

* black bw gray rgb cmyk all none

`\setcounter [...]1 [...]2 [...]3`

1 NAME

2 NUMBER

3 NUMBER

`\setcounterown [...]1 [...]2 [...]3`

1 NAME

2 NUMBER

3 TEXT

`\setcurrentfontclass {...}*`

* NAME

`\setdataset [...]1 [...]2 [...,...3...] [...]`

1 NAME

2 NAME

3 KEY = VALUE

`\setdefaultpenalties`

`\setdigitsmanipulation [...]*`

* reset NUMBER

`\setdirection [...]*`

* NUMBER

`\setdocumentargument {...}1 {...}2`

1 NAME

2 TEXT

`\setdocumentargumentdefault {...}1 {...}2`

1 NAME

2 TEXT

`\setdocumentfilename {...}1 {...}2`

1 NUMBER

2 TEXT

`\setdummyparameter {...} {...}`

- 1 KEY
- 2 COMMAND

`\setelementexporttag [...] [...] [...]`

- 1 NAME
- 2 `export` nature pdf
- 3 inline display mixed

`\setemeasure {...} {...}`

- 1 NAME
- 2 DIMENSION

`\setevalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setevariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setevariables [...] [...,...2...,...]`

- 1 NAME
- 2 `set` = COMMAND
`reset` = COMMAND
`KEY` = VALUE

`\setfirstline [...]`

- * NAME

`\setflag {...}`

- * NAME

`\setfont ...`

- * FONT

`\setfontcolorsheme [...]`

- * NAME

`\setfontfeature {...}`

- * NAME

`\setfontsolution [...]`

- * NAME

`\setfontstrut`

`\setgmeasure {...} {...}`

- 1 NAME
- 2 DIMENSION

`\setgvalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setgvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setgvariables [...] [...2...]`

- 1 NAME
- 2 set = COMMAND
reset = COMMAND
KEY = VALUE

`\sethyphenatedurlafter {...}`

- * TEXT

`\sethyphenatedurlbefore {...}`

- * TEXT

`\sethyphenatedurlnormal {...}`

- * TEXT

`\sethyphenationfeatures [...,*...]`

- * NAME reset

`\setinitial [...] [...2...]`

- 1 NAME
- 2 inherits: \setupinitial

`\setinjector [...] [...2,...] [...3]`

- 1 NAME
- 2 NUMBER
- 3 COMMAND

`\setinteraction [...]`

- * hidden NAME

`\setinterfacecommand {...} {...}`

- 1 NAME
- 2 NAME

`\setinterfaceconstant {...} {...}`

1 NAME

2 NAME

`\setinterfaceelements {...} {...}`

1 NAME

2 NAME

`\setinterfacemessage {...} {...} {...}`

1 NAME

2 title NAME NUMBER

3 TEXT

`\setinterfacevariable {...} {...}`

1 NAME

2 NAME

`\setinternalrendering [...] [...] {...}`

1 NAME

2 auto embed

3 CONTENT

`\setitaliccorrection [...]`

* reset 1 2

`\setJSpreamble {...} {...}`

1 NAME

2 CONTENT

`\setlayer [...] [...] [...,..3...,...] {...4}`

1 NAME

2 left right even odd

3 inherits: \setuplayer

4 CONTENT

`\setlayerframed [...] [...,..2...,...] [...,..3...,...] {...4}`

1 NAME

2 inherits: \setuplayer

3 inherits: \setupframed

4 CONTENT

`\setlayerframed [...] [...,..2...,...] {...3}`

1 NAME

2 inherits: \setuplayerinherits: \setupframed

3 CONTENT

\setlayertext [¹...] [²...] [³...] {⁴...}

1 NAME
2 inherits: \setupplayer
3 align = inherits: \setupalign
width = DIMENSION
style =
color = COLOR
4 TEXT

\setlocalhsize [...]

* [-+]DIMENSION

\setMPlayer [¹...] [²...] [³...] {⁴...}

1 NAME
2 NAME
3 inherits: \setupplayer
4 CONTENT

\setMPpositiongraphic {¹...} {²...} {³...}

1 NAME
2 NAME
3 KEY = VALUE

\setMPpositiongraphicrange {¹...} {²...} {³...} {⁴...}

1 NAME
2 NAME
3 NAME
4 KEY = VALUE

\setMPtext {¹...} {²...}

1 NAME
2 TEXT

\setMPvariable [¹...] [²...]

1 NAME
2 KEY = VALUE

\setMPvariables [¹...] [²...]

1 NAME
2 KEY = VALUE

\setmainbodyfont

\setmainparbuilder [...]

* default oneline basic NAME

\setmarker [¹...] [²...]

1 NAME
2 NUMBER

`\setmarking [...]1 {...}2`

1 MARK

2 TEXT

`\setmathstyle {...,*,...}`

* NAME

`\setmeasure {...}1 {...}2`

1 NAME

2 DIMENSION

`\setmessagetext {...}1 {...}2`

1 NAME

2 NAME NUMBER

`\setmode {...}`

* NAME

`\setnostrut`

`\setnotetext [...]1 [...,2...] {...}3`

1 NAME

2 REFERENCE

3 TEXT

`\setnotetext [...]1 [...,2...,...]`

1 NAME

2 title = TEXT
bookmark = TEXT
list = TEXT
reference = REFERENCE

`\setnote [...]1 [...,2...] {...}3`

1 NAME

2 REFERENCE

3 TEXT

`\setnote [...]1 [...,2...,...]`

1 NAME

2 title = TEXT
bookmark = TEXT
list = TEXT
reference = REFERENCE

`\setobject {...}1 {...}2 \... {...}3 {...}4`

1 NAME

2 NAME

3 CSNAME

4 CONTENT

\setoldstyle	
\setpagegrid [... ¹ ...] { ² .} 1 c = NUMBER r = NUMBER option = <u>none</u> 2 CONTENT	
\setpagereference { ¹ .} { ² ...,...} 1 NAME 2 REFERENCE	
\setpagestate [¹ .] [² .] 1 NAME 2 NAME NUMBER	
\setpagestaterealpageno { ¹ .} { ² .} 1 NAME 2 NAME NUMBER	
\setpenalties \ ¹ . { ² .} { ³ .} 1 CSNAME 2 NUMBER 3 NUMBER	
\setpercentdimen { ¹ .} { ² .} 1 DIMENSION CSNAME 2 DIMENSION NUMBER	
\setposition { [*] .} * NAME	
\setpositionbox { ¹ .} \ ² . { ³ .} 1 NAME 2 CSNAME 3 CONTENT	
\setpositiondata { ¹ .} { ² .} { ³ .} { ⁴ .} 1 NAME 2 DIMENSION 3 DIMENSION 4 DIMENSION	

\setpositiondataplus {...¹} {...²} {...³} {...⁴} {...,⁵...}

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION
- 4 DIMENSION
- 5 TEXT

\setpositiononly {...}

- * NAME

\setpositionplus {...¹} {...,²...} \...³ {...⁴}

- 1 NAME
- 2 TEXT
- 3 CSNAME
- 4 CONTENT

\setpositionstrut {...}

- * NAME

\setprofile [...]

- * none fixed strict halffixed quarterfixed eightsfixed NAME

\setrandomseed {...}

- * NUMBER

\setreference [...,¹...] [...,²...,...]

- 1 REFERENCE
- 2 KEY = VALUE

\setreferencedobject {...¹} {...²} \...³ {...⁴}

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

\setregisterentry [...¹] [...,²...,...]³ [...,³...,...]

- 1 NAME
- 2 label = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
keys:1 = TEXT
keys:2 = TEXT
keys:3 = TEXT
entries:1 = TEXT
entries:2 = TEXT
entries:3 = TEXT
alternative = TEXT
- 3 KEY = VALUE

\setreplacement [...]

- * reset NAME

<pre> \setrigidcolumnbalance ... * CSNAME NUMBER </pre>
<pre> \setrigidcolumnhsize {...} {...} {...} 1 DIMENSION 2 DIMENSION 3 NUMBER </pre>
<pre> \setscript [...] * hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \setsectionblock [...] [..., ...²..., ...] 1 NAME 2 bookmark = TEXT </pre>
<pre> \setsimplecolumnhsize [..., ...[*]..., ...] * n = NUMBER width = DIMENSION distance = DIMENSION lines = NUMBER </pre>
<pre> \setsmallbodyfont </pre>
<pre> \setsmallcaps </pre>
<pre> \setstackbox {...} {...²} {...³} 1 NAME 2 NAME 3 CONTENT </pre>
<pre> \setstructurepageregister [...] [..., ...²..., ...] [..., ...³..., ...] 1 NAME 2 label = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternative = TEXT 3 KEY = VALUE </pre>
<pre> \setstrut </pre>
<pre> \setsuperiors </pre>
<pre> \setsystemmode {...} * NAME </pre>
<pre> \settabular </pre>

`\settaggedmetadata [...,*...]`

* KEY = VALUE

`\settextcontent [...] [...] [...] [...] [...]`

1 top header text footer bottom
2 text margin edge
3 left middle right
4 date pagenumber MARK TEXT COMMAND
5 date pagenumber MARK TEXT COMMAND

`\settightobject {...} {...} \... {...}`

1 NAME
2 NAME
3 CSNAME
4 CONTENT

`\settightreferencedobject {...} {...} \... {...}`

1 NAME
2 NAME
3 CSNAME
4 CONTENT

`\settightunreferencedobject {...} {...} \... {...}`

1 NAME
2 NAME
3 CSNAME
4 CONTENT

`\settrialtypesetting`

`\setuevalue {...} {...}`

1 NAME
2 CONTENT

`\setugvalue {...} {...}`

1 NAME
2 CONTENT

`\setunreferencedobject {...} {...} \... {...}`

1 NAME
2 NAME
3 CSNAME
4 CONTENT

`\setupalign [...,*...]`

* broad wide bottom height line high low lohi flushright flushleft middle yes no width normal reset inner outer
flushinner flushouter left right center disable last end paragraph lefttoright righttoleft l2r r2l table lessshyphenation
morehyphenation hanging nothanging hz fullhz nohz hyphenated nothyphenated tolerant verytolerant stretch extremestretch
final 2*final 3*final 4*final

`\setuparranging [...,*...]`

* disable mirrored doublesided negative 90 180 270 reset background normal 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP 2UP
2DOWN 2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW
1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME

`\setupattachment [...,1...] [...,2...]`

1 NAME

2 title = TEXT
 subtitle = TEXT
 author = TEXT
 file = FILE
 name = NAME
 buffer = BUFFER
 state = start stop
 method = normal hidden
 symbol = Graph Paperclip Pushpin Default
 width = fit DIMENSION
 height = fit DIMENSION
 depth = fit DIMENSION
 color = COLOR
 textlayer = NAME
 location = leftedge rightedge inmargin leftmargin rightmargin text high none
 distance = DIMENSION

`\setupbackend [...,*...]`

* export = yes FILE
 xhtml = FILE
 file = FILE
 intent = NAME
 space = yes no
 xmpfile = FILE
 format = version default NAME
 level = NUMBER
 option = always never
 profile = FILE

`\setupbackground [...,1...] [...,2...]`

1 NAME

2 state = start stop
 leftoffset = DIMENSION
 rightoffset = DIMENSION
 topoffset = DIMENSION
 bottomoffset = DIMENSION
 before = COMMAND
 after = COMMAND
 inherits: \setupframed

`\setupbackgrounds [...,1...] [...,2...] [...,3...]`

1 top header text footer bottom

2 leftedge leftmargin text rightmargin rightedge

3 inherits: \setupframed

`\setupbackgrounds [...,1...] [...,2...]`

1 paper page leftpage rightpage text hidden

2 state = start stop
 inherits: \setupframed

`\setupbar [...1,...] [...2,...]`

1 NAME

2 color = COLOR
continue = yes no all
empty = yes no
unit = ex em pt in cm mm sp bp pc dd cc nc
order = foreground background
rulethickness = DIMENSION
method = NUMBER
offset = NUMBER
dy = NUMBER
max = NUMBER
foregroundstyle =
foregroundcolor = COLOR
mp = NAME
left = TEXT
right = TEXT

`\setupblackrules [...*,...]`

* width = max DIMENSION
height = max DIMENSION
depth = max DIMENSION
distance = DIMENSION
n = NUMBER
alternative = a b
style =
color = COLOR
type = mp yes no
mp = NAME

`\setupblank [...*,...]`

* inherits: \vspacing

`\setupbleeding [...*,...]`

* width = DIMENSION
height = DIMENSION
offset = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
location = t b l r bl lb br rb tl lt tr rt
stretch = yes no
page = yes no

`\setupblock [...1,...] [...2,...]`

1 NAME

2 before = COMMAND
after = COMMAND
inner = COMMAND
style =
color = COLOR

`\setupbodyfont [...*,...]`

* DIMENSION NAME global reset x xx small big script scriptscript rm ss tt hw cg roman serif regular sans sansserif support type teletype mono handwritten calligraphic

`\setupbookmark [...*,...]`

* force = yes no
number = yes no
numberseparatorset = NAME
numberconversionset = NAME
numberstarter = COMMAND
numberstopper = COMMAND
numbersegments =
sectionblock = yes no

```
\setupbottom [...]1 [...]2...
```

- 1 text margin edge
- 2 inherits: \setuplayoutelement

```
\setupbottomtexts [...]1 [...]2 [...]3 [...]4 [...]5
```

- 1 text margin edge
- 2 date pagenumber MARK TEXT COMMAND
- 3 date pagenumber MARK TEXT COMMAND
- 4 date pagenumber MARK TEXT COMMAND
- 5 date pagenumber MARK TEXT COMMAND

```
\setupbtxdataset [...]1 [...]2...
```

- 1 NAME
- 2 language = LANGUAGE

```
\setupbtxlabeltext [...]1 [...]2...
```

- 1 LANGUAGE
- 2 KEY = VALUE

```
\setupbtxlist [...]1 [...]2...
```

- 1 NAME
- 2 inherits: \setuplist

```
\setupbtxregister [...]1 [...]2...
```

- 1 NAME
- 2 state = start stop
- dataset = NAME
- field = keyword range pagenumber author
- register = NAME
- method = once
- alternative = normalshort invertedshort
- style =
- color = COLOR

```
\setupbtxrendering [...]1 [...]2...
```

- 1 NAME
- 2 textstate = start stop
- pagestate = start stop
- separator = COMMAND
- criterion = previous cite here all none
- specification = NAME
- title = TEXT
- before = COMMAND
- after = COMMAND
- dataset = NAME
- method = dataset force local global none
- sorttype = short dataset list reference used default cite index
- repeat = yes no
- group = NAME
- numbering = yes no num index tag short page

`\setupbtx [...]1 [...,...2...,...]`

```
1 NAME

2 specification = default apa aps NAME
  dataset      = default NAME
  command      = CD:ONEARGUMENT
  left         = COMMAND
  right        = COMMAND
  authorconversion = normal normalshort normalinverted invertedshort short
  etallimit    = NUMBER
  etaldisplay   = NUMBER
  etaloption    = last
  stopper      = initials
  interaction   = start stop all
  alternative   =
  sorttype     = normal reverse
  compress     = yes no
  default      = default NAME
  style        =
  color        = COLOR
```

`\setupbtx [...]`

`* NAME`

`\setupbuffer [...]1,... [...,...2...,...]`

```
1 BUFFER

2 before = COMMAND
  after  = COMMAND
```

`\setupbutton [...]1,... [...,...2...,...]`

```
1 NAME

2 state      = start stop
  samepage   = yes no empty none normal default
  style      =
  color      = COLOR
  contrastcolor = COLOR
  alternative = hidden
  inherits: \setupframed
```

`\setupcapitals [...]1,... [...,...2...,...]`

```
1 NAME

2 title = yes no
  sc    = yes no
  style =
```

`\setupcaption [...]1,... [...,...2...,...]`

```
1 NAME

2 inherits: \setupfloatcaption
```

`\setupcharacterkerning [...]1,... [...,...2...,...]`

```
1 NAME

2 factor = max NUMBER
  width  = DIMENSION
  features = NAME
  style  =
  color  = COLOR
```

`\setupcharacterspacing [...1.] [...2.] [...,3...]`

```
1 NAME
2 NUMBER
3 left      = NUMBER
  right     = NUMBER
  alternative = 0 1
```

`\setupchemical [...1,...] [...,2...]`

```
1 NAME
2 strut      = inherits: \value-strut
  width      = fit none NUMBER
  height     = fit none NUMBER
  left       = fit none NUMBER
  right      = fit none NUMBER
  top        = fit none NUMBER
  bottom     = fit none NUMBER
  scale      = small medium big normal NUMBER
  rotation   = NUMBER
  symalign   = auto
  axis       = on off
  framecolor = COLOR
  rulethickness = DIMENSION
  offset     = DIMENSION
  unit       = DIMENSION
  factor     = NUMBER
  frame      = on off
  rulecolor  = COLOR
  bodyfont   = inherits: \setupbodyfont
  size       = small medium big
  style      =
  color      = COLOR
```

`\setupchemicalframed [...1,...] [...,2...]`

```
1 NAME
2 inherits: \setupframed
```

`\setupclipping [...,*...]`

```
* state      = start stop
  width      = DIMENSION
  height     = DIMENSION
  hoffset    = DIMENSION
  voffset    = DIMENSION
  x          = NUMBER
  y          = NUMBER
  nx         = NUMBER
  ny         = NUMBER
  sx         = NUMBER
  sy         = NUMBER
  leftoffset = DIMENSION
  rightoffset = DIMENSION
  topoffset  = DIMENSION
  bottomoffset = DIMENSION
  mp         = NAME
  n          = NUMBER
  offset     = DIMENSION
```

`\setupcollector [...1,...] [...,2...]`

```
1 NAME
2 rotation = left right inner outer NUMBER
  corner   = left middle right top bottom
  x        = DIMENSION
  y        = DIMENSION
  hoffset  = DIMENSION
  voffset  = DIMENSION
  location =
  state    = start stop
```

`\setupcolor [...]`

* FILE

`\setupcolors [...,*...,...]`

* state = start stop
spot = yes no
expansion = yes no
factor = yes no
rgb = yes no
cmyk = yes no
conversion = yes no always
pagecolormodel = auto none NAME
textcolor = COLOR
intent = overprint knockout none

`\setupcolumns [...,*...,...]`

* n = NUMBER
distance = DIMENSION
option = background
offset = DIMENSION
command = CD:ONEARGUMENT
height = DIMENSION
direction = left right
balance = yes no
align = setupalign
tolerance = setuptolerance
blank = inherits: \blank
ntop = NUMBER
rule = on off COMMAND

`\setupcolumnspan [...,*...,...]`

* n = NUMBER
inherits: \setupframed

`\setupcombination [...,1...] [...,2...,...]`

1 NAME
2 nx = NUMBER
ny = NUMBER
width = fit DIMENSION
height = fit DIMENSION
location = left middle right top bottom
distance = DIMENSION
alternative = label text
align = inherits: \setupalign
continue = yes no
before = COMMAND
after = COMMAND
inbetween = COMMAND
style =
color = COLOR

`\setupcombinedlist [...,1] [...,2...,...]`

1 LIST
2 inherits: \setuplist

`\setupcombinedlist [...,*...,...]`

* inherits: \setuplist

`\setupcomment [...,1...] [...,2...,...]`

```
1  NAME

2  state      = start stop none
   method    = normal hidden
   symbol     = Comment Help Insert Key Newparagraph Note Paragraph Default
   width      = fit DIMENSION
   height     = fit DIMENSION
   depth      = fit DIMENSION
   title      = TEXT
   subtitle   = TEXT
   author     = TEXT
   nx         = NUMBER
   ny         = NUMBER
   color      = COLOR
   option     = xml max
   textlayer  = NAME
   location   = leftedge rightedge inmargin leftmargin rightmargin text high none
   distance   = DIMENSION
```

`\setupcontent [...,*...,...]`

`* inherits: \setuplist`

`\setupcounter [...,1...] [...,2...,...]`

```
1  NAME

2  start      = NUMBER
   counter    = NAME
   method     = page
   state      = start stop
   way        = bypage byblock bytext byhead bySECTION
   prefix     = yes no
   prefixseparatorset = NAME
   prefixconversion = NAME
   prefixconversionset = NAME
   prefixstarter =
   prefixstopper =
   prefixset   = NAME
   prefixsegments =
   numberorder = reverse
   numberseparatorset = NAME
   numberconversion = NAME
   numberconversionset = NAME
   numberstarter =
   numberstopper =
   numbersegments =
   type        = first previous next last number
   criterium   = strict positive all
   prefixconnector =
```

`\setupdataset [...,*...,...]`

`* delay = yes no`

`\setupdelimitedtext [...1,...] [...2...]`

```
1  NAME
2  before      = COMMAND
   after       = COMMAND
   language    = LANGUAGE
   method      = font
   repeat      = yes no
   location    = text paragraph margin
   left        = COMMAND
   middle      = COMMAND
   right       = COMMAND
   nextleft    = COMMAND
   nextright   = COMMAND
   spacebefore = inherits: \blank
   spaceafter  = inherits: \blank
   leftmargin  =
   rightmargin =
   indenting   = inherits: \setupindenting
   indentnext  =
   style       =
   color       = COLOR
   symstyle    =
   symcolor    = COLOR
```

`\setupdescription [...1,...] [...2...]`

```
1  NAME
2  title       = yes no
   level       = NUMBER
   text        = TEXT
   headcommand = CD:ONEARGUMENT
   before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   alternative  = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin serried
                  hanging top command NAME
   align       = inherits: \setupalign
   headalign    = inherits: \setupalign
   indenting   = inherits: \setupindenting
   display     = yes no
   indentnext  =
   width       = fit broad line DIMENSION
   distance    = none DIMENSION
   hang        = fit broad none margin NUMBER
   closesymbol = COMMAND
   closecommand = CD:ONEARGUMENT
   expansion   = yes no xml
   sample      = TEXT
   margin      =
   style       =
   color       = COLOR
   headstyle   =
   headcolor   = COLOR
```

`\setupdirections [...*...]`

```
*  bidi      = on off local global
   method    = one two default
   fences    = yes no
```

`\setupdocument [...*...]`

```
*  before      = COMMAND
   after       = COMMAND
   metadata:author = TEXT
   metadata:title  = TEXT
   metadata:subject = TEXT
   metadata:keywords = TEXT
   KEY         = VALUE
```

`\setupeffect [...,1...] [...,2...,...]`

1 NAME

2 method = none command
stretch = NUMBER
rulethickness = NUMBER
alternative = normal inner outer both hidden stretch

`\setupenumeration [...,1...] [...,2...,...]`

1 NAME

2 title = yes no
number = yes no
numbercommand = CD:ONEARGUMENT
titledistance = DIMENSION
titlestyle =
titlecolor = COLOR
titlecommand = CD:ONEARGUMENT
titleleft = COMMAND
titleright = COMMAND
left = COMMAND
right = COMMAND
symbol = COMMAND
starter = COMMAND
stopper = COMMAND
coupling = NAME
counter = NAME
level = NUMBER
text = TEXT
headcommand = CD:ONEARGUMENT
before = COMMAND
after = COMMAND
inbetween = COMMAND
alternative = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin serried
hanging top command NAME
align = inherits: \setupalign
headalign = inherits: \setupalign
indenting = inherits: \setupindenting
display = yes no
indentnext =
width = fit broad line DIMENSION
distance = none DIMENSION
hang = fit broad none margin NUMBER
closesymbol = COMMAND
closecommand = CD:ONEARGUMENT
expansion = yes no xml
sample = TEXT
margin =
style =
color = COLOR
headstyle =
headcolor = COLOR
inherits: \setupcounter

`\setupenv [...,*...,...]`

* set = COMMAND
reset = COMMAND
KEY = VALUE

`\setupexport [...,*...,...]`

* align = flushleft middle flushright normal
bodyfont = DIMENSION
width = DIMENSION
title = TEXT
subtitle = TEXT
author = TEXT
alternative = html div
properties = yes no
hyphen = yes no
cssfile = FILE
firstpage = FILE
lastpage = FILE

`\setupexternalfigure [...1,...] [...2,...,...]`

```
1  NAME
2  width          = DIMENSION
   height         = DIMENSION
   label          = NAME
   page           = NUMBER
   object         = yes no
   prefix         = TEXT
   method         = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controls       = yes no
   preview        = yes no
   mask           = none
   resolution     = NUMBER
   color          = COLOR
   arguments      = CD:STRING
   repeat         = yes no
   factor         = fit broad max auto default
   hfactor        = fit broad max auto default
   wfactor        = fit broad max auto default
   maxwidth       = DIMENSION
   maxheight      = DIMENSION
   equalwidth     = DIMENSION
   equalheight    = DIMENSION
   scale          = NUMBER
   xscale         = NUMBER
   yscale         = NUMBER
   s              = NUMBER
   sx             = NUMBER
   sy             = NUMBER
   lines          = NUMBER
   location        = local global default
   directory      = PATH
   option          = test frame empty
   foregroundcolor = COLOR
   reset          = yes no
   background     = color foreground NAME
   frame          = on off
   backgroundcolor = COLOR
   align          = inherits: \setupalign
   xmax           = NUMBER
   ymax           = NUMBER
   frames         = on off
   interaction     = yes all none reference layer bookmark
   bodyfont       = DIMENSION
   comment        = COMMAND TEXT
   size           = none media crop trim art
   cache          = PATH
   resources      = PATH
   display        = FILE
   conversion     = TEXT
   order          = LIST
   crossreference = yes no NUMBER
```

`\setupexternalsoundtracks [...*,...,...]`

* option = repeat

`\setupfield [...1] [...2,...] [...3,...,...4] [...4,...,...5] [...5,...,...]`

```
1  NAME
2  reset label frame horizontal vertical
3  inherits: \setupfieldtotalframed
4  inherits: \setupfieldlabelframed
5  inherits: \setupfieldcontentframed
```

`\setupfieldbody [...1,...] [...2,...,...]`

```
1  NAME
2  category = NAME
   inherits: \setupfieldcategory
```

`\setupfieldcategory [...1,...] [...2...]`

```

1  NAME
2  start          = NUMBER
   style          =
   color          = COLOR
   type           = radio sub text line push check signature
   values         = TEXT
   default        = TEXT
   fieldframecolor = COLOR
   fieldbackgroundcolor = COLOR
   width          = DIMENSION
   height         = DIMENSION
   depth         = DIMENSION
   align          = left middle right flushleft center flushright
   n              = NUMBER
   symbol         = NAME
   fieldlayer     = NAME
   option         = readonly required protected sorted unavailable nocheck fixed file hidden printable auto
   clickin        = REFERENCE
   clickout       = REFERENCE
   regionin       = REFERENCE
   regionout      = REFERENCE
   afterkey       = REFERENCE
   format         = REFERENCE
   validate       = REFERENCE
   calculate      = REFERENCE
   focusin        = REFERENCE
   focusout       = REFERENCE
   openpage       = REFERENCE
   closepage      = REFERENCE

```

`\setupfieldcontentframed [...1,...] [...2...]`

```

1  NAME
2  inherits: \setupframedinherits: \setupfieldcategory

```

`\setupfieldlabelframed [...1,...] [...2...]`

```

1  NAME
2  inherits: \setupframed

```

`\setupfields [...1,...] [...2...] [...3...] [...4...]`

```

1  reset label frame horizontal vertical
2  inherits: \setupfieldtotalframed
3  inherits: \setupfieldlabelframed
4  inherits: \setupfieldcontentframed

```

`\setupfieldtotalframed [...1,...] [...2...]`

```

1  NAME
2  before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   distance    = DIMENSION
   alternative = reset label frame horizontal vertical
   inherits: \setupframed

```


`\setupfiller [...1,...] [...2...,...]`

```
1  NAME

2  leftmargin   = DIMENSION
   rightmargin  = DIMENSION
   left         = COMMAND
   right        = COMMAND
   alternative  = symbol stretch rule space
   method       = local global middle broad
   width        = DIMENSION
   height       = DIMENSION
   depth        = DIMENSION
   offset       = DIMENSION
   distance     = DIMENSION
   align        =
   symbol       = COMMAND
   style        =
   color        = COLOR
```

`\setupfillinlines [...*...,...]`

```
*  before      = COMMAND
   after       = COMMAND
   margin      = DIMENSION
   width       = DIMENSION
   distance    = DIMENSION
   rulethickness = DIMENSION
   color       = COLOR
```

`\setupfillinrules [...*...,...]`

```
*  before      = COMMAND
   after       = COMMAND
   n           = NUMBER
   interlinespace = small medium big NUMBER
   distance     = DIMENSION
   width        = fit broad DIMENSION
   separator    = COMMAND
   style        =
   color        = COLOR
```

`\setupfirstline [...1,...] [...2...,...]`

```
1  NAME

2  n           = NUMBER
   alternative = default line word
   style       =
   color       = COLOR
```

`\setupfittingpage [...1,...] [...2...,...]`

```
1  NAME

2  pagestate = start stop
   command   = CD:ONEARGUMENT
   margin    = page
   scale     = NUMBER
   paper     = auto default NAME
   inherits: \setupframed
```

`\setupfloat [...1,...] [...2,...]`

```

1  SINGULAR
2  indentnext      =
   default         = inherits: \placefloat
   fallback        = inherits: \placefloat
   inner           = COMMAND
   criterium        = DIMENSION
   method          = NUMBER
   sidemethod       = NUMBER
   textmethod       = NUMBER
   sidealign        = height depth line halfline grid normal
   local           = yes no
   command          = CD:ONEARGUMENT
   availablewidth   = DIMENSION
   availableheight  = DIMENSION
   minwidth         = DIMENSION
   maxwidth         = DIMENSION
   location         =
   leftmargindistance = DIMENSION
   rightmargindistance = DIMENSION
   leftmargin       = DIMENSION
   rightmargin      = DIMENSION
   innermargin       = DIMENSION
   outermargin       = DIMENSION
   bottombefore     = COMMAND
   bottomafter      = COMMAND
   spacebefore       = none inherits: \blank
   spaceafter        = none inherits: \blank
   width            = DIMENSION
   height           = DIMENSION
   offset           = DIMENSION none overlay
   sidespacebefore   = none inherits: \blank
   sidespaceafter    = none inherits: \blank
   margin           = DIMENSION
   ntop             = DIMENSION
   nbottom          = DIMENSION
   step             = small medium big line depth
   nlines           = NUMBER
   cache            = yes no

```

`\setupfloatcaption [...1,...] [...2,...]`

```

1  NAME
2  suffix           = COMMAND
   suffixseparator   = COMMAND
   suffixstopper     = COMMAND
   location          = left right middle low high grid overlay inner outer innermargin outermargin leftmargin rightmargin
                     lefthanging righthanging hang top bottom stretch none default
   command           = CD:ONEARGUMENT
   numbercommand      = CD:ONEARGUMENT
   textcommand        = CD:ONEARGUMENT
   spacebefore        = inherits: \blank
   spaceinbetween     = inherits: \blank
   spaceafter         = inherits: \blank
   distance           = DIMENSION
   inbetween          = COMMAND
   style              =
   color              = COLOR
   topoffset          = DIMENSION
   bottomoffset       = DIMENSION
   number             = yes no none
   group              = TEXT
   leftmargin         = DIMENSION
   rightmargin        = DIMENSION
   innermargin        = DIMENSION
   outermargin        = DIMENSION
   align              = inherits: \setupalign
   width              = fit max DIMENSION
   minwidth           = fit DIMENSION
   maxwidth           = DIMENSION
   inherits: \setupcounter

```

```
\setupfloatsplitting [...,..*...,...]
```

```
* before      = COMMAND
  after       = COMMAND
  inbetween   = COMMAND
  lines       = auto NUMBER
  conversion  = NAME
```

```
\setupfontexpansion [...]1 [...,..2...,...]
```

```
1  NAME

2  vector      = NAME
   factor      = NUMBER
   stretch    = NUMBER
   shrink      = NUMBER
   step        = NUMBER
```

```
\setupfontprotrusion [...]1 [...,..2...,...]
```

```
1  NAME

2  vector      = NAME
   factor      = NUMBER
   left        = NUMBER
   right       = NUMBER
```

```
\setupfonts [...,..*...,...]
```

```
* language = no auto
```

```
\setupfontsolution [...]1,... [...,..2...,...]
```

```
1  NAME

2  goodies      = FILE
   solution     = NAME
   less         = NAME
   more         = NAME
   method       = preroll split normal reverse random
   criterium    = NUMBER
```

```
\setupfooter [...]1 [...,..2...,...]
```

```
1  text margin edge

2  inherits: \setuplayoutelement
```

```
\setupfootertexts [...]1 [...]2 [...]3 [...]4 [...]5
```

```
1  text margin edge

2  date pagenumber MARK TEXT COMMAND

3  date pagenumber MARK TEXT COMMAND

4  date pagenumber MARK TEXT COMMAND

5  date pagenumber MARK TEXT COMMAND
```

```
\setupforms [...,..*...,...]
```

```
* method = XML HTML PDF
  export  = yes no
```

`\setupformula [...1,...] [...2...,...]`

```

1  NAME
2  location      = left right
   align         = left middle right flushleft center flushright normal
   strut         = yes no
   distance      = DIMENSION
   left          = COMMAND
   right         = COMMAND
   spacebefore   = inherits: \blank
   spaceafter    = inherits: \blank
   numbercommand = CD:ONEARGUMENT
   color         = COLOR
   numberstyle   =
   numbercolor   = COLOR
   option        = middle
   margin        =
   leftmargin    = DIMENSION
   rightmargin   = DIMENSION
   alternative   = NAME
   indentnext    =
   grid          = inherits: \suptogrid
   inherits: \setupcounter

```

`\setupframed [...1,...] [...2...,...]`

```

1  NAME
2  corner          = rectangular round NUMBER
   framecorner     = rectangular round NUMBER
   backgroundcorner = rectangular round NUMBER
   radius          = DIMENSION
   frameradius     = DIMENSION
   backgroundradius = DIMENSION
   depth           = DIMENSION
   frameddepth     = DIMENSION
   backgrounddepth = DIMENSION
   framecolor      = COLOR
   topframe        = on off NAME
   bottomframe     = on off NAME
   leftframe       = on off NAME
   rightframe      = on off NAME
   region          = yes no
   rulethickness   = DIMENSION
   frameoffset     = DIMENSION
   frame           = on off overlay none
   background      =
   backgroundoffset = frame DIMENSION
   component       = NAME
   extras          = COMMAND
   foregroundstyle  =
   foregroundcolor  = COLOR
   setups          = NAME
   offset          = default overlay none DIMENSION
   width           = local fit max broad fixed DIMENSION
   height          = fit max broad DIMENSION
   align           = inherits: \setupalign
   strut           = yes no none local global
   autostrut       = yes no
   location        = height depth high low top middle bottom line lohi hanging keep mathematics normal
   autowidth       = yes no force
   lines           = NUMBER
   top             = COMMAND
   bottom          = COMMAND
   blank           = yes no
   profile         = NAME
   empty           = yes no
   loffset         = DIMENSION
   roffset         = DIMENSION
   toffset         = DIMENSION
   boffset         = DIMENSION
   orientation     = NUMBER

```

`\setupframedcontent [...1,...] [...2...]`

1 NAME

2 left = COMMAND
right = COMMAND
leftoffset = DIMENSION
rightoffset = DIMENSION
topoffset = DIMENSION
bottomoffset = DIMENSION
linecorrection = yes no
inherits: \setupframed

`\setupframedtext [...1,...] [...2...]`

1 NAME

2 left = COMMAND
right = COMMAND
inner = COMMAND
location = left right middle none
depthcorrection = on off
bodyfont = inherits: \setupbodyfont
indenting = inherits: \setupindenting
style =
color = COLOR
inherits: \setupframedinherits: \setupplacement

`\setupglobalreferenceprefix [...*]`

*

`\setuphead [...,1...] [...,2...,...]`

```

1  SECTION
2  frontpartlabel      = NAME
   bodypartlabel      = NAME
   appendixlabel      = NAME
   backpartlabel      = NAME
   expansion          = yes no xml
   catcodes            = NAME
   sectionresetset    = NAME
   sectionseparatorset = NAME
   sectionconversionset = NAME
   conversion         = NAME
   sectionstarter     =
   sectionstopper     =
   sectionset         = NAME
   sectionsegments    =
   referenceprefix    = + - TEXT
   style              =
   color              = COLOR
   textstyle          =
   textcolor          = COLOR
   numberstyle        =
   numbercolor        = COLOR
   coupling           = SECTION
   ownnumber          = yes no
   beforesection      = COMMAND
   aftersection       = COMMAND
   insidesection      = COMMAND
   incrementnumber    = yes no list empty
   placehead          = yes no hidden empty
   number             = yes no
   page               = inherits: \page
   marking            = page reset
   header             =
   header             =
   text               =
   footer             =
   before             = COMMAND
   after              = COMMAND
   inbetween          = COMMAND
   continue           = yes no
   aligntitle         = yes no float
   interlinespace     = NAME
   interaction         = list reference
   internalgrid       = NAME
   grid               =
   align              = inherits: \setupalign
   tolerance          = inherits: \setuptolerance
   strut              = yes no
   hang               = line broad fit none NUMBER
   margin             = DIMENSION
   indentnext         =
   alternative        = text paragraph normal margin inmargin top middle bottom reverse NAME
   width              = DIMENSION
   numberwidth        = DIMENSION
   textwidth          = DIMENSION
   distance           = DIMENSION
   commandbefore      = COMMAND
   commandafter       = COMMAND
   command            = CD:TWOARGUMENTS
   textcommand        = CD:ONEARGUMENT
   deeptextcommand    = CD:ONEARGUMENT
   numbercommand      = CD:ONEARGUMENT
   deepnumbercommand  = CD:ONEARGUMENT

```

`\setupheadalternative [...,1...] [...,2...,...]`

```

1  NAME
2  alternative      = horizontal vertical
   renderingsetup  = NAME

```

`\setupheader [...]1 [...,2...,...]`

```

1  text margin edge
2  inherits: \setuplayoutelement

```

`\setupheadertexts [...1] [...2] [...3] [...4] [...5]`

```
1 text margin edge
2 date pagenumber MARK TEXT COMMAND
3 date pagenumber MARK TEXT COMMAND
4 date pagenumber MARK TEXT COMMAND
5 date pagenumber MARK TEXT COMMAND
```

`\setupheadnumber [...1] [...2]`

```
1 SECTION
2 [-+]NUMBER
```

`\setupheadtext [...1] [...,2...]`

```
1 LANGUAGE
2 KEY = VALUE
```

`\setuphelp [...,1...] [...,2...]`

```
1 NAME
2 inherits: \setupframed
```

`\setuphigh [...,1...] [...,2...]`

```
1 NAME
2 distance = DIMENSION
  up       = DIMENSION
  style    =
  color    = COLOR
```

`\setuphighlight [...,1...] [...,2...]`

```
1 NAME
2 command = yes no
  style   =
  color   = COLOR
```

`\setuphyphenation [...,*...]`

```
* method = original tex default hyphenate expanded traditional none
```

`\setuphyphenmark [...,*...]`

```
* sign = normal wide
```

`\setupindentedtext [...,1...] [...,2...]`

```
1 NAME
2 before = COMMAND
  after  = COMMAND
  distance = DIMENSION
  sample = TEXT
  text   = TEXT
  width  = fit broad DIMENSION
  separator = COMMAND
  style   =
  color   = COLOR
  headstyle =
  headcolor = COLOR
```

`\setupindenting [...,*...]`

```
* [-+]small [-+]medium [-+]big none no not first next yes always never odd even normal reset toggle DIMENSION NAME
```

`\setupindex [...1,...] [...2...]`

1 NUMBER
2 inherits: \setupregister

`\setupinitial [...1,...] [...2...]`

1 NAME
2 n = NUMBER
m = NUMBER
before = COMMAND
distance = DIMENSION
hoffset = DIMENSION
voffset = line DIMENSION
style =
color = COLOR
font = FONT
text = TEXT
location = margin text
method = first last auto none

`\setupinsertion [...1,...] [...2...]`

1 NAME
2 location = page text columns firstcolumn lastcolumn

`\setupinteractionbar [...1,...] [...2...]`

1 NAME
2 alternative = a b c d e f g
state = start stop
command = CSNAME
width = DIMENSION
height = DIMENSION max broad
depth = DIMENSION max
distance = DIMENSION
step = small medium big
backgroundcolor = COLOR
style =
color = COLOR
contrastcolor = COLOR
symbol = yes no
inherits: \setupframed

`\setupinteractionmenu [...1,...] [...2...]`

1 NAME
2 alternative = vertical horizontal hidden
category = NAME
leftoffset = overlay frame none default DIMENSION
rightoffset = overlay frame none default DIMENSION
topoffset = overlay frame none default DIMENSION
bottomoffset = overlay frame none default DIMENSION
maxwidth = DIMENSION
maxheight = DIMENSION
itemalign = left middle right flushleft flushright low high lohi
state = start empty local
left = COMMAND
right = COMMAND
distance = overlay DIMENSION
before = COMMAND
after = COMMAND
inbetween = COMMAND
position = yes no
middle = COMMAND
style =
color = COLOR
samepage = yes no empty none normal default
contrastcolor = COLOR
inherits: \setupframed

\setupinteractionscreen [...,*...]

* width = fit max tight DIMENSION
height = fit max tight DIMENSION
backspace = DIMENSION
horoffset = DIMENSION
veroffset = DIMENSION
topspace = DIMENSION
option = fit max singlesided doublesided bookmark auto none default fixed landscape portrait page paper
copies = NUMBER
delay = none NUMBER

\setupinteraction [...¹,...] [...²,...]

1 NAME
2 state = start stop
style =
color = COLOR
contrastcolor = COLOR
title = TEXT
subtitle = COLOR
author = TEXT
date = TEXT
keyword = TEXT
focus = standard frame width minwidth height minheight fit tight
menu = on off
fieldlayer = auto NAME
calculate = REFERENCE
click = yes no
display = normal new
page = yes no page name auto
openaction = REFERENCE
closeaction = REFERENCE
openpageaction = REFERENCE
closepageaction = REFERENCE
symbolset = NAME
height = DIMENSION
depth = DIMENSION
focusoffset = DIMENSION

\setupinteraction [...]

* NAME

\setupinterlinespace [...¹,...] [...²,...]

1 NAME
2 line = DIMENSION
height = NUMBER
depth = NUMBER
minheight = NUMBER
mindepth = NUMBER
distance = DIMENSION
top = NUMBER height
bottom = NUMBER
stretch = NUMBER
shrink = NUMBER

\setupinterlinespace [...*,...]

* on off reset auto small medium big NUMBER DIMENSION

\setupinterlinespace [...]

* NAME

\setupitaliccorrection [...*,...]

* text always global none

```
\setupitemgroup [...]1 [...,2...] [...,3...] [...,4...,...]
```

```
1 NAME
```

```
2 each NUMBER
```

```
3 intro random continue packed autointro broad text before after nowite margin inmargin atmargin intext loose fit
  nofit paragraph joinedup serried stopper unpacked repeat norepeat reverse columns one two three four five six
  seven eight nine standard NUMBER*broad NUMBER*serried horizontal NAME
```

```
4 before      = COMMAND
  after       = COMMAND
  inbetween   = COMMAND
  beforehead  = COMMAND
  afterhead   = COMMAND
  lefttext    = COMMAND
  righttext   = COMMAND
  left        = COMMAND
  right       = COMMAND
  factor      = NUMBER
  step        = DIMENSION
  width       = DIMENSION
  distance    = DIMENSION
  margin      =
  leftmargin  =
  rightmargin =
  align       = inherits: \setupalign
  indenting   =
  start       = NUMBER
  symalign    = left middle right flushleft center flushright
  symbol      = NAME
  n           = NUMBER
  indentnext  =
  inner       = COMMAND
  command     = CSNAME
  items       = NUMBER
  maxwidth    = DIMENSION
  itemalign   =
  alignsymbol = yes no
  textdistance = small medium big none space DIMENSION
  placestopper = yes no
  style       =
  color       = COLOR
  headstyle   =
  headcolor   = COLOR
  marstyle    =
  marcolor    = COLOR
  symstyle    =
  symcolor    = COLOR
  inherits: \setupcounter
```

`\setupitemgroup [...1,...] [...2,...]`

```

1  NAME NAME:NUMBER

2  before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   beforehead  = COMMAND
   afterhead   = COMMAND
   lefttext    = COMMAND
   righttext   = COMMAND
   left        = COMMAND
   right       = COMMAND
   factor      = NUMBER
   step        = DIMENSION
   width       = DIMENSION
   distance    = DIMENSION
   option      = intro random continue packed autointro broad text before after nowwhite margin inmargin atmargin
                intext loose fit nofit paragraph joinedup serried stopper unpacked repeat norepeat reverse
                columns one two three four five six seven eight nine standard NUMBER*broad NUMBER*serried horizontal
                NAME

   margin      =
   leftmargin  =
   rightmargin =
   align       = inherits: \setupalign
   indenting   =
   start       = NUMBER
   symalign    = left middle right flushleft center flushright
   symbol      = NAME
   n           = NUMBER
   indentnext  =
   inner       = COMMAND
   command     = CSNAME
   items       = NUMBER
   maxwidth    = DIMENSION
   itemalign   =
   alignsymbol = yes no
   textdistance = small medium big none space DIMENSION
   placestopper = yes no
   style       =
   color       = COLOR
   headstyle   =
   headcolor   = COLOR
   marstyle    =
   marcolor    = COLOR
   symstyle    =
   symcolor    = COLOR
   inherits: \setupcounter

```

`\setupitems [...1,...] [...2,...]`

```

1  NAME

2  alternative = left right top bottom inmargin
   textwidth  = DIMENSION
   width      = DIMENSION
   distance   = DIMENSION
   symbol     = none NAME
   align      = left middle right flushleft flushright inner outer margin
   textalign  = left middle right flushleft flushright inner outer
   n         = NUMBER
   before    = COMMAND
   after     = COMMAND
   inbetween = COMMAND

```

`\setuplabel [...1,...] [...2...,...]`

```

1  NAME
2  title      = yes no
   number     = yes no
   numbercommand = CD:ONEARGUMENT
   titledistance = DIMENSION
   titlestyle  =
   titlecolor  = COLOR
   titlecommand = CD:ONEARGUMENT
   titleleft   = COMMAND
   titleright  = COMMAND
   left        = COMMAND
   right       = COMMAND
   symbol      = COMMAND
   starter     = COMMAND
   stopper     = COMMAND
   coupling    = NAME
   counter     = NAME
   level       = NUMBER
   text        = TEXT
   headcommand = CD:ONEARGUMENT
   before      = COMMAND
   after       = COMMAND
   inbetween   = COMMAND
   alternative  = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin serried
                  hanging top command intext NAME
   align        = inherits: \setupalign
   headalign    = inherits: \setupalign
   indenting    = inherits: \setupindenting
   display      = yes no
   indentnext   =
   width        = fit broad line DIMENSION
   distance     = none DIMENSION
   hang         = fit broad none margin NUMBER
   closesymbol  = COMMAND
   closecommand = CD:ONEARGUMENT
   expansion    = yes no xml
   sample       = TEXT
   margin       =
   style        =
   color        = COLOR
   headstyle    =
   headcolor    = COLOR
   inherits: \setupcounter

```

`\setuplabeltext [...1] [...2...,...]`

```

1  LANGUAGE
2  KEY = VALUE

```

`\setuplabeltext [...1] [...2...,...]`

```

1  LANGUAGE
2  KEY = VALUE

```

`\setuplanguage [...]1 [...,...2...,...]`

```
1  LANGUAGE default
2  default          = LANGUAGE
   state           = start stop
   date            = inherits: \currentdate
   patterns        = FILE
   factor          = yes no
   lefthyphenmin   = NUMBER
   righthyphenmin  = NUMBER
   lefthyphenchar  = NUMBER
   righthyphenchar = NUMBER
   setups          = NAME
   spacing         = broad packed
   font            = auto
   text            = TEXT
   limitttext      = TEXT
   hyphen          = TEXT
   compoundhyphen  = TEXT
   leftcompoundhyphen = TEXT
   rightcompoundhyphen = TEXT
   leftquote       = COMMAND
   rightquote      = COMMAND
   leftquotation   = COMMAND
   rightquotation  = COMMAND
   leftspeech      = COMMAND
   rightspeech     = COMMAND
   leftsentence    = COMMAND
   middlespeech    = COMMAND
   rightsentence   = COMMAND
   midsentence     = COMMAND
   leftsubsentence = COMMAND
   rightsubsentence = COMMAND
```

`\setupplayer [...]1,... [...,...2...,...]`

```
1  NAME
2  state           = start stop continue next repeat
   option          = test
   page            = NUMBER
   width           = DIMENSION
   height          = DIMENSION
   region          = NAME
   rotation        = left right inner outer NUMBER
   position        = yes no overlay
   hoffset         = max DIMENSION
   voffset         = max DIMENSION
   offset          = DIMENSION
   dx              = DIMENSION
   dy              = DIMENSION
   sx              = NUMBER
   sy              = NUMBER
   x               = DIMENSION
   y               = DIMENSION
   corner          = left middle right top bottom
   location        = grid
   line            = NUMBER
   column          = NUMBER
   direction       = normal reverse
   doublesided     = yes no
   method          = fit overlay
   repeat          = yes
   preset          = lefttop righttop leftbottom rightbottom middle middletop middlebottom middleleft middleright
                   lefttopleft lefttopright NAME
```

`\setuplayeredtext [...]1,... [...,...2...,...]`

```
1  NAME
2  style =
   color = COLOR
   inherits: \setupframed
```

`\setuplayouttext` [¹...] [²...] [...,³...,...]

```

1 top header text footer bottom
2 text margin edge
3 state      = start stop empty high none normal nomarking NAME
  style      =
  color      = COLOR
  strut      = yes no
  n          = NUMBER
  before     = COMMAND
  after      = COMMAND
  leftstyle  =
  rightstyle =
  leftcolor  = COLOR
  rightcolor = COLOR
  width      = DIMENSION
  leftwidth  = DIMENSION
  rightwidth = DIMENSION

```

`\setuplayout` [¹...] [...,²...,...]

```

1 NAME
2 state      = start stop normal repeat
  margin     = DIMENSION
  edge       = DIMENSION
  margindistance = DIMENSION
  edgedistance = DIMENSION
  leftedgedistance = DIMENSION
  rightedgedistance = DIMENSION
  leftmargindistance = DIMENSION
  rightmargindistance = DIMENSION
  topdistance = DIMENSION
  headerdistance = DIMENSION
  footerdistance = DIMENSION
  bottomdistance = DIMENSION
  preset      = NAME
  leftmargin  = DIMENSION
  rightmargin = DIMENSION
  leftedge    = DIMENSION
  rightedge   = DIMENSION
  header      = DIMENSION
  footer      = DIMENSION
  top         = DIMENSION
  bottom      = DIMENSION
  backspace   = DIMENSION
  topspace    = DIMENSION
  setups      = NAME
  cutspace    = DIMENSION
  width       = DIMENSION middle fit
  bottomspace = DIMENSION
  lines       = NUMBER
  height      = DIMENSION middle fit
  horoffset   = DIMENSION
  veroffset   = DIMENSION
  columns     = NUMBER
  columndistance = DIMENSION
  method      = default normal NAME
  location    = left middle right top bottom singlesided doublesided
  textwidth   = DIMENSION
  textheight  = DIMENSION
  nx          = NUMBER
  ny          = NUMBER
  dx          = DIMENSION
  dy          = DIMENSION
  scale       = NUMBER
  sx          = NUMBER
  sy          = NUMBER
  marking     = on off page empty color
  grid        = yes no off
  textdistance = DIMENSION
  alternative  = default normal makeup NAME
  clipoffset  = DIMENSION
  cropoffset  = DIMENSION
  trimoffset  = DIMENSION
  bleedoffset = DIMENSION
  artoffset   = DIMENSION

```

`\setuplayout [...]`

* reset NAME

`\setuplegend [...,1*,...]`

* inherits: \setuppairedbox

`\setuplinenote [...,1...] [...,2*,...]`

1 NAME

2 compress = yes no
compressmethod = separator stopper space
compressseparator = COMMAND
compressdistance = DIMENSION
inherits: \setupnote

`\setuplinenumbering [...,1...] [...,2*,...]`

1 NAME

2 start = NUMBER
step = NUMBER
method = page first next
conversion = NAME
continue = yes no
location = text begin end default left right inner outer inleft inright margin inmargin
distance = DIMENSION
align = inner outer flushleft flushright left right middle auto
command = CD:ONEARGUMENT
left = COMMAND
right = COMMAND
margin = DIMENSION
width = margin DIMENSION
style =
color = COLOR

`\setuplines [...,1...] [...,2*,...]`

1 NAME

2 option = packed
before = COMMAND
after = COMMAND
inbetween = COMMAND
indenting = inherits: \setupindenting
align = inherits: \setupalign
space = yes on off fixed default
command = COMMAND
style =
color = COLOR
left = COMMAND
right = COMMAND

```
\setuplinetable [...]1 [...]2 [...,...]3 [...,...]
```

```
1 r c
```

```
2 odd even header NUMBER
```

```
3 lines          = fit NUMBER
  before         = COMMAND
  after          = COMMAND
  inbetween      = COMMAND
  stretch       = yes no DIMENSION
  maxwidth       = fit DIMENSION
  nleft          = NUMBER
  n              = NUMBER
  repeat         = yes no
  nx             = NUMBER
  width          = DIMENSION
  height         = fit line DIMENSION
  distance       = DIMENSION
  leftoffset     = DIMENSION
  rightoffset    = DIMENSION
  align          = inherits: \setupalign
  background     = color
  backgroundcolor = COLOR
  xheight        = max DIMENSION
  xdepth         = max DIMENSION
  style          =
  color          = COLOR
```

```
\setuplinewidth [...]
```

```
* small medium big DIMENSION
```


\setuplist [...,¹...] [...,²...]

```

1  LIST
2  state           = start stop
   location        = none here
   type            = simple command userdata
   criterium       = local intro reference SECTIONBLOCK:reference all SECTIONBLOCK:all text SECTIONBLOCK:text
                   current SECTIONBLOCK:current here previous SECTIONBLOCK:previous component SECTION
                   SECTIONBLOCK:SECTION
   list            = NAME
   width           = fit broad auto DIMENSION
   height          = fit broad DIMENSION
   depth           = fit broad DIMENSION
   symbol          = one two three none default
   label           = yes no none NAME
   starter         = COMMAND
   stopper         = COMMAND
   command         = CD:THREEARGUMENT
   numbercommand   = CD:ONEARGUMENT
   textcommand     = CD:ONEARGUMENT
   pagecommand     = CD:ONEARGUMENT
   pagenumber      = yes no always
   headnumber      = yes no always
   before          = COMMAND
   after           = COMMAND
   inbetween       = COMMAND
   margin          = none DIMENSION
   distance        = none DIMENSION
   aligntitle      = yes no
   numberalign     =
   align           = inherits: \setupalign
   hang            = yes no
   left            = COMMAND
   right           = COMMAND
   interaction      = yes no all number text title page sectionnumber pagenumber
   limittext       =
   style           =
   color           = COLOR
   numberstyle     =
   numbercolor     = COLOR
   textstyle       =
   textcolor       = COLOR
   pagestyle       =
   pagecolor       = COLOR
   reference       = NUMBER
   extras          = NAME
   order           = command all title
   alternative      = a b c d e f g left right top bottom command none interactive paragraph horizontal
                   vertical NAME
   maxwidth        = DIMENSION
   pageprefix      = yes no
   pageprefixseparatorset = NAME
   pageprefixconversionset = NAME
   pageprefixset   = NAME
   pageprefixsegments =
   pageprefixconnector =
   pageconversionset = NAME
   pagestarter     =
   pagestopper     =
   inherits: \setupcounterinherits: \setupframed

```

\setuplistalternative [...,¹...] [...,²...]

```

1  NAME
2  before          = COMMAND
   after           = COMMAND
   command         = CD:THREEARGUMENTS
   renderingsetup  = NAME
   width           = DIMENSION
   distance        = DIMENSION
   stretch        = DIMENSION
   filler          = COMMAND

```

`\setuplistextra [...,1...] [...,2...,...]`

1 NAME
2 before = COMMAND
after = COMMAND

`\setuplocalfloats [...,*...,...]`

* before = COMMAND
after = COMMAND
inbetween = COMMAND

`\setuplocalinterlinespace [...,1...] [...,2...,...]`

1 NAME
2 inherits: \setupinterlinespace

`\setuplocalinterlinespace [...,*...]`

* on off reset auto small medium big NUMBER DIMENSION

`\setuplocalinterlinespace [...*...]`

* NAME

`\setuplow [...,1...] [...,2...,...]`

1 NAME
2 distance = DIMENSION
down = DIMENSION
style =
color = COLOR

`\setuplowhigh [...,1...] [...,2...,...]`

1 NAME
2 distance = DIMENSION
up = DIMENSION
down = DIMENSION
style =
color = COLOR

`\setuplowmidhigh [...,1...] [...,2...,...]`

1 NAME
2 up = DIMENSION
down = DIMENSION
style =
color = COLOR

`\setupMPgraphics [...,*...,...]`

* color = local global
mpy = FILE

`\setupMPinstance [...,1...] [...,2...,...]`

1 NAME
2 format = metafun mpost
initializations = yes no
setups = NAME
textstyle =
textcolor = COLOR
extensions = yes no
method = binary decimal double scaled default

```
\setupMPpage [...,1...,...]
```

```
* inherits: \setupfittingpage
```

```
\setupMPvariables [...]1 [...,2...,...]
```

```
1 NAME
```

```
2 KEY = VALUE
```

```
\setupmakeup [...,1...] [...,2...,...]
```

```
1 NAME
```

```
2 page      = inherits: \page
  command   = COMMAND
  width      = DIMENSION
  height     = DIMENSION
  align      = inherits: \setupalign
  setups     = NAME
  top        = COMMAND
  bottom     = COMMAND
  before     = COMMAND
  after      = COMMAND
  location   = top
  reference  = REFERENCE
  pagestate  = start stop
  headerstate = start stop high empty none normal
  footerstate = start stop high empty none normal
  topstate   = start stop high empty none normal
  bottomstate = start stop high empty none normal
  textstate  = start stop high empty none normal
  doublesided = yes no empty
  style      = inherits: \value-style
  color      = COLOR
```

```
\setupmarginblock [...,1...] [...,2...,...]
```

```
1 NAME
```

```
2 state      = start stop
  width      = DIMENSION
  before     = COMMAND
  after      = COMMAND
  inbetween  = COMMAND
  align      = inherits: \setupalign
  style      =
  color      = COLOR
  top        = COMMAND
  bottom     = COMMAND
  location   = left right middle inmargin
  left       = COMMAND
  right      = COMMAND
```

`\setupmargindata [...1,...] [...2,...]`

```
1 NAME
2 strut      =
  command    = CD:ONEARGUMENT
  width      = DIMENSION
  align      = inherits: \setupalign
  anchor     = region text
  location   = left right inner outer
  method     = top line first depth height
  category   = default edge
  scope      = local global
  option     = text paragraph
  margin     = local normal margin edge
  distance   = DIMENSION
  hoffset    = DIMENSION
  voffset    = DIMENSION
  dy         = DIMENSION
  bottomspace = DIMENSION
  threshold  = DIMENSION
  line       = NUMBER
  stack      = yes continue
  style      =
  color      = COLOR
```

`\setupmarginframed [...1,...] [...2,...]`

```
1 NAME
2 inherits: \setupframed
```

`\setupmarginrule [...1] [...2,...]`

```
1 NUMBER
2 inherits: \setupsidebar
```

`\setupmarginrules [...1] [...2,...]`

```
1 NUMBER
2 inherits: \setupmarginrule
```

`\setupmarking [...1,...] [...2,...]`

```
1 MARK
2 state      = start stop
  expansion  = yes no
  separator  = COMMAND
  filtercommand = CD:ONEARGUMENT
```

`\setupmathalignment [...1,...] [...2,...]`

```
1 NAME
2 n          = NUMBER
  m          = NUMBER
  distance   = DIMENSION
  align      = left middle right normal
```

`\setupmathcases [...1,...] [...2,...]`

```
1 NAME
2 left       = COMMAND
  right      = COMMAND
  strut      = yes no
  style      =
  distance   = DIMENSION
  numberdistance = DIMENSION
```

`\setupmathematics [...1,...] [...2,...,...]`

```
1 NAME
2 openup          = yes no
  symbolset       = NAME
  functionstyle   =
  compact         = yes no
  align           = l2r r2l
  bidi            = yes no
  sygreek         = normal italic none
  lcgreek         = normal italic none
  ucgreek         = normal italic none
  italics         = 1 2 3 4 none reset
  autopunctuation = yes no all
  setups          = NAME
  domain         = NAME reset
  textstyle       =
  textcolor       = COLOR
  functioncolor   =
  integral        = limits nolimits autolimits displaylimits none
  stylealternative = LIST
  default         = normal italic
```

`\setupmathfence [...1,...] [...2,...,...]`

```
1 NAME
2 command = yes no
  left    = NUMBER
  middle  = NUMBER
  right   = NUMBER
  mathstyle =
  color   = COLOR
  state   = auto
```

`\setupmathfraction [...1,...] [...2,...,...]`

```
1 NAME
2 topdistance    = DIMENSION
  bottomdistance = DIMENSION
  margin         = DIMENSION
  color          = COLOR
  strut          = yes no math tight
  alternative     = inner outer both
  rule           = yes no auto
  left           = NUMBER
  right          = NUMBER
  rulethickness  = DIMENSION
  mathstyle      =
  distance       = no none overlay
```

`\setupmathframed [...1,...] [...2,...,...]`

```
1 NAME
2 inherits: \setupframed
```

`\setupmathlabeltext [1] [...2,...,...]`

```
1 LANGUAGE
2 KEY = VALUE
```

`\setupmathmatrix [...1,...] [...2,...,...]`

```
1 NAME
2 left    = COMMAND
  right   = COMMAND
  strut   = yes no NUMBER
  align   = left middle right normal
  style   =
  distance = DIMENSION
  location = top bottom high low lohi normal
```

`\setupmathornament [...1,...] [...2.,...]`

```
1  NAME
2  alternative = mp
   color      = COLOR
   mppoffset  = DIMENSION
   mp         = NAME
```

`\setupmathradical [...1,...] [...2.,...]`

```
1  NAME
2  alternative = default normal mp
   color      = COLOR
   mppoffset  = DIMENSION
   mp         = NAME
```

`\setupmathstackers [...1,...] [...2.,...]`

```
1  NAME
2  left        = COMMAND
   right       = COMMAND
   topcommand  = CD:ONEARGUMENT
   bottomcommand = CD:ONEARGUMENT
   middlecommand = CD:ONEARGUMENT
   mp          = NAME
   mpheight    = DIMENSION
   mpdepth     = DIMENSION
   mppoffset   = DIMENSION
   color       = COLOR
   hoffset     = DIMENSION
   voffset     = DIMENSION
   minheight   = DIMENSION
   mindepth    = DIMENSION
   mathclass   = rel ord
   offset      = min max normal
   location    = top bottom high low middle NUMBER
   strut       = yes no
   alternative = normal default mp
   minwidth    = DIMENSION
   distance    = DIMENSION
   moffset     = DIMENSION
   order       = normal reverse
   mathlimits  = yes no
```

`\setupmathstyle [...*,...]`

```
*  NAME
```

`\setupmixedcolumns [...1,...] [...2.,...]`

```
1  NAME
2  grid          = inherits: \setupgrid
   rulethickness = DIMENSION
   method        = otr box
   before        = COMMAND
   after         = COMMAND
   distance      = DIMENSION
   n             = NUMBER
   maxheight     = DIMENSION
   maxwidth      = DIMENSION
   step          = DIMENSION
   profile       = NAME
   align         = inherits: \setupalign
   setups        = NAME
   balance       = yes no
   splitmethod   = none fixed
   alternative    = local global
   internalgrid  = line halfline
   separator     = rule
   strut         = yes no
   color         = COLOR
   rulecolor     = COLOR
   direction     = normal reverse
   inherits:    \setupframed
```

`\setupmodule [...]1 [...,...2...,...]`

```
1  FILE
2  test  = yes no
    KEY   = VALUE
```

`\setupnarrower [...]1,... [...,...2...,...]`

```
1  NAME
2  left   = DIMENSION
    middle = DIMENSION
    right  = DIMENSION
    default = [-+]left [-+]middle [-+]right NUMBER*left NUMBER*middle NUMBER*right reset
    before = COMMAND
    after  = COMMAND
```

`\setupnotation [...]1,... [...,...2...,...]`

```
1  NAME
2  title      = yes no
    number    = yes no
    type      = note
    numbercommand = CD:ONEARGUMENT
    titledistance = DIMENSION
    titlestyle =
    titlecolor  = COLOR
    titlecommand = CD:ONEARGUMENT
    titleleft   = COMMAND
    titleright  = COMMAND
    left        = COMMAND
    right       = COMMAND
    symbol      = COMMAND
    starter     = COMMAND
    stopper     = COMMAND
    coupling    = NAME
    counter     = NAME
    level       = NUMBER
    text        = TEXT
    headcommand = CD:ONEARGUMENT
    before      = COMMAND
    after       = COMMAND
    inbetween   = COMMAND
    alternative = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin serried
                  hanging top command note NAME
    align       = inherits: \setupalign
    headalign   = inherits: \setupalign
    indenting   = inherits: \setupindenting
    display     = yes no
    indentnext  =
    width       = fit broad line DIMENSION
    distance    = none DIMENSION
    hang        = fit broad none margin NUMBER
    closesymbol = COMMAND
    closecommand = CD:ONEARGUMENT
    expansion   = yes no xml
    sample      = TEXT
    margin      =
    style       =
    color       = COLOR
    headstyle   =
    headcolor   = COLOR
    inherits: \setupcounter
```

`\setupnote [...1,...] [...2,...]`

```
1  NAME

2  interaction      = yes no number text all
   symbolcommand   = CD:ONEARGUMENT
   textcommand     = CD:ONEARGUMENT
   indicator       = yes no
   textseparator   = COMMAND
   width           = DIMENSION
   height          = DIMENSION
   distance        = DIMENSION
   rulecommand     = COMMAND
   rule            = on off normal left right command paragraph
   split           = tolerant strict verystrict NUMBER
   factor          = NUMBER
   location        = text page high bottom none columns firstcolumn lastcolumn
   next            = COMMAND
   n               = NUMBER
   rulecolor       = COLOR
   rulethickness   = DIMENSION
   setups          = NAME
   interlinespace  = NAME
   paragraph       = yes no
   before          = COMMAND
   after           = cd.command
   inbetween       = COMMAND
   scope           = page
   columndistance  = DIMENSION
   continue        = yes no
   alternative      = grid fixed columns note none
   criterium       = page
   bodyfont        = inherits: \setupbodyfont
   align           = inherits: \setupalign
   textstyle       =
   textcolor       = COLOR
   anchor          = next
   inherits: \setupframed
```

`\setupoffset [...*,...]`

* inherits: \setupoffsetbox

`\setupoffsetbox [...*,...]`

```
*  x               = DIMENSION
   y               = DIMENSION
   leftoffset      = DIMENSION
   rightoffset     = DIMENSION
   topoffset       = DIMENSION
   bottomoffset    = DIMENSION
   method          = fixed
   width           = DIMENSION
   height          = DIMENSION
   depth           = DIMENSION
   location        =
```

`\setupoperatortext [...1] [...2,...]`

```
1  LANGUAGE
2  KEY = VALUE
```

`\setupoppositeplacing [...*,...]`

```
*  state          = start stop
   before         = COMMAND
   after          = COMMAND
   inbetween      = COMMAND
```

`\setupoutputroutine [...1] [...2,...]`

```
1  NAME
2  KEY = CSNAME
```


`\setupoutputroutine [...]`

* NAME

`\setuppagechecker [...1,...] [...2,...,...]`

1 NAME

2 lines = NUMBER
offset = DIMENSION
method = 0 1 2 3
before = COMMAND
after = COMMAND
inbetween = COMMAND

`\setuppagecomment [...*,...,...]`

* location = left right top bottom none
state = start stop none
offset = DIMENSION
distance = DIMENSION
width = DIMENSION
height = DIMENSION

`\setuppagegrid [...1,...] [...2,...,...]`

1 NAME

2 n = NUMBER
nleft = NUMBER
nright = NUMBER
width = DIMENSION auto
distance = DIMENSION
lines = NUMBER
maxwidth = DIMENSION
maxheight = DIMENSION
direction = normal reverse
page = inherits: \page
inherits: \setupframed

`\setuppagegridarea [...1,...] [...2,...,...]`

1 NAME

2 state = start stop repeat
x = NUMBER
y = NUMBER
nx = NUMBER
ny = NUMBER
style =
color = COLOR
clipoffset = DIMENSION
rightoffset = DIMENSION
inherits: \setupframed

`\setuppagegridareatext [...1] [...2]`

1 NAME

2 TEXT

`\setuppagegridlines [...1] [...2] [...3] [...4]`

1 NAME

2 NUMBER

3 NUMBER

4 NUMBER

`\setuppagegridspan [...1,...] [...2.,...]`

```
1  NAME
2  n      = NUMBER
   style  =
   color  = COLOR
   before = COMMAND
   after  = COMMAND
   inherits: \setupframed
```

`\setuppagegridstart [...1] [...2] [...3] [...4]`

```
1  NAME
2  NUMBER
3  NUMBER
4  NUMBER
```

`\setuppageinjection [...1,...] [...2.,...]`

```
1  NAME
2  state      = previous next NUMBER
   delay      = yes no
   alternative = figure buffer setups none NAME
   page       = inherits: \page
   pagestate  = start stop
   n          = NUMBER
   inherits: \setupframed
```

`\setuppageinjectionalternative [...1,...] [...2.,...]`

```
1  NAME
2  renderingsetup = NAME
```

`\setuppagenumber [...*.,...]`

```
*  inherits: \setupuserpagenumber
```

`\setuppagenumbering [...*.,...]`

```
*  alternative = singlesided doublesided
   page       = inherits: \page
   strut      = yes no
   command    = CD:ONEARGUMENT
   left       = COMMAND
   right      = COMMAND
   state      = start stop
   width      = DIMENSION
   location   = header footer left middle right inleft inright margin inmargin atmargin marginedge
   style      =
   color      = COLOR
```

`\setuppageshift [...1] [...2] [...3]`

```
1  page paper
2  NAME
3  NAME
```

`\setuppagestate [...*.,...]`

```
*  delay = yes no
```

`\setuppagetransitions [...*]`

```
*  reset auto start random NUMBER
```

`\setuppairedbox [...1,...] [...2,...]`

```
1 NAME
2 before = COMMAND
  after  = COMMAND
  inbetween = COMMAND
  location = left middle right top bottom high low
  n       = NUMBER
  distance = DIMENSION
  bodyfont = inherits: \setupbodyfont
  width    = DIMENSION
  height   = DIMENSION
  maxwidth = DIMENSION
  maxheight = DIMENSION
  align    = inherits: \setupalign
  style    =
  color    = COLOR
```

`\setuppairedbox [...*,...]`

* inherits: \setuppairedbox

`\setuppalet [...]`

* NAME

`\setuppaper [...*,...]`

* inherits: \setuppapersize

`\setuppapersize [...1,...] [...2,...]`

```
1 reset landscape mirrored negative rotated 90 180 270 NAME
2 reset landscape mirrored negative rotated 90 180 270 NAME
```

`\setuppapersize [...1,] [...2,...]`

```
1 NAME
2 top      = COMMAND
  bottom   = COMMAND
  left     = COMMAND
  right    = COMMAND
  method   = normal none NAME
  scale    = NUMBER
  nx       = NUMBER
  ny       = NUMBER
  dx       = DIMENSION
  dy       = DIMENSION
  width    = DIMENSION
  height   = DIMENSION
  topspace = DIMENSION
  backspace = DIMENSION
  offset   = DIMENSION
  page     = reset landscape mirrored negative rotated 90 180 270 NAME
  paper    = reset landscape mirrored negative rotated 90 180 270 NAME
  option   = fit max
  distance = DIMENSION
```

`\setupparagraph [...1,...] [...2,...]`

```
1 NAME
2 style =
  color = COLOR
  align = inherits: \setupalign
  setups = NAME
```

`\setupparagraphintro [...1,...] [...2,]`

```
1 reset each first next
2 COMMAND
```

`\setupparagraphnumbering [...,..*...,...]`

```
* state      = start stop line reset
  distance   = DIMENSION
  style      =
  color      = COLOR
```

`\setupparagraphs [...1.] [...,2...] [...,3...,...]`

```
1 NAME
2 each NUMBER
3 n          = NUMBER
  before     = COMMAND
  after      = COMMAND
  width      = DIMENSION
  distance   = DIMENSION
  height     = DIMENSION fit
  top        = COMMAND
  bottom     = COMMAND
  align      = inherits: \setupalign
  inner      = COMMAND
  command    = COMMAND
  rule       = on off
  rulethickness = DIMENSION
  rulecolor  = COLOR
  style      =
  color      = COLOR
```

`\setupparagraphs [...1.] [...,2...,...]`

```
1 NAME:NUMBER
2 n          = NUMBER
  before     = COMMAND
  after      = COMMAND
  width      = DIMENSION
  distance   = DIMENSION
  height     = DIMENSION fit
  top        = COMMAND
  bottom     = COMMAND
  align      = inherits: \setupalign
  inner      = COMMAND
  command    = COMMAND
  rule       = on off
  rulethickness = DIMENSION
  rulecolor  = COLOR
  style      =
  color      = COLOR
```

`\setupparallel [...1.] [...,2...] [...,3...,...]`

```
1 NAME
2 NAME
3 setups     = NAME
  start      = NUMBER
  n          = NUMBER
  criterium  = all
```

`\setupperiods [...,*...,...]`

```
* n          = NUMBER
  width      = DIMENSION fit
  distance   = DIMENSION
  symbol     = COMMAND
```

`\setupplacement [...1,...] [...2,...]`

```
1 NAME
2 before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  grid        = inherits: \suptogrid
  linecorrection = on off
  depthcorrection = on off
  margin      = yes no standard
```

`\setuppositionbar [...*,...]`

```
* style =
  color = COLOR
  n      = NUMBER
  min    = NUMBER
  max    = NUMBER
  text   = TEXT
  width  = DIMENSION
  height = DIMENSION
  depth  = DIMENSION
```

`\setuppositioning [...1,...] [...2,...]`

```
1 NAME
2 offset = yes no
  unit   = ex em pt in cm mm sp bp pc dd cc nc
  state  = start overlay
  xoffset = DIMENSION
  yoffset = DIMENSION
  xstep   = absolute relative
  ystep   = absolute relative
  xscale  = NUMBER
  yscale  = NUMBER
  xfactor = NUMBER
  yfactor = NUMBER
  factor  = NUMBER
  scale   = NUMBER
```

`\setupprefixtext [...1,...] [...2,...]`

```
1 LANGUAGE
2 KEY = VALUE
```

`\setupprocessor [...1,...] [...2,...]`

```
1 NAME
2 state = start stop
  left  = COMMAND
  right = COMMAND
  command = CD:ONEARGUMENT
  style  =
  color  = COLOR
```

`\setupprofile [...1,...] [...2,...]`

```
1 NAME
2 height = DIMENSION
  depth  = DIMENSION
  distance = DIMENSION
  factor = NUMBER
  lines  = NUMBER
  method = strict fixed none
```

`\setupprograms [...*,...]`

```
* style =
  color = COLOR
```

`\setupquotation [...,..*...,...]`

* inherits: \setupdelimitedtext

`\setupquote [...,..*...,...]`

* inherits: \setupdelimitedtext

`\setuprealpagenumber [...,..*...,...]`

* inherits: \setupcounter

`\setupreferenceformat [...,..1...] [...,..2...,...]`

1 NAME
2 label = * NAME
left = COMMAND
right = COMMAND
type =
setups = NAME
autocase = yes no
text = TEXT
style =
color = COLOR

`\setupreferenceprefix [...]`

*

`\setupreferencestructureprefix [...]1 [...]2 [...,..3...,...]`

1 NAME SECTION
2 default
3 prefix = yes no
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter =
prefixstopper =
prefixset = NAME
prefixsegments =
numberconversion = NAME
numberconversionset = NAME
numberstarter =
numberstopper =
numbersegments =
numberseparatorset = NAME
prefixconnector =

`\setuppreferencing [...,..*...,...]`

* state = start stop
expansion = yes no xml
autofile = yes no
export = yes no
left = COMMAND
right = COMMAND
width = DIMENSION
doublesided = yes no
interaction = label text symbol all
separator = COMMAND
prefix =

`\setupregister [...,..1...] [...,..2...,...]`

1 NUMBER
2 inherits: \setupregister

\setupregister [...¹,...] [...²,...] [...,³...,...]

```

1  NAME
2  NUMBER
3  referencemethod      = forward
   expansion            = yes no xml
   ownnumber            = yes no
   xmlsetup             = NAME
   alternative          = a b A B
   method              =
   compress             = yes no all
   criterium            = local text current previous all SECTION
   pageprefixseparatorset = COMMAND
   pageprefixconversionset = NAME
   pageprefixstarter    =
   pageprefixstopper    =
   pageprefixset        = NAME
   pageprefixsegments   =
   pageprefixconnector  = COMMAND
   pageprefix           = yes no
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          =
   pagestopper          =
   pagesegments         =
   maxwidth             = DIMENSION
   indicator            = yes no
   before               = COMMAND
   after                = COMMAND
   command              = CD:ONEARGUMENT
   textcommand          = CD:ONEARGUMENT
   deeptextcommand      = CD:ONEARGUMENT
   pagecommand          = CD:ONEARGUMENT
   distance             = DIMENSION
   interaction          = text pagenumber
   pagenumber           = yes no
   symbol               = a n none 1 2 COMMAND
   language             =
   style               =
   color               = COLOR
   textstyle           =
   textcolor           = COLOR
   pagestyle           =
   pagecolor           = COLOR
   n                   = NUMBER
   balance              = yes no
   align               = inherits: \setupalign
   numberorder         = numbers

```

`\setupregister [...]1 [...,...2...,...]`

```

1  NAME:NUMBER
2  referencemethod      = forward
   expansion            = yes no xml
   ownnumber            = yes no
   xmlsetup             = NAME
   alternative          = a b A B
   method               =
   compress             = yes no all
   criterium            = local text current previous all SECTION
   pageprefixseparatorset = COMMAND
   pageprefixconversionset = NAME
   pageprefixstarter    =
   pageprefixstopper    =
   pageprefixset        = NAME
   pageprefixsegments   =
   pageprefixconnector  = COMMAND
   pageprefix           = yes no
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          =
   pagestopper          =
   pagesegments         =
   maxwidth             = DIMENSION
   indicator            = yes no
   before               = COMMAND
   after                = COMMAND
   command              = CD:ONEARGUMENT
   textcommand          = CD:ONEARGUMENT
   deeptextcommand      = CD:ONEARGUMENT
   pagecommand          = CD:ONEARGUMENT
   distance             = DIMENSION
   interaction          = text pagenumber
   pagenumber           = yes no
   symbol               = a n none 1 2 COMMAND
   language             =
   style                =
   color                = COLOR
   textstyle            =
   textcolor            = COLOR
   pagestyle            =
   pagecolor            = COLOR
   n                    = NUMBER
   balance              = yes no
   align                = inherits: \setupalign
   numberorder          = numbers

```

`\setuprenderingwindow [...]1,... [...,...2...,...]`

```

1  NAME
2  openpageaction = REFERENCE
   closepageaction = REFERENCE
   inherits: \setupframed

```

`\setuprotate [...,...*...,...]`

```

*  location = fit broad depth high middle default normal
   rotation = left right inner outer NUMBER
   inherits: \setupframed

```


`\setupscale [...1,...] [...2,...]`

```
1  NAME

2  scale      = NUMBER
   xscale     = NUMBER
   yscale     = NUMBER
   width      = DIMENSION
   height     = DIMENSION
   depth      = yes no
   lines      = NUMBER
   factor     = fit broad max auto default
   hfactor    = fit broad max auto default
   wfactor    = fit broad max auto default
   maxwidth   = DIMENSION
   maxheight  = DIMENSION
   s          = NUMBER
   sx         = NUMBER
   sy         = NUMBER
   equalwidth = DIMENSION
   equalheight = DIMENSION
   grid       = yes fit height depth halfline
```

`\setupscrip [...1,...] [...2,...]`

```
1  NAME

2  method     = hangul hanzi nihongo ethiopic thai test
   preset     = NAME
   features    = auto
```

`\setupsectionblock [...1,...] [...2,...]`

```
1  NAME

2  page       = inherits: \page
   before     = COMMAND
   after      = COMMAND
   number     = yes no
```

`\setupselector [...1] [...2,...]`

```
1  NAME

2  n = NUMBER
   m = NUMBER
```

`\setupshift [...1,...] [...2,...]`

```
1  NAME

2  continue   = yes no
   unit       = ex em pt in cm mm sp bp pc dd cc nc
   method     = NUMBER
   dy         = NUMBER
   align      = inherits: \setupalign
   style      =
   color      = COLOR
```

`\setupsidebar [...1,...] [...2,...]`

```
1  NAME

2  rulethickness = DIMENSION
   rulecolor    = COLOR
   alternative   = NUMBER
   topoffset    = DIMENSION
   bottomoffset = DIMENSION
   distance     = DIMENSION
   leftmargindistance = DIMENSION
   level        = NUMBER
```

\setupsorting [...¹,...] [...²...,...]

```
1 SINGULAR
2 expansion      = yes no xml
  alternative    = first last normal NAME
  next           = COMMAND
  command        = CD:THREEARGUMENTS
  textcommand    = CD:ONEARGUMENT
  synonymcommand = CD:ONEARGUMENT
  language       =
  method         =
  criterium      = current previous local text all SECTION
  style          =
  color          = COLOR
  textstyle      =
  textcolor      = COLOR
  synonymstyle   =
  synonymcolor   = COLOR
```

\setupspacing [...]

* fixed packed broad

\setupspellchecking [...^{*}...,...]

```
* state = start stop
  method = 1 2 3
  list   = NAME
```

\setupstartstop [...¹,...] [...²...,...]

```
1 NAME
2 before = COMMAND
  after  = COMMAND
  inbetween = COMMAND
  setups = NAME
  left   = COMMAND
  right  = COMMAND
  style  =
  color  = COLOR
```

\setupstretched [...^{*}...,...]

* inherits: \setupcharacterkerning

\setupstruts [...]

*

\setupstyle [...¹,...] [...²...,...]

```
1 NAME
2 method = command
  style  =
  color  = COLOR
```

\setupsubformula [...¹,...] [...²...,...]

```
1 NAME
2 indentnext =
```

\setupsubpagenumber [...^{*}...,...]

* inherits: \setupcounter

\setupsymbolset [...]

* NAME

`\setupsynonyms [...1,...] [...2,...]`

```
1 SINGULAR
2 expansion      = yes no xml
  alternative    = first last normal NAME
  next          = COMMAND
  command        = CD:THREEARGUMENTS
  textcommand    = CD:ONEARGUMENT
  synonymcommand = CD:ONEARGUMENT
  language       =
  method         =
  criterium      = current previous local text all SECTION
  style          =
  color          = COLOR
  textstyle      =
  textcolor      = COLOR
  synonymstyle   =
  synonymcolor   = COLOR
```

`\setups [...*,...]`

* NAME

`\setups {...*,...}`

* NAME

`\setupTABLE [...1,...] [...2,...] [...3,...]`

```
1 r c x y row column first last start header each odd even one NUMBER -NUMBER
2 first least each two odd even NUMBER -NUMBER
3 extras          = COMMAND
  left            = COMMAND
  right           = COMMAND
  headcolor       = COLOR
  headstyle       =
  leftmargindistance = DIMENSION
  rightmargindistance = DIMENSION
  columndistance  = DIMENSION
  maxwidth        = DIMENSION
  setups          = NAME
  textwidth       = DIMENSION local
  split           = yes no repeat auto
  header          = repeat
  option          = stretch tight
  before          = COMMAND
  after           = COMMAND
  samepage        = before after both
  spaceinbetween  = inherits: \blank
  splitoffset     = DIMENSION
  aligncharacter  = yes no
  alignmentcharacter = TEXT
  distance        = DIMENSION
  color           = COLOR
  style           =
  inherits: \setupframed
```

`\setupTEXpage [...*,...]`

* inherits: \setupfittingpage

`\setuptables [...,*...]`

```
* text      = DIMENSION max
  split     = yes no repeat auto
  frame     = on off
  NL        = inherits: \blank
  VL        = small medium big none NUMBER
  HL        = small medium big none NUMBER
  distance  = small medium big none
  align     = left middle right
  commands  = COMMAND
  bodyfont  = inherits: \setupbodyfont
  rulethickness = DIMENSION
  height    = strut NUMBER
  depth     = strut NUMBER
```

`\setuptabulate [...]1 [...]2 [...,*...]3...`

```
1 NAME
2 NAME
3 inherits: \setuptabulation
```

`\setuptabulation [...]1 [...]2 [...,*...]`

```
1 NAME
2 format      = TEMPLATE none
  before      = COMMAND
  after       = COMMAND
  distance    = small medium big none blank depth grid DIMENSION
  align       = left middle right dimension
  rule        = line normal
  rulecolor   = COLOR
  rulethickness = DIMENSION
  bodyfont    = inherits: \setupbodyfont
  indenting   = yes no
  split       = yes no repeat auto
  unit        = DIMENSION
  margin      = DIMENSION
  inner       = COMMAND
  EQ          = COMMAND
  header      = yes repeat text
  frame       = on off
  title       = TEXT
  kepttogether = yes no
```

`\setuptagging [...,*...]`

```
* state = start stop
  method = auto
```

`\setuptaglabeltext [...]1 [...,*...]2...`

```
1 LANGUAGE
2 KEY = VALUE
```

`\setuptext [...]1 [...,*...]2...`

```
1 text margin edge
2 inherits: \setuplayoutelement
```

`\setuptextbackground [...1,...] [...2...,...]`

```
1  NAME
2  state           = start stop
   location        = text paragraph none
   alternative     = NUMBER
   mp              = NAME
   method          = NAME
   background      = color
   backgroundcolor = COLOR
   corner          = rectangular round
   level           = NUMBER
   backgroundoffset = DIMENSION
   before          = COMMAND
   after           = COMMAND
   align           = inherits: \setupalign
   dash            = NUMBER
   radius          = DIMENSION
   frame           = on off
   framecolor      = COLOR
   rulethickness   = DIMENSION
   voffset         = DIMENSION
   frameoffset     = DIMENSION
   leftoffset      =
   rightoffset     =
   topoffset       = small medium big line DIMENSION
   bottomoffset    = small medium big line DIMENSION
   style           =
   color           = COLOR
```

`\setuptextflow [...1,...] [...2...,...]`

```
1  NAME
2  width = DIMENSION
   style =
   color = COLOR
```

`\setuptextrules [...*...,...]`

```
*  before          = COMMAND
   after           = COMMAND
   inbetween       = COMMAND
   rulethickness   = DIMENSION
   location        = left inmargin
   style           =
   color           = COLOR
   rulecolor       = COLOR
   width           = DIMENSION
   height          = DIMENSION
   distance        = DIMENSION
   depthcorrection = on off
   bodyfont        = inherits: \setupbodyfont
```

`\setuptexttexts [1...] [2...] [3...] [4...] [5...]`

```
1  text margin edge
2  date pagenumber MARK TEXT COMMAND
3  date pagenumber MARK TEXT COMMAND
4  date pagenumber MARK TEXT COMMAND
5  date pagenumber MARK TEXT COMMAND
```

`\setupthinrules` [...,¹...,...]

* height = max DIMENSION
 depth = max DIMENSION
 background = color
 frame = on off
 rulethickness = DIMENSION
 alternative = a b c none
 backgroundcolor = COLOR
 color = COLOR
 interlinespace = small medium big NUMBER
 before = COMMAND
 after = COMMAND
 inbetween = COMMAND
 n = NUMBER

`\setuptolerance` [...,¹...,...]

* horizontal vertical veryststrict strict tolerant verytolerant space stretch

`\setuptooltip` [...,¹...,...] [...,²...,...]

1 NAME

2 location = left middle right
 inherits: \setupframed

`\setuptop` [...¹...] [...,²...,...]

1 text margin edge

2 inherits: \setuplayoutelement

`\setuptoptexts` [...¹...] [...²...] [...³...] [...⁴...] [...⁵...]

1 text margin edge

2 date pagenumber MARK TEXT COMMAND

3 date pagenumber MARK TEXT COMMAND

4 date pagenumber MARK TEXT COMMAND

5 date pagenumber MARK TEXT COMMAND

`\setuptype` [...,¹...,...] [...,²...,...]

1 NAME

2 option = mp lua xml parsed-xml nested tex context none NAME
 command = CSNAME
 left = COMMAND
 right = COMMAND
 tab = yes no NUMBER
 compact = absolute last all
 escape = yes no TEXT PROCESSOR->TEXT
 style =
 color = COLOR
 lines = yes no normal hyphenated
 space = on off normal fixed stretch

`\setuptyping [...,*...]`

```
* oddmargin      = DIMENSION
  evenmargin     = DIMENSION
  margin         =
  option         = mp lua xml parsed-xml nested tex context none NAME
  style          =
  color          = COLOR
  align          = inherits: \setupalign
  lines          = yes no normal hyphenated
  space          = on off normal fixed stretch
  kepttogether   = yes no
  before         = COMMAND
  after          = COMMAND
  strip          = yes no NUMBER
  range          = NUMBER NAME
  tab            = yes no NUMBER
  escape         = yes no TEXT PROCESSOR->TEXT
  indentnext     =
  continue       = yes no
  start          = NUMBER
  stop           = NUMBER
  step           = NUMBER
  numbering      = file line no
  blank         = inherits: \blank
```

`\setupunit [...,1...] [...,2...]`

```
1 NAME
2 method      = 1 2 3 4 5 6
  language     = LANGUAGE
  alternative   = text mathematics
  order        = reverse normal
  separator    = small medium big normal none NAME
  space        = small medium big normal none NAME
  style        =
  color        = COLOR
```

`\setupunittext [...,1...] [...,2...]`

```
1 LANGUAGE
2 KEY = VALUE
```

`\setupurl [...,*...]`

```
* style =
  color = COLOR
```

`\setupuserpagenumber [...,*...]`

```
* viewerprefix = TEXT
  state         = start stop none keep empty
  inherits: \setupcounter
```

`\setupversion [...]`

```
* concept file temporary final NAME
```

`\setupviewerlayer [...,*...]`

```
* title      = TEXT
  state       = start stop
  export      = yes no
  printable   = yes no
  scope       = local global
  method      = none command
```

`\setupvspacing [...,*...]`

```
* inherits: \vspacing
```

`\setupwhitespace [...]*...]`

* fix fixed flexible line halfline quarterline none small medium big default DIMENSION

`\setupwithargument {...} {...}^1`

1 NAME

2 CONTENT

`\setupwithargumentswapped {...} {...}^1`

1 CONTENT

2 NAME

`\setupxml [...]*...=...]`

* default = hidden none text
compress = yes no

`\setupxtable [...]*^1...] [...]*^2...]`

1 NAME

2 textwidth = DIMENSION local
bodyfont = inherits: \setupbodyfont
spaceinbetween = inherits: \blank
option = tight max stretch width height fixed
textheight = DIMENSION
maxwidth = DIMENSION
columnndistance = DIMENSION
leftmargindistance = DIMENSION
rightmargindistance = DIMENSION
header = repeat
footer = repeat
rulethickness = DIMENSION
split = yes no repeat auto
splitoffset = DIMENSION
samepage = before after both
distance = DIMENSION
inherits: \setupframed

`\setup [...]*...`

* NAME

`\setup {...}^*`

* NAME

`\setuvalue {...} {...}^1`

1 NAME

2 CONTENT

`\setuxvalue {...} {...}^1`

1 NAME

2 CONTENT

`\setvalue {...} {...}^1`

1 NAME

2 CONTENT

`\setvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setvariables [...] [...,..2...,...]`

- 1 NAME
- 2 `set` = COMMAND
`reset` = COMMAND
`KEY` = VALUE

`\setvisualizerfont [...]`

- * FONT

`\setwidthof ... \to ...`

- 1 TEXT
- 2 CSNAME

`\setxmeasure {...} {...}`

- 1 NAME
- 2 DIMENSION

`\setxvalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setxvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setxvariables [...] [...,..2...,...]`

- 1 NAME
- 2 `set` = COMMAND
`reset` = COMMAND
`KEY` = VALUE

`\sfrac {...} {...}`

- 1 CONTENT
- 2 CONTENT

`\shapedhbox {...}`

- * CONTENT

`\shiftdown {...}`

- * CONTENT

`\shiftup {...}`

- * CONTENT

<code>\shift {...}</code> * CONTENT
<code>\showallmakeup</code>
<code>\showattributes</code>
<code>\showbodyfont [...,*,...]</code> * inherits: \setupbodyfont
<code>\showbodyfontenvironment [...,*,...]</code> * inherits: \setupbodyfont
<code>\showboxes</code>
<code>\showbtxdatasetauthors [...,*=...,...]</code> * specification = NAME * dataset = NAME * field =
<code>\showbtxdatasetauthors [...]</code> * NAME
<code>\showbtxdatasetcompleteness [...,*=...,...]</code> * specification = NAME * dataset = NAME * field =
<code>\showbtxdatasetcompleteness [...]</code> * NAME
<code>\showbtxdatasetfields [...,*=...,...]</code> * specification = NAME * dataset = NAME * field =
<code>\showbtxdatasetfields [...]</code> * NAME
<code>\showbtxfields [...,*=...,...]</code> * rotation = NUMBER * specification = NAME
<code>\showbtxfields [...]</code> * NAME
<code>\showbtxhashedauthors [...]</code> * TEXT
<code>\showbtxtables [...]</code> * TEXT

\showchardata {...} * TEXT
\showcharratio {...} * TEXT
\showcolor [...] * COLOR
\showcolorbar [...] * COLOR
\showcolorcomponents [...] * COLOR
\showcolorgroup [... ¹] [... ² ,...] 1 NAME 2 <u>horizontal</u> vertical number value name
\showcolorset [...] * COLOR
\showcolorstruts
\showcounter [...] * NAME
\showdirectives
\showdirlsinmargin
\showedebuginfo
\showexperiments
\showfont [... ¹] [... ² ,...] 1 FONT 2 NUMBER
\showfontdata
\showfontkerns
\showfontparameters
\showfontstrip [...*,...] * inherits: \setupbodyfont

`\showfontstyle [...1,...] [...2,...] [...3,...] [...4,...]`

1 inherits: \setupbodyfont
2 rm ss tt mm hw cg
3 tf bf it sl bi bs
4 all NUMBER

`\showframe [...1,...] [...2,...]`

1 top header text footer bottom
2 leftedge leftmargin text rightmargin rightedge

`\showglyphs`

`\showgrid [...*,...]`

* reset bottom top none all lines frame nonumber right left outer columns

`\showgridsnapping`

`\showhelp {...1} [...2]`

1 TEXT
2 REFERENCE

`\showhyphenationtrace [...1] [...2]`

1 LANGUAGE
2 TEXT

`\showhyphens {...*}`

* TEXT

`\showinjector [...*,...]`

* NAME

`\showjustification`

`\showkerning {...*}`

* TEXT

`\showlayout [...*,...]`

* pt bp cm mm dd cc pc nd nc sp in

`\showlayoutcomponents`

`\showligature {...*}`

* TEXT

`\showligatures [...*]`

* FONT

`\showlogcategories`

`\showmakeup [...]`

* `makeup` all boxes glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox
simplevtop user math italic origin reset

`\showmargins`

`\showmessage {...} {...} {...,3...}`

1 NAME

2 NAME NUMBER

3 TEXT

`\showminimalbaseline`

`\shownextbox \... {2...}`

1 CSNAME

2 CONTENT

`\showotfcomposition {...} {...} {...3}`

1 FONT

2 -1 1 +1 l2r r2l

3 TEXT

`\showpalet [1...] [...,2...]`

1 NAME

2 `horizontal` vertical number value name

`\showparentchain \... {2...}`

1 CSNAME

2 NAME

`\showprint [...,1...] [...,2...] [...,3...,...]`

1 inherits: \setuppapersize

2 inherits: \setuppapersize

3 inherits: \setuplayout

`\showsetups [...,*...]`

* `pt` `bp` `cm` `mm` `dd` `cc` `pc` `nd` `nc` `sp` `in`

`\showsetupsdefinition [...]`

* NAME

`\showstruts`

`\showsymbolset [...]`

* NAME

`\showtimer {...}`

* TEXT

<code>\showtokens [...]</code> * NAME
<code>\showtrackers</code>
<code>\showvalue {...}</code> * NAME
<code>\showvariable {...} {...}</code> 1 NAME 2 KEY
<code>\showwarning {...} {...} {..., 1 NAME 2 NAME NUMBER 3 TEXT </code>
<code>\simplealignedbox {...} {...} {...}</code> 1 DIMENSION 2 3 CONTENT
<code>\simplealignedboxplus {...} {...} {...} {...}</code> 1 DIMENSION 2 3 TEXT 4 CONTENT
<code>\simplealignedspreadbox {...} {...} {...}</code> 1 DIMENSION 2 3 CONTENT
<code>\simplegroupedcommand {...} {...}</code> 1 COMMAND 2 COMMAND
<code>\simplereversealignedbox {...} {...} {...}</code> 1 DIMENSION 2 3 CONTENT
<code>\simplereversealignedboxplus {...} {...} {...} {...}</code> 1 DIMENSION 2 3 TEXT 4 CONTENT

`\singalcharacteralign {...} {...}`

1 NUMBER

2 NUMBER

`\singlebond`

`\sixthofsixarguments {...} {...} {...} {...} {...} {...}`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

6 TEXT

`\slanted`

`\slantedbold`

`\slicepages [...1] [...2...,...] [...3...,...]`

1 FILE

2 offset = DIMENSION

 hoffset = DIMENSION

 voffset = DIMENSION

 width = DIMENSION

 height = DIMENSION

 n = NUMBER

3 offset = DIMENSION

 hoffset = DIMENSION

 voffset = DIMENSION

 width = DIMENSION

 height = DIMENSION

 n = NUMBER

`\slovenianNumerals {...}`

* NUMBER

`\sloveniannumerals {...}`

* NUMBER

`\small`

`\smallbodyfont`

`\smallbold`

`\smallbolditalic`

`\smallboldslanted`

`\smallcapped {...}`

* TEXT

<code>\smallcappedcharacters {...}</code> * NUMBER
<code>\smallcappedromannumerals {...}</code> * NUMBER
<code>\smaller</code>
<code>\smalllitalicbold</code>
<code>\smallnormal</code>
<code>\smallskip</code>
<code>\smallslanted</code>
<code>\smallslantedbold</code>
<code>\smalltype</code>
<code>\smash [...]¹ {...}²}</code> 1 <code>w h d t b</code> 2 CONTENT
<code>\smashbox ...</code> * CSNAME NUMBER
<code>\smashboxed ...</code> * CSNAME NUMBER
<code>\smashedhbox ...¹ {...}²}</code> 1 TEXT 2 CONTENT
<code>\smashedvbox ...¹ {...}²}</code> 1 TEXT 2 CONTENT
<code>\snaptogrid [...]¹ \...² {...}³}</code> 1 2 CSNAME 3 CONTENT
<code>\snaptogrid [...,¹...] \...² {...}³}</code> 1 inherits: \definegridsnapping 2 CSNAME 3 CONTENT

<p><code>\someheadnumber [...]¹ [...]²</code></p> <p>1 SECTION</p> <p>2 previous current next first last</p>
<p><code>\somekindoftab [...,...[*]...,...]</code></p> <p>* alternative = horizontal <u>vertical</u></p> <p> width = DIMENSION</p> <p> height = DIMENSION</p> <p> n = NUMBER</p> <p> m = NUMBER</p>
<p><code>\someline [...][*]</code></p> <p>* REFERENCE</p>
<p><code>\somalocalfloat</code></p>
<p><code>\somenamedheadnumber {...}¹ {...}²</code></p> <p>1 SECTION</p> <p>2 previous current next first last</p>
<p><code>\someplace {...}¹ {...}² {...}³ {...}⁴ {...}⁵ [...]⁶</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 REFERENCE</p>
<p><code>\somewhere {...}¹ {...}² [...]³</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 REFERENCE</p>
<p><code>\sorting [...]¹ {...}²</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\space</code></p>
<p><code>\spanishNumerals {...}[*]</code></p> <p>* NUMBER</p>
<p><code>\spanishnumerals {...}[*]</code></p> <p>* NUMBER</p>
<p><code>\speech {...}[*]</code></p> <p>* CONTENT</p>

$\backslash\mathrm{splitdfrac}\{\ldots\}\{\ldots\}$ 1 CONTENT 2 CONTENT
$\backslash\mathrm{splitfilename}\{.*\}$ * FILE
$\backslash\mathrm{splitfloat}[\ldots,\ldots^1\ldots,\ldots]\{\ldots\}\{\ldots\}$ 1 inherits: $\backslash\mathrm{setupfloatsplitting}$ 2 COMMAND 3 CONTENT
$\backslash\mathrm{splitfrac}\{\ldots\}\{\ldots\}$ 1 CONTENT 2 CONTENT
$\backslash\mathrm{splitoffbase}$
$\backslash\mathrm{splitofffull}$
$\backslash\mathrm{splitoffkind}$
$\backslash\mathrm{splitoffname}$
$\backslash\mathrm{splitoffpath}$
$\backslash\mathrm{splitoffroot}$
$\backslash\mathrm{splitofftokens}\ldots\backslash\mathrm{from}\ldots\backslash\mathrm{to}\ldots\backslash\ldots$ 1 TEXT 2 TEXT 3 CSNAME
$\backslash\mathrm{splitofftype}$
$\backslash\mathrm{splitstring}\ldots\backslash\mathrm{at}\ldots\backslash\mathrm{to}\ldots\backslash\mathrm{and}\ldots$ 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
$\backslash\mathrm{spreadhbox}\ldots$ * CSNAME NUMBER
$\backslash\mathrm{sqrt}[\ldots]\{\ldots\}$ 1 TEXT 2 CONTENT

<pre> \stackrel{.1.}{.2.} 1 CONTENT 2 CONTENT </pre>
<pre> \startalign [...,*...] ... \stopalign * inherits: \setupmathalignment </pre>
<pre> \startalignment [...,*...] ... \stopalignment * inherits: \setupalign </pre>
<pre> \startallmodes [...,*...] ... \stopallmodes * NAME </pre>
<pre> \startappendices [...,*...] ... \stopappendices * bookmark = TEXT inherits: \setupsectionblock </pre>
<pre> \startattachment [..1.] [...,*2...] ... \stopattachment 1 NAME 2 inherits: \setupattachment </pre>
<pre> \startattachment [..1.] [...,*2...] ... \stopattachment 1 NAME 2 inherits: \setupattachment </pre>
<pre> \startbackground [...,*...] ... \stopbackground * inherits: \setupbackground </pre>
<pre> \startbackground [...,*...] ... \stopbackground * inherits: \setupbackground </pre>
<pre> \startbackmatter [...,*...] ... \stopbackmatter * bookmark = TEXT inherits: \setupsectionblock </pre>
<pre> \startbar [.*] ... \stopbar * NAME </pre>
<pre> \startbitmapimage [...,*...] ... \stopbitmapimage * color = rgb cmyk gray width = DIMENSION height = DIMENSION x = NUMBER y = NUMBER </pre>
<pre> \startblockquote [...,*...] ... \stopblockquote * inherits: \startnarrower </pre>
<pre> \startbodymatter [...,*...] ... \stopbodymatter * bookmark = TEXT inherits: \setupsectionblock </pre>

$\backslash\text{startboxedcolumns}$ [... [*] ...] ... $\backslash\text{stopboxedcolumns}$ * inherits: $\backslash\text{setupmixedcolumns}$
$\backslash\text{startbtxlabeltext}$ [... ¹] [... ²] ... $\backslash\text{stopbtxlabeltext}$ 1 LANGUAGE 2 KEY
$\backslash\text{startbtxrenderingdefinitions}$ [...] ... $\backslash\text{stopbtxrenderingdefinitions}$ * NAME
$\backslash\text{startbuffer}$ [...] ... $\backslash\text{stopbuffer}$ * NAME
$\backslash\text{startbuffer}$... $\backslash\text{stopbuffer}$
$\backslash\text{startbut}$ [...] ... $\backslash\text{stopbut}$ * REFERENCE
$\backslash\text{startcases}$ [... [*] ...] ... $\backslash\text{stopcases}$ * inherits: $\backslash\text{setupmathcases}$
$\backslash\text{startcatcodetable}$ *... ... $\backslash\text{stopcatcodetable}$ * CSNAME
$\backslash\text{startcenteraligned}$... $\backslash\text{stopcenteraligned}$
$\backslash\text{startchapter}$ [... ¹ ...] [... ² ...] ... $\backslash\text{stopchapter}$ 1 title = TEXT bookmark = TEXT marking = TEXT list = TEXT reference = REFERENCE ownnumber = TEXT 2 KEY = VALUE
$\backslash\text{startcharacteralign}$ [...] ... $\backslash\text{stopcharacteralign}$ * TEXT number->TEXT text->TEXT
$\backslash\text{startcheckedfences}$... $\backslash\text{stopcheckedfences}$
$\backslash\text{startchemical}$ [... ¹] [... ² ...] ... $\backslash\text{stopchemical}$ 1 NAME 2 inherits: $\backslash\text{setupchemical}$
$\backslash\text{startcollect}$... $\backslash\text{stopcollect}$
$\backslash\text{startcollecting}$... $\backslash\text{stopcollecting}$
$\backslash\text{startcolor}$ [...] ... $\backslash\text{stopcolor}$ * COLOR

<code>\startcolorintent [...] ... \stopcolorintent</code> <code>* knockout overprint none</code>
<code>\startcoloronly [...] ... \stopcoloronly</code> <code>* COLOR</code>
<code>\startcolorset [...] ... \stopcolorset</code> <code>* NAME</code>
<code>\startcolumns [...,..¹...,...] ... \stopcolumns</code> <code>* inherits: \setupcolumns</code>
<code>\startcolumnspan [...,..¹...,...] ... \stopcolumnspan</code> <code>* inherits: \setupcolumnspan</code>
<code>\startcombination [¹...] [²...] ... \stopcombination</code> <code>1 NAME</code> <code>2 N*M</code>
<code>\startcombination [¹] [...,..²...,...] ... \stopcombination</code> <code>1 NAME</code> <code>2 inherits: \setupcombination</code>
<code>\startcomment [¹] [...,..²...,...] ... \stopcomment</code> <code>1 TEXT</code> <code>2 inherits: \setupcomment</code>
<code>\startcomment [¹] [...,..²...,...] ... \stopcomment</code> <code>1 TEXT</code> <code>2 inherits: \setupcomment</code>
<code>\startcomponent [...] ... \stopcomponent</code> <code>* FILE *</code>
<code>\startcomponent \stopcomponent</code> <code>* FILE *</code>
<code>\startcom ... \stopcom</code>
<code>\startcontextcode ... \stopcontextcode</code>
<code>\startcontextdefinitioncode ... \stopcontextdefinitioncode</code>
<code>\startctxfunction \stopctxfunction</code> <code>* NAME</code>
<code>\startctxfunctiondefinition \stopctxfunctiondefinition</code> <code>* NAME</code>

<code>\startcurrentcolor ... \stopcurrentcolor</code>
<code>\startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper</code>
<code>\startdelimited [...¹] [...²;...] ... \stopdelimited</code> 1 NAME 2 inherits: \startnarrower
<code>\startdelimitedtext [...¹] [...²;...] ... \stopdelimitedtext</code> 1 NAME 2 inherits: \startnarrower
<code>\startdelimitedtext [...*;...] ... \stopdelimitedtext</code> * inherits: \startnarrower
<code>\startdescription [...,*=...,...] ... \stopdescription</code> * title = TEXT bookmark = TEXT list = TEXT reference = REFERENCE
<code>\startdescription [...,¹;...] {...².} ... \stopdescription</code> 1 REFERENCE 2 TEXT
<code>\startdisplaymath ... \stopdisplaymath</code>
<code>\startdmath ... \stopdmath</code>
<code>\startdocument [...,*=...,...] ... \stopdocument</code> * inherits: \setupdocument
<code>\starteffect [...*] ... \stopeffect</code> * NAME
<code>\starteffect ... \stopeffect</code>
<code>\startembeddedxtable [...,*=...,...] ... \stopembeddedxtable</code> * inherits: \setupxtable
<code>\startembeddedxtable [...*] ... \stopembeddedxtable</code> * NAME
<code>\startendnote [...,*=...,...] ... \stopendnote</code> * title = TEXT bookmark = TEXT list = TEXT reference = REFERENCE
<code>\startendnote [...*;...] ... \stopendnote</code> * REFERENCE

`\startenumeration [...,..*...,...] ... \stopenumeration`

* title = TEXT
bookmark = TEXT
list = TEXT
reference = REFERENCE

`\startenumeration [...,1...,...] {...2.} ... \stopenumeration`

1 REFERENCE
2 TEXT

`\startenvironment [...*] ... \stopenvironment`

* FILE *

`\startenvironment ...* ... \stopenvironment`

* FILE *

`\startexceptions [...*] ... \stopexceptions`

* LANGUAGE

`\startexpanded ... \stopexpanded`

`\startexpandedcollect ... \stopexpandedcollect`

`\startextendedcatcodetable \...* ... \stopextendedcatcodetable`

* CSNAME

`\startexternalfigurecollection [...*] ... \stopexternalfigurecollection`

* NAME

`\startfact [...1] [...,..2...,...] ... \stopfact`

1 NAME
2 inherits: \setuptabulate

`\startfigure [...1] [...2] [...,..3...,...] ... \stopfigure`

1 NAME
2 FILE
3 inherits: \externalfigure

`\startfiguretext [...,1...,...] [...,2...,...] {...3.} ... \stopfiguretext`

1
2 REFERENCE
3 TEXT

`\startfittingpage [...1] [...,..2...,...] ... \stopfittingpage`

1 NAME
2 inherits: \setupfittingpage

`\startfittingpage [...,..*...,...] ... \stopfittingpage`

* inherits: \setupfittingpage

<p><code>\startfloatcombination [...]</code> ... <code>\stopfloatcombination</code></p> <p>* N*M NAME</p>
<p><code>\startfloatcombination [...,*...,...]</code> ... <code>\stopfloatcombination</code></p> <p>* inherits: <code>\setupcombination</code></p>
<p><code>\startfloattext [...,¹...] [...,²...] {...³} ...</code> <code>\stopfloattext</code></p> <p>1</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\startfont [...]</code> ... <code>\stopfont</code></p> <p>* FONT</p>
<p><code>\startfontclass [...]</code> ... <code>\stopfontclass</code></p> <p>* each NAME</p>
<p><code>\startfontsolution [...]</code> ... <code>\stopfontsolution</code></p> <p>* NAME</p>
<p><code>\startfootnote [...,*...,...]</code> ... <code>\stopfootnote</code></p> <p>* title = TEXT</p> <p>bookmark = TEXT</p> <p>list = TEXT</p> <p>reference = REFERENCE</p>
<p><code>\startfootnote [...,*...] ...</code> <code>\stopfootnote</code></p> <p>* REFERENCE</p>
<p><code>\startformula [...,*...] ...</code> <code>\stopformula</code></p> <p>* packed tight middle frame inherits: <code>\setupbodyfont</code></p>
<p><code>\startformulas [...,*...] ...</code> <code>\stopformulas</code></p> <p>* + - REFERENCE</p>
<p><code>\startformulaformula [...,*...] ...</code> <code>\stopformulaformula</code></p> <p>* packed tight middle frame inherits: <code>\setupbodyfont</code></p>
<p><code>\startframed [...¹] [...,*²...,...]</code> ... <code>\stopframed</code></p> <p>1 NAME</p> <p>2 inherits: <code>\setupframed</code></p>
<p><code>\startframedcontent [...]</code> ... <code>\stopframedcontent</code></p> <p>* NAME off</p>
<p><code>\startframedtext [...¹] [...,*²...,...]</code> ... <code>\stopframedtext</code></p> <p>1 left right middle none</p> <p>2 inherits: <code>\setupframedtext</code></p>

<code>\startframedtext [...]¹ [...]²... \stopframedtext</code> 1 left right middle none 2 inherits: \setupframedtext
<code>\startfrontmatter [...][*]... \stopfrontmatter</code> * bookmark = TEXT inherits: \setupsectionblock
<code>\startgoto [...][*]... \stopgoto</code> * REFERENCE
<code>\startgot [...][*]... \stopgot</code> * REFERENCE
<code>\startgraphictext [...]¹ [...]² {...}³... \stopgraphictext</code> 1 2 REFERENCE 3 TEXT
<code>\startgridsnapping [...][*]... \stopgridsnapping</code> *
<code>\startgridsnapping [...][*]... \stopgridsnapping</code> * inherits: \definegridsnapping
<code>\starthboxestohbox ... \stophboxestohbox</code>
<code>\starthead [...]¹ {...}²... \stophead</code> 1 REFERENCE 2 TEXT
<code>\startheadtext [...]¹ [...]²... \stopheadtext</code> 1 LANGUAGE 2 KEY
<code>\starthelptext [...][*]... \stophelptext</code> * REFERENCE
<code>\starthelp [...][*]... \stophelp</code> * REFERENCE
<code>\starthiding ... \stophiding</code>
<code>\starthighlight [...][*]... \stophighlight</code> * NAME
<code>\starthyphenation [...][*]... \stophyphenation</code> * original tex <u>default</u> hyphenate expanded traditional none

<code>\startimath ... \stopimath</code>
<code>\startindentedtext [...][*] ... \stopindentedtext</code> <code>* NAME</code>
<code>\startindentedtext ... \stopindentedtext</code>
<code>\startinteraction [...][*] ... \stopinteraction</code> <code>* hidden NAME</code>
<code>\startinteractionmenu [...][*] ... \stopinteractionmenu</code> <code>* NAME</code>
<code>\startinterface ...[*] ... \stopinterface</code> <code>* all LANGUAGE</code>
<code>\startintermezzotext [...]¹,...² [...]³ ... \stopintermezzotext</code> <code>1</code> <code>2 REFERENCE</code> <code>3 TEXT</code>
<code>\startintertext ... \stopintertext</code>
<code>\startitem [...][*],... \stopitem</code> <code>* REFERENCE</code>
<code>\startitemgroup [...]¹ [...]²,... [...]³,... \stopitemgroup</code> <code>1 NAME</code> <code>2 inherits: \setupitemgroup</code> <code>3 inherits: \setupitemgroup</code>
<code>\startitemgroup [...]¹,... [...]²,... \stopitemgroup</code> <code>1 inherits: \setupitemgroup</code> <code>2 inherits: \setupitemgroup</code>
<code>\startitemize [...]¹,... [...]²,... \stopitemize</code> <code>1 inherits: \setupitemgroup</code> <code>2 inherits: \setupitemgroup</code>
<code>\startJScode ...¹ ...² ...³ ... \stopJScode</code> <code>1 NAME</code> <code>2 uses</code> <code>3 NAME</code>
<code>\startJSreamble ...¹ ...² ...³ ... \stopJSreamble</code> <code>1 NAME</code> <code>2 used</code> <code>3 now later</code>

<code>\startknockout ... \stopknockout</code>
<code>\startLUA [...,*=...,...] ... \stopLUA</code> <code>* inherits: \setuptyping</code>
<code>\startlua [...,*...] ... \stoplua</code> <code>* continue</code>
<code>\startlabeltext [...¹] [...²] ... \stoplabeltext</code> <code>1 LANGUAGE</code> <code>2 KEY</code>
<code>\startlabeltext [...¹] [...²] ... \stoplabeltext</code> <code>1 LANGUAGE</code> <code>2 KEY</code>
<code>\startlayout [...[*]] ... \stoplayout</code> <code>* NAME</code>
<code>\startleftaligned ... \stopleftaligned</code>
<code>\startlegend [...¹] [...,*²...,...] ... \stoplegend</code> <code>1 NAME</code> <code>2 inherits: \setuptabulate</code>
<code>\startline [...[*]]</code> <code>* REFERENCE</code>
<code>\startlinealignment [...[*]] ... \stoplinealignment</code> <code>* left middle right max</code>
<code>\startlinecorrection [...,*...] ... \stoplinecorrection</code> <code>* blank inherits: \blank</code>
<code>\startlinenote [...¹] {...²}</code> <code>1 REFERENCE</code> <code>2 TEXT</code>
<code>\startlinenote [...¹] {...²}</code> <code>1 REFERENCE</code> <code>2 TEXT</code>
<code>\startlinenumbering [...¹] [...,*²...,...] ... \stoplinenumbering</code> <code>1 NAME</code> <code>2 inherits: \setuplinenumbering</code>

<pre> \startlinenumbering [...] [...] ... \stoplinenumbering 1 NAME 2 continue NUMBER </pre>
<pre> \startlines [...] [...] ... \stoplines * inherits: \setuplines </pre>
<pre> \startlines [...] [...] ... \stoplines * inherits: \setuplines </pre>
<pre> \startlinetable ... \stoplinetable </pre>
<pre> \startlinetablebody ... \stoplinetablebody </pre>
<pre> \startlinetablecell [...] [...] ... \stoplinetablecell * inherits: \setuplinetable </pre>
<pre> \startlinetablehead ... \stoplinetablehead </pre>
<pre> \startlocalfootnotes ... \stoplocalfootnotes </pre>
<pre> \startlocalheadsetup ... \stoplocalheadsetup </pre>
<pre> \startlocallinecorrection [...]*[...] ... \stoplocallinecorrection * blank inherits: \blank </pre>
<pre> \startlocalnotes [...]*[...] ... \stoplocalnotes * NAME </pre>
<pre> \startlocalsetups [...] [...] ... \stoplocalsetups 1 grid 2 NAME </pre>
<pre> \startlocalsetups \stoplocalsetups * NAME </pre>
<pre> \startlua ... \stoplua </pre>
<pre> \startluacode ... \stopluacode </pre>
<pre> \startluaparameterset [...] ... \stopluaparameterset * NAME </pre>
<pre> \startluasetups [...] [...] ... \stopluasetups 1 grid 2 NAME </pre>
<pre> \startluasetups \stopluasetups * NAME </pre>

<pre> \startMPclip {...} ... \stopMPclip * NAME </pre>
<pre> \startMPcode {...} ... \stopMPcode * NAME </pre>
<pre> \startMPdefinitions {...} ... \stopMPdefinitions * NAME </pre>
<pre> \startMPdrawing [...] ... \stopMPdrawing * - </pre>
<pre> \startMPenvironment [...] ... \stopMPenvironment * reset global + </pre>
<pre> \startMPextensions {...,*...} ... \stopMPextensions * NAME </pre>
<pre> \startMPinclusions [¹...] {²...} ... \stopMPinclusions 1 + 2 NAME </pre>
<pre> \startMPinitializations ... \stopMPinitializations </pre>
<pre> \startMPpage [...,*...,...] ... \stopMPpage * inherits: \setupfittingpage </pre>
<pre> \startMPpositiongraphic {¹...} {²...,...} ... \stopMPpositiongraphic 1 NAME 2 KEY </pre>
<pre> \startMPpositionmethod {...} ... \stopMPpositionmethod * NAME </pre>
<pre> \startMPrun {...} ... \stopMPrun * NAME </pre>
<pre> \startMP [...,*...,...] ... \stopMP * inherits: \setuptyping </pre>
<pre> \startMP [...,*...] ... \stopMP * continue </pre>
<pre> \startmakeup [¹] [...,*²...,...] ... \stopmakeup 1 NAME 2 inherits: \setupmakeup </pre>

$\backslash\textit{startmakeupmakeup}$ [...,*...,...] ... $\backslash\textit{stopmakeupmakeup}$ * inherits: $\backslash\textit{setupmakeup}$ instances: standard page text middle
$\backslash\textit{startmarginblock}$ [...] ... $\backslash\textit{stopmarginblock}$ * NAME
$\backslash\textit{startmarginrule}$ [...] ... $\backslash\textit{stopmarginrule}$ * NUMBER
$\backslash\textit{startmarginrule}$ [...,*...,...] ... $\backslash\textit{stopmarginrule}$ * inherits: $\backslash\textit{setupmarginrule}$
$\backslash\textit{startmarkedcontent}$ [...] ... $\backslash\textit{stopmarkedcontent}$ * reset <u>all</u> NAME
$\backslash\textit{startmathalignment}$ [...,*...,...] ... $\backslash\textit{stopmathalignment}$ * inherits: $\backslash\textit{setupmathalignment}$
$\backslash\textit{startmathalignment}$ [...,*...,...] ... $\backslash\textit{stopmathalignment}$ * inherits: $\backslash\textit{setupmathalignment}$
$\backslash\textit{startmathcases}$ [...,*...,...] ... $\backslash\textit{stopmathcases}$ * inherits: $\backslash\textit{setupmathcases}$
$\backslash\textit{startmathcases}$ [...,*...,...] ... $\backslash\textit{stopmathcases}$ * inherits: $\backslash\textit{setupmathcases}$
$\backslash\textit{startmathlabeltext}$ [...] [¹ ...] [²] ... $\backslash\textit{stopmathlabeltext}$ 1 LANGUAGE 2 KEY
$\backslash\textit{startmathmatrix}$ [...,*...,...] ... $\backslash\textit{stopmathmatrix}$ * inherits: $\backslash\textit{setupmathmatrix}$
$\backslash\textit{startmathmatrix}$ [...,*...,...] ... $\backslash\textit{stopmathmatrix}$ * inherits: $\backslash\textit{setupmathmatrix}$
$\backslash\textit{startmathmode}$... $\backslash\textit{stopmathmode}$
$\backslash\textit{startmathstyle}$ [...,*...] ... $\backslash\textit{stopmathstyle}$ * NAME
$\backslash\textit{startmatrices}$ [...,*...,...] ... $\backslash\textit{stopmatrices}$ * inherits: $\backslash\textit{setupmathmatrix}$

```
\startmatrix [...,*...] ... \stopmatrix
```

```
* inherits: \setupmathmatrix
```

```
\startmaxaligned ... \stopmaxaligned
```

```
\startmdformula [...,*...] ... \stopmdformula
```

```
* packed tight middle frame inherits: \setupbodyfont
```

```
\startmidaligned ... \stopmidaligned
```

```
\startmiddlealigned ... \stopmiddlealigned
```

```
\startmixedcolumns [...1.] [...2...] ... \stopmixedcolumns
```

```
1 NAME
```

```
2 inherits: \setupmixedcolumns
```

```
\startmixedcolumns [...,*...] ... \stopmixedcolumns
```

```
* inherits: \setupmixedcolumns
```

```
\startmode [...,*...] ... \stopmode
```

```
* NAME
```

```
\startmodeset [...1.] {...2.} ... \stopmodeset
```

```
1 NAME default
```

```
2 CONTENT
```

```
\startmoduletestsection ... \stopmoduletestsection
```

```
\startmodule [...*] ... \stopmodule
```

```
* FILE
```

```
\startmodule ...*... \stopmodule
```

```
* FILE
```

```
\startmpformula [...,*...] ... \stopmpformula
```

```
* packed tight middle frame inherits: \setupbodyfont
```

```
\startnamedsection [...1.] [...2...] [...3...] ... \stopnamedsection
```

```
1 SECTION
```

```
2 title      = TEXT  
  bookmark  = TEXT  
  marking   = TEXT  
  list      = TEXT  
  reference = REFERENCE  
  ownnumber = TEXT
```

```
3 KEY = VALUE
```

```
\startnamedsubformulas [...1.] {...2.} ... \stopnamedsubformulas
```

```
1 + - REFERENCE
```

```
2 TEXT
```

$\backslash\startnarrower [...,*...] \dots \backstopnarrower$ * $[-+]left [-+]middle [-+]right$ NUMBER*left NUMBER*middle NUMBER*right reset
$\backstopnarrower [...,*...] \dots \backstopnarrower$ * $[-+]left [-+]middle [-+]right$ NUMBER*left NUMBER*middle NUMBER*right reset
$\backstartnarrow [...^1...] [...,\dots^2,...] \dots \backstopnarrow$ 1 NAME 2 inherits: \backsetupnarrower
$\backstopnarrow [...^1...] [...,\dots^2,...] \dots \backstopnarrow$ 1 NAME 2 $[-+]left [-+]middle [-+]right$ NUMBER*left NUMBER*middle NUMBER*right reset
$\backstartnarrow [...,\dots^1,...] [...,\dots^2,...] \dots \backstopnarrow$ 1 inherits: \backsetupnarrower 2 $[-+]left [-+]middle [-+]right$ NUMBER*left NUMBER*middle NUMBER*right reset
$\backstartnegative \dots \backstopnegative$
$\backstartnicelyfilledbox [...,\dots^*,...] \dots \backstopnicelyfilledbox$ * width = DIMENSION * height = DIMENSION * offset = DIMENSION * strut = <u>yes</u> no
$\backstartnointerference \dots \backstopnointerference$
$\backstartnop \dots \backstopnop$
$\backstartnotallmodes [...,*...] \dots \backstopnotallmodes$ * NAME
$\backstartnotext \dots \backstopnotext$
$\backstartnote [...,\dots^*,...] \dots \backstopnote$ * title = TEXT * bookmark = TEXT * list = TEXT * reference = REFERENCE
$\backstopnote [...,*...] \dots \backstopnote$ * REFERENCE
$\backstartnotmode [...,*...] \dots \backstopnotmode$ * NAME
$\backstartoperatortext [...^1...] [...^2...] \dots \backstopoperatortext$ 1 LANGUAGE 2 KEY

<code>\startopposite ... \stopopposite</code>
<code>\startoutputstream [...] ... \stopoutputstream</code> <code>* NAME</code>
<code>\startoverlay ... \stopoverlay</code>
<code>\startoverprint ... \stopoverprint</code>
<code>\startPARSEDXML [...,..¹...,...] ... \stopPARSEDXML</code> <code>* inherits: \setuptyping</code>
<code>\startPARSEDXML [...,..¹...,...] ... \stopPARSEDXML</code> <code>* continue</code>
<code>\startpacked [...] ... \stoppacked</code> <code>* blank</code>
<code>\startpagecomment ... \stoppagecomment</code>
<code>\startpagefigure [...¹.] [...,..²...,...] ... \stoppagefigure</code> <code>1 FILE</code> <code>2 inherits: \setupexternalfigure</code>
<code>\startpagegrid [...¹.] [...,..²...,...] ... \stoppagegrid</code> <code>1 NAME</code> <code>2 inherits: \setuppagegrid</code>
<code>\startpagegridspan [...¹.] [...,..²...,...] ... \stoppagegridspan</code> <code>1 NAME</code> <code>2 inherits: \setuppagegridspan</code>
<code>\startpagegrid [...,..¹...,...] ... \stoppagegrid</code> <code>* inherits: \setuppagegrid</code>
<code>\startpagelayout [...] ... \stoppagelayout</code> <code>* page leftpage rightpage</code>
<code>\startpar [...¹.] [...,..²...,...] ... \stoppar</code> <code>1 NAME</code> <code>2 inherits: \setupparagraph</code>
<code>\startparagraph [...¹.] [...,..²...,...] ... \stopparagraph</code> <code>1 NAME</code> <code>2 inherits: \setupparagraph</code>
<code>\startparagraphs [...] ... \stopparagraphs</code> <code>* NAME</code>

```
\startparagraphscell ... \stopparagraphscell
```

```
\startparagraphs ... \stopparagraphs
```

```
\startparallel ... \stopparallel
```

```
\startparbuilder [...] ... \stopparbuilder
```

```
* default oneline basic NAME
```

```
\startpart [...1...] [...2...] ... \stoppart
```

```
1 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  reference   = REFERENCE
  ownnumber   = TEXT
```

```
2 KEY = VALUE
```

```
\startplacechemical [...1...] [...2...] ... \stopplacechemical
```

```
1 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  location    =
  reference   = REFERENCE
```

```
2 KEY = VALUE
```

```
\startplacefigure [...1...] [...2...] ... \stopplacefigure
```

```
1 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  location    =
  reference   = REFERENCE
```

```
2 KEY = VALUE
```

```
\startplacefloat [...1] [...2...] [...3...] ... \stopplacefloat
```

```
1 SINGULAR
```

```
2 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  location    =
  reference   = REFERENCE
```

```
3 KEY = VALUE
```

```
\startplacefloat [...1...] [...2...] ... \stopplacefloat
```

```
1 title      = TEXT
  bookmark   = TEXT
  marking     = TEXT
  list        = TEXT
  location    =
  reference   = REFERENCE
```

```
2 KEY = VALUE
```

```
\startplaceformula [...*...] ... \stopplaceformula
```

```
* title      = TEXT
  suffix      = TEXT
  reference    = + - TEXT
```

`\startplaceformula [...,*...] ... \stopplaceformula`

* + - REFERENCE

`\startplacegraphic [...,1...] [...,2...] ... \stopplacegraphic`

1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location =
reference = REFERENCE

2 KEY = VALUE

`\startplaceintermezzo [...,1...] [...,2...] ... \stopplaceintermezzo`

1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location =
reference = REFERENCE

2 KEY = VALUE

`\startplacelegend [...,*...] ... \stopplacelegend`

* inherits: \setuppairedbox

`\startplacepairedbox [...,1] [...,2...] ... \stopplacepairedbox`

1 NAME

2 inherits: \setuppairedbox

`\startplacepairedbox [...,*...] ... \stopplacepairedbox`

* inherits: \setuppairedbox

`\startplacetable [...,1...] [...,2...] ... \stopplacetable`

1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location =
reference = REFERENCE

2 KEY = VALUE

`\startpositioning [...,1] [...,2...] ... \stoppositioning`

1 NAME

2 inherits: \setuppositioning

`\startpositionoverlay {...} ... \stoppositionoverlay`

* NAME

`\startpositive ... \stoppositive`

`\startpostponing [...] ... \stoppostponing`

* [-+]NUMBER

<pre> \startprefixtext [...] [...] ... \stopprefixtext 1 LANGUAGE 2 KEY </pre>
<pre> \startprocessassignmentcommand [...,*...,...] ... \stopprocessassignmentcommand * KEY = VALUE </pre>
<pre> \startprocessassignmentlist [...,*...,...] ... \stopprocessassignmentlist * KEY = VALUE </pre>
<pre> \startprocesscommacommand [...,*...] ... \stopprocesscommacommand * COMMAND </pre>
<pre> \startprocesscommalist [...,*...] ... \stopprocesscommalist * COMMAND </pre>
<pre> \startproduct [...] ... \stopproduct * FILE * </pre>
<pre> \startproduct \stopproduct * FILE * </pre>
<pre> \startproject [...] ... \stopproject * FILE * </pre>
<pre> \startproject \stopproject * FILE * </pre>
<pre> \startprotectedcolors ... \stopprotectedcolors </pre>
<pre> \startpsh [...] ... \stoppsh * REFERENCE </pre>
<pre> \startpublication [.¹.] [...,²...,...] ... \stoppublication 1 NAME 2 tag = REFERENCE category = TEXT k = REFERENCE t = TEXT </pre>
<pre> \startquotation [...,*...] ... \stopquotation * inherits: \startnarrower </pre>
<pre> \startquote ... \stopquote </pre>
<pre> \starandomized ... \stoprandomized </pre>

```
1  grid
2  NAME
```

* NAME

* REFERENCE

```
* inherits: \enableregime
```

```

1  NAME
2  NAME
3  TEXT
4  TEXT PROCESSOR->TEXT
5  INDEX

```

```
1  NAME
2  KEY
```

* REFERENCE

```
* hangul hanzi nihongo ethiopic thai test NAME
```

* packed tight middle frame inherits: \setupbodyfont

```
1  title      = TEXT
   bookmark   = TEXT
   marking    = TEXT
   list       = TEXT
   reference  = REFERENCE
   ownnumber  = TEXT

2  KEY = VALUE
```

<pre> \startsectionblock [...¹] [...²...,...] ... \stopsectionblock 1 NAME 2 bookmark = TEXT inherits: \setupsectionblock </pre>
<pre> \startsectionblockenvironment [...[*]] ... \stopsectionblockenvironment * NAME </pre>
<pre> \startsectionblock [...[*]...,...] ... \stopsectionblock * bookmark = TEXT inherits: \setupsectionblock </pre>
<pre> \startsectionlevel [...¹] [...²...,...] [...³...,...] ... \stopsectionlevel 1 NAME 2 title = TEXT bookmark = TEXT marking = TEXT list = TEXT reference = REFERENCE ownnumber = TEXT 3 KEY = VALUE </pre>
<pre> \startsection [...¹...,...] [...²...,...] ... \stopsection 1 title = TEXT bookmark = TEXT marking = TEXT list = TEXT reference = REFERENCE ownnumber = TEXT 2 KEY = VALUE </pre>
<pre> \startsetups [...¹] [...²] ... \stopsetups 1 grid 2 NAME </pre>
<pre> \startsetups \stopsetups * NAME </pre>
<pre> \startshift [...[*]] ... \stopshift * NAME </pre>
<pre> \startsidebar [...¹] [...²...,...] ... \stopsidebar 1 NAME 2 inherits: \setupsidebar </pre>
<pre> \startsimplecolumns [...[*]...,...] ... \stopsimplecolumns * inherits: \setsimplecolumnhsize </pre>
<pre> \startspecialitem [...¹] [...²,...] ... \stopspecialitem 1 <u>item</u> 2 REFERENCE </pre>

`\startspecialitem [...]1 {...}2 ... \stopspecialitem`

1 sym ran mar

2 TEXT

`\startspecialitem [...]* ... \stopspecialitem`

* sub its

`\startspeech [...,*...] ... \stopspeech`

* inherits: \startnarrower

`\startspformula [...,*...] ... \stopspformula`

* packed tight middle frame inherits: \setupbodyfont

`\startspread ... \stopspread`

`\start [...]* ... \stop`

* NAME

`\startstartstop ... \stopstartstop`

`\startstaticMPfigure {...}* ... \stopstaticMPfigure`

* NAME

`\startstaticMPgraphic {...}1 {...,2...} ... \stopstaticMPgraphic`

1 NAME

2 KEY

`\startstop {...}*`

* CONTENT

`\startstrictinspectnextcharacter ... \stopstrictinspectnextcharacter`

`\startstructurepageregister [...]1 [...]2 [...,3...,...] [...,4...,...]`

1 NAME

2 NAME

3 label = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
keys:1 = TEXT
keys:2 = TEXT
keys:3 = TEXT
entries:1 = TEXT
entries:2 = TEXT
entries:3 = TEXT
alternative = TEXT

4 KEY = VALUE

`\startstyle ... \stopstyle`

`\startstyle [...]* ... \stopstyle`

* NAME FONT

`\startstyle [...,..1...,...] ... \stopstyle`

`* inherits: \setupstyle`

`\startsubformulas [...,..*...,...] ... \stopsubformulas`

`* + - REFERENCE`

`\startsubject [...,..1...,...] [...,..2...,...] ... \stopsubject`

1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
reference = REFERENCE
ownnumber = TEXT

2 KEY = VALUE

`\startsubjectlevel [...,..1...,...] [...,..2...,...] [...,..3...,...] ... \stopsubjectlevel`

1 NAME

2 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
reference = REFERENCE
ownnumber = TEXT

3 KEY = VALUE

`\startsubsection [...,..1...,...] [...,..2...,...] ... \stopsubsection`

1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
reference = REFERENCE
ownnumber = TEXT

2 KEY = VALUE

`\startsubsentence ... \stopsubsentence`

`\startsubstack ... \stopsubstack`

`\startsubsubject [...,..1...,...] [...,..2...,...] ... \stopsubsubject`

1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
reference = REFERENCE
ownnumber = TEXT

2 KEY = VALUE

`\startsubsubsection [...,..1...,...] [...,..2...,...] ... \stopsubsubsection`

1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
reference = REFERENCE
ownnumber = TEXT

2 KEY = VALUE


```
\startsubsubsubject [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubject
```

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference  = REFERENCE
  ownnumber  = TEXT
```

```
2 KEY = VALUE
```

```
\startsubsubsubsection [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubsection
```

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference  = REFERENCE
  ownnumber  = TEXT
```

```
2 KEY = VALUE
```

```
\startsubsubsubsubject [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubsubject
```

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference  = REFERENCE
  ownnumber  = TEXT
```

```
2 KEY = VALUE
```

```
\startsubsubsubsubsection [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubsubsection
```

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference  = REFERENCE
  ownnumber  = TEXT
```

```
2 KEY = VALUE
```

```
\startsubsubsubsubsubject [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubsubsubject
```

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference  = REFERENCE
  ownnumber  = TEXT
```

```
2 KEY = VALUE
```

```
\startsymbolset [...] ... \stopsymbolset
```

```
* NAME
```

```
\startTABLE [...,\superscript{...},...] ... \stopTABLE
```

```
* inherits: \setupTABLE
```

```
\startTABLEbody [...,\superscript{...},...] ... \stopTABLEbody
```

```
* inherits: \setupTABLE
```

```
\startTABLEfoot [...,\superscript{...},...] ... \stopTABLEfoot
```

```
* inherits: \setupTABLE
```

<pre> \startTABLEhead [...,\u003d...,...] ... \stopTABLEhead * inherits: \setupTABLE </pre>
<pre> \startTABLEnext [...,\u003d...,...] ... \stopTABLEnext * inherits: \setupTABLE </pre>
<pre> \startTEXpage [...,\u003d...,...] ... \stopTEXpage * inherits: \setupfittingpage </pre>
<pre> \startTEX [...,\u003d...,...] ... \stopTEX * inherits: \setuptyping </pre>
<pre> \startTEX [...,\u003d,...] ... \stopTEX * continue </pre>
<pre> \starttablehead [...] ... \stoptablehead * NAME </pre>
<pre> \starttables [...] ... \stoptables * TEMPLATE </pre>
<pre> \starttables [...] ... \stoptables * NAME </pre>
<pre> \starttabletail [...] ... \stoptabletail * NAME </pre>
<pre> \starttabletext [...,\u00b9,...] [...,\u00b2,...] {...} ... \stoptabletext 1 2 REFERENCE 3 TEXT </pre>
<pre> \starttable [...,\u00b9,...] [...,\u00b2...,...] ... \stoptable 1 TEMPLATE 2 inherits: \setuptables </pre>
<pre> \starttable [...,\u00b9,...] [...,\u00b2...,...] ... \stoptable 1 NAME 2 inherits: \setuptables </pre>
<pre> \starttabulate [...,\u00b9,...] [...,\u00b2...,...] ... \stoptabulate 1 TEMPLATE 2 inherits: \setuptabulate </pre>
<pre> \starttabulatehead [...] ... \stoptabulatehead * NAME </pre>

<code>\starttabulatetail [...] ... \stoptabulatetail</code> <code>* NAME</code>
<code>\starttabulate [¹.] [...²...,...] ... \stoptabulate</code> <code>1 NAME</code> <code>2 inherits: \setuptabulate</code>
<code>\starttabulation [¹.] [...²...,...] ... \stoptabulation</code> <code>1 NAME</code> <code>2 inherits: \setuptabulation</code>
<code>\starttaglabeltext [¹.] [².] ... \stoptaglabeltext</code> <code>1 LANGUAGE</code> <code>2 KEY</code>
<code>\starttexcode ... \stoptexcode</code>
<code>\starttexdefinition ¹... ²... ³... ⁴... ⁵... ⁶... ... \stoptexdefinition</code> <code>1 spaces nospaces</code> <code>2 global</code> <code>3 unexpanded</code> <code>4 expanded</code> <code>5 NAME</code> <code>6 TEMPLATE</code>
<code>\starttext ... \stoptext</code>
<code>\starttextbackground [¹.] [...²...,...] ... \stoptextbackground</code> <code>1 NAME</code> <code>2 inherits: \setuptextbackground</code>
<code>\starttextbackgroundmanual ... \stoptextbackgroundmanual</code>
<code>\starttextbackground [...[*]...,...] ... \stoptextbackground</code> <code>* inherits: \setuptextbackground</code>
<code>\starttextcolor [...] ... \stoptextcolor</code> <code>* COLOR</code>
<code>\starttextcolorintent ... \stoptextcolorintent</code>
<code>\starttextflow [...] ... \stoptextflow</code> <code>* NAME</code>
<code>\starttextrule {...} ... \stoptextrule</code> <code>* TEXT</code>

`\starttitle [...,1...,...] [...,2...,...] ... \stoptitle`

1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
reference = REFERENCE
ownnumber = TEXT

2 KEY = VALUE

`\starttokens [...] ... \stoptokens`

* NAME

`\starttransparent [...] ... \stoptransparent`

* COLOR

`\starttxt ... \stoptxt`

`\starttypescript [...,1...,...] [...,2...,...] [...,3...,...] ... \stoptypescript`

1 serif sans mono math handwriting calligraphy

2 NAME

3 size name

`\starttypescriptcollection [...] ... \stoptypescriptcollection`

* NAME

`\starttyping [...,*...,...] ... \stoptyping`

* inherits: \setuptyping

`\starttyping [...,*...,...] ... \stoptyping`

* continue

`\starttyping [...,*...,...] ... \stoptyping`

* inherits: \setuptyping

`\starttyping [...,*...,...] ... \stoptyping`

* continue

`\startuniqueMPgraphic {.1.} {...,2...,...} ... \stopuniqueMPgraphic`

1 NAME

2 KEY

`\startuniqueMPpagegraphic {.1.} {...,2...,...} ... \stopuniqueMPpagegraphic`

1 NAME

2 KEY

`\startunittext [...,1.] [...,2.] ... \stopunittext`

1 LANGUAGE

2 KEY

`\startunpacked ... \stopunpacked`

$\backslash\text{startusableMPgraphic } \{.^1.\} \{.^2.,...\} \dots \backslash\text{stopusableMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startuseMPgraphic } \{.^1.\} \{.^2.,...\} \dots \backslash\text{stopuseMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startusemathstyleparameter } \backslash.^* \dots \backslash\text{stopusemathstyleparameter}$ * CSNAME
$\backslash\text{startusingbtxs specification } [.^*] \dots \backslash\text{stopusingbtxs specification}$ * NAME
$\backslash\text{startvboxtohbox } \dots \backslash\text{stopvboxtohbox}$
$\backslash\text{startvboxtohboxseparator } \dots \backslash\text{stopvboxtohboxseparator}$
$\backslash\text{startviewerlayer } [.^*] \dots \backslash\text{stopviewerlayer}$ * NAME
$\backslash\text{startviewerlayer } \dots \backslash\text{stopviewerlayer}$
$\backslash\text{startXML } [^*] \dots \backslash\text{stopXML}$ * inherits: $\backslash\text{setuptyping}$
$\backslash\text{startXML } [...] \dots \backslash\text{stopXML}$ * continue
$\backslash\text{startxcell } [.^1.] [.^2.,...,] \dots \backslash\text{stopxcell}$ 1 NAME 2 nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxcellgroup } [.^1.] [.^2.,...,] \dots \backslash\text{stopxcellgroup}$ 1 NAME 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxgroup } [...] [.^2.,...,] \dots \backslash\text{stopxgroup}$ 1 NAME 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxmldisplayverbatim } [.^*] \dots \backslash\text{stopxmldisplayverbatim}$ * NAME
$\backslash\text{startxmlinlineverbatim } [.^*] \dots \backslash\text{stopxmlinlineverbatim}$ * NAME

<code>\startxmlraw ... \stopxmlraw</code>
<code>\startxmlsetups [...] [...] ... \stopxmlsetups</code> 1 <code>grid</code> 2 <code>NAME</code>
<code>\startxmlsetups \stopxmlsetups</code> * <code>NAME</code>
<code>\startxrow [...] [...] ... \stopxrow</code> 1 <code>NAME</code> 2 <code>inherits: \setupxtable</code>
<code>\startxrowgroup [...] [...] ... \stopxrowgroup</code> 1 <code>NAME</code> 2 <code>inherits: \setupxtable</code>
<code>\startxtablebody [..., ...*, ..., ...] ... \stopxtablebody</code> * <code>inherits: \setupxtable</code>
<code>\startxtablebody [...] ... \stopxtablebody</code> * <code>NAME</code>
<code>\startxtablefoot [..., ...*, ..., ...] ... \stopxtablefoot</code> * <code>inherits: \setupxtable</code>
<code>\startxtablefoot [...] ... \stopxtablefoot</code> * <code>NAME</code>
<code>\startxtablehead [..., ...*, ..., ...] ... \stopxtablehead</code> * <code>inherits: \setupxtable</code>
<code>\startxtablehead [...] ... \stopxtablehead</code> * <code>NAME</code>
<code>\startxtablenext [..., ...*, ..., ...] ... \stopxtablenext</code> * <code>inherits: \setupxtable</code>
<code>\startxtablenext [...] ... \stopxtablenext</code> * <code>NAME</code>
<code>\startxtable [..., ...*, ..., ...] ... \stopxtable</code> * <code>inherits: \setupxtable</code>
<code>\startxtable [..., ...*, ..., ...] ... \stopxtable</code> * <code>inherits: \setupxtable</code>

<code>\startxtable [...]</code> ... <code>\stopxtable</code> * NAME
<code>\stopline [...]</code> * REFERENCE
<code>\stoplinenote [...]</code> * REFERENCE
<code>\stoplinenote [...]</code> * REFERENCE
<code>\stopregister [...]</code> <code>[...]</code> 1 NAME 2 NAME
<code>\stopstructurepageregister [...]</code> <code>[...]</code> 1 NAME 2 NAME
<code>\stretched [...]</code> <code>[...]</code> <code>{...}</code> 1 inherits: <code>\setupstretched</code> 2 TEXT
<code>\strictdoifelsenextoptional {...}</code> <code>{...}</code> 1 TRUE 2 FALSE
<code>\strictdoifnnextoptionalelse {...}</code> <code>{...}</code> 1 TRUE 2 FALSE
<code>\stripcharacter ...</code> <code>\from ...</code> <code>\to ...</code> 1 CHARACTER 2 TEXT 3 CSNAME
<code>\strippedcsname \...</code> * CSNAME
<code>\strippedcsname ...</code> * TEXT
<code>\stripspaces \from ...</code> <code>\to ...</code> 1 TEXT 2 CSNAME

<code>\structurelistuservariable {...}</code> * KEY
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\styleinstance [...]</code> * NAME
<code>\style {...}</code> * TEXT
<code>\style [...¹] {...²}</code> 1 NAME FONT 2 TEXT
<code>\style [...,¹...²] {...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\subject [...,¹...] {...²}</code> 1 REFERENCE 2 TEXT
<code>\subpagenumber</code>
<code>\subsection [...,¹...] {...²}</code> 1 REFERENCE 2 TEXT

\subsentence {...} * CONTENT
\substituteincommalist {...} {...} \ ³ .. 1 TEXT 2 TEXT 3 CSNAME
\subsubject [..., ¹ ...] {.. ² .} 1 REFERENCE 2 TEXT
\subsubsection [..., ¹ ...] {.. ² .} 1 REFERENCE 2 TEXT
\subsubsubject [..., ¹ ...] {.. ² .} 1 REFERENCE 2 TEXT
\subsubsubsection [..., ¹ ...] {.. ² .} 1 REFERENCE 2 TEXT
\subsubsubsubject [..., ¹ ...] {.. ² .} 1 REFERENCE 2 TEXT
\subsubsubsubsection [..., ¹ ...] {.. ² .} 1 REFERENCE 2 TEXT
\subsubsubsubsubject [..., ¹ ...] {.. ² .} 1 REFERENCE 2 TEXT
\subsubsubsubsubsection [..., ¹ ...] {.. ² .} 1 REFERENCE 2 TEXT
\subsubsubsubsubsubject [..., ¹ ...] {.. ² .} 1 REFERENCE 2 TEXT
\subtractfeature [...] * NAME
\subtractfeature {...} * NAME
\sub
\swapcounts \ ¹ .. \ ² .. 1 CSNAME 2 CSNAME

<code>\swapdimens \¹ \²</code> 1 CSNAME 2 CSNAME
<code>\swapface</code>
<code>\swapmacros \¹ \²</code> 1 CSNAME 2 CSNAME
<code>\swaptypeface</code>
<code>\switchstyleonly [...]</code> * rm ss tt hw cg roman serif regular sans sansserif support type teletype mono handwritten calligraphic
<code>\switchstyleonly *</code> * CSNAME
<code>\switchtobodyfont [...*,...]</code> * inherits: \setupbodyfont
<code>\switchtocolour [...]</code> * COLOR
<code>\switchtointerlinespace [...,¹...] [...,²...,...]</code> 1 NAME 2 inherits: \setupinterlinespace
<code>\switchtointerlinespace [...*,...]</code> * on off reset auto small medium big NUMBER DIMENSION
<code>\switchtointerlinespace [...]</code> * NAME
<code>\symbolreference [...]</code> * REFERENCE
<code>\symbol [...¹] [...²]</code> 1 NAME 2 NAME
<code>\symbol {...}</code> * NAME
<code>\sym {...}</code> * TEXT
<code>\synchronizeblank</code>

<code>\synchronizeindenting</code>
<code>\synchronizemarking [...]¹ [...]² [...]³</code> 1 MARK 2 NUMBER 3 keep
<code>\synchronizeoutputstreams [...,*,...]</code> * NAME
<code>\synchronizestrut {...[*]}</code> *
<code>\synchronizewhitespace</code>
<code>\synonym [...]¹ {...}² {...}³</code> 1 NAME 2 TEXT 3 CONTENT
<code>\systemlog {...}¹ {...}² {...}³</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemlogfirst {...}¹ {...}² {...}³</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemloglast {...}¹ {...}² {...}³</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemsetups {...[*]}</code> * NAME
<code>\TABLE</code>
<code>\TaBlE</code>
<code>\TEX</code>
<code>\TeX</code>
<code>\TheNormalizedFontSize</code>

<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> * COMMAND
<code>\taggedlabeltexts {...} {...} {...}</code> 1 NAME 2 NAME 3 CONTENT
<code>\taglabellanguage</code>
<code>\taglabeltext {...}</code> * KEY
<code>\tbinom {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\tbox {...}</code> * CONTENT
<code>\tequal {...} {...}</code> 1 TEXT 2 TEXT
<code>\testandsplitstring .¹. \at .². \to \³. \and \⁴.</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\testcolumn [¹.] [².]</code> 1 NUMBER 2 DIMENSION
<code>\testfeature {...}</code> * NUMBER

`\testfeatureonce {...}`

* NUMBER

`\testpage [...]1 [...]2`

1 NUMBER

2 DIMENSION

`\testpageonly [...]1 [...]2`

1 NUMBER

2 DIMENSION

`\testpagesync [...]1 [...]2`

1 NUMBER

2 DIMENSION

`\testtokens [...]`

* NAME

`\tex {...}`

* CONTENT

`\texdefinition {...}`

* NAME

`\texsetup {...}`

* NAME

`\textbackground {...}`

* CONTENT

`\textcitation [...]1 [...]2`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 REFERENCE

`\textcitation [...]1 [...]2`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 KEY = VALUE

`\textcitation [...]1 [...]2`

1

2 REFERENCE

`\textcite [...1...] [...2]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 REFERENCE

`\textcite [...1...] [...2...]`

1 reference = REFERENCE
alternative =
before = COMMAND
after = COMMAND
left = COMMAND
right = COMMAND
inherits: \setupbtx

2 KEY = VALUE

`\textcite [...1] [...2]`

1

2 REFERENCE

`\textcontrolspace`

`\textflowcollector {...}`

* NAME

`\textmath {...}`

* CONTENT

`\textminus`

`\textormathchar {...}`

* NUMBER

`\textplus`

`\textreference [...1,...] {...2}`

1 REFERENCE

2 TEXT

`\textrule [...1] {...2}`

1 top middle bottom

2 TEXT

`\textvisiblespace`

`\tfrac {...1} {...2}`

1 CONTENT

2 CONTENT

<code>\thai</code>
<code>\thainumerals {...}</code> * NUMBER
<code>\thefirstcharacter {...}</code> * TEXT
<code>\thenormalizedbodyfontsize {...}</code> * DIMENSION
<code>\theremainingcharacters {...}</code> * TEXT
<code>\thickspace</code>
<code>\thinrule</code>
<code>\thinrules [...,...*=...,...]</code> * inherits: \setupthinrules
<code>\thinspace</code>
<code>\thirddoffivearguments {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\thirddoffourarguments {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\thirddofsixarguments {...} {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\thirddofthreearguments {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT

`\thirdofthreeunexpanded {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\thookleftarrow {...} {...}`

- 1 TEXT
- 2 TEXT

`\thookrightarrow {...} {...}`

- 1 TEXT
- 2 TEXT

`\threedigitrounding {...}`

- * NUMBER

`\tibetannumerals {...}`

- * NUMBER

`\tightlayer [...]`

- * NAME

`\tilde {...}`

- * CHARACTER

`\tinyfont`

`\title [...1,...] {...2}`

- 1 REFERENCE
- 2 TEXT

`\tLeftarrow {...} {...2}`

- 1 TEXT
- 2 TEXT

`\tLeftrightarrow {...} {...2}`

- 1 TEXT
- 2 TEXT

`\tlap {...}`

- * CONTENT

`\tleftarrow {...} {...2}`

- 1 TEXT
- 2 TEXT

`\tleftharpoondown {...} {...}`

1 TEXT

2 TEXT

`\tleftharpoonup {...} {...}`

1 TEXT

2 TEXT

`\tleftrightarrow {...} {...}`

1 TEXT

2 TEXT

`\tleftrightharpoons {...} {...}`

1 TEXT

2 TEXT

`\tmapsto {...} {...}`

1 TEXT

2 TEXT

`\tochar {...}`

* NAME

`\tolinenote [...]`

* REFERENCE

`\tooltip [...,\stackrel{.1}{=},...] {...} {...}`

1 inherits: \setuptooltip

2 TEXT

3 TEXT

`\tooltip [...] {...} {...}`

1 left middle right

2 TEXT

3 TEXT

`\tooltip [...,\stackrel{.1}{=},...] {...} {...}`

1 inherits: \setuptooltip

2 TEXT

3 TEXT

`\tooltip [...] {...} {...}`

1 left middle right

2 TEXT

3 TEXT

<code>\topbox {...}</code> * CONTENT
<code>\topleftbox {...}</code> * CONTENT
<code>\toplinebox {...}</code> * CONTENT
<code>\toprightbox {...}</code> * CONTENT
<code>\topskippedbox {...}</code> * CONTENT
<code>\tRrightarrow {...} {...}</code> 1 TEXT 2 TEXT
<code>\tracecatcodetables</code>
<code>\tracedfontname {...}</code> * FONT
<code>\traceoutputroutines</code>
<code>\tracepositions</code>
<code>\translate [...]*=...,...</code> * LANGUAGE = TEXT
<code>\transparencycomponents {...}</code> * COLOR
<code>\transparent [...]¹ {...}²</code> 1 COLOR 2 CONTENT
<code>\trel {...}¹ {...}²</code> 1 TEXT 2 TEXT
<code>\trightarrow {...}¹ {...}²</code> 1 TEXT 2 TEXT

$\backslash\mathrm{trightharpoonowdown}\{\ldots\}\{\ldots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{trightharpoonoup}\{\ldots\}\{\ldots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{trightleftharpoons}\{\ldots\}\{\ldots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{trightoverleftarrow}\{\ldots\}\{\ldots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{triplebond}$
$\backslash\mathrm{truefilename}\{.\ast.\}$ * FILE
$\backslash\mathrm{truefontname}\{.\ast.\}$ * FONT
$\backslash\mathrm{ttraggedright}$
$\backslash\mathrm{ttriplerel}\{\ldots\}\{\ldots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{twoheadleftarrow}\{\ldots\}\{\ldots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{twoheadrightarrow}\{\ldots\}\{\ldots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{twodigitrounding}\{.\ast.\}$ * NUMBER
$\backslash\mathrm{tx}$
$\backslash\mathrm{txt}\ldots\backslash\backslash$ * TEXT

<p><code>\txt {¹...} [...,²...]</code></p> <p>1 TEXT</p> <p>2 REFERENCE</p>
<p><code>\txx</code></p>
<p><code>\typebuffer [...,¹...] [...,²...]</code></p> <p>1 BUFFER</p> <p>2 inherits: \setuptyping</p>
<p><code>\typebuffer [...,[*]...]</code></p> <p>* inherits: \setuptyping</p>
<p><code>\typedefinedbuffer [¹...] [...,²...]</code></p> <p>1 BUFFER</p> <p>2 inherits: \setuptyping</p>
<p><code>\typeface</code></p>
<p><code>\typefile [¹...] [...,²...] {³...}</code></p> <p>1 NAME</p> <p>2 inherits: \setuptyping</p> <p>3 FILE</p>
<p><code>\typescriptone</code></p>
<p><code>\typescriptprefix {[*]...}</code></p> <p>* NAME</p>
<p><code>\typescriptthree</code></p>
<p><code>\typescripttwo</code></p>
<p><code>\typesetbuffer [¹...] [...,²...]</code></p> <p>1 * BUFFER</p> <p>2 inherits: \setupexternalfigure</p>
<p><code>\typesetfile [¹...] [²...] [...,³...]</code></p> <p>1 NAME FILE</p> <p>2 FILE TEXT</p> <p>3 inherits: \setupexternalfigure</p>
<p><code>\type [...,¹...] {²...}</code></p> <p>1 inherits: \setuptype</p> <p>2 CONTENT</p>

$\backslash type [\dots\overset{1}{=}\dots] <<\overset{2}{\dots}>$ 1 inherits: $\backslash setuptype$ 2 ANGLES
$\backslash type [\dots\overset{1}{=}\dots] \{\overset{2}{\dots}\}$ 1 inherits: $\backslash setuptype$ 2 CONTENT
$\backslash type [\dots\overset{1}{=}\dots] <<\overset{2}{\dots}>$ 1 inherits: $\backslash setuptype$ 2 ANGLES
$\backslash typ [\dots\overset{1}{=}\dots] \{\overset{2}{\dots}\}$ 1 inherits: $\backslash setuptype$ 2 CONTENT
$\backslash typ [\dots\overset{1}{=}\dots] <<\overset{2}{\dots}>$ 1 inherits: $\backslash setuptype$ 2 ANGLES
$\backslash uconvertnumber \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 inherits: $\backslash convertnumber$ 2 NUMBER
$\backslash uedcatcodecommand \overset{1}{\dots} \overset{2}{\dots} \{\overset{3}{\dots}\}$ 1 CSNAME 2 CHARACTER NUMBER 3 COMMAND
$\backslash undefinevalue \{\dots\}$ * NAME
$\backslash undepthed \{\dots\}$ * CONTENT
$\backslash underbar \{\dots\}$ * CONTENT
$\backslash underbars \{\dots\}$ * CONTENT
$\backslash underbartext \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 TEXT 2 TEXT
$\backslash underbrace \{\dots\}$ * TEXT

$$\underbrace{\text{...}}^{.1} \underbrace{\text{...}}^{.2}$$

1 TEXT

2 TEXT

`\underbracket {.*.}`

* TEXT

`\underbrackettext {..1..} {..2..}`

1 TEXT

2 TEXT

 $\underdash \{...\}$

* CONTENT

`\underdashes {...}`

* CONTENT

 $\backslash\mathrm{underdot} \{.\!.\!. \}$

* CONTENT

 $\backslash\mathrm{underdotes} \{.\!.\!.\}$

* CONTENT

 $\underleftarrow{\{...\}}$

* TEXT

$$\underleftarrow{\hspace{1cm}} \{...\}$$

* TEXT

 $\underleftarrow{\hspace{1cm}} \{...\}$

* TEXT

 $\underleftrightarrow{...}$

* TEXT

`\underparent {...}`

* TEXT

`\underparenttext {..1.} {..2.}`

1 TEXT

2 TEXT

 $\underset{\text{random}}{\{...\}}$

* CONTENT

`\underrandoms {...}`

* CONTENT

\rightarrow <code>\underrightarrow {...}</code> * TEXT
\downarrow <code>\underrightharpoondown {...}</code> * TEXT
\uparrow <code>\underrightharpoonup {...}</code> * TEXT
$\underset{\text{TEXT}}{\text{TEXT}}$ <code>\underset {...} {...}</code> 1 TEXT 2 TEXT
CONTENT <code>\understrike {...}</code> * CONTENT
CONTENT <code>\understrikes {...}</code> * CONTENT
\leftarrow <code>\undertwoheadleftarrow {...}</code> * TEXT
\rightarrow <code>\undertwoheadrightarrow {...}</code> * TEXT
$\text{KEY} = \text{VALUE}$ <code>\undoassign [...] [...=...]</code> 1 TEXT 2 KEY = VALUE
CONTENT <code>\unframed [...,\overset{1}{...},...] {...}</code> 1 inherits: \setupframed 2 CONTENT
CSNAME NUMBER <code>\unhhbox ... \with {...}</code> 1 CSNAME NUMBER 2 COMMAND
NUMBER <code>\unihex {...}</code> * NUMBER
$\text{KEY} = \text{VALUE}$ <code>\uniqueMPgraphic {...} {...,\overset{2}{...},...}</code> 1 NAME 2 KEY = VALUE
$\text{KEY} = \text{VALUE}$ <code>\uniqueMPpagegraphic {...} {...,\overset{2}{...},...}</code> 1 NAME 2 KEY = VALUE

<code>\unit {...}</code> * CONTENT
<code>\unitlanguage</code>
<code>\unittext {...}</code> * KEY
<code>\unit {...}</code> * CONTENT
<code>\unknown</code>
<code>\unprotect ... \protect</code>
<code>\unprotected ... \par</code> * CONTENT
<code>\unregisterhyphenationpattern [...] [...]</code> 1 LANGUAGE 2 TEXT
<code>\unspaceafter ... {...}</code> 1 CSNAME 2 TEXT
<code>\unspaceargument ... \to ...</code> 1 TEXT 2 CSNAME
<code>\unspaced {...}</code> * TEXT
<code>\unspacestring ... \to ...</code> 1 TEXT 2 CSNAME
<code>\untexargument {...} \to ...</code> 1 TEXT 2 CSNAME
<code>\untexcommand {...} \to ...</code> 1 CSNAME 2 CSNAME
<code>\uppercased {...}</code> * TEXT

<code>\uppercasestring ¹... \to ²...</code> 1 TEXT 2 CSNAME
<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\url [...]</code> * NAME
<code>\usealignparameter *</code> * CSNAME
<code>\useblankparameter *</code> * CSNAME
<code>\useblocks [...¹,...] [...²,...] [...³,...,...]</code> 1 NAME 2 + - 3 criterium = <u>text</u> SECTION
<code>\usebodyfont [...*,...]</code> * inherits: \setupbodyfont
<code>\usebodyfontparameter *</code> * CSNAME
<code>\usebtxdataset [...¹] [...²] [...³,...,...]</code> 1 NAME 2 FILE 3 specification = NAME
<code>\usebtxdefinitions [...*]</code> * FILE

<pre>\usecolors [...]</pre> <p>* FILE</p>
<pre>\usecomponent [...]</pre> <p>* FILE</p>
<pre>\usedummycolorparameter {...}</pre> <p>* KEY</p>
<pre>\usedummystyleandcolor {...} {...}</pre> <p>1 KEY</p> <p>2 KEY</p>
<pre>\usedummystyleparameter {...}</pre> <p>* KEY</p>
<pre>\useenvironment [...]</pre> <p>* FILE</p>
<pre>\useexternaldocument [...]¹ [...]² [...]³</pre> <p>1 NAME</p> <p>2 FILE</p> <p>3 TEXT</p>
<pre>\useexternalfigure [...]¹ [...]² [...]³ [...]⁴₌...,...</pre> <p>1 NAME</p> <p>2 FILE</p> <p>3 NAME</p> <p>4 inherits: \setupexternalfigure</p>
<pre>\useexternalrendering [...]¹ [...]² [...]³ [...]⁴</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 FILE</p> <p>4 auto embed</p>
<pre>\useexternalsoundtrack [...]¹ [...]²</pre> <p>1 NAME</p> <p>2 FILE</p>
<pre>\usefigurebase [...]</pre> <p>* reset FILE</p>
<pre>\usefile [...]¹ [...]² [...]³</pre> <p>1 NAME</p> <p>2 FILE</p> <p>3 TEXT</p>

<pre>\usegridparameter *..</pre> <pre>* CSNAME</pre>
<pre>\useindentingparameter *..</pre> <pre>* CSNAME</pre>
<pre>\useindentnextparameter *..</pre> <pre>* CSNAME</pre>
<pre>\useinterlinespaceparameter *..</pre> <pre>* CSNAME</pre>
<pre>\useJSscripts [...]¹ [...,²...]</pre> <pre>1 FILE</pre> <pre>2 NAME</pre>
<pre>\uselanguageparameter *..</pre> <pre>* CSNAME</pre>
<pre>\uselua module [...]</pre> <pre>* FILE</pre>
<pre>\useMPenvironmentbuffer [...]</pre> <pre>* NAME</pre>
<pre>\useMPgraphic {...}¹ {...,²...}</pre> <pre>1 NAME</pre> <pre>2 KEY = VALUE</pre>
<pre>\useMPlibrary [...]</pre> <pre>* FILE</pre>
<pre>\useMPrun {...}¹ {...}²</pre> <pre>1 NAME</pre> <pre>2 NUMBER</pre>
<pre>\useMPvariables [...]¹ [...,²...]</pre> <pre>1 NAME</pre> <pre>2 KEY</pre>
<pre>\usemathstyleparameter *..</pre> <pre>* CSNAME</pre>
<pre>\usemodule [...]¹ [...,²...]³ [...,³...]</pre> <pre>1 m p s x t</pre> <pre>2 FILE</pre> <pre>3 KEY = VALUE</pre>

<code>\usepath [...,*,...]</code> * FILE
<code>\useproduct [...]</code> * FILE
<code>\useprofileparameter *..</code> * CSNAME
<code>\useproject [...]</code> * FILE
<code>\userferenceparameter *..</code> * CSNAME
<code>\userpagenumber</code>
<code>\usesetupsparemeter *..</code> * CSNAME
<code>\usestaticMPfigure [...,¹...²...]</code> 1 inherits: \setupscale 2 NAME
<code>\usesubpath [...,*,...]</code> * FILE
<code>\usesymbols [...]</code> * FILE
<code>\usetexmodule [...¹] [...²,...]</code> <code>[...³...]</code> 1 m p s x t 2 FILE 3 KEY = VALUE
<code>\usetypescript [...¹] [...²] [...³]</code> 1 serif sans mono math handwriting calligraphy casual all 2 NAME fallback default dtp simple 3 size name
<code>\usetypescriptfile [...]</code> * reset FILE
<code>\useURL [...¹] [...²] [...³] [...⁴]</code> 1 NAME 2 URL 3 FILE 4 TEXT

<code>\useurl [...]¹ [...]² [...]³ [...]⁴</code> 1 NAME 2 URL 3 FILE 4 TEXT
<code>\usezipfile [...]¹ [...]²</code> 1 FILE 2 FILE
<code>\utfchar {...}</code> * NUMBER
<code>\utflower {...}</code> * TEXT
<code>\utfupper {...}</code> * TEXT
<code>\utilityregisterlength</code>
<code>\VerboseNumber {...}</code> * NUMBER
<code>\vboxreference [...]¹, [...]² {...}</code> 1 REFERENCE 2 CONTENT
<code>\vec {...}</code> * CHARACTER
<code>\verbatim {...}</code> * CONTENT
<code>\verbatimstring {...}</code> * CONTENT
<code>\verbozenumber {...}</code> * NUMBER
<code>\version [...]</code> * concept file temporary final NAME
<code>\verticalgrowingbar [...][*] [...]</code> * inherits: \setuppositionbar
<code>\verticalpositionbar [...][*] [...]</code> * inherits: \setuppositionbar

<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\vglue ...</code> <code>* DIMENSION</code>
<code>\viewerlayer [...]{...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\vl [...]</code> <code>* NUMBER</code>
<code>\vphantom {...}</code> <code>* CONTENT</code>
<code>\vpos {...}{...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\vsmash {...}</code> <code>* CONTENT</code>
<code>\vsmashbox ...</code> <code>* CSNAME NUMBER</code>
<code>\vsmashed {...}</code> <code>* CONTENT</code>
<code>\vspace [...]{...}</code> <code>1 NAME</code> <code>2 NAME</code>
<code>\vspacing [...]{...}</code> <code>* preference samepage max force enable disable nowhite back overlay always weak strong default before inbetween</code> <code> after fixed flexible none small medium big line halfline quarterline formula white height depth standard NUMBER*small</code> <code> NUMBER*medium NUMBER*big NUMBER*line NUMBER*halfline NUMBER*quarterline NUMBER*formula NUMBER*white NUMBER*height</code> <code> NUMBER*depth category:NUMBER order:NUMBER penalty:NUMBER DIMENSION NAME</code>
<code>\WEEKDAY {...}</code> <code>* NUMBER</code>
<code>\WidthSpanningText {...}{...}{...}</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 FONT</code>

<p><code>\WORD {...}</code></p> <p>* TEXT</p>
<p><code>\WORDS {...}</code></p> <p>* TEXT</p>
<p><code>\Word {...}</code></p> <p>* TEXT</p>
<p><code>\Words {...}</code></p> <p>* TEXT</p>
<p><code>\wdofstring {...}</code></p> <p>* TEXT</p>
<p><code>\weekday {...}</code></p> <p>* NUMBER</p>
<p><code>\widthofstring {...}</code></p> <p>* TEXT</p>
<p><code>\widthspanningtext {...¹} {...²} {...³}</code></p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>
<p><code>\withoutpt {...}</code></p> <p>* DIMENSION</p>
<p><code>\word {...}</code></p> <p>* TEXT</p>
<p><code>\wordright [...¹] {...²}</code></p> <p>1 right DIMENSION</p> <p>2 CONTENT</p>
<p><code>\words {...}</code></p> <p>* TEXT</p>
<p><code>\wordtonumber {...¹} {...²}</code></p> <p>1 one two three four five</p> <p>2 TEXT</p>
<p><code>\writebetweenlist [...¹] [...,²...,...] {...³}</code></p> <p>1 LIST</p> <p>2 inherits: \setuplist</p> <p>3 COMMAND</p>

`\writedatatolist [...]1 [...,...2...,...]2 [...,...3...,...]3`

- 1 LIST
- 2 inherits: \setuplist
- 3 KEY = VALUE

`\writestatus {...}1 {...}2`

- 1 TEXT
- 2 TEXT

`\writetolist [...]1 [...,...2...,...]2 {...}3 {...}4`

- 1 LIST
- 2 inherits: \setuplist
- 3 NUMBER
- 4 TEXT

`\XETEX`

`\XeTeX`

`\xdefconvertedargument \...1 {...}2`

- 1 CSNAME
- 2 TEXT

`\xequal {...}1 {...}2`

- 1 TEXT
- 2 TEXT

`\xfrac {...}1 {...}2`

- 1 CONTENT
- 2 CONTENT

`\xhookleftarrow {...}1 {...}2`

- 1 TEXT
- 2 TEXT

`\xhookrightarrow {...}1 {...}2`

- 1 TEXT
- 2 TEXT

`\xLeftarrow {...}1 {...}2`

- 1 TEXT
- 2 TEXT

`\xLeftrightarrow {...}1 {...}2`

- 1 TEXT
- 2 TEXT

`\xleftarrow {...} {...}`

1 TEXT

2 TEXT

`\xleftharpoondown {...} {...}`

1 TEXT

2 TEXT

`\xleftharpoonup {...} {...}`

1 TEXT

2 TEXT

`\xleftrightharpoonrightarrow {...} {...}`

1 TEXT

2 TEXT

`\xleftrightharpoons {...} {...}`

1 TEXT

2 TEXT

`\xmapsto {...} {...}`

1 TEXT

2 TEXT

`\xmladdindex {...}`

* NODE

`\xmllafterdocumentsetup {...} {...} {...}`

1 NAME

2 SETUP

3 SETUP

`\xmllaftersetup {...} {...}`

1 SETUP

2 SETUP

`\xmlall {...} {...}`

1 NODE

2 LPATH

`\xmlappenddocumentsetup {...} {...}`

1 NAME

2 SETUP

`\xmlappendsetup {...}`

* SETUP

\xmlapplyselectors {...}

* NODE

\xmlatt {...} {...}

1 NODE

2 NAME

\xmlattdef {...} {...} {...}

1 NODE

2 NAME

3 TEXT

\xmlattribute {...} {...} {...}

1 NODE

2 LPATH

3 NAME

\xmlattributedef {...} {...} {...} {...}

1 NODE

2 LPATH

3 NAME

4 TEXT

\xmlbadinclusions {...}

* NODE

\xmlbeforedocumentsetup {...} {...} {...}

1 NAME

2 SETUP

3 SETUP

\xmlbeforesetup {...} {...}

1 SETUP

2 SETUP

\xmlchainatt {...} {...}

1 NODE

2 NAME

\xmlchainattdef {...} {...} {...}

1 NODE

2 NAME

3 TEXT

\xmlchecknamespace {...} {...}

1 NODE

2 NAME

`\xmlcommand {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 XMLSETUP

`\xmlconcat {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT

`\xmlconcatrange {...} {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT
- 4 FIRST
- 5 LAST

`\xmlcontext {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlcount {...}`

- * NODE

`\xmldefaulttotext {...}`

- * NODE

`\xmldirectives {...}`

- * NODE

`\xmldirectivesafter {...}`

- * NODE

`\xmldirectivesbefore {...}`

- * NODE

`\xmldisplayverbatim {...}`

- * NODE

`\xmldoif {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE

`\xmldoifelse {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE
- 4 FALSE

`\xmldoifelseempty {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE
- 4 FALSE

`\xmldoifelseselfempty {...} {...} {...}`

- 1 NODE
- 2 TRUE
- 3 FALSE

`\xmldoifelsetext {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE
- 4 FALSE

`\xmldoifelsevalue {...} {...} {...} {...}`

- 1 CATEGORY
- 2 NAME
- 3 TRUE
- 4 FALSE

`\xmldoifnot {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE

`\xmldoifnotselfempty {...} {...}`

- 1 NODE
- 2 TRUE

`\xmldoifnottext {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE

`\xmldoifselfempty {...} {...}`

- 1 NODE
- 2 TRUE

`\xmldoiftext {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE

`\xmlelement {...} {...}`

- 1 NODE
- 2 NUMBER

`\xmlfilter {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlfirst {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlflush {...}`

- * NODE

`\xmlflushcontext {...}`

- * NODE

`\xmlflushdocumentsetups {...} {...}`

- 1 NAME
- 2 SETUP

`\xmlflushlinewise {...}`

- * NODE

`\xmlflushpure {...}`

- * NODE

`\xmlflushspacewise {...}`

- * NODE

`\xmlflushtext {...}`

- * NODE

`\xmlinclude {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 NAME

`\xmlinclusion {...}`

- * NODE

\xmlinclusions {...} * NODE
\xmlinfo {...} * NODE
\xmlinjector {...} * NAME
\xmlinlineverbatim {...} * NODE
\xmlinstalldirective {...} {...} 1 NAME 2 CSNAME
\xmllast {...} {...} 1 NODE 2 LPATH
\xmllastatt
\xmllastmatch
\xmlloadbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP
\xmlloaddata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP
\xmlloaddirectives {...} * FILE
\xmlloadfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlloadonly {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP

<code>\xmlmain {...}</code> * NAME
<code>\xmlmapvalue {.¹.} {.².} {.³.}</code> 1 CATEGORY 2 NAME 3 TEXT
<code>\xmlname {...}</code> * NODE
<code>\xmlnamespace {...}</code> * NODE
<code>\xmlnonspace {.¹.} {.².}</code> 1 NODE 2 LPATH
<code>\xmlpath {...}</code> * NODE
<code>\xmlpos {...}</code> * NODE
<code>\xmlposition {.¹.} {.².} {.³.}</code> 1 NODE 2 LPATH 3 NUMBER
<code>\xmlprependdocumentsetup {.¹.} {.².}</code> 1 NAME 2 SETUP
<code>\xmlprependsetup {...}</code> * SETUP
<code>\xmlprettyprint {.¹.} {.².}</code> 1 NODE 2 NAME
<code>\xmlprocessbuffer {.¹.} {.².} {.³.}</code> 1 BUFFER 2 NAME 3 XMLSETUP

\xmlprocessdata {...} {...} {...}

- 1 NAME
- 2 TEXT
- 3 XMLSETUP

\xmlprocessfile {...} {...} {...}

- 1 NAME
- 2 FILE
- 3 XMLSETUP

\xmlpure {...} {...}

- 1 NODE
- 2 LPATH

\xmlraw {...}

- * NODE

\xmlrefatt {...} {...}

- 1 NODE
- 2 NAME

\xmlregisterddocumentsetups {...} {...}

- 1 NAME
- 2 SETUP

\xmlregisteredsetups

\xmlregisterns {...} {...}

- 1 NAME
- 2 URL

\xmlremapname {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 NAME

\xmlremapnamespace {...} {...} {...}

- 1 NODE
- 2 NAME
- 3 NAME

\xmlremoveddocumentsetup {...} {...}

- 1 NAME
- 2 SETUP

\xmlremovesetup {...}

* SETUP

\xmlresetdocumentsetups {...}

* NAME

\xmlresetinjectors

\xmlresetsetups {...}

* NAME

\xmlsave {...} {...}

1 NODE

2 FILE

\xmlsetentity {...} {...}

1 NAME

2 TEXT

\xmlsetfunction {...} {...} {...}

1 NODE

2 LPATH

3 LUAFUNCTION

\xmlsetinjectors [...,*,...]

* NAME

\xmlsetsetup {...} {...} {...}

1 NAME

2 LPATH

3 SETUP

\xmlsetup {...} {...}

1 NODE

2 SETUP

\xmlshow {...}

* NODE

\xmlsnippet {...} {...}

1 NODE

2 NUMBER

\xmlstrip {...} {...}

1 NODE

2 LPATH

`\xmlstripnolines {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlstripped {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlstrippednolines {...} {...}`

- 1 NODE
- 2 LPATH

`\xmltag {...}`

- * NODE

`\xmlexentity {...} {...}`

- 1 NAME
- 2 TEXT

`\xmltext {...} {...}`

- 1 NODE
- 2 LPATH

`\xmltobuffer {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 BUFFER

`\xmltobufferverbose {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 BUFFER

`\xmltofile {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 FILE

`\xmlvalue {...} {...} {...}`

- 1 CATEGORY
- 2 NAME
- 3 TEXT

`\xmlverbatim {...}`

- * NODE

`\xrightarrow {...} {...}`

1 TEXT

2 TEXT

`\xrel {...} {...}`

1 TEXT

2 TEXT

`\xrightarrow {...} {...}`

1 TEXT

2 TEXT

`\xrightarrow[...]{...}`

1 TEXT

2 TEXT

`\xrightarrowup {...} {...}`

1 TEXT

2 TEXT

`\xleftrightarrow {...} {...}`

1 TEXT

2 TEXT

`\xrightarrowleftarrow {...} {...}`

1 TEXT

2 TEXT

`\xsplitstring \^... {...}`

1 CSNAME

2 TEXT

`\xtriplerel {...} {...}`

1 TEXT

2 TEXT

`\xtwoheadleftarrow {...} {...}`

1 TEXT

2 TEXT

`\xtwoheadrightarrow {...} {...}`

1 TEXT

2 TEXT


`\xxfrac {...} {...}`

1 CONTENT

2 CONTENT

`\xypos {...}`

* NAME

The background of the entire page is an abstract composition of various geometric shapes, primarily rectangles and trapezoids, in shades of light green and grey. These shapes are layered and overlap, creating a sense of depth and movement. The lines defining the shapes are thick and hand-drawn, giving the background a graphic, almost architectural feel.

PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com