



ConTeXt

přikazy

CS

ConTeXt

přikazy

language : cs / český
version : 10. září 2026
maintainer : Wolfgang Schuster
comments : ntg-context@ntg.nl

\addfeature [...] * NAME
\addfeature {...} * NAME
\addrivertobox [...] . ² 1 marginalie = DIMENSION ^{OPT} krok = DIMENSION vyska = DIMENSION hloubka = DIMENSION spaceinbetween = DIMENSION 2 CSNAME NUMMER
\addtocommalist {. ¹ .} \. ² 1 TEXT 2 CSNAME
\addtoJSreamble {. ¹ .} {. ² .} 1 NAME 2 CONTENT
\addvalue {. ¹ .} {. ² .} 1 NAME 2 TEXT
\aftersplitstring . ¹ . \at . ² . \to \. ³ . 1 TEXT 2 TEXT 3 CSNAME
\aftertestandsplitstring . ¹ . \at . ² . \to \. ³ . 1 TEXT 2 TEXT 3 CSNAME
\aktualnicislonaadpisu
\aktualnidatum [...*...] * rok year:NAME y y:NAME YY Y Y:NAME YY mesic month:mnem month:hebrew month:jalali m m:mnem m:hebrew m:jalali MESIC MONTH:mnem MONTH:hebrew MONTH:jalali mm M den day:NAME day:++ day:ord day:++ day:highord d d:NAME d:++ d:ord d:++ d:highord dd dd:++ dd:ord dd:++ dd:highord D D:++ D:ord D:++ D:highord vsedniden weekday:mnem weekday:hebrew weekday:jalali w w:mnem w:hebrew w:jalali VSEDNIDEN WEEKDAY:mnem WEEKDAY:hebrew WEEKDAY:jalali W znacka mezera _ TEXT hebrew:to jalali:to jalali:from
\aktualnidatum [...] * NAME ^{OPT}
\alignanchor {. ¹ .} {. ² .} {. ³ .} {. ⁴ .} 1 NAME 2 NUMMER 3 NUMMER 4 r vpravo c m nastred
\alignbottom
\aligncontentleft
\aligncontentmiddle
\aligncontentright

<code>\aligned [...¹,...] {...}</code> 1 vlevo nastred vpravo vrsek spodek radek l c r m t b g 2 CONTENT
<code>\alignedbox [...¹,...] \.² {...}</code> 1 vlevo nastred vpravo vrsek spodek radek l c r m t b g 2 CSNAME 3 CONTENT
<code>\alignedline {...¹} {...²} {...³}</code> 1 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana 2 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana 3 CONTENT
<code>\alignhere</code>
<code>\alignmentcharacter</code>
<code>\allinputpaths</code>
<code>\allowbreak</code>
<code>\allowhbreak</code>
<code>\allowvbreak</code>
<code>\alphabeticnumerals {...}</code> * NUMMER
<code>\alternate {...¹} {...²}</code> 1 TEXT 2 CONTENT
<code>\alwayscitation [...¹,...¹,...] [...²]</code> 1 odkaz = REFERENCE ^{OPT} alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE
<code>\alwayscitation [...¹] [...²]</code> 1 implicitni category entry ^{OPT} short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE
<code>\alwayscitation [...¹,...¹,...] [...²,...²,...]</code> 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE

<pre> \alwayscite [...] ¹ [...] ² 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>
<pre> \alwayscite [¹] [²] 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>
<pre> \alwayscite [...] ¹ [...] [...] ² [...] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \amedian {...} * CONTENT </pre>
<pre> \ampersand </pre>
<pre> \analyzelocalanchors ... * CSNAME NUMBER </pre>
<pre> \anchor [¹] [...] ² [...] [...] ³ [...] [...] ⁴ 1 NAME OPT OPT 2 inherits: \setuplayer 3 inherits: \setuplayerinherits: \nastavoramovani 4 CONTENT </pre>
<pre> \antikva </pre>
<pre> \ap [...] * NUMMER </pre>
<pre> \appendetoks ... \to \²... 1 BEFEHL 2 CSNAME </pre>
<pre> \appendgvalue {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \appendhiddenbackground {...,*,...} * NAME </pre>
<pre> \appendtocommalist {...} \²... 1 TEXT 2 CSNAME </pre>
<pre> \appendtoks ... \to \²... 1 BEFEHL 2 CSNAME </pre>

\appendtoksonce ¹ \to ² .. 1 BEFEHL 2 CSNAME
\appendvalue { ¹ ..} { ² .. 1 NAME 2 BEFEHL
\apply { ¹ ..} { ² .. 1 CONTENT 2 CONTENT
\applyalternativestyle { [*] .. * NAME
\applypattern [¹ ..] [.. ² .. 1 NAME OPT OPT 2 jmeno = NAME sirka = DIMENSION vyska = DIMENSION
\applyprocessor { ¹ ..} { ² .. 1 NAME 2 CONTENT
\applytofirstcharacter \ ¹ .. { ² .. 1 CSNAME 2 TEXT
\applytocharacters \ ¹ .. { ² .. 1 CSNAME 2 TEXT
\applytosplitstringchar \ ¹ .. { ² .. 1 CSNAME 2 TEXT
\applytosplitstringcharspaced \ ¹ .. { ² .. 1 CSNAME 2 TEXT
\applytosplitstringline \ ¹ .. { ² .. 1 CSNAME 2 TEXT
\applytosplitstringlinespaced \ ¹ .. { ² .. 1 CSNAME 2 TEXT
\applytosplitstringword \ ¹ .. { ² .. 1 CSNAME 2 TEXT
\applytosplitstringwordspaced \ ¹ .. { ² .. 1 CSNAME 2 TEXT
\applytowords \ ¹ .. { ² .. 1 CSNAME 2 TEXT

\arabicdecimals {...} * NUMBER
\arabicexnumerals {...} * NUMBER
\arabicnumerals {...} * NUMBER
\arg {...} * CONTENT
\asciimode
\asciistr {...} * CONTENT
\assignalfadimension {...} \^{2...} {...} {...} {...} {...} 1 male stredni velke zadny DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION
\assigndimen \^{1...} {...} 1 CSNAME 2 DIMENSION
\assigndimension {...} \^{2...} {...} {...} {...} {...} 1 [-+]male [-+]stredni [-+]velke zadny DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION
\assignifempty \^{1...} {...} 1 CSNAME 2 BEFEHL
\assigntranslation [...,\^{1}...,...] \to \^{2...} 1 SPRACHE = TEXT 2 CSNAME
\assignvalue {...} \^{2...} {...} {...} {...} {...} 1 male stredni velke TEXT 2 CSNAME 3 BEFEHL 4 BEFEHL 5 BEFEHL
\assignwidth {...} \^{2...} {...} {...} 1 prizpusobive siroky DIMENSION 2 CSNAME 3 TEXT 4 DIMENSION
\assumelongusagecs \^{1...} {...} 1 CSNAME 2 CONTENT
\astype {...} * CONTENT

$\backslash\text{async}$ $\{...\}^1$ $\dots^2$ $\{...\}^3$ 1 NAME 2 NUMMER 3 r vpravo c m nastred
$\backslash\text{attachinsert}$ $\{...\}^*$ * CONTENT
$\backslash\text{attachinsertion}$ $\dots^1$ $\backslash\dots^2$ 1 NUMMER 2 CSNAME
$\backslash\text{attachinsertions}$ $\backslash\dots^*$ * CSNAME
$\backslash\text{ATTACHMENT}$ $[\dots]^1_{\text{OPT}}$ $[\dots,\dots,\dots,\dots]^2_{\text{OPT}}$ 1 NAME 2 inherits: \setupattachment instances: attachment
$\backslash\text{attachment}$ $[\dots]^1_{\text{OPT}}$ $[\dots,\dots,\dots,\dots]^2_{\text{OPT}}$ 1 NAME 2 inherits: \setupattachment
$\backslash\text{autobigmath}$
$\backslash\text{autocap}$ $\{...\}^*$ * TEXT
$\backslash\text{autodirhbox}$ $\dots^1$ $\{...\}^2$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvbox}$ $\dots^1$ $\{...\}^2$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvtop}$ $\dots^1$ $\{...\}^2$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{autointegral}$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{automathematics}$ $\{...\}^*$ * CONTENT
$\backslash\text{automathtext}$
$\backslash\text{autoorientation}$ $\{...\}^*$ * normalni up down vlevo vpravo vrsek spodek NAME
$\backslash\text{autopagestaterealignpage}$ $\{...\}^*$ * NAME

\autopagestaterealpageorder {...} * NAME
\autoreferencedetailtext
\autoreferencekindtext
\autoreferencelabeltext
\autoreferencenametext
\autorule \relax * width_DIMENSION height_DIMENSION depth_DIMENSION xoffset_DIMENSION yoffset_DIMENSION left_DIMENSION right_DIMENSION
\autosetups {...,*...} * NAME
\autostarttext ... \autostoptext
\autosync {...} {...} 1 NAME 2 NUMMER
\availablehsize
\averagecharwidth
\BeforePar {...} * BEFEHL
\Big ... * CHARACTER
\Bigg ... * CHARACTER
\Biggl ... * CHARACTER
\Biggm ... * CHARACTER
\Biggr ... * CHARACTER
\Bigl ... * CHARACTER
\Bigm ... * CHARACTER
\Bigr ... * CHARACTER

\backgroundimage	{.. ¹ ..}	{.. ² ..}	{.. ³ ..}	{.. ⁴ ..}
1	NUMBER			
2	DIMENSION			
3	DIMENSION			
4	BEFEHL			

	<code>\backgroundimagefill</code>	<code>{...}^1</code>	<code>{...}^2</code>	<code>{...}^3</code>	<code>{...}^4</code>
1	NUMBER				
2	DIMENSION				
3	DIMENSION				
4	BEFEHL				

```
\backgroundline    [...^]    {...^}
1  COLOR
2  CONTENT
```

```
\balancesubcolumnsets    [...]
*   spread                OPT
```

```
\barevna1ista    [...,*,...]
*    COLOR
```

```
\barva      [^...]    {.^..}
1  COLOR
2  CONTENT
```

```
\BAR    {...}
*  CONTENT
instances: overbar underbar overstrike understrike overbars underbars overstrikes
understrikes hiddenbar outline outlined backgroundbar mathbackground undergraphic
underrandom underrandoms underdash underdashes underdot underdots
```

`\backgroundbar` `{...}`
* CONTENT

```
\hiddenbar    {...}
*    CONTENT
```

```
\mathbackground    {...}
*    CONTENT
```

```
\outline    {...}
*    CONTENT
```

```
\outlined    {...}
*   CONTENT
```

```
\overbar    {...}
*  CONTENT
```

`\overbars` `{...}`
* CONTENT

```
\overstrike    {...}
*    CONTENT
```

```
\overstrikes    {...}
*    CONTENT
```

<code>\underbar {...}</code> * CONTENT
<code>\underbars {...}</code> * CONTENT
<code>\underdash {...}</code> * CONTENT
<code>\underdashes {...}</code> * CONTENT
<code>\underdot {...}</code> * CONTENT
<code>\underdots {...}</code> * CONTENT
<code>\undergraphic {...}</code> * CONTENT
<code>\underrandom {...}</code> * CONTENT
<code>\underrandoms {...}</code> * CONTENT
<code>\understrike {...}</code> * CONTENT
<code>\understrikes {...}</code> * CONTENT
<code>\base [.¹.] {.².}</code> 1 TEXT OPT 2 TEXT
<code>\basegrid [...,.*,...]</code> * nx = NUMBER ny = NUMBER dx = NUMBER dy = NUMBER faktor = NUMBER meritko = NUMBER xkrok = NUMBER ykrok = NUMBER offset = DIMENSION xoffset = DIMENSION yoffset = DIMENSION zarovnani = nastred jednotka = cm mm in pc pt bp pismo = STYLE BEFEHL barva = COLOR barvalinky = COLOR tloustkalinky = DIMENSION
<code>\baselinebottom</code>
<code>\baselineleftbox {...}</code> * CONTENT

$\backslash$ baselinemiddlebox {...} * CONTENT
$\backslash$ baselinerightbox {...} * CONTENT
$\backslash$ bbordermatrix {...} * CONTENT
$\backslash$ bbox {...} * CONTENT
$\backslash$ before split string ¹ ... \at ² ... \to \ ³ ... 1 TEXT 2 TEXT 3 CSNAME
$\backslash$ before test and split string ¹ ... \at ² ... \to \ ³ ... 1 TEXT 2 TEXT 3 CSNAME
$\backslash$ beginBLOCK [..., ¹ ...] [..., ² ...,...] ... \endBLOCK 1 + - NAME OPT OPT 2 KEY = VALUE
$\backslash$ beginhbox ... \endhbox
$\backslash$ begin of shape box ... \end of shape box
$\backslash$ begin vbox ... \end vbox
$\backslash$ begin vtop ... \end vtop
$\backslash$ begstrut ... \endstrut
$\backslash$ bengalinumerals {...} * NUMMER
$\backslash$ bezserifu
$\backslash$ bigbodyfont
$\backslash$ bigbreak
$\backslash$ bigg ... * CHARACTER
$\backslash$ bigger
$\backslash$ biggl ... * CHARACTER
$\backslash$ biggm ... * CHARACTER

<code>\biggr ...</code> * CHARACTER
<code>\bigl ...</code> * CHARACTER
<code>\bigm ...</code> * CHARACTER
<code>\bigmath</code>
<code>\bigr ...</code> * CHARACTER
<code>\bigskip</code>
<code>\bilemisto</code>
<code>\bitmapimage [...,¹...,...] {..².}</code> 1 barva = rgb cmyk seda sirka = DIMENSION vyska = DIMENSION x = NUMMER y = NUMMER 2 NUMMER
<code>\blankafter [...*,...]</code> * inherits: \preskoc
<code>\blankbefore [...*,...]</code> * inherits: \preskoc
<code>\blap {..¹.}</code> * CONTENT
<code>\bleedheight</code>
<code>\bleeding [...¹.] [...,²...,...] {..³.}</code> 1 NAME 2 inherits: \setupbleeding 3 CONTENT
<code>\bleedwidth</code>
<code>\BLEED [...,¹...,...] {..².}</code> 1 inherits: \setupbleeding 2 CONTENT instances: bleed
<code>\bleed [...,¹...,...] {..².}</code> 1 inherits: \setupbleeding 2 CONTENT
<code>\blockcolumnsetrows</code>
<code>\blockligatures [...*,...]</code> * TEXT

<code>\blocksynctexfile</code> <code>[...;...]</code> * FILE
<code>\blockuservariable</code> <code>{...}</code> * KEY
<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\boldface</code>
<code>\booleanmodevalue</code> <code>{...}</code> * NAME
<code>\bordermatrix</code> <code>{...}</code> * CONTENT
<code>\bottombox</code> <code>{...}</code> * CONTENT
<code>\bottomleftbox</code> <code>{...}</code> * CONTENT
<code>\bottomrightbox</code> <code>{...}</code> * CONTENT
<code>\boxanchorpresetcode</code> <code>{...}</code> * radek vyska podlehloubky vlevo left,height left,top left,depth left,bottom vpravo right,height right,top right,depth right,bottom nastred middle,height middle,top middle,depth middle,bottom middle,left middle,right
<code>\boxcursor</code>
<code>\boxfixstretch</code> <code>... ...</code> 1 DIMENSION 2 CSNAME NUMMER
<code>\boxmarker</code> <code>{...} {...}</code> 1 NAME 2 NUMMER
<code>\boxofsize</code> <code>\... {...}</code> 1 CSNAME 2 DIMENSION 3 CONTENT
<code>\boxreference</code> <code>[...¹;...]</code> <code>\... {...}</code> 1 REFERENCE 2 CSNAME 3 CONTENT
<code>\bpar ... \epar</code>
<code>\bpos</code> <code>{...}</code> * NAME
<code>\break</code>

<code>\breakhere</code> [¹ ...] { ² ...} 1 vlevo vpravo pred po stranka stejnastranka 2 TEXT
<code>\bTABLE</code> [...,.. [*] ...,...] ... \eTABLE * inherits: \setupTABLE
<code>\bTABLEbody</code> [...,.. [*] ...,...] ... \eTABLEbody * inherits: \setupTABLE ^{OPT}
<code>\bTABLEfoot</code> [...,.. [*] ...,...] ... \eTABLEfoot * inherits: \setupTABLE ^{OPT}
<code>\bTABLEhead</code> [...,.. [*] ...,...] ... \eTABLEhead * inherits: \setupTABLE ^{OPT}
<code>\bTABLEnested</code> [...,.. [*] ...,...] ... \eTABLEnested * inherits: \setupTABLE ^{OPT}
<code>\bTABLEnext</code> [...,.. [*] ...,...] ... \eTABLEnext * inherits: \setupTABLE ^{OPT}
<code>\bTABLEsection</code> [...,.. [*] ...,...] ... \eTABLEsection * opakovat = NUMMER ^{OPT}
<code>\bTC</code> [...,.. [*] ...,...] ... \eTC * inherits: \bTF
<code>\bTD</code> [...,.. [*] ...,...] ... \eTD * nx = NUMMER ny = NUMMER nc = NUMMER nr = NUMMER n = NUMMER m = NUMMER akce = REFERENCE inherits: \setupTABLE
<code>\bTDs</code> [...] ... \eTDs * NAME
<code>\bTH</code> [...,.. [*] ...,...] ... \eTH * inherits: \bTF
<code>\bTN</code> [...,.. [*] ...,...] ... \eTN * inherits: \bTF
<code>\bTR</code> [...,.. [*] ...,...] ... \eTR * inherits: \setupTABLE
<code>\bTRs</code> [...] ... \eTRs * NAME
<code>\bTX</code> [...,.. [*] ...,...] ... \eTX * inherits: \bTF
<code>\bTY</code> [...,.. [*] ...,...] ... \eTY * inherits: \setupTABLE ^{OPT}

\btx ... \etx	
\btxabbreviatedjournal {...}	
* NAME	
\btxaddjournal [...] ¹ [...] ²	
1 NAME	
2 NAME	
\btxalwayscitation [...] ¹ [...] ²	
1 odkaz = REFERENCE ^{OPT}	
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears	
authornum authoryear	
pred = BEFEHL	
po = BEFEHL	
vlevo = BEFEHL	
vpravo = BEFEHL	
inherits: \setupbtx	
2 REFERENCE	
\btxalwayscitation [...] ¹ [...] ²	
1 implicitni category entry ^{OPT} short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear	
2 REFERENCE	
\btxalwayscitation [...] ¹ [...] ²	
1 odkaz = REFERENCE	
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears	
authornum authoryear	
pred = BEFEHL	
po = BEFEHL	
vlevo = BEFEHL	
vpravo = BEFEHL	
inherits: \setupbtx	
2 KEY = VALUE	
\btxauthorfield {...}	
* initials firstnames vons surnames juniors	
\btxdetail {...}	
* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language	
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok	
yearfiled NAME	
\btxdirect {...}	
* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language	
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok	
yearfiled NAME	
\btxdoif {...} ¹ {...} ²	
1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language	
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok	
yearfiled NAME	
2 TRUE	
\btxdoifcitedoneelse {...} ¹ {...} ² {...} ³ {...} ⁴	
1 NAME	
2 REFERENCE	
3 TRUE	
4 FALSE	
\btxdoifcombiinlistelse {...} ¹ {...} ² {...} ³ {...} ⁴	
1 NAME	
2 NAME	
3 TRUE	
4 FALSE	

\btxdfalse { ¹ .} { ² .} { ³ .} 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME 2 TRUE 3 FALSE
\btxdfalsecitedone { ¹ .} { ² .} { ³ .} { ⁴ .} 1 NAME 2 REFERENCE 3 TRUE 4 FALSE
\btxdfalsecombiinlist { ¹ .} { ² .} { ³ .} { ⁴ .} 1 NAME 2 NAME 3 TRUE 4 FALSE
\btxdfalsesameasprevious { ¹ .} { ² .} { ³ .} 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME 2 TRUE 3 FALSE
\btxdfalsesameaspreviouschecked { ¹ .} { ² .} { ³ .} { ⁴ .} 1 vzdy dvoustranny 2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME 3 TRUE 4 FALSE
\btxdfalseuservariable { ¹ .} { ² .} { ³ .} 1 KEY 2 TRUE 3 FALSE
\btxdfifnot { ¹ .} { ² .} 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME 2 TRUE
\btxdfifsameaspreviouselse { ¹ .} { ² .} { ³ .} 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME 2 TRUE 3 FALSE
\btxdfifsameaspreviouscheckedelse { ¹ .} { ² .} { ³ .} { ⁴ .} 1 vzdy dvoustranny 2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME 3 TRUE 4 FALSE
\btxdfifuservariableelse { ¹ .} { ² .} { ³ .} 1 KEY 2 TRUE 3 FALSE
\btexpandedjournal { [*] .} * NAME

\btxfieldd {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\btxfielddname {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\btxfielddtype {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\btxfirstofrange {...} * volume pages
\btxflush {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\btxflushauthor [.¹.] {².} 1 num normalni normalshort inverted invertedshort 2 autor editor
\btxflushauthorinverted {...} * autor editor
\btxflushauthorinvertedshort {...} * autor editor
\btxflushauthorname {...} * autor editor
\btxflushauthornormal {...} * autor editor
\btxflushauthornormalshort {...} * autor editor
\btxflushsuffix
\btxfoundname {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\btxfoundtype {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\btxhiddencitation [...]
* REFERENCE

\btxhybridcite [...¹...] [...²]

```
1 odkaz      = REFERENCEOPT
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

\btxhybridcite [...¹] [...²]

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

\btxhybridcite {...}

* REFERENCE

\btxhybridcite [...¹...] [...²...]

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

\btxlistcitation [...¹...] [...²]

```
1 odkaz      = REFERENCEOPT
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

\btxlistcitation [...¹] [...²]

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

\btxlistcitation [...¹...] [...²...]

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

\btxloadjournalist [...]

* FILE

\btxoneorrange {...} {...} {...}

```
1 volume pages
2 TRUE
3 FALSE
```

\btxrawfield {...}

* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language
mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok
yearfiled NAME

<pre> \btxremapauthor [...¹] [...²] 1 TEXT 2 TEXT </pre>
<pre> \btxsavejournalist [...] * FILE </pre>
<pre> \btxsetup {...} * NAME </pre>
<pre> \btxsingularorplural {...¹} {...²} {...³} 1 editor producer director 2 TRUE 3 FALSE </pre>
<pre> \btxsingularplural {...¹} {...²} {...³} 1 editor producer director 2 TRUE 3 FALSE </pre>
<pre> \btxstarttaggedcite ... \btxstoptaggedcite </pre>
<pre> \btxttextcitation [...¹...¹...¹] [...²] 1 odkaz = REFERENCE^{OPT} alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>
<pre> \btxttextcitation [...¹] [...²] 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>
<pre> \btxttextcitation [...¹...¹...¹] [...²...²...²] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \TOOLTIP [...¹...¹...¹] {...²} {...³} 1 inherits: \setup^{OPT}tip 2 TEXT 3 TEXT instances: tooltip </pre>
<pre> \TOOLTIP [...¹] {...²} {...³} 1 vlevo nastred^{OPT}vpravo 2 TEXT 3 TEXT instances: tooltip </pre>
<pre> \tooltip [...¹] {...²} {...³} 1 vlevo nastred^{OPT}vpravo 2 TEXT 3 TEXT </pre>

\tooltip [... ¹ ... ² ...] {...} {...} 1 inherits: \setuptooltip 2 TEXT 3 TEXT
\buildtextaccent {...} {...} 1 CHARACTER 2 CHARACTER
\buildtextbottomcomma {...} * CHARACTER
\buildtextbottomdot {...} * CHARACTER
\buildtextcedilla {...} * CHARACTER
\buildtextgrave {...} * CHARACTER
\buildtextmacron {...} * CHARACTER
\buildtextognek {...} * CHARACTER
\Camel {...} * TEXT
\Caps {...} * TEXT
\Cisla {...} * NUMMER
\CONTEXT
\ConTeXt
\Context
\ConvertConstantAfter \ ¹ ... {... ² } {... ³ } 1 CSNAME 2 TEXT 3 TEXT
\ConvertToConstant \ ¹ ... {... ² } {... ³ } 1 CSNAME 2 TEXT 3 TEXT
\camel {...} * TEXT
\casing [... ¹] {... ² } 1 reset SLOVO slovo Slovo Slova kapitalky Kapitalky nahodny mixed camel Camel kap Kap 2 CONTENT


```

\citation [...1...] [...2...]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE

```

```

\cite [...1...] [...2]
1 odkaz =OPTREFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 REFERENCE

```

```

\cite [...1] [...2]
1 implicitniOPT category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE

```

```

\cite {...}
* REFERENCE

```

```

\cite [...1...] [...2...]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE

```

```

\clap {...}
* CONTENT

```

```

\classfont {...} {...}
1 NAME
2 FONT

```

```

\cldcommand {...}
* BEFEHL

```

```

\cldcontext {...}
* BEFEHL

```

```

\cldloadfile {...}
* FILE

```

```

\cldprocessfile {...}
* FILE

```

```

\clearmarking [...]
* BESCHRIFTUNG

```

```

\clippedoverlayimage {...}
* FILE

```

<code>\collapsehyphensequences</code>
<code>\collect {...}</code> <code>* CONTENT</code>
<code>\collectedmath</code>
<code>\collectedtext [...,\overset{1}{=}\dots,] [...,\overset{2}{=}\dots,] {...} {...}</code> <code>1 inherits: \setupcollector^{OPT}</code> <code>2 pismeno = STYLE BEFEHL</code> <code>barva = COLOR</code> <code>inherits: \nastavoramovani</code> <code>3 TEXT</code> <code>4 CONTENT</code>
<code>\collectexpanded {...}</code> <code>* CONTENT</code>
<code>\collectexported</code>
<code>\colorcomponents {...}</code> <code>* COLOR</code>
<code>\colored [...,\overset{1}{=}\dots,] {...}</code> <code>1 inherits: \definujbarvu</code> <code>2 CONTENT</code>
<code>\colored [...]\{...}</code> <code>1 COLOR</code> <code>2 CONTENT</code>
<code>\coloronly [...]\{...}</code> <code>1 COLOR</code> <code>2 CONTENT</code>
<code>\columnbreak [...,*,...]</code> <code>* ano ne nastaveni lokalne sila prvni posledni NUMMER NAME</code>
<code>\columnsetgridlines {...}</code> <code>* NUMMER</code>
<code>\combinepages [...]\ [...,\overset{2}{=}\dots,]</code> <code>1 FILE^{OPT}</code> <code>2 alternativa = a b c horizontalne vertikalne</code> <code>n = NUMMER</code> <code>nx = NUMMER</code> <code>ny = NUMMER</code> <code>start = NUMMER</code> <code>stop = NUMMER</code> <code>vzdalenost = DIMENSION</code> <code>vrsek = BEFEHL</code> <code>spodek = BEFEHL</code> <code>vlevo = BEFEHL</code> <code>vpravo = BEFEHL</code> <code>pred = BEFEHL</code> <code>po = BEFEHL</code> <code>mezi = BEFEHL</code> <code>ramecek = zap vyp</code> <code>pozadi = popredi barevne NAME</code> <code>barvapozadi = COLOR</code>
<code>\commalistelement</code>

\commalistprocessor {...} * NAME
\commalistsentence [... ¹ ,...] [... ² ,...] 1 TEXT 2 TEXT
\commalistsize
\PRIKAZnamespace
\PRIKAZparameter {...} * KEY
\PRIKAZparameterhash {...} * KEY
\PRIKAZsetupmode
\comparedimension {...} {...} 1 DIMENSION 2 DIMENSION
\comparedimensioneps {...} {...} 1 DIMENSION 2 DIMENSION
\comparetext [...]
\completebtxrendering [... ¹] [... ² ,...] 1 NAME 2 inherits: \setupbtxrendering
\uplныCOMBINEDLIST [... [*] ,...] * inherits: \nastavkombinovanyseznam instances: content
\uplныcontent [... [*] ,...] * inherits: \nastavkombinovanyseznam
\completelist [... ¹] [... ² ,...] 1 LISTE 2 inherits: \nastavseznam
\completelistofFLOATS [... [*] ,...] * inherits: \nastavseznam instances: chemicals figures tables intermezzi graphics
\completelistoffigures [... [*] ,...] * inherits: \nastavseznam
\completelistofgraphics [... [*] ,...] * inherits: \nastavseznam
\completelistofchemicals [... [*] ,...] * inherits: \nastavseznam

```
* inherits: \nastavseznam
```

```
* inherits: \nastavseznam
```

```
1  NAME
2  inherits: \setupbtxrendering
```

```
2 inherits: \nastavtrideni
```

```
* inherits: \nastavtrideni
instances: logos
```

```
* inherits: \nastavtrideni
```

```
1 SINGULAR
2 inherits: \nastavsynonyma
```

```
* inherits: \nastavsynonyma
instances: abbreviations
```

```
* inherits: \nastavsynonyma
```

\completepagenumber

```
1  NAME
2  inherits: \nastavrejstrik
```

```
* inherits: \nastavrejstrikOPT
instances: index
```

```
* inherits: \nastavrejstrikOPT
```

* CSNAME

* CSNAME

* TEXT CSNAME

* TEXT CSNAME

<code>\composedcollector</code> <code>{...}</code> * NAME
<code>\composedlayer</code> <code>{...}</code> * NAME
<code>\compounddiscretionary</code>
<code>\compresult</code>
<code>\connectboxanchors</code> <code>[...¹]</code> <code>[...²]</code> <code>[...³...]</code> <code>[...⁴...]</code> <code>{...⁵}</code> <code>{...⁶}</code> 1 NAME 2 NAME 3 inherits: \setupboxanchorcontent 4 inherits: \setupboxanchorcontent 5 NAME 6 NAME
<code>\connectmatrixanchors</code> <code>[...¹]</code> <code>[...²]</code> <code>[...³...]</code> <code>[...⁴...]</code> <code>{...⁵}</code> <code>{...⁶}</code> 1 NAME 2 NAME 3 inherits: \setupboxanchorcontent 4 inherits: \setupboxanchorcontent 5 NAME 6 NAME
<code>\constantdimen</code> <code>*...</code> * CSNAME
<code>\constantdimenargument</code> <code>*...</code> * CSNAME
<code>\constantemptyargument</code> <code>*...</code> * CSNAME
<code>\constantnumber</code> <code>*...</code> * CSNAME
<code>\constantnumberargument</code> <code>*...</code> * CSNAME
<code>\contentreference</code> <code>[...¹...]</code> <code>[...²...]</code> <code>{...³}</code> 1 REFERENCE 2 inherits: \nastavoramovani 3 CONTENT
<code>\continuednumber</code> <code>{...}</code> * NUMMER
<code>\continueifinputfile</code> <code>{...}</code> * FILE
<code>\convertargument</code> <code>...¹ \to</code> <code>...²</code> 1 TEXT 2 CSNAME
<code>\convertcommand</code> <code>\...¹ \to</code> <code>...²</code> 1 CSNAME 2 CSNAME

$\backslash$ convertedcounter [¹ ...] [...,.. ² ...,...] 1 NAME OPT 2 inherits: \setupcounter
$\backslash$ convertedddimen { ¹ ...} { ² ...} 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc
$\backslash$ convertedsubcounter [¹ ...] [² ...] [...,.. ³ ...,...] 1 NAME OPT OPT 2 NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse 3 inherits: \setupcounter
$\backslash$ convertmonth {.*...} * NUMBER
$\backslash$ convertvalue . ¹ ... \to \. ² ... 1 NAME 2 CSNAME
$\backslash$ convertvboxtohbox
$\backslash$ copyboxfromcache { ¹ ...} { ² ...} . ³ ... 1 NAME 2 NUMBER TEXT 3 CSNAME NUMBER
$\backslash$ copyLABELtext [¹ ...] [...,.. ² ...,...] 1 SPRACHE OPT 2 KEY = KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash$ copybtxlabeltext [¹ ...] [...,.. ² ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash$ copyheadtext [¹ ...] [...,.. ² ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash$ copylabeltext [¹ ...] [...,.. ² ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash$ copymathlabeltext [¹ ...] [...,.. ² ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash$ copyoperatortext [¹ ...] [...,.. ² ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash$ copyprefixtext [¹ ...] [...,.. ² ...,...] 1 SPRACHE OPT 2 KEY = KEY
$\backslash$ copysuffixtext [¹ ...] [...,.. ² ...,...] 1 SPRACHE OPT 2 KEY = KEY

2 KEY = KEY

2 KEY = KEY

```
3 inherits: \setupexternalfigure
```

3 KEY

1	NAME
2	NAME

1	NAME
2	NAME

1	NAME
2	NUMMER

3	CSNAME
---	--------

```

1  TEXT
2  CSNAME

```

* CONTENT

* CONTENT

* CONTENT

* CONTENT

\crlf

\crlfplaceholder

1 TEXT
2 CONTENT

\ctxcommand {...} * BEFEHL
\ctxdirectcommand {...} * BEFEHL
\ctxdirectlua {...} * BEFEHL
\ctxfunction {...} * NAME
\CTXFUNCTIONDEFINITION
\CTXFUNCTION
\ctxlatecommand {...} * BEFEHL
\ctxlatelua {...} * BEFEHL
\ctxloadluafile {...} * FILE
\ctxlua {...} * BEFEHL
\ctxluabuffer [...] * BUFFER OPT
\ctxluabuffer {...} * BUFFER
\ctxluacode {...} * BEFEHL
\ctxreport {...} * BEFEHL
\CTXSCANNER
\ctxsprint {...} * BEFEHL
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} * KEY
\currentcommalistitem
\currentPRIKAZ

\currentPRIKAZhash
\currentPRIKAZparent
\currentcomponent
\currentenvironment
\currentfeaturetest
\currentinterface
\currentPOPISEK [..., ¹ ...] {... ² } 1 REFERENCE OPT OPT 2 TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} * TEXT
\currentlistentrynumber
\currentlistentrypagenumber
\currentlistentryreferenceattribute {...} * cislo text cislostranky vse
\currentlistentrytitle
\currentlistentrytitlrendered
\currentlistsymbol
\currentmainlanguage
\currentmessagetext
\currentmoduleparameter {...} * KEY
\currentoutputstream
\currentproduct
\currentproject
\currentregime
\currentregisterpageuserdata {...} * KEY


```

1  d  =  NUMMER                                OPT
    m  =  NUMMER
    y  =  NUMMER
2  NAME

```

```

1 rok year:NAME y y:NAME yy Y Y:NAME YY mesic month:mnem month:hebrew month:jalali m m:mnem m:hebrew m:jalali
MESIC MONTH:mnem MONTH:hebrew MONTH:jalali mm M den day:NAME day:+ day:ord day:++ day:highord d d:NAME d:+ d:ord
d:++ d:highord dd dd:+ dd:ord dd:++ dd:highord D D:+ D:ord D:++ D:highord vsedniden weekday:mnem weekday:hebrew
weekday:jalali w w:mnem w:hebrew w:jalali VSEDNIDEN WEEKDAY:mnem WEEKDAY:hebrew WEEKDAY:jalali W znacka mezera \_
TEXT hebrew:to jalali:to jalali:from
2 d = NUMBER
m = NUMBER
v = NUMBER

```

```

1  NAME
2  d  =  NUMBER
   m  =  NUMBER
   v  =  NUMBER

```

* NUMMER.

1	NUMMER
2	NUMMER
3	NUMMER

* NUMMER.

1	NUMMER
2	NUMMER

* CSNAME.

```

1  NAME                                     OPT
2  NUMMER

```

* NAME

* NAME

* CSNAME, NUMMER.

<code>\defaultobjectreference</code>
<code>\defcatcodecommand \¹... \²... {\³...}</code> 1 CSNAME 2 CHARACTER NUMBER 3 BEFEHL
<code>\defconvertedargument \¹... {\²...}</code> 1 CSNAME 2 TEXT
<code>\defconvertedcommand \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\defconvertedvalue \¹... {\²...}</code> 1 CSNAME 2 NAME
<code>\defineactivecharacter \¹... {\²...}</code> 1 CHARACTER 2 BEFEHL
<code>\defineadaptive [...¹] [...²] [...,³...,...]</code> 1 NAME 2 NAME 3 inherits: \setupadaptive
<code>\definealign [...¹] [...,²...]</code> 1 NAME 2 inherits: \nastavzarovnani
<code>\definealternativestyle [...,¹...] [...²] [...³]</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\defineanchor [...¹] [...²] [...,³...,...] [...,⁴...,...]</code> 1 NAME 2 NAME 3 inherits: \setupplayer 4 inherits: \setupplayerinherits: \nastavoramovani
<code>\defineanchorbox [...[*]]</code> * NAME
<code>\defineanchorboxoverlay [...[*]]</code> * NAME
<code>\defineattachment [...¹] [...²] [...,³...,...]</code> 1 NAME 2 NAME 3 inherits: \setupattachment
<code>\defineattribute [...¹] [...,²...]</code> 1 NAME 2 lokalne globalne public private pickup
<code>\definebackground [...¹] [...²] [...,³...,...]</code> 1 NAME 2 NAME 3 inherits: \nastavpozadi

<pre> \definebalancing [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupbalancing </pre>
<pre> \definebar [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupbar </pre>
<pre> \definebleeding {...¹} {...²} [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupbleeding </pre>
<pre> \definebodyfontswitch [...¹] [...²,...] 1 NAME 2 inherits: \nastavzakladnifont </pre>
<pre> \defineboundary [...¹] [...²] 1 NAME 2 public </pre>
<pre> \defineboxanchor [...[*]] * NAME </pre>
<pre> \defineboxanchorcontent [...¹] [...,...²...,...] 1 NAME 2 inherits: \setupboxanchorcontent </pre>
<pre> \definebreakpoint [...¹] [...²] [...,...³...,...] 1 NAME 2 CHARACTER 3 typ = 1 2 3 4 5 nvlevo = NUMMER nvpravo = NUMMER vlevo = BEFEHL stredni = BEFEHL vpravo = BEFEHL range = ano ne language = SPRACHE </pre>
<pre> \definebreakpoints [...[*]] * NAME </pre>
<pre> \definebtx [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupbtx </pre>
<pre> \definebtxdataset [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupbtxdataset </pre>
<pre> \definebtxregister [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupbtxregister </pre>
<pre> \definebtxrendering [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupbtxrendering </pre>

<pre> \definebutton [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupbutton </pre>
<pre> \definecapitals [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavkapitalky </pre>
<pre> \definecollector [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupcollector </pre>
<pre> \definecolumnbreak [...] [...] 1 NAME 2 ano ne nastaveni lokalne sila prvni posledni NUMBER </pre>
<pre> \definecolumnset [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupcolumnset </pre>
<pre> \definecolumnsetarea [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupcolumnsetarea </pre>
<pre> \definecolumnsetspan [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupcolumnsetspan </pre>
<pre> \definecombination [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupcombination </pre>
<pre> \definecomment [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavkomentar </pre>
<pre> \definecomparingtext [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupcomparingtext </pre>
<pre> \definecomplexorsimple *... * CSNAME </pre>
<pre> \definecomplexorsimpleempty *... * CSNAME </pre>
<pre> \definecomplexorsimpleempty {...} * TEXT CSNAME </pre>
<pre> \definecomplexorsimple {...} * TEXT CSNAME </pre>

<pre> \defineconversionset [...¹] [...,²...] [...³] 1 NAME SECTIONBLOCK:NAME 2 NAME PROCESSOR->NAME 3 NAME PROCESSOR->NAME </pre>
<pre> \definecounter [...¹] [...²] [...,³...] 1 NAME 2 NAME 3 inherits: \setupcounter </pre>
<pre> \definedataset [...¹] [...²] [...,³...] 1 NAME 2 NAME 3 inherits: \setupdataset </pre>
<pre> \definedate [...¹] [...,²...] 1 NAME 2 rok year:NAME y y:NAME yy Y Y:NAME YY mesic month:mnem month:hebrew month:jalali m m:mnem m:hebrew m:jalali MESIC MONTH:mnem MONTH:hebrew MONTH:jalali mm M den day:NAME day:+ day:ord day:++ day:highord d d:NAME d:+ d:ord d:++ d:highord dd dd:+ dd:ord dd:++ dd:highord D D:+ D:ord D:++ D:highord vsedniden weekday:mnem weekday:hebrew weekday:jalali w w:mnem w:hebrew w:jalali VSEDNIDEN WEEKDAY:mnem WEEKDAY:hebrew WEEKDAY:jalali W znacka mezera _ TEXT hebrew:to jalali:to jalali:from </pre>
<pre> \definedelimitedtext [...¹] [...²] [...,³...] 1 NAME 2 NAME 3 inherits: \setupdelimitedtext </pre>
<pre> \definedfont [...¹] * FONT </pre>
<pre> \definedocument [...¹] [...²] [...,³...] 1 NAME 2 NAME 3 inherits: \setupdocument </pre>
<pre> \defineeffect [...¹] [...²] [...,³...] 1 NAME 2 NAME 3 inherits: \setupeffect </pre>
<pre> \defineexpandable [...¹] \... {...³} 1 NUMMER 2 CSNAME 3 CONTENT </pre>
<pre> \defineexpansion [...¹] [...²] [...,³...] 1 NAME 2 NAME 3 inherits: \setupexpansion </pre>
<pre> \defineextensiblefiller [...¹] [...²] 1 NAME 2 NUMMER </pre>
<pre> \defineexternalfigure [...¹] [...²] [...,³...] 1 NAME 2 NAME 3 inherits: \setupexternalfigure </pre>
<pre> \definefacingfloat [...¹] [...²] [...,³...] 1 NAME 2 NAME 3 inherits: \setupfacingfloat </pre>


```

\definefallbackfamily [...] [...] [...] [...,..4...,...]
1 NAME OPT
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math
  matematika
3 FONT
4 rscale = NUMBER
  designsizes = implicitni auto
  goodies = FILE
  range = NUMBER NAME
  offset = NUMBER NAME
  check = ano ne
  sila = ano ne
  features = NAME
  tf = TEXT
  bf = TEXT
  it = TEXT
  sl = TEXT
  bi = TEXT
  bs = TEXT
  sc = TEXT

```

```

\definefallbackfamily [...] [...] [...] [...,..4...,...]
1 NAME OPT
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math
  matematika
3 FONT
4 NAME

```

```

\definefieldbody [...] [2...] [...,..3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfieldbody

```

```

\definefieldbodyset [1] [...,2...]
1 NAME
2 NAME

```

```

\definefieldcategory [1] [2] [...,..3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfieldcategory

```

```

\definefileconstant {...} {...}
1 NAME
2 NAME

```

```

\definefilefallback [...] [...,2...]
1 NAME
2 FILE

```

```

\definefilesynonym [...] [2]
1 NAME
2 FILE

```

```

\definefiller [...] [2] [...,..3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfiller

```

```

\definefirstline [1] [2] [...,..3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfirstline

```

```

\definefittingpage [1] [2] [...,..3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfittingpage

```

```
\definefontalternative  [...]
```

```
*  NAME
```

```
\definefontfallback  [...1]  [...2]  [...3,...]  [...4...4,...]
1  NAME
2  FONT NAME
3  NAME NUMMER
4  rscale    =  NUMMER
    sila     =  ano ne
    check    =  ano ne
    offset   =  NUMMER NAME
    target   =  NUMMER NAME
    features  =  NAME
    faktor   =  NUMMER
    metoda   =  lowercase uppercase
```

```
\definefontfamily  [...1]  [...2]  [...3]  [...4...4,...]
1  NAME
2  rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math
   matematika
3  FONT
4  rscale     =  NUMMER
   designsize =  implicitni auto
   goodies    =  FILE
   features   =  NAME
   tf         =  TEXT
   bf         =  TEXT
   it         =  TEXT
   sl         =  TEXT
   bi         =  TEXT
   bs         =  TEXT
   sc         =  TEXT
```

```
\definefontfamilypreset  [...1]  [...2...2,...]
1  NAME
2  inherits: \definefontfamily
```

```
\definefontfamilypreset  [...1]  [...2]
1  NAME
2  NAME
```

```
\definefontfamily  [...1]  [...2]  [...3]  [...4...4,...]
1  NAME
2  rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math
   matematika
3  FONT
4  NAME
```

```

\definefontfeature  [...1]  [...2]  [...,...3...,...]
1  NAME
2  NAME
3  language      = NAME
    script       = NAME auto
    mode         = node base auto zadny
    liga         = ano ne
    kern         = ano ne
    extrakerns   = ano ne
    tlig         = ano ne
    trep         = ano ne
    missing      = ano ne
    dummies      = ano ne
    analyze      = ano ne
    unicoding    = ano ne
    expanzen     = NAME
    protrusion   = NAME
    nostackmath  = ano ne
    realdimensions = ano ne
    itlc         = ano ne
    textitalics  = ano ne
    mathitalics  = ano ne
    slant        = NUMMER
    extend       = NUMMER
    dimensions   = NUMMER strut
    boundingbox  = ano ne pozadi ramecek prazdne COLOR
    compose      = ano ne
    char-ligatures = ano ne
    compat-ligatures = ano ne
    goodies      = FILE
    extrafeatures = ano ne
    featureset   = NAME
    colorscheme  = NAME
    postprocessor = NAME
    mathdimensions = NAME
    keepligatures = ano ne auto
    devanagari   = ano ne
    features     = ano ne
    tcom         = ano ne
    anum        = ano ne
    mathsize     = ano ne
    decomposehangul = ano ne
    mathalternatives = ano ne
    mathgaps     = ano ne
    checkmarks   = ano ne
    uppercasing  = ano ne
    lowercasing  = ano ne
    mathnolimitsmode = NUMMER
    blockligatures = ano ne
    metapost     = NAME
    NAME        = ano ne

```

```

\definefontfile  [...1]  [...2]  [...,...3...,...]
1  NAME
2  FILE
3  features      = NAME
    fallbacks    = NAME
    goodies      = NAME
    designsize   = auto implicitni

```

```

\definefontscriptset  [...1]  [...,...2...,...]
1  NAME
2  NAME

```

```

\definefontsize  [...1]
*  NAME

```

```

\definefontsolution  [...1]  [...2]  [...,...3...,...]
1  NAME
2  NAME
3  inherits: \setupfontsolution

```

$\backslash\text{defineformula}$ $[^1\ldots]$ $[^2\ldots]$ $[^3\ldots\ldots]$
1 NAME 2 NAME 3 inherits: \nastavrovnice
$\backslash\text{defineformulaalternative}$ $[^1\ldots]$ $[^2\ldots]$ $[^3\ldots]$
1 NAME 2 CSNAME 3 CSNAME
$\backslash\text{defineformulaframed}$ $[^1\ldots]$ $[^2\ldots]$ $[^3\ldots\ldots]$
1 NAME 2 NAME 3 inherits: \setupformulaframed
$\backslash\text{defineframedcontent}$ $[^1\ldots]$ $[^2\ldots]$ $[^3\ldots\ldots]$
1 NAME 2 NAME 3 inherits: \setupframedcontent
$\backslash\text{defineframedmath}$ $[^1\ldots]$ $[^2\ldots]$ $[^3\ldots\ldots]$
1 NAME 2 NAME 3 inherits: \nastavoramovani
$\backslash\text{defineframedtable}$ $[^1\ldots]$ $[^2\ldots]$
1 NAME 2 NAME
$\backslash\text{definefrozenfont}$ $[^1\ldots]$ $[^2\ldots]$
1 NAME 2 FONT
$\backslash\text{defineglobalcolor}$ $[^1\ldots]$ $[^2\ldots\ldots]$
1 NAME 2 inherits: \definujbarvu
$\backslash\text{defineglobalcolor}$ $[^1\ldots]$ $[^2\ldots]$
1 NAME 2 COLOR
$\backslash\text{definegraphicstypesynonym}$ $[^1\ldots]$ $[^2\ldots]$
1 NAME 2 NAME
$\backslash\text{definegridsnapping}$ $[^1\ldots]$ $[^2\ldots]$
1 NAME 2 lokalne globalne noheight nodepth box max min zadny radek pulradku prvni posledni minvyska maxheight mindepth maxdepth vrsek spodek strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER box:NUMMER top:NUMMER bottom:NUMMER offset:NUMMER
$\backslash\text{defineheadalternative}$ $[^1\ldots]$ $[^2\ldots]$ $[^3\ldots\ldots]$
1 NAME 2 NAME 3 inherits: \setupheadalternative
$\backslash\text{definehelp}$ $[^1\ldots]$ $[^2\ldots]$ $[^3\ldots\ldots]$
1 NAME 2 NAME 3 inherits: \setuphelp

`\definehigh` [¹...] [²...] [³...,...³...,...]

1 NAME
2 NAME
3 inherits: \setuphigh

`\definehighlight` [¹...] [²...] [³...,...³...,...]

1 NAME
2 NAME
3 inherits: \setuphighlight

`\definehorizontalbox` [¹...] [²...] [³...,...³...,...]

1 NAME
2 NAME
3 inherits: \setuphorizontalbox

`\definehspace` [¹...] [²...] [³...]

1 NAME
2 NAME
3 DIMENSION

`\definehyphenationfeatures` [¹...] [²...,...²...,...]

1 NAME
2 characters = TEXT
hyphens = ano vse TEXT
joiners = ano vse TEXT
rightwords = NUMMER
hyphenmin = NUMMER
lefthyphenmin = NUMMER
righthyphenmin = NUMMER
lefthyphenchar = NUMMER
righthyphenchar = NUMMER
alternativa = original tex hyphenate expanded traditional zadny
pravahrana = tex
rightchars = slovo NUMMER

`\definecharacterkerning` [¹...] [²...] [³...,...³...,...]

1 NAME
2 NAME
3 inherits: \setupcharacterkerning

`\definecharacterspacing` [¹...] [²...]

1 NAME
2 NAME

`\definechemical` [¹...] {²...}

1 NAME
2 CONTENT

`\definechemicals` [¹...] [²...] [³...,...³...,...]

1 NAME
2 NAME
3 inherits: \setupchemical

`\definechemicalsymbol` [¹...] [²...]

1 NAME
2 TEXT

`\definechemistry` [¹...] [²...] [³...,...³...,...]

1 NAME
2 NAME
3 inherits: \setupchemistry

`\defineindentedtext` [¹...] [²...] [³...,...³...,...]

1 NAME
2 NAME
3 inherits: \setupindentedtext

```

\defineindenting [1...] [2...]
1 NAME
2 [-+]male [-+]stredni [-+]velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION

```

```

\defineinitial [1...] [2...] [3...]
1 NAME
2 NAME
3 inherits: \setupinitial

```

```

\defineinsertion [1...] [2...] [3...]
1 NAME
2 NAME
3 inherits: \setupinsertion

```

```

\defineinteraction [1...] [2...] [3...]
1 NAME
2 NAME
3 inherits: \nastavinterakci

```

```

\defineinteractionbar [1...] [2...] [3...]
1 NAME
2 NAME
3 inherits: \nastavinterakcnilistu

```

```

\defineinterfaceconstant {...} {...}
1 NAME
2 NAME

```

```

\defineinterfaceelement {...} {...}
1 NAME
2 NAME

```

```

\defineinterfacevariable {...} {...}
1 NAME
2 NAME

```

```

\defineinterlinespace [1...] [2...] [3...]
1 NAME
2 NAME
3 inherits: \nastavmeziradkovoumezeru

```

```

\defineintermediatecolor [1...] [2...] [3...]
1 NAME
2 COLOR NUMMER
3 a = NUMMER
t = NUMMER

```

```

\defineitemgroup [1...] [2...] [3...]
1 NAME
2 NAME
3 inherits: \setupitemgroup

```

```

\defineitems [1...] [2...] [3...]
1 NAME
2 NAME
3 inherits: \nastavpolozky

```

```

\definelabcolor    [...]1    [...,...2...,...]2
1  NAME
2  l = NUMBER
    a = NUMBER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference
        exclusion hue saturation barevne luminosity
    b = NUMBER
    c = NUMBER
    h = NUMBER
    t = NUMBER
    x = NUMBER
    y = NUMBER
    z = NUMBER
    s = NUMBER

```

```

\definelabcolor    [...]1    [...]2
1  NAME
2  COLOR

```

```

\definelabelclass    [...]1    [...]2
1  NAME
2  NUMBER

```

```

\definelayar    [...]1    [...]2    [...,...3...,...]3
1  NAME
2  NAME
3  inherits: \setuplayer

```

```

\definelayarpreset    [...]1    [...,...2...,...]2
1  NAME
2  inherits: \setuplayer

```

```

\definelayarpreset    [...]1    [...]2
1  NAME
2  NAME

```

```

\definelayout    [...]1    [...]2    [...,...3...,...]3
1  NAME
2  NAME
3  inherits: \nastavvzhled

```

```

\definelinefiller    [...]1    [...]2    [...,...3...,...]3
1  NAME
2  NAME
3  inherits: \setuplinefiller

```

```

\definelinenote    [...]1    [...]2    [...,...3...,...]3
1  NAME
2  NAME
3  inherits: \setuplinenote

```

```

\definelinenumbering    [...]1    [...]2    [...,...3...,...]3
1  NAME
2  NAME
3  inherits: \nastavcislovaniradku

```

```

\definelineprofile    [...]1    [...]2    [...,...3...,...]3
1  NAME
2  NAME
3  inherits: \setuplineprofile

```

```

\definelines    [...]1    [...]2    [...,...3...,...]3
1  NAME
2  NAME
3  inherits: \nastavradky

```

<pre> \definelistalternative [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuplistalternative </pre>
<pre> \definelistextra [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuplistextra </pre>
<pre> \definelocalboxes [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuplocalboxes </pre>
<pre> \definelow [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuplow </pre>
<pre> \definelowhigh [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuplowhigh </pre>
<pre> \definelowmidhigh [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuplowmidhigh </pre>
<pre> \defineMPinstance [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupMPinstance </pre>
<pre> \definemarginblock [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupmarginblock </pre>
<pre> \definemargindata [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupmargindata </pre>
<pre> \definemarker [...] * NAME </pre>
<pre> \definemathaccent [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupmathaccent </pre>
<pre> \definemathalignment [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupmathalignment </pre>
<pre> \definemathannotation [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupmathannotation </pre>

<pre> \definemathbottomaccent [...] [...] [...] 1 spodek bottom:stretch NAME OPT 2 NAME 3 NUMMER </pre>
<pre> \definemathcases [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathcases </pre>
<pre> \definemathcommand [...] [...] {...} 1 NAME OPT OPT 2 vse begin end unset ordinary operator binary relation open close punctuation variable active uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential exponential integral ellipsis function digit division factorial wrapped construct dimension unary textpunctuation unspaced experimental fake numbergroup continuation 3 BEFEHL </pre>
<pre> \definemathcommand [...] [...] [...] {...} 1 NAME 2 vse begin end unset ordinary operator binary relation open close punctuation variable active uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential exponential integral ellipsis function digit division factorial wrapped construct dimension unary textpunctuation unspaced experimental fake numbergroup continuation 3 vse begin end unset ordinary operator binary relation open close punctuation variable active uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential exponential integral ellipsis function digit division factorial wrapped construct dimension unary textpunctuation unspaced experimental fake numbergroup continuation 4 BEFEHL </pre>
<pre> \definemathcommand [...] [...] [...] {...} 1 NAME 2 vse begin end unset ordinary operator binary relation open close punctuation variable active uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential exponential integral ellipsis function digit division factorial wrapped construct dimension unary textpunctuation unspaced experimental fake numbergroup continuation 3 jedna 4 \...#1 </pre>
<pre> \definemathcommand [...] [...] [...] {...} 1 NAME 2 vse begin end unset ordinary operator binary relation open close punctuation variable active uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential exponential integral ellipsis function digit division factorial wrapped construct dimension unary textpunctuation unspaced experimental fake numbergroup continuation 3 dve 4 \...#1#2 </pre>
<pre> \definemathconstant [...] [...] 1 NAME 2 CHARACTER </pre>
<pre> \definemathdelimited [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathdelimited </pre>
<pre> \definemathdelimiter [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathdelimiters </pre>
<pre> \definemathdouble [...] [...] [...] [...] [...] 1 obe vfenced NAME OPT 2 inherits: \setupmathstackers 3 NAME 4 NUMMER 5 NUMMER </pre>

<pre> \definemathdoubleaccent [...] [...] [...] [...] 1 obe both:stretch NAME OPT 2 NAME 3 NUMMER 4 NUMMER </pre>
<pre> \definemathdoubleextensible [...] [...] [...] [...] 1 obe vfenced OPT 2 NAME 3 NUMMER 4 NUMMER </pre>
<pre> \definematematics [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmatematics </pre>
<pre> \definemathextensible [...] [...] [...] 1 reverse mathematika text chemistry 2 NAME 3 NUMMER </pre>
<pre> \definemathfence [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathfences </pre>
<pre> \definemathfraction [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathfraction </pre>
<pre> \definemathframed [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathframed </pre>
<pre> \definemathfunction [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathfunctions </pre>
<pre> \definemathgroupset [...] [...] 1 NAME 2 every implicitni binary_set_relation binary_set_relation integral limit number_set postfix_operator prime binary_operator binary_vector binary_arithmetic binary_logical binary_set constant arithmetic constant_set differential differential2 factorial interval quantifier unary_set constant_logical partial nary_operator nary_logical specifier specifier2 pause punctuation unary_logical whatever whatever2 </pre>
<pre> \definemathmatrix [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathmatrix </pre>
<pre> \definemathnesting [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathnesting </pre>
<pre> \definemathoperator [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupmathoperators </pre>

$\backslash$ definemathornament [¹ ...] [² ...] [³ ...,... ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupmathornament
$\backslash$ definemathover [¹ ...] [² ...] [³ ...] 1 vrsek vfenced NAME 2 NAME 3 NUMMER
$\backslash$ definemathoverextensible [¹ ...] [² ...] [³ ...] 1 vrsek vfenced 2 NAME 3 NUMMER
$\backslash$ definemathovertextextensible [¹ ...] [² ...] [³ ...] 1 bothtext 2 NAME 3 NUMMER
$\backslash$ definemathpreset [¹ ...] [² ... ² ...] 1 NAME 2 faktor = NUMMER pismeno = vse obrazovka text script scriptscript crampeddisplay crampedtext crampedscript crampedscriptscript seznam = quad exheight axis accentbaseheight accentbasedepth flattenedaccentbaseheight flattenedaccentbasedepth xscale yscale operatorsize overbarkern overbarrule overbarvgap underbarkern underbarrule underbarvgap radicalkern radicalrule radicalvgap radicaldegreebefore radicaldegreeafter radicaldegreeraise radicalextensibleafter radicalextensiblebefore stackvgap stacknumup stackdenomdown fractionrule fractionnumvgap fractionnumup fractiondenomvgap fractiondenomdown fractionondelsize skewedfractionhgap skewedfractionvgap limitabovevgap limitabovebgap limitabovekern limitbelowvgap limitbelowbgap limitbelowkern nolimitsubfactor nolimitsupfactor underdelimitervgap underdelimiterbgap overdelimitervgap overdelimiterbgap subshiftdrop supshiftdrop subshiftdown subsupshiftdown subtopmax supshiftdown subbottommin supsubbottommax subsupvgap spacebeforescript spacebetween script spaceafterscript connectoroverlapmin superscriptsnap subscriptsnap extrasuperscriptshift extrasubscriptshift extrasuperprescriptshift extrasubprescriptshift primeraise primeraisecomposed primeshiftup primeshiftdrop primespaceafter ruleheight ruledepth extrasuperscriptspace extrasubscriptspace extrasuperprescriptspace extrasubprescriptspace skeweddelimiter tolerance accenttopshiftup accentbottomshiftdown accenttopovershoot accentbottomovershoot accentsuperscriptdrop accentsuperscriptpercent accentextendmargin flattenedaccenttopshiftup flattenedaccentbottomshiftdown delimiterpercent delimitershortfall delimiterextendmargin overlinevariant underlinevariant overdelimitervariant underdelimitervariant delimiterovervariant delimiterundervariant hextensiblevariant vextensiblevariant fractionvariant radicalvariant accentvariant degreevariant topaccentvariant bottomaccentvariant overlayaccentvariant numeratorvariant denominatorvariant superscriptvariant subscriptvariant primevariant stackvariant jednotka = axis
$\backslash$ definemathradical [¹ ...] [² ...] [³ ...,... ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupmathradical
$\backslash$ definemathsimplealign [¹ ...] [² ...] [³ ...,... ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupmathsimplealign
$\backslash$ definemathspacing [¹ ...] [² ...] [³ ...] 1 NAME 2 horizontalne vertikalne NUMMER 3 NUMMER
$\backslash$ definemathstackers [¹ ...] [² ...] [³ ...,... ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupmathstackers
$\backslash$ definemathstyle [¹ ...] [² ...,... ² ...] 1 NAME 2 obrazovka text script scriptscript cramped uncramped normalni zhustene male velke

```

\definemathsymbol    [^1.]    [^2.]    [^3.]
1  NAME
2  vse begin end unset ordinary operator binary relation open close punctuation variable active uvnitr under over
   fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential exponential integral
   ellipsis function digit division factorial wrapped construct dimension unary textpunctuation unspaced experimental
   fake numbergroup continuation
3  NUMMER

```

```

\definemathtext    [^1.]    [^2.]    [^3.]
1  NAME
2  NAME
3  inherits: \setupmathtext

```

```

\definemathtopaccent    [^1.]    [^2.]    [^3.]
1  vrsek top:stretch top:dot NAME
2  NAME
3  NUMMER

```

```

\definemathtoysymbol    [^1.]    [^2.]    [^3.]
1  NAME
2  vse begin end unset ordinary operator binary relation open close punctuation variable active uvnitr under over
   fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential exponential integral
   ellipsis function digit division factorial wrapped construct dimension unary textpunctuation unspaced experimental
   fake numbergroup continuation
3  CHARACTER

```

```

\definemathtriplet    [^1.]    [^2.]    [^3.]
1  NAME
2  NAME
3  TEXT

```

```

\definemathunder    [^1.]    [^2.]    [^3.]
1  spodek vfenced NAME
2  NAME
3  NUMMER

```

```

\definemathunderextensible    [^1.]    [^2.]    [^3.]
1  spodek vfenced
2  NAME
3  NUMMER

```

```

\definemathundertextextensible    [^1.]    [^2.]    [^3.]
1  bothtext
2  NAME
3  NUMMER

```

```

\definemathunstacked    [^1.]    [^2.]    [^3.]
1  siroce
2  NAME
3  NUMMER

```

```

\definemeasure    [^1.]    [^2.]
1  NAME
2  DIMENSION

```

```

\definemessageconstant    {.*}
*  NAME

```

```

\definemixedcolumns    [^1.]    [^2.]    [^3.]
1  NAME
2  NAME
3  inherits: \setupmixedcolumns

```

<pre> \definemode [...¹,...] [...²] 1 NAME 2 ano ne drzet </pre>
<pre> \definemulticolumns [...¹] [...²] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupmulticolumns </pre>
<pre> \definemultitonecolor [...¹] [...,²...,...] [...,³...,...] [...,⁴...,...] 1 NAME 2 COLOR = NUMMER 3 inherits: \definujbarvu 4 inherits: \definespotcolor </pre>
<pre> \definenamecolor [...¹] [...,²...,...] 1 NAME 2 inherits: \definujbarvu </pre>
<pre> \definenamecolor [...¹] [...²] 1 NAME 2 COLOR </pre>
<pre> \definenamespace [...¹] [...,²...,...] 1 NAME 2 jmeno = TEXT parent = TEXT pismo = ano ne prikaz = ano ne seznam setup = ano ne seznam set = ano ne seznam ramecek = ano ne </pre>
<pre> \definennarrower [...¹] [...²] [...,³...,...] 1 NAME 2 NAME 3 inherits: \nastavzuzeni </pre>
<pre> \definernote [...¹] [...²] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupnote </pre>
<pre> \defineoptimize [...¹] [...²] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupoptimize </pre>
<pre> \defineorientation [...¹] [...²] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setuporientation </pre>
<pre> \defineornament [...¹] [...,²...,...] [...,³...,...] 1 NAME 2 alternativa = a b inherits: \setupcollector 3 pismo = STYLE BEFEHL barva = COLOR inherits: \nastavoramovani </pre>
<pre> \defineornament [...¹] [...,²...,...] [...,³...,...] 1 NAME 2 alternativa = a b inherits: \setuplayer 3 inherits: \setuplayeredtext </pre>

<code>\defineoutputroutine</code> [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupoutputroutine
<code>\defineoutputroutinecommand</code> [...,*...] * KEY
<code>\definepage</code> [¹ ...] [² ...] 1 NAME 2 REFERENCE
<code>\definepagebreak</code> [¹ ...] [..., ² ...] 1 NAME 2 prazdne zahlavi upati dummy ramecek NUMBER +NUMBER implicitni reset zablokovat ano ne zlom prazdny nastaveni vysokapriorita vlevo vpravo sude liche ctyrnasobny posledni poslednistrana start stop xy note
<code>\definepagecolumns</code> [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setuppagecolumns
<code>\definepagechecker</code> [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setuppagechecker
<code>\definepageinjection</code> [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setuppageinjection
<code>\definepageinjectionalternative</code> [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setuppageinjectionalternative
<code>\definepageshift</code> [¹ ...] [² ...] [..., ³ ...] 1 NAME 2 horizontalne vertikalne 3 DIMENSION
<code>\definepagestate</code> [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setuppagestate
<code>\definepairedbox</code> [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setuppairedbox
<code>\defineparagraph</code> [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupparagraph
<code>\defineparallel</code> [¹ ...] [..., ² ...] 1 NAME 2 NAME
<code>\defineparbuilder</code> [¹ ...] * NAME

<pre> \defineparinsert [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupparinsert </pre>
<pre> \defineperiodkerning [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupperiodkerning </pre>
<pre> \defineplaceholder [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupplaceholder </pre>
<pre> \defineplacement [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupplacement </pre>
<pre> \definepositioning [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \nastavumistovani </pre>
<pre> \defineprefixset [...¹] [...,²...] [...³] 1 NAME SECTIONBLOCK:NAME 2 ABSCHNITT 3 ABSCHNITT </pre>
<pre> \defineprocesscolor [...¹] [...²] [...,...³...,...] 1 NAME 2 COLOR 3 inherits: \definujbarvu </pre>
<pre> \defineprocessor [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupprocessor </pre>
<pre> \definepushbutton [...¹] [...,...²...,...] 1 NAME 2 inherits: \setupfieldcontentframed </pre>
<pre> \definepushsymbol [...¹] [...²] 1 NAME 2 n r d </pre>
<pre> \definerenderingwindow [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuprenderingwindow </pre>
<pre> \defineresetset [...¹] [...,²...] [...³] 1 NAME SECTIONBLOCK:NAME 2 NUMMER 3 NUMMER </pre>
<pre> \defineruby [...¹] [...²] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupruby </pre>

<pre> \definesavebuffer [¹...] [²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupsavebuffer </pre>
<pre> \definescale [¹...] [²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupscale </pre>
<pre> \definescript [¹...] [²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupscrip </pre>
<pre> \definesectionlevels [¹...] [...,²...] 1 NAME 2 ABSCHNITT </pre>
<pre> \defineselector [¹...] [...,²...,...] 1 NAME 2 inherits: \setupselector </pre>
<pre> \defineseparatorset [¹...] [...,²...] [³...] 1 NAME SECTIONBLOCK:NAME 2 BEFEHL PROCESSOR->BEFEHL 3 BEFEHL PROCESSOR->BEFEHL </pre>
<pre> \defineshadow [¹...] [²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupshadow </pre>
<pre> \defineshift [¹...] [²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupshift </pre>
<pre> \definesidebar [¹...] [²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupsidebar </pre>
<pre> \definesort [¹...] [²...] [³...] {⁴...} 1 ano ne 2 SINGULAR 3 NAME 4 CONTENT </pre>
<pre> \definespotcolor [¹...] [²...] [...,³...,...] 1 NAME 2 COLOR 3 a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity t = NUMMER e = TEXT p = NUMMER </pre>
<pre> \definestacking [¹...] [²...] [...,³...,...] 1 NAME 2 NAME 3 inherits: \setupstacking </pre>


```
\definestyleinstance  [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT
2 rm ss tt mm hw cg
3 tf bf it sl bi bs sc
4 BEFEHL
```

```
\definesubcolumnset [...]1 [...]2 [...]3, [...]4
1 NAME
2 NAME
3 NUMMER
```

```
\definesubformula [...]1 [...]2 [...]3, [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupsformula
```

```
\definesynchronize [...]1 [...]2 [...]3, [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupsynchronize
```

```
\definesynchronizecontent [...]1 [...]2 [...]3, [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupsynchronizecontent
```

```
\definesynonym [...]1 [...]2 [...]3 [...]4 {...}5 {...}6
1 ano ne OPT OPT
2 SINGULAR
3 NAME
4 TEXT
5 TEXT
6 CONTENT
```

```
\definesystemattribute [...]1 [...]2, [...]3
1 NAME OPT
2 lokale globale public private pickup
```

```
\definesystemconstant {...}*
* NAME
```

```
\definesystemvariable {...}*
* NAME
```

```
\defineTABLEsetup [...]1 [...]2, [...]3, [...]4
1 NAME
2 inherits: \setupTABLE
```

```
\definetabulatemove [...]1 [...]2 [...]3, [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setuptabulatemove
```

```
\definetextbackground [...]1 [...]2 [...]3, [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setuptextbackground
```

```
\definetextdisplay [...]1 [...]2 [...]3, [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setuptextdisplay
```

<pre> \definetextflow [...]¹ [...]² [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuptextflow </pre>
<pre> \definetextnote [...]¹ [...]² [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuptextnote </pre>
<pre> \definetokenlist [...][*] * NAME </pre>
<pre> \definetooltip [...]¹ [...]² [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuptooltip </pre>
<pre> \definetransliteration [...]¹ [...]² [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuptransliteration </pre>
<pre> \definetransparency [...]¹ [...]² 1 NAME 2 NUMMER </pre>
<pre> \definetransparency [...]¹ [...,...²...,...] 1 NAME 2 a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity t = NUMMER </pre>
<pre> \definetransparency [...]¹ [...]² 1 NAME 2 NAME </pre>
<pre> \definetweakedfont [...]¹ [...]² [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setuptweakedfont </pre>
<pre> \definetype [...]¹ [...]² [...,...³...,...] 1 NAME 2 NAME 3 inherits: \nastavtype </pre>
<pre> \definetypeface [...]¹ [...]² [...]³ [...]⁴ [...]⁵ [...,...⁶...,...] 1 NAME 2 rm ss tt mm hw cg 3 serif sans mono math handwriting calligraphy 4 NAME 5 implicitni dtp 6 rscale = auto NUMMER features = NAME fallbacks = NAME goodies = NAME designsize = auto implicitni smer = obe </pre>
<pre> \definetypescriptprefix [...]¹ [...]² 1 NAME 2 TEXT </pre>

$\backslash$ definetypescriptsynonym [¹ ...] [...] 1 NAME 2 TEXT
$\backslash$ definetypesetting [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 TEXT 3 inherits: \setupexternalfigure
$\backslash$ defineunit [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupunit
$\backslash$ defineuserdata [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupuserdata
$\backslash$ defineuserdataalternative [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupuserdataalternative
$\backslash$ defineverticalbox [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupverticalbox
$\backslash$ defineviewerlayer [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupviewerlayer
$\backslash$ definevspace [¹ ...] [² ...] [³] 1 NAME 2 NAME 3 DIMENSION
$\backslash$ definevspacing [¹ ...] [²] 1 NAME 2 inherits: \vspacing
$\backslash$ definevspacingamount [¹ ...] [² ...] [³] 1 NAME 2 DIMENSION 3 DIMENSION
$\backslash$ definewrows [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setuprows
$\backslash$ definetable [¹ ...] [² ...] [..., ³ ...,...] 1 NAME 2 NAME 3 inherits: \setupxtable
$\backslash$ definuj [¹ ...] \ ² ... { ³ ...} 1 NUMBER 2 CSNAME 3 CONTENT

<pre> \definujakcent .¹. .². .³. 1 CHARACTER 2 CHARACTER 3 CHARACTER </pre>
<pre> \definujbarvu [...]¹ [...,...²...,...]³ 1 NAME 2 r = NUMBER g = NUMBER b = NUMBER c = NUMBER m = NUMBER y = NUMBER k = NUMBER h = NUMBER s = NUMBER v = NUMBER w = NUMBER x = NUMBER a = NUMBER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity t = NUMBER </pre>
<pre> \definujbarvu [...]¹ [...]² 1 NAME 2 COLOR </pre>
<pre> \definujblok [...]¹ [...]² [...,...³...,...]³ 1 NAME OPT OPT 2 NAME 3 inherits: \nastavblok </pre>
<pre> \definujbloksekce [...]¹ [...]² [...,...³...,...]³ 1 NAME OPT 2 NAME 3 inherits: \nastavbloksekce </pre>
<pre> \definujbuffer [...]¹ [...]² [...,...³...,...]³ 1 NAME OPT OPT 2 BUFFER 3 inherits: \nastavbuffer </pre>
<pre> \definujfont [...]¹ [...]² [...,...³...,...]³ 1 NAME OPT 2 FONT 3 inherits: \nastavmeziradkovoumezeru </pre>
<pre> \definujfont [...]¹ [...]² [...]³ 1 NAME OPT 2 FONT 3 NAME </pre>
<pre> \definujformatodkazu [...]¹ [...]² [...,...³...,...]³ 1 NAME OPT OPT 2 NAME 3 inherits: \setupreferenceformat </pre>
<pre> \definujhbox [...]¹ [...]² 1 NAME 2 DIMENSION </pre>
<pre> \definujinterakcnimenu [...]¹ [...]² [...,...³...,...]³ 1 NAME OPT OPT 2 NAME 3 inherits: \nastavinterakcnimenu </pre>

<pre> \definujkombinovanyseznam [...¹] [...,²...] [...,³...^{OPT},...] 1 NAME 2 LISTE 3 inherits: \nastavkombinovanyseznam </pre>
<pre> \definujkonverzi [...¹] [...²] [...³] 1 SPRACHE 2 NAME 3 CSNAME </pre>
<pre> \definujkonverzi [...¹] [...²] [...,³...] 1 SPRACHE 2 NAME 3 TEXT </pre>
<pre> \definujnadpis [...¹] [...²] [...,³...^{OPT},...] 1 NAME 2 ABSCHNITT 3 inherits: \nastavnadpis </pre>
<pre> \definujobrazeksymbol [...¹] [...²] [...,³...^{OPT},...] 1 NAME 2 FILE NAME 3 inherits: \externiobraz </pre>
<pre> \definujodkaz [...¹] [...,²...] 1 NAME 2 REFERENCE </pre>
<pre> \definujodstavce [...¹] [...²] [...,³...^{OPT},...] 1 NAME 2 NAME 3 inherits: \nastavodstavce </pre>
<pre> \definujopis [...¹] [...²] [...,³...^{OPT},...] 1 NAME 2 NAME 3 inherits: \nastavopis </pre>
<pre> \definujoramovani [...¹] [...²] [...,³...^{OPT},...] 1 NAME 2 NAME 3 inherits: \nastavoramovani </pre>
<pre> \definujoramovanytext [...¹] [...²] [...,³...^{OPT},...] 1 NAME 2 NAME 3 inherits: \setupframedtext </pre>
<pre> \definujpaletu [...¹] [...,²...^{OPT},...] 1 NAME 2 NAME = COLOR </pre>
<pre> \definujpaletu [...¹] [...²] 1 NAME 2 NAME </pre>
<pre> \definujplvouciobjekt [...¹] [...²] [...,³...^{OPT},...] 1 SINGULAR 2 SINGULAR PLURAL 3 inherits: \nastavplvouciobjekt instances: chemical figure table intermezzo graphic </pre>

```
\definujplvouciobjekt  [...1]  [...2]  [...3]
1  SINGULAR
2  PLURAL
3  SINGULAR
instances: chemical figure table intermezzo graphic
```

```
\definujpodpole  [...1]  [...2]  [...3,...]
1  NAME
2  NAME
3  NAME
```

```
\definujpole  [...1]  [...2]  [...3]  [...4,...]  [...5]
1  NAME
2  radio pod text radek push check signature
3  NAME
4  NAME
5  NAME
```

```
\definujpopis  [...1]  [...2]  [...3,...3,...]
1  NAME
2  NAME
3  inherits: \setupdescription
```

```
\definujpopisek  [...1]  [...2]  [...3,...3,...]
1  NAME
2  NAME
3  inherits: \setuplabel
```

```
\definujprekryv  [...1,...]  [...2]  [...3]
1  NAME
2  NAME
3  BEFEHL
```

```
\definujprikaz  ...1  ...2
1  CHARACTER
2  BEFEHL
```

```
\definujprofil  [...1]  [...2]  [...3,...3,...]
1  NAME
2  NAME
3  inherits: \setupprofile
```

```
\definujprogram  [...1]  [...2]  [...3]
1  NAME
2  TEXT
3  TEXT
```

```
\definujprostredizakladnihofontu  [...1]  [...2]  [...3,...3,...]
1  NAME
2  implicitni DIMENSION
3  velky = DIMENSION NUMMER
   male = DIMENSION NUMMER
   a = DIMENSION NUMMER
   b = DIMENSION NUMMER
   c = DIMENSION NUMMER
   d = DIMENSION NUMMER
   text = DIMENSION NUMMER
   x = DIMENSION NUMMER
   xx = DIMENSION NUMMER
   script = DIMENSION NUMMER
   scriptscript = DIMENSION NUMMER
   meziradkovamezera = DIMENSION
   em = sklonene kurziva STYLE BEFEHL
   * = NUMMER
```

<pre> \definujrejstrik [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \nastavrejstrik </pre>
<pre> \definujsablonutabulky [...] [...] [...] [...] 1 NAME 2 TEMPLATE 3 NAME 4 NAME </pre>
<pre> \definujsekcii [...] * NAME </pre>
<pre> \definujseznam [...] [...] [...,...³...,...] 1 NAME 2 LISTE 3 inherits: \nastavseznam </pre>
<pre> \definujskupinubarev [...] [...] [x:y:³z,...] 1 NAME 2 seda rgb cmyk spot 3 TRIPLET </pre>
<pre> \definujstartstop [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupstartstop </pre>
<pre> \definujstyl [...] [...] [...,...³...,...] 1 NAME 2 NAME 3 inherits: \setupstyle </pre>
<pre> \definujstylfontu [...,¹...] [...] 1 NAME 2 NAME </pre>
<pre> \definujsymbol [...] [...] [...] 1 NAME 2 NAME 3 BEFEHL </pre>
<pre> \definujsynonumumfontu [...] [...] [...,...³...,...] 1 NAME 2 FONT 3 features = NAME fallbacks = NAME goodies = NAME designsize = auto implicitni </pre>
<pre> \definujsynonyma [...] [...] [...] [...] 1 SINGULAR 2 PLURAL 3 CSNAME 4 CSNAME </pre>
<pre> \definujtabelaci [...] [...] [...] 1 NAME 2 NAME 3 TEMPLATE </pre>

<pre> \definujtext [...¹] [...²] [...³] [...⁴] [...⁵] [...⁶] [...⁷] 1 NAME 2 vrsek zahlavi text upati spodek 3 text marginalie hrana 4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL 5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL 6 datum cislostranky BESCHRIFTUNG TEXT BEFEHL 7 datum cislostranky BESCHRIFTUNG TEXT BEFEHL </pre>
<pre> \definujtrideni [...¹] [...²] [...³] 1 SINGULAR 2 PLURAL 3 zadny CSNAME </pre>
<pre> \definujupravu [...¹] [...²] [...³...,...] 1 NAME 2 NAME 3 inherits: \nastavupravu </pre>
<pre> \definujvelikostpapiru [...¹] [...²...,...] 1 NAME 2 sirka = DIMENSION vyska = DIMENSION vrsek = BEFEHL spodek = BEFEHL vlevo = BEFEHL vpravo = BEFEHL vzdalenost = DIMENSION stranka = inherits: \nastavvelikostpapiru papir = inherits: \nastavvelikostpapiru </pre>
<pre> \definujvelikostpapiru [...¹] [...²...,...] [...³...,...] 1 NAME 2 inherits: \nastavvelikostpapiru 3 inherits: \nastavvelikostpapiru </pre>
<pre> \definujvycet [...¹] [...²] [...³...,...] 1 NAME 2 NAME 3 inherits: \setupenumeration </pre>
<pre> \definujzakladnifont [...¹...,...] [...²...,...] [...³...,...] [...⁴...,...] 1 NAME implicitni 2 NAME DIMENSION 3 rm ss tt hw cg 4 tf = FILE bf = FILE it = FILE sl = FILE bi = FILE bs = FILE sc = FILE mr = FILE mrlr = FILE mrrl = FILE mb = FILE mblr = FILE mbrl = FILE </pre>
<pre> \definujzakladnifont [...¹...,...] [...²...,...] [...³...,...] [...⁴] 1 NAME implicitni 2 NAME DIMENSION 3 rm ss tt hw cg 4 NAME </pre>
<pre> \definujzasobnikpoli [...¹] [...²...,...] [...³...,...] 1 NAME 2 NAME 3 inherits: \setupfieldcategory </pre>


```
\definujznaceni    [ 1... ]    [ 2... ]    [ 3...OPT...OPT ]
1 NAME
2 BESCHRIFTUNG
3 inherits: \nastavznaceni
```

```
\definujznak      .1 .2
1  CHARACTER
2  NUMBER
```

```
\defrostoparagraphproperties
```

```
\delimited    [.^..]    [.^..]    {.^..}
1  NAME
2  SPRACHE
3  CONTENT
```

```
\delimitedtext    [.1.]    [.2...]    {.3.}
```

```
1  NAME
```

```
2  SPRACHE
```

```
3  CONTENT
```

<pre> \DELIMITEDTEXT [..] {...} 1 SPRACHE 2 CONTENT instances: quotation quote blockquote speech aside </pre>

```
\aside    [1...]    {...}
1  SPRACHE    OPT
2  CONTENT
```

```
\blockquote    [.1.]    {.2.}
```

```
1  SPRACHE      OPT
```

```
2  CONTENT
```

<pre> \quotation [.¹.] {..².} 1 SPRACHE OPT 2 CONTENT </pre>

```
\quote  [1...]  {2...}
```

```
1  SPRACHE      OPT
```

```
2  CONTENT
```

```
\speech [..1..] {..2..}
1  SPRACHE      OPT
2  CONTENT
```

\delkaseznamu

`\depthlinebottom`

```
\depthofstring  {...}
*   TEXT
```

```
\depthonlybox    {...}
*    CONTENT
```

```
\depthspanningtext   {...}   {...}   {...}
1   TEXT
2   DIMENSION
3   FONT
```

<code>\depthstrut</code>
<code>\detachinsections ...</code> <code>* NUMMER</code>
<code>\determinednoflines {...}</code> <code>* CONTENT</code>
<code>\determinenoflines {...}</code> <code>* CONTENT</code>
<code>\detokenizedPRIKAZparameter {...}</code> <code>* KEY</code>
<code>\detokenizedrootPRIKAZparameter {...}</code> <code>* KEY</code>
<code>\devanagarinumerals {...}</code> <code>* NUMMER</code>
<code>\digits {...}</code> <code>* NUMMER</code>
<code>\digitsbreak</code>
<code>\digits ...</code> <code>* NUMMER</code>
<code>\dimensiontocount {¹...} \²...</code> <code>1 DIMENSION</code> <code>2 CSNAME</code>
<code>\directboxfromcache {¹...} {²...}</code> <code>1 NAME</code> <code>2 NUMMER TEXT</code>
<code>\directcolor [...]</code> <code>* COLOR</code>
<code>\directcolored [...[*]...]</code> <code>* inherits: \definujbarvu</code>
<code>\directcolored [...]</code> <code>* COLOR</code>
<code>\directPRIKAZparameter {...}</code> <code>* KEY</code>
<code>\directconvertedcounter {¹...} {²...}</code> <code>1 NAME</code> <code>2 prvni predchozi dalsi posledni cislo</code>
<code>\directcopyboxfromcache {¹...} {²...}</code> <code>1 NAME</code> <code>2 NUMMER TEXT</code>
<code>\directdummyparameter {...}</code> <code>* KEY</code>

<code>\directgetboxllx .*</code> <code>* CSNAME NUMBER</code>
<code>\directgetboxlly .*</code> <code>* CSNAME NUMBER</code>
<code>\directgoto {¹...} [²...]</code> <code>1 CONTENT</code> <code>2 REFERENCE</code>
<code>\directhighlight {¹...} {²...}</code> <code>1 NAME</code> <code>2 TEXT</code>
<code>\directlocalframed [¹...] {²...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\directluacode {.*}</code> <code>* BEFEHL</code>
<code>\directmathextensible [¹...] {²...} {³...} {⁴...}</code> <code>1 reverse mathematika text chemistry</code> <code>2 NUMBER</code> <code>3 TEXT</code> <code>4 TEXT</code>
<code>\directparwrapper {¹...} {²...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code>
<code>\directselect {¹...} {²...} {³...} {⁴...} {⁵...} {⁶...}</code> <code>1 NAME</code> <code>2 CONTENT</code> <code>3 CONTENT</code> <code>4 CONTENT</code> <code>5 CONTENT</code> <code>6 CONTENT</code>
<code>\directsetbar {.*}</code> <code>* NAME</code>
<code>\directsetup {.*}</code> <code>* NAME</code>
<code>\directsymbol {¹...} {²...}</code> <code>1 NAME</code> <code>2 NAME</code>
<code>\directtextextensible [¹...] {²...} {³...} {⁴...}</code> <code>1 reverse mathematika text chemistry</code> <code>2 NUMBER</code> <code>3 TEXT</code> <code>4 TEXT</code>
<code>\directvspacing {...,*...}</code> <code>* inherits: \vspacing</code>
<code>\dis {.*}</code> <code>* CONTENT</code>
<code>\disableddelimiter</code>

<code>\disabledirectives</code> [...,*,...] * NAME
<code>\disableexperiments</code> [...,*,...] * NAME
<code>\disablefiller</code>
<code>\disablemathautofencing</code>
<code>\disablemathautonumbers</code>
<code>\disablemathautospaceing</code>
<code>\disablemathpunctuation</code>
<code>\disablemode</code> [...,*,...] * NAME
<code>\disableoutputstream</code>
<code>\disableparpositions</code>
<code>\disableregime</code>
<code>\disabletrackers</code> [...,*,...] * NAME
<code>\displaymath</code> {...} * CONTENT
<code>\displaymathematics</code> {...} * CONTENT
<code>\displaymessage</code> {...} * TEXT
<code>\disposeuatable</code> *... * CSNAME
<code>\distributedhsize</code> {...} {...} {...} 1 DIMENSION 2 DIMENSION 3 NUMMER
<code>\dividedsize</code> {...} {...} {...} 1 DIMENSION 2 DIMENSION 3 NUMMER
<code>\dm</code> {...} * CONTENT
<code>\doadaptleftskip</code> {...} * ano ne standardni DIMENSION

\doadaptrightskip {...} * ano ne standardni DIMENSION
\doaddfeature {...,*...} * NAME
\doapostrophes
\doassign [... ¹] [... ² ...] 1 TEXT 2 KEY = VALUE
\doassignempty [... ¹] [... ² ...] 1 TEXT 2 KEY = VALUE
\doboundtext {... ¹ } {... ² } {... ³ } 1 TEXT 2 DIMENSION 3 BEFEHL
\documentvariable {...} * KEY
\dodoubleargument \... [... ²] [... ³] 1 CSNAME 2 TEXT 3 TEXT
\dodoubleargumentwithset \... [... ² ,...] [... ³] 1 CSNAME 2 TEXT 3 TEXT
\dodoubleempty \... [... ²] _{OPT} [... ³] _{OPT} 1 CSNAME 2 TEXT 3 TEXT
\dodoubleemptywithset \... [... ² ,...] _{OPT} [... ³] _{OPT} 1 CSNAME 2 TEXT 3 TEXT
\dodoublegroupempty \... {... ² } _{OPT} {... ³ } _{OPT} 1 CSNAME 2 TEXT 3 TEXT
\doeassign [... ¹] [... ² ...] 1 TEXT 2 KEY = VALUE
\doexpandedrecurse {... ¹ } {... ² } 1 NUMMER 2 BEFEHL
\doexpandedrecursed {... ¹ } {... ² } 1 NUMMER 2 BEFEHL
\doexplicitlyphens

```

1  NUMMER
2  CSNAME

```

* NAME

* NAME

1	NUMMER
2	TEXT
3	CSNAME

1	NAME
2	NAME
3	CSNAME
4	CONTENT

1	NAME
2	NAME
3	CSNAME
4	CONTENT

```

1  TEXT
2  TEXT

```

* TEXT

\dohyphens

* TEXT

* TEXT

```
1  CONTENT
2  CONTENT
3  TRUE
```

```
1 TEXT
2 TEXT
3 TRUE
```

```
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

\doifalldefinedelse {...,¹...} {...².} {...³.}

1 NAME
2 TRUE
3 FALSE

\doifallmodes {...,¹...} {...².}

1 NAME
2 TRUE

\doifallmodeselse {...,¹...} {...².} {...³.}

1 NAME
2 TRUE
3 FALSE

\doifallundefinedelse {...,¹...} {...².} {...³.}

1 NAME
2 TRUE
3 FALSE

\doifassignmentelse {...¹.} {...².} {...³.}

1 TEXT
2 TRUE
3 FALSE

\doifassignmentelsecs {...¹.} \...² \...³.

1 TEXT
2 CSNAME
3 CSNAME

\doifblackelse {...¹.} {...².} {...³.}

1 COLOR
2 TRUE
3 FALSE

\doifbothsides {...¹.} {...².} {...³.}

1 BEFEHL
2 BEFEHL
3 BEFEHL

\doifbothsidesoverruled {...¹.} {...².} {...³.}

1 BEFEHL
2 BEFEHL
3 BEFEHL

\doifboxelse {...¹.} {...².} {...³.} {...⁴.}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifbufferelse {...¹.} {...².} {...³.}

1 BUFFER
2 TRUE
3 FALSE

\doifcolor {...¹.} {...².}

1 COLOR
2 TRUE

\doifcolorelse {...¹.} {...².} {...³.}

1 COLOR
2 TRUE
3 FALSE

\doifcommandhandler \... {...} {...}

1 CSNAME
2 NAME
3 TRUE

\doifcommandhandlerelse \... {...} {...} {...}

1 CSNAME
2 NAME
3 TRUE
4 FALSE

\doifcommon {...¹,...} {...²,...} {...³}

1 TEXT
2 TEXT
3 TRUE

\doifcommonelse {...¹,...} {...²,...} {...³} {...⁴}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifcontent {...¹} {...²} {...³} \... {...⁵}

1 BEFEHL
2 BEFEHL
3 BEFEHL
4 CSNAME
5 CONTENT

\doifconversiondefinedelse {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifconversionnumberelse {...¹} {...²} {...³} {...⁴}

1 NAME
2 NUMMER
3 TRUE
4 FALSE

\doifcounter {...¹} {...²}

1 NAME
2 TRUE

\doifcounterelse {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifcurrentfonthasfeatureelse {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifdefined {...¹} {...²}

1 NAME
2 TRUE

\doifdefinedcounter {...¹} {...²}

1 NAME
2 TRUE

\doifdefinedcounterelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifdefinedelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifdimensionelse {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifdimenstringelse {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifdocumentargument {...} {...}

1 NAME
2 TRUE

\doifdocumentargumentelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifdocumentfilename {...} {...}

1 NUMMER
2 TRUE

\doifdocumentfilenameelse {...} {...} {...}

1 NUMMER
2 TRUE
3 FALSE

\doifdocumentvariable {...} {...}

1 KEY
2 TRUE

\doifdocumentvariableelse {...} {...} {...}

1 KEY
2 TRUE
3 FALSE

\doifdrawingblackelse {...} {...}

1 TRUE
2 FALSE

\doifelse {...} {...} {...} {...}

1 CONTENT
2 CONTENT
3 TRUE
4 FALSE

\doifelseallcommon {...¹,...} {...²,...} {...³} {...⁴}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelsealldefined {...¹,...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelseallmodes {...¹,...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelseallundefined {...¹,...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelseassignment {...¹} {...²} {...³}

1 TEXT
2 TRUE
3 FALSE

\doifelseassignmentcs {...¹} \...² \...³

1 TEXT
2 CSNAME
3 CSNAME

\doifelseblack {...¹} {...²} {...³}

1 COLOR
2 TRUE
3 FALSE

\doifelseblockempty {...¹} {...²} {...³} {...⁴} {...⁵}

1 NAME
2 NAME
3 text ABSCHNITT
4 TRUE
5 FALSE

\doifelsebox {...¹} {...²} {...³} {...⁴}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseboxincache {...¹} {...²} {...³} {...⁴}

1 NAME
2 NUMMER TEXT
3 TRUE
4 FALSE

\doifelsebuffer {...¹} {...²} {...³}

1 BUFFER
2 TRUE
3 FALSE

\doifelsebufferempty {...¹} {...²} {...³}

1 BUFFER
2 TRUE
3 FALSE

\doifelsecolor {...¹} {...²} {...³}

1 COLOR
2 TRUE
3 FALSE

```
\doifelsecommandhandler \... {}{}{}{}
1 CSNAME
2 NAME
3 TRUE
4 FALSE
```

```
\doifelsecommon {...,...} {...,...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifelseconversiondefined {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelseconversionnumber {...} {...} {...} {...}
1 NAME
2 NUMBER
3 TRUE
4 FALSE
```

```
\doifelsecounter {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsecounteractive {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsecurrentfonthasfeature {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsecurrentsortingingused {...} {...}
1 TRUE
2 FALSE
```

```
\doifelsecurrentsynonymshown {...} {...}
1 TRUE
2 FALSE
```

```
\doifelsecurrentsynonymused {...} {...}
1 TRUE
2 FALSE
```

```
\doifelsedefined {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsedefinedcounter {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsedimension {...} {...} {...}
1 TEXT
2 TRUE
3 FALSE
```

\doifelsedimenstring {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE
\doifelsedocumentargument {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsedocumentfilename {...} {...} {...} 1 NUMBER 2 TRUE 3 FALSE
\doifelsedocumentvariable {...} {...} {...} 1 KEY 2 TRUE 3 FALSE
\doifelsedrawingblack {...} {...} 1 TRUE 2 FALSE
\doifelseempty {...} {...} {...} 1 CONTENT 2 TRUE 3 FALSE
\doifelseemptyvalue {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelseemptyvariable {...} {...} {...} {...} 1 NAME 2 KEY 3 TRUE 4 FALSE
\doifelseenv {...} {...} {...} 1 KEY 2 TRUE 3 FALSE
\doifelsefastoptionalcheck {...} {...} 1 TRUE 2 FALSE
\doifelsefastoptionalcheckcs \ ¹ ... \ ² ... 1 CSNAME 2 CSNAME
\doifelsefieldbody {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsefieldcategory {...} {...} {...} 1 NAME 2 TRUE 3 FALSE

\doifelsefigure {¹...} {²...} {³...}

1 FILE
2 TRUE
3 FALSE

\doifelsefile {¹...} {²...} {³...}

1 FILE
2 TRUE
3 FALSE

\doifelsefiledefined {¹...} {²...} {³...}

1 NAME
2 TRUE
3 FALSE

\doifelsefileexists {¹...} {²...} {³...}

1 FILE
2 TRUE
3 FALSE

\doifelsefirstchar {¹...} {²...} {³...} {⁴...}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelseflagged {¹...} {²...} {³...}

1 NAME
2 TRUE
3 FALSE

\doifelsefontfeature {¹...} {²...} {³...}

1 NAME
2 TRUE
3 FALSE

\doifelsefontchar {¹...} {²...} {³...} {⁴...}

1 FONT
2 NUMMER
3 TRUE
4 FALSE

\doifelsefontpresent {¹...} {²...} {³...}

1 FONT
2 TRUE
3 FALSE

\doifelsefontsynonym {¹...} {²...} {³...}

1 NAME
2 TRUE
3 FALSE

\doifelseframed \¹... {²...} {³...}

1 CSNAME
2 TRUE
3 FALSE

\doifelsehasspace {¹...} {²...} {³...}

1 TEXT
2 TRUE
3 FALSE

\doifelsehelp {¹...} {²...}

1 TRUE
2 FALSE

\doifelseincsname { ¹ ..} { ² ..} { ³ ..} { ⁴ ..} 1 TEXT 2 CSNAME 3 TRUE 4 FALSE
\doifelseindented { ¹ ..} { ² ..} 1 TRUE 2 FALSE
\doifelseinelement { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 TRUE 3 FALSE
\doifelseinputfile { ¹ ..} { ² ..} { ³ ..} 1 FILE 2 TRUE 3 FALSE
\doifelseinsertion { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 TRUE 3 FALSE
\doifelseinset { ¹ ..} {..., ² ...} { ³ ..} { ⁴ ..} 1 TEXT 2 TEXT 3 TRUE 4 FALSE
\doifelseinstring { ¹ ..} { ² ..} { ³ ..} { ⁴ ..} 1 TEXT 2 TEXT 3 TRUE 4 FALSE
\doifelseinsymbolset { ¹ ..} { ² ..} { ³ ..} { ⁴ ..} 1 NAME 2 NAME 3 TRUE 4 FALSE
\doifelseintoks { ¹ ..} { ² ..} { ³ ..} { ⁴ ..} 1 BEFEHL 2 BEFEHL 3 TRUE 4 FALSE
\doifelseitalic { ¹ ..} { ² ..} 1 TRUE 2 FALSE
\doifelselanguage { ¹ ..} { ² ..} { ³ ..} 1 SPRACHE 2 TRUE 3 FALSE
\doifelselayerdata { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 TRUE 3 FALSE

\doifelselayoutdefined { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 TRUE 3 FALSE
\doifelselayoutsomeline { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 TRUE 3 FALSE
\doifelselayouttextline { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 TRUE 3 FALSE
\doifelseleapyear { ¹ ..} { ² ..} { ³ ..} 1 NUMMER 2 TRUE 3 FALSE
\doifelselist { ¹ ..} { ² ..} { ³ ..} 1 LISTE 2 TRUE 3 FALSE
\doifelselocation { ¹ ..} { ² ..} 1 TRUE 2 FALSE
\doifelselocfile { ¹ ..} { ² ..} { ³ ..} 1 FILE 2 TRUE 3 FALSE
\doifelseMPgraphic { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 TRUE 3 FALSE
\doifelsemainfloatbody { ¹ ..} { ² ..} 1 TRUE 2 FALSE
\doifelsemarkedcontent { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 TRUE 3 FALSE
\doifelsemarkedpage { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 TRUE 3 FALSE
\doifelsemarking { ¹ ..} { ² ..} { ³ ..} 1 BESCHRIFTUNG 2 TRUE 3 FALSE
\doifelsemessage { ¹ ..} { ² ..} { ³ ..} { ⁴ ..} 1 NAME 2 NAME NUMMER 3 TRUE 4 FALSE

\doifelsemode {..., ¹ ...} {... ² } {... ³ } 1 NAME 2 TRUE 3 FALSE
\doifelsenextbgroup {... ¹ } {... ² } 1 TRUE 2 FALSE
\doifelsenextbgroupcs \... ¹ \... ² 1 CSNAME 2 CSNAME
\doifelsenextchar {... ¹ } {... ² } {... ³ } 1 CHARACTER 2 TRUE 3 FALSE
\doifelsenextoptional {... ¹ } {... ² } 1 TRUE 2 FALSE
\doifelsenextoptionalcs \... ¹ \... ² 1 CSNAME 2 CSNAME
\doifelsenextparenthesis {... ¹ } {... ² } 1 TRUE 2 FALSE
\doifelsenonzeropositive {... ¹ } {... ² } {... ³ } 1 NUMBER 2 TRUE 3 FALSE
\doifelsenoteonsamepage {... ¹ } {... ² } {... ³ } 1 NAME 2 TRUE 3 FALSE
\doifelsenothing {... ¹ } {... ² } {... ³ } 1 TEXT 2 TRUE 3 FALSE
\doifelsenumber {... ¹ } {... ² } {... ³ } 1 TEXT 2 TRUE 3 FALSE
\doifelseobjectfound {... ¹ } {... ² } {... ³ } {... ⁴ } 1 NAME 2 NAME 3 TRUE 4 FALSE
\doifelseobjectreferencefound {... ¹ } {... ² } {... ³ } {... ⁴ } 1 NAME 2 NAME 3 TRUE 4 FALSE

\doifelseoddpage {...} {...} 1 BEFEHL 2 BEFEHL
\doifelseoddpagefloat {...} {...} 1 TRUE 2 FALSE
\doifelseoldercontext {...} {...} {...} 1 NUMMER 2 TRUE 3 FALSE
\doifelseolderversion {...} {...} {...} {...} 1 NUMMER 2 NUMMER 3 TRUE 4 FALSE
\doifelseorientation {...} {...} {...} 1 normalni up down vlevo vpravo vrsek spodek NAME 2 TRUE 3 FALSE
\doifelseoverlapping {...} {...} {...} {...} 1 NAME 2 NAME 3 TRUE 4 FALSE
\doifelseoverlay {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelseparallel {...} {..., ² ...} {...} {...} 1 NAME 2 NAME vse 3 TRUE 4 FALSE
\doifelseparentfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE
\doifelseparwrapper {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsepath {...} {...} {...} 1 PATH 2 TRUE 3 FALSE
\doifelsepathexists {...} {...} {...} 1 PATH 2 TRUE 3 FALSE
\doifelsepatterns {...} {...} {...} 1 SPRACHE 2 TRUE 3 FALSE

\doifelseposition {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsepositionaction {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsepositiononpage {...} {...} {...} {...} 1 NAME 2 NUMMER 3 TRUE 4 FALSE
\doifelsepositionsonsamepage {..., ¹ ...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsepositionsonthispage {..., ¹ ...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifelsepositionsused {...} {...} 1 TRUE 2 FALSE
\doifelsereferenced {...} {...} {...} 1 REFERENCE 2 TRUE 3 FALSE
\doifelsereferencefound {...} {...} {...} 1 REFERENCE 2 TRUE 3 FALSE
\doifelsereferencechecked {...} {...} {...} 1 REFERENCE 2 TRUE 3 FALSE
\doifelserightpage {...} {...} 1 TRUE 2 FALSE
\doifelserightpagefloat {...} {...} 1 TRUE 2 FALSE
\doifelserighttoleftinbox ... {...} {...} 1 CSNAME NUMMER 2 TRUE 3 FALSE
\doifelsesamelinereference {...} {...} {...} 1 REFERENCE 2 TRUE 3 FALSE

```
\doifelsesamestring  {...}  {...}  {...}  {...}
1  TEXT
2  TEXT
3  TRUE
4  FALSE
```

```
\doifelsesetups  {...}  {...}  {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifelsesimilartokens  {...}  {...}  {...}  {...}
1  TEXT
2  TEXT
3  TRUE
4  FALSE
```

```
\doifelsesomebackground  {...}  {...}  {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifelsesomespace  {...}  {...}  {...}
1  TEXT
2  TRUE
3  FALSE
```

```
\doifelsesomething  {...}  {...}  {...}
1  TEXT
2  TRUE
3  FALSE
```

```
\doifelsesometoks  \...  {...}  {...}
1  CSNAME
2  TRUE
3  FALSE
```

```
\doifelsestringinstring  {...}  {...}  {...}  {...}
1  TEXT
2  TEXT
3  TRUE
4  FALSE
```

```
\doifelsestructurelisthasnumber  {...}  {...}
1  TRUE
2  FALSE
```

```
\doifelsestructurelisthaspage  {...}  {...}
1  TRUE
2  FALSE
```

```
\doifelsesymboldefined  {...}  {...}  {...}
1  NAME
2  TRUE
3  FALSE
```

```
\doifelsesymbolset  {...}  {...}  {...}
1  NAME
2  TRUE
3  FALSE
```

<pre> \doifelsetaggednoteonsamepage {...} {...} {...} {...} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifelsetext {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifelsetextflow {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsetextflowcollector {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsetopofpage {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifelsetypingfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifelseundefined {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelseupcomingrightpage {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifelseurldefined {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsevalue {...} {...} {...} {...} 1 NAME 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifelsevaluenothing {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsevariable {...} {...} {...} {...} 1 NAME 2 KEY 3 TRUE 4 FALSE </pre>
<pre> \doifempty {...} {...} 1 CONTENT 2 TRUE </pre>

<pre> \doifemptyelse {...} {...} {...} 1 CONTENT 2 TRUE 3 FALSE </pre>
<pre> \doifemptytoks \^1.. {...} 1 CSNAME 2 TRUE </pre>
<pre> \doifemptyvalue {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifemptyvalueelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifemptyvariable {...} {...} {...} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifemptyvariableelse {...} {...} {...} {...} 1 NAME 2 KEY 3 TRUE 4 FALSE </pre>
<pre> \doifenv {...} {...} 1 KEY 2 TRUE </pre>
<pre> \doifenvelse {...} {...} {...} 1 KEY 2 TRUE 3 FALSE </pre>
<pre> \doiffastoptionalcheckcselse \^1.. \^2.. 1 CSNAME 2 CSNAME </pre>
<pre> \doiffastoptionalcheckelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doiffielddbbodyelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiffielddcategoryelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiffigureelse {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doiffile {...} {...} 1 FILE 2 TRUE </pre>

<pre> \doiffiledefinedelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiffileelse {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doiffileexistselse {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doiffirstcharelse {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifflaggedelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiffontfeatureelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiffontcharelse {...} {...} {...} {...} 1 FONT 2 NUMMER 3 TRUE 4 FALSE </pre>
<pre> \doiffontpresentelse {...} {...} {...} 1 FONT 2 TRUE 3 FALSE </pre>
<pre> \doiffontsynonymelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifhasspaceelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifhelpelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifcheckedpagestate {...} {...} {...} {...} {...} {...} {...} 1 REFERENCE 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 BEFEHL 6 BEFEHL 7 BEFEHL </pre>

<pre> \doifcheckedreferencefoundelse {...} {...} {...} 1 REFERENCE 2 TRUE 3 FALSE </pre>
<pre> \doifincsnameelse {...} {...} {...} {...} 1 TEXT 2 CSNAME 3 TRUE 4 FALSE </pre>
<pre> \doifinelementelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifinputfileelse {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifinsectionelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifinset {...} {...,²...} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifinsetelse {...¹} {...,²...} {...³} {...⁴} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifinstring {...¹} {...²} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifinstringelse {...¹} {...²} {...³} {...⁴} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifinsymbolset {...¹} {...²} {...³} {...⁴} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifinsymbolsetelse {...¹} {...²} {...³} {...⁴} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifintokselse {...¹} {...²} {...³} {...⁴} 1 BEFEHL 2 BEFEHL 3 TRUE 4 FALSE </pre>

<pre> \doifitalicelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doiflanguageelse {...} {...} {...} 1 SPRACHE 2 TRUE 3 FALSE </pre>
<pre> \doiflayerdataelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiflayoutdefinedelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiflayoutsomelineelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiflayouttextlineelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifleapyearelse {...} {...} {...} 1 NUMMER 2 TRUE 3 FALSE </pre>
<pre> \doiflistelse {...} {...} {...} 1 LISTE 2 TRUE 3 FALSE </pre>
<pre> \doiflocationelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doiflocfileelse {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifMPgraphicelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifmainfloatbodyelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifmarkedpage {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>

<pre> \doifmarkingelse {...} {...} {...} 1 BESCHRIFTUNG 2 TRUE 3 FALSE </pre>
<pre> \doifmessageelse {...} {...} {...} {...} 1 NAME 2 NAME NUMMER 3 TRUE 4 FALSE </pre>
<pre> \doifmode {...,¹...} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifmodeelse {...,¹...} {...²} {...³} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnextbgroupcselse \¹... \²... 1 CSNAME 2 CSNAME </pre>
<pre> \doifnextbgroupelse {...¹} {...²} 1 TRUE 2 FALSE </pre>
<pre> \doifnextcharelse {...¹} {...²} {...³} 1 CHARACTER 2 TRUE 3 FALSE </pre>
<pre> \doifnextoptionalcselse \¹... \²... 1 CSNAME 2 CSNAME </pre>
<pre> \doifnextoptionalelse {...¹} {...²} 1 TRUE 2 FALSE </pre>
<pre> \doifnextparenthesiselse {...¹} {...²} 1 TRUE 2 FALSE </pre>
<pre> \doifnonzeropositiveelse {...¹} {...²} {...³} 1 NUMMER 2 TRUE 3 FALSE </pre>
<pre> \doifnot {...¹} {...²} {...³} 1 CONTENT 2 CONTENT 3 TRUE </pre>
<pre> \doifnotallcommon {...,¹...} {...,²...} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotallmodes {...,¹...} {...²} 1 NAME 2 TRUE </pre>

\doifnotanchorbox { ¹ ...} { ² ...} 1 NAME 2 TRUE
\doifnotcommandhandler \ ¹ ... { ² ...} { ³ ...} 1 CSNAME 2 NAME 3 TRUE
\doifnotcommon { ¹ ..., ¹ ...} { ² ..., ² ...} { ³ ...} 1 TEXT 2 TEXT 3 TRUE
\doifnotcounter { ¹ ...} { ² ...} 1 NAME 2 TRUE
\doifnotdocumentargument { ¹ ...} { ² ...} 1 NAME 2 TRUE
\doifnotdocumentfilename { ¹ ...} { ² ...} 1 NUMBER 2 TRUE
\doifnotdocumentvariable { ¹ ...} { ² ...} 1 KEY 2 TRUE
\doifnotempty { ¹ ...} { ² ...} 1 CONTENT 2 TRUE
\doifnotemptyvalue { ¹ ...} { ² ...} 1 NAME 2 TRUE
\doifnotemptyvariable { ¹ ...} { ² ...} { ³ ...} 1 NAME 2 KEY 3 TRUE
\doifnotenv { ¹ ...} { ² ...} 1 KEY 2 TRUE
\doifnoteonsamepageelse { ¹ ...} { ² ...} { ³ ...} 1 NAME 2 TRUE 3 FALSE
\doifnotescollected { ¹ ...} { ² ...} 1 NAME 2 TRUE
\doifnotfile { ¹ ...} { ² ...} 1 FILE 2 TRUE
\doifnotflagged { ¹ ...} { ² ...} 1 NAME 2 TRUE

<pre> \doifnothing {...} {...} 1 TEXT 2 TRUE </pre>
<pre> \doifnothingelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifnotinset {...} {...,²...} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotinfloat {...} * TRUE </pre>
<pre> \doifnotinstring {...¹} {...²} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotmode {...,¹...} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotnumber {...¹} {...²} 1 TEXT 2 TRUE </pre>
<pre> \doifnotsamestring {...¹} {...²} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotsetups {...¹} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotvalue {...¹} {...²} {...³} 1 NAME 2 TEXT 3 TRUE </pre>
<pre> \doifnotvariable {...¹} {...²} {...³} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifnumber {...¹} {...²} 1 TEXT 2 TRUE </pre>
<pre> \doifnumberelse {...¹} {...²} {...³} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifobjectfoundelse {...¹} {...²} {...³} {...⁴} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>

<pre> \doifobjectreferencefoundelse {...} {...} {...} {...} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifoddpagelse {...} {...} 1 BEFEHL 2 BEFEHL </pre>
<pre> \doifoddpagefloatelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifoldercontextelse {...} {...} {...} 1 NUMMER 2 TRUE 3 FALSE </pre>
<pre> \doifolderversionelse {...} {...} {...} {...} 1 NUMMER 2 NUMMER 3 TRUE 4 FALSE </pre>
<pre> \doifoutermode {...} * CONTENT </pre>
<pre> \doifoverlappingelse {...} {...} {...} {...} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifoverlayelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifparallelelse {...} {...,²...} {...} {...} 1 NAME 2 NAME vse 3 TRUE 4 FALSE </pre>
<pre> \doifparentfileelse {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifpathelse {...} {...} {...} 1 PATH 2 TRUE 3 FALSE </pre>
<pre> \doifpathexistselse {...} {...} {...} 1 PATH 2 TRUE 3 FALSE </pre>
<pre> \doifpatternselse {...} {...} {...} 1 SPRACHE 2 TRUE 3 FALSE </pre>

\doifposition {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifpositionaction {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifpositionactionelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifpositionelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifpositiononpageelse {...} {...} {...} {...} 1 NAME 2 NUMMER 3 TRUE 4 FALSE
\doifpositionsonsamepageelse {..., ¹ ...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifpositionsonthispageelse {..., ¹ ...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifpositionsusedelse {...} {...} 1 TRUE 2 FALSE
\doifreferencedelse {...} {...} {...} 1 REFERENCE 2 TRUE 3 FALSE
\doifreferencefoundelse {...} {...} {...} 1 REFERENCE 2 TRUE 3 FALSE
\doifrightpageelse {...} {...} 1 TRUE 2 FALSE
\doifrightpagefloatelse {...} {...} 1 TRUE 2 FALSE
\doifrightttolleftinboxelse ... {...} {...} 1 CSNAME NUMBER 2 TRUE 3 FALSE

```
\doifsamelinereferenceelse  {...}  {...}  {...}  
1  REFERENCE  
2  TRUE  
3  FALSE
```

```
\doifsamestring  {...}  {...}  {...}  
1  TEXT  
2  TEXT  
3  TRUE
```

```
\doifsamestringelse  {...}  {...}  {...}  {...}  
1  TEXT  
2  TEXT  
3  TRUE  
4  FALSE
```

```
\doifsetups  {...}  {...}  
1  NAME  
2  TRUE
```

```
\doifsetupself  {...}  {...}  {...}  
1  NAME  
2  TRUE  
3  FALSE
```

```
\doifsomebackground  {...}  {...}  {...}  
1  NAME  
2  TRUE  
3  FALSE
```

```
\doifsomebackgroundelse  {...}  {...}  {...}  
1  NAME  
2  TRUE  
3  FALSE
```

```
\doifsomepaceelse  {...}  {...}  {...}  
1  TEXT  
2  TRUE  
3  FALSE
```

```
\doifsomething  {...}  {...}  
1  TEXT  
2  TRUE
```

```
\doifsomethingelse  {...}  {...}  {...}  
1  TEXT  
2  TRUE  
3  FALSE
```

```
\doifsomeetoks  \...  {...}  
1  CSNAME  
2  TRUE
```

```
\doifsomeetokselse  \...  {...}  {...}  
1  CSNAME  
2  TRUE  
3  FALSE
```

```
\doifstringinstringelse  {...}  {...}  {...}  {...}  
1  TEXT  
2  TEXT  
3  TRUE  
4  FALSE
```

<pre> \doifstructurelisthasnumberelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifstructurelisthaspageelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifsymboldefinedelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifsymbolsetelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiftaggednoteonsamepageelse {...} {...} {...} {...} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doiftext {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doiftextelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doiftextflowcollectorelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiftextflowelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doiftopofpageelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doiftypingfileelse {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifundefined {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifundefinedcounter {...} {...} 1 NAME 2 TRUE </pre>

<pre> \doifundefinedelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifunknownfontfeature {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifurldefinedelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifvalue {...} {...} {...} 1 NAME 2 TEXT 3 TRUE </pre>
<pre> \doifvalueelse {...} {...} {...} {...} 1 NAME 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifvaluenothing {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifvaluenothingelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifvaluesomething {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifvariable {...} {...} {...} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifvariableelse {...} {...} {...} {...} 1 NAME 2 KEY 3 TRUE 4 FALSE </pre>
<pre> \doindentation </pre>
<pre> \dollar </pre>
<pre> \doloop {...} * BEFEHL </pre>
<pre> \doloopoverlist {...,¹...} {...} 1 TEXT 2 BEFEHL </pre>
<pre> \donothing </pre>

<code>\dontconvertfont</code>
<code>\dontleavehmode</code>
<code>\dontpermitspacesbetweengroups</code>
<code>\dopositionaction {...}</code> <code>* NAME</code>
<code>\doprocesslocalsetups {...,*...}</code> <code>* NAME</code>
<code>\doquadrupleargument \¹... [²...] [³] [⁴] [⁵]</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>4 TEXT</code> <code>5 TEXT</code>
<code>\doquadrupleempty \¹... [²] [³] [⁴] [⁵]</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>4 TEXT</code> <code>5 TEXT</code>
<code>\doquadruplegroupempty \¹... {...²} {...³} {...⁴} {...⁵}</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>4 TEXT</code> <code>5 TEXT</code>
<code>\doquintupleargument \¹... [²] [³] [⁴] [⁵] [⁶]</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>4 TEXT</code> <code>5 TEXT</code> <code>6 TEXT</code>
<code>\doquintupleempty \¹... [²] [³] [⁴] [⁵] [⁶]</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>4 TEXT</code> <code>5 TEXT</code> <code>6 TEXT</code>
<code>\doquintuplegroupempty \¹... {...²} {...³} {...⁴} {...⁵} {...⁶}</code> <code>1 CSNAME</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>4 TEXT</code> <code>5 TEXT</code> <code>6 TEXT</code>
<code>\dorecurse {...¹} {...²}</code> <code>1 NUMMER</code> <code>2 BEFEHL</code>
<code>\dorechecknextindentation</code>

```

1  TEXT NUMMER*TEXT
2  CSNAME

```

* NAME

* NAME

* NAME

```

1  NUMMER
2  CSNAME
3  CONTENT

```

```

1  NAME
2  NUMMER

```

* ano ne standardni DIMENSION

* ano ne standardni DIMENSION

```
* inherits: \nastaymeziradkovoumezeru
```

* zap vyp reset auto male stredni velke NUMMER DIMENSION

* NAME

1	CSNAME
2	TEXT
3	TEXT
4	TEXT
5	TEXT
6	TEXT
7	TEXT
8	TEXT

1	CSNAME
2	TEXT
3	TEXT
4	TEXT
5	TEXT
6	TEXT
7	TEXT
8	TEXT

```

1 CSNAME
2 TEXT

```

```

1 CSNAME OPT
2 TEXT

```

```

1 CSNAME OPT
2 TEXT

```

1	CSNAME
2	TEXT
3	TEXT
4	TEXT
5	TEXT
6	TEXT
7	TEXT

1	CSNAME	OPT	OPT	OPT	OPT	OPT	OPT
2	TEXT						
3	TEXT						
4	TEXT						
5	TEXT						
6	TEXT						
7	TEXT						

* CSNAME

```

1  NAME
2  NAME

```

1	NAME
2	NAME
3	NAME
4	NAME

* NAME

- 1 NUMBER
- 2 NUMBER
- 3 [-+] NUMBER
- 4 BEFEHL.

* NAME

* DIMENSION

* CSNAME

`\dotripleargument \1... [2...] [3...] [4...]`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotripleargumentwithset \1... [...,2...] [3...] [4...]`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotripleempty \1... [2...] [3...] [4...]`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotripleemptywithset \1... [...,2...] [3...] [4...]`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotriplegroupempty \1... {2...} {3...} {4...}`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\doublebond`

`\dousecurrentlanguageparameter`

`\douselanguageparameter \*...`

* CSNAME

`\dowith {...,1...} {2...}`

1 BEFEHL
2 BEFEHL

`\dowithminmaxrangeslice {1...} {2...} {3...} {4...} {...,5...}`

1 NUMMER
2 NUMMER
3 NUMMER
4 NUMMER
5 NUMMER

`\dowithnextbox {1...} \2... {3...}`

1 BEFEHL
2 CSNAME
3 CONTENT

`\dowithnextboxcontent {1...} {2...} \3... {4...}`

1 BEFEHL
2 BEFEHL
3 CSNAME
4 CONTENT

`\dowithnextboxcontentcs \1... \2... \3... {4...}`

1 CSNAME
2 CSNAME
3 CSNAME
4 CONTENT

<code>\dowithnextboxcs \¹... \²... {³...}</code> 1 CSNAME 2 CSNAME 3 CONTENT
<code>\dowithpargument \[*]...</code> * CSNAME
<code>\dowithrange {...,¹...} \²...</code> 1 NUMBER NUMBER:NUMBER 2 CSNAME
<code>\dowithwargument \[*]...</code> * CSNAME
<code>\dpofstring {[*]...}</code> * TEXT
<code>\drawbalancepoints [...,[*]..._{OPT},...]</code> * dx = DIMENSION dy = DIMENSION sx = DIMENSION sy = DIMENSION tloustkalinky = DIMENSION
<code>\drawbreakpoints [...,[*]..._{OPT},...]</code> * dx = DIMENSION dy = DIMENSION sx = DIMENSION sy = DIMENSION tloustkalinky = DIMENSION
<code>\dummydigit</code>
<code>\dummyparameter {[*]...}</code> * KEY
<code>\ETEX</code>
<code>\EveryLine {[*]...}</code> * BEFEHL
<code>\EveryPar {[*]...}</code> * BEFEHL
<code>\edefconvertedargument \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\efcmaxheight {[*]...}</code> * NAME
<code>\efcmaxwidth {[*]...}</code> * NAME
<code>\efcminheight {[*]...}</code> * NAME
<code>\efcminwidth {[*]...}</code> * NAME

$$\backslash\mathrm{efcparameter}\quad \{.^1.\}\quad \{.^2.\}$$

1 NAME

2 KEY

$$\backslash \text{effect} \quad [\dots] \quad \{ \dots \}$$

```
1 uvnitr vnejsi obe normalni skryte orez natahnout NAME
```

2 CONTENT

\elapsedseconds

```
\elapsedsteptime
```

\elapsedtime

\em

\emph{isboldface}

\emphisistypeface

\emphsize

`\emptycolumnset` $[\dots, \dots^* \dots, \dots]$

```
* sirka = DIMENSION
```

vyska = DIMENSION

C = NUMMER

```

r      =  NUMMER

```

```
metoda = zde fixne vrsek spodek tblr lrtb tblr rltb btlr lrbt btrl rlbt fxtb fxbt
```

volba = stranka

```
nvrsek = NUMMER
```

```
nspodek = NUMMER
```

\emptyhangrangestep

\emptylines [...]

* NUMMER OPT

\emspace

\enableasciimode

\enabledelimiter

`\enabledirectives` $[\dots, \ast, \dots]$

* NAME

```
\enableexperiments [...,*,...]
```

* NAME

\enablefiller

\enablemathautofencing

\enablemathautonumbers

\enablemathautospacing

<code>\enablemathpunctuation</code>
<code>\enablemathrules</code>
<code>\enablemode [...;...]</code> <code>* NAME</code>
<code>\enableoutputstream [...]</code> <code>* NAME</code>
<code>\enableparpositions</code>
<code>\enableregime [...]</code> <code>* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13</code> <code>8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256</code> <code>windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4</code> <code>iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6</code> <code>latin7 latin8 latin9 latin10 utf-8 utf8 windows</code>
<code>\enabletrackers [...;...]</code> <code>* NAME</code>
<code>\enskip</code>
<code>\enspace</code>
<code>\env {...}</code> <code>* KEY</code>
<code>\envvar {...} {...}</code> <code>1 KEY</code> <code>2 BEFEHL</code>
<code>\epos {...}</code> <code>* NAME</code>
<code>\equaldigits {...}</code> <code>* TEXT</code>
<code>\eTeX</code>
<code>\everydefinePRIKAZ</code>
<code>\everypresetPRIKAZ</code>
<code>\everysetupPRIKAZ</code>
<code>\everysetupPRIKAZroot</code>
<code>\everyswitchPRIKAZ</code>
<code>\executeifdefined {...} {...}</code> <code>1 NAME</code> <code>2 BEFEHL</code>
<code>\exitloop</code>

<code>\exitloopnow</code>
<code>\expanded {...}</code> <code>* CONTENT</code>
<code>\expandeddoif {...} {...} {...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code> <code>3 TRUE</code>
<code>\expandeddoifelse {...} {...} {...} {...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code> <code>3 TRUE</code> <code>4 FALSE</code>
<code>\expandeddoifnot {...} {...} {...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code> <code>3 TRUE</code>
<code>\expandfontsynonym \... {...}</code> <code>1 CSNAME</code> <code>2 NAME</code>
<code>\expandcheckedcsname \... {...} {...}</code> <code>1 CSNAME</code> <code>2 KEY</code> <code>3 TEXT</code>
<code>\expdoif {...} {...} {...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code> <code>3 TRUE</code>
<code>\expdoifcommonelse {...,¹...} {...,²...} {...} {...}</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 TRUE</code> <code>4 FALSE</code>
<code>\expdoifelse {...} {...} {...} {...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code> <code>3 TRUE</code> <code>4 FALSE</code>
<code>\expdoifelsecommon {...,¹...} {...,²...} {...} {...}</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 TRUE</code> <code>4 FALSE</code>
<code>\expdoifelseinset {...} {...,²...} {...} {...}</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 TRUE</code> <code>4 FALSE</code>
<code>\expdoifinsetelse {...} {...,²...} {...} {...}</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 TRUE</code> <code>4 FALSE</code>

<code>\expdoifnot</code> $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1 CONTENT 2 CONTENT 3 TRUE
<code>\externalfigurecollectionmaxheight</code> $\{.^*.\}$ * NAME
<code>\externalfigurecollectionmaxwidth</code> $\{.^*.\}$ * NAME
<code>\externalfigurecollectionminheight</code> $\{.^*.\}$ * NAME
<code>\externalfigurecollectionminwidth</code> $\{.^*.\}$ * NAME
<code>\externalfigurecollectionparameter</code> $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 KEY
<code>\externiobraz</code> $[.^1.]$ $[.^2.]$ $[.^3.,.^3.,.^3.]$ 1 FILE 2 NAME 3 inherits: \setupexternalfigure
<code>\F</code> $\{.^*.\}$ * + - = * NUMBER
<code>\fakebox</code> $\{.^*.\}$ * CSNAME NUMBER
<code>\fakeleftdelimiter</code>
<code>\fakelimit</code>
<code>\fastdecrement</code> $\{.^*.\}$ * CSNAME
<code>\fastincrement</code> $\{.^*.\}$ * CSNAME
<code>\fastlocalframed</code> $[.^1.]$ $[.^2.,.^2.,.^2.]$ $\{.^3.\}$ 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
<code>\fastloopfinal</code>
<code>\fastloopindex</code>
<code>\fastscale</code> $\{.^1.\}$ $\{.^2.\}$ 1 NUMBER 2 CONTENT
<code>\fastsetup</code> $\{.^*.\}$ * NAME

$\backslash\text{fastsetupwithargument}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 CONTENT
$\backslash\text{fastsetupwithargumentswapped}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 NAME
$\backslash\text{fastswitchtobodyfont}$ $\{.^*\}$ * x xx male velke script scriptscript
$\backslash\text{fastsxsy}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1 NUMMER 2 NUMMER 3 CONTENT
$\backslash\text{feature}$ $[.^1.]$ $[.^2.,.^3.]$ 1 + - = ! > < more less novy reset implicitni old lokalne 2 NAME
$\backslash\text{feature}$ $\{.^1.\}$ $\{.^2.,.^3.\}$ 1 + - = ! > < more less novy reset implicitni old lokalne 2 NAME
$\backslash\text{fenced}$ $[.^1.]$ $[.^2.,.^3.,.^4.,.^5.]$ $\{.^3.\}$ 1 cases sesac tekcarb parenthesis bracket brace bar doublebar triplebar angle doubleangle solidus ceiling floor moustache uppercorner lowercorner group openbracket nothing mirroredparenthesis mirroredbracket mirroredbrace mirroredbar mirroreddoublebar mirroredtriplebar mirroredangle mirroreddoubleangle mirroredsolidus mirroredceiling mirroredfloor mirroredmoustache mirroreduppercorner mirroredlowercorner mirroredgroup mirroredopenbracket mirrorednothing interval openinterval closedinterval leftopeninterval rightopeninterval varopeninterval varleftopeninterval varrightopeninterval integerinterval abs innerproduct integerpart norm set sequence tuple NAME 2 inherits: \setupmathfences 3 CONTENT
$\backslash\text{fenced}$ $[.^1.]$ $[.^2.,.^3.,.^4.,.^5.]$ $\{.^3.\}$ $\{.^4.\}$ 1 tupanddownarrows tupdownarrows tdownuparrows tuparrow tdownarrow NAME 2 inherits: \setupmathfences 3 CONTENT 4 CONTENT
$\backslash\text{FENCE}$ $[.^1.,.^2.,.^3.,.^4.,.^5.]$ $\{.^2.\}$ 1 inherits: \setupmathfences 2 CONTENT instances: parenthesis bracket brace ceiling floor interval openinterval closedinterval leftopeninterval rightopeninterval varopeninterval varleftopeninterval varrightopeninterval integerinterval abs innerproduct integerpart norm set sequence tuple
$\backslash\text{abs}$ $[.^1.,.^2.,.^3.,.^4.,.^5.]$ $\{.^2.\}$ 1 inherits: \setupmathfences 2 CONTENT
$\backslash\text{FENCE}$ $[.^1.,.^2.,.^3.,.^4.,.^5.]$ $\{.^2.\}$ $\{.^3.\}$ 1 inherits: \setupmathfences 2 CONTENT 3 CONTENT
$\backslash\text{brace}$ $[.^1.,.^2.,.^3.,.^4.,.^5.]$ $\{.^2.\}$ 1 inherits: \setupmathfences 2 CONTENT
$\backslash\text{bracket}$ $[.^1.,.^2.,.^3.,.^4.,.^5.]$ $\{.^2.\}$ 1 inherits: \setupmathfences 2 CONTENT

$\backslash\text{ceiling}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{closedinterval}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{floor}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{innerproduct}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{integerinterval}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{integerpart}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{interval}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{leftopeninterval}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{norm}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{openinterval}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{parenthesis}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{rightopeninterval}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{sequence}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{set}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT
$\backslash\text{tuple}$ $[\dots,\dots,\dots,\dots,\dots] \{\dots\}$ 1 inherits: $\backslash\text{setupmathfences}^{\text{OPT}}$ 2 CONTENT

$\backslash\mathrm{varleftopeninterval}$ $[...,\dots\overset{1}{=}\dots, ...]$ $\{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathfences}$ OPT 2 CONTENT
$\backslash\mathrm{varopeninterval}$ $[...,\dots\overset{1}{=}\dots, ...]$ $\{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathfences}$ OPT 2 CONTENT
$\backslash\mathrm{varrightopeninterval}$ $[...,\dots\overset{1}{=}\dots, ...]$ $\{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathfences}$ OPT 2 CONTENT
$\backslash\mathrm{fetchallmarkings}$ $[\dots]$ $[\dots]$ 1 BESCHRIFTUNG 2 stranka NAME NUMBER
$\backslash\mathrm{fetchallmarks}$ $[\dots]$ * BESCHRIFTUNG
$\backslash\mathrm{fetchmark}$ $[\dots]$ $[\dots]$ 1 BESCHRIFTUNG OPT 2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
$\backslash\mathrm{fetchmarking}$ $[\dots]$ $[\dots]$ $[\dots]$ 1 BESCHRIFTUNG 2 stranka NAME NUMBER 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
$\backslash\mathrm{fetchonemark}$ $[\dots]$ $[\dots]$ 1 BESCHRIFTUNG OPT 2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
$\backslash\mathrm{fetchonemarking}$ $[\dots]$ $[\dots]$ $[\dots]$ 1 BESCHRIFTUNG 2 stranka NAME NUMBER 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
$\backslash\mathrm{fetchruntimecommand}$ $\backslash\dots$ $\{\dots\}$ 1 CSNAME 2 FILE
$\backslash\mathrm{fetchtwomarkings}$ $[\dots]$ $[\dots]$ 1 BESCHRIFTUNG 2 stranka NAME NUMBER
$\backslash\mathrm{fetchtwomarks}$ $[\dots]$ * BESCHRIFTUNG
$\backslash\mathrm{fieldbody}$ $[\dots]$ $[...,\dots\overset{2}{=}\dots, ...]$ 1 NAME OPT 2 inherits: $\backslash\mathrm{setupfieldbody}$
$\backslash\mathrm{fifthoffivearguments}$ $\{\dots\}$ $\{\dots\}$ $\{\dots\}$ $\{\dots\}$ $\{\dots\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT

\fifthofsixarguments { ¹ ...} { ² ...} { ³ ...} { ⁴ ...} { ⁵ ...} { ⁶ ...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\figurefilename
\figurefilepath
\figurefiletype
\figurefullname
\figureheight
\figurenaturalheight
\figurenaturalwidth
\figuresymbol [¹ ...] [..., ² ... _{OPT} ,...] 1 FILE NAME 2 inherits: \externiobraz
\figurewidth
\filbreak
\filename { [*] ...} * FILE
\filledhboxb ¹ ... { ² ...} 1 TEXT 2 CONTENT
\filledhboxc ¹ ... { ² ...} 1 TEXT 2 CONTENT
\filledhboxg ¹ ... { ² ...} 1 TEXT 2 CONTENT
\filledhboxk ¹ ... { ² ...} 1 TEXT 2 CONTENT
\filledhboxm ¹ ... { ² ...} 1 TEXT 2 CONTENT
\filledhboxr ¹ ... { ² ...} 1 TEXT 2 CONTENT

```

1  TEXT                                OPT
2  CONTENT

```

```
*  sym symbol linka sirka mezera NAME
```

```
1  sym symbol linka sirka mezera NAME
2  TEXT
```

1	NUMMER	OPT	OPT	OPT	OPT	OPT
2	NUMMER					
3	CONTENT					
4	CONTENT					
5	CONTENT					
6	CONTENT					
7	CONTENT					

1	NAME
2	NUMMER
3	NUMMER

```

1  NODE
2  LPATH

```

```

1 FILE
2 sude lice NUMBER NUMBER:NUMBER
3 sirka      = DIMENSION
  n          = NUMBER
  category   = NAME
  alternativa = a b implicitni stranka

```

```
* implicitni text titul cislo stranka realpage
```

```

1  NAME
2  popisek      = NAME
   keys        = TEXT  PROCESSOR->TEXT
   entries      = TEXT  PROCESSOR->TEXT
   alternativa = TEXT
3  KEY = VALUE

```

```

1  NAME
2  NUMMER

```

* NAME

* BEFEHL

\firstoffivearguments {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\firstoffourarguments {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT
\firstofoneargument {...} * TEXT
\firstofoneunexpanded {...} * TEXT
\firstofsixarguments {...} {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\firstofthreearguments {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\firstofthreeunexpanded {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\firstoftwoarguments {...} {...} 1 TEXT 2 TEXT
\firstoftwounexpanded {...} {...} 1 TEXT 2 TEXT
\firstrealpage
\firstrealpagenumber
\firstsubcountervalue [...] ¹ [...] ² 1 NAME 2 NUMMER
\firstsubpagenumber
\firstuserpage
\firstuserpagenumber
\fitfieldframed [...] ¹ {...} ² 1 inherits: \nastavoramovani ^{OPT} 2 CONTENT

\fittopbaselinegrid {...} * CONTENT
\flag {...} * NAME
\floatuserdataparameter {...} * KEY
\flushallmarginblocks [...] * DIMENSION OPT
\flushbox {...} {...} 1 NAME 2 NAME
\flushboxregister ... * CSNAME NUMBER
\flushcollector [...] * NAME
\flushcolumnset
\flushedrightlastline
\flushinitial
\flushlayer [...] * NAME
\flushlocalfloats
\flushnextbox
\flushnoterange [...] * NAME
\flushnotes
\flushoutputstream [...] * NAME
\flushpageblocks [...;...] * NAME
\flushshapebox
\flushsidefloats
\flushsidefloatsafterpar
\flushsubcolumnsets [...] * spread OPT

\flushtextflow {...} * NAME
\flushtokens [...] * NAME
\flushtoks \... * CSNAME
\fontalternative
\fontbody
\fontclass
\fontclassname {...} {...} 1 NAME 2 FONT
\fontface
\fontfeaturelist [...] 1 NAME 2 TEXT
\fontchar {...} * NAME
\fontcharbyindex {...} * NUMMER
\fontsize
\fontstyle
\footnotetext [..., ¹ ...] {...} 1 REFERENCE OPT 2 TEXT
\footnotetext [..., [*] ...,...] * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT
\forcecharacterstripping
\forcelocalfloats
\forgeteverypar
\forgetinitial
\forgetparagraphfreezing

$\backslash\text{forgetparameters}$ $[...^1...^2...]$ 1 TEXT 2 KEY = VALUE
$\backslash\text{forgetparskip}$
$\backslash\text{forgetparwrapper}$
$\backslash\text{forgetragged}$
$\backslash\text{forgetsidefloats}$
$\backslash\text{forgettagging}$
$\backslash\text{foundbox}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 NAME
$\backslash\text{fourthoffivearguments}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ $\{.^5.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
$\backslash\text{fourthoffourarguments}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{fourthofsixarguments}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ $\{.^5.\}$ $\{.^6.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
$\backslash\text{frameddimension}$ $\{.^*.\}$ * KEY
$\backslash\text{FRAMEDMATH}$ $[...^1...^2...]$ $\{.^2.\}$ 1 inherits: $\backslash\text{nastavoramovani}$ 2 CONTENT instances: framedmath mathstrikeout mathcrossout
$\backslash\text{framedmath}$ $[...^1...^2...]$ $\{.^2.\}$ 1 inherits: $\backslash\text{nastavoramovani}$ 2 CONTENT
$\backslash\text{mathcrossout}$ $[...^1...^2...]$ $\{.^2.\}$ 1 inherits: $\backslash\text{nastavoramovan}^{\text{PPT}}$ 2 CONTENT
$\backslash\text{mathstrikeout}$ $[...^1...^2...]$ $\{.^2.\}$ 1 inherits: $\backslash\text{nastavoramovan}^{\text{PPT}}$ 2 CONTENT
$\backslash\text{framedparameter}$ $\{.^*.\}$ * KEY

<code>\freezeaveragecharacterwidth</code>
<code>\freezeimagenmacro \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\freezemeasure [¹...] [²...]</code> 1 NAME 2 DIMENSION
<code>\freezeparagraphproperties</code>
<code>\frenchspacing</code>
<code>\fromlinenote [¹...] {²...}</code> 1 REFERENCE 2 TEXT
<code>\frozenhbox {¹...}</code> * CONTENT
<code>\frule .. [*]... .. \relax</code> * width _␣ DIMENSION height _␣ DIMENSION depth _␣ DIMENSION radius _␣ DIMENSION line _␣ DIMENSION type _␣ TEXT data _␣ TEXT name _␣ TEXT radius _␣ DIMENSION corner _␣ TEXT
<code>\fsp {[*]...}</code> * CHARACTER
<code>\GetPar</code>
<code>\GotoPar</code>
<code>\Greeknumerals {[*]...}</code> * NUMMER
<code>\gdefconvertedargument \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\gdefconvertedcommand \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\getboxfromcache {¹...} {²...} ³...</code> 1 NAME 2 NUMMER TEXT 3 CSNAME NUMMER
<code>\getboxllx [*]...</code> * CSNAME NUMMER
<code>\getboxlly [*]...</code> * CSNAME NUMMER
<code>\getbufferdata [[*]...]</code> * BUFFER OPT

\getcommacommandsize [...,*,...] * BEFEHL
\getcommalistsize [...,*,...] * BEFEHL
\getdatavalue {...} * NAME
\getdayoftheweek {... ¹ } {... ² } {... ³ } 1 NUMMER 2 NUMMER 3 NUMMER
\getdayspermonth {... ¹ } {... ² } 1 NUMMER 2 NUMMER
\getdefinedbuffer {...} * BUFFER
\getdocumentargument {...} * NAME
\getdocumentargumentdefault {... ¹ } {... ² } 1 NAME 2 TEXT
\getdocumentfilename {...} * NUMMER
\getdummyparameters [...,.. [≡] ...,...] * KEY = VALUE
\getemptyparameters [... ¹] [...,.. [≡] ...,...] 1 TEXT 2 KEY = VALUE
\getparameters [... ¹] [...,.. [≡] ...,...] 1 TEXT 2 KEY = VALUE
\getexpandedparameters [... ¹] [...,.. [≡] ...,...] 1 TEXT 2 KEY = VALUE
\getfiguredimensions [... ¹] [...,.. [≡] ...,...] 1 FILE 2 inherits: \setupexternalfigure OPT
\getfirstcharacter {...} * TEXT
\getfromcommacommand [..., ¹ ...] [... ² .] 1 BEFEHL 2 NUMMER
\getfromcommalist [..., ¹ ...] [... ² .] 1 BEFEHL 2 NUMMER

\getfromluatable \ ¹ ... { ² ...} 1 CSNAME 2 KEY NUMBER
\getglyphdirect { ¹ ...} { ² ...} 1 FONT 2 NUMMER CHARACTER
\getglyphstyled { ¹ ...} { ² ...} 1 FONT 2 NUMMER CHARACTER
\getgparameters [¹ ...] [..., ² ...,...] 1 TEXT 2 KEY = VALUE
\getinlineuserdata
\getlocalfloat {.*} * NUMBER
\getlocalfloats
\getMPdata
\getMPdrawing
\getMPlayer [¹ ...] [..., ² ...,...] { ³ ...} 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\getmessage { ¹ ...} { ² ...} 1 NAME 2 NAME NUMBER
\getnamedglyphdirect { ¹ ...} { ² ...} 1 FONT 2 NAME
\getnamedglyphdirectscaled { ¹ ...} { ² ...} { ³ ...} 1 NUMBER 2 FONT 3 NAME
\getnamedglyphstyled { ¹ ...} { ² ...} 1 FONT 2 NAME
\getnaturaldimensions ... * CSNAME NUMBER
\getnoflines {.*} * DIMENSION
\getobject { ¹ ...} { ² ...} 1 NAME 2 NAME

\getobjectdimensions { ¹ ..} { ² ..} 1 NAME 2 NAME
\getobjectreference { ¹ ..} { ² ..} \ ³ .. { ⁴ ..} 1 NAME 2 NAME 3 CSNAME 4 CONTENT
\getobjectreferencepage { ¹ ..} { ² ..} \ ³ .. { ⁴ ..} 1 NAME 2 NAME 3 CSNAME 4 CONTENT
\getpaletsize [¹ ..] * NAME
\getparameters [¹ ..] [² .., ² .., ² ..] 1 TEXT 2 KEY = VALUE
\getparwrapper { ¹ ..} * NAME
\getprivatechar { ¹ ..} * NAME
\getprivateslot { ¹ ..} * NAME
\getrandomcount \ ¹ .. { ² ..} { ³ ..} 1 CSNAME 2 NUMMER 3 NUMMER
\getrandomdimen \ ¹ .. { ² ..} { ³ ..} 1 CSNAME 2 DIMENSION 3 DIMENSION
\getrandomfloat \ ¹ .. { ² ..} { ³ ..} 1 CSNAME 2 NUMMER 3 NUMMER
\getrandomnumber \ ¹ .. { ² ..} { ³ ..} 1 CSNAME 2 NUMMER 3 NUMMER
\getrandomseed \ ¹ .. * CSNAME
\getraweparameters [¹ ..] [² .., ² .., ² ..] 1 TEXT 2 KEY = VALUE
\getrawgparameters [¹ ..] [² .., ² .., ² ..] 1 TEXT 2 KEY = VALUE

\getrawnoflines {...} * DIMENSION
\getrawparameters [¹ ...] [..., ² ...,...] 1 TEXT 2 KEY = VALUE
\getrawxparameters [¹ ...] [..., ² ...,...] 1 TEXT 2 KEY = VALUE
\getreference [¹ ...] [² ...] 1 implicitni text titul cislo stranka realpage 2 REFERENCE
\getreferenceentry {...} * implicitni text titul cislo stranka realpage
\getroundednoflines {...} * DIMENSION
\getshapetext
\getsubstring {...} {...} {...} 1 NUMMER 2 NUMMER 3 TEXT
\gettokenlist {...} * NAME
\getuserdata
\getuvalue {...} * NAME
\getvalue {...} * NAME
\getvariable {...} {...} 1 NAME 2 KEY
\getvariabledefault {...} {...} {...} 1 NAME 2 KEY 3 BEFEHL
\getxparameters [¹ ...] [..., ² ...,...] 1 TEXT 2 KEY = VALUE
\globaldisablemode [...,*...] * NAME
\globalenablemode [...,*...] * NAME

\globalletempty *.. * CSNAME
\globalpopbox ... * CSNAME NUMMER
\globalpopmacro *.. * CSNAME
\globalpreventmode [...,*...] * NAME
\globalprocesscommalist [...] ¹ *.. ² 1 BEFEHL 2 CSNAME
\globalpushbox ... * CSNAME NUMMER
\globalpushmacro *.. * CSNAME
\globalpushreferenceprefix {...} ... \globalpopreferenceprefix * + - TEXT
\globalswapcounts *.. ¹ *.. ² 1 CSNAME 2 CSNAME
\globalswapdimens *.. ¹ *.. ² 1 CSNAME 2 CSNAME
\globalswapmacros *.. ¹ *.. ² 1 CSNAME 2 CSNAME
\globalundefine {...} * NAME
\glyphfontfile {...} * FONT
\glyphscaled {...} * NUMMER
\gobbledoubleempty [...] ¹ [...] ² 1 TEXT OPT OPT 2 TEXT
\gobbleeightarguments {...} ¹ {...} ² {...} ³ {...} ⁴ {...} ⁵ {...} ⁶ {...} ⁷ {...} ⁸ 1 CONTENT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT 7 CONTENT 8 CONTENT

<pre> \gobblefivearguments {...} {...} {...} {...} {...} 1 CONTENT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT </pre>
<pre> \gobblefiveoptionals [...] [...] [...] [...] [...] 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT </pre>
<pre> \gobblefourarguments {...} {...} {...} {...} 1 CONTENT 2 CONTENT 3 CONTENT 4 CONTENT </pre>
<pre> \gobblefouroptionals [...] [...] [...] [...] 1 TEXT 2 TEXT 3 TEXT 4 TEXT </pre>
<pre> \gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...} 1 CONTENT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT 7 CONTENT 8 CONTENT 9 CONTENT </pre>
<pre> \gobbleoneargument {...} * CONTENT </pre>
<pre> \gobbleoneoptional [...] * TEXT </pre>
<pre> \gobblesevenarguments {...} {...} {...} {...} {...} {...} {...} 1 CONTENT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT 7 CONTENT </pre>
<pre> \gobblesingleempty [...] * TEXT OPT </pre>
<pre> \gobblesixarguments {...} {...} {...} {...} {...} {...} 1 CONTENT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT </pre>
<pre> \gobblespacetokens </pre>

<code>\greedystring</code> ¹... \at ²... \to \³... \and \⁴... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\greeknumerals</code> {...} * NUMBER
<code>\groupedcommand</code> {¹...} {²...} 1 BEFEHL 2 BEFEHL
<code>\groupedcommandcs</code> \¹... \²... 1 CSNAME 2 CSNAME
<code>\gsetboxllx</code> ¹... {²...} 1 CSNAME NUMBER 2 DIMENSION
<code>\gsetboxlly</code> ¹... {²...} 1 CSNAME NUMBER 2 DIMENSION
<code>\gujaratinumerals</code> {...} * NUMBER
<code>\gurmukhinumerals</code> {...} * NUMBER
<code>\hairspace</code>
<code>\halflinestrut</code>
<code>\halfstrut</code>
<code>\halfwaybox</code> {...} * CONTENT
<code>\handlemissingcharacters</code>
<code>\handletokens</code> ¹... \with \²... 1 TEXT 2 CSNAME
<code>\hash</code>
<code>\hboxofvbox</code> ¹... * CSNAME NUMBER
<code>\hboxreference</code> [...,¹...] {²...} 1 REFERENCE 2 CONTENT
<code>\hboxBOX</code> {...} * CONTENT
<code>\hbreak</code>

<code>\hcontainer</code> ¹ <code>...</code> OPT <code>{...}</code> 1 TEXT 2 CONTENT
<code>\hdofstring</code> <code>{...}</code> * TEXT
<code>\headhbox</code> ¹ <code>...</code> OPT <code>{...}</code> 1 TEXT 2 CONTENT
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtextdistance</code>
<code>\headtextwidth</code>
<code>\headvbox</code> ¹ <code>...</code> OPT <code>{...}</code> 1 TEXT 2 CONTENT
<code>\headwidth</code>
<code>\hebrewnumerals</code> <code>{...}</code> * NUMBER
<code>\heightanddepthofstring</code> <code>{...}</code> * TEXT
<code>\heightofstring</code> <code>{...}</code> * TEXT
<code>\heightspanningtext</code> ¹ ² ³ <code>{...}</code> <code>{...}</code> <code>{...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\HELP</code> [¹ ...] { ² ...} { ³ ...} 1 REFERENCE ^{PT} 2 TEXT 3 TEXT instances: helptext
<code>\helptext</code> [¹ ...] { ² ...} { ³ ...} 1 REFERENCE OPT 2 TEXT 3 TEXT

\hexnumber {...} * NUMBER
\hexstringtonumber {...} * NUMBER
\hglue ... * DIMENSION
\hiddencitation [...] * REFERENCE
\hiddencite [...] * REFERENCE
\hidestacking [...,*...] * NUMBER
\highlight [...] 1 NAME 2 TEXT
\HIGHLIGHT {...} * TEXT
\highordinalstr {...} * TEXT
\hilo [...] 1 vlevo vprávo 2 CONTENT 3 CONTENT
\himilo {...} 1 CONTENT 2 CONTENT 3 CONTENT
\hl [...] * NUMBER ^{OPT}
\hlavnijazyk [...] * SPRACHE
\hodnotabarvy {...} * COLOR
\horizontalbox [...] 1 NAME 2 inherits: \setuphorizontalbox 3 CONTENT
\horizontalgrowingbar [...,*...] * inherits: \setuppositionbar
\horizontalpositionbar [...,*...] * inherits: \setuppositionbar
\hpackbox

<code>\hpackedbox</code>
<code>\hphantom {...}</code> <code>* CONTENT</code>
<code>\hpos {¹.} {².}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\hsizefraction {¹.} {².}</code> <code>1 DIMENSION</code> <code>2 NUMMER</code>
<code>\hsmash {...}</code> <code>* CONTENT</code>
<code>\hsmashbox ...</code> <code>* CSNAME NUMMER</code>
<code>\hsmashed {...}</code> <code>* CONTENT</code>
<code>\hspace [¹.] [².]</code> <code>1 NAME OPT OPT</code> <code>2 male stredni velke normalni implicitni zadny .5 1 2 3 speech citovat interquotation citace sentence intersentence finalni NAME</code>
<code>\htdpofstring {...}</code> <code>* TEXT</code>
<code>\htofstring {...}</code> <code>* TEXT</code>
<code>\hyphen</code>
<code>\hyphenatedcoloredword {...}</code> <code>* TEXT</code>
<code>\hyphenatedddigits [¹.] {².}</code> <code>1 CSNAME OPT</code> <code>2 NUMMER</code>
<code>\hyphenatedfile {...}</code> <code>* FILE</code>
<code>\hyphenatedfilename {...}</code> <code>* TEXT</code>
<code>\hyphenatedhbox {...}</code> <code>* CONTENT</code>
<code>\hyphenatedpar {...}</code> <code>* TEXT</code>
<code>\hyphenatedurl {...}</code> <code>* TEXT</code>

\checknextinjector [...] * NAME
\checkpage [¹...] [...,²...,...] 1 NAME OPT 2 inherits: \setuppagechecker
\checkparameters [...] * TEXT
\checkpreviousinjector [...] * NAME
\checksidefloat
\checkvariables [¹...] [...,²...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
\chem {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\chemical [¹...] [...,²...] [...,³...,...] 1 NAME OPT OPT 2 TEXT 3 TEXT
\chemicalbottext {...} * TEXT
\chemicalmidtext {...} * TEXT
\chemicalsymbol [...] * NAME
\chemicaltext {...} * TEXT
\chemicaltoptext {...} * TEXT
\chineseallnumerals {...} * NUMBER
\chinesecapnumerals {...} * NUMBER
\chinesenumerals {...} * NUMBER
\chr {...} * TEXT
\INRSTEX

\ibox {...} * CONTENT
\idxfromluatable ^{1} ^{2} 1 CSNAME 2 NUMMER
\ifassignment ^{1} \else ^{2} \fi 1 TRUE 2 FALSE
\ifcommandhandler ^{1} {...} ^{3} \else ^{4} \fi 1 CSNAME 2 NAME 3 TRUE 4 FALSE
\ifinobject ^{1} \else ^{2} \fi 1 TRUE 2 FALSE
\ifinoutputstream ^{1} \else ^{2} \fi 1 TRUE 2 FALSE
\iflua ^{1} ^{2} \else ^{3} \fi 1 TEXT 2 TRUE 3 FALSE
\ifparameters ^{1} \else ^{2} \fi 1 TRUE 2 FALSE
\iftrialtypesetting ^{1} \else ^{2} \fi 1 TRUE 2 FALSE
\ifxml {...} {...} ^{3} \else ^{4} \fi 1 NODE 2 LPATH 3 TRUE 4 FALSE
\ifxmlatt {...} {...} {...} ^{4} \else ^{5} \fi 1 NODE 2 NAME 3 TEXT 4 TRUE 5 FALSE
\ifxmlattempty {...} {...} ^{3} \else ^{4} \fi 1 NODE 2 NAME 3 TRUE 4 FALSE
\ifxmlempty {...} {...} ^{3} \else ^{4} \fi 1 NODE 2 LPATH 3 TRUE 4 FALSE

<pre> \ifxmlselfempty {...} {...} ... \else ... \fi 1 NODE 2 LPATH 3 TRUE 4 FALSE </pre>
<pre> \ifxmltext {...} {...} ... \else ... \fi 1 NODE 2 LPATH 3 TRUE 4 FALSE </pre>
<pre> \ignoreimplicitspaces </pre>
<pre> \ignoretagsinexport [...,*...] * NAME </pre>
<pre> \ignorevalue {...} * NAME </pre>
<pre> \im {...} * CONTENT </pre>
<pre> \includeMPOverlaydata </pre>
<pre> \includemenu [...] * NAME </pre>
<pre> \includesvgbuffer [...¹] [...,...²...,...] 1 BUFFER 2 offset = DIMENSION cache = ano PATH OPT </pre>
<pre> \includesvgfile [...¹] [...,...²...,...] 1 FILE 2 offset = DIMENSION cache = ano PATH OPT </pre>
<pre> \includeversioninfo {...} * NAME </pre>
<pre> \incrementcounter [...¹] [...²] 1 NAME 2 NUMMER OPT </pre>
<pre> \incrementedcounter [...] * NAME </pre>
<pre> \incrementpagenumber </pre>
<pre> \incrementsubpagenumber </pre>
<pre> \incrementvalue {...} * NAME </pre>
<pre> \indentation </pre>
<pre> \infofont </pre>

<code>\infofontbold</code>
<code>\inheritedPRIKAZoramovani {...}</code> <code>* CONTENT</code>
<code>\inheritedPRIKAZframedbox {...} ...</code> <code>1 TEXT</code> <code>2 CSNAME NUMBER</code>
<code>\inheritparameter [...] [...] [...]</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 KEY</code>
<code>\inhibitallspacing</code>
<code>\inhibitblank</code>
<code>\inhibitwhitespace</code>
<code>\initializeboxstack {...}</code> <code>* NAME</code>
<code>\inlinebar [...] {...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\inlinebuffer [...,*...] OPT</code> <code>* BUFFER</code>
<code>\inlinedbox {...}</code> <code>* CONTENT</code>
<code>\inlinemath {...}</code> <code>* CONTENT</code>
<code>\inlinemathematics {...}</code> <code>* CONTENT</code>
<code>\inlinemessage {...}</code> <code>* TEXT</code>
<code>\inlineordisplaymath {...} {...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code>
<code>\inlineprettyprintbuffer {...} {...}</code> <code>1 BUFFER</code> <code>2 mp lua xml parsed-xml nested tex context zadny NAME</code>
<code>\inlinerange [...]</code> <code>* REFERENCE</code>
<code>\innerflushshapebox</code>
<code>\input {...}</code> <code>* FILE</code>

<code>\inputfilebarename</code>
<code>\inputfilename</code>
<code>\inputfilerealsuffix</code>
<code>\inputfilesuffix</code>
<code>\inputgivenfile {...}</code> <code>* FILE</code>
<code>\input ...</code> <code>* FILE</code>
<code>\insertblankafter [...*...]</code> <code>* inherits: \preskoc</code>
<code>\insertblankbefore [...*...]</code> <code>* inherits: \preskoc</code>
<code>\insertlineafter {...}</code> <code>* CONTENT</code>
<code>\insertlinebefore {...}</code> <code>* CONTENT</code>
<code>\insertpages [¹...] [...,²...] [...,³=...,...]</code> <code>1 FILE</code> <code>2 NUMMER</code> <code>3 sirka = DIMENSION</code> <code> n = NUMMER</code> <code> category = NAME</code> <code> alternativa = a b implicitni stranka</code>
<code>\inspectluatable \...</code> <code>* CSNAME</code>
<code>\instalacejazyka [¹] [...,²...,...]</code> <code>1 NAME</code> <code>2 inherits: \nastavjazyk</code>
<code>\instalacejazyka [¹] [²...]</code> <code>1 NAME</code> <code>2 SPRACHE</code>
<code>\installactionhandler {...}</code> <code>* NAME</code>
<code>\installactivecharacter ...</code> <code>* CHARACTER</code>
<code>\installaligncommand {¹...} {²...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\installanddefineactivecharacter ¹... {²...}</code> <code>1 CHARACTER</code> <code>2 BEFEHL</code>

<pre> \installattributestack \.* * CSNAME </pre>
<pre> \installautocommandhandler \.^... {...} \.^... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installautosetuphandler \.^... {...} 1 CSNAME 2 NAME </pre>
<pre> \installbasicautosetuphandler \.^... {...} 1 CSNAME 2 NAME </pre>
<pre> \installbasicparameterhandler \.^... {...} 1 CSNAME 2 NAME </pre>
<pre> \installbottomframerenderer {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installcommalistprocessor {...} \.^... 1 NAME 2 CSNAME </pre>
<pre> \installcommalistprocessorcommand {...} \.^... 1 NAME 2 CSNAME </pre>
<pre> \installcommandhandler \.^... {...} \.^... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installcorenamespace {...} * NAME </pre>
<pre> \installctxfunction \.^... {...} 1 CSNAME 2 CONTENT </pre>
<pre> \installctxscanner \.^... {...} 1 CSNAME 2 CONTENT </pre>
<pre> \installdefinehandler \.^... {...} \.^... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installdefinitionset \.^... {...} 1 CSNAME 2 NAME </pre>
<pre> \installdefinitionsetmember \.^... {...} \.^... {...} 1 CSNAME 2 NAME 3 CSNAME 4 NAME </pre>

\installdirectcommandhandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installdirectparameterhandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installdirectparametersethandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installdirectsetuphandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installdirectstyleandcolorhandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installframedautocommandhandler \ ¹ ... { ² ...} \ ³ ... 1 CSNAME 2 NAME 3 CSNAME
\installframedcommandhandler \ ¹ ... { ² ...} \ ³ ... 1 CSNAME 2 NAME 3 CSNAME
\installglobalmacrostack *... * CSNAME
\installinheritedframed { [*] ...} * NAME
\installleftframerenderer { ¹ ...} { ² ...} 1 NAME 2 BEFEHL
\installlocalcurrenthandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installmacrostack *... * CSNAME
\installnamespace { [*] ...} * NAME
\installoutputroutine \ ¹ ... { ² ...} 1 CSNAME 2 BEFEHL
\installpagearrangement ¹ ... { ² ...} 1 NAME 2 BEFEHL
\installparameterhandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME

\installparameterhashhandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installparametersethandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installparentinjector \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installprotectedctxfunction \ ¹ ... { ² ...} 1 CSNAME 2 CONTENT
\installprotectedctxscanner \ ¹ ... { ² ...} 1 CSNAME 2 CONTENT
\installrightframerenderer { ¹ ...} { ² ...} 1 NAME 2 BEFEHL
\installrootparameterhandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installsetuphandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installsetuponlycommandhandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installshipoutmethod { ¹ ...} { ² ...} 1 NAME 2 BEFEHL
\installsimplecommandhandler \ ¹ ... { ² ...} \ ³ ... 1 CSNAME 2 NAME 3 CSNAME
\installsimpleframedcommandhandler \ ¹ ... { ² ...} \ ³ ... 1 CSNAME 2 NAME 3 CSNAME
\installstyleandcolorhandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installstylisticautohandler \ ¹ ... { ² ...} 1 CSNAME 2 NAME
\installswitchcommandhandler \ ¹ ... { ² ...} \ ³ ... 1 CSNAME 2 NAME 3 CSNAME

1	CSNAME
2	NAME

```

1  NAME
2  BEFEHL
3  BEFEHL

```

```

1  NAME
2  BEFEHL
3  BEFEHL

```

```

1  NAME
2  BEFEHL

```

```

1  NAME
2  BEFEHL

```

```

1  NAME
2  BEFEHL

```

```

1  NAME
2  BEFEHL

```

* KEY

* NUMMER

```
1 NAME OPT
2 inherits: \nastavinterakcnilistu
```

```
1 inherits: \nastavinterakcnilistuOPT
2 stranka podstranka REFERENCE
```

```
1  NAME
2  inherits: \nastavinterakcnimenu
```

* TEXT

* NUMMER

* NUMMER.

\interwordspacesbefore {...} * NUMBER
\invokepagehandler {...} {...} 1 normalni zadny NAME 2 CONTENT
\italiccorrection
\italicface
\itemtag [...,*...] * REFERENCE OPT
\jazyk [...] * SPRACHE
\LANGUAGE
\jdidolu [...] * DIMENSION
\jdina {...} [...] 1 CONTENT 2 REFERENCE
\jdinabox {...} [...] 1 CONTENT 2 REFERENCE
\jdinastranu {...} [...] 1 TEXT 2 REFERENCE
\UNIT {...} * CONTENT instances: unit
\unit {...} * CONTENT
\jobfilename
\jobfilesuffix
\justimages
\Kap {...} * TEXT
\kaligraficke
\kannadanumerals {...} * NUMBER
\kap {...} * TEXT

\kapitalky {...} * TEXT
\keephyphensequences
\keeplinestogether {...} * NUMMER
\keeporphans
\keeptoddlers
\keeptwins
\keepunwantedspaces
\kerncharacters [... ¹] {... ² } 1 NUMMER OPT 2 TEXT
\klonujpole [... ¹] [... ²] [... ³] [... ⁴ ,...] 1 NAME 2 NAME 3 NAME 4 NAME
\COMMENT [... ¹] [... ² ,... ² ,...] {... ³ } 1 TEXT OPT OPT 2 inherits: \nastavkomentar 3 TEXT instances: comment
\comment [... ¹] [... ² ,... ² ,...] {... ³ } 1 TEXT OPT OPT 2 inherits: \nastavkomentar 3 TEXT
\komponenta [...] * FILE
\komponenta ... * FILE
\konvertujcislo {... ¹ } {... ² } 1 prazdne implicitni zadny mesic month:mnem pismeno Pismeno pismena Pismena a A Csla slovo words Slovo Slova n N rimskecislice Rimskecislice i I r R KR RK recky Recky math:greek math:Greek g G abjadnumerals abjadnodotnumerals abjadnaivenumerals hebrewnumerals yiddishnumerals thainumerals devanagarinumerals malayalamnumerals tamilnumerals kannadanumerals telugunumerals bengalinumerals gurmurkhinumerals gujaratinumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals mathgreeknumerals mathGreeknumerals koreannumerals koreanparentnumerals koreancirclenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals chinesedatenumerals cn cn-c cn-a cn-d sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals russiannumerals russianNumerals mathgreek set_0 set_1 set_2 set_3 set_1x continued zero NAME 2 NUMMER
\kopirujpole [... ¹] [... ²]
\koreancirclenumerals {...} * NUMMER

<code>\koreannumerals {...}</code> <code>* NUMBER</code>
<code>\koreannumeralsc {...}</code> <code>* NUMBER</code>
<code>\koreannumeralsp {...}</code> <code>* NUMBER</code>
<code>\koreanparentnumerals {...}</code> <code>* NUMBER</code>
<code>\korekcebilehomista {...}</code> <code>* CONTENT</code>
<code>\kurziva</code>
<code>\kurzivnitucne</code>
<code>\LAMSTEX</code>
<code>\LATEX</code>
<code>\LamSTeX</code>
<code>\LaTeX</code>
<code>\LMTX</code>
<code>\LUAJITTEX</code>
<code>\LUAMETATEX</code>
<code>\LUATEX</code>
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaMetaTeX</code>
<code>\LuaTeX</code>
<code>\LABELjazyk</code> instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
<code>\btxlabeljazyk</code>
<code>\headjazyk</code>
<code>\labeljazyk</code>
<code>\mathlabeljazyk</code>

<code>\lastpredefinedsymbol</code>
<code>\lastrealpage</code>
<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue</code> [¹ ...] [² ...] 1 NAME 2 NUMMER
<code>\lastsubpagenumber</code>
<code>\lasttwodigits</code> {...} * NUMMER
<code>\lastunitstring</code>
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode</code> {...} * BEFEHL
<code>\layeredtext</code> [..., ¹ ...,...] [..., ² ...,...] {... ³ } {... ⁴ } 1 inherits: \setuplayer OPT OPT 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
<code>\layerheight</code>
<code>\layerwidth</code>
<code>\lbox</code> ¹ ... {... ² } 1 TEXT OPT 2 CONTENT
<code>\leftbottombox</code> {...} * CONTENT
<code>\leftbox</code> {...} * CONTENT
<code>\lefthbox</code> {...} * CONTENT
<code>\leftLABELtext</code> {...} * KEY instances: head label mathlabel
<code>\leftheadtext</code> {...} * KEY
<code>\leftlabeltext</code> {...} * KEY

$$\left\{ \begin{array}{l} \text{leftmathlabeltext} \end{array} \right\} \{ \dots \}$$

```
\leftline {...}
```

$$\backslash\text{leftorright hbox} \quad \overset{1}{\dots} \quad \overset{2}{\{\dots\}}$$
$$\backslash\text{leftorrightvbox} \quad \overset{1}{\dots} \quad \overset{2}{\{\dots\}}$$
$$\text{\texttt{\textbackslashleftorrightvtop}} \quad \overset{1}{\dots} \quad \overset{2}{\{ \dots \}}$$
$$\backslash\text{leftparbox} \quad [\overset{1}{\dots}] \quad \{ \overset{2}{\dots} \}$$

\leftskipadaption

 $\leftsubguillemot$

`\lefttopbox` $\{...\}$

\lefttoright

$$\text{\texttt{\textbackslashlefttorightbox}} \quad \overset{1}{\dots} \quad \overset{2}{\{\dots\}}$$
$$\text{\texttt{\textbackslashlefttorightvbox}} \quad \overset{1}{\dots} \quad \overset{2}{\{ \dots \}}$$
$$\text{\texttt{\textbackslashlefttorightvtop}} \quad \overset{1}{\dots} \quad \overset{2}{\{\dots\}}$$

\lesshyphens

```
\letbeundefined {..}
```

$$\backslash \text{letcatcodecommand} \quad \backslash \overset{1}{\dots} \quad \overset{2}{\dots} \quad \backslash \overset{3}{\dots}$$
$$\backslash \text{letPRIKAZparameter} \quad \{ \dots \} \quad \backslash \dots$$

<code>\letcscsname \.^... \cscsname .^... \endcscsname</code> 1 CSNAME 2 NAME
<code>\letcsnamecs \cscsname .^... \endcscsname \.^...</code> 1 NAME 2 CSNAME
<code>\letcsnamecsname \cscsname .^... \endcscsname \cscsname .^... \endcscsname</code> 1 NAME 2 NAME
<code>\letdummyparameter {.^...} \.^...</code> 1 KEY 2 CSNAME
<code>\letempty \.^...</code> * CSNAME
<code>\letfromPRIKAZparameter \.^... {.^...}</code> 1 CSNAME 2 KEY
<code>\letgvalue {.^...} \.^...</code> 1 NAME 2 CSNAME
<code>\letgvalueempty {.^...}</code> * NAME
<code>\letgvaluerelax {.^...}</code> * NAME
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letterereggroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>

<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterhyphen</code>
<code>\letterleftbrace</code>
<code>\letterleftbracket</code>
<code>\letterleftparenthesis</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\letterrightbracket</code>
<code>\letterrightparenthesis</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> $[^{1}]$ $\{^{2}\}$ 1 NUMBER OPT 2 TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue</code> $\{^{1}\}$ $\backslash^{2}$ 1 NAME 2 CSNAME
<code>\letvalueempty</code> $\{^{*}\}$ * NAME
<code>\letvaluerelax</code> $\{^{*}\}$ * NAME
<code>\lfence</code> $\dots$ * $\{ \} [\] (\) \bgroup \lparent \lparenthesis \lparen \lbracket \lbrack \lbrace \lceil \lceiling \lfloor \floor \ulcorner$ $\llcorner \lmoustache \llbracket \langle \llangle \lgroup \vert \singleverticalbar \doubleverticalbar \tripleverticalbar$ $\lvert \lVert \linterval \llointerval$ CHARACTER

<code>\lhbox {...}</code> * CONTENT
<code>\lchexnumber {...}</code> * NUMMER
<code>\lchexnumbers {...}</code> * NUMMER
<code>\limitatefirstline {¹...} {²...} {³...}</code> 1 TEXT 2 DIMENSION 3 BEFEHL
<code>\limitatelines {¹...} {²...} {³...}</code> 1 NUMMER 2 BEFEHL 3 TEXT
<code>\limitatetext {¹...} {²...} {³...}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\limitatetext {¹...} {...,²...} {³...}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\linebox {.*}</code> * CONTENT
<code>\linefillerhbox [¹...] ²... {³...}</code> 1 NAME 2 TEXT 3 CONTENT OPT
<code>\linefillervbox [¹...] ²... {³...}</code> 1 NAME 2 TEXT 3 CONTENT OPT
<code>\linefillervtop [¹...] ²... {³...}</code> 1 NAME 2 TEXT 3 CONTENT OPT
<code>\LINENOTE {.*}</code> * TEXT instances: linenote
<code>\linenote {.*}</code> * TEXT
<code>\linespanningtext {¹...} {²...} {³...}</code> 1 TEXT 2 DIMENSION 3 FONT

`\listcitation [...1...] [...2]`

```
1 odkaz      = REFERENCEPT
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\listcitation [...1] [...2]`

```
1 implicitni categoryPT entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\listcitation [...1...] [...2...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\listcite [...1...] [...2]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\listcite [...1] [...2]`

```
1 implicitni categoryPT entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\listcite [...1...] [...2...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                authornum authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\listnamespaces`

`\literalmode`

`\llap {...}`

* CONTENT

`\loadanyfile [...]`

* FILE

`\loadanyfileonce [...]`

* FILE

`\loadbtxdefinitionfile [...]`

* FILE

\loadbtxreplacementfile [...] * FILE
\loadcldfile [...] * FILE
\loadcldfileonce [...] * FILE
\loadfontgoodies [...] * FILE
\loadluafile [...] * FILE
\loadluafileonce [...] * FILE
\loadspellchecklist [...] ¹ [...] ² 1 NAME 2 FILE
\loadtexfile [...] * FILE
\loadtexfileonce [...] * FILE
\loadtypescriptfile [...] * FILE
\localanchorx {...} ¹ ... ² ... ³ 1 NAME 2 NUMMER 3 NUMMER
\localanchory {...} ¹ ... ² ... ³ 1 NAME 2 NUMMER 3 NUMMER
\localbox [...] ¹ {...} ² 1 NAME 2 CONTENT
\localframed [...] ¹ [..., ² ... ² ,...] {...} ³ 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\localframedwithsettings [...] ¹ [..., ² ... ² ,...] {...} ³ 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\localhsize
\localmargintext [...] ¹ {...} ² 1 NAME 2 CONTENT

<code>\localpopbox ...</code> <code>* CSNAME NUMBER</code>
<code>\localpopmacro \...</code> <code>* CSNAME</code>
<code>\localpushbox ...</code> <code>* CSNAME NUMBER</code>
<code>\localpushmacro \...</code> <code>* CSNAME</code>
<code>\localundefine {...}</code> <code>* NAME</code>
<code>\locatedfilepath</code>
<code>\locatefilepath {...}</code> <code>* FILE</code>
<code>\locfilename {...}</code> <code>* FILE</code>
<code>\loggingall</code>
<code>\lomihi {¹...} {²...} {³...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code> <code>3 CONTENT</code>
<code>\lowerbox {¹...} \²... {³...}</code> <code>1 DIMENSION</code> <code>2 CSNAME</code> <code>3 CONTENT</code>
<code>\lowercased {...}</code> <code>* TEXT</code>
<code>\lowercasestring ¹... \to \²...</code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\lowercasing</code>
<code>\lowerlefthdoubleninequote</code>
<code>\lowerleftsingleninequote</code>
<code>\lowerrighthdoubleninequote</code>
<code>\lowerrightsingleninequote</code>
<code>\LOWHIGH [¹...] {²...} {³...}</code> <code>1 vlevo vpravo^{OPT}</code> <code>2 CONTENT</code> <code>3 CONTENT</code>

<code>\LOWMIDHIGH</code> <code>{...}</code> <code>{...}</code> <code>{...}</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\lrbbox</code> <code>{...}</code> <code>{...}</code> <code>{...}</code> <code>{...}</code> 1 DIMENSION 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 CONTENT
<code>\ltop</code> <code>...¹</code> <code>{...}</code> 1 TEXT OPT 2 CONTENT
<code>\ltrhbox</code> <code>...¹</code> <code>{...}</code> 1 TEXT OPT 2 CONTENT
<code>\ltrtext</code> <code>{...}</code> * CONTENT
<code>\ltrvbox</code> <code>...¹</code> <code>{...}</code> 1 TEXT OPT 2 CONTENT
<code>\ltrvtop</code> <code>...¹</code> <code>{...}</code> 1 TEXT OPT 2 CONTENT
<code>\luacode</code> <code>{...}</code> * BEFEHL
<code>\luaconditional</code> <code>*...</code> * CSNAME
<code>\luaenvironment</code> <code>...</code> * FILE
<code>\luaexpanded</code> <code>{...}</code> * BEFEHL
<code>\luaexpr</code> <code>[...¹]</code> <code>{...²}</code> 1 TEXT OPT 2 CONTENT
<code>\luafunction</code> <code>{...}</code> * BEFEHL
<code>\luajitTeX</code>
<code>\luamajorversion</code>
<code>\luametaTeX</code>
<code>\luaminorversion</code>

\luaparameterset {...} {...} 1 NAME 2 CONTENT
\luasetup {...} * NAME
\luaTeX
\luaversion
\MESIC {...} * NUMMER
\METAFONT
\METAFUN
\METAPOST
\MetaFont
\MetaFontLogo
\MetaFun
\MetaPost
\MetaPostLogo
\MKII
\MKIV
\MKIX
\MKLX
\MKVI
\MKXI
\MKXL
\MONTHLONG {...} * NUMMER
\MONTHSHORT {...} * NUMMER
\MPanchor {...} * NAME

\MPbetex {...} * NAME
\MPc {...} * NAME
\MPcode [. ¹ .] {... ² .} 1 metafun minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost doublepost binarypost decimalpost simplefun 2 CONTENT
\MPcolor {...} * COLOR
\MPcoloronly {...} * COLOR
\MPcolumn {...} * NAME
\MPd {...} * NAME
\MPdpar \. ¹ . {... ² .} 1 CSNAME 2 KEY
\MPdrawing {...} * CONTENT
\MPfontsizehskip {...} * FONT
\MPgetmultipars {... ¹ .} {... ² .} 1 NAME 2 NAME
\MPgetmultishape {... ¹ .} {... ² .} 1 NAME 2 NAME
\MPgetposboxes {... ¹ .,...} {... ² .} 1 NAME 2 NAME
\MPh {...} * NAME
\MPII
\MPIV
\MPinclusions [. ¹ .] {... ² .} {... ³ .} 1 + OPT OPT 2 metafun minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost doublepost binarypost decimalpost simplefun 3 CONTENT
\MPLX

\MPleftskip {...} * NAME
\MPll {...} * NAME
\MPlr {...} * NAME
\MPls {...} * NAME
\MPMI
\MPML
\MPmenubuttons {...} * NAME
\MPn {...} * NAME
\MPnpar \. ¹ ... {.. ² .} 1 CSNAME 2 KEY
\MPoptions {...} * COLOR
\MPoverlayanchor {...} * NAME
\MPp {...} * NAME
\MPpage {...} * NAME
\MPpardata {...} * NAME
\MPplus {.. ¹ .} {.. ² .} {.. ³ .} 1 NAME 2 NUMMER 3 CONTENT
\MPpos {...} * NAME
\MPpositiongraphic {.. ¹ .} {...,.. ² ...,.. ² ...} 1 NAME 2 KEY = VALUE OPT
\MPposset {...} * NAME
\MPr {...} * NAME

\MPrawvar {...} {...} 1 NAME 2 KEY
\MPregion {...} * NAME
\MPrest {...} {...} 1 NAME 2 CONTENT
\MPrightskip {...} * NAME
\MPrs {...} * NAME
\MPspar \ ¹ ... {...} 1 CSNAME 2 KEY
\MPstring {...} * NAME
\MPtext {...} * NAME
\MPtransparency {...} * COLOR
\MPul {...} * NAME
\MPur {...} * NAME
\MPVI
\MPv {... ¹ } {... ² } {... ³ } 1 NAME 2 NUMMER 3 CONTENT
\MPvar {...} * KEY
\MPvariable {...} * KEY
\MPvv {...} {...} 1 NAME 2 CONTENT
\MPw {...} * NAME
\MPwhd {...} * NAME

<code>\MPXL</code>
<code>\MPx {...}</code> <code>* NAME</code>
<code>\MPxy {...}</code> <code>* NAME</code>
<code>\MPxywhd {...}</code> <code>* NAME</code>
<code>\MPy {...}</code> <code>* NAME</code>
<code>\m [...¹] {...²}</code> <code>1 impli²itni i:default i:half i:tight i:fixed NAME</code> <code>2 CONTENT</code>
<code>\makecharacteractive ...</code> <code>* CHARACTER</code>
<code>\makerawcommalist [...¹;...²] \...</code> <code>1 BEFEHL</code> <code>2 CSNAME</code>
<code>\makestrutofbox ...</code> <code>* CSNAME NUMBER</code>
<code>\malayalamnumerals {...}</code> <code>* NUMBER</code>
<code>\male</code>
<code>\malekurzivni</code>
<code>\malekurzivnitucne</code>
<code>\malenormalni</code>
<code>\malesklonene</code>
<code>\malesklonenetucne</code>
<code>\maletucne</code>
<code>\maletucnekurzivni</code>
<code>\maletucnesklonene</code>
<code>\maletype</code>
<code>\mapfontsize [...¹] [...²] [...³]</code> <code>1 NAME OPT OPT</code> <code>2 DIMENSION</code> <code>3 DIMENSION</code>

<code>\mappedfontsize</code> $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 DIMENSION
<code>\margindata</code> $[.^1.]$ $[.^2.^3.^4.]$ $[.^3.^4.]$ $\{.^4.\}$ 1 NAME 2 odkaz = REFERENCE inherits: \setupmargindata 3 inherits: \setupmarginframed 4 CONTENT
<code>\MARGINDATA</code> $[.^1.^2.^3.]$ $[.^2.^3.]$ $\{.^3.\}$ 1 odkaz = REFERENCE OPT OPT inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT instances: inleftmargin inrightmargin inoutermargin ininnermargin inleftedge inrightedge inouteredge ininneredge atleftmargin atrightmargin inleft inright inouter ininner inmargin inother margintext
<code>\atleftmargin</code> $[.^1.^2.^3.]$ $[.^2.^3.]$ $\{.^3.\}$ 1 odkaz = REFERENCE OPT OPT inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\atrightrightmargin</code> $[.^1.^2.^3.]$ $[.^2.^3.]$ $\{.^3.\}$ 1 odkaz = REFERENCE OPT OPT inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\ininner</code> $[.^1.^2.^3.]$ $[.^2.^3.]$ $\{.^3.\}$ 1 odkaz = REFERENCE OPT OPT inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\ininneredge</code> $[.^1.^2.^3.]$ $[.^2.^3.]$ $\{.^3.\}$ 1 odkaz = REFERENCE OPT OPT inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\ininnermargin</code> $[.^1.^2.^3.]$ $[.^2.^3.]$ $\{.^3.\}$ 1 odkaz = REFERENCE OPT OPT inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inleft</code> $[.^1.^2.^3.]$ $[.^2.^3.]$ $\{.^3.\}$ 1 odkaz = REFERENCE OPT OPT inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inleftedge</code> $[.^1.^2.^3.]$ $[.^2.^3.]$ $\{.^3.\}$ 1 odkaz = REFERENCE OPT OPT inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inleftmargin</code> $[.^1.^2.^3.]$ $[.^2.^3.]$ $\{.^3.\}$ 1 odkaz = REFERENCE OPT OPT inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT

$\backslash\text{inmargin}$ $[\dots,\dots,\overset{1}{=}\dots,\dots]$ $[\dots,\dots,\overset{2}{=}\dots,\dots]$ $\{\dots\}^3$ 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{inotherr}$ $[\dots,\dots,\overset{1}{=}\dots,\dots]$ $[\dots,\dots,\overset{2}{=}\dots,\dots]$ $\{\dots\}^3$ 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{inouter}$ $[\dots,\dots,\overset{1}{=}\dots,\dots]$ $[\dots,\dots,\overset{2}{=}\dots,\dots]$ $\{\dots\}^3$ 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{inouteredge}$ $[\dots,\dots,\overset{1}{=}\dots,\dots]$ $[\dots,\dots,\overset{2}{=}\dots,\dots]$ $\{\dots\}^3$ 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{inoutermargin}$ $[\dots,\dots,\overset{1}{=}\dots,\dots]$ $[\dots,\dots,\overset{2}{=}\dots,\dots]$ $\{\dots\}^3$ 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{inright}$ $[\dots,\dots,\overset{1}{=}\dots,\dots]$ $[\dots,\dots,\overset{2}{=}\dots,\dots]$ $\{\dots\}^3$ 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{inrightedge}$ $[\dots,\dots,\overset{1}{=}\dots,\dots]$ $[\dots,\dots,\overset{2}{=}\dots,\dots]$ $\{\dots\}^3$ 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{inrightmargin}$ $[\dots,\dots,\overset{1}{=}\dots,\dots]$ $[\dots,\dots,\overset{2}{=}\dots,\dots]$ $\{\dots\}^3$ 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{margintext}$ $[\dots,\dots,\overset{1}{=}\dots,\dots]$ $[\dots,\dots,\overset{2}{=}\dots,\dots]$ $\{\dots\}^3$ 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{markanchor}$ $\{\dots\}^1$ $\{\dots\}^2$ $\{\dots\}^3$ 1 NAME 2 NUMMER 3 NUMMER
$\backslash\text{markcontent}$ $[\dots]^1$ $\{\dots\}^2$ 1 reset vse NAME ^{OPT} 2 CONTENT
$\backslash\text{markedpages}$ $[\dots]^*$ * NAME

$\backslash$ marker {...} * NAME
$\backslash$ markinjector {...} * NAME
$\backslash$ markpage [...] ¹ [...] ² ,...] 1 NAME OPT 2 [-+]NUMBER
$\backslash$ markreferencepage
$\backslash$ mat {...} * CONTENT
$\backslash$ matematika [...] ¹ {...} ² 1 implicitni i:default i:half i:tight i:fixed NAME 2 CONTENT
$\backslash$ matematika [...] ¹ ,... {...} ² 1 inherits: \setupmathematics 2 CONTENT
$\backslash$ math [...] ¹ {...} ² 1 implicitni i:default i:half i:tight i:fixed NAME 2 CONTENT
$\backslash$ MATHACCENT [...] ¹ ,... {...} ² 1 inherits: \setupmathaccents 2 CONTENT instances: grave acute hat tilde bar breve dot ddot overhook ring check overleftharpoon overrightharpoon dddot ddddots widegrave wideacute widehat widetilde widebar widebreve widedot wideddot widering widecheck widedddot vec wideoverleftharpoon wideoverrightharpoon wideoverleftarrow wideoverrightarrow wideoverlefttriarightarrow conjugate closure wideundertilde wideunderbar wideunderlefttriarightarrow wideunderleftharpoon wideunderleftarrow wideunderrightarrow
$\backslash$ acute [...] ¹ ,... {...} ² 1 inherits: \setupmathaccents 2 CONTENT
$\backslash$ bar [...] ¹ ,... {...} ² 1 inherits: \setupmathaccents 2 CONTENT
$\backslash$ breve [...] ¹ ,... {...} ² 1 inherits: \setupmathaccents 2 CONTENT
$\backslash$ closure [...] ¹ ,... {...} ² 1 inherits: \setupmathaccents 2 CONTENT
$\backslash$ conjugate [...] ¹ ,... {...} ² 1 inherits: \setupmathaccents 2 CONTENT
$\backslash$ ddddot [...] ¹ ,... {...} ² 1 inherits: \setupmathaccents 2 CONTENT

$\text{\dddot } [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\ddot{}} [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\dot{}} [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\grave{}} [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\hat{}} [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\check{}} [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\overhook } [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\overleftharpoonup } [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\overrightharpoonup } [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\ring } [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\tilde{}} [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\vec{}} [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\wideacute } [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\widebar } [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT
$\text{\widebreve } [...,\dots^1,...]$ $\{\dots^2\}$ 1 inherits: $\text{\setupmathaccents}^{\text{OPT}}$ 2 CONTENT

```

1 inherits: \setupmathaccents
2 CONTENT

```

```

1 inherits: \setupmathaccentsOPT
2 CONTENT

```

```

1 inherits: \setupmathaccentsOPT
2 CONTENT

```

```
1 inherits: \setupmathaccentsOPT
2 CONTENT
```

```
1 inherits: \setupmathaccentsOPT
2 CONTENT
```

```

1 inherits: \setupmathaccentsOPT
2 CONTENT

```

```

1 inherits: \setupmathaccents      OPT
2 CONTENT

```

```
1 inherits: \setupmathaccents
2 CONTENT
```

```

1 inherits: \setupmathaccents
2 CONTENT

```

```

1 inherits: \setupmathaccents
2 CONTENT

```

```

1 inherits: \setupmathaccents
2 CONTENT

```

```

1 inherits: \setupmathaccentsOPT
2 CONTENT

```

```
1 inherits: \setupmathaccentsOPT
2 CONTENT
```

```
1 inherits: \setupmathaccentsDEF
2 CONTENT
```

```
1 inherits: \setupmathaccents
2 CONTENT
```

$\wideunderleftharpoon$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathaccents}$ OPT 2 CONTENT
$\wideunderleftrightharpoon$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathaccents}$ OPT 2 CONTENT
$\wideunderrightarrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathaccents}$ OPT 2 CONTENT
$\wideunderrightarrowharpoon$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathaccents}$ OPT 2 CONTENT
$\wideundertilde$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathaccents}$ OPT 2 CONTENT
$\text{\MATHANNOTATION}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathannotation}$ OPT 2 TEXT instances: mathannotation
$\text{\mathannotation}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathannotation}$ OPT 2 TEXT
$\text{\mathbf}$
$\text{\mathbi}$
$\text{\mathbb}$
$\text{\mathbox}$ $\{...\}$ * CONTENT
$\text{\mathboxanchored}$ $[...,\overset{1}{=}]$ $\{...\}$ $\{...\}$ 1 nucleus OPT 2 TEXT 3 NAME NUMBER
$\text{\mathbs}$
$\text{\mathcellanchored}$ $\{...\}$ * NAME NUMBER
$\text{\MATHCOMMAND}$ $\{...\}$ $\{...\}$ 1 TEXT OPT OPT 2 TEXT
$\text{\mathdefault}$
$\text{\MATHDELIMITED}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ OPT 2 CONTENT instances: ddotmarked barmarked hatmarked checkmarked brevemarked ringmarked tildemarked ddotmarked daggermarked ddaggermarked astmarked starmarked primed doubleprimed tripleprimed quadrupleprimed reverseprimed doublereverseprimed triplereverseprimed

$\backslash\text{astmarked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{barmarked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{breve} \text{marked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{dagger} \text{marked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{ddagger} \text{marked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{dddotted} \text{marked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{ddotted} \text{marked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{double} \text{primed} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{double} \text{reverse} \text{primed} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{hat} \text{marked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{check} \text{marked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{primed} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{quadruple} \text{primed} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{reverse} \text{primed} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT
$\backslash\text{ring} \text{marked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\text{setupmathdelimited}$ 2 CONTENT

$\backslash\mathrm{starmarked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathdelimited}$ 2 CONTENT
$\backslash\mathrm{tildemarked} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathdelimited}$ 2 CONTENT
$\backslash\mathrm{tripleprimed} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathdelimited}$ 2 CONTENT
$\backslash\mathrm{triplereverseprimed} \quad [\dots\overset{1}{=}\dots] \quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathdelimited}$ OPT 2 CONTENT
$\backslash\mathrm{mathdelimiter} \quad [\overset{1}{\dots}] \quad [\overset{2}{\dots}]$ 1 NAME OPT 2 NUMMER
$\backslash\mathrm{mathdelimiter} \quad [\overset{1}{\dots}] \quad [\dots\overset{2}{=}\dots]$ 1 NAME OPT 2 inherits: $\backslash\mathrm{setupmathdelimiters}$
$\backslash\mathrm{mathdelimiter} \quad [\overset{*}{\dots}]$ * NUMMER OPT
$\backslash\mathrm{mathdelimiter} \quad [\dots\overset{*}{=}\dots]$ * inherits: $\backslash\mathrm{setupmathdelimiters}$
$\backslash\mathrm{mathdigits} \quad \{\dots\}$ * TEXT
$\backslash\mathrm{mathdouble} \quad [\overset{1}{\dots}] \quad \{\overset{2}{\dots}\} \quad \{\overset{3}{\dots}\} \quad \{\overset{4}{\dots}\}$ 1 obe vfenced OPT 2 NUMMER 3 TEXT 4 TEXT
$\backslash\mathrm{MATHDOUBLEEXTENSIBLE} \quad [\dots\overset{1}{=}\dots] \quad \{\overset{2}{\dots}\}$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT instances: doublebar doublebrace doubleparent doublebracket overbarunderbar overbraceunderbrace overparentunderparent overbracketunderbracket
$\backslash\mathrm{doublebar} \quad [\dots\overset{1}{=}\dots] \quad \{\overset{2}{\dots}\}$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT
$\backslash\mathrm{doublebrace} \quad [\dots\overset{1}{=}\dots] \quad \{\overset{2}{\dots}\}$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT
$\backslash\mathrm{doublebracket} \quad [\dots\overset{1}{=}\dots] \quad \{\overset{2}{\dots}\}$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT
$\backslash\mathrm{doubleparent} \quad [\dots\overset{1}{=}\dots] \quad \{\overset{2}{\dots}\}$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT

$\overline{\underbrace{\dots^1\dots}}^{\dots^2}$ 1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\overbrace{\underbrace{\dots^1\dots}}^{\dots^2}$ 1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\overbracket{\underbrace{\dots^1\dots}}^{\dots^2}$ 1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\overparent{\underparent{\dots^1\dots}}^{\dots^2}$ 1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\text{\MATHDOUBLE}\{\dots\}$ * TEXT
$\text{\MATHEXTENSIBLE}\left[\dots^1\dots\right]\left\{\dots^2\dots\right\}\left\{\dots^3\dots\right\}$ 1 reverse matematika text chemistry ^{OPT} 2 TEXT 3 TEXT instances: xrel xequal xleftarrow xrightarrow xleftrightharrow xlongleftarrow xlongrightarrow xlongleftrightharrow xleftarrow xrightarrow xleftrightharrow xtwoheadleftarrow xtwoheadrightarrow xmapsto xhookleftarrow xhookrightarrow xleftharpoondown xleftharpoonup xrightharpoondown xrightharpoonup xrightoverleftarrow xleftoverrightarrow xleftrightharpoons xrightleftharpoons xtriplerel mrel mequal mleftarrow mrightarrow mleftrightharrow mLeftarrow mRightarrow mleftrightharrow mtwoheadleftarrow mtwoheadrightarrow mmapsto mhookleftarrow mhookrightarrow mleftharpoondown mleftharpoonup mrightharpoondown mrightharpoonup mrightoverleftarrow mleftoverrightarrow mleftrightharpoons mrightrightleftharpoons mtriplerel trel tequal tmapsto tleftarrow trightarrow tleftrightharrow tLeftarrow tRightarrow tleftrightharrow ttwoheadleftarrow ttwoheadrightarrow tmapsto thookleftarrow thookrightarrow tleftharpoondown tleftharpoonup trightharpoondown trightharpoonup trightoverleftarrow tleftoverrightarrow tleftrightharpoons trightleftharpoons ttriplerel creturns cgives cmesomeric cequilibrium cleaningright cleaningleft clongreturns clonggives clongmesomeric clongequilibrium clongcleaningright clongcleaningleft
$\text{\MATHEXTENSIBLE}\left[\dots^1\dots\right]\left\{\dots^2\dots\right\}\left\{\dots^3\dots\right\}$ 1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT instances: xrel xequal xleftarrow xrightarrow xleftrightharrow xlongleftarrow xlongrightarrow xlongleftrightharrow xleftarrow xrightarrow xleftrightharrow xtwoheadleftarrow xtwoheadrightarrow xmapsto xhookleftarrow xhookrightarrow xleftharpoondown xleftharpoonup xrightharpoondown xrightharpoonup xrightoverleftarrow xleftoverrightarrow xleftrightharpoons xrightleftharpoons xtriplerel mrel mequal mleftarrow mrightarrow mleftrightharrow mLeftarrow mRightarrow mleftrightharrow mtwoheadleftarrow mtwoheadrightarrow mmapsto mhookleftarrow mhookrightarrow mleftharpoondown mleftharpoonup mrightharpoondown mrightharpoonup mrightoverleftarrow mleftoverrightarrow mleftrightharpoons mrightrightleftharpoons mtriplerel trel tequal tmapsto tleftarrow trightarrow tleftrightharrow tLeftarrow tRightarrow tleftrightharrow ttwoheadleftarrow ttwoheadrightarrow tmapsto thookleftarrow thookrightarrow tleftharpoondown tleftharpoonup trightharpoondown trightharpoonup trightoverleftarrow tleftoverrightarrow tleftrightharpoons trightleftharpoons ttriplerel creturns cgives cmesomeric cequilibrium cleaningright cleaningleft clongreturns clonggives clongmesomeric clongequilibrium clongcleaningright clongcleaningleft
$\text{\cequilibrium}\left[\dots^1\dots\right]\left\{\dots^2\dots\right\}\left\{\dots^3\dots\right\}$ 1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT

$\backslash\text{cgives}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{cleaningleft}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{cleaningright}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{clongequilibrium}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT OPT 2 TEXT 3 TEXT
$\backslash\text{clonggives}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{clongcleaningleft}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT OPT 2 TEXT 3 TEXT
$\backslash\text{clongcleaningright}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT OPT 2 TEXT 3 TEXT
$\backslash\text{clongmesomeric}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{clongreturns}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{cmesomeric}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{creturns}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{mequal}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT
$\backslash\text{mhookleftarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT OPT 2 TEXT 3 TEXT

$\hookrightarrow$ <code>\mhookrightarrow</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\leftarrow$ <code>\mLeftarrow</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\Leftrightarrow$ <code>\mLeftrightarrow</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\leftarrow$ <code>\mleftarrow</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\harpoonright$ <code>\mleftharpoondown</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\harpoonup$ <code>\mleftharpoonup</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\overrightarrow{\leftarrow}$ <code>\mleftoverrightarrow</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\overrightarrow{\rightarrow}$ <code>\mleftrightharpoonup</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\leftrightharpoons$ <code>\mleftrightharpoons</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\mapsto$ <code>\mmapsto</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\rightarrow$ <code>\mRightarrow</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\rel$ <code>\mrel</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT
$\rightarrow$ <code>\mrightarrow</code> $[...,\overset{1}{=},...]$ $\{\dots\}$ $\{\dots\}$ 1 inherits: <code>\setupmathstackers</code> ^{OPT} OPT OPT 2 TEXT 3 TEXT

$\mrightharpoonupdown$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\mrightharpoonup$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\mrightrightarpoons$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\mrightrightarrow$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\mtriplerel$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\mtwoheadleftarrow$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\mtwoheadrightarrow$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\tequal$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\thookleftarrow$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\thookrightarrow$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\tleftarrow$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\tleftrightarrow$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\tleftarrow$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT

$\text{\tlefttharpoondown}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\tleftharpoonup}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\tleftoverrightarrow}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\tleftrightarrow}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\tleftrightharpoons}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\tmapsto}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\tRightarrow}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\trel}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\trightarrow}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\trightharpoondown}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\trightharpoonup}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\trightleftharpoons}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT
$\text{\trightoverleftarrow}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT 3 TEXT

$\text{\tttriplelrel}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\tttwoheadleftarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\tttwoheadrightarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxequal}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxhookleftarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxhookrightarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxLeftarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxLeftrightarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxleftarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxleftharpoondown}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxleftharpoonup}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxleftoverrightarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT
$\text{\ttxleftrightarrow}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$
1 inherits: $\text{\ttsetupmathstackers}$ 2 TEXT 3 TEXT


```
\xleftarrow[\text{inherits: \setupmathstackers}]{\text{TEXT}}
```

```
\xlongleftarrow[...,\overset{1}{=},...]{...} \overset{2}{...} \overset{3}{...}
```

```
1 inherits: \setupmathstackersOPT OPT OPT
```

```
2 TEXT
```

```
3 TEXT
```

```
\xlongleftarrow[...]{...} \overset{1}{...} \overset{2}{...} \overset{3}{...}
```

1 inherits: \setupmathstackers OPT OPT OPT

2 TEXT

3 TEXT

$$\backslash xlongrightarrow \quad [\dots, \dots, \overset{1}{\dots}, \dots] \quad \{ \overset{2}{\dots} \} \quad \{ \overset{3}{\dots} \}$$

```

1 inherits: \setupmathstackersOPT
2 TEXT
3 TEXT

```

```
\xmapsto [1]{2}{3}
1 inherits: \setupmathstackers OPT OPT
2 TEXT
3 TEXT
```

```
\xrightarrow{[\dots,\overset{1}{\dots},\dots]} \{\overset{2}{\dots}\} \{\overset{3}{\dots}\}
```

```
1 inherits: \setupmathstackers OPT OPT
```

```
2 TEXT
```

```
3 TEXT
```

```
\xrel    [...1...2...]  {...3}
1  inherits: \setupmathstackers OPT OPT
2  TEXT
3  TEXT
```

```
\xrightarrow{[\dots,\overset{1}{\dots},\dots]} \{\overset{2}{\dots}\} \{\overset{3}{\dots}\}
```

```
1 inherits: \setupmathstacks OPT OPT
```

```
2 TEXT
```

```
3 TEXT
```

<pre> \xrightharpoonowdown [...,\tfrac{1}{...},...] {\tfrac{2}{...}} {\tfrac{3}{...}} 1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT </pre>

$\backslash\mathrm{xrightharpoonup}$ $[...,\overset{1}{=}...,...]$ $\{.\overset{2}{.}\}$ $\{.\overset{3}{...}\}$
1 inherits: $\backslash\mathrm{setupmathstackers}^{\mathrm{OPT}}$ OPT OPT
2 TEXT
3 TEXT

<pre> \xrightleftharpoons[...,\stackrel{1}{...},...]{...^{2}}{...^{3}} 1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT </pre>

$\xrightarrow{\quad} \left[\dots, \dots, \frac{1}{\dots}, \dots \right] \quad \{ \dots \}^2 \quad \{ \dots \}^3$			
1	inherits: <code>\setupmathstackers</code>	OPT	OPT
2	TEXT		
3	TEXT		

```
\xtriplerel    [...1...]    {...2}    {...3}
1 inherits: \setupmathstackers      OPT      OPT
2 TEXT
3 TEXT
```

$\xrightarrow{... \overset{1}{=}, ...}$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\xrightarrow{... \overset{1}{=}, ...}$ $\{...\}^2$ $\{...\}^3$
1 inherits: \setupmathstackers OPT OPT OPT 2 TEXT 3 TEXT
$\ce{...}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\cgives$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\cleaningleft$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\cleaningright$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\clongequilibrium$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\clonggives$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\clongcleaningleft$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\clongcleaningright$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\clongmesomeric$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\clongreturns$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT
$\cmesomeric$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$
1 reverse mathematika ^{OPT} text chemistry ^{OPT} 2 TEXT 3 TEXT

`\creturns` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mequal` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mhookleftarrow` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mhookrightarrow` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mLeftarrow` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mLeftrightarrow` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mleftarrow` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mleftharpoondown` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mleftharpoonup` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mleftoverrightarrow` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mleftrightharpoonup` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mleftrightharpoons` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

`\mmapsto` [¹...] {²...} {³...}

1 reverse mathematika text^{OPT}chemistry^{OPT}
2 TEXT
3 TEXT

```

\mRrightarrow [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT

```

```

\mrel [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT

```

```

\mrightarrow [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT

```

```

\mrightharpoondown [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```

\mrightharpoonup [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```

\mrightharpoons [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```

\mrightrightarrow [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```

\mtriplerel [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```

\mtwoheadleftarrow [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```

\mtwoheadrightarrow [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```

\tequal [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```

\thookleftarrow [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```

\thookrightarrow [...] {...} {...}
1 reverse matematika text chemiOPTstry
2 TEXT
3 TEXT

```

```
\tLeftarrow [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\tLeftrightarrow [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\tleftarrow [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\tleftharpoondown [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\tleftharpoonup [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\tleftoverrightarrow [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\tleftrightarrow [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\tleftrightharpoons [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\tmapsto [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\tRrightarrow [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\trel [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\trightarrow [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

```
\trightharpoondown [...] {...} {...}
1 reverse matematikaOPT text chemiOPTstry
2 TEXT
3 TEXT
```

$\backslash\mathrm{trightharpoonup}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{trightleftharpoons}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{trightoverleftarrow}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{ttriplelrel}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{twoheadleftarrow}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{twoheadrightarrow}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{xequal}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{xhookleftarrow}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{xhookrightarrow}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{xLeftarrow}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{xLeftrightarrow}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{xleftarrow}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{xleftharpoondown}$ $[...] \{...\} \{...\}$ 1 reverse matematika text chemistry 2 TEXT 3 TEXT

```

1 reverse matematika text chemistry OPT
2 TEXT
3 TEXT

```

```
1 reverse matematika text chemistry OPT OPT OPT
2 TEXT
3 TEXT
```

```

1 reverse matematika textOPT chemistryOPT OPT
2 TEXT
3 TEXT

```

```
1 reverse matematika text chemistry OPT OPT
2 TEXT
3 TEXT
```

```

1 reverse matematika text chemistry OPT
2 TEXT
3 TEXT

```

```
1 reverse matematika text chemistry OPT OPT
2 TEXT
3 TEXT
```

```

1 reverse matematika textOPT chemistryOPT OPT
2 TEXT
3 TEXT

```

```

1 reverse matematika textOPT chemistryOPT
2 TEXT
3 TEXT

```

```

1 reverse mathematikaOPT text chemistryOPT
2 TEXT
3 TEXT

```

```

1 reverse OPTmathematikaOPTtext GPTchemistry
2 TEXT
3 TEXT

```

```
1 reverse matematikaOPT text chemiOPTstry OPT
2 TEXT
3 TEXT
```

```
1 reverse matematika text chemistry OPT OPT OPT
2 TEXT
3 TEXT
```

```
1 reverse matematika textOPT chemistryOPT OPT
2 TEXT
3 TEXT
```

```
\xrightleftharpoons[...]{...}
1 reverse mathematica text chemistry
2 TEXT
3 TEXT
```

```
\xrightarrowleftarrow{...} {\overset{2}{...}} {\overset{3}{...}}
```

1 reverse matematika text chemistry OPT OPT

2 TEXT

3 TEXT

```
\xtriplerel [...] {1...} {2...} {3...}
1 reverse matematika text chemistry OPT
2 TEXT
3 TEXT
```

```
\xtwoheadleftarrow{[...]}{\overset{2}{...}}{\overset{3}{...}}
1 reverse matematika text OPTChemistry OPT
2 TEXT
3 TEXT
```

```
\xtwoheadrightarrow [..1] {..2} {..3}
1 reverse matematika text chemistry
2 TEXT
3 TEXT
```

```
\mathfiller    {...}
*   NUMMER
```

$\backslash$ MATHFILLER
 instances: relfill equalfill leftarrowfill rightarrowfill twoheadleftarrowfill
 twoheadrightarrowfill mapstofill leftharpoonupdownfill leftharpoonupfill rightharpoonupdownfill
 rightharpoonupfill rightoverleftarrowfill leftoverrightarrowfill triplereleftfill
 leftrightarrowfill Leftarrowfill Rightarrowfill Lefttriplearrowfill Rightleftarrowfill

\equalfill

 $\xrightarrow{\hspace{1.5cm}}$ $\xrightarrow{\hspace{1.5cm}}$ $\leftarrow$ $\leftharpoonowdownfill$ $\leftharpoonupfill$ `\leftoverrightarrowfill` $\longleftrightarrow$

\mapstofill

 $\rightarrow$ $\rightarrow$

\relfill

<code>\rightarrowfill</code>
<code>\rightharpoondownfill</code>
<code>\rightharpoonupfill</code>
<code>\rightoverleftarrowfill</code>
<code>\triplerelfill</code>
<code>\twoheadleftarrowfill</code>
<code>\twoheadrightarrowfill</code>
<code>\mathfraktur</code>
<code>\MATHFRAMED</code> $[...,\overset{1}{...},...]$ $\{...\}^2$ 1 inherits: <code>\setupmathframed</code> 2 CONTENT instances: <code>mframed inmframed mcframed mtframed</code>
<code>\inmframed</code> $[...,\overset{1}{...},...]$ $\{...\}^2$ 1 inherits: <code>\setupmathframed</code> 2 CONTENT
<code>\mcframed</code> $[...,\overset{1}{...},...]$ $\{...\}^2$ 1 inherits: <code>\setupmathframed</code> 2 CONTENT
<code>\mframed</code> $[...,\overset{1}{...},...]$ $\{...\}^2$ 1 inherits: <code>\setupmathframed</code> 2 CONTENT
<code>\mtframed</code> $[...,\overset{1}{...},...]$ $\{...\}^2$ 1 inherits: <code>\setupmathframed</code> 2 CONTENT
<code>\MATHFUNCTION</code> instances: <code>arccos arcsin arctan arccosh arcsinh arctanh acos asin atan arg cosh cos coth cot</code> <code>csc deg det dim erf erfc erfi exp gcd hom inf inv injlim ker lg liminf limsup lim ln log</code> <code>median max min mod projlim Pr sec sinh sin sup tanh tan diff adj coker neg</code>
<code>\acos</code>
<code>\adj</code>
<code>\arccos</code>
<code>\arccosh</code>
<code>\arcsin</code>
<code>\arcsinh</code>
<code>\arctan</code>

<code>\arctanh</code>
<code>\arg</code>
<code>\MATHFUNCTION {...}</code> <code>* CONTENT</code> instances: adjoint orthogonalcomplement transpose derivative secondderivative thirdderivative fourthderivative preimage inverse
<code>\adjoint {...}</code> <code>* CONTENT</code>
<code>\derivative {...}</code> <code>* CONTENT</code>
<code>\fourthderivative {...}</code> <code>* CONTENT</code>
<code>\inverse {...}</code> <code>* CONTENT</code>
<code>\orthogonalcomplement {...}</code> <code>* CONTENT</code>
<code>\preimage {...}</code> <code>* CONTENT</code>
<code>\secondderivative {...}</code> <code>* CONTENT</code>
<code>\thirdderivative {...}</code> <code>* CONTENT</code>
<code>\transpose {...}</code> <code>* CONTENT</code>
<code>\asin</code>
<code>\atan</code>
<code>\coker</code>
<code>\cos</code>
<code>\cosh</code>
<code>\cot</code>
<code>\coth</code>
<code>\csc</code>
<code>\deg</code>
<code>\det</code>

$\backslash\mathrm{diff}$
$\backslash\mathrm{dim}$
$\backslash\mathrm{erf}$
$\backslash\mathrm{erfc}$
$\backslash\mathrm{erfi}$
$\backslash\mathrm{exp}$
$\backslash\mathrm{gcd}$
$\backslash\mathrm{hom}$
$\backslash\mathrm{inf}$
$\backslash\mathrm{injl\!im}$
$\backslash\mathrm{inv}$
$\backslash\mathrm{ker}$
$\backslash\mathrm{lg}$
$\backslash\mathrm{lim}$
$\backslash\mathrm{liminf}$
$\backslash\mathrm{limsup}$
$\backslash\mathrm{ln}$
$\backslash\mathrm{log}$
$\backslash\mathrm{max}$
$\backslash\mathrm{median}$
$\backslash\mathrm{min}$
$\backslash\mathrm{mod}$
$\backslash\mathrm{neg}$
$\backslash\mathrm{Pr}$
$\backslash\mathrm{projlim}$
$\backslash\mathrm{sec}$

<code>\sin</code>
<code>\sinh</code>
<code>\sup</code>
<code>\tan</code>
<code>\tanh</code>
<code>\mathGreeknumerals {.*.}</code> * NUMBER
<code>\mathgreeknumerals {.*.}</code> * NUMBER
<code>\mathgroupedcommandcs *. .</code> * CSNAME
<code>\mathit</code>
<code>\mathitalic</code>
<code>\mathlimop {.*.}</code> * CONTENT
<code>\MATHMATRIX [...,\frac{.}{.},...]</code> <code>{.^{.2.}}</code> 1 inherits: \setupmathmatrix 2 CONTENT instances: matrix bmatrix pmatrix vmatrix vvmatrix vvvmatrix gmatrix bracedmatrix thematrix
<code>\bmatrix [...,\frac{.}{.},...]</code> <code>{.^{.2.}}</code> 1 inherits: \setupmathmatrix 2 CONTENT
<code>\bracedmatrix [...,\frac{.}{.},...]</code> <code>{.^{.2.}}</code> 1 inherits: \setupmathmatrix 2 CONTENT
<code>\gmatrix [...,\frac{.}{.},...]</code> <code>{.^{.2.}}</code> 1 inherits: \setupmathmatrix 2 CONTENT
<code>\matrix [...,\frac{.}{.},...]</code> <code>{.^{.2.}}</code> 1 inherits: \setupmathmatrix 2 CONTENT
<code>\pmatrix [...,\frac{.}{.},...]</code> <code>{.^{.2.}}</code> 1 inherits: \setupmathmatrix 2 CONTENT
<code>\thematrix [...,\frac{.}{.},...]</code> <code>{.^{.2.}}</code> 1 inherits: \setupmathmatrix 2 CONTENT
<code>\vmatrix [...,\frac{.}{.},...]</code> <code>{.^{.2.}}</code> 1 inherits: \setupmathmatrix 2 CONTENT

$\backslash\mathrm{vvmatrix}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathmatrix}$ 2 CONTENT
$\backslash\mathrm{vvvmatrix}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathmatrix}$ 2 CONTENT
$\backslash\mathrm{mathnesting}$ $[\overset{1}{...}]$ $\{...\}$ 1 NUMBER 2 CONTENT
$\backslash\mathrm{MATHNESTING}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathnesting}$ 2 CONTENT instances: mathtogether mathloose
$\backslash\mathrm{mathloose}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathnesting}$ 2 CONTENT
$\backslash\mathrm{mathtogether}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathnesting}$ 2 CONTENT
$\backslash\mathrm{mathnolop}$ $\{...\}$ * CONTENT
$\backslash\mathrm{mathop}$ $\{...\}$ * CONTENT
$\backslash\mathrm{mathopdolimits}$ $\{...\}$ * CONTENT
$\backslash\mathrm{MATHOPERATOR}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}$ 2 CONTENT instances: integral iintegral iiintegral iiiintegral int iint iiint iiiint oint oint oiiint intc ointc aointc sumint barint doublebarint slashint aodownintc rectangularpoleintc semicirclepoleintc circlepoleoutsideintc circlepoleinsideintc squareintc hookleftarrowint timesint capint cupint upperint lowerint sum blackboardsum modtwosum prod coprod bigwedge bigvee bigcap bigcup bigodot bigoplus bigotimes bigodot biguplus bigsqcap bigsqcup bigtimes leftouterjoin rightouterjoin fullouterjoin bigbottom bigtop bigsolidus bigreversesolidus bigdoublewedge bigdoublevee
$\backslash\mathrm{aodownintc}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}$ 2 CONTENT
$\backslash\mathrm{aointc}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}$ 2 CONTENT
$\backslash\mathrm{barint}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}$ 2 CONTENT
$\backslash\mathrm{bigbottom}$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}$ 2 CONTENT

$\backslash\text{bigcap}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigcup}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigdoublevee}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigdoublewedge}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigodot}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigoplus}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigotimes}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigreversesolidus}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT OPT 2 CONTENT
$\backslash\text{bigsolidus}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT OPT 2 CONTENT
$\backslash\text{bigsqcap}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigsqcup}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigtimes}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigtop}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigudot}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{biguplus}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT

$\backslash\text{bigvee}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{bigwedge}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{blackboardsum}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{capint}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{circlepoleinsideintc}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT OPT 2 CONTENT
$\backslash\text{circlepoleoutsideintc}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT OPT 2 CONTENT
$\backslash\text{coprod}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{cupint}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{doublebarint}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{fullouterjoin}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{hookleftarrowint}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT OPT 2 CONTENT
$\backslash\text{iiiint}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{iiiintegral}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT OPT 2 CONTENT
$\backslash\text{iiint}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT 2 CONTENT
$\backslash\text{iiintegral}$ $[...,\overset{1}{=},...]$ $\{\dots\}$ 1 inherits: $\backslash\text{setupmathoperators}$ OPT OPT 2 CONTENT

$\backslash\mathrm{iint}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{iintegral}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{int}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{intc}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{integral}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{leftouterjoin}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{lowerint}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{modtwosum}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{oiint}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{oint}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{oint}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{ointc}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{prod}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{rectangularpoleintc}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT
$\backslash\mathrm{rightouterjoin}\quad [\dots,\overset{1}{=}\dots]\quad \{\dots\}$ 1 inherits: $\backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$ 2 CONTENT

$\backslash$ semicirclepoleintc [$\dots\overset{1}{=}\dots$] $\{\dots\}^2$ 1 inherits: $\backslash$ setupmathoperators OPT OPT 2 CONTENT
$\backslash$ slashint [$\dots\overset{1}{=}\dots$] $\{\dots\}^2$ 1 inherits: $\backslash$ setupmathoperators OPT OPT 2 CONTENT
$\backslash$ squareintc [$\dots\overset{1}{=}\dots$] $\{\dots\}^2$ 1 inherits: $\backslash$ setupmathoperators OPT OPT 2 CONTENT
$\backslash$ sum [$\dots\overset{1}{=}\dots$] $\{\dots\}^2$ 1 inherits: $\backslash$ setupmathoperators OPT 2 CONTENT
$\backslash$ sumint [$\dots\overset{1}{=}\dots$] $\{\dots\}^2$ 1 inherits: $\backslash$ setupmathoperators OPT 2 CONTENT
$\backslash$ timesint [$\dots\overset{1}{=}\dots$] $\{\dots\}^2$ 1 inherits: $\backslash$ setupmathoperators OPT 2 CONTENT
$\backslash$ upperint [$\dots\overset{1}{=}\dots$] $\{\dots\}^2$ 1 inherits: $\backslash$ setupmathoperators OPT 2 CONTENT
$\backslash$ mathopnolimits $\{.*\}$ * CONTENT
$\backslash$ mathoptext $\{.*\}$ * TEXT
$\backslash$ mathopwithlimits $\{.^1\}$ $\{.^2\}$ 1 CONTENT 2 CONTENT
$\backslash$ MATHORNAMENT $\{.*\}$ * CONTENT
$\backslash$ mathortext $\{.^1\}$ $\{.^2\}$ 1 TEXT 2 TEXT
$\backslash$ mathover [$\{.^1\}$] [$\dots\overset{2}{=}\dots$] $\{.^3\}$ $\{.^4\}$ 1 vrsek vfenced OPT OPT 2 inherits: $\backslash$ setupmathstackers 3 NUMMER 4 TEXT
$\backslash$ MATHOVEREXTENSIBLE [$\dots\overset{1}{=}\dots$] $\{.^2\}$ 1 inherits: $\backslash$ setupmathstackers OPT 2 TEXT instances: overleftarrow overrightarrow overleftrightarrow overtwoheadleftarrow overtwoheadrightarrow overlefttailarrow overrighttailarrow overleftbararrow overrightbararrow overlefthookarrow overrighthookarrow overleftharpoonup overleftharpoonup overrightarrow overleftarrow overleftrightarrow overleftbararrow overrightarrow overbar overbrace overparent overbracket

$\overbar$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overline{\text{setupmathstackers}}$ 2 TEXT
$\overbrace$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overbrace{\text{setupmathstackers}}$ 2 TEXT
$\overbracket$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overbracket{\text{setupmathstackers}}$ 2 TEXT
$\overleftarrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overleftarrow{\text{setupmathstackers}}$ 2 TEXT
$\overleftbararrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overleftbararrow{\text{setupmathstackers}}$ OPT 2 TEXT
$\overleftrightharpoonup$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overleftrightharpoonup{\text{setupmathstackers}}$ OPT 2 TEXT
$\overleftarrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overleftarrow{\text{setupmathstackers}}$ OPT 2 TEXT
$\overleftbararrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overleftbararrow{\text{setupmathstackers}}$ OPT 2 TEXT
$\overleftharpoonupdown$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overleftharpoonupdown{\text{setupmathstackers}}$ OPT 2 TEXT
$\overleftharpoonup$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overleftharpoonup{\text{setupmathstackers}}$ OPT 2 TEXT
$\overlefthookarrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overlefthookarrow{\text{setupmathstackers}}$ OPT 2 TEXT
$\overleftrightharpoonup$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overleftrightharpoonup{\text{setupmathstackers}}$ OPT 2 TEXT
$\overlefttailarrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overlefttailarrow{\text{setupmathstackers}}$ OPT 2 TEXT
$\overparent$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overparent{\text{setupmathstackers}}$ OPT 2 TEXT
$\overrightarrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\overrightarrow{\text{setupmathstackers}}$ OPT 2 TEXT

$$\overrightarrow{\hspace{1.5cm}} \quad [\dots,\dots\overset{1}{=}\dots,\dots] \quad \{\dots\overset{2}{\}$$
$$\overrightarrow{\hspace{1.5cm}} \quad [\dots,\dots\overset{1}{=}\dots,\dots] \quad \{\dots\}^2$$
$$\overrightarrow{\hspace{1.5cm}} \quad [\dots,\dots\overset{1}{=}\dots,\dots] \quad \{\dots\overset{2}{\}$$
$$\overrightarrow{\text{harpoon}} \downarrow \quad [\dots, \dots \overset{1}{=} \dots, \dots] \quad \{\overset{2}{\dots}\}$$
$$\overrightarrow{\text{harpoonup}} \quad [\dots\overset{1}{=}\dots] \quad \{\overset{2}{\dots}\}$$
$$\overrightarrow{\hspace{1.5cm}} \quad [\dots\overset{1}{=}\dots] \quad \{\overset{2}{\dots}\}$$
$$\overrightarrow{\hspace{1.5cm}} \quad [\dots\dots\overset{1}{=}\dots\dots] \quad \{\overset{2}{\dots}\}$$
$$\overrightarrow{\text{twoheadleftarrow}} \left[\dots \overset{1}{=} \dots \right] \{ \overset{2}{\dots} \}$$
$$\overrightarrow{\quad\quad\quad} \quad [\dots\overset{1}{=}\dots] \quad \{\overset{2}{\dots}\}$$
$$\mathop{\mathrm{vertext}}\limits \left[\begin{smallmatrix} 1 \\ \cdot \\ \cdot \end{smallmatrix} \right] \quad \left\{ \begin{smallmatrix} 2 \\ \cdot \\ \cdot \end{smallmatrix} \right\} \quad \left\{ \begin{smallmatrix} 3 \\ \cdot \\ \cdot \end{smallmatrix} \right\}$$
$$\backslash\mathrm{MATHOVERTEXTTEXTENSIBLE} \quad \{...\}^1 \quad \{...\}^2$$
$$\overline{\text{text}} \quad \{.^1..\} \quad \{.^2..\}$$
$$\overbrace{\text{text}}^1 \quad \overbrace{\text{text}}^2$$
$$\overbrace{\text{text}}^1 \quad \overbrace{\text{text}}^2$$
$$\overparenttext \quad \{ \dots \}^1 \quad \{ \dots \}^2$$

$\backslash$ MATHOVER {...} * TEXT instances: interiorset
$\backslash$ interiorset {...} * TEXT
$\backslash$ mathqed
$\backslash$ MATHRADICAL [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT instances: root sqrt rannuity lannuity lrannuity rlannuity annuity lbannuity rbannuity rlbannuity lrbannuity
$\backslash$ annuity [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT
$\backslash$ lannuity [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT
$\backslash$ lbannuity [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT
$\backslash$ lrannuity [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT
$\backslash$ rlbannuity [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT
$\backslash$ rannuity [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT
$\backslash$ rbannuity [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT
$\backslash$ rlannuity [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT
$\backslash$ rlbannuity [...,\dots^{\frac{1}{d}}...] [...^2] {...^3} 1 inherits: \setupmathradical _{OPT} 2 TEXT 3 CONTENT

$\sqrt[n]{\dots}$ <code>\root</code> $[\dots]$ $\{\dots\}$ 1 inherits: <code>\setupmathradical</code> OPT 2 TEXT 3 CONTENT
$\sqrt[n]{\dots}$ <code>\sqrt</code> $[\dots]$ $\{\dots\}$ 1 inherits: <code>\setupmathradical</code> OPT 2 TEXT 3 CONTENT
$\mathrm{\dots}$ <code>\mathrm</code>
$\text{\dots}$ <code>\mathrowanchored</code> $\{\dots\}$ * NAME NUMMER
$\mathscr{\dots}$ <code>\mathscript</code>
$\mathop{\dots}\limits^{\dots}$ <code>\MATHSIMPLEALIGN</code> $[\dots]$ $\{\dots\}$ 1 inherits: <code>\setupmathsimplealign</code> OPT 2 CONTENT instances: equationsystem lequationsystem reequationsystem
$\mathop{\dots}\limits^{\dots}$ <code>\equationsystem</code> $[\dots]$ $\{\dots\}$ 1 inherits: <code>\setupmathsimplealign</code> OPT 2 CONTENT
$\mathop{\dots}\limits^{\dots}$ <code>\lequationsystem</code> $[\dots]$ $\{\dots\}$ 1 inherits: <code>\setupmathsimplealign</code> OPT 2 CONTENT
$\mathop{\dots}\limits^{\dots}$ <code>\requationsystem</code> $[\dots]$ $\{\dots\}$ 1 inherits: <code>\setupmathsimplealign</code> OPT 2 CONTENT
$\mathsf{\dots}$ <code>\mathsl</code>
$\mathss{\dots}$ <code>\mathss</code>
$\mathop{\dots}\limits^{\dots}$ <code>\mathstacker</code> $[\dots]$ $\{\dots\}$ $\{\dots\}$ $\{\dots\}$ 1 reverse mathematika ^{OPT} text chemistry 2 NUMMER 3 TEXT 4 TEXT
$\mathop{\dots}\limits^{\dots}$ <code>\mathsync</code> $\{\dots\}$ $\{\dots\}$ 1 NAME 2 NUMMER
$\mathop{\dots}\limits^{\dots}$ <code>\mathtext</code> $\{\dots\}$ $\{\dots\}$ 1 TEXT OPT 2 TEXT
$\mathop{\dots}\limits^{\dots}$ <code>\mathtextauto</code> $\{\dots\}$ $\{\dots\}$ 1 TEXT 2 TEXT
$\mathop{\dots}\limits^{\dots}$ <code>\MATHTEXT</code> $\{\dots\}$ * TEXT instances: mathtext mathtexttf mathtextit mathtextsl mathtextbf mathtextbi mathtextbs mathword mathwordtf mathwordit mathwordsl mathwordbf mathwordbi mathwordbs mathsplit mathsplittf mathsplitit mathsplitsl mathsplitbf mathsplitbi mathsplitbs

$\backslash\mathsf{split}$ {...} * TEXT
$\backslash\mathsf{splitbf}$ {...} * TEXT
$\backslash\mathsf{splitbi}$ {...} * TEXT
$\backslash\mathsf{splitbs}$ {...} * TEXT
$\backslash\mathsf{splitit}$ {...} * TEXT
$\backslash\mathsf{plitsl}$ {...} * TEXT
$\backslash\mathsf{plittf}$ {...} * TEXT
$\backslash\mathsf{text}$ {...} * TEXT
$\backslash\mathsf{textbf}$ {...} * TEXT
$\backslash\mathsf{textbi}$ {...} * TEXT
$\backslash\mathsf{textbs}$ {...} * TEXT
$\backslash\mathsf{textit}$ {...} * TEXT
$\backslash\mathsf{textsl}$ {...} * TEXT
$\backslash\mathsf{texttf}$ {...} * TEXT
$\backslash\mathsf{word}$ {...} * TEXT
$\backslash\mathsf{wordbf}$ {...} * TEXT
$\backslash\mathsf{wordbi}$ {...} * TEXT
$\backslash\mathsf{wordbs}$ {...} * TEXT
$\backslash\mathsf{wordit}$ {...} * TEXT

$\backslash\mathrm{mathwordsl}\quad\{...\}$ $\ast$ TEXT
$\backslash\mathrm{mathwordtf}\quad\{...\}$ $\ast$ TEXT
$\backslash\mathrm{mathtf}$
$\backslash\mathrm{mathtriplet}\quad[...]\quad\{...\}^2\quad\{...\}^3\quad\{...\}^4$ 1 NAME OPT OPT OPT OPT 2 TEXT 3 TEXT 4 TEXT
$\backslash\mathrm{MATHTRIPLET}\quad[...]\quad\{...\}^2\quad\{...\}^3\quad\{...\}^4$ 1 NAME OPT OPT OPT OPT 2 TEXT 3 TEXT 4 TEXT
$\backslash\mathrm{mathtt}$
$\backslash\mathrm{mathunder}\quad[...]\quad[...]\stackrel{2}{=}...]\quad\{...\}^3\quad\{...\}^4$ 1 $\mathrm{spodek}\ \mathrm{vfenced}$ OPT OPT 2 inherits: $\backslash\mathrm{setupmathstackers}$ 3 NUMMER 4 TEXT
$\backslash\mathrm{MATHUNDEREXTENSIBLE}\quad[...]\stackrel{1}{=}...]\quad\{...\}^2$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT instances: $\mathrm{underleftarrow}\ \mathrm{underrightarrow}\ \mathrm{underleftrightarrow}\ \mathrm{undertwoheadleftarrow}\ \mathrm{undertwoheadrightarrow}\ \mathrm{underlefttailarrow}\ \mathrm{underrighttailarrow}\ \mathrm{underleftbararrow}\ \mathrm{underrightbararrow}\ \mathrm{underlefthookarrow}\ \mathrm{underrighthookarrow}\ \mathrm{underleftharpoondown}\ \mathrm{underleftharpoonup}\ \mathrm{underrightharpoondown}\ \mathrm{underrightharpoonup}\ \mathrm{underRightarrow}\ \mathrm{underLeftarrow}\ \mathrm{underLeftrightarrow}\ \mathrm{underLeftbararrow}\ \mathrm{underRightbararrow}\ \mathrm{underbar}\ \mathrm{underbrace}\ \mathrm{underparent}\ \mathrm{underbracket}$
$\backslash\mathrm{underbar}\quad[...]\stackrel{1}{=}...]\quad\{...\}^2$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT
$\backslash\mathrm{underbrace}\quad[...]\stackrel{1}{=}...]\quad\{...\}^2$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT
$\backslash\mathrm{underbracket}\quad[...]\stackrel{1}{=}...]\quad\{...\}^2$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT
$\backslash\mathrm{underLeftarrow}\quad[...]\stackrel{1}{=}...]\quad\{...\}^2$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT
$\backslash\mathrm{underLeftbararrow}\quad[...]\stackrel{1}{=}...]\quad\{...\}^2$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT
$\backslash\mathrm{underLeftrightarrow}\quad[...]\stackrel{1}{=}...]\quad\{...\}^2$ 1 inherits: $\backslash\mathrm{setupmathstackers}$ OPT 2 TEXT

$\underleftarrow{\quad}$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underleftarrow{\bar{\quad}}$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underleftharpoonupdown$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underleftharpoonup$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underlefthookarrow$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underleftrightharpoonup$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underlefttailarrow$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underparent$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underrightarrow$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underrightarrow{\bar{\quad}}$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underrightarrow$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underrightarrow{\bar{\quad}}$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underrightharpoonupdown$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underrightharpoonup$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT
$\underrighthookarrow$ $[...,\overset{1}{=},...]$ $\{\dots\}$
1 inherits: \setupmathstackers ^{OPT} 2 TEXT

$\underrightarrowtail$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT 2 TEXT
$\undertwoheadleftarrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT 2 TEXT
$\undertwoheadrightarrow$ $[...,\overset{1}{=},...]$ $\{...\}$ 1 inherits: $\backslash\text{setupmathstackers}$ OPT 2 TEXT
$\mathbf{\text{under}}\text{text}$ $[...\overset{1}{}]$ $\{...\overset{2}{}}$ $\{...\overset{3}{}}$ 1 spodek OPT 2 TEXT 3 TEXT
$\text{MATHUNDERTEXTTEXTENSIBLE}$ $\{...\overset{1}{}}$ $\{...\overset{2}{}}$ 1 TEXT 2 TEXT instances: underbartext underbracetext underparenttext underbrackettext
underbartext $\{...\overset{1}{}}$ $\{...\overset{2}{}}$ 1 TEXT 2 TEXT
underbracetext $\{...\overset{1}{}}$ $\{...\overset{2}{}}$ 1 TEXT 2 TEXT
underbrackettext $\{...\overset{1}{}}$ $\{...\overset{2}{}}$ 1 TEXT 2 TEXT
underparenttext $\{...\overset{1}{}}$ $\{...\overset{2}{}}$ 1 TEXT 2 TEXT
MATHUNDER $\{...\overset{*}{}}$ * TEXT
MATHUNSTACKED instances: impliedby implies iff impliesby And
And
iff
impliedby
implies
impliesby
mathupright
math $[...,\overset{1}{=},...]$ $\{...\overset{2}{}}$ 1 inherits: $\backslash\text{setupmathematics}$ OPT 2 CONTENT

$\backslash$ matrix {...} * CONTENT
$\backslash$ maxaligned {...} * CONTENT
$\backslash$ mbinsync {...} {...} 1 NAME 2 NUMMER
$\backslash$ mbox {...} * CONTENT
$\backslash$ measure {...} * NAME
$\backslash$ measured {...} * NAME
$\backslash$ medbreak
$\backslash$ medskip
$\backslash$ medspace
$\backslash$ meritko [...] ¹ [...,...] ² [...] {...} ³ 1 NAME OPT 2 inherits: \setupscale 3 CONTENT
$\backslash$ mesic {...} * NUMMER
$\backslash$ message {...} * TEXT
$\backslash$ mezera
$\backslash$ mfence ... * \vert \singleverticalbar \doubleverticalbar \tripleverticalbar \mvert \mVert
$\backslash$ mfunction [...,...] ¹ [...] [...] ² 1 inherits: \setupmathfunctions OPT 2 NAME
$\backslash$ mfunctionlabeltext {...} * NAME
$\backslash$ mfunction [...,...] ¹ [...] [...] ² 1 inherits: \setupmathfunctions OPT 2 NAME
$\backslash$ mhbox {...} * CONTENT
$\backslash$ middlealigned {...} * CONTENT

<code>\middlebox {...}</code> <code>* CONTENT</code>
<code>\middleparbox [...¹] {...²}</code> <code>1 globalne OPT</code> <code>2 CONTENT</code>
<code>\midhbox {...}</code> <code>* CONTENT</code>
<code>\midsubsentence</code>
<code>\minimalhbox ...¹ {...²}</code> <code>1 TEXT OPT</code> <code>2 CONTENT</code>
<code>\mixedcaps {...}</code> <code>* TEXT</code>
<code>\mkvibuffer [...¹]</code> <code>* BUFFER OPT</code>
<code>\mkvibuffer {...}</code> <code>* BUFFER</code>
<code>\moduleparameter {...¹} {...²}</code> <code>1 FILE</code> <code>2 KEY</code>
<code>\molecule {...}</code> <code>* CONTENT</code>
<code>\mono</code>
<code>\mononormal</code>
<code>\monotucne</code>
<code>\monthlong {...}</code> <code>* NUMMER</code>
<code>\monthshort {...}</code> <code>* NUMMER</code>
<code>\mordsync {...¹} {...²}</code> <code>1 NAME</code> <code>2 NUMMER</code>
<code>\morehyphens</code>
<code>\movedownsidefloat [...*...]</code> <code>* [-+]radek [-+]2*line [-+]zaveseni</code>
<code>\movesidefloat [...*...]</code> <code>* [-+]radek [-+]2*line [-+]zaveseni</code>

$\backslash\text{movesidefloat}$ $[...,\overset{*}{...},...]$ * x = DIMENSION * y = DIMENSION
$\backslash\text{mparagraph}$ $[...,\overset{1}{...},...]$ $\{...\overset{2}{...}\}$ 1 inherits: $\backslash\text{nastavoramofvani}$ 2 CONTENT
$\backslash\text{mplocation}$ $\{...\}$ * vlevo vpravo uvnitr vnejsi
$\backslash\text{mprandomnumber}$
$\backslash\text{mrelsync}$ $\{...\overset{1}{...}\}$ $\{...\overset{2}{...}\}$ 1 NAME 2 NUMMER
$\backslash\text{mrizka}$ $[...,\overset{*}{...},...]$ * inherits: $\backslash\text{basegpfid}$
$\backslash\text{mscaledtext}$ $\{...\}$ * CONTENT
$\backslash\text{mstack}$ $\{...\overset{*}{...},...\}$ * TEXT
$\backslash\text{mtext}$ $\{...\}$ * CONTENT
$\backslash\text{mtp}$ $\{...\}$ * CONTENT
$\backslash\text{mx}$
$\backslash\text{mxx}$
$\backslash\text{m}$ $[...,\overset{1}{...},...]$ $\{...\overset{2}{...}\}$ 1 inherits: $\backslash\text{Setupmathematics}$ 2 CONTENT
$\backslash\text{NormalizeFontHeight}$ $\overset{1}{\backslash}...$ $\{...\overset{2}{...}\}$ $\{...\overset{3}{...}\}$ $\{...\overset{4}{...}\}$ 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
$\backslash\text{NormalizeFontWidth}$ $\overset{1}{\backslash}...$ $\{...\overset{2}{...}\}$ $\{...\overset{3}{...}\}$ $\{...\overset{4}{...}\}$ 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
$\backslash\text{NormalizeTextHeight}$ $\{...\overset{1}{...}\}$ $\{...\overset{2}{...}\}$ $\{...\overset{3}{...}\}$ 1 FONT 2 DIMENSION 3 TEXT
$\backslash\text{NormalizeTextWidth}$ $\{...\overset{1}{...}\}$ $\{...\overset{2}{...}\}$ $\{...\overset{3}{...}\}$ 1 FONT 2 DIMENSION 3 TEXT

\namedanchorbox {...} * NAME
\namedboxanchor {...} * NAME NUMBER
\namedPRIKAZhash {...} * NAME
\namedPRIKAZparameter {...} {...} 1 NAME 2 KEY
\namedgoto [...] {...} [...] 1 NAME 2 CONTENT 3 REFERENCE
\namedheadnumber {...} * ABSCHNITT
\namedstructureheadlocation {...} * ABSCHNITT
\namedstructureuservariable {...} {...} 1 ABSCHNITT 2 KEY
\namedstructurevariable {...} {...} 1 ABSCHNITT 2 KEY
\namedtaggedlabeltexts {...} {...} {...} {...} {...} 1 NAME 2 NAME 3 NAME 4 NAME 5 CONTENT
\namespacedboxanchor {...} * NAME NUMBER
\nastavbarvu [...] * FILE
\nastavbarvy [...,*,...] * status = start stop spot = ano ne expanzen = ano ne faktor = ano ne rgb = ano ne cmyk = ano ne konverze = ano ne vzdy pagecolormodel = auto zadny NAME barvatextu = COLOR intent = overprint knockout zadny
\nastavbilamista [...,*,...] * fixuj fixne prizpusobive řádek pulradku quarterline zadny male stredni velke implicitni DIMENSION

```

1  NAME                                OPT
2  pred                               = BEFEHL
   po                                 = BEFEHL
   vlevo                             = BEFEHL
   vpravo                             = BEFEHL
   alternativa                        = odstavec text
   vnitrni                           = BEFEHL
   setups                             = NAME
   zarovnani                         = inherits: \nastavzarovnani
   pismo                             = STYLE BEFEHL
   barva                             = COLOR

```

```

1  NAME                                OPT
2  stranka = inherits: \strana
   pred    = BEFEHL
   po      = BEFEHL
   cislo   = ano ne

```

```

1  BUFFER
2  define = ano ne
    pred  = BEFEHL
    po    = BEFEHL
    strip = ano ne

```

```
* sirka          = max DIMENSION
  vyska          = max DIMENSION
  hloubka        = max DIMENSION
  vzdalenost     = DIMENSION
  n              = NUMMER
  alternativa    = a b
  pismeno        = STYLE BEFEHL
  barva          = COLOR
  typ            = mp ano ne
  mp             = NAME
  tloustkalinky  = DIMENSION
  shrink         = DIMENSION
  natahnout      = DIMENSION
  zap            = DIMENSION
  vyp            = DIMENSION
  snapping       = ano normalni 0 1 2 0:10 1:10 2:10 2:20 1:top 1:bottom 2:top 2:bottom
```

```

1  ABSCHNITT
2  [-+]NUMMER

```

```
* viewerprefix = TEXT
  status       = start stop zadny drzet prazdne
  popisek      = TEXT
  inherits: \setupcounter
```

```
*  status      = start stop radex reset
   vzdalenost  = DIMENSION
   pismo       = STYLE BEFEHL
   barva       = COLOR
```

```

\nastavcislovaniradku [...] 1 [...] [...] 2 [...]
1 NAME OPT
2 start = NUMMER
  krok = NUMMER
  metoda = stranka prvni dalsi
  konverze = NAME
  pokracovat = ano ne
  misto = text begin end implicitni vlevo vpravo uvnitr vnejsi ivlevo ivpravo marginalie naokraj
  vzdalenost = DIMENSION
  zarovnani = uvnitr vnejsi flushleft flushright vlevo vpravo nastred auto
  prikaz = \...#1
  vlevo = BEFEHL
  vpravo = BEFEHL
  marginalie = DIMENSION
  sirka = marginalie DIMENSION
  pismo = STYLE BEFEHL
  barva = COLOR

```

```

\nastavcislovanistran [...] * [...]
* alternativa = jednostranne dvoustranny
  stranka = inherits: \strana
  strut = ano ne
  prikaz = \...#1
  vlevo = BEFEHL
  vpravo = BEFEHL
  status = start stop
  sirka = DIMENSION
  misto = zahlavi upati vlevo nastred vpravo ivlevo ivpravo marginalie naokraj naokraj textovahrana zadny
  pismo = STYLE BEFEHL
  barva = COLOR

```

```

\nastavcitaci [...] * [...]
* inherits: \setupdelimitedtext

```

```

\nastavdeleniplvoucichobjektu [...] * [...]
* pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  radky = auto NUMMER
  konverze = NAME

```

```

\nastavdelitko [...] * [...]
* znak = normalni siroce

```

```

\nastavdolnitexty [...] 1 [...] [...] 2 [...] [...] 3 [...] [...] 4 [...] [...] 5 [...]
1 text marginalie hrana OPT OPT OPT OPT OPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

```

```

\nastaveni [...] * [...]
* NAME

```

```

\nastaveni [...] * [...]
* NAME

```

```

\nastavexterniobrazy [...] 1 [...] [...] 2 [...]
1 NAME OPT
2 inherits: \setupexternalfigure

```

\nastavhorejsek [¹...] [².........]

```

1 text marginalie hranaOPT
2 status      = start stop prazdne vysoko zadny normalni zadneznamenani NAME
  pismeno     = STYLE BEFEHL
  barva       = COLOR
  strut       = ano ne
  n           = NUMMER
  pred        = BEFEHL
  po          = BEFEHL
  textvlevo   = TEXT
  strednitext = TEXT
  textvpravo  = TEXT
  stylvlevo   = STYLE BEFEHL
  middlestyle = STYLE BEFEHL
  stylvpravo  = STYLE BEFEHL
  barvavlevo  = COLOR
  middlecolor = COLOR
  barvavpravo = COLOR
  sirka       = DIMENSION
  sirkavlevo  = DIMENSION
  middlewidth = DIMENSION
  sirkavpravo = DIMENSION

```

\nastavhornitexty [¹...] [²...] [³...] [⁴...] [⁵...]

```

1 text marginalie hranaOPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

```

\nastavinterakci [¹.........] [².........]

```

1 NAMEOPT
2 status      = start stop
  pismeno     = STYLE BEFEHL
  barva       = COLOR
  kontrastnibarva = COLOR
  titul       = TEXT
  podtitulek   = COLOR
  autor       = TEXT
  datum       = TEXT
  keyword     = TEXT
  zaostreni    = standardni ramecek sirka minsirka vyska minvyska prizpusobive tight
  menu        = zap vyp
  fieldlayer   = auto NAME
  pocitat     = REFERENCE
  klik        = ano ne
  obrazovka    = normalni novy
  stranka     = ano ne stranka jmeno auto
  oteвриakci  = REFERENCE
  zavriakci   = REFERENCE
  akceotevrenistranky = REFERENCE
  akcezavrenistranky  = REFERENCE
  sadasymbolu  = NAME
  vyska        = DIMENSION
  hloubka      = DIMENSION
  focusoffset  = DIMENSION
  prefix       = TEXT

```

\nastavinterakci [...]

```

* NAMEOPT

```


\nastavinterakcnilistu [...] ¹ [...] [...] ² [...]

1 NAME OPT
2 alternativa = a b c d e f g
status = start stop
prikaz = CSNAME
sirka = DIMENSION
vyska = DIMENSION max široky
hloubka = DIMENSION max
vzdalenost = DIMENSION
krok = male stredni velke
barvapozadi = COLOR
pismeno = STYLE BEFEHL
barva = COLOR
kontrastnibarva = COLOR
symbol = ano ne
inherits: \nastavoramovani

\nastavinterakcnimenu [...] ¹ [...] [...] ² [...]

1 NAME OPT
2 alternativa = vertikalne horizontalne skryte
category = NAME
levyoffset = prekryv ramecek zadny implicitni DIMENSION
pravyoffset = prekryv ramecek zadny implicitni DIMENSION
offsetvrsku = prekryv ramecek zadny implicitni DIMENSION
offsetspodku = prekryv ramecek zadny implicitni DIMENSION
maxsirka = DIMENSION
maxvyska = DIMENSION
itemalign = vlevo nastred vpravo flushleft flushright nizko vysoko nivy
status = start prazdne lokalne
vlevo = BEFEHL
vpravo = BEFEHL
vzdalenost = prekryv DIMENSION
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
position = ano ne
stredni = BEFEHL
pismeno = STYLE BEFEHL
barva = COLOR
stejnastranka = ano ne prazdne zadny normalni implicitni
kontrastnibarva = COLOR
inherits: \nastavoramovani

\nastavinterakcniobrazovku [...] ⁺ [...]

* sirka = prizpusobive max tight DIMENSION
vyska = prizpusobive max tight DIMENSION
zpetnamezera = DIMENSION
horoffset = DIMENSION
offsethlavicky = DIMENSION
svrchnimezera = DIMENSION
volba = prizpusobive max jednostranne dvoustranny zalozka auto zadny implicitni fixne nasirku portrait
stranka papir attachment layer titul lefttoright righttoleft nomenubar
copies = NUMMER
print = LISTE
prodleva = zadny NUMMER

\nastavjazyk [...]¹ [...,...²...,...]

```

1  SPRACHE implicitniOPT
2  implicitni      = SPRACHE
    status         = start stop
    datum          = inherits: \aktualnidatum
    time           = inherits: \currenttime
    patterns       = FILE
    lefthyphenmin  = NUMBER
    righthyphenmin = NUMBER
    lefthyphenchar = NUMBER
    righthyphenchar = NUMBER
    explicitlefthyphenchar = NUMBER
    explicitrighthyphenchar = NUMBER
    setups         = NAME
    mezerovani     = siroky zhustene
    font           = auto NAME
    bidi           = vlevo vpravo l2r r2l
    text           = TEXT
    limittext      = TEXT
    hyphen         = TEXT
    compoundhyphen = TEXT
    leftcompoundhyphen = TEXT
    rightcompoundhyphen = TEXT
    citovatvlevo   = BEFEHL
    citovatvpravo  = BEFEHL
    citacevlevo    = BEFEHL
    citacevpravo   = BEFEHL
    leftspeech     = BEFEHL
    rightspeech    = BEFEHL
    vetavlevo      = BEFEHL
    middlespeech   = BEFEHL
    vetavpravo     = BEFEHL
    midsentence    = BEFEHL
    podvetavlevo   = BEFEHL
    podvetavpravo  = BEFEHL
    faktor         = ano ne
    goodies        = FILE

```

\nastavkapitalky [...]¹,... [...,...²...,...]

```

1  NAMEOPT
2  category = NUMBER
    xmeritko = NUMBER
    ymeritko = NUMBER
    weight   = NUMBER
    titul    = ano ne
    sc       = ano ne
    pismeno  = STYLE BEFEHL

```

\nastavkombinovanyseznam [...]¹ [...,...²...,...]

```

1  LISTE
2  kriterium = lokalne uvod odkaz SECTIONBLOCK:odkaz vse SECTIONBLOCK:vse text SECTIONBLOCK:text aktualni SECTIONBLOCK:aktualni
                zde predchozi SECTIONBLOCK:predchozi komponenta ABSCHNITT SECTIONBLOCK:ABSCHNITT
    odkaz     = NUMBER
    extras    = NAME
    order     = prikaz vse titul
    alternativa = a b c d e f g vlevo vpravo vrsek spodek prikaz zadny interactive odstavec horizontalne vertikalne
                NAME

```

\nastaveniCOMBINEDLIST [...,...^{*}...,...]

```

* inherits: \nastavkombinovanyseznam
instances: content

```

\nastavenicontent [...,...^{*}...,...]

```

* inherits: \nastavkombinovanyseznam

```

\nastavkomentar [...¹,...] [...²,...]

1 NAME OPT
 2 status = start stop zadny
 metoda = normalni skryte
 symbol = Comment Napoveda Insert Klavesa Newparagraph Note Odstavec Default
 sirka = prizpusobive DIMENSION
 vyska = prizpusobive DIMENSION
 hloubka = prizpusobive DIMENSION
 titul = TEXT
 podtitulek = TEXT
 autor = TEXT
 nx = NUMMER
 ny = NUMMER
 barva = COLOR
 volba = xml max
 textlayer = NAME
 misto = levahrana pravahrana naokraji levyokraj pravyokraj text vysoko zadny
 vzdalenost = DIMENSION
 mezera = ano
 buffer = BUFFER

\nastavkomentarstrany [...^{*},...]

* misto = vlevo vpravo vrsek spodek zadny
 status = start stop zadny
 offset = DIMENSION
 vzdalenost = DIMENSION
 sirka = DIMENSION
 vyska = DIMENSION

\nastavmarginalnilinky [...¹] [...²,...]

1 NUMMER OPT
 2 inherits: \setupmarginrule

\nastavmeziradkovoumezeru [...¹,...] [...²,...]

1 NAME OPT
 2 radek = DIMENSION
 vyska = NUMMER
 hloubka = NUMMER
 minvyska = NUMMER
 mindepth = NUMMER
 vzdalenost = DIMENSION
 vrsek = NUMMER vyska
 spodek = NUMMER
 nvrsek = NUMMER
 natahnout = NUMMER
 shrink = NUMMER

\nastavmeziradkovoumezeru [...^{*},...]

* zap vyp reset auto male stredni velke^{OPT} NUMMER DIMENSION

\nastavmeziradkovoumezeru [...]

* NAME

```

\nastavnadpis [...] 1 [...] 2 [...]
1 ABSCHNITT OPT
2 frontpartlabel = NAME
  bodypartlabel = NAME
  appendixlabel = NAME
  backpartlabel = NAME
  expanzen = ano ne xml
  catcodes = NAME
  sectionresetset = NAME
  sectionseparatorset = NAME
  sectionconversionset = NAME
  konverze = NAME
  sectionstarter = BEFEHL PROCESSOR->BEFEHL
  sectionstopper = BEFEHL PROCESSOR->BEFEHL
  sectionset = NAME
  sectionsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
    ABSCHNITT:vse aktualni
  referenceprefix = + - TEXT
  pismeno = STYLE BEFEHL
  barva = COLOR
  styltextu = STYLE BEFEHL
  barvatextu = COLOR
  stylcisla = STYLE BEFEHL
  barvacisla = COLOR
  propojeni = ABSCHNITT
  vlastnicislo = ano ne
  beforesection = BEFEHL
  aftersection = BEFEHL
  insidesection = BEFEHL
  predhlavickou = BEFEHL
  pohlavice = BEFEHL
  zvysujicicislo = ano ne seznam prazdne
  umistihlavicku = ano ne skryte prazdne sekce
  cislo = ano ne
  stranka = inherits: \strana
  znaceni = stranka reset novy
  zahlavi = start stop vysoko zadny normalni prazdne zadneznaceni NAME
  text = start stop vysoko zadny normalni prazdne zadneznaceni NAME
  upati = start stop vysoko zadny normalni prazdne zadneznaceni NAME
  pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  pokracovat = ano ne
  zarovnejtitul = ano ne plvouciobjekt
  meziradkovamezera = NAME
  interakce = seznam odkaz
  internalgrid = NAME
  mrizka = normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvnι
    posledni vysoko jedna nizko zadny radek strut box min max nastred math math:radek math:pulradku
    math:-line math:-halflne NAME
  zarovnani = inherits: \nastavzarovnani
  tolerance = inherits: \nastavtoleranci
  strut = ano ne
  zaveseni = radek široky prizpusobive zadny NUMMER
  marginalie = DIMENSION
  odsadpristi = ano ne auto
  alternativa = text odstavec normalni marginalie naokraji vrsek nastred spodek reverse marginalnitext
    NAME
  sirka = DIMENSION
  numberwidth = DIMENSION
  sirkatextu = DIMENSION
  vzdalenost = DIMENSION
  textdistance = DIMENSION
  predchoziprikaz = BEFEHL
  prikazpo = BEFEHL
  prikaz = \...#1#2
  textovyprikaz = \...#1
  deeptextcommand = \...#1
  ciselnyprikaz = \...#1
  deepnumbercommand = \...#1
  misto = NAME
  kriterium = striktni pozitiv vse
  hidenumber = ano ne
  extradata = BEFEHL
  snapping = ano normalni 0 1 2 0:10 1:10 2:10 2:20 1:top 1:bottom 2:top 2:bottom

```

```

\nastavnadpisy [...] 1 [...] 2 [...]
1 ABSCHNITT OPT
2 inherits: \nastavnadpis

```

\nastavodkazovani [...¹,...²,...]

```
* status = start stop
  expanzen = ano ne xml
  autofile = ano ne
  export = ano ne
  vlevo = BEFEHL
  vpravo = BEFEHL
  sirka = DIMENSION
  oboustranne = ano ne
  interakce = popis text symbol vse
  oddelovac = BEFEHL
  prefix = + - TEXT
  labelalternative = nalevyokraj napravokraj inoutermargin ininnermargin nalevo napravo inouteredge ininneredge
                    atleftmargin atrightmargin ivlevo ivpravo inouter ininner naokraji inother marginalnitext NAME
  labelstyle = STYLE BEFEHL
  labelcolor = COLOR
```

\nastavodsazovani [...¹,...²,...]

```
* [-+]male [-+]stredni [-+]velike zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION
  NAME
```

\nastavodstavce [...¹] [...²,...³,...]

```
1 NAME OPT OPT
2 kazdy NUMMER
3 n = NUMMER
  pred = BEFEHL
  po = BEFEHL
  sirka = DIMENSION
  vzdalenost = DIMENSION
  vyska = DIMENSION prizpusobive
  vrsek = BEFEHL
  spodek = BEFEHL
  zarovnnani = inherits: \nastavzarovnnani
  vnitrni = BEFEHL
  prikaz = BEFEHL
  linka = zap vyp
  tloustkalinky = DIMENSION
  barvalinky = COLOR
  pismeno = STYLE BEFEHL
  barva = COLOR
  smer = normalni reverse
```

\nastavodstavce [...¹] [...²,...³,...]

```
1 NAME NAME:NUMMER OPT
2 n = NUMMER
  pred = BEFEHL
  po = BEFEHL
  sirka = DIMENSION
  vzdalenost = DIMENSION
  vyska = DIMENSION prizpusobive
  vrsek = BEFEHL
  spodek = BEFEHL
  zarovnnani = inherits: \nastavzarovnnani
  vnitrni = BEFEHL
  prikaz = BEFEHL
  linka = zap vyp
  tloustkalinky = DIMENSION
  barvalinky = COLOR
  pismeno = STYLE BEFEHL
  barva = COLOR
```

\nastavopis [...,¹...] [...,²...,...]

```

1  NAME                      OPT
2  lichyokraj                = DIMENSION
   sudamarginalie            = DIMENSION
   marginalie                 = ano ne standardni DIMENSION
   volba                      = mp lua xml parsed-xml nested tex context zadny NAME
   pismo                      = STYLE BEFEHL
   barva                      = COLOR
   zarovnani                  = inherits: \nastavzarovnani
   radky                      = ano ne normalni hyphenated
   mezera                     = zap vyp normalni fixne natahnout
   keeptogether               = ano ne odstavec
   pred                      = BEFEHL
   po                        = BEFEHL
   strip                      = ano ne NUMMER
   range                      = NUMMER NAME
   tab                       = ano ne NUMMER
   odstavec                  = ano ne
   escape                    = ano TEXT PROCESSOR->TEXT
   odsadpristi               = ano ne auto
   pokračovat                = ano ne
   start                     = NUMMER
   stop                      = NUMMER
   krok                      = NUMMER
   cislovani                 = soubor radek ne
   prazdny                   = inherits: \preskoc
   zakladnifont              = inherits: \nastavzakladnifont

```

\nastavoramovanetexty [...,¹...] [...,²...,...]

```

1  NAME                      OPT
2  inherits: \setupframedtext

```

```

\nastavoramovani  [...,1...]  [...,2...,...]
1  NAME              OPT
2  roh                = pravouhly zaobleny NUMMER 1 r b t lr rl tb bt rt tr rb br bl lb tl lt trb rtl tlb blt ltr rtl
                        lbr rbl ltrb trbl rblt bltr
    rohramecku        = pravouhly zaobleny NUMMER 1 r b t lr rl tb bt rt tr rb br bl lb tl lt trb rtl tlb blt ltr rtl
                        lbr rbl ltrb trbl rblt bltr
    rohpozadi         = pravouhly zaobleny NUMMER 1 r b t lr rl tb bt rt tr rb br bl lb tl lt trb rtl tlb blt ltr rtl
                        lbr rbl ltrb trbl rblt bltr
    polomer           = DIMENSION
    polomerramecku    = DIMENSION
    polomerpozadi     = DIMENSION
    hloubka           = DIMENSION
    hloubkaramecku    = DIMENSION
    hloubkapozadi     = DIMENSION
    barvaramecku      = COLOR
    rameceknahore     = zap vyp male pomlcka NAME
    ramecekdole       = zap vyp male pomlcka NAME
    ramecekvlevo      = zap vyp male pomlcka NAME
    ramecekvpravo     = zap vyp male pomlcka NAME
    region            = ano ne
    tloustkalinky     = DIMENSION
    offsetramecku     = DIMENSION
    ramecek           = zap vyp prekryv male pomlcka closed zadny
    pozadi            = popredi barevne NAME
    offsetpozadi      = ramecek DIMENSION
    barvapozadi       = COLOR
    component         = NAME
    extras            = BEFEHL
    foregroundstyle    = STYLE BEFEHL
    foregroundcolor    = COLOR
    setups            = NAME
    offset            = implicitni prekryv zadny DIMENSION
    sirka             = lokalne prizpusobive max široky fixne DIMENSION
    vyska             = prizpusobive max široky DIMENSION
    minvyska          = DIMENSION
    zarovnani         = inherits: \nastavzarovnani
    strut            = ano ne zadny lokalne globalne
    autostrut         = ano ne
    misto             = vyska podlehloubky vysoko nizko vrsek nastred spodek radek nivy visici drzet rovnice matematika
                        normalni inline
    autosirka         = ano ne sila
    radky             = NUMMER
    vrsek             = BEFEHL
    spodek            = BEFEHL
    prazdny           = ano ne
    profile           = NAME
    prazdne           = ano ne
    loffset           = DIMENSION
    roffset           = DIMENSION
    toffset           = DIMENSION
    boffset           = DIMENSION
    orientation       = NUMMER
    anchoring         = normalni up down vlevo vpravo vrsek spodek NAME
    xanchor           = DIMENSION
    yanchor           = DIMENSION
    linedirection     = normalni reverse
    dashstep          = DIMENSION
    synchronize       = ano ne text pozadi
    adaptive          = ano delay NUMMER
    freezespacing     = NUMMER

```

```

\nastavorez  [...,*...,...]

```

```

*  status            = start stop
    sirka            = DIMENSION
    vyska            = DIMENSION
    hoffset          = DIMENSION
    voffset          = DIMENSION
    x                = NUMMER
    y                = NUMMER
    nx               = NUMMER
    ny               = NUMMER
    sx               = NUMMER
    sy               = NUMMER
    levyoffset       = DIMENSION
    pravyoffset       = DIMENSION
    offsetvrsku      = DIMENSION
    offsetspodku     = DIMENSION
    mp               = NAME
    n                = NUMMER
    offset           = DIMENSION

```

\nastavotoceni [...,*...]

* misto = prizpusobive siroky podlehloubky vysoko nastred implicitni normalni
rotace = vlevo vpravo uvnitr vnejsi NUMMER
inherits: \nastavoramovani

\nastavpaletu [...]

* NAME

\nastavplvouciobjekt [...,¹...] [...,²...]

1 SINGULAR OPT
2 odsadpristi = ano ne auto
implicitni = inherits: \placefloat
fallback = inherits: \placefloat
vnitrni = BEFEHL
kriterium = DIMENSION
metoda = NUMBER
sidemethod = NUMBER
textmethod = NUMBER
sidealign = vyska podlehloubky radek pulradku mrizka normalni
mrizka = inherits: \snaptogrid
lokalne = ano ne
prikaz = \...#1
availablewidth = DIMENSION
availableheight = DIMENSION
minsirka = DIMENSION
maxsirka = DIMENSION
misto = vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin
inneredge outeredge zpetnamezera cutspace levyokraj pravyokraj levahrana pravahrana
vzdalenostlevehookraje = DIMENSION
vzdalenostpravehookraje = DIMENSION
levyokraj = DIMENSION
pravyokraj = DIMENSION
innermargin = DIMENSION
outermargin = DIMENSION
bottombefore = BEFEHL
bottomafter = BEFEHL
expanzen = ano ne xml
referenceprefix = + - TEXT
xmlsetup = NAME
catcodes = NAME
freeregion = ano ne
vzdalenostvrsku = DIMENSION NUMBER
vzdalenostspodku = DIMENSION NUMBER
mezerapred = zadny inherits: \preskoc
mezeraza = zadny inherits: \preskoc
sirka = DIMENSION
vyska = DIMENSION
offset = DIMENSION zadny prekryv
bocnimezerapred = zadny inherits: \preskoc
bocnimezeraza = zadny inherits: \preskoc
spacebeforeside = zadny inherits: \preskoc
spaceafterside = zadny inherits: \preskoc
sidethreshold = old dimension
marginalie = DIMENSION
nvrsek = NUMBER
nspodek = NUMBER
krok = male stredni velke radek podlehloubky
nradky = NUMBER
cache = ano ne
compress = ano ne
compressdistance = DIMENSION
inherits: \nastavoramovani

\nastavplvouciobjekty [...,¹...] [...,²...]

1 SINGULAR OPT
2 inherits: \nastavplvouciobjekt

\nastavpodcislostrany [...,*...]

* inherits: \setupcounter

`\nastavpole` [¹...] [²...,...] [³...,...³...,...] [⁴...,...⁴...,...] [⁵...,...⁵...,...]

1 NAME OPT OPT OPT OPT

2 reset popiscek ramecek horizontalne vertikalne

3 inherits: \setupfieldtotalframed

4 inherits: \setupfieldlabelframed

5 inherits: \setupfieldcontentframed

`\nastavpolozky` [¹...,...] [²...,...²...,...]

1 NAME OPT

2 alternativa = vlevo vpravo vrsek spodek naokraj

sirkatextu = DIMENSION

sirka = DIMENSION

vzdalenost = DIMENSION

symbol = zadny NAME

zarovnani = vlevo nastred vpravo flushleft flushright uvnitr vnejsi marginalie

textalign = vlevo nastred vpravo flushleft flushright uvnitr vnejsi

n = NUMMER

pred = BEFEHL

po = BEFEHL

mezi = BEFEHL

`\nastavpopisek` [¹...,...] [²...,...²...,...]

1 NAME OPT

2 suffix = BEFEHL

suffixseparator = BEFEHL

suffixstopper = BEFEHL

misto = vlevo vpravo nastred nizko vysoko mrizka radky prekryv uvnitr vnejsi innermargin outermargin
levyokraj pravyyokraj lefthanging righthanging zaveseni vrsek spodek natahnout tolerantni
velmitolerantni zadny implicitni

prikaz = \...#1

ciselnyprikaz = \...#1

textovyprikaz = \...#1

mezerapred = inherits: \preskoc

spaceinbetween = inherits: \preskoc

mezeraza = inherits: \preskoc

vzdalenost = DIMENSION

stylhlavicky = STYLE BEFEHL

barvahlavicky = COLOR

headseparator = TEXT

mezi = BEFEHL

pismeno = STYLE BEFEHL

barva = COLOR

offsetvrsku = DIMENSION

offsetspodku = DIMENSION

cislo = ano ne zadny

group = TEXT

levyokraj = DIMENSION

pravyokraj = DIMENSION

innermargin = DIMENSION

outermargin = DIMENSION

zarovnani = inherits: \nastavzarovnani

sirka = prizpusobive max DIMENSION

minsirka = prizpusobive DIMENSION

maxsirka = DIMENSION

zaveseni = ano ne

mode = NAME

inherits: \setupcounterinherits: \nastavoramovani

`\nastavpopisky` [¹...,...] [²...,...²...,...]

1 NAME OPT

2 inherits: \nastavpopisek

`\nastavpopisy` [¹...,...] [²...,...²...,...]

1 NAME OPT

2 inherits: \setupdescription

```

\nastavpozadi [...] [...]
1 NAME OPT
2 status = start stop
  levyoffset = DIMENSION
  pravyoffset = DIMENSION
  offsetvrsku = DIMENSION
  offsetspodku = DIMENSION
  pred = BEFEHL
  po = BEFEHL
  inherits: \nastavoramovani

```

```

\nastavpozadi [...] [...]
1 papir stranka levastranka pravastranka text skryte
2 status = start stop opakovat
  offset = DIMENSION
  hloubka = DIMENSION
  inherits: \nastavoramovani

```

```

\nastavpoznampakypodcarou [...]
* inherits: \setupnote

```

```

\nastavprechodstrany [...]
* reset auto start nahodny NUMBER

```

```

\nastavpreskok [...]
* inherits: \preskok OPT

```

```

\nastavprogramy [...]
* pismeno = STYLE BEFEHL
  barva = COLOR

```

```

\nastavprostredizakladnihofontu [...] [...] [...]
1 NAME OPT
2 implicitni DIMENSION
3 inherits: \definujprostredizakladnihofontu

```

```

\nastavradkovani [...]
* fixne zhustene siroky fixed:small broad:small

```

```

\nastavradky [...] [...]
1 NAME OPT
2 volba = zhustene
  pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  odsazovani = inherits: \nastavodsazovani
  zarovnani = inherits: \nastavzarovnani
  mezera = ano zap vyp fixne implicitni
  prikaz = BEFEHL
  pismeno = STYLE BEFEHL
  barva = COLOR
  vlevo = BEFEHL
  vpravo = BEFEHL
  indentlist = DIMENSION *
  keptogether = odstavec

```

```

\nastavrejstrik  [1...]  [2...,...,...]
1  NAME NAME:NUMMER      OPT
2  referencemethod      = vpred
   expanzen             = ano ne xml
   vlastnicislo         = ano ne
   xmlsetup             = NAME
   alternativa          = a b A B
   metoda               = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress              = ano ne vse zhustene text
   check                = ano ne
   kriterium            = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse aktualni
   pageprefixconnector  = BEFEHL
   pageprefix           = ano ne
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
   maxsirka             = DIMENSION
   indikator            = ano ne
   pred                 = BEFEHL
   po                   = BEFEHL
   prikaz               = \...#1
   textovyprikaz        = \...#1
   deeptextcommand      = \...#1
   strankovyprikaz      = \...#1
   vzdalenost           = DIMENSION
   interakce            = text cislostranky
   cislostranky         = ano ne
   symbol               = a n zadny 1 2 BEFEHL
   language             = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismo                = STYLE BEFEHL
   barva                = COLOR
   styltextu            = STYLE BEFEHL
   barvatextu           = COLOR
   stylstranky          = STYLE BEFEHL
   barvastranky         = COLOR
   pageleft             = BEFEHL
   pageright            = BEFEHL
   n                    = NUMMER
   rovnovaha            = ano ne
   zarovnnani           = inherits: \nastavzarovnnani
   numberorder          = ciska
   pagemethod           = stranka sekce

```

\nastavrejstrik	[... ¹ ,...]	[... ² ,...]	[... ³ ,...]
	OPT	OPT	
1 NAME			
2 NUMMER			
3 referencemethod	= vpred		
expanzen	= ano ne xml		
vlastnicislo	= ano ne		
xmlsetup	= NAME		
alternativa	= a b A B		
metoda	= implicitni pred po prvni posledni ch mm zm pm mc zc pc uc		
compress	= ano ne vse zhustene text		
check	= ano ne		
kriterium	= lokalne text aktualni predchozi vse ABSCHNITT		
pageprefixseparatorset	= BEFEHL		
pageprefixconversionset	= NAME		
pageprefixstarter	= BEFEHL PROCESSOR->BEFEHL		
pageprefixstopper	= BEFEHL PROCESSOR->BEFEHL		
pageprefixset	= NAME		
pageprefixsegments	= NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse aktualni		
pageprefixconnector	= BEFEHL		
pageprefix	= ano ne		
pageseparatorset	= NAME		
pageconversionset	= NAME		
pagestarter	= BEFEHL PROCESSOR->BEFEHL		
pagestopper	= BEFEHL PROCESSOR->BEFEHL		
pagesegments	= NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse		
maxsirka	= DIMENSION		
indikator	= ano ne		
pred	= BEFEHL		
po	= BEFEHL		
prikaz	= \...#1		
textovyprikaz	= \...#1		
deeptextcommand	= \...#1		
strankovyprikaz	= \...#1		
vzdalenost	= DIMENSION		
interakce	= text cislostranky		
cislostranky	= ano ne		
symbol	= a n zadny 1 2 BEFEHL		
language	= implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE		
pismeno	= STYLE BEFEHL		
barva	= COLOR		
styltextu	= STYLE BEFEHL		
barvatextu	= COLOR		
stylstranky	= STYLE BEFEHL		
barvastranky	= COLOR		
pageleft	= BEFEHL		
pageright	= BEFEHL		
n	= NUMMER		
rovnovaha	= ano ne		
zarovnani	= inherits: \nastavzarovnani		
numberorder	= cisla		
pagemethod	= stranka sekce		

```

\nastaveniREGISTER [...,1...] [...,2...,...]
1  NUMMER OPT
2  referencemethod = vpred
    expanzen = ano ne xml
    vlastnicislo = ano ne
    xmlsetup = NAME
    alternativa = a b A B
    metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
    compress = ano ne vse zhustene text
    check = ano ne
    kriterium = lokalne text aktualni predchozi vse ABSCHNITT
    pageprefixseparatorset = BEFEHL
    pageprefixconversionset = NAME
    pageprefixstarter = BEFEHL PROCESSOR->BEFEHL
    pageprefixstopper = BEFEHL PROCESSOR->BEFEHL
    pageprefixset = NAME
    pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse aktualni
    pageprefixconnector = BEFEHL
    pageprefix = ano ne
    pageseparatorset = NAME
    pageconversionset = NAME
    pagestarter = BEFEHL PROCESSOR->BEFEHL
    pagestopper = BEFEHL PROCESSOR->BEFEHL
    pagesegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
    maxsirka = DIMENSION
    indikator = ano ne
    pred = BEFEHL
    po = BEFEHL
    prikaz = \...#1
    textovyprikaz = \...#1
    deeptextcommand = \...#1
    strankovyprikaz = \...#1
    vzdalenost = DIMENSION
    interakce = text cislostranky
    cislostranky = ano ne
    symbol = a n zadny 1 2 BEFEHL
    language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
    pismo = STYLE BEFEHL
    barva = COLOR
    styltextu = STYLE BEFEHL
    barvatextu = COLOR
    stylstranky = STYLE BEFEHL
    barvastranky = COLOR
    pageleft = BEFEHL
    pageright = BEFEHL
    n = NUMMER
    rovnovaha = ano ne
    zarovnani = inherits: \nastavzarovnani
    numberorder = cisla
    pagemethod = stranka sekce
instances: index

```

```

\nastaveniindex    [...,1...]    [...,2...,...]
1  NUMMER          OPT
2  referencemethod = vpred
   expanzen        = ano ne xml
   vlastnicislo    = ano ne
   xmlsetup        = NAME
   alternativa     = a b A B
   metoda         = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress        = ano ne vse zhustene text
   check          = ano ne
   kriterium       = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper = BEFEHL PROCESSOR->BEFEHL
   pageprefixset   = NAME
   pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                     ABSCHNITT:vse aktualni
   pageprefixconnector = BEFEHL
   pageprefix      = ano ne
   pageseparatorset = NAME
   pageconversionset = NAME
   pagestarter     = BEFEHL PROCESSOR->BEFEHL
   pagestopper     = BEFEHL PROCESSOR->BEFEHL
   pagesegments    = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
   maxsirka        = DIMENSION
   indikator       = ano ne
   pred            = BEFEHL
   po              = BEFEHL
   prikaz          = \...#1
   textovyprikaz   = \...#1
   deeptextcommand = \...#1
   strankovyprikaz = \...#1
   vzdalenost      = DIMENSION
   interakce       = text cislostranky
   cislostranky    = ano ne
   symbol          = a n zadny 1 2 BEFEHL
   language        = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismo          = STYLE BEFEHL
   barva           = COLOR
   styltextu       = STYLE BEFEHL
   barvatextu      = COLOR
   stylstranky     = STYLE BEFEHL
   barvastranky    = COLOR
   pageleft        = BEFEHL
   pageright       = BEFEHL
   n               = NUMMER
   rovnovaha       = ano ne
   zarovnani       = inherits: \nastavzarovnani
   numberorder     = cisla
   pagemethod      = stranka sekce

```

```

\nastavrovnice    [...,1...]    [...,2...,...]
1  NAME          OPT
2  misto          = vlevo vpravo atleftmargin atrightmargin uvnitr vnejsi
   zarovnani      = vlevo nastred vpravo flushleft flushright sklonene
   split          = ano ne radek NAME
   strut          = ano ne
   numberstrut    = ano ne vzdy
   vlevo          = BEFEHL
   vpravo         = BEFEHL
   mezerapred     = zadny inherits: \preskoc
   mezeraza       = zadny inherits: \preskoc
   spaceinbetween = inherits: \nastavbilamista
   ciselnyprkaz   = \...#1
   stylcisla      = STYLE BEFEHL
   barvacisla     = COLOR
   volba          = zhustene tight nastred podlehloubky radek pulradku -radek -pulradku ramecek male
                   DIMENSION
   marginalie     = ano ne standardni DIMENSION
   levyokraj      = ano ne standardni DIMENSION
   pravyokraj     = ano ne standardni DIMENSION
   vzdalenostokraje = cislo DIMENSION
   vzdalenostlevehookraje = cislo DIMENSION
   rightmargidistance = cislo DIMENSION
   alternativa    = implicitni single multi NAME
   odsadpristi    = ano ne auto
   mrizka         = inherits: \snaptogrid
   referenceprefix = + - TEXT
   numberthreshold = DIMENSION
   order          = reverse
   numberlocation = prekryv
   numbermethod   = down
   textmargin     = DIMENSION
   penalties      = NAME
   meziradkovamezera = DIMENSION
   textdistance   = DIMENSION
   splitmethod    = prvni posledni obe
   setups         = NAME
   snap           = ano ne
   snapstep       = reset male stredni velke radek
   zakladnifont   = inherits: \nastavzakladnifont
   pismeno        = STYLE BEFEHL
   barva          = COLOR
   functionstyle   = STYLE BEFEHL
   functioncolor   = COLOR
   sirka          = DIMENSION
   numberdistance  = DIMENSION
   numberstate     = auto
   mathematics    = NAME
   gridcorrection = inherits: \setgridcorrection
   inherits: \setupcounter

```

```

\nastavsadusymbolu [...]
*  NAME

```

```

\nastavseznam      [...,1...]      [...,2...,...]
1  LISTE
2  status           = start stop
   misto            = zadny zde
   typ              = simple prikaz userdata
   kriterium        = lokalne uvod odkaz SECTIONBLOCK:odkaz vse SECTIONBLOCK:vse text SECTIONBLOCK:text
                     aktualni SECTIONBLOCK:aktualni zde predchozi SECTIONBLOCK:predchozi komponenta ABSCHNITT
                     SECTIONBLOCK:ABSCHNITT
   seznam           = NAME
   sirka            = prizpusobive siroky DIMENSION
   vyska            = prizpusobive siroky DIMENSION
   hloubka          = prizpusobive siroky DIMENSION
   symbol           = jedna dve tri zadny implicitni
   popisek          = ano ne zadny NAME
   starter          = BEFEHL
   predel           = BEFEHL
   prikaz           = \...#1#2#3
   ciselnyprikaz    = \...#1
   textovyprikaz    = \...#1
   strankovyprikaz  = \...#1
   cislostranky     = ano ne vzdy realpage
   cislonadpisu     = ano ne vzdy
   pred            = BEFEHL
   po              = BEFEHL
   mezi            = BEFEHL
   marginalie       = zadny DIMENSION
   levyokraj        = DIMENSION
   pravyokraj       = DIMENSION
   vzdalenost       = zadny DIMENSION
   zarovnejtitul    = ano ne
   numberalign      = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   zarovnani        = inherits: \nastavzarovnani
   zaveseni         = ano ne
   vlevo            = BEFEHL
   vpravo           = BEFEHL
   interakce        = ano ne vse cislo text titul stranka cislooddilu cislostranky
   limittext        = ano ne TEXT
   pismeno          = STYLE BEFEHL
   barva            = COLOR
   stylcisla        = STYLE BEFEHL
   barvacisla       = COLOR
   styltextu        = STYLE BEFEHL
   barvatextu       = COLOR
   stylstranky      = STYLE BEFEHL
   barvastranky     = COLOR
   odkaz            = NUMMER
   extras           = NAME
   order            = prikaz vse titul
   urovne           = NUMMER
   alternativa      = a b c d e f g vlevo vpravo vrsek spodek prikaz zadny interactive odstavec horizontalne
                     vertikalne NAME
   maxsirka         = DIMENSION
   pageprefix       = ano ne
   pageprefixseparatorset = NAME
   pageprefixconversionset = NAME
   pageprefixset    = NAME
   pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                     ABSCHNITT:vse aktualni
   pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
   pageconversionset = NAME
   pagestarter      = BEFEHL PROCESSOR->BEFEHL
   pagestopper      = BEFEHL PROCESSOR->BEFEHL
   inherits: \setupcounterinherits: \nastavoramovani

```

```

\nastavsirkucary  [...]
*   male stredni velke DIMENSION

```

```

\nastavsloupce    [...,*...,...]
*   inherits: \setupmixedcolumns

```


\nastavspodek [¹...] [²...,...]

```

1 text marginalie hrařã
2 status      = start stop prazdne vysoko zadny normalni zadneznamení NAME
pismeno      = STYLE BEFEHL
barva        = COLOR
strut        = ano ne
n            = NUMMER
pred         = BEFEHL
po           = BEFEHL
textvlevo    = TEXT
strednitext  = TEXT
textvpravo   = TEXT
stylvlevo    = STYLE BEFEHL
middlestyle  = STYLE BEFEHL
stylvpravo   = STYLE BEFEHL
barvavlevo   = COLOR
middlecolor  = COLOR
barvavpravo  = COLOR
sirka        = DIMENSION
sirkavlevo   = DIMENSION
middlewidth  = DIMENSION
sirkavpravo  = DIMENSION

```

\nastavsynonyma [¹...,...]^{OPT} [²...,...]

```

1 SINGULAR
2 expanzen    = ano ne xml
alternativa  = prvni posledni normalni NAME
dalsi        = BEFEHL
prikaz       = \...#1#2#3
textovyprikaz = \...#1
synonymcommand = \...#1
language     = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scñ SPRACHE
metoda       = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
kriterium    = aktualni predchozi lokalne text vse ABSCHNITT
pismeno      = STYLE BEFEHL
barva        = COLOR
styltextu    = STYLE BEFEHL
barvatextu   = COLOR
stylsynonyma = STYLE BEFEHL
barvasynonyma = COLOR
vlevo        = BEFEHL
vpravo       = BEFEHL
pred         = BEFEHL
po           = BEFEHL
mezi         = BEFEHL
hyphens      = ano ne
prikaz       = \...#1#2#3

```

\nastavsystem [...,...*=...,...]

* n = NUMMER

```

\nastavtabelaci    [ 1... ]    [ 2... ]    [ 3...,...,... ]
1  NAME              OPT          OPT
2  NAME
3  formatovat        =  TEMPLATE zadny
   pred              =  BEFEHL
   po                 =  BEFEHL
   vzdalenost         =  male stredni velke zadny prazdny podlehloubky mrizka DIMENSION
   prazdny            =  nastaveni stejnastranka max sila enable zablockovat zadnabila zhustene zpet prekryv vzdy drzet
                        weak strong implicitni pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku
                        halflinebefore halflineafter quarterline rovnice bily vyska podlehloubky standardni NUMMER*male
                        NUMMER*stredni NUMMER*velke NUMMER*radek NUMMER*pulradku NUMMER*quarterline NUMMER*rovnice
                        NUMMER*bily NUMMER*vyska NUMMER*podlehloubky category:NUMMER order:NUMMER penalty:NUMMER
                        DIMENSION NAME
   stylhlavicky       =  STYLE BEFEHL
   barvahlavicky      =  COLOR
   pozadi             =  NAME
   barvapozi          =  COLOR
   foregroundstyle     =  STYLE BEFEHL
   foregroundcolor     =  COLOR
   zarovnani          =  vlevo nastred vpravo dimension
   linka              =  radek normalni
   barvalinky         =  COLOR
   tloustkalinky      =  DIMENSION
   zakladnifont        =  inherits: \nastavzakladnifont
   odsazovani         =  ano ne
   split              =  ano ne opakovat auto
   jednotka           =  DIMENSION
   marginalie          =  DIMENSION
   vnitri             =  BEFEHL
   EQ                 =  BEFEHL
   zahlavi            =  ano opakovat text
   ramecek            =  zap vyp
   titul              =  TEXT
   keptogether         =  ano ne
   dashstep           =  DIMENSION

```

```

\nastavtabulky    [ *...,...,... ]
*  sirkatextu        =  DIMENSION max
   split              =  ano ne opakovat auto
   ramecek            =  zap vyp
   NL                 =  inherits: \preskoc
   VL                 =  male stredni velke zadny NUMMER
   HL                 =  male stredni velke zadny NUMMER
   vzdalenost         =  male stredni velke zadny
   zarovnani          =  vlevo nastred vpravo
   prikazy            =  BEFEHL
   zakladnifont        =  inherits: \nastavzakladnifont
   tloustkalinky      =  DIMENSION
   vyska              =  strut NUMMER
   hloubka            =  strut NUMMER
   openup             =  DIMENSION

```

```

\nastavtenkelinky [ *...,...,... ]
*  vyska              =  max DIMENSION
   hloubka            =  max DIMENSION
   pozadi             =  barevne
   ramecek            =  zap vyp
   tloustkalinky      =  DIMENSION
   alternativa        =  a b c zadny
   barvapozi          =  COLOR
   barva              =  COLOR
   meziradkovamezera  =  male stredni velke NUMMER
   pred              =  BEFEHL
   po                 =  BEFEHL
   mezi               =  BEFEHL
   n                  =  NUMMER
   zap                =  DIMENSION
   vyp                =  DIMENSION

```

```

\nastavtext      [...]1    [...,...2...,...]
1  text marginalie OPT HTana
2  status          = start stop prazdne vysoko zadny normalni zadneznaceni NAME
    pismeno        = STYLE BEFEHL
    barva          = COLOR
    strut          = ano ne
    n              = NUMMER
    pred           = BEFEHL
    po             = BEFEHL
    textvlevo      = TEXT
    strednitext    = TEXT
    textvpravo     = TEXT
    stylvlevo      = STYLE BEFEHL
    middlestyle    = STYLE BEFEHL
    stylvpravo     = STYLE BEFEHL
    barvavlevo     = COLOR
    middlecolor    = COLOR
    barvavpravo    = COLOR
    sirka          = DIMENSION
    sirkavlevo     = DIMENSION
    middlewidth    = DIMENSION
    sirkavpravo    = DIMENSION

```

```

\nastavtextovelinky [...,...2...,...]
*  pred           = BEFEHL
    po            = BEFEHL
    mezi          = BEFEHL
    tloustkalinky = DIMENSION
    misto         = vlevo naokraji
    pismeno       = STYLE BEFEHL
    barva         = COLOR
    barvalinky    = COLOR
    sirka         = DIMENSION
    vyska         = DIMENSION
    vzdalenost    = DIMENSION
    korekcehloubky = zap vyp
    zakladnifont  = inherits: \nastavzakladnifont
    zap           = DIMENSION
    vyp           = DIMENSION

```

```

\nastaveniLABELtext [...]1    [...,...2...,...]
1  SPRACHE OPT
2  KEY = VALUE
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

```

```

\nastavenibtxlabeltext [...]1    [...,...2...,...]
1  SPRACHE OPT
2  KEY = VALUE

```

```

\nastaveniheadtext [...]1    [...,...2...,...]
1  SPRACHE OPT
2  KEY = VALUE

```

```

\nastavenilabeltext [...]1    [...,...2...,...]
1  SPRACHE OPT
2  KEY = VALUE

```

```

\nastavenimathlabeltext [...]1    [...,...2...,...]
1  SPRACHE OPT
2  KEY = VALUE

```

```

\nastavenioperatortext [...]1    [...,...2...,...]
1  SPRACHE OPT
2  KEY = VALUE

```

```

\nastaveniprefixtext [...]1    [...,...2...,...]
1  SPRACHE OPT
2  KEY = VALUE

```


\nastavumisteniprotejsku [...,*...]

* status = start stop
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL

\nastavumistovani [...,¹...] [...,*²...]

1 NAME OPT
2 offset = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
status = start prekryv
xoffset = DIMENSION
yoffset = DIMENSION
xkrok = absolutni relativni
ykrok = absolutni relativni
xmeritko = NUMMER
ymeritko = NUMMER
xfaktor = NUMMER
yfaktor = NUMMER
faktor = NUMMER
meritko = NUMMER

\nastavupati [...¹...] [...,*²...]

1 text marginalie hr^oha
2 status = start stop prazdne vysoko zadny normalni zadneznamen NAME
pismo = STYLE BEFEHL
barva = COLOR
strut = ano ne
n = NUMMER
pred = BEFEHL
po = BEFEHL
textvlevo = TEXT
strednitext = TEXT
textvpravo = TEXT
stylvlevo = STYLE BEFEHL
middlestyle = STYLE BEFEHL
stylvpravo = STYLE BEFEHL
barvavlevo = COLOR
middlecolor = COLOR
barvavpravo = COLOR
sirka = DIMENSION
sirkavlevo = DIMENSION
middlewidth = DIMENSION
sirkavpravo = DIMENSION

\nastavupravu [...,¹...] [...,*²...]

1 NAME OPT
2 stranka = inherits: \strana
prikaz = BEFEHL
sirka = DIMENSION
vyska = DIMENSION
zarovnani = inherits: \nastavzarovnani
setups = NAME
vrsek = BEFEHL
spodek = BEFEHL
pred = BEFEHL
po = BEFEHL
misto = vrsek
odkaz = REFERENCE
pagestate = start stop
statuszahlavi = start stop vysoko prazdne zadny normalni
statusupati = start stop vysoko prazdne zadny normalni
statusvrsku = start stop vysoko prazdne zadny normalni
statusspodku = start stop vysoko prazdne zadny normalni
statustextu = start stop vysoko prazdne zadny normalni
oboustranne = ano ne prazdne
pismo = STYLE BEFEHL
barva = COLOR
popisek = TEXT

\nastavurl [...,*...]

* pismo = STYLE BEFEHL
barva = COLOR

\nastavusporadani [...,*,...]

* zablokovat zrcadleno dvoustranny negativ 90 180 270 reset pozadi normalni 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP 2UP
2DOWN 2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW
1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY FLASHCARD NAME

\nastavvelikostpapiru [¹...] [...,²...,...]

1 NAME OPT
2 vrsek = BEFEHL
spodek = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
metoda = normalni zadny NAME
meritko = NUMMER
nx = NUMMER
ny = NUMMER
dx = DIMENSION
dy = DIMENSION
sirka = DIMENSION
vyska = DIMENSION
svrchnimezera = DIMENSION
zpetnamezera = DIMENSION
offset = DIMENSION
stranka = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
papir = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
volba = prizpusobive max
vzdalenost = DIMENSION

\nastavvelikostpapiru [...,¹...] [...,²...,...]

1 reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
2 reset nasirku zrcadleno negativ otoceno 90 180 270 NAME

\nastavvsechnapole [...,¹...] [...,²...,...] [...,³...,...] [...,⁴...,...]

1 reset popiscek ramecek horizontalne vertikálne OPT
2 inherits: \setupfieldtotalframed
3 inherits: \setupfieldlabelframed
4 inherits: \setupfieldcontentframed

\nastavvycty [...,¹...] [...,²...,...]

1 NAME OPT
2 inherits: \setupenumeration

\nastavvyplnovelinky [...,^{*}...,...]

* pred = BEFEHL
po = BEFEHL
n = NUMMER
meziradkovamezera = male stredni velke NUMMER
vzdalenost = DIMENSION
sirka = prizpusobive siroky DIMENSION
oddelovac = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR

\nastavvyplnoveradky [...,^{*}...,...]

* pred = BEFEHL
po = BEFEHL
marginalie = DIMENSION
sirka = DIMENSION
vzdalenost = DIMENSION
tloustkalinky = DIMENSION
barva = COLOR

\nastavvystup [...*...]

* implicitni pdf lua json js mps zadny prazdne

```

\nastavvzhled  [..1.]  [.....2...,.]
1  NAME          OPT
2  status         = start stop normalni opakovat
   marginalie     = DIMENSION
   hrana          = DIMENSION
   vzdalenostokraje = DIMENSION
   vzdalenosthrany = DIMENSION
   vzdalenostlevehrawy = DIMENSION
   vzdalenostpravehrany = DIMENSION
   vzdalenostlevehookraje = DIMENSION
   vzdalenostpravehookraje = DIMENSION
   vzdalenostvrsku = DIMENSION
   vzdalenostzahlavi = DIMENSION
   vzdalenostupati = DIMENSION
   vzdalenostspodku = DIMENSION
   prednastaveni  = NAME
   levyokraj      = DIMENSION
   pravyokraj     = DIMENSION
   levahrana      = DIMENSION
   pravahrana     = DIMENSION
   zahlavi       = DIMENSION
   upati          = DIMENSION
   vrsek          = DIMENSION
   spodek         = DIMENSION
   zpetnamezera   = DIMENSION
   svrchnamezera  = DIMENSION
   setups         = NAME
   cutspace       = DIMENSION
   sirka          = DIMENSION nastred prizpusobive
   bottomspace    = DIMENSION
   radky          = NUMMER
   vyska          = DIMENSION nastred prizpusobive
   horoffset      = DIMENSION
   offsethlavicky = DIMENSION
   sloupce        = NUMMER
   vzdalenostsloupcu = DIMENSION
   metoda         = implicitni normalni NAME
   misto          = vlevo nastred vpravo vrsek spodek jednostranne dvoustranny
   sirkatextu     = DIMENSION
   vyskatextu     = DIMENSION
   nx             = NUMMER
   ny             = NUMMER
   dx             = DIMENSION
   dy             = DIMENSION
   meritko        = NUMMER
   sx             = NUMMER
   sy             = NUMMER
   znaceni        = zap vyp stranka prazdne barevne jedna dve ctyri
   mrizka         = ano ne snapping vyp
   textdistance   = DIMENSION
   alternativa    = implicitni normalni zlom NAME
   clipoffset     = DIMENSION
   cropoffset     = DIMENSION auto
   trimoffset     = DIMENSION
   bleedoffset    = DIMENSION
   artoffset      = DIMENSION
   smer           = normalni reverse
   limitstretch   = ano auto DIMENSION
   vz             = ano NUMMER
   adaptive       = DIMENSION
   rows           = NUMMER
   rowdistance    = DIMENSION
   snapping       = ano normalni 0 1 2 0:10 1:10 2:10 2:20 1:top 1:bottom 2:top 2:bottom

```

```

\nastavvzhled  [..1.]
*  reset NAME

```

\nastavzhlavi [¹...] [²...,...]

```
1 text marginalie hranPT
2 status      = start stop prazdne vysoko zadny normalni zadneznamenani NAME
  pismeno     = STYLE BEFEHL
  barva       = COLOR
  strut       = ano ne
  n           = NUMMER
  pred        = BEFEHL
  po          = BEFEHL
  textvlevo   = TEXT
  strednitext = TEXT
  textvpravo  = TEXT
  stylvlevo   = STYLE BEFEHL
  middlestyle = STYLE BEFEHL
  stylvpravo  = STYLE BEFEHL
  barvavlevo  = COLOR
  middlecolor = COLOR
  barvavpravo = COLOR
  sirka       = DIMENSION
  sirkavlevo  = DIMENSION
  middlewidth = DIMENSION
  sirkavpravo = DIMENSION
```

\nastavzakladnifont [...,*,...]

* DIMENSION NAME globalne reset⁰⁸ rztet x xx male velke script scriptscript rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke

\nastavzarovnani [...,*,...]

* široky siroce squeeze spodek vyska podlehloubky radek vysoko nizko nivy flushright flushleft nastred ano ne sirka normalni reset uvnitr vnejsi flushinner flushouter vlevo vpravo center zablockovat posledni end odstavec lefttoright righttoleft l2r r2l tabulka lessshyphenation morehyphenation visici hangingboth nothanging hz fullhz nohz hyphenated nothyphenated collapsed notcollapsed explicit tolerantni velmitolerantni natahnout extremestretch finalni 1*final 2*final 3*final 4*final more 1*more 2*more hangleft hangright flushforward flushbackward vzdy profile prizpusobive noorphans keeporphans notwins keptwins notoddlers keptoddlers tight sklonene granular lesswidows lessclubs lessbroken lessorphans lessorphans:2 lessorphans:3 lessorphans:4 defaultwidows defaultclubs defaultbroken strictwidows strictwidows:2 strictwidows:3 strictwidows:4 strictclubs strictclubs:2 strictclubs:3 strictclubs:4 strictbroken defaultmath strictmath nonstrictmath implicitni snapping nosnapping snapping:yes snapping:normal snapping:0 snapping:1 snapping:2 snapping:0:10 snapping:1:10 snapping:2:10 snapping:2:20 snapping:1:top snapping:1:bottom snapping:2:top snapping:2:bottom

\nastavznaceni [...,¹...] [...,²...,...]

```
1 BESCHRIFTUNG
2 status      = start stop
  expanzen    = ano ne
  oddelovac   = BEFEHL
  filtercommand = \...#1
```

\nastavzuzeni [...,¹...] [...,²...,...]

```
1 NAME
2 vlevo      = DIMENSION
  stredni    = DIMENSION
  vpravo     = DIMENSION
  implicitni = [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset
  pred       = BEFEHL
  po         = BEFEHL
```

\nastrane [...*...]

* REFERENCE

\nastred ...*

* CHARACTER

\naturalhbox ...¹ {...²...}

```
1 TEXT
2 CONTENT
```

\naturalhpack ...¹ {...²...}

```
1 TEXT
2 CONTENT
```


$\backslash\text{naturaltpack}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvcenter}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvpack}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvtop}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalwd}$ $\overset{*}{\dots}$ * CSNAME NUMBER
$\backslash\text{negatecolorbox}$ $\overset{*}{\dots}$ * CSNAME NUMBER
$\backslash\text{negated}$ $\{\overset{*}{\dots}\}$ * TEXT
$\backslash\text{negemspace}$
$\backslash\text{negenspace}$
$\backslash\text{negthinspace}$
$\backslash\text{nejakyradek}$ $[\overset{*}{\dots}]$ * REFERENCE
$\backslash\text{nekde}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ $[\overset{3}{\dots}]$ 1 TEXT 2 TEXT 3 REFERENCE
$\backslash\text{newattribute}$ $\backslash\overset{*}{\dots}$ * CSNAME
$\backslash\text{newboundary}$ $\backslash\overset{*}{\dots}$ * CSNAME
$\backslash\text{newcatcodetable}$ $\backslash\overset{*}{\dots}$ * CSNAME
$\backslash\text{newcounter}$ $\backslash\overset{*}{\dots}$ * CSNAME
$\backslash\text{newevery}$ $\backslash\overset{1}{\dots}$ $\backslash\overset{2}{\dots}$ 1 CSNAME 2 CSNAME

<code>\newfrenchspacing</code>
<code>\newluatable \...</code> <code>* CSNAME</code>
<code>\newmode {...}</code> <code>* NAME</code>
<code>\newrepeatablerandom \... {...}</code> <code>1 CSNAME</code> <code>2 NUMMER</code>
<code>\newsignal \...</code> <code>* CSNAME</code>
<code>\newsystemmode {...}</code> <code>* NAME</code>
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...] [...]</code> <code>1 NAME OPT</code> <code>2 NUMMER</code>
<code>\nextcountervalue [...]</code> <code>* NAME</code>
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\dalsiPARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...] [...]</code> <code>1 NAME</code> <code>2 NUMMER</code>
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>

<code>\neznamo</code>
<code>\nivy [¹...] {²...} {³...}</code> 1 vlevo vprávo 2 CONTENT 3 CONTENT
<code>\nizky {...}</code> * CONTENT
<code>\LOW {...}</code> * CONTENT instances: unitslow
<code>\unitslow {...}</code> * CONTENT
<code>\nm {...}</code> * CONTENT
<code>\noapostrophes</code>
<code>\nobar {...}</code> * CONTENT
<code>\nobigmath</code>
<code>\nobreak</code>
<code>\nocasing {...}</code> * CONTENT
<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE
<code>\nodepthstrut</code>
<code>\nodetostring \¹... {²...}</code> 1 CSNAME 2 CONTENT
<code>\noexplicithyphens</code>
<code>\nofdetachedinsertions . . .</code> * NUMBER
<code>\noffigurepages</code>

<code>\noflines</code>
<code>\noflinesinbox ...</code> <code>* CSNAME NUMBER</code>
<code>\noflocalfloats</code>
<code>\nohbreak</code>
<code>\noheightstrut</code>
<code>\nohyphencollapsing</code>
<code>\nohyphens</code>
<code>\nocharacteralign</code>
<code>\noindentation</code>
<code>\noitaliccorrection</code>
<code>\noitem</code>
<code>\nokap {...}</code> <code>* TEXT</code>
<code>\nokerning</code>
<code>\noleftkerning</code>
<code>\noleftligaturing</code>
<code>\noligaturing</code>
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> <code>* CONTENT</code>
<code>\nonpenalizedspacing</code>
<code>\nonvalidassignment {...}</code> <code>* TEXT</code>
<code>\noorphans</code>
<code>\norightkerning</code>
<code>\norightligaturing</code>
<code>\normalboldface</code>

\normalframedwithsettings [...,.. ¹ ...,...] {...} 1 inherits: \nastavoramovani 2 CONTENT
\normalitalicface
\normalizebodyfontsize \... {...} 1 CSNAME 2 DIMENSION
\normalizedfontsize
\normalizefontdepth \... {...} {...} {...} 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
\normalizefontheight \... {...} {...} {...} 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
\normalizefontline \... {...} {...} {...} 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
\normalizefontwidth \... {...} {...} {...} 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
\normalizetextdepth {...} {...} {...} 1 FONT 2 DIMENSION 3 TEXT
\normalizetextheight {...} {...} {...} 1 FONT 2 DIMENSION 3 TEXT
\normalizetextline {...} {...} {...} 1 FONT 2 DIMENSION 3 TEXT
\normalizetextwidth {...} {...} {...} 1 FONT 2 DIMENSION 3 TEXT
\normalni
\normalslantedface
\normaltypeface

<code>\odkaz [...¹,...] {...²}</code> 1 REFERENCE 2 TEXT
<code>\odkaznastranu [...[*],...]</code> * REFERENCE
<code>\odkaznatekst [...¹,...] {...²}</code> 1 REFERENCE 2 TEXT
<code>\odkazujici (...¹,...) (...²,...) [...³]</code> 1 POSITION 2 POSITION 3 REFERENCE
<code>\offset [...¹,...] {...²}</code> 1 inherits: \setupoffset 2 CONTENT
<code>\offsetbox [...¹,...] \...² {...³}</code> 1 inherits: \setupoffsetbox 2 CSNAME 3 CONTENT
<code>\onedigitrounding {...[*]}</code> * NUMMER
<code>\opis [...¹,...] {...²}</code> 1 inherits: \nastavtype 2 CONTENT
<code>\opissoubor [...¹] [...²,...] {...³}</code> 1 NAME 2 inherits: \nastavtype 3 FILE
<code>\opis [...¹,...] <<...²>></code> 1 inherits: \nastavtype 2 ANGLES
<code>\OPIS [...¹,...] {...²}</code> 1 inherits: \nastavtype 2 CONTENT
<code>\OPIS [...¹,...] <<...²>></code> 1 inherits: \nastavtype 2 ANGLES
<code>\optimize [...[*]]</code> * +line -line flushleft flushright normalni NAME
<code>\optimize [...[*],...]</code> * inherits: \setuptoptimize
<code>\optionalword</code>
<code>\oramovani [...¹,...] {...²}</code> 1 inherits: \nastavtype 2 CONTENT

<pre> \FRAMED [...,\stackrel{1}{=}\dots] {...} 1 inherits: \nastavoptamovani 2 CONTENT instances: unframed fitfieldframed potracebitmap </pre>
<pre> \fitfieldframed [...,\stackrel{1}{=}\dots] {...} 1 inherits: \nastavoramovani OPT 2 CONTENT </pre>
<pre> \potracebitmap [...,\stackrel{1}{=}\dots] {...} 1 inherits: \nastavoramovani OPT 2 CONTENT </pre>
<pre> \unframed [...,\stackrel{1}{=}\dots] {...} 1 inherits: \nastavoroptamovani 2 CONTENT </pre>
<pre> \FRAMEDTEXT [...,\stackrel{1}{=}\dots] {...} 1 inherits: \setupframedtext 2 CONTENT instances: framedtext </pre>
<pre> \framedtext [...,\stackrel{1}{=}\dots] {...} 1 inherits: \setupframedtext 2 CONTENT </pre>
<pre> \ordinaldaynumber {...} * NUMMER </pre>
<pre> \ordinalstr {...} * TEXT </pre>
<pre> \oref [...] * REFERENCE </pre>
<pre> \orez [...,\stackrel{1}{=}\dots] {...} 1 inherits: \nastavptavorez 2 CONTENT </pre>
<pre> \ornamenttext [...,\stackrel{1}{=}\dots] [...,\stackrel{2}{=}\dots] {...} {...} 1 alternativa = a b inherits: \setupcollector 2 pismo = STYLE BEFEHL barva = COLOR inherits: \nastavoramovani 3 TEXT 4 CONTENT </pre>
<pre> \ornamenttext [...] {...} {...} 1 NAME 2 TEXT 3 CONTENT </pre>
<pre> \ornamenttext [...,\stackrel{1}{=}\dots] [...,\stackrel{2}{=}\dots] {...} {...} 1 alternativa = a b inherits: \setuplayer 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT </pre>
<pre> \ORNAMENT {...} {...} 1 TEXT 2 CONTENT </pre>

$\otocit$ [..., ¹ ...,...] {...} 1 inherits: \nastav ^{08T} toceni 2 CONTENT
\outputfilename
\outputstreambox [...] * NAME
\outputstreamcopy [...] * NAME
\outputstreamunvbox [...] * NAME
\outputstreamunvcopy [...] * NAME
\over [...] * REFERENCE
\overlayanchorbox {...} * NAME
\overlaybutton [...] * REFERENCE
\overlaybutton {...} * REFERENCE
\overlaycolor
\overlaydepth
\overlayfigure {...} * FILE
\overlayheight
\overlayimage {...} * FILE
\overlaylinecolor
\overlaylinewidth
\overlayoffset
\overlayrollbutton [... ¹] [... ²] 1 REFERENCE 2 REFERENCE
\overlaywidth
\overloaderror

$\backslash\text{overset}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT 2 TEXT
$\backslash\text{oznaceni}$ $(.^1.,.^2.,.^3.,.^4.)$ $[.^1.,.^2.,.^3.,.^4.]$ $\{.^1.,.^2.,.^3.,.^4.\}$ 1 POSITION 2 POSITION 3 inherits: \nastavoramovani 4 TEXT
$\backslash\text{PDFcolor}$ $\{.^1.,.^2.,.^3.,.^4.\}$ * NAME
$\backslash\text{PDFETEX}$
$\backslash\text{PDFhighlight}$ $[.^1.,.^2.,.^3.,.^4.]$ $\{.^1.,.^2.,.^3.,.^4.\}$ 1 NAME 2 TEXT 3 TEXT
$\backslash\text{PDFTEX}$
$\backslash\text{Periodic}$ $\{.^1.,.^2.,.^3.,.^4.\}$ * TEXT
$\backslash\text{PCTEX}$
$\backslash\text{PiCTeX}$
$\backslash\text{PointsToBigPoints}$ $\{.^1.,.^2.,.^3.,.^4.\}$ $\backslash.^1.,.^2.,.^3.,.^4..$ 1 DIMENSION 2 CSNAME
$\backslash\text{PointsToReal}$ $\{.^1.,.^2.,.^3.,.^4.\}$ $\backslash.^1.,.^2.,.^3.,.^4..$ 1 DIMENSION 2 CSNAME
$\backslash\text{PointsToWholeBigPoints}$ $\{.^1.,.^2.,.^3.,.^4.\}$ $\backslash.^1.,.^2.,.^3.,.^4..$ 1 DIMENSION 2 CSNAME
$\backslash\text{PPCHTEX}$
$\backslash\text{PPCHTeX}$
$\backslash\text{PRAGMA}$
$\backslash\text{PtToCm}$ $\{.^1.,.^2.,.^3.,.^4.\}$ * DIMENSION
$\backslash\text{pagearea}$ $[.^1.,.^2.,.^3.,.^4.]$ $[.^1.,.^2.,.^3.,.^4.]$ $[.^1.,.^2.,.^3.,.^4.]$ 1 vrsek zahlavi text upati spodek 2 text marginalie hrana 3 vlevo vpravo textvlevo middletext textvpravo
$\backslash\text{pageblockrealpage}$ $\{.^1.,.^2.,.^3.,.^4.\}$ * NAME

<code>\pagebreak</code> [...*...] * prazdne zahlavi upoti dummy ramecek NUMBER +NUMBER implicitni reset zablokovat ano ne zlom prazdny nastaveni vysokapriorita vlevo vpravo sude liche cytrnasobny posledni poslednistrana start stop xy note NAME
<code>\pagefigure</code> [...¹] [...²...] 1 FILE ^{OPT} 2 offset = implicitni prekryv zadny DIMENSION
<code>\pageinjection</code> [...¹] [...²...] 1 NAME ^{OPT} 2 KEY = VALUE ^{OPT}
<code>\pageinjection</code> [...¹...]¹ [...²...]² 1 inherits: \setuppageinjection ^{OPT} 2 KEY = VALUE ^{OPT}
<code>\pagelayout</code> [...] * stranka levestranka pravastranka
<code>\pagestaterealpage</code> {...¹} {...²} 1 NAME 2 NAME NUMBER
<code>\pagestaterealpageorder</code> {...¹} {...²} 1 NAME 2 NAME NUMBER
<code>\paletsize</code>
<code>\PARAGRAPHS</code>
<code>\parbreak</code>
<code>\PARINSERT</code> [...¹...]¹ {...²} 1 inherits: \setupparinsert ^{OPT} 2 CONTENT instances: leftparinsert rightparinsert
<code>\leftparinsert</code> [...¹...]¹ {...²} 1 inherits: \setupparinsert ^{OPT} 2 CONTENT
<code>\rightparinsert</code> [...¹...]¹ {...²} 1 inherits: \setupparinsert ^{OPT} 2 CONTENT
<code>\pbsp</code>
<code>\pdfactualtext</code> {...¹} {...²} 1 CONTENT 2 TEXT
<code>\pdfalternativetext</code> {...¹} {...²} 1 CONTENT 2 TEXT
<code>\pdfbackendactualtext</code> {...¹} {...²} 1 CONTENT 2 TEXT

<code>\pdfbackendalternativetext</code> <code>{...}</code> <code>{...}</code> 1 CONTENT 2 TEXT
<code>\pdfbackendcurrentresources</code>
<code>\pdfbackendsetcatalog</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetcolorspace</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsettextgstate</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetinfo</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetname</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpageattribute</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpageresource</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpagesattribute</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpattern</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetshade</code> <code>{...}</code> <code>{...}</code> 1 NAME 2 TEXT
<code>\pdfcolor</code> <code>{...}</code> * NAME
<code>\pdfTeX</code>
<code>\pdfsetuserdata</code>
<code>\pdfTeX</code>
<code>\penalizedspacing</code>
<code>\percent</code>

<code>\percentdimen</code> $\{.^1.\}$ $\{.^2.\}$ 1 DIMENSION CSNAME 2 DIMENSION NUMBER%
<code>\periodic</code> $\{.^*.\}$ * TEXT
<code>\permitcaretescape</code>
<code>\permitcircumflexescape</code>
<code>\permitspacesbetweengroups</code>
<code>\persiandecimals</code> $\{.^*.\}$ * NUMBER
<code>\persiannumerals</code> $\{.^*.\}$ * NUMBER
<code>\phantom</code> $\{.^*.\}$ * CONTENT
<code>\phantombox</code> $[...^*...]$ * sirka = DIMENSION * vyska = DIMENSION * hloubka = DIMENSION
<code>\pickupgroupedcommand</code> $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1 BEFEHL 2 BEFEHL 3 BEFEHL
<code>\pickupgroupedcommandcs</code> $\backslash.^1$ $\backslash.^2$ $\backslash.^3$ 1 CSNAME 2 CSNAME 3 CSNAME
<code>\pickupperinsert</code>
<code>\pis</code> $[...^1...]$ $\{.^2.\}$ 1 inherits: $\backslash n^{\text{ST}}\text{avtype}$ 2 CONTENT
<code>\pis</code> $[...^1...]$ $\langle\langle.^2.\rangle\rangle$ 1 inherits: $\backslash n^{\text{OPT}}\text{avtype}$ 2 ANGLES
<code>\placeattachments</code>
<code>\placebalancing</code> $[.^1]$ $[...^2...]$ 1 NAME 2 inherits: $\backslash\text{setupbalancing}$
<code>\placebtxrendering</code> $[.^1]$ $[...^2...]$ 1 NAME 2 inherits: $\backslash\text{setupbtxrendering}$
<code>\placecitation</code> $[.^*]$ * REFERENCE

\placecomments	
\placecurrentformulanumber	
\placedbox {...} * CONTENT	
\placefloat [... ¹] [..., ² ...] [..., ³ ...] {... ⁴ } {... ⁵ } 1 SINGULAR 2 split keepetogether vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append 3 REFERENCE 4 TEXT 5 CONTENT	
\placefloatcaption [... ¹] [..., ² ...] [..., ³ ...] 1 NAME 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT 3 KEY = VALUE	
\placefloatplaceholder	
\placefloatwithsetups [... ¹] [..., ² ...] [..., ³ ...] {... ⁴ } {... ⁵ } 1 NAME 2 split keepetogether vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append 3 REFERENCE 4 TEXT 5 CONTENT	
\umistiFLOAT [..., ¹ ...] [..., ² ...] {... ³ } {... ⁴ } 1 split keepetogether vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append 2 REFERENCE 3 TEXT 4 CONTENT instances: chemical figure table intermezzo graphic	
\umistifigure [..., ¹ ...] [..., ² ...] {... ³ } {... ⁴ } 1 split keepetogether vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append 2 REFERENCE 3 TEXT 4 CONTENT	

<code>\umistigraphic</code> [...¹,...] [...²,...] {...³} {...⁴} 1 split keepetogether vzdý^{OPT}vlevo vpravo u^{OPT}vnitř vnější zpetnamezera cutspace ivlevo ivpravo naokrají levýokraj pravýokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [--]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavce nekde effective zahlaví upatí tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbv fxbt fixd append 2 REFERENCE 3 TEXT 4 CONTENT
<code>\umistichemical</code> [...¹,...] [...²,...] {...³} {...⁴} 1 split keepetogether vzdý^{OPT}vlevo vpravo u^{OPT}vnitř vnější zpetnamezera cutspace ivlevo ivpravo naokrají levýokraj pravýokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [--]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavce nekde effective zahlaví upatí tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbv fxbt fixd append 2 REFERENCE 3 TEXT 4 CONTENT
<code>\umistiintermezzo</code> [...¹,...] [...²,...] {...³} {...⁴} 1 split keepetogether vzdý^{OPT}vlevo vpravo u^{OPT}vnitř vnější zpetnamezera cutspace ivlevo ivpravo naokrají levýokraj pravýokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [--]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavce nekde effective zahlaví upatí tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbv fxbt fixd append 2 REFERENCE 3 TEXT 4 CONTENT
<code>\umistitable</code> [...¹,...] [...²,...] {...³} {...⁴} 1 split keepetogether vzdý^{OPT}vlevo vpravo u^{OPT}vnitř vnější zpetnamezera cutspace ivlevo ivpravo naokrají levýokraj pravýokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [--]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavce nekde effective zahlaví upatí tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbv fxbt fixd append 2 REFERENCE 3 TEXT 4 CONTENT
<code>\placeframed</code> [...¹.] [...²,...²,...] {...³} 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
<code>\placeheadnumber</code> [...] * ABSCHNITT
<code>\placeheadtext</code> [...] * ABSCHNITT
<code>\placehelp</code>
<code>\placeholder</code> [...] * NAME
<code>\placeinitial</code> [...] * NAME
<code>\placelayer</code> [...] * NAME

<code>\placelayeredtext</code> ¹<code>[...]</code> ²<code>[...<u>=</u>...,...]</code> ³<code>[...<u>=</u>...,...]</code> ⁴<code>{...}</code> ⁵<code>{...}</code> 1 NAME 2 inherits: \setuplayer 3 inherits: \setuplayeredtext 4 TEXT 5 CONTENT
<code>\placelistofFLOATS</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavseznam OPT instances: chemicals figures tables intermezzi graphics
<code>\placelistoffigures</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistofgraphics</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistofchemicals</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistofintermezzi</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistoftables</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavseznam OPT
<code>\placelistofpublications</code> ¹<code>[...]</code> ²<code>[...<u>=</u>...,...]</code> 1 NAME OPT OPT 2 inherits: \setupbtxrendering
<code>\placelistofsorts</code> ¹<code>[...]</code> ²<code>[...<u>=</u>...,...]</code> 1 SINGULAR OPT 2 inherits: \nastavtrideni
<code>\placelistofSORTS</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavtrideni OPT instances: logos
<code>\placelistoflogos</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavtrideni OPT
<code>\placelistofsynonyms</code> ¹<code>[...]</code> ²<code>[...<u>=</u>...,...]</code> 1 SINGULAR OPT 2 inherits: \nastavsynonyma
<code>\placelistofSYNONYMS</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavsynonyma OPT instances: abbreviations
<code>\placelistofabbreviations</code> [*]<code>[...<u>=</u>...,...]</code> * inherits: \nastavsynonyma OPT
<code>\placelocalnotes</code> ¹<code>[...]</code> ²<code>[...<u>=</u>...,...]</code> 1 NAME OPT 2 inherits: \setupnote
<code>\placement</code> ¹<code>[...]</code> ²<code>[...<u>=</u>...,...]</code> ³<code>{...}</code> 1 NAME OPT 2 inherits: \setupplacement 3 CONTENT


```
1 inherits: \setupplacementGPT
2 CONTENT
```

1	NAME
2	REFERENCE

```

1  + - REFERENCE
2  TEXT
3  TEXT

```

```
1  NAME
2  inherits: \setupnote
```

```
1  NAME
2  inherits: \setuppairedbox
3  CONTENT
4  TEXT
```

```
1 inherits: \setuppairedbox OPT
2 CONTENT
3 TEXT
```

```

1 inherits: \setuppairedboxOPT
2 CONTENT
3 TEXT

```

```
1  NAME
2  NAME
3  inherits: \setupparallel
```

* ABSCHNITT

* ABSCHNITT

* ABSCHNITT

```
1  LISTE
2  inherits: \nastavseznam
```

1	NAME
2	NAME

\placesavedfloat [¹...] [²] [...,³...,...] 1 NAME OPT 2 REFERENCE 3 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append odkaz = REFERENCE referencetext = TEXT
\placesynchronize [¹] [...,²...,...] 1 NAME OPT 2 inherits: \setupsynchronize
\plainmatrix {...} * CONTENT
\plnezneni {...} * NAME
\pole [¹] [²] 1 NAME OPT 2 TEXT
\polozka [...,*,...] * REFERENCE OPT
\polozky [...,¹...,...] {...²} 1 inherits: \nastavpolozky 2 TEXT
\popattribute *.. * CSNAME
\POPIS [...,¹...,...] {...²} ³... \par 1 REFERENCE OPT OPT 2 TEXT 3 CONTENT
\popmacro *.. * CSNAME
\popmode [...] * NAME
\POPISEK [...,¹...,...] {...²} 1 REFERENCE OPT OPT 2 TEXT
\popsystemmode {...} * NAME
\porovnejpaletu [...] * NAME
\porovnejskupinubarev [...] * NAME

<code>\positionoverlay {...}</code> * NAME
<code>\positionregionoverlay {¹...} {²...}</code> 1 NAME 2 NAME
<code>\poslaednipodstranka</code>
<code>\postponenotes</code>
<code>\pozadi {...}</code> * CONTENT
<code>\POZADI {...}</code> * CONTENT instances: pozadi
<code>\pozice [...,¹...^{OPT},...] (...²,...) {³...}</code> 1 inherits: \nastavumistovani 2 POSITION 3 CONTENT
<code>\poznamka [¹...] [²...]</code> 1 NAME ^{OPT} 2 REFERENCE
<code>\NOTE [...¹,...] {²...}</code> 1 REFERENCE ^{OPT} 2 TEXT instances: footnote endnote mathnote publicationnote
<code>\NOTE [...[*],...]</code> * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT instances: footnote endnote mathnote publicationnote
<code>\endnote [...[*],...]</code> * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT
<code>\footnote [...[*],...]</code> * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT
<code>\mathnote [...[*],...]</code> * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT

<code>\publicationnote</code> [...¹...[*]...] * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT
<code>\endnote</code> [...¹...] {²...} 1 REFERENCE OPT 2 TEXT
<code>\footnote</code> [...¹...] {²...} 1 REFERENCE OPT 2 TEXT
<code>\mathnote</code> [...¹...] {²...} 1 REFERENCE OPT 2 TEXT
<code>\publicationnote</code> [...¹...] {²...} 1 REFERENCE OPT 2 TEXT
<code>\pravidelne</code>
<code>\predefinedfont</code> [...[*]...] * FONT
<code>\predefinefont</code> [...¹...] [...²...] 1 NAME 2 FONT
<code>\predefinesymbol</code> [...[*]...] * NAME
<code>\pref</code> {¹...} {²...} [...³...] 1 TEXT OPT OPT 2 TEXT 3 REFERENCE
<code>\prefixedpagenumber</code>
<code>\prelozit</code> [...[*]...] * SPRACHE = TEXT OPT
<code>\prependetoks</code> ...¹ \to \²... 1 BEFEHL 2 CSNAME
<code>\prependgvalue</code> {¹...} {²...} 1 NAME 2 BEFEHL
<code>\prependhiddenbackground</code> {...[*]...} * NAME
<code>\prependtocommalist</code> {¹...} \²... 1 TEXT 2 CSNAME

<pre> \prependtoks ... \to \... 1 BEFEHL 2 CSNAME </pre>
<pre> \prependtoksonce ... \to \... 1 BEFEHL 2 CSNAME </pre>
<pre> \prependvalue {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \prepninazakladnifont [...,*...] * inherits: \nastavzakladnifont </pre>
<pre> \prerollblank [...,*...] * inherits: \preskoc </pre>
<pre> \prerolledpages [...,*...] * NAME </pre>
<pre> \presetdocument [...¹...] [...,...²...,...] 1 NAME OPT 2 inherits: \setupdocument </pre>
<pre> \presetfieldsymbols [...,*...] * NAME </pre>
<pre> \presetLABELtext [...¹...] [...,...²...,...] 1 SPRACHE OPT 2 KEY = VALUE instances: head label mathlabel taglabel unit operator prefix suffix btxlabel </pre>
<pre> \presetbtxlabeltext [...¹...] [...,...²...,...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetheadtext [...¹...] [...,...²...,...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetlabeltext [...¹...] [...,...²...,...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetmathlabeltext [...¹...] [...,...²...,...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetoperatortext [...¹...] [...,...²...,...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetprefixtext [...¹...] [...,...²...,...] 1 SPRACHE OPT 2 KEY = VALUE </pre>
<pre> \presetsuffixtext [...¹...] [...,...²...,...] 1 SPRACHE OPT 2 KEY = VALUE </pre>

<pre> \presettaglabeltext [...]¹ [...,...²...,...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetunittext [...]¹ [...,...²...,...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetmathematics [...,*...] * NAME </pre>
<pre> \preskoc [...,*...] * nastaveni stejna stranka max sila enable zablockovat zadnabila zhustene zpet prekryv vzdy drzet weak strong implicitni pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku halflinebefore halflineafter quarterline rovnice bily vyska podlehloubky standardni NUMMER*male NUMMER*stredni NUMMER*velke NUMMER*radek NUMMER*pulradku NUMMER*quarterline NUMMER*rovnice NUMMER*bily NUMMER*vyska NUMMER*podlehloubky category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME </pre>
<pre> \pretocommalist {...}¹ \...² 1 TEXT 2 CSNAME </pre>
<pre> \prettyprintbuffer {...}¹ {...}² 1 BUFFER 2 mp lua xml parsed-xml nested tex context zadny NAME </pre>
<pre> \prevcounter [...]¹ [...]² 1 NAME 2 NUMMER </pre>
<pre> \prevcountervalue [...][*] * NAME </pre>
<pre> \preventmode [...,*...] * NAME </pre>
<pre> \predchoziPRIKAZ </pre>
<pre> \prevrealpage </pre>
<pre> \prevrealpagenumber </pre>
<pre> \prevsubcountervalue [...]¹ [...]² 1 NAME 2 NUMMER </pre>
<pre> \prevsubpage </pre>
<pre> \prevsubpagenumber </pre>
<pre> \prevuserpage </pre>
<pre> \prevuserpagenumber </pre>
<pre> \privatecharacter {...}[*] * NAME </pre>
<pre> \privatecharactercode {...}[*] * NAME </pre>

$\backslash\text{prizpusobivepole}$ $[\dots]^1$ $[\dots,\dots]^2,\dots$ 1 NAME 2 inherits: \setupfieldbody
$\backslash\text{prizpusobvzhled}$ $[\dots,\dots]^1$ $[\dots,\dots]^2,\dots$ 1 NUMBER 2 vyska = max DIMENSION radky = NUMBER vrsek = DIMENSION
$\backslash\text{procent}$
$\backslash\text{processaction}$ $[\dots]^1$ $[\dots,\dots]^2>\dots$ 1 BEFEHL 2 APPLY
$\backslash\text{processallactionsinset}$ $[\dots]^1$ $[\dots,\dots]^2>\dots$ 1 BEFEHL 2 APPLY
$\backslash\text{processassignlist}$ $[\dots,\dots]^1$ $\backslash\dots^2$ 1 TEXT 2 CSNAME
$\backslash\text{processassignmentcommand}$ $[\dots,\dots]^1,\dots$ $\backslash\dots^2$ 1 KEY = VALUE 2 CSNAME
$\backslash\text{processassignmentlist}$ $[\dots,\dots]^1,\dots$ $\backslash\dots^2$ 1 KEY = VALUE 2 CSNAME
$\backslash\text{processbetween}$ $\{\dots\}^1$ $\backslash\dots^2$ 1 NAME 2 CSNAME
$\backslash\text{processbodyfontenvironmentlist}$ $\backslash\dots^*$ * CSNAME
$\backslash\text{processcolorcomponents}$ $\{\dots\}^*$ * COLOR
$\backslash\text{processcolumnset}$
$\backslash\text{processcommacommand}$ $[\dots,\dots]^1$ $\backslash\dots^2$ 1 BEFEHL 2 CSNAME
$\backslash\text{processcommalist}$ $[\dots,\dots]^1$ $\backslash\dots^2$ 1 BEFEHL 2 CSNAME
$\backslash\text{processcommalistwithparameters}$ $[\dots,\dots]^1$ $\backslash\dots^2$ 1 BEFEHL 2 CSNAME
$\backslash\text{processcontent}$ $\{\dots\}^1$ $\backslash\dots^2$ 1 NAME 2 CSNAME

```
\processdataset      [.1..]      [.2..]      [.3..]
1  FILE
2  NAME
3  NAME
```

```
\processfile  {...}
*  FILE
```

```
\processfilemany  {...}
*  FILE
```

```
\processfilenone    {...}
*   FILE
```

```
\processfileonce  {...}
*  FILE
```

```
\processfirstactioninset    [...]1    [...,...2>...,...]
```

```
1  BEFEHL
```

```
2  APPLY
```

```
\processinsertions
```

```
\processisolatedchars  {...}  \.^...
```

```
1  TEXT
```

```
2  CSNAME
```

```
\processisolatedwords  {...}  \.^2...
1  TEXT
2  CSNAME
```

```
\processlinetablebuffer    [...]
```

```
*    BUFFER                OPT
```

```
\processlinetablefile    {...}
*   FILE
```

	<code>{...}</code> ¹	<code>{...}</code> ²	<code>{...}</code> ³	<code>\...</code> ⁴
<code>\processlist</code>				
1	CHARACTER			
2	CHARACTER			
3	TEXT			
4	CSNAME			

```
\processMPbuffer    [...,*...]
*   NAME            OPT
```

```
\processMPfigurefile    {...}
*   FILE
```

```
\processmonth    {\.^1.}    {\.^2.}    {\.^3.}
```

```
1  NUMBER
```

```
2  NUMBER
```

```
3  BEFEHL
```

```
\processranges    [...,1...]    \..2
1  NUMBER NUMBER:NUMBER
2  CSNAME
```



```

1  TEXT
2  TEXT
3  CSNAME BEFEHL.

```

* BUFFER

* BUFFER

1	BEFEHL
2	BEFEHL
3	BEFEHL
4	BEFEHL
5	TEXT

* CSNAME

* NAME

* FILE

* NAME

1	NUMMER
2	BEFEHL
3	BEFEHL
4	BEFEHL

* FILE

* FILE

```

1      zadny fixne strikthi halffixed quarterfixed eightsfixed NAME
2      inherits: \setupprofile
3      CONTENT

```

```
1  zadny fixne striktni haiffixed quarterfixed eightsfixed NAME
2  CSNAME NUMBER
```

* NAME

* FILE

* FILE

\prostredi [...] * FILE
\prostredi ... * FILE
\prvnipodstranka
\pseudoMixedCapped {...} * TEXT
\pseudoSmallCapped {...} * TEXT
\pseudoSmallcapped {...} * TEXT
\pseudosmallcapped {...} * TEXT
\purenumber {...} * NUMMER
\pusharrangedpages ... \poparrangedpages
\pushattribute \... * CSNAME
\pushbar [...] ... \popbar * NAME
\pushbarva [...] ... \popbarva * COLOR
\pushbutton [. ¹ .] [. ² .] 1 NAME 2 REFERENCE
\pushcatcodetable ... \popcatcodetable
\pushendofline ... \popendofline
\pushglobalsetups ... \popglobalsetups
\pushindentation ... \popindentation
\pushlocalanchors ... \poplocalanchors
\pushMPdrawing ... \popMPdrawing
\pushmacro \... * CSNAME
\pushmathstyle ... \popmathstyle

* NAME

* NAME.

`\pushoverloadmode ... \popoverloadmode`

* PATH

* NAME

`\pushpunctuation ... \poppunctuation`

`\pushrandomseed ... \poprandomseed`

* + - TEXT

* NAME

1 NAME.

1 NAME
2 NUMMER TEXT

3 CSNAME NUMMER

1 NAME

2 NUMMER TEXT

3 CSNAME

4 CONTENT

* vlevo vpravo ^{OPT} pred po mezi

$$\backslash\mathrm{qqquad}$$

```
*  text      = TEXT
   sirka     = DIMENSION
   buffer    = NAME
   barva     = COLOR
```

 $\backslash quad$

* NUMMER.

`\quarterstrut`

\quitcommalist

\quitprevcommalist

\quittypescriptscanning

<code>\rawgetparameters</code> $[...]$ $[...,\overset{2}{=},...]$ 1 TEXT 2 KEY = VALUE
<code>\rawMPdata</code>
<code>\rawmathematics</code> $\{...\}$ * CONTENT
<code>\rawparagraphshape</code> $\{...\}$ * NAME
<code>\rawprocessaction</code> $[...]$ $[...,\overset{2}{\Rightarrow},...]$ 1 BEFEHL 2 APPLY
<code>\rawprocesscommacommand</code> $[...,\overset{1}{},...]$ $\backslash\overset{2}{}...$ 1 BEFEHL 2 CSNAME
<code>\rawprocesscommalist</code> $[...,\overset{1}{},...]$ $\backslash\overset{2}{}...$ 1 BEFEHL 2 CSNAME
<code>\rawstructurelistuservariable</code> $\{...\}$ * KEY
<code>\rawsubcountervalue</code> $[...]$ $[...]$ 1 NAME 2 NUMMER
<code>\rbox</code> $\overset{1}{}...$ $\{...\}$ 1 TEXT OPT 2 CONTENT
<code>\readfile</code> $\{...\}$ $\{...\}$ $\{...\}$ 1 FILE 2 TRUE 3 FALSE
<code>\readfixfile</code> $\{...\}$ $\{...\}$ $\{...\}$ $\{...\}$ 1 PATH 2 FILE 3 TRUE 4 FALSE
<code>\readjobfile</code> $\{...\}$ $\{...\}$ $\{...\}$ 1 FILE 2 TRUE 3 FALSE
<code>\readlocfile</code> $\{...\}$ $\{...\}$ $\{...\}$ 1 FILE 2 TRUE 3 FALSE
<code>\readsetfile</code> $\{...\}$ $\{...\}$ $\{...\}$ $\{...\}$ 1 PATH 2 FILE 3 TRUE 4 FALSE

<code>\readsysfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readtexfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\realpagenumber</code>
<code>\realSmallCapped {...}</code> * TEXT
<code>\realSmallcapped {...}</code> * TEXT
<code>\realsmallcapped {...}</code> * TEXT
<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [...]</code> <code>[...]</code> 1 implicitni text titul cislo stranka realpage 2 REFERENCE
<code>\referencecolumnnumber</code>
<code>\REFERENCEFORMAT {...} {...} [...]</code> 1 TEXT OPT OPT 2 TEXT 3 REFERENCE
<code>\referencepagedetail</code>
<code>\referencepagestate</code>
<code>\referenceprefix</code>
<code>\referencerealpage</code>
<code>\referencesymbol</code>
<code>\referencewildcard</code>
<code>\registerattachment [...]</code> <code>[...,...²...,...]</code> 1 NAME 2 inherits: \setupattachment
<code>\registerboxanchor</code>

<pre> \registercxtluafile {...} {...} 1 FILE 2 NUMMER </pre>
<pre> \registerexternalfigure [...]¹ [...]² [...,...³...,...]^{OPT} 1 FILE 2 NAME 3 inherits: \setupexternalfigure </pre>
<pre> \registerfallbackfont [...]¹ [...,²...] 1 serif sans mono 2 FONT </pre>
<pre> \registerfiguremask [...]¹ {...}² 1 NAME 2 CONTENT </pre>
<pre> \registerfigurerange [...]¹ {...}² 1 NAME 2 CONTENT </pre>
<pre> \registerfontclass {...} * NAME </pre>
<pre> \registerhyphenationexception [...]¹ [...]² 1 SPRACHE 2 TEXT </pre>
<pre> \registerhyphenationpattern [...]¹ [...]² 1 SPRACHE 2 TEXT </pre>
<pre> \registermathfunction [...][*] * NAME </pre>
<pre> \registermathsymbol [...]¹ [...]² [...]³ [...]⁴ 1 NAME 2 SPRACHE 3 NAME 4 TEXT </pre>
<pre> \registermenubuttons [...]¹ [...]² 1 NAME 2 TEXT </pre>
<pre> \registeroverloads [...][*] * NAME </pre>
<pre> \registerparwrapper {...}¹ {...}² {...}³ 1 NAME 2 CONTENT 3 CONTENT </pre>
<pre> \registerparwrapperreverse {...}¹ {...}² {...}³ 1 NAME 2 CONTENT 3 CONTENT </pre>

<pre> \registerpattern [...¹] [...,...²...,...] {...³} 1 NAME OPT OPT 2 jmeno = NAME sirka = auto DIMENSION vyska = auto DIMENSION hoffset = auto -auto DIMENSION voffset = auto -auto DIMENSION 3 CONTENT </pre>
<pre> \registersort [...¹] [...²] 1 SINGULAR 2 NAME </pre>
<pre> \registersortpage [...¹] [...²] 1 SINGULAR 2 NAME </pre>
<pre> \registersynonym [...¹] [...²] 1 SINGULAR 2 NAME </pre>
<pre> \registertopcontent [...¹] \...² {...³} 1 NUMMER 2 CSNAME 3 CONTENT </pre>
<pre> \registerunit [...¹] [...,...²...,...] 1 prefix jednotka operátor suffix symbol packaged 2 KEY = VALUE </pre>
<pre> \registerunitshortcut [...¹] [...,...²...,...] 1 prefix jednotka operator suffix symbol packaged 2 KEY = VALUE </pre>
<pre> \REGISTER [...¹] {...+...²+...} 1 TEXT PROCESSOR^{QES}->TEXT 2 INDEX instances: index </pre>
<pre> \index [...¹] {...+...²+...} 1 TEXT PROCESSOR^{QES}->TEXT 2 INDEX </pre>
<pre> \REGISTER [...¹] {...²} {...+...³+...} 1 TEXT PROCESSOR^{QES}->TEXT 2 TEXT 3 INDEX instances: index </pre>
<pre> \index [...¹] {...²} {...+...³+...} 1 TEXT PROCESSOR^{QES}->TEXT 2 TEXT 3 INDEX </pre>
<pre> \relatemarking [...¹] [...²] 1 BESCHRIFTUNG 2 BESCHRIFTUNG </pre>
<pre> \relateparameterhandlers {...¹} {...²} {...³} {...⁴} 1 NAME 2 NAME 3 NAME 4 NAME </pre>

\relateparameterhandlersbyns \ ¹ ... { ² ...} \ ³ ... { ⁴ ...} 1 CSNAME 2 NAME 3 CSNAME 4 NAME
\relaxvalueifundefined { [*] ...} * NAME
\remainingcharacters
\removebottomthings
\removedepth
\removefromcommalist { ¹ ...} \ ² ... 1 TEXT 2 CSNAME
\removelastskip
\removelastspace
\removemarkedcontent [[*] ...] * NAME
\removemissingcharacters
\removepunctuation
\removesubstring ¹ ... \from ² ... \to \ ³ ... 1 TEXT 2 TEXT 3 CSNAME
\removetoks ¹ ... \from \ ² ... 1 BEFEHL 2 CSNAME
\removeunwantedspaces
\reorderfloats [... [*] ,...] * NAME
\repeathead [[*] ...] * ABSCHNITT
\replacefeature [[*] ...] * NAME
\replacefeature { [*] ...} * NAME
\replaceincommalist \ ¹ ... { ² ...} 1 CSNAME 2 NUMMER
\replacemissingcharacters

<pre> \replaceword [...]¹ [...]² [...]³ 1 NAME 2 TEXT 3 TEXT </pre>
<pre> \rescan {...} * CONTENT </pre>
<pre> \rescanwithsetup {...}¹ {...}² 1 NAME 2 CONTENT </pre>
<pre> \reservecolumnset </pre>
<pre> \resetalignmentcharacter </pre>
<pre> \resetallattributes </pre>
<pre> \resetalternate </pre>
<pre> \resetandaddfeature [...] * NAME </pre>
<pre> \resetandaddfeature {...} * NAME </pre>
<pre> \resetbar </pre>
<pre> \resetboxesincache {...} * NAME </pre>
<pre> \resetbreakpoints </pre>
<pre> \resetbuffer [...] * BUFFER </pre>
<pre> \resetcollector [...] * NAME </pre>
<pre> \resetPRIKAZparameter {...} * KEY </pre>
<pre> \resetcomparingtext </pre>
<pre> \resetcounter [...]¹ [...]² 1 NAME 2 NUMMER </pre>
<pre> \resetctxscanner \... * CSNAME </pre>
<pre> \resetdigitsmanipulation </pre>
<pre> \resetdirection </pre>

<pre> \resetdummyparameter {...} \^2... 1 KEY 2 CSNAME </pre>
<pre> \resetexpansion </pre>
<pre> \resetextrafontkerns </pre>
<pre> \resetfeature </pre>
<pre> \resetflag {...} * NAME </pre>
<pre> \resetfontcolorscheme </pre>
<pre> \resetfontfallback [...^1.] [...^2.] 1 NAME OPT 2 FONT </pre>
<pre> \resetfontsolution </pre>
<pre> \resethyphenationfeatures </pre>
<pre> \resetcharacteralign </pre>
<pre> \resetcharacterkerning </pre>
<pre> \resetcharacterspacing </pre>
<pre> \resetcharacterstripping </pre>
<pre> \resetinjector [...^*] * NAME </pre>
<pre> \resetinteractionmenu [...^*] * NAME </pre>
<pre> \resetitaliccorrection </pre>
<pre> \resetlayer [...^*] * NAME </pre>
<pre> \resetlineprofile </pre>
<pre> \resetlistsynonyms [...^*] * SINGULAR </pre>
<pre> \resetlocalbox [...^*] * NAME </pre>
<pre> \resetlocalfloats </pre>
<pre> \resetlocalshowmakeup </pre>
<pre> \resetMPdrawing </pre>

\resetsynonyms [...] * SINGULAR
\resetsynonymsprogress [...] * SINGULAR
\resetsystemmode {...} * NAME
\resettimer
\resettokenlist [...] * NAME
\resettrackers
\resettransliteration
\resettrialtypesetting
\resetusedsortings [...] * SINGULAR
\resetusedsynonyms [...] * SINGULAR
\resetuserpagenumber
\resetvalue {...} * NAME
\resetvisualizers
\resetznaceni [...] * BESCHRIFTUNG
\reshapebox {...} * BEFEHL
\resolvedglyphdirect {...} {...} 1 FONT 2 e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
\resolvedglyphstyled {...} {...} 1 FONT 2 e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
\restartcounter [... ¹] [... ²] [... ³] 1 NAME 2 NUMMER 3 NUMMER OPT
\restorebox {... ¹ } {... ² } 1 NAME 2 NAME
\restorecatcodes

\restorecounter [...] * NAME
\restorecurrentattributes {...} * NAME
\restoreendofline
\restoreglobalbodyfont
\retestfeature
\reusableMPgraphic {...} {..., ² ...} 1 NAME 2 KEY = VALUE
\reusableMPgraphic [..., ¹ ...] {...} 1 instance = metafun ^{OPT} minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost doublepost binarypost decimalpost simplefun descriptiontext = TEXT alternativetext = TEXT 2 NAME
\reuseMPgraphic {...} {..., ² ...} 1 NAME 2 KEY = VALUE
\reuseMPgraphic [..., ¹ ...] {...} 1 instance = metafun ^{OPT} minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost doublepost binarypost decimalpost simplefun descriptiontext = TEXT alternativetext = TEXT 2 NAME
\reuserandomseed
\reversehbox ... {...} 1 TEXT 2 CONTENT
\reversehpack ... {...} 1 TEXT 2 CONTENT
\reversetpack ... {...} 1 TEXT 2 CONTENT
\reversevbox ... {...} 1 TEXT 2 CONTENT
\reversevboxcontent ... * CSNAME NUMBER
\reversevpack ... {...} 1 TEXT 2 CONTENT

$\backslash$ reversevtop $\dots$ ¹ $\{\dots\}$ ² 1 TEXT OPT 2 CONTENT
$\backslash$ revivefeature
$\backslash$ rfence $\dots$ * $\backslash\}$ $\backslash]$ $\backslash)$ $\backslash\$ $\backslash$ egroup $\backslash$ rparent $\backslash$ rparenthesis " $\backslash$ rparen " $\backslash$ rbracket $\backslash$ rbrack " $\backslash$ rbrace $\backslash$ rceil $\backslash$ rceiling $\backslash$ rfloor $\backslash$ urcorner $\backslash$ lrcorner $\backslash$ rmoustache $\backslash$ rrbracket $\backslash$ rangle $\backslash$ rrangle $\backslash$ rgroup $\backslash$ vert $\backslash$ singleverticalbar $\backslash$ doubleverticalbar $\backslash$ tripleverticalbar $\backslash$ rvert $\backslash$ rVert $\backslash$ rointerval $\backslash$ rlinterval CHARACTER
$\backslash$ rhbox $\{\dots\}$ * CONTENT
$\backslash$ riggedcenter
$\backslash$ riggedleft
$\backslash$ riggedright
$\backslash$ rightbottombox $\{\dots\}$ * CONTENT
$\backslash$ rightbox $\{\dots\}$ * CONTENT
$\backslash$ righthbox $\{\dots\}$ * CONTENT
$\backslash$ rightLABELtext $\{\dots\}$ * KEY instances: head label mathlabel
$\backslash$ rightheadtext $\{\dots\}$ * KEY
$\backslash$ rightlabeltext $\{\dots\}$ * KEY
$\backslash$ rightmathlabeltext $\{\dots\}$ * KEY
$\backslash$ rightline $\{\dots\}$ * CONTENT
$\backslash$ rightorleftpageaction $\{\dots\}$ ¹ $\{\dots\}$ ² 1 BEFEHL 2 BEFEHL
$\backslash$ rightpageorder
$\backslash$ rightparbox $[\dots]$ ¹ $\{\dots\}$ ² 1 globalne OPT 2 CONTENT
$\backslash$ rightskipadaption

\rozdelplvouciobjekt [...,.. ¹ ...,...] {...} {...} 1 inherits: \nastavdeleniplvoucichobjektu 2 BEFEHL 3 CONTENT
\rozmer {...} * CONTENT
\roztazene [...,.. ¹ ...,...] {...} 1 inherits: \setupstretched 2 TEXT
\rtlhbox ... ¹ {...} 1 TEXT OPT 2 CONTENT
\rtlttext {...} * CONTENT
\rtlvbox ... ¹ {...} 1 TEXT OPT 2 CONTENT
\rtlvtop ... ¹ {...} 1 TEXT OPT 2 CONTENT
\rtop ... ¹ {...} 1 TEXT OPT 2 CONTENT
\ruby [... ¹] {...} {...} 1 NAME OPT 2 TEXT 3 TEXT
\rukopisne
\ruledddbox ... ¹ {...} 1 TEXT OPT 2 CONTENT
\ruledddpack ... ¹ {...} 1 TEXT OPT 2 CONTENT
\ruledhbox ... ¹ {...} 1 TEXT OPT 2 CONTENT
\ruledhpack ... ¹ {...} 1 TEXT OPT 2 CONTENT
\ruledmbox {...} * CONTENT
\ruledtpack ... ¹ {...} 1 TEXT OPT 2 CONTENT

\ruledvbox		¹ ...	{...}
1	TEXT	OPT	
2	CONTENT		
\ruledvpack		¹ ...	{...}
1	TEXT	OPT	
2	CONTENT		
\ruledvtop		¹ ...	{...}
1	TEXT	OPT	
2	CONTENT		
\runbuffer		[¹ ...]	[² ...]
1	BUFFER		OPT
2	NAME		
\runMPbuffer		[... [*] ...]	
*	NAME	OPT	
\runninghbox		{...}	
*	CONTENT		
\russianNumerals		{...}	
*	NUMMER		
\russiannumerals		{...}	
*	NUMMER		
\ScaledPointsToBigPoints		{ ¹ ...}	\ ² ...
1	DIMENSION		
2	CSNAME		
\ScaledPointsToWholeBigPoints		{ ¹ ...}	\ ² ...
1	DIMENSION		
2	CSNAME		
\SLOVA		{...}	
*	TEXT		
\SLOVO		{...}	
*	TEXT		
\Slova		{...}	
*	TEXT		
\Slovo		{...}	
*	TEXT		
\Smallcapped		{...}	
*	TEXT		
\safechar		{...}	
*	NUMMER		
\samplefile		{...}	
*	FILE		
\sans			

<code>\sansnormal</code>
<code>\sanstucne</code>
<code>\savebarva ... \restorebarva</code>
<code>\savebox {...} {...} {...}</code> 1 NAME 2 NAME 3 CONTENT
<code>\savebtxdataset [...]¹ [...]² [...]³...</code> 1 NAME OPT OPT OPT 2 FILE 3 dataset = NAME typ = bib lua xml soubor = FILE kritérium = vse text uvod odkaz aktualni zde predchozi lokalne komponenta SECTIONBLOCK:vse SECTIONBLOCK:odkaz SECTIONBLOCK:aktualni SECTIONBLOCK:predchozi volba = TEXT
<code>\savebuffer [...]¹... [...]²...</code> 1 BUFFER OPT 2 inherits: \setupsavebuffer
<code>\savebuffer [...]¹... [...]²</code> 1 BUFFER 2 FILE
<code>\savecounter [...]</code> * NAME
<code>\savecurrentattributes {...}</code> * NAME
<code>\savemathexport [...][*]...</code> * inherits: \setupmathexport OPT
<code>\savenormalmeaning \...</code> * CSNAME
<code>\sbox {...}</code> * CONTENT
<code>\scaps {...}</code> * TEXT
<code>\SCRIPT</code> instances: hangul hanzi nihongo ethiopic thai latin test
<code>\ethiopic</code>
<code>\hangul</code>
<code>\hanzi</code>
<code>\latin</code>
<code>\nihongo</code>

\test
\thai
\secondoffivearguments {... ¹ } {... ² } {... ³ } {... ⁴ } {... ⁵ } 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\secondoffourarguments {... ¹ } {... ² } {... ³ } {... ⁴ } 1 TEXT 2 TEXT 3 TEXT 4 TEXT
\secondofsixarguments {... ¹ } {... ² } {... ³ } {... ⁴ } {... ⁵ } {... ⁶ } 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\secondofthreearguments {... ¹ } {... ² } {... ³ } 1 TEXT 2 TEXT 3 TEXT
\secondofthreeunexpanded {... ¹ } {... ² } {... ³ } 1 TEXT 2 TEXT 3 TEXT
\secondoftwoarguments {... ¹ } {... ² } 1 TEXT 2 TEXT
\secondoftwounexpanded {... ¹ } {... ² } 1 TEXT 2 TEXT
\sedabarva [... ¹] {... ² } 1 COLOR 2 CONTENT
\vizREGISTER [... ¹] {... ² +... ² +...} {... ³ } 1 TEXT PROCESSOR->TEXT 2 INDEX 3 TEXT PROCESSOR->TEXT instances: index
\vizindex [... ¹] {... ² +... ² +...} {... ³ } 1 TEXT PROCESSOR ^{OPT} ->TEXT 2 INDEX 3 TEXT PROCESSOR->TEXT
\SECTION [... ¹ ,... ¹] {... ² } 1 REFERENCE ^{OPT} 2 TEXT instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\SECTION` `[...,*=...,...]`

```
*   titul      = TEXT
    zalozka    = TEXT
    znaceni    = TEXT
    seznam     = TEXT
    odkaz      = REFERENCE
    referencetext = TEXT
    vlastnicislo = TEXT
    placeholder = TEXT
```

instances: part chapter section subsection subsubsection subsubsubsection
subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject
subsubsubsubsubject

`\chapter` `[...,*=...,...]`

```
*   titul      = TEXT
    zalozka    = TEXT
    znaceni    = TEXT
    seznam     = TEXT
    odkaz      = REFERENCE
    referencetext = TEXT
    vlastnicislo = TEXT
    placeholder = TEXT
```

`\part` `[...,*=...,...]`

```
*   titul      = TEXT
    zalozka    = TEXT
    znaceni    = TEXT
    seznam     = TEXT
    odkaz      = REFERENCE
    referencetext = TEXT
    vlastnicislo = TEXT
    placeholder = TEXT
```

`\section` `[...,*=...,...]`

```
*   titul      = TEXT
    zalozka    = TEXT
    znaceni    = TEXT
    seznam     = TEXT
    odkaz      = REFERENCE
    referencetext = TEXT
    vlastnicislo = TEXT
    placeholder = TEXT
```

`\subject` `[...,*=...,...]`

```
*   titul      = TEXT
    zalozka    = TEXT
    znaceni    = TEXT
    seznam     = TEXT
    odkaz      = REFERENCE
    referencetext = TEXT
    vlastnicislo = TEXT
    placeholder = TEXT
```

`\subsection` `[...,*=...,...]`

```
*   titul      = TEXT
    zalozka    = TEXT
    znaceni    = TEXT
    seznam     = TEXT
    odkaz      = REFERENCE
    referencetext = TEXT
    vlastnicislo = TEXT
    placeholder = TEXT
```

`\subsubject` `[...,*=...,...]`

```
*   titul      = TEXT
    zalozka    = TEXT
    znaceni    = TEXT
    seznam     = TEXT
    odkaz      = REFERENCE
    referencetext = TEXT
    vlastnicislo = TEXT
    placeholder = TEXT
```

\subsubsection [...,.*=.,...]

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
referencetext = TEXT
vlastnicislo = TEXT
placeholder = TEXT

\subsubsubject [...,.*=.,...]

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
referencetext = TEXT
vlastnicislo = TEXT
placeholder = TEXT

\subsubsubsection [...,.*=.,...]

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
referencetext = TEXT
vlastnicislo = TEXT
placeholder = TEXT

\subsubsubsubject [...,.*=.,...]

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
referencetext = TEXT
vlastnicislo = TEXT
placeholder = TEXT

\subsubsubsubsection [...,.*=.,...]

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
referencetext = TEXT
vlastnicislo = TEXT
placeholder = TEXT

\subsubsubsubsubject [...,.*=.,...]

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
referencetext = TEXT
vlastnicislo = TEXT
placeholder = TEXT

\title [...,.*=.,...]

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
referencetext = TEXT
vlastnicislo = TEXT
placeholder = TEXT

<pre> \chapter [...,¹...] {...²} 1 REFERENCE OPT 2 TEXT </pre>
<pre> \SECTION [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject </pre>
<pre> \chapter [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>
<pre> \part [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>
<pre> \section [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>
<pre> \subject [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>
<pre> \subsection [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>
<pre> \subsubject [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>
<pre> \subsubsection [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>
<pre> \subsubsubject [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>
<pre> \subsubsubsection [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>
<pre> \subsubsubsubject [...,¹...] {...²} {...³} 1 REFERENCE OPT 2 NUMMER 3 TEXT </pre>

<pre> \select {...} {...} {...} {...} {...} {...} 1 NAME OPT OPT OPT OPT OPT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT </pre>
<pre> \serializecommalist [...,*...] * BEFEHL </pre>
<pre> \serializedcommalist </pre>
<pre> \serif </pre>
<pre> \serifbold </pre>
<pre> \serifnormal </pre>
<pre> \setalignmentcharacter </pre>
<pre> \setalignmentswitch {...} * vlevo nastred vpravo </pre>
<pre> \setalternate {...} * TEXT </pre>
<pre> \setanchorbox [...] [...,...²...,...] \...³ {...}⁴ 1 NAME 2 inherits: \setupboxanchor 3 CSNAME 4 CONTENT </pre>
<pre> \setautopagestaterealpageno {...} * NAME </pre>
<pre> \setbar [...] * NAME </pre>
<pre> \setbigbodyfont </pre>
<pre> \setboxanchor [...]¹ [...]² [...,...³...,...]³ {...}⁴ 1 NAME 2 NAME 3 inherits: \setupboxanchorcontent 4 CONTENT </pre>
<pre> \setboxllx ...¹ {...}² 1 CSNAME NUMBER 2 DIMENSION </pre>
<pre> \setboxlly ...¹ {...}² 1 CSNAME NUMBER 2 DIMENSION </pre>
<pre> \setbreakpoints [...] * reset NAME </pre>
<pre> \setbuffer [...] ... \endbuffer * NAME </pre>

\setcapstrut		
\setcatcodetable *... * CSNAME		
\setcollector [...] ¹ [...,... ² ...] ² {...} ³ 1 NAME 2 inherits: \setupcollector 3 CONTENT		
\setcolormodel [...] * black bw seda rgb cmyk vse zadny		
\setcolumnset [...,... ¹ ...] ¹ {...} ² 1 c = NUMBER r = NUMBER nc = NUMBER nr = NUMBER metoda = zde fixne vrsek spodek tblr lrtb tbrl rltb btlr lrbt btrl rlbt fxtb fxbt volba = stranka nvrsek = NUMBER nspodek = NUMBER 2 CONTENT		
\setPRIKAZparameter {...} ¹ {...} ² 1 KEY 2 CONTENT		
\setcomparingtext [...] * reset NAME		
\setcounter [...] ¹ [...] ² [...] ³ 1 NAME 2 NUMBER 3 NUMBER		
\setcounterown [...] ¹ [...] ² [...] ³ 1 NAME 2 NUMBER 3 TEXT		
\setctxluafunction {...} ¹ {...} ² 1 NAME 2 NUMBER		
\setcurrentfontclass {...} * NAME		
\setcurrentinsection {...} * NAME		
\setdataset [...] ¹ [...] ² [...,... ³ ...] ³ 1 NAME 2 NAME 3 KEY = VALUE		
\setdatavalue {...} ¹ {...} ² 1 NAME 2 NUMBER		

\setdate [...] * d = NUMBER m = NUMBER y = NUMBER
\setdefaultpenalties
\setdigitsmanipulation [...] * reset NUMBER
\setdirection [...] * NUMBER
\setdirectsymbolicfont {...} * FONT
\setdocumentargument {...} {...} 1 NAME 2 TEXT
\setdocumentargumentdefault {...} {...} 1 NAME 2 TEXT
\setdocumentfilename {...} {...} 1 NUMBER 2 TEXT
\setdummyparameter {...} {...} 1 KEY 2 BEFEHL
\setelementbackendtag [...] [...] 1 NAME 2 BlockQuote Caption Code Div Formula H L Lbl LBody LI Link P Quote Reference Sect Span Table TBODY TD TFOOT TH THEAD TOC TOCI TR
\setelementexporttag [...] [...] [...] 1 NAME 2 export nature pdf 3 inline obrazovka mixed
\setelementexporttag [...] [...] [...] 1 NAME 2 nature 3 inline obrazovka mixed
\setelementexporttag [...] [...] [...] 1 NAME 2 pdf 3 BlockQuote Caption Code Div Formula H L Lbl LBody LI Link P Quote Reference Sect Span Table TBODY TD TFOOT TH THEAD TOC TOCI TR
\setelementnature [...] [...] 1 NAME 2 inline obrazovka mixed
\setemeasure {...} {...} 1 NAME 2 DIMENSION

<code>\setevalue {...} {...}</code> 1 NAME 2 CONTENT
<code>\setevariable {...} {...} {...}</code> 1 NAME 2 KEY 3 VALUE
<code>\setevariables [^{.}] [...,^{.},...]</code> 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
<code>\setexcept [^{.}] {...}</code> 1 vlevo vpravo OPT 2 CONTENT
<code>\setexpandedPRIKAZparameter {...} {...}</code> 1 KEY 2 CONTENT
<code>\setexpandeddummyparameter {...} {...}</code> 1 KEY 2 BEFEHL
<code>\setexpansion [^{.}]</code> * NAME OPT
<code>\setextrafontkerns [^{.}]</code> * zadny min max mixed reset OPT
<code>\setfirstline [^{.}]</code> * NAME OPT
<code>\setfirstpasscharacteralign</code>
<code>\setflag {...}</code> * NAME
<code>\setfont ...</code> * FONT
<code>\setfontcolorscheme [^{.}]</code> * NAME
<code>\setfontfeature {...}</code> * NAME
<code>\setfontsolution [^{.}]</code> * NAME
<code>\setfontstrut</code>
<code>\setfractions</code>
<code>\setglobalscript [^{.}]</code> * hangul hanzi nihongo ethiopic thai test NAME

\setgmeasure {...} {...} 1 NAME 2 DIMENSION
\setgvalue {...} {...} 1 NAME 2 CONTENT
\setgvariable {...} {...} {...} 1 NAME 2 KEY 3 VALUE
\setgvariables [...] ¹ [...,... ² ...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
\sethboxregister . ¹ ... {...} ² 1 CSNAME NUMBER 2 CONTENT
\sethyphenatedurlafter {...} [*] * TEXT
\sethyphenatedurlbefore {...} [*] * TEXT
\sethyphenatedurlnormal {...} [*] * TEXT
\sethyphenationfeatures [..., [*] ...] OPT * NAME reset
\setcharacteralign {...} ¹ {...} ² 1 NUMMER 2 TEXT number->TEXT text->TEXT
\setcharacteraligndetail {...} ¹ {...} ² {...} ³ {...} ⁴ 1 NUMMER 2 TEXT number->TEXT text->TEXT 3 DIMENSION 4 DIMENSION
\setcharactercasing [...] [*] * reset SLOVO slovo Slovo Slova kapitalky Kapitalky nahodny mixed camel Camel kap Kap
\setcharactercleaning [...] [*] * reset 1
\setcharacterkerning [...] [*] * reset NAME
\setcharacterspacing [...] [*] * reset NAME
\setcharacterstripping [...] [*] * reset 1

\setcharstrut {...} * TEXT
\setinitial [...] [...] [...] [...] [...] 1 NAME OPT OPT 2 inherits: \setupinitial
\setinjector [...] [...] [...] [...] 1 NAME 2 NUMMER 3 BEFEHL
\setinteraction [...] * skryte NAME
\setinterfacecommand [...] [...] 1 NAME 2 NAME
\setinterfaceconstant [...] [...] 1 NAME 2 NAME
\setinterfaceelement [...] [...] 1 NAME 2 NAME
\setinterfacemessage [...] [...] [...] 1 NAME 2 titul NAME NUMMER 3 TEXT
\setinterfacevariable [...] [...] 1 NAME 2 NAME
\setinternalrendering [...] [...] [...] 1 NAME 2 auto embed 3 CONTENT
\setitaliccorrection [...] * ano ne reset male sredni velke
\setJSpreamble [...] [...] 1 NAME 2 CONTENT
\setlayer [...] [...] [...] [...] [...] 1 NAME OPT OPT 2 vlevo vpravo sude liche 3 inherits: \setuplayer 4 CONTENT
\setlayerframed [...] [...] [...] [...] [...] 1 NAME OPT OPT 2 inherits: \setuplayer 3 inherits: \nastavoramovani 4 CONTENT

<pre> \setlayerframed [¹...] [²...,..._{OPT}...] {...³} 1 NAME 2 inherits: \setuplayerinherits: \nastavoramovani 3 CONTENT </pre>
<pre> \setlayertext [¹...] [²...,..._{OPT}...] [³...,..._{OPT}...] {...⁴} 1 NAME 2 inherits: \setuplayer 3 zarovnani = inherits: \nastavzarovnani sirka = DIMENSION pismeno = STYLE BEFEHL barva = COLOR 4 TEXT </pre>
<pre> \setlinefiller [...[*]] * filler NAME </pre>
<pre> \setlineprofile [...[*]] * NAME </pre>
<pre> \setlocalalignanchor {...¹} ...² ...³ {...⁴} 1 NAME 2 NUMMER 3 NUMMER 4 r vpravo c m nastred </pre>
<pre> \setlocalanchoring </pre>
<pre> \setlocalhsize [...[*]] * [-+]DIMENSION _{OPT} </pre>
<pre> \setlocalmarkanchor {...¹} ...² ...³ 1 NAME 2 NUMMER 3 NUMMER </pre>
<pre> \setlocalscript [...[*]] * hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \setlocalshowmakeup </pre>
<pre> \setlocalsyncanchor {...¹} ...² ...³ 1 NAME 2 NUMMER 3 NUMMER </pre>
<pre> \setluatable \.¹... {...²} 1 CSNAME 2 CONTENT </pre>
<pre> \setMPlayer [¹...] [²...] [³...,..._{OPT}...] {...⁴} 1 NAME 2 NAME 3 inherits: \setuplayer 4 CONTENT </pre>
<pre> \setMPpositiongraphic {...¹} {...²} {...³...,..._{OPT}...} 1 NAME 2 NAME 3 KEY = VALUE </pre>

$\backslash\text{setMPpositiongraphicrange}$ $\{...\}^1$ $\{...\}^2$ $\{...\}^3$ $\{...\}^4_{\text{OPT}}$ 1 NAME 2 NAME 3 NAME 4 KEY = VALUE
$\backslash\text{setMPtext}$ $\{...\}^1$ $\{...\}^2$ 1 NAME 2 TEXT
$\backslash\text{setMPvariable}$ $[...]^1$ $[...]^2$ 1 NAME 2 KEY = VALUE
$\backslash\text{setMPvariables}$ $[...]^1$ $[...]^2_{\text{OPT}}$ 1 NAME 2 KEY = VALUE
$\backslash\text{setmainbodyfont}$
$\backslash\text{setmainlineprofile}$
$\backslash\text{setmainparbuilder}$ $[...]^*$ * implicitni oneline basic NAME
$\backslash\text{setmarker}$ $[...]^1$ $[...]^2$ 1 NAME 2 NUMMER
$\backslash\text{setmarking}$ $[...]^1$ $\{...\}^2$ 1 BESCHRIFTUNG 2 TEXT
$\backslash\text{setmathgroupset}$ $[...]^*$ * NAME
$\backslash\text{setmathmatrixanchoring}$ $[...]^*$ * ano obe
$\backslash\text{setmathstyle}$ $\{...\}^*$ * obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME
$\backslash\text{setmeasure}$ $\{...\}^1$ $\{...\}^2$ 1 NAME 2 DIMENSION
$\backslash\text{setmessagetext}$ $\{...\}^1$ $\{...\}^2$ 1 NAME 2 NAME NUMMER
$\backslash\text{setmode}$ $\{...\}^*$ * NAME
$\backslash\text{setmxscale}$
$\backslash\text{setmxxscale}$
$\backslash\text{setnostrut}$

$\backslash\text{setnote}$ $[...^1]$ $[...^2,...]$ $\{...^3\}$ 1 NAME 2 REFERENCE 3 TEXT
$\backslash\text{setnotetext}$ $[...^1]$ $[...^2,...]$ $\{...^3\}$ 1 NAME 2 REFERENCE 3 TEXT
$\backslash\text{setnotetext}$ $[...^1]$ $[...^2,...]$ 1 NAME 2 titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT
$\backslash\text{setnote}$ $[...^1]$ $[...^2,...]$ 1 NAME 2 titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT
$\backslash\text{setobject}$ $\{...^1\}$ $\{...^2\}$ $\backslash...^3$ $\{...^4\}$ 1 NAME 2 NAME 3 CSNAME 4 CONTENT
$\backslash\text{setoldstyle}$
$\backslash\text{setoverloads}$ $[...^*]$ * NAME
$\backslash\text{setpagelooseness}$ $[...^*]$ * NUMMER
$\backslash\text{setpagelooseness}$ $[...^*,...]$ * radky = DIMENSION vyska = DIMENSION natahnout = DIMENSION shrink = DIMENSION
$\backslash\text{setpagereference}$ $\{...^1\}$ $\{...^2,...\}$ 1 NAME 2 REFERENCE
$\backslash\text{setpagestate}$ $[...^1]$ $[...^2]$ 1 NAME 2 NAME NUMBER
$\backslash\text{setpagestaterealpageno}$ $\{...^1\}$ $\{...^2\}$ 1 NAME 2 NAME NUMBER
$\backslash\text{setparagraphfreezing}$
$\backslash\text{setparagraphshape}$ $[...^*]$ * NAME

\setpenalties \ ¹ ... { ² ...} { ³ ...} 1 CSNAME 2 NUMMER 3 NUMMER
\setpercentdimen { ¹ ...} { ² ...} 1 DIMENSION CSNAME 2 DIMENSION NUMMER%
\setperiodkerning [[*] ...] * reset NAME
\setposition { [*] ...} * NAME
\setpositionbox { ¹ ...} \ ² ... { ³ ...} 1 NAME 2 CSNAME 3 CONTENT
\setpositiondata { ¹ ...} { ² ...} { ³ ...} { ⁴ ...} 1 NAME 2 DIMENSION 3 DIMENSION 4 DIMENSION
\setpositiondataplus { ¹ ...} { ² ...} { ³ ...} { ⁴ ...} { ⁵ ...,...} 1 NAME 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 TEXT
\setpositiononly { [*] ...} * NAME
\setpositionplus { ¹ ...} { ² ...,...} \ ³ ... { ⁴ ...} 1 NAME 2 TEXT 3 CSNAME 4 CONTENT
\setpositionstrut { [*] ...} * NAME
\setprofile [[*] ...] * zadny fixne striktni halffixed quarterfixed eightsfixed NAME
\setrandomseed { [*] ...} * NUMMER
\setreference [..., ¹ ...] [..., ² ...,...] 1 REFERENCE 2 KEY = VALUE
\setreferencedobject { ¹ ...} { ² ...} \ ³ ... { ⁴ ...} 1 NAME 2 NAME 3 CSNAME 4 CONTENT

```

\setregisterentry [...] [...] [...]
1 NAME
2 popisek = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
processors = PROCESSOR
keys:1 = TEXT
keys:2 = TEXT
keys:3 = TEXT
entries:1 = TEXT
entries:2 = TEXT
entries:3 = TEXT
alternativa = TEXT
processors:1 = PROCESSOR
processors:2 = PROCESSOR
processors:3 = PROCESSOR
3 KEY = VALUE

```

```

\setreplacements [...] [...]
1 reset NAME
2 NAME

```

```

\setrigidcolumnbalance ...
* CSNAME NUMMER

```

```

\setrigidcolumnhsize {...} {...} {...}
1 DIMENSION
2 DIMENSION
3 NUMMER

```

```

\setscaleddirectsymbolicfont {...} {...} {...}
1 DIMENSION
2 NUMMER
3 FONT

```

```

\setscaledstyledsymbolicfont {...} {...} {...}
1 DIMENSION
2 NUMMER
3 FONT

```

```

\setscript [...]
* hangul hanzi nihongo ethiopic thai test NAME

```

```

\setsecondpasscharacteralign

```

```

\setsectionblock [...] [...]
1 NAME
2 zalozka = TEXT

```

```

\setsimplecolumnshsize [...]
* n = NUMMER
sirka = DIMENSION
vzdalenost = DIMENSION
radky = NUMMER

```

```

\setsmallbodyfont

```

```

\setsmallcaps

```

```

\setstackbox {...} {...} {...}
1 NAME
2 NAME
3 CONTENT

```

<pre> \setstructurepageregister [.¹.] [...,²...,...] [...,³...,...] 1 NAME 2 popisek = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT processors = PROCESSOR keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternativa = TEXT processors:1 = PROCESSOR processors:2 = PROCESSOR processors:3 = PROCESSOR 3 KEY = VALUE </pre>	OPT
\setstrut	
<pre> \setstyledsymbolicfont {.*.} * FONT </pre>	
\setsuperiors	
<pre> \setsystemmode {.*.} * NAME </pre>	
\settabular	
<pre> \settaggedmetadata [...,[*]...,...] * KEY = VALUE </pre>	
\settestcrlf	
<pre> \settextcontent [...]¹ [...]² [...]³ [...]⁴ [...]⁵ 1 vrsek zahlavi text upati spodek 2 text marginalie hrana 3 vlevo nastred vpravo 4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL 5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL </pre>	OPT OPT
<pre> \settightobject {.¹.} {.².} \.³. {.⁴.} 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>	
<pre> \settightreferencedobject {.¹.} {.².} \.³. {.⁴.} 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>	
\settightstrut	
<pre> \settightunreferencedobject {.¹.} {.².} \.³. {.⁴.} 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>	
<pre> \settokenlist [...]¹ {.².} 1 NAME 2 TEXT </pre>	

\settransliteration [...] * NAME
\settransliteration {...} * NAME
\settrialtypesetting
\setuevalue {...} {...} 1 NAME 2 CONTENT
\setugvalue {...} {...} 1 NAME 2 CONTENT
\setunreferencedobject {...} {...} \... {...} 1 NAME 2 NAME 3 CSNAME 4 CONTENT
\setupadaptive [..., ¹ ...] [..., ² ...,...] 1 NAME 2 setups = NAME foregroundstyle = STYLE BEFEHL foregroundcolor = COLOR strut = ano ne metoda = NUMMER barva = COLOR alternativa = NAME tloustkalinky = DIMENSION marginalie = DIMENSION natahnout = DIMENSION shrink = DIMENSION misto = vlevo vpravo
\setupalignpass [...] * zadny granular decent quality NAME
\setupalternativestyles [..., [*] ...,...] * metoda = normalni auto
\setupattachment [..., ¹ ...] [..., ² ...,...] 1 NAME 2 titul = TEXT podtitulek = TEXT autor = TEXT soubor = FILE jmeno = NAME buffer = BUFFER typ = NAME status = start stop metoda = normalni skryte symbol = Graph Paperclip Pushpin Default sirka = prizpusobive DIMENSION vyska = prizpusobive DIMENSION hloubka = prizpusobive DIMENSION barva = COLOR textlayer = NAME misto = levahrana pravahrana naokraji lev yokraj pravyokraj text vysoko zadny vzdalenost = DIMENSION
\setupattachments [..., ¹ ...] [..., ² ...,...] 1 NAME 2 inherits: \setupattachment

\setupbackend [...,¹...]

* export = ano FILE
xhtml = FILE
soubor = FILE
intent = Coated_FOGRA39_(ISO_12647-2:2004) GRACoL2006_Coated1v2.icc ISO_Coated_v2_300%(ECI) ISO_Coated_v2_(ECI)
ISOnewspaper26v4 ISOnewspaper26v4_gr ISO_Uncoated ISO_Uncoated_Yellowish ISO_Web_Coated Japan_Color_2001_Coated
Japan_Color_2002_Newspaper Japan_Web_Coated_(Ad) SNAP_2007 SWOP2006_Coated3v2.icc SWOP2006_Coated5v2.icc
Uncoated_FOGRA29_(ISO_12647-2:2004) Web_Coated_FOGRA28_(ISO_12647-2:2004) PSR_LWC_PLUS_V2_PT
PSR_LWC_STD_V2_PT PSR_SC_PLUS_V2_PT PSR_SC_STD_V2_PT PSRgravureMF
mezera = ano ne
hyphen = ano ne
xmpfile = FILE
formatovat = version implicitni PDF/X-1a:2001 PDF/X-1a:2003 PDF/X-3:2002 PDF/X-3:2003 PDF/X-4 PDF/X-4p PDF/X-5g
PDF/X-5pg PDF/X-5n PDF/A-1a:2005 PDF/A-1b:2005 PDF/A-2a PDF/A-3a PDF/UA-1
uroven = NUMMER
volba = vzdy nikdy
profile = FILE

\setupbalancing [...,¹...] [...,²...]

1 NAME OPT
2 vzdalenost = DIMENSION
vyska = DIMENSION
pred = BEFEHL
po = BEFEHL
setups = NAME
zarovnani = inherits: \nastavzarovnani

\setupbar [...,¹...] [...,²...]

1 NAME OPT
2 barva = COLOR
pokracovat = ano ne vse vzdy
prazdne = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
order = popredi pozadi
tloustkalinky = DIMENSION
metoda = NUMMER
offset = NUMMER DIMENSION
vyska = DIMENSION
hloubka = DIMENSION
dy = NUMMER
max = NUMMER
foregroundstyle = STYLE BEFEHL
foregroundcolor = COLOR
mp = NAME
vlevo = TEXT
vpravo = TEXT
opakovat = ano ne
text = TEXT

\setupbars [...,¹...] [...,²...]

1 NAME OPT
2 inherits: \setupbar

\setupbleeding {...,¹...} [...,²...]

1 NAME OPT
2 define = ano ne
sirka = DIMENSION
vyska = DIMENSION
offset = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
misto = t b l r bl lb br rb tl lt tr rt
natahnout = ano ne
stranka = ano ne

```

\setupbookmark    [...,..*...,...]
*   sila          = ano ne
    cislo         = ano ne
    numberseparatorset = NAME
    numberconversionset = NAME
    numberstarter  = BEFEHL
    numberstopper  = BEFEHL
    numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
    aktualni       =
    sectionblock   = ano ne

```

```

\setupboxanchor    [...,..*...,...]
*   xoffset = DIMENSION
    yoffset = DIMENSION
    target  = radex vyska podlehloubky vlevo left,height left,top left,depth left,bottom vpravo right,height right,top
             right,depth right,bottom nastred middle,height middle,top middle,depth middle,bottom middle,left
             middle,right
    source  = radex vyska podlehloubky vlevo left,height left,top left,depth left,bottom vpravo right,height right,top
             right,depth right,bottom nastred middle,height middle,top middle,depth middle,bottom middle,left
             middle,right

```

```

\setupboxanchorcontent [...,..1...] [...,..2...,...]
1  NAME OPT
2  xoffset = DIMENSION
    yoffset = DIMENSION
    roh     = radex vyska podlehloubky vlevo left,height left,top left,depth left,bottom vpravo right,height
             right,top right,depth right,bottom nastred middle,height middle,top middle,depth middle,bottom
             middle,left middle,right
    misto    = radex vyska podlehloubky vlevo left,height left,top left,depth left,bottom vpravo right,height
             right,top right,depth right,bottom nastred middle,height middle,top middle,depth middle,bottom
             middle,left middle,right
    vzdalenost = DIMENSION
    pomlcka    = NUMMER
    sipka      = ano ne reverse obe
    alternativa = vlevo nastred vpravo vrsek spodek
    text       = TEXT
    tloustkalinky = DIMENSION
    barvalinky  = COLOR
    mp         = NAME
    stranka    = ano ne

```

```

\setupboxexport    [...,..*...,...]
*   buffer = NAME
    soubor  = FILE

```

```

\setupbtx    [...,..1...] [...,..2...,...]
1  NAME OPT
2  specification = implicitni apa aps NAME
    dataset      = implicitni NAME
    prikaz       = \...#1
    vlevo        = BEFEHL
    vpravo       = BEFEHL
    authorconversion = normalni normalshort normalinverted invertedshort short
    etallimit    = NUMMER
    etaldisplay  = NUMMER
    etaloption   = posledni
    predel       = initials
    interakce    = start stop cislo text stranka vse
    alternativa  = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                  authornum authoryear
    sorttype     = normalni reverse
    compress     = ano ne
    implicitni   = implicitni NAME
    pismeno      = STYLE BEFEHL
    barva        = COLOR

```

```

\setupbtxdataset    [...,..1...] [...,..2...,...]
1  NAME OPT
2  language = SPRACHE

```

```

\setupbtxlist    [...,..1...] [...,..2...,...]
1  NAME OPT
2  inherits: \nastavseznam

```

\setupbtregister [...¹,...] [...²,...]

1 NAME OPT
2 status = start stop
dataset = NAME
field = keyword range cislostranky autor
register = NAME
metoda = once
alternativa = normalshort invertedshort
pismo = STYLE BEFEHL
barva = COLOR

\setupbtxrendering [...¹,...] [...²,...]

1 NAME OPT
2 statustextu = start stop
pagestate = start stop
oddelovac = BEFEHL
kriterium = predchozi cite zde vse zadny
filter = TEXT
specification = NAME
titul = TEXT
pred = BEFEHL
po = BEFEHL
dataset = NAME
metoda = dataset popisak sila lokalne globalne zadny
sorttype = short dataset seznam odkaz uzito implicitni cite rejstrik
opakovat = ano ne
group = NAME
cislovani = ano ne num rejstrik tag short stranka
soubor = FILE

\setupbtx [...]

* NAME

\setupbutton [...¹,...] [...²,...]

1 NAME OPT
2 status = start stop
stejnastranka = ano ne prazdne zadny normalni implicitni
pismo = STYLE BEFEHL
barva = COLOR
kontrastnibarva = COLOR
alternativa = skryte
inherits: \nastavoramovani

\setupcollector [...¹,...] [...²,...]

1 NAME OPT
2 rotace = vlevo vpravo uvnitr vnejsi NUMMER
roh = vlevo nastred vpravo vrsek spodek
x = DIMENSION
y = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
misto = vlevo nastred vpravo vrsek spodek radek l c r m t b g
status = start stop

\setupcolumnset [...¹,...] [...²,...]

1 NAME OPT
2 radky = NUMMER
n = NUMMER
nvlevo = NUMMER
nvpravo = NUMMER
status = start stop
vzdalenost = DIMENSION
sirka = DIMENSION
stranka = inherits: \strana
maxsirka = DIMENSION
maxvyska = DIMENSION
limit = NUMMER
language = SPRACHE
region = NAME
smer = normalni reverse
misto = vlevo vpravo
zarovnani = inherits: \nastavzarovnani
inherits: \nastavoramovani

\setupcolumnsetarea [...¹,...] [...²,...]

1 NAME OPT
2 typ = sheet
sheet = NUMBER
status = opakovat stop
x = NUMBER
y = NUMBER
nx = NUMBER
ny = NUMBER
text = TEXT
sirka = DIMENSION
vyska = DIMENSION
clipoffset = DIMENSION
levyoffset = DIMENSION
pravyoffset = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR
inherits: \nastavoramovani

\setupcolumnsetareatext [...¹] [...²]

1 NAME
2 TEXT

\setupcolumnsetlines [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMBER
3 NUMBER
4 NUMBER

\setupcolumnsetspan [...¹,...] [...²,...]

1 NAME OPT
2 n = NUMBER
pred = BEFEHL
po = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR
inherits: \nastavoramovani

\setupcolumnsetstart [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMBER
3 NUMBER
4 NUMBER

\setupcombination [...¹,...] [...²,...]

1 NAME OPT
2 nx = NUMBER
ny = NUMBER
sirka = prizpusobive DIMENSION
vyska = prizpusobive DIMENSION
misto = vlevo nastred vpravo vrsek spodek
vzdalenost = DIMENSION
alternativa = popisek text
zarovnani = inherits: \nastavzarovnani
pokracovat = ano ne
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR
metoda = rovnice
strut = ano ne

\nastaveniPRIKAZ [...¹,...] [...²,...]

1 NAME OPT
2 KEY = VALUE

\setupcomparingtext [...¹,...] [...²,...]

1 NAME OPT
2 metoda = pismo slovo
barva = COLOR

```

\setupcounter    [...,1...]    [...,2...,...]
1  NAME          OPT
2  start          = NUMBER
   cislo          = NUMBER
   counter        = NAME
   metoda         = stranka
   status         = start stop
   zpusob         = bystranka byblock bytext byhlavicka byABSCHNITT
   prefix         = ano ne
   prefixseparatorset = NAME
   prefixconversion = NAME
   prefixconversionset = NAME
   prefixstarter  = BEFEHL PROCESSOR->BEFEHL
   prefixstopper  = BEFEHL PROCESSOR->BEFEHL
   prefixset      = NAME
   prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
                        aktualni
   numberorder    = reverse
   numberseparatorset = NAME
   numberconversion = NAME
   numberconversionset = NAME
   numberstarter  = BEFEHL PROCESSOR->BEFEHL
   numberstopper  = BEFEHL PROCESSOR->BEFEHL
   numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
   typ            = prvni predchozi dalsi posledni cislo
   kriterium      = striktni pozitiv vse
   prefixconnector = BEFEHL PROCESSOR->BEFEHL

```

```

\setupcurrentPRIKAZ    [...,*...,...]
* KEY = VALUE

```

```

\setupdataset    [...,1...]    [...,2...,...]
1  NAME          OPT
2  prodleva      = ano ne

```

```

\setupdelimitedtext [...,1...]    [...,2...,...]
1  NAME NAME:NUMBER OPT
2  pred          = BEFEHL
   po            = BEFEHL
   language      = lokalne globalne SPRACHE
   metoda       = font text odstavec
   opakovat     = ano ne
   misto        = text odstavec marginalie
   vlevo        = BEFEHL
   stredni      = BEFEHL
   vpravo       = BEFEHL
   nextleft     = BEFEHL
   nextright    = BEFEHL
   mezerapred   = inherits: \preskoc
   mezeraza     = inherits: \preskoc
   levyokraj    = ano ne standardni DIMENSION
   pravyokraj   = ano ne standardni DIMENSION
   odsazovani   = inherits: \nastavodsazovani
   odsadpristi  = ano ne auto
   pismeno      = STYLE BEFEHL
   barva        = COLOR
   stylsymboly  = STYLE BEFEHL
   barvasymbolu = COLOR
   zarovnani    =

```

\setupdescription [...,¹...] [...,²...,...]

```

1  NAME                      OPT
2  titul                    = ano ne
   define                   = ano ne
   uroven                   = NUMMER
   text                     = TEXT
   headcommand              = \...#1
   pred                     = BEFEHL
   po                       = BEFEHL
   mezi                     = BEFEHL
   alternativa              = vlevo vpravo naokraj i vlevo i vpravo
                             marginalie levýokraj pravýokraj innermargin outermargin
                             semknuto visici vrsek prázdné příkaz NAME
   zarovnani                = inherits: \nastavzarovnani
   headalign                 = inherits: \nastavzarovnani
   odsazovani               = inherits: \nastavodsazovani
   obrazovka                = ano ne
   odsadpristi              = ano ne auto
   sirka                    = prizpusobive široky radek DIMENSION
   vzdalenost               = zadny DIMENSION
   natahnout                = NUMMER
   shrink                   = NUMMER
   zaveseni                 = prizpusobive široky zadny marginalie NUMMER
   closesymbol              = BEFEHL
   closecommand             = \...#1
   expanzen                 = ano ne xml
   referenceprefix          = + - TEXT
   vzor                     = TEXT
   marginalie               = ano ne standardni DIMENSION
   pismo                    = STYLE BEFEHL
   barva                    = COLOR
   stylhlavicky             = STYLE BEFEHL
   barvahlavicky            = COLOR
   zarovnejtitul            = ano ne
   headindenting            = ano ne
   prodleva                 = text

```

\setupdirections [...,^{*}...,...]

```

*  bidi    = zap vyp lokalne globalne
   metoda  = jedna dve implicitni
   fences  = ano ne
   break   = obe pred

```

\setupdocument [...,¹...] [...,²...,...]

```

1  NAME                      OPT
2  pred                     = BEFEHL
   po                       = BEFEHL
   metadata:author          = TEXT
   metadata:title           = TEXT
   metadata:subject         = TEXT
   metadata:keywords        = TEXT
   KEY                      = VALUE

```

\setupeffect [...,¹...] [...,²...,...]

```

1  NAME                      OPT
2  metoda                   = zadny prikaz
   natahnout                = NUMMER
   tloustkalinky            = DIMENSION
   alternativa              = normalni uvnitr vnejsi obe skryte orez natahnout

```

```

\setupenumeration    [...,1...]    [...,2...,...]
1  NAME              OPT
2  titul              = ano ne
   cislo              = ano ne
   ciselny prikaz     = \...#1
   stylcisla          = STYLE BEFEHL
   barvacisla         = COLOR
   vzdalenosttitulek  = DIMENSION
   styltitulek        = STYLE BEFEHL
   barvatitulek       = COLOR
   titlecommand       = \...#1
   titleleft         = BEFEHL
   titleright        = BEFEHL
   vlevo              = BEFEHL
   vpravo             = BEFEHL
   symbol             = BEFEHL
   starter            = BEFEHL
   predel             = BEFEHL
   propojeni          = NAME
   counter            = NAME
   define             = ano ne
   popisek            = NAME
   uroven             = NUMMER
   text              = TEXT
   headcommand       = \...#1
   pred              = BEFEHL
   po                 = BEFEHL
   mezi              = BEFEHL
   alternativa       = vlevo vpravo naokrajivlevo ivpravo marginalie lev yokraj prav yokraj innermargin outermargin
                     semknuto visici vrsek prazdne prikaz NAME
   zarovnnani         = inherits: \nastavzarovnnani
   headalign          = inherits: \nastavzarovnnani
   odsazovani         = inherits: \nastavodsazovani
   obrazovka          = ano ne
   odsadpristi        = ano ne auto
   sirka              = prizpusobive siroky radek DIMENSION
   vzdalenost         = zadny DIMENSION
   natahnout          = NUMMER
   shrink             = NUMMER
   zaveseni           = prizpusobive siroky zadny marginalie NUMMER
   closesymbol        = BEFEHL
   closecommand       = \...#1
   expanzen           = ano ne xml
   referenceprefix    = + - TEXT
   vzor               = TEXT
   marginalie         = ano ne standardni DIMENSION
   pismo              = STYLE BEFEHL
   barva              = COLOR
   stylhlavicky       = STYLE BEFEHL
   barvahlavicky      = COLOR
   zarovnejtitul      = ano ne
   headindenting      = ano ne
   prodleva           = text
   inherits: \setupcounter

```

```

\setupenv    [...,*...,...]
*  set       = BEFEHL
   reset     = BEFEHL
   KEY       = VALUE

```

```

\setupexpansion    [...,1...]    [...,2...,...]
1  NAME              OPT
2  krok              = NUMMER
   natahnout         = NUMMER
   shrink            = NUMMER

```

```

\setupexport      [...,*...,...]
*   zarovnani      = flushleft nastred flushright normalni
    zakladnifont    = DIMENSION
    sirka           = DIMENSION
    titul           = TEXT
    podtitulek      = TEXT
    autor           = TEXT
    alternativa     = html div
    properties      = ano ne
    hyphen          = ano ne
    cssfile         = FILE
    prvnistranka    = FILE
    poslednistrana  = FILE

```

```

\setupexternalfigure  [...,1...]  [...,*2...,...]
1  NAME              OPT
2  sirka              = DIMENSION
    vyska             = DIMENSION
    popisek           = NAME
    stranka           = NUMMER
    objekt            = ano ne
    prefix            = TEXT
    metoda            = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
    controls          = ano ne
    nahled            = ano ne
    mask              = zadny NAME
    rozliseni         = NUMMER
    barva             = COLOR
    cmyk              = ano ne auto
    gray              = ano ne auto
    arguments         = TEXT
    opakovat          = ano ne
    faktor            = prizpusobive siroky max auto implicitni
    hfaktor           = prizpusobive siroky max auto implicitni
    sfaktor           = prizpusobive siroky max auto implicitni
    maxsirka          = DIMENSION
    maxvyska          = DIMENSION
    equalwidth        = DIMENSION
    equalheight       = DIMENSION
    meritko           = NUMMER
    xmeritko          = NUMMER
    ymeritko          = NUMMER
    s                 = NUMMER
    sx                = NUMMER
    sy                = NUMMER
    radky             = NUMMER
    misto             = lokalne globalne implicitni
    adresar           = PATH
    volba             = test ramecek prazdne
    foregroundcolor    = COLOR
    reset             = ano ne
    pozadi            = barevne popredi NAME
    ramecek           = zap vyp
    barvapozadi       = COLOR
    xmax              = NUMMER
    ymax              = NUMMER
    ramecky           = zap vyp
    interakce         = ano vse zadny odkaz layer zalozka
    zakladnifont      = DIMENSION
    comment           = BEFEHL TEXT
    velikost          = zadny media crop trim art
    cache             = PATH
    resources         = PATH
    obrazovka         = FILE
    konverze          = TEXT
    order             = LISTE
    crossreference     = ano ne NUMMER
    transform         = auto NUMMER
    userpassword       = TEXT
    ownerpassword     = TEXT
    orientation       = NUMMER
    compact           = ano ne merge tikz NAME
    metadata          = ano ne stranka document
    defaultwidth      = DIMENSION
    defaultheight     = DIMENSION
    range             = zadny NAME

```

```

1  NAME                                OPT
2  mezi                                = BEFEHL
   stranka                            = inherits: \strana
   spaceinbetween                     = inherits: \preskoc
   pismoeno                           = STYLE BEFEHL
   barva                              = COLOR
   sirka                              = prizpusobive ramecek DIMENSION
   inherits: \nastavoramovani

```

```

1  NAME                                OPT
2  category = NAME
   inherits: \setupfieldcategory

```

1	NAME	OPT
2	start	= NUMMER
	pismo	= STYLE BEFEHL
	barva	= COLOR
	typ	= radio pod text radek push check signature
	values	= TEXT
	implicitni	= TEXT
	barvameckupole	= COLOR
	barvapozadipole	= COLOR
	sirka	= DIMENSION
	vyska	= DIMENSION
	hloubka	= DIMENSION
	zarovnani	= vlevo nastred vpravo flushleft center flushright
	n	= NUMMER
	symbol	= NAME
	fieldlayer	= NAME
	volba	= pouze procteni pozadovane chranene tridene nedostupne nocheck fixne soubor skryte tisknutelne auto
	klikuvnitr	= REFERENCE
	klikvne	= REFERENCE
	oblastuvnitr	= REFERENCE
	oblastvne	= REFERENCE
	klavesapo	= REFERENCE
	formatovat	= REFERENCE
	validovat	= REFERENCE
	pocitat	= REFERENCE
	focusin	= REFERENCE
	focusout	= REFERENCE
	openpage	= REFERENCE
	closepage	= REFERENCE

```
1 NAME OPT
2 inherits: \nastavoramovaniinherits: \setupfieldcategory
```

```
1  NAME OPT
2  inherits: \nastavoramovani
```

```

1  NAME                                OPT
2  pred                                = BEFEHL
   po                                  = BEFEHL
   mezi                               = BEFEHL
   vzdaleness                         = DIMENSION
   alternativa = reset popisovamek ramecek horizontalne vertikalne
   inherits: \nastavoramovani

```

\setupfiller [...¹,...] [...²,...]

1 NAME OPT
2 levyokraj = DIMENSION
pravyokraj = DIMENSION
vlevo = BEFEHL
vpravo = BEFEHL
alternativa = symbol natahnout linka mezera
metoda = lokalne globalne nastred siroky
sirka = DIMENSION
vyska = DIMENSION
hloubka = DIMENSION
offset = DIMENSION
vzdalenost = DIMENSION
zarovnani = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
symbol = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR

\setupfirstline [...¹,...] [...²,...]

1 NAME OPT
2 n = NUMMER
alternativa = implicitni radek slovo
pismo = STYLE BEFEHL
barva = COLOR

\setupfittingpage [...¹,...] [...²,...]

1 NAME OPT
2 pagestate = start stop
prikaz = \...#1
marginalie = stranka
meritko = NUMMER
papir = auto implicitni NAME
instance = metafun minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost
nofun scaledpost doublepost binarypost decimalpost simplefun
stacking = TEXT
popisek = TEXT
inherits: \nastavoramovani

\setupfloatframed [...¹,...] [...²,...]

1 NAME OPT
2 inherits: \nastavoramovani

\setupfontexpansion [...¹] [...²,...]

1 NAME
2 vector = NAME
faktor = NUMMER
natahnout = NUMMER
shrink = NUMMER
krok = NUMMER

\setupfontprotrusion [...¹] [...²,...]

1 NAME
2 vector = NAME
faktor = NUMMER
vlevo = NUMMER
vpravo = NUMMER

\setupfonts [...^{*},...]

* language = ne auto
serif = FONT
sans = FONT
mono = FONT

\setupfontsolution [...¹,...] [...²,...]

1 NAME OPT
2 goodies = FILE
solution = NAME
less = NAME
more = NAME
metoda = preroll split normalni reverse nahodny
kriterium = NUMMER

\setupforms [...¹...]

* metoda = XML HTML PDF
export = ano ne

\setupformula [...¹...] [...²...]

1 NAME OPT
2 inherits: \nastavrovnice

\setupformulaframed [...¹...] [...²...]

1 NAME OPT
2 inherits: \nastavoramovani

\setupframedcontent [...¹...] [...²...]

1 NAME OPT
2 vlevo = BEFEHL
vpravo = BEFEHL
levyoffset = DIMENSION
pravyoffset = DIMENSION
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
korekceradku = ano ne
inherits: \nastavoramovani

\setupframedtable [...¹...] [...²...]

1 NAME OPT
2 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
vzdalenost = DIMENSION
inherits: \nastavoramovani

\setupframedtablecolumn [...¹...] [...²...] [...³...]

1 NAME OPT
2 NUMMER kazdy
3 inherits: \nastavoramovani

\setupframedtablerow [...¹...] [...²...] [...³...]

1 NAME OPT
2 NUMMER kazdy
3 inherits: \nastavoramovani

\setupframedtext [...¹...] [...²...]

1 NAME OPT
2 vlevo = BEFEHL
vpravo = BEFEHL
vnitrni = BEFEHL
misto = vlevo vpravo nastred zadny
korekcehloubky = zap vyps
zakladnifont = inherits: \nastavzakladnifont
odsazovani = inherits: \nastavodsazovani
pismo = STYLE BEFEHL
barva = COLOR
inherits: \nastavoramovaniinherits: \setupplacement

\setupglobalreferenceprefix [...^{*}...]

* + - TEXT

\setuphanging [...^{*}...]

* vzdalenost = DIMENSION
n = NUMMER
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
misto = vlevo vpravo

\setupheadalternative [...¹...] [...²...]

1 NAME OPT
2 alternativa = horizontalne vertikalne nekde
renderingsetup = NAME


```
\setuphelp    [...,1...]    [...,2...,...]
1  NAME              OPT
2  inherits: \nastavoramovani
```

```
\setuphigh    [...,1...]    [...,2...,...]
1  NAME              OPT
2  vzdalenost  =  DIMENSION
   up          =  DIMENSION
   pismo       =  STYLE BEFEHL
   barva       =  COLOR
```

```
\setuphighlight [...,1...]    [...,2...,...]
1  NAME              OPT
2  prikaz      =  ano ne
   language    =  SPRACHE
   pismo       =  STYLE BEFEHL
   barva       =  COLOR
```

```
\setuphorizontalbox [...,1...]    [...,2...,...]
1  NAME              OPT      OPT
2  sirka        =  max lokalne DIMENSION
   natahnout    =  DIMENSION
   smer         =  normalni reverse lefttoright righttoleft
   xoffset      =  DIMENSION
   yoffset      =  DIMENSION
   pismo       =  STYLE BEFEHL
   barva       =  COLOR
   vlevo       =  BEFEHL
   vpravo      =  BEFEHL
   strut       =  ano ne
```

```
\setuphyphenation [...,*...,...]
* metoda = original tex implicitni hyphenate expanded traditional zadny
hyphens  = ano ne
```

```
\setupcharacteralign [...,*...,...]
* sirkavlevo  =  DIMENSION
  sirkavpravo =  DIMENSION
  leftsample  =  TEXT
  rightsample =  TEXT
  character    =  TEXT number->TEXT text->TEXT
```

```
\setupcharacterkerning [...,1...]    [...,2...,...]
1  NAME              OPT
2  faktor           =  max NUMMER
   sirka            =  DIMENSION
   features         =  NAME
   pismo            =  STYLE BEFEHL
   barva            =  COLOR
```

```
\setupcharacterspacing [...1]    [...2]    [...,3...,...]
1  NAME              OPT
2  NUMMER
3  vlevo             =  NUMMER
   vpravo            =  NUMMER
   alternativa      =  0 1
   language          =  SPRACHE
```

```

\setupchemical    [...1,...]    [...2,...,...]
1  NAME          OPT
2  strut         = ano ne auto kap prizpusobive radek implicitni CHARACTER
   sirka         = prizpusobive zadny NUMMER
   vyska         = prizpusobive zadny NUMMER
   vlevo         = prizpusobive zadny NUMMER
   vpravo        = prizpusobive zadny NUMMER
   vrsek         = prizpusobive zadny NUMMER
   spodek        = prizpusobive zadny NUMMER
   meritko       = male stredni velke normalni NUMMER
   rotace        = NUMMER
   symzarovnani  = auto
   osa           = zap vyp
   barvamecku    = COLOR
   tloustkalinky = DIMENSION
   offset        = DIMENSION
   jednotka      = DIMENSION
   faktor        = NUMMER
   ramecek       = zap vyp
   barvalinky    = COLOR
   zakladnifont  = inherits: \nastavzakladnifont
   velikost      = male stredni velke
   pismo        = STYLE BEFEHL
   barva         = COLOR

```

```

\setupchemicalframed [...1,...]    [...2,...,...]
1  NAME          OPT
2  inherits: \nastavoramovani

```

```

\setupchemistry    [...1,...]    [...2,...,...]
1  NAME          OPT          OPT
2  mezerovani    = inherits: \setupmathspacing
   meritko       = NUMMER
   filter        = ano ne

```

```

\setupindentedtext [...1,...]    [...2,...,...]
1  NAME          OPT
2  pred          = BEFEHL
   po            = BEFEHL
   vzdalenost    = DIMENSION
   vzor          = TEXT
   text          = TEXT
   sirka         = prizpusobive siroky DIMENSION
   oddelovac     = BEFEHL
   pismo        = STYLE BEFEHL
   barva         = COLOR
   stylhlavicky = STYLE BEFEHL
   barvahlavicky = COLOR

```

```

\setupinitial    [...1,...]    [...2,...,...]
1  NAME          OPT
2  n             = NUMMER
   m             = NUMMER
   pred          = BEFEHL
   vzdalenost    = DIMENSION
   hoffset       = DIMENSION
   voffset       = radek DIMENSION
   pismo        = STYLE BEFEHL
   barva         = COLOR
   font          = FONT
   text          = TEXT
   misto         = marginalie text
   metoda       = prvni posledni auto zadny
   pokracovat    = ano ne

```

```

\setupinsertion    [...1,...]    [...2,...,...]
1  NAME          OPT
2  misto         = stranka text sloupce firstcolumn lastcolumn
   anchoring     = auto

```

```

\setupitaliccorrection [...]
* inherits: \setitaliccorrection

```

```

\setupitemgroup  [...1]  [...2,...]  [...3,...]  [...4,...4,...]
1  NAME
2  kazdy NUMMER
3  uvod nointro nahodny pokračovat zhustene autouvod široky text pred po zadnabila marginalie naokraj naokraj
   dotextu headintext uvolnene prizpusobive nofit odstavec spojeno notjoinedup semknuto predel nostopper rozbalene
   opakovat norepeat reverse sloupce prekryv jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky
   NUMMER*semknuto horizontalne NAME
4  pred = BEFEHL
   po = BEFEHL
   mezi = BEFEHL
   predhlavickou = BEFEHL
   pohlavicce = BEFEHL
   textvlevo = BEFEHL
   textvpravo = BEFEHL
   vlevo = BEFEHL
   vpravo = BEFEHL
   faktor = NUMMER
   krok = DIMENSION
   sirka = DIMENSION
   vzdalenost = DIMENSION
   marginalie = ano ne standardni DIMENSION
   levyokraj = ano ne standardni DIMENSION
   pravyokraj = ano ne standardni DIMENSION
   vzdalenostlevehookraje = ano ne standardni DIMENSION
   vzdalenostpravehookraje = ano ne standardni DIMENSION
   zarovnani = inherits: \nastavzarovnani
   odsazovani = inherits: \nastavodsazovani
   start = NUMMER
   symzarovnani = vlevo nastred vpravo flushleft center flushright
   symbol = NAME
   n = NUMMER
   odsadpristi = ano ne auto
   vnitrni = BEFEHL
   prikaz = CSNAME
   polozky = NUMMER
   maxsirka = DIMENSION
   itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   alignsymbol = ano ne
   textdistance = male stredni velke zadny mezera DIMENSION
   oddelovactextu = BEFEHL
   lasttextseparator = BEFEHL
   predelmista = ano ne obrazovka inline
   pismo = STYLE BEFEHL
   barva = COLOR
   stylhlavicky = STYLE BEFEHL
   barvahlavicky = COLOR
   stylsnacky = STYLE BEFEHL
   barvaznacky = COLOR
   stylsymboly = STYLE BEFEHL
   barvasymbolu = COLOR
   mrizka = inherits: \definegridsnapping
   packcriterium = NUMMER
   vzdalenostsloupcu = DIMENSION
   inherits: \setupcounter

```

```

\setupitemgroup [...1,...] [...2,...]
1 NAME NAME:NUMMER OPT
2 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
predhlavickou = BEFEHL
pohlavicce = BEFEHL
textvlevo = BEFEHL
textvpravo = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
faktor = NUMMER
krok = DIMENSION
sirka = DIMENSION
vzdalenost = DIMENSION
volba = uvod nahodny pokracovat zhustene autouvod široky text pred po zadnabila marginalie
naokraj naokraj dotextu headintext uvolnene prizpusobive nofit odstavec spojeno
notjoinedup semknuto predel rozbalene opakovat norepeat reverse sloupce prekryv
jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky NUMMER*semknuto
horizontalne NAME
marginalie = ano ne standardni DIMENSION
levyokraj = ano ne standardni DIMENSION
pravyokraj = ano ne standardni DIMENSION
vzdalenostlevehookraje = ano ne standardni DIMENSION
vzdalenostpravehookraje = ano ne standardni DIMENSION
zarovnani = inherits: \nastavzarovnani
odsazovani = inherits: \nastavodsazovani
start = NUMMER
symzarovnani = vlevo nastred vpravo flushleft center flushright
symbol = NAME
n = NUMMER
odsadpristi = ano ne auto
vnitrni = BEFEHL
prikaz = CSNAME
polozky = NUMMER
maxsirka = DIMENSION
itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
alignsymbol = ano ne
textdistance = male stredni velke zadny mezera DIMENSION
oddelovactextu = BEFEHL
lasttextseparator = BEFEHL
predelmista = ano ne obrazovka inline
pismo = STYLE BEFEHL
barva = COLOR
stylhlavicky = STYLE BEFEHL
barvahlavicky = COLOR
stylsnacky = STYLE BEFEHL
barvaznacky = COLOR
stylsymboly = STYLE BEFEHL
barvasymbolu = COLOR
mrizka = inherits: \definegridsnapping
packcriterium = NUMMER
vzdalenostsloupcu = DIMENSION
inherits: \setupcounter

```

```

\nastaveniITEMGROUP [...] [...] [...]
1 kazdy NUMMER OPT OPT OPT
2 uvod nointro nahodny pokracovat zhustene autouvod široky text pred po zadnabila marginalie naokraj naokraj
dotextu headintext uvolnene prizpusobive nofit odstavec spojeno notjoinedup semknuto predel nostopper rozbalene
opakovat norepeat reverse sloupce prekryv jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky
NUMBER*semknuto horizontalne NAME
3 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
predhlavickou = BEFEHL
pohlavicce = BEFEHL
textvlevo = BEFEHL
textvpravo = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
faktor = NUMMER
krok = DIMENSION
sirka = DIMENSION
vzdalenost = DIMENSION
marginalie = ano ne standardni DIMENSION
levyokraj = ano ne standardni DIMENSION
pravyokraj = ano ne standardni DIMENSION
vzdalenostlevehookraje = ano ne standardni DIMENSION
vzdalenostpravehookraje = ano ne standardni DIMENSION
zarovnani = inherits: \nastavzarovnani
odsazovani = inherits: \nastavodsazovani
start = NUMMER
symzarovnani = vlevo nastred vpravo flushleft center flushright
symbol = NAME
n = NUMMER
odsadpristi = ano ne auto
vnitrni = BEFEHL
prikaz = CSNAME
polozky = NUMMER
maxsirka = DIMENSION
itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
alignsymbol = ano ne
textdistance = male stredni velke zadny mezera DIMENSION
oddelovactextu = BEFEHL
lasttextseparator = BEFEHL
predelmista = ano ne obrazovka inline
pismo = STYLE BEFEHL
barva = COLOR
stylhlavicky = STYLE BEFEHL
barvahlavicky = COLOR
stylsnacky = STYLE BEFEHL
barvaznacky = COLOR
stylsymboly = STYLE BEFEHL
barvasymbolu = COLOR
mrizka = inherits: \definegridsnapping
packcriterium = NUMMER
vzdalenostsloupcu = DIMENSION
inherits: \setupcounter
instances: itemize

```

```

\nastaveniitemize [...] [...] [...]
1 kazdy NUMMER OPT OPT OPT
2 uvod nointro nahodny pokracovat zhustene autouvod široky text pred po zadnabila marginalie naokraj naokraj
dotextu headintext uvolnene prizpusobive nofit odstavec spojeno notjoinedup semknuto predel nostopper rozbalene
opakovat norepeat reverse sloupce prekryv jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky
NUMMER*semknuto horizontalne NAME
3 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
predhlavickou = BEFEHL
pohlavicce = BEFEHL
textvlevo = BEFEHL
textvpravo = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
faktor = NUMMER
krok = DIMENSION
sirka = DIMENSION
vzdalenost = DIMENSION
marginalie = ano ne standardni DIMENSION
levyokraj = ano ne standardni DIMENSION
pravyokraj = ano ne standardni DIMENSION
vzdalenostlevehookraje = ano ne standardni DIMENSION
vzdalenostpravehookraje = ano ne standardni DIMENSION
zarovnani = inherits: \nastavzarovnani
odsazovani = inherits: \nastavodsazovani
start = NUMMER
symzarovnani = vlevo nastred vpravo flushleft center flushright
symbol = NAME
n = NUMMER
odsadpristi = ano ne auto
vnitrni = BEFEHL
prikaz = CSNAME
polozky = NUMMER
maxsirka = DIMENSION
itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
alignsymbol = ano ne
textdistance = male stredni velke zadny mezera DIMENSION
oddelovactextu = BEFEHL
lasttextseparator = BEFEHL
predelmista = ano ne obrazovka inline
pismo = STYLE BEFEHL
barva = COLOR
stylhlavicky = STYLE BEFEHL
barvahlavicky = COLOR
stylsnacky = STYLE BEFEHL
barvaznacky = COLOR
stylsymboly = STYLE BEFEHL
barvasymbolu = COLOR
mrizka = inherits: \definegridsnapping
packcriterium = NUMMER
vzdalenostsloupcu = DIMENSION
inherits: \setupcounter

```

\setuplabel [...¹,...] [...²,...]

```

1  NAME                                OPT
2  titul                               = ano ne
   cislo                               = ano ne
   ciselnyprikaz                       = \...#1
   vzdalenosttitulek                   = DIMENSION
   styltitulek                         = STYLE BEFEHL
   barvatitulek                        = COLOR
   titlecommand                       = \...#1
   titleleft                           = BEFEHL
   titleright                          = BEFEHL
   vlevo                               = BEFEHL
   vpravo                              = BEFEHL
   symbol                              = BEFEHL
   starter                             = BEFEHL
   predel                             = BEFEHL
   propojeni                           = NAME
   counter                             = NAME
   uroven                              = NUMMER
   text                                = TEXT
   headcommand                         = \...#1
   pred                               = BEFEHL
   po                                  = BEFEHL
   mezi                                = BEFEHL
   alternativa                        = vlevo vpravo naokrajiv vlevo vpravo marginalie lev yokraj prav yokraj innermargin outermargin
                                     semknuto visici vrsek prazdne prikaz dotextu NAME
   zarovnani                           = inherits: \nastavzarovnani
   headalign                           = inherits: \nastavzarovnani
   odsazovani                         = inherits: \nastavodsazovani
   obrazovka                           = ano ne
   odsadpristi                         = ano ne auto
   sirka                               = prizpusobive siroky radek DIMENSION
   vzdalenost                         = zadny DIMENSION
   natahnout                           = NUMMER
   shrink                              = NUMMER
   zaveseni                           = prizpusobive siroky zadny marginalie NUMMER
   closesymbol                         = BEFEHL
   closecommand                       = \...#1
   expanzen                            = ano ne xml
   referenceprefix                    = + - TEXT
   vzor                               = TEXT
   marginalie                         = ano ne standardni DIMENSION
   pismo                               = STYLE BEFEHL
   barva                               = COLOR
   stylhlavicky                       = STYLE BEFEHL
   barvahlavicky                      = COLOR
   zarovnejtitul                      = ano ne
   headindenting                      = ano ne
   prodleva                           = text
   inherits: \setupcounter

```

\setuplayer [...¹,...] [...²,...]

```

1  NAME                                OPT
2  status                             = start stop pokracovat dalsi opakovat
   volba                              = test
   stranka                            = NUMMER
   sirka                              = DIMENSION
   vyska                              = DIMENSION
   region                             = NAME
   rotace                             = vlevo vpravo uvnitr vnejsi NUMMER
   position                           = ano ne prekryv
   hoffset                            = max DIMENSION
   voffset                            = max DIMENSION
   offset                             = DIMENSION
   dx                                 = DIMENSION
   dy                                 = DIMENSION
   sx                                 = NUMMER
   sy                                 = NUMMER
   x                                  = DIMENSION
   y                                  = DIMENSION
   roh                                = vlevo nastred vpravo vrsek spodek
   misto                              = mrizka vlevo nastred vpravo vrsek spodek radek l c r m t b g
   radek                              = NUMMER
   sloupec                            = NUMMER
   smer                               = normalni reverse
   oboustranne                        = ano ne
   metoda                             = prizpusobive prekryv
   opakovat                           = ano
   prednastaveni                     = leftttop rightttop leftbottom rightbottom nastred middletop middlebottom middleleft middleright
                                     lefttopleft lefttopleft NAME

```

```

\setuplayeredtext [...1,...] [...2,...]
1 NAME OPT
2 pismoeno = STYLE BEFEHL
   barva = COLOR
   inherits: \nastavoramovani

```

```

\setuplayouttext [...1] [...2] [...3,...,...]
1 vrsek zahlavi text upati spodek OPT
2 text marginalie hrana
3 status = start stop prazdne vysoko zadny normalni zadneznaceni NAME
   pismoeno = STYLE BEFEHL
   barva = COLOR
   strut = ano ne
   n = NUMMER
   pred = BEFEHL
   po = BEFEHL
   textvlevo = TEXT
   strednitext = TEXT
   textvpravo = TEXT
   stylvlevo = STYLE BEFEHL
   middlestyle = STYLE BEFEHL
   stylvpravo = STYLE BEFEHL
   barvavlevo = COLOR
   middlecolor = COLOR
   barvavpravo = COLOR
   sirka = DIMENSION
   sirkavlevo = DIMENSION
   middlewidth = DIMENSION
   sirkavpravo = DIMENSION

```

```

\setuplinefiller [...1,...] [...2,...]
1 NAME OPT
2 misto = vlevo vpravo obe
   rozsah = vlevo vpravo lokalne globalne
   mp = NAME
   vyska = DIMENSION
   hloubka = DIMENSION
   vzdalenost = DIMENSION
   threshold = DIMENSION
   tloustkalinky = DIMENSION
   pred = BEFEHL
   po = BEFEHL
   barva = COLOR
   styltextu = STYLE BEFEHL
   barvatextu = COLOR
   zarovnani = inherits: \nastavzarovnani

```

```

\setuplinefillers [...1,...] [...2,...]
1 NAME OPT
2 inherits: \setuplinefiller

```

```

\setuplinenote [...1,...] [...2,...]
1 NAME OPT
2 compress = ano ne
   compressmethod = separator predel mezera
   compressseparator = BEFEHL
   compressdistance = DIMENSION
   compressstopper = BEFEHL
   inherits: \setupnote

```

```

\setuplineprofile [...1,...] [...2,...]
1 NAME OPT
2 krok = DIMENSION
   faktor = NUMMER
   metoda = a
   odstavec = ano ne

```


`\setuplinetable` [¹...] [²...] [...,³...,...]

```

1  r c                OPT      OPT
2  liche sude zahlavi NUMMER
3  radky              = prizpusobive NUMMER
   pred               = BEFEHL
   po                 = BEFEHL
   mezi              = BEFEHL
   natahnout         = ano ne DIMENSION
   maxsirka          = prizpusobive DIMENSION
   nvlevo            = NUMMER
   n                 = NUMMER
   opakovat          = ano ne
   nx                = NUMMER
   sirka             = DIMENSION
   vyska             = prizpusobive radek DIMENSION
   vzdalenost        = DIMENSION
   levyoffset        = DIMENSION
   pravyoffset       = DIMENSION
   zarovnani         = inherits: \nastavzarovnani
   pozadi            = barevne
   barvapozadi       = COLOR
   xheight           = max DIMENSION
   xdepth            = max DIMENSION
   pismo             = STYLE BEFEHL
   barva             = COLOR

```

`\setuplistalternative` [...,¹...] [...,²...,...]

```

1  NAME                OPT
2  pred                = BEFEHL
   po                  = BEFEHL
   prikaz              = \...#1#2#3
   renderingsetup      = NAME
   sirka               = DIMENSION
   vzdalenost          = DIMENSION
   natahnout           = DIMENSION
   filler              = BEFEHL

```

`\setuplistextra` [...,¹...] [...,²...,...]

```

1  NAME                OPT
2  pred = BEFEHL
   po  = BEFEHL

```

`\setuplocalboxes` [...,¹...] [...,²...,...]

```

1  NAME                OPT      OPT
2  prikaz              = BEFEHL
   opakovat           = ano ne
   misto              = vlevo vpravo nastred textvlevo textvpravo
   sirka              = DIMENSION
   vzdalenost         = DIMENSION
   pismo              =
   barva              = COLOR

```

`\setuplocalfloats` [...,^{*}...,...]

```

*  pred = BEFEHL
   po   = BEFEHL
   mezi = BEFEHL

```

`\setuplocalinterlinespace` [...,¹...] [...,²...,...]

```

1  NAME                OPT
2  inherits: \nastavmeziradkovoumezeru

```

`\setuplocalinterlinespace` [...,^{*}...]

```

*  zap vyp reset auto male stredni velkeOPT NUMMER DIMENSION

```

`\setuplocalinterlinespace` [...]

```

*  NAME

```

```

\setuplow   [...] 1 [...] [...] 2 [...]
1  NAME      OPT
2  vzdalenost = DIMENSION
   down      = DIMENSION
   pismo     = STYLE BEFEHL
   barva     = COLOR

```

```

\setuplowhigh [...] 1 [...] [...] 2 [...]
1  NAME      OPT
2  vzdalenost = DIMENSION
   up        = DIMENSION
   down      = DIMENSION
   pismo     = STYLE BEFEHL
   barva     = COLOR

```

```

\setuplowmidhigh [...] 1 [...] [...] 2 [...]
1  NAME      OPT
2  up        = DIMENSION
   down      = DIMENSION
   pismo     = STYLE BEFEHL
   barva     = COLOR

```

```

\setupMPgraphics [...] * [...]
*  barva = lokalne globalne
   mpy   = FILE

```

```

\setupMPinstance [...] 1 [...] [...] 2 [...]
1  NAME      OPT
2  formatovat = metafun minifun mpost
   initializations = ano ne
   setups          = NAME
   styltextu       = STYLE BEFEHL
   barvatextu      = COLOR
   extensions      = ano ne
   metoda          = binary decimal double scaled posit interval implicitni

```

```

\setupMPpage [...] * [...]
*  inherits: \setupfittingpage

```

```

\setupMPvariables [...] 1 [...] [...] 2 [...]
1  NAME      OPT
2  KEY = VALUE

```

```

\setupmarginblock [...] 1 [...] [...] 2 [...]
1  NAME      OPT
2  status     = start stop
   sirka     = DIMENSION
   pred      = BEFEHL
   po        = BEFEHL
   mezi      = BEFEHL
   zarovnnani = inherits: \nastavzarovnnani
   pismo     = STYLE BEFEHL
   barva     = COLOR
   vrsek     = BEFEHL
   spodek    = BEFEHL
   misto     = vlevo vpravo nastred naokrajji
   vlevo     = BEFEHL
   vpravo    = BEFEHL

```

```

\setupmargindata [...1,...] [...2,...]
1 NAME OPT
2 strut = ano ne auto kap prizpusobive radek implicitni CHARACTER
   prikaz = \...#1
   sirka = DIMENSION
   zarovnani = inherits: \nastavzarovnani
   anchor = region text
   misto = vlevo vpravo uvnitr vnejsi
   metoda = vrsek radek prvni podlehloubky vyska
   category = implicitni hrana
   rozsah = lokalne globalne
   volba = text odstavec
   marginalie = lokalne normalni marginalie hrana
   vzdalenost = DIMENSION
   hoffset = DIMENSION
   voffset = DIMENSION
   dy = DIMENSION
   bottomspace = DIMENSION
   threshold = DIMENSION
   radek = NUMMER
   stack = ano pokracovat
   pismeno = STYLE BEFEHL
   barva = COLOR

```

```

\setupmarginframed [...1,...] [...2,...]
1 NAME OPT
2 inherits: \nastavoramovani

```

```

\setupmarginrule [...1] [...2,...]
1 NUMMER OPT
2 inherits: \setupsidebar

```

```

\setupmathaccent [...1,...] [...2,...]
1 NAME OPT OPT
2 inherits: \setupmathaccents

```

```

\setupmathaccents [...1,...] [...2,...]
1 NAME OPT OPT
2 mathstyle = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
   meritko = ano ne drzet
   plugin = mp
   mp = NAME
   barva = COLOR
   barvatextu = COLOR
   symbolcolor = COLOR
   zarovnani = nastred
   natahnout = ano ne
   shrink = ano ne
   snap = ano
   alignsymbol = ano ne
   offset = auto
   i = auto

```

```

\setupmathalignment [...1,...] [...2,...]
1 NAME OPT
2 n = NUMBER
m = NUMBER
vzdalenost = DIMENSION
cislo = auto
numberdistance = DIMENSION
oddelovac = TEXT
zarovnani = vlevo nastred vpravo flushleft flushright normalni auto NUMBER:vlevo NUMBER:nastred NUMBER:vpravo
NUMBER:flushleft NUMBER:flushright
misto = vrsek center spodek vlevo nastred vpravo zhustene rozbalene rovnice
snapping = ano normalni 0 1 2 0:10 1:10 2:10 2:20 1:top 1:bottom 2:top 2:bottom
mathstyle = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
styltextu = STYLE BEFEHL
textstyle:NUMBER = STYLE BEFEHL
barvatextu = COLOR
textcolor:NUMBER = COLOR
text = TEXT
text:NUMBER = TEXT
fences = cases sesac tekcarb parenthesis bracket brace bar doublebar triplebar angle doubleangle
solidus ceiling floor moustache uppercorner lowercorner group openbracket mirroredparenthesis
mirroredbracket mirroredbrace mirroredbar mirroreddoublebar mirroredtriplebar mirroredangle
mirroreddoubleangle mirroredsolidus mirroredceiling mirroredfloor mirroredmoustache mirroreduppercorner
mirroredlowercorner mirroredgroup mirroredopenbracket interval openinterval closedinterval
leftopeninterval rightopeninterval varopeninterval varleftopeninterval varrightopeninterval
integerinterval tupanddownarrows tupdownarrows tdownuparrows tuparrow tdownarrow abs innerproduct
integerpart norm set sequence tuple
adaptive = ano ne
spaceinbetween = inherits: \nastavbilamista
odkaz = + - REFERENCE
suffix = TEXT
numberthreshold = DIMENSION
tloustkalinky = DIMENSION
barvalinky = COLOR
toffset = DIMENSION
boffset = DIMENSION

```

```

\setupmathannotation [...1,...] [...2,...]
1 NAME OPT
2 vrsek = TEXT
spodek = TEXT
strut = ano ne
mathclass = vse begin end unset ordinary operator binary relation open close punctuation variable active uvnitř
under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential
exponential integral ellipsis function digit division factorial wrapped construct dimension unary
textpunctuation unspaced experimental fake numbergroup continuation

```

```

\setupmathcases [...1,...] [...2,...]
1 NAME OPT
2 vlevo = BEFEHL
vpravo = BEFEHL
strut = ano ne
mathstyle = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
vzdalenost = DIMENSION
numberdistance = DIMENSION
simplecommand = NAME
textvlevo = TEXT
textvpravo = TEXT
levyokraj = DIMENSION
pravyokraj = DIMENSION
fences = cases sesac tekcarb parenthesis bracket brace bar doublebar triplebar angle doubleangle solidus
ceiling floor moustache uppercorner lowercorner group openbracket mirroredparenthesis mirroredbracket
mirroredbrace mirroredbar mirroreddoublebar mirroredtriplebar mirroredangle mirroreddoubleangle
mirroredsolidus mirroredceiling mirroredfloor mirroredmoustache mirroreduppercorner mirroredlowercorner
mirroredgroup mirroredopenbracket interval openinterval closedinterval leftopeninterval rightopeninterval
varopeninterval varleftopeninterval varrightopeninterval integerinterval tupanddownarrows
tupdownarrows tdownuparrows tuparrow tdownarrow abs innerproduct integerpart norm set sequence
tuple
spaceinbetween = inherits: \nastavbilamista

```

`\setupmathdelimited` $[\dots^1,\dots]$ $[\dots^2,\dots]$

```
1 NAME
2 define = ano ne
   strut = ano ne vyska podlehloubky math
   levyokraj = DIMENSION
   pravyokraj = DIMENSION
   alternativa = implicitni normalni
   symbolcolor = COLOR
   vyska = DIMENSION
   hloubka = DIMENSION
   offsetvrsku = DIMENSION
   offsetspodku = DIMENSION
   source = NAME
   velikost = NUMMER
   vlevo = NUMMER
   vpravo = NUMMER
   mathmeaning = TEXT
   barva = COLOR
   barvatextu = COLOR
```

`\setupmathdelimiter` $[\dots^1,\dots]$ $[\dots^2,\dots]$

```
1 NAME
2 define = ano ne
   faktor = NUMMER
   levyoffset = DIMENSION
   pravyoffset = DIMENSION
   exact = ano ne
   osa = ano ne
   vyska = DIMENSION
   hloubka = DIMENSION
   symbol = NUMMER
```

`\setupmathematics` $[\dots^1,\dots]$ $[\dots^2,\dots]$

```
1 NAME
2 openup = ano ne
   sadasymbolu = blackboard-to-bold mikael's-favourites NAME
   functionstyle = STYLE BEFEHL
   compact = ano ne
   zarovnnani = l2r lefttoright r2l righttleft
   sygreek = normalni kurziva zadny
   lcgreek = normalni kurziva zadny
   ucgreek = normalni kurziva zadny
   italics = ano ne
   autopunctuation = ano ne vse comma yes,semicolon comma,semicolon all,semicolon
   setups = NAME
   styltextu = STYLE BEFEHL
   barvatextu = COLOR
   functioncolor = COLOR
   integral = horizontalne vertikalne auto autolimits limits nolimits
   stylealternative = NAME
   implicitni = normalni kurziva
   collapsing = 0 1 2 3 implicitni tex seznam vse zadny reset
   kernpairs = ano ne
   mathconstants = kurziva upright
   differentiald = kurziva upright
   exponentiale = kurziva upright
   imaginaryi = kurziva upright
   imaginaryj = kurziva upright
   constantpi = kurziva upright
   snap = ano ne
   textdistance = DIMENSION
   threshold = zadny male stredni velke DIMENSION
   mathstyle = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
   barva = COLOR
   autospacing = ano ne
   autonumbers = ano ne NUMMER
   autofencing = ano ne
   hz = ano ne
   alignscripts = ano ne vzdy prazdne
   interscriptfactor = NUMMER
   autointervals = ano ne
   limitstretch = ano ne
   domain = implicitni chemistry
   snapping = reset radek male stredni velke
```

`\setupmathexport` [$\dots,\dots^*\dots,\dots$]

* `buffer` = NAME
`soubor` = FILE
`n` = NUMMER
`volba` = ascii

`\setupmathfence` [$\dots,\dots^1\dots$] [$\dots,\dots^2\dots,\dots$]

1 NAME OPT
2 inherits: \setupmathfences

`\setupmathfences` [$\dots,\dots^1\dots$] [$\dots,\dots^2\dots,\dots$]

1 NAME OPT
2 `define` = ano ne
`vlevo` = NUMMER
`stredni` = NUMMER
`vpravo` = NUMMER
`mathstyle` = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
`barva` = COLOR
`barvavlevo` = COLOR
`middlecolor` = COLOR
`barvavpravo` = COLOR
`symbolcolor` = COLOR
`status` = auto
`metoda` = auto
`velikost` = velke Big bigg Bigg NUMMER
`faktor` = zadny fixne sila velikost auto NUMMER
`overflow` = ne auto
`mathclass` = vse begin end unset ordinary operator binary relation open close punctuation variable active
unitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary
differential exponential integral ellipsis function digit division factorial wrapped construct
dimension unary textpunctuation unspaced experimental fake numbergroup continuation

`vyska` = DIMENSION
`hloubka` = DIMENSION
`plugin` = mp
`mp` = NAME
`displayfactor` = NUMMER
`inlinefactor` = NUMMER
`mathmeaning` = TEXT
`svrchnimezera` = DIMENSION
`bottomspace` = DIMENSION
`snap` = ano ne
`alternativa` = male velke
`setups` = NAME
`source` = NUMMER
`leftsource` = NUMMER
`middlesource` = NUMMER
`rightsource` = NUMMER
`stylvlevo` = STYLE BEFEHL
`stylvpravo` = STYLE BEFEHL
`leftclass` = NUMMER
`middleclass` = NUMMER
`rightclass` = NUMMER
`vzdalenost` = DIMENSION
`text` = ano ne

`\setupmathfraction` [$\dots,\dots^1\dots$] [$\dots,\dots^2\dots,\dots$]

1 NAME OPT
2 inherits: \setupmathfractions

```

\setupmathfractions [...1,...] [...2,...]
1 NAME OPT
2 vzdalenostvrsku = DIMENSION
  vzdalenostspodku = DIMENSION
  marginalie = DIMENSION
  barva = COLOR
  barvatextu = COLOR
  symbolcolor = COLOR
  topcolor = COLOR
  bottomcolor = COLOR
  strut = ano ne tight text math
  alternativa = uvnitr vnejsi obe
  linka = ano ne auto skryte symbol
  vlevo = NUMMER
  vpravo = NUMMER
  stredni = NUMMER
  symbol = NUMMER
  tloustkalinky = font DIMENSION
  mathstyle = STYLE BEFEHL
  mathnumeratorstyle = STYLE BEFEHL
  mathdenominatorstyle = STYLE BEFEHL
  vzdalenost = ne zadny vrsek spodek obe prekryv DIMENSION
  threshold = DIMENSION
  inlinethreshold = auto NUMMER
  displaythreshold = auto NUMMER
  fences =
  mathmeaning = binom limits
  mathclass = vse begin end unset ordinary operator binary relation open close punctuation variable
              active uvnitr under over fraction radical nastred prime accent fenced ghost vcenter
              explicit imaginary differential exponential integral ellipsis function digit division
              factorial wrapped construct dimension unary textpunctuation unspaced experimental fake
              numbergroup continuation
  hfaktor = NUMMER
  metoda = horizontalne vertikalne radek
  plugin = mp
  mp = NAME
  vfaktor = NUMMER
  source = NAME
  topalign = vlevo vpravo nastred flushleft flushright split:flushleft split:flushright
  bottomalign = vlevo vpravo nastred flushleft flushright split:flushleft split:flushright

```

```

\setupmathframed [...1,...] [...2,...]
1 NAME OPT
2 mathstyle = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
  mathclass = vse begin end unset ordinary operator binary relation open close punctuation variable active uvnitr
              under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential
              exponential integral ellipsis function digit division factorial wrapped construct dimension unary
              textpunctuation unspaced experimental fake numbergroup continuation
  inherits: \nastavoramovani

```

```

\setupmathfunction [...1,...] [...2,...]
1 NAME OPT
2 inherits: \setupmathfunctions

```

```

\setupmathfunctions [...1,...] [...2,...]
1 NAME OPT
2 barva = COLOR
  pismo = STYLE BEFEHL
  class = vse begin end unset ordinary operator binary relation open close punctuation variable active
          uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary
          differential exponential integral ellipsis function digit division factorial wrapped construct
          dimension unary textpunctuation unspaced experimental fake numbergroup continuation
  vlevo = BEFEHL
  vpravo = BEFEHL
  mathlimits = ano ne auto
  metoda = limits
  prikaz = \...#1

```

```

\setupmathmatrix [...1,...] [...2,...]
1 NAME OPT
2 vlevo = BEFEHL
vpravo = BEFEHL
strut = ano ne NUMMER
zarovnani = vlevo nastred vpravo flushleft flushright normalni auto NUMMER:vlevo NUMMER:nastred NUMMER:vpravo
NUMMER:flushleft NUMMER:flushright
mathstyle = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
vzdalenost = DIMENSION
simplecommand = TEXT
misto = vrsek spodek vysoko nizko nivy center normalni
tloustkalinky = DIMENSION
barvalinky = COLOR
moffset = DIMENSION
toffset = DIMENSION
boffset = DIMENSION
levyokraj = DIMENSION
pravyyokraj = DIMENSION
fences = cases sesac tekcarb parenthesis bracket brace bar doublebar triplebar angle doubleangle solidus
ceiling floor moustache uppercorner lowercorner group openbracket mirroredparenthesis mirroredbracket
mirroredbrace mirroredbar mirroreddoublebar mirroredtriplebar mirroredangle mirroreddoubleangle
mirroredsolidus mirroredceiling mirroredfloor mirroredmoustache mirroreduppercorner mirroredlowercorner
mirroredgroup mirroredopenbracket interval openinterval closedinterval leftopeninterval rightopeninterval
varopeninterval varleftopeninterval varrightopeninterval integerinterval tupanddownarrows
tupdownarrows tdownuparrows tuparrow tdownarrow abs innerproduct integerpart norm set sequence
tuple
levahrana = zadny DIMENSION
pravahrana = zadny DIMENSION
akce = transpose negate scale

```

```

\setupmathnesting [...1,...] [...2,...]
1 NAME OPT
2 vlevo = BEFEHL
vpravo = BEFEHL
displayfactor = NUMMER
inlinefactor = NUMMER

```

```

\setupmathoperator [...1,...] [...2,...]
1 NAME OPT
2 inherits: \setupmathoperators

```

```

\setupmathoperators [...1,...] [...2,...]
1 NAME OPT
2 mathclass = vse begin end unset ordinary operator binary relation open close punctuation variable active
uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary
differential exponential integral ellipsis function digit division factorial wrapped construct
dimension unary textpunctuation unspaced experimental fake numbergroup continuation
symbolcolor = COLOR
metoda = horizontalne vertikalne auto autolimits limits nolimits
velikost = auto DIMENSION
vrsek = TEXT
topcolor = COLOR
spodek = TEXT
bottomcolor = COLOR
barvatextu = COLOR
barva = COLOR
barvacisla = COLOR
vlevo = NUMMER

```

```

\setupmathornament [...1,...] [...2,...]
1 NAME OPT
2 alternativa = mp
barva = COLOR
mpoffset = DIMENSION
mp = NAME

```


`\setupmathradical` $[...,\overset{1}{...}]$ $[...,\overset{2}{...},...]$

```

1 NAME
2 barva = COLOR
  barvatextu = COLOR
  barvacisla = COLOR
  symbolcolor = COLOR
  plugin = mp
  mp = NAME
  vlevo = NUMMER
  vpravo = NUMMER
  vrsek = NUMMER
  n = TEXT
  vyska = zadny DIMENSION
  hloubka = zadny DIMENSION
  mindepth = DIMENSION
  levyokraj = DIMENSION
  pravyokraj = DIMENSION
  linka = ano ne symbol spodek
  source = NAME
  mathstyle = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
  strut = ano ne vyska podlehloubky math

```

`\setupmathsimplealign` $[...,\overset{1}{...}]$ $[...,\overset{2}{...},...]$

```

1 NAME
2 strut = ano ne
  zarovnani = normalni flushright vlevo vpravo flushleft nastred NUMMER:normalni NUMMER:flushright NUMMER:vlevo
               NUMMER:vpravo NUMMER:flushleft NUMMER:nastred
  misto = vrsek spodek center nastred vlevo vpravo zhustene rovnice
  vzdalenost = math DIMENSION
  spaceinbetween = inherits: \nastavbilamista
  levyokraj = DIMENSION
  pravyokraj = DIMENSION
  vlevo = BEFEHL
  vpravo = BEFEHL
  fences = cases sesac tekcarb parenthesis bracket brace bar doublebar triplebar angle doubleangle solidus
               ceiling floor moustache uppercorner lowercorner group openbracket mirroredparenthesis mirroredbracket
               mirroredbrace mirroredbar mirroreddoublebar mirroredtriplebar mirroredangle mirroreddoubleangle
               mirroredsolidus mirroredceiling mirroredfloor mirroredmoustache mirroreduppercorner mirroredlowercorner
               mirroredgroup mirroredopenbracket interval openinterval closedinterval leftopeninterval rightopeninterval
               varopeninterval varleftopeninterval varrightopeninterval integerinterval tupanddownarrows
               tupdownarrows tdownuparrows tuparrow tdownarrow abs innerproduct integerpart norm set sequence
               tuple
  text = TEXT
  textdistance = DIMENSION
  alternativa = equationsystem
  simplecommand = NAME

```

`\setupmathspacing` $[..^.]$

* normalni tight uvolnene uzky siroce less more chemistry NAME

```

\setupmathstackers [...1,...] [...2,...]
1  NAME                      OPT
2  vrsek                    = TEXT
   spodek                   = TEXT
   vlevo                     = BEFEHL
   vpravo                    = BEFEHL
   topcommand                = \...#1
   bottomcommand             = \...#1
   middlecommand             = \...#1
   topstyle                  = STYLE BEFEHL
   bottomstyle               = STYLE BEFEHL
   middlestyle               = STYLE BEFEHL
   topcolor                  = COLOR
   bottomcolor               = COLOR
   middlecolor               = COLOR
   topalign                  = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   bottomalign               = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   plugin                    = mp
   mp                        = NAME
   mpheight                  = DIMENSION
   mpdepth                   = DIMENSION
   mpoffset                  = DIMENSION
   barva                     = COLOR
   symbolcolor               = COLOR
   offsetvrsku               = DIMENSION
   hoffset                   = DIMENSION
   voffset                   = DIMENSION
   minvyska                  = DIMENSION
   mindepth                  = DIMENSION
   mathclass                 = vse begin end unset ordinary operator binary relation open close punctuation variable active
                               uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary
                               differential exponential integral ellipsis function digit division factorial wrapped construct
                               dimension unary textpunctuation unspaced experimental fake numbergroup continuation

   offset                   = min max normalni
   misto                     = vrsek spodek vysoko nizko nastred NUMBER
   strut                     = ano ne
   alternativa               = normalni implicitni mp
   minsirka                  = DIMENSION
   vzdalenost                = DIMENSION
   order                     = normalni reverse
   mathlimits                = ano ne
   lt                        = DIMENSION
   rt                        = DIMENSION
   lb                        = DIMENSION
   rb                        = DIMENSION
   shrink                    = ano ne
   natahnout                 = ano ne
   vzor                      = NUMBER

```

```

\setupmathstyle [...*...]
*  obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME

```

```

\setupmathtext [...1,...] [...2,...]
1  NAME                      OPT
2  alternativa              = split slovo
   pismeno                  = STYLE BEFEHL
   barva                    = COLOR
   class                    = vse begin end unset ordinary operator binary relation open close punctuation variable active
                               uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary
                               differential exponential integral ellipsis function digit division factorial wrapped construct
                               dimension unary textpunctuation unspaced experimental fake numbergroup continuation

   leftclass                = vse begin end unset ordinary operator binary relation open close punctuation variable active
                               uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary
                               differential exponential integral ellipsis function digit division factorial wrapped construct
                               dimension unary textpunctuation unspaced experimental fake numbergroup continuation

   rightclass               = vse begin end unset ordinary operator binary relation open close punctuation variable active
                               uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary
                               differential exponential integral ellipsis function digit division factorial wrapped construct
                               dimension unary textpunctuation unspaced experimental fake numbergroup continuation

```

```

\setupmetadata [...*...]
*  titul                    = TEXT
   podtitulek               = TEXT
   autor                    = TEXT
   keyword                  = TEXT
   datum                   = TEXT

```

\setupmixedcolumns [...¹,...] [...²,...]

```
1 NAME OPT
2 mrizka = inherits: \definegridsnapping
  tloustkalinky = DIMENSION
  metoda = otr box
  pred = BEFEHL
  po = BEFEHL
  vzdalenost = DIMENSION
  n = NUMMER
  maxvyska = DIMENSION
  maxsirka = DIMENSION
  krok = DIMENSION
  profile = NAME
  zarovnani = inherits: \nastavzarovnani
  setups = NAME
  rovnovaha = ano ne
  splitmethod = zadny fixne
  alternativa = lokalne globalne
  internalgrid = radek pulradku
  oddelovac = linka
  strut = ano ne
  barva = COLOR
  barvalinky = COLOR
  smer = normalni reverse
  notes = ano ne
  prazdny = inherits: \preskoc
  odsazovani = inherits: \nastavodsazovani
  profile = NAME
  define = ano ne
  inherits: \nastavoramovani
```

\setupmodule [...¹] [...²,...]

```
1 FILE OPT
2 test = ano ne
  KEY = VALUE
```

\setupmulticolumns [...¹,...] [...²,...]

```
1 NAME OPT
2 n = NUMMER
  vzdalenost = DIMENSION
  smer = vpravo reverse
  rovnovaha = ano ne
  prazdny = inherits: \preskoc
  zarovnani = inherits: \nastavzarovnani
  nvrsek = NUMMER
```

```

\setupnotation    [...,1...]    [...,2...,...]
1  NAME          OPT
2  titul          = ano ne
   cislo          = ano ne
   typ            = note
   ciselnyprikaz  = \...#1
   vzdalenosttitulek = DIMENSION
   styltitulek    = STYLE BEFEHL
   barvatitulek   = COLOR
   titlecommand   = \...#1
   titleleft      = BEFEHL
   titleright     = BEFEHL
   vlevo          = BEFEHL
   vpravo         = BEFEHL
   symbol         = BEFEHL
   starter        = BEFEHL
   predel         = BEFEHL
   propojeni      = NAME
   counter        = NAME
   uroven         = NUMBER
   text           = TEXT
   headcommand    = \...#1
   deeptextcommand = \...#1
   pred           = BEFEHL
   po             = BEFEHL
   mezi           = BEFEHL
   alternativa    = vlevo vpravo naokraj i vlevo i vpravo marginalie lev yokraj prav yokraj innermargin outermargin
                   semknuto visici vrsek prikaz note NAME
   zarovnani      = inherits: \nastavzarovnani
   headalign      = inherits: \nastavzarovnani
   odsazovani     = inherits: \nastavodsazovani
   obrazovka      = ano ne
   odsadpristi    = ano ne auto
   sirka          = prizpusobive siroky radek DIMENSION
   vzdalenost     = zadny DIMENSION
   natahnout      = NUMBER
   shrink         = NUMBER
   zaveseni       = prizpusobive siroky zadny marginalie NUMBER
   closesymbol    = BEFEHL
   closecommand   = \...#1
   expanzen       = ano ne xml
   referenceprefix = + - TEXT
   vzor           = TEXT
   marginalie     = ano ne standardni DIMENSION
   pismo          = STYLE BEFEHL
   barva          = COLOR
   stylhlavicky   = STYLE BEFEHL
   barvahlavicky  = COLOR
   zarovnejtitul  = ano ne
   headindenting  = ano ne
   prodleva       = text
   inherits: \setupcounter

```

```

\setupnotations  [...,1...]    [...,2...,...]
1  NAME          OPT
2  inherits: \setupnotation

```

\setupnote [...,¹...] [...,²...,...]

1	NAME	OPT	
2	interakce	=	ano ne cislo text vse
	symbolcommand	=	\...#1
	textovyprikaz	=	\...#1
	indikator	=	ano ne
	oddelovactextu	=	BEFEHL
	sirka	=	DIMENSION
	vyska	=	DIMENSION
	vzdalenost	=	DIMENSION
	rulecommand	=	BEFEHL
	linka	=	zap vyp normalni vlevo vpravo prikaz odstavec
	split	=	tolerantni striktni velmistriktni NUMMER
	faktor	=	NUMMER
	misto	=	text stranka seznam vysoko spodek zadny sloupce firstcolumn lastcolumn
	dalsi	=	BEFEHL
	n	=	NUMMER
	barvalinky	=	COLOR
	tloustkalinky	=	DIMENSION
	rulewidth	=	DIMENSION
	ruledistance	=	DIMENSION
	setups	=	NAME
	meziradkovamezera	=	NAME
	odstavec	=	ano ne
	pred	=	BEFEHL
	po	=	BEFEHL
	mezi	=	BEFEHL
	rozsah	=	stranka
	vzdalenostsloupcu	=	DIMENSION
	pokracovat	=	ano ne
	alternativa	=	mrizka fixne sloupce note zadny
	kriterium	=	stranka
	zakladnifont	=	inherits: \nastavzakladnifont
	zarovnani	=	inherits: \nastavzarovnani
	styltextu	=	STYLE BEFEHL
	barvatextu	=	COLOR
	anchor	=	dalsi
	range	=	ano
	mezerapred	=	inherits: \preskoc
	spaceinbetween	=	inherits: \preskoc
	inherits:	=	\nastavoramovani

\setupnotes [...,¹...] [...,²...,...]

1	NAME	OPT	
2	inherits:	=	\setupnote

\setupoffset [...,^{*}...,...]

* inherits: \setupoffsetbox

\setupoffsetbox [...,^{*}...,...]

* x	=	DIMENSION
y	=	DIMENSION
levyoffset	=	DIMENSION
pravyoffset	=	DIMENSION
offsetvrsku	=	DIMENSION
offsetspodku	=	DIMENSION
metoda	=	fixne
sirka	=	DIMENSION
vyska	=	DIMENSION
hloubka	=	DIMENSION
misto	=	vlevo nastred vpravo vrsek spodek radek l c r m t b g

\setuptoptimize [...,¹...] [...,²...,...]

1	NAME	OPT	
2	vlevo	=	DIMENSION
	vpravo	=	DIMENSION
	radky	=	NUMMER
	vzdalenost	=	DIMENSION

\setuporientation [...,¹...] [...,²...,...]

1	NAME	OPT	
2	orientation	=	up down vlevo vpravo vrsek spodek normalni radek
	horizontalne	=	vlevo nastred vpravo flushleft flushright normalni
	vertikalne	=	radek vrsek nastred spodek normalni

```
\setupoutputroutine [...] [.,..2.,..]
```

\setupoutputroutine [...]

$$\backslash\mathrm{setuppagecolumns} \quad [\ldots,\overset{1}{\ldots}] \quad [\ldots,\overset{2}{\ldots},\ldots]$$
$$\backslash\mathrm{setuppagechecker} \quad [\dots^1\dots] \quad [\dots\dots^2\dots]$$
$$\backslash\mathrm{setuppageinjection} \quad [\dots, \dots]^1 \quad [\dots, \dots]^2 \dots$$
$$\backslash\mathrm{setuppageinjectionalternative} \quad [\dots,\dots] \quad [\dots,\dots\stackrel{2}{=}\dots,\dots]$$

`\setuppageshift` [¹...] [²...] [³...]

$$\backslash\mathrm{setuppagestate} \quad [\dots, \dots]^1 \quad [\dots, \dots]^2, \dots]$$
$$\backslash\mathrm{setuppairedbox} \quad [\ldots,\overset{1}{\ldots}] \quad [\ldots,\ldots\overset{2}{=}\ldots,\ldots]$$

\nastaveniPAIREDBOX [...,..^{*}...,...]

* inherits: \setuppairedbox

instances: legend

\nastavenilegend [...,..^{*}...,...]

* inherits: \setuppairedbox

\setuppaper [...,..^{*}...,...]

* inherits: \nastavvelikostpapiru

\setupparagraph [...,¹...] [...,..²...,...]

1 NAME OPT
2 pismo = STYLE BEFEHL
barva = COLOR
zarovnani = inherits: \nastavzarovnani
setups = NAME

\setupparagraphintro [...,¹...] [...².]

1 reset kazdy prvni dalsi
2 BEFEHL

\setupparallel [...¹.] [...²,...] [...,..³...,...]

1 NAME
2 NAME
3 setups = NAME
start = NUMMER
n = NUMMER
kriterium = vse

\setupparinsert [...,¹...] [...,..²...,...]

1 NAME OPT
2 xoffset = DIMENSION
yoffset = DIMENSION
vzdalenost = DIMENSION
radky = NUMMER
misto = vlevo vpravo
volba = podlehloubky
pismo = STYLE BEFEHL
barva = COLOR

\setupperiodkerning [...,¹...] [...,..²...,...]

1 NAME OPT
2 faktor = NUMMER

\setupperiods [...,..^{*}...,...]

* n = NUMMER
sirka = DIMENSION prizpusobive
vzdalenost = DIMENSION
symbol = BEFEHL

\setupplaceholder [...,¹...] [...,..²...,...]

1 NAME OPT
2 pred = BEFEHL
po = BEFEHL
text = TEXT
pismo = STYLE BEFEHL
barva = COLOR

\setupplacement [...,¹...] [...,..²...,...]

1 NAME OPT
2 pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
mrizka = inherits: \snaptogrid
korekceradku = zap vyp
korekcehloubky = zap vyp
marginalie = ano ne standardni

`\setuppositionbar` [...,¹*,...]

* pismeno = STYLE BEFEHL
barva = COLOR
n = NUMMER
min = NUMMER
max = NUMMER
text = TEXT
sirka = DIMENSION
vyska = DIMENSION
hloubka = DIMENSION

`\setupprocessor` [...,¹...] [...,²*,...]

1 NAME OPT
2 status = start stop
vlevo = BEFEHL
vpravo = BEFEHL
prikaz = \...#1
pismeno = STYLE BEFEHL
barva = COLOR

`\setupprofile` [...,¹...] [...,²*,...]

1 NAME OPT
2 vyska = DIMENSION
hloubka = DIMENSION
vzdalenost = DIMENSION
faktor = NUMMER
radky = NUMMER
metoda = striktni fixne zadny
define = ano ne

`\setupquotation` [...,¹*,...]

* inherits: \setupdelimitedtext

`\setuprealpagenumber` [...,¹*,...]

* inherits: \setupcounter

`\setupreferenceformat` [...,¹...] [...,²*,...]

1 NAME OPT
2 popisek = * NAME
vlevo = BEFEHL
vpravo = BEFEHL
typ = implicitni text titul cislo stranka realpage
setups = NAME
autocase = ano ne
text = TEXT
pismeno = STYLE BEFEHL
barva = COLOR

`\setupreferenceprefix` [...¹*]

* + - TEXT

`\setupreferencestructureprefix` [...¹...] [...²...] [...,³*,...]

1 NAME ABSCHNITT OPT
2 implicitni OPT
3 prefix = ano ne
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter = BEFEHL PROCESSOR->BEFEHL
prefixstopper = BEFEHL PROCESSOR->BEFEHL
prefixset = NAME
prefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
aktualni
numberconversion = NAME
numberconversionset = NAME
numberstarter = BEFEHL PROCESSOR->BEFEHL
numberstopper = BEFEHL PROCESSOR->BEFEHL
numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
numberseparatorset = NAME
prefixconnector = BEFEHL PROCESSOR->BEFEHL


```

\setupregisters [1...] [2...,...2...,...]
1 NAME NAME:NUMMER OPT
2 referencemethod = vpred
  expanzen = ano ne xml
  vlastnicislo = ano ne
  xmlsetup = NAME
  alternativa = a b A B
  metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
  compress = ano ne vse zhustene text
  check = ano ne
  kriterium = lokalne text aktualni predchozi vse ABSCHNITT
  pageprefixseparatorset = BEFEHL
  pageprefixconversionset = NAME
  pageprefixstarter = BEFEHL PROCESSOR->BEFEHL
  pageprefixstopper = BEFEHL PROCESSOR->BEFEHL
  pageprefixset = NAME
  pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
    ABSCHNITT:vse aktualni
  pageprefixconnector = BEFEHL
  pageprefix = ano ne
  pageseparatorset = NAME
  pageconversionset = NAME
  pagestarter = BEFEHL PROCESSOR->BEFEHL
  pagestopper = BEFEHL PROCESSOR->BEFEHL
  pagesegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
  maxsirka = DIMENSION
  indikator = ano ne
  pred = BEFEHL
  po = BEFEHL
  prikaz = \...#1
  textovyprikaz = \...#1
  deeptextcommand = \...#1
  strankovyprikaz = \...#1
  vzdalenost = DIMENSION
  interakce = text cislostranky
  cislostranky = ano ne
  symbol = a n zadny 1 2 BEFEHL
  language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
  pismo = STYLE BEFEHL
  barva = COLOR
  styltextu = STYLE BEFEHL
  barvatextu = COLOR
  stylstranky = STYLE BEFEHL
  barvastranky = COLOR
  pageleft = BEFEHL
  pageright = BEFEHL
  n = NUMMER
  rovnovaha = ano ne
  zarovnani = inherits: \nastavzarovnani
  numberorder = ciska
  pagemethod = stranka sekce

```

```

\setupregisters      [...,1...]      [...,2...]      [...,3...,...]
1  NAME              OPT              OPT
2  NUMMER
3  referencemethod   = vpred
   expanzen          = ano ne xml
   vlastnicislo      = ano ne
   xmlsetup          = NAME
   alternativa       = a b A B
   metoda            = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress          = ano ne vse zhustene text
   check             = ano ne
   kriterium         = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper = BEFEHL PROCESSOR->BEFEHL
   pageprefixset     = NAME
   pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse aktualni
   pageprefixconnector = BEFEHL
   pageprefix        = ano ne
   pageseparatorset  = NAME
   pageconversionset  = NAME
   pagestarter       = BEFEHL PROCESSOR->BEFEHL
   pagestopper       = BEFEHL PROCESSOR->BEFEHL
   pagesegments      = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
   maxsirka          = DIMENSION
   indikator         = ano ne
   pred              = BEFEHL
   po                 = BEFEHL
   prikaz            = \...#1
   textovyprikaz     = \...#1
   deeptextcommand   = \...#1
   strankovyprikaz   = \...#1
   vzdalenost        = DIMENSION
   interakce         = text cislostranky
   cislostranky      = ano ne
   symbol            = a n zadny 1 2 BEFEHL
   language          = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismeno           = STYLE BEFEHL
   barva             = COLOR
   styltextu         = STYLE BEFEHL
   barvatextu        = COLOR
   stylstranky       = STYLE BEFEHL
   barvastranky      = COLOR
   pageleft          = BEFEHL
   pageright         = BEFEHL
   n                 = NUMBER
   rovnovaha         = ano ne
   zarovnani         = inherits: \nastavzarovnani
   numberorder       = ciska
   pagemethod        = stranka sekce

```

```

\setuprenderingwindow [...,1...]      [...,2...,...]
1  NAME              OPT
2  akceotevrenistranky = REFERENCE
   akcezavrenistranky  = REFERENCE
   inherits: \nastavoramovani

```

```

\setuprows      [...,1...]      [...,2...,...]
1  NAME              OPT
2  define            = ano ne
   n                 = NUMBER
   vzdalenost        = DIMENSION
   sirka             = prizpusobive DIMENSION
   zarovnani         = inherits: \nastavzarovnani
   pred             = BEFEHL
   po                = BEFEHL
   alternativa       = tight
   order             = vertikalne
   vyska             = max DIMENSION
   hloubka           = max DIMENSION

```

```

\setuppruby    [...,1...]    [...,2...,...]
1  NAME              OPT
2  misto             = vrsek vlevo vpravo zadny
   zarovnani         = auto flushleft nastred flushright
   natahnout         = ano ne
   hoffset           = DIMENSION
   voffset           = DIMENSION
   vzdalenost        = zadny DIMENSION
   vlevo             = BEFEHL
   vpravo            = BEFEHL
   pismo             = STYLE BEFEHL
   barva             = COLOR

```

```

\setups    [...,*...]
*  NAME

```

```

\setupsavebuffer  [...,1...]    [...,2...,...]
1  NAME              OPT
2  seznam           = BUFFER
   soubor           = FILE
   prefix           = ano ne
   volba            = append
   adresar          = TEXT

```

```

\setupscale    [...,1...]    [...,2...,...]
1  NAME              OPT
2  meritko          = NUMMER
   xmeritko         = NUMMER
   ymeritko         = NUMMER
   sirka            = DIMENSION
   vyska            = DIMENSION
   hloubka          = ano ne
   radky            = NUMMER
   faktor           = prizpusobive siroky max min auto implicitni
   hfaktor          = prizpusobive siroky max min auto implicitni
   sfaktor          = prizpusobive siroky max min auto implicitni
   maxsirka         = DIMENSION
   maxvyska         = DIMENSION
   s                = NUMMER
   sx               = NUMMER
   sy               = NUMMER
   equalwidth       = DIMENSION
   equalheight      = DIMENSION
   mrizka           = ano prizpusobive vyska podlehloubky pulradku

```

```

\setupscript    [...,1...]    [...,2...,...]
1  NAME              OPT
2  metoda           = hangul hanzi nihongo ethiopic thai tibetan test
   prednastaveni    = NAME
   features          = auto

```

```

\setupscripts    [...,1...]    [...,2...,...]
1  NAME              OPT
2  inherits: \setupscript

```

```

\setupselector    [...1]    [...,2...,...]
1  NAME
2  n                = NUMMER
   max              = NUMMER

```

```

\setupshadow    [...,1...]    [...,2...,...]
1  NAME              OPT
2  pismo            = STYLE BEFEHL
   barva            = COLOR
   kontrastnibarva  = COLOR
   pokracovat       = ano ne vse
   jednotka         = ex em pt in cm mm sp bp pc dd cc nc
   weight           = NUMMER
   dx               = NUMMER
   dy               = NUMMER

```

\setupshapedparagraph [...,¹...,...]

* mp = NAME
opakovat = ano ne
seznam = NAME
metoda = cycle shift
voffset = DIMENSION
hoffset = DIMENSION
vzdalenost = DIMENSION
radky = NUMMER
sirka = DIMENSION
text = TEXT

\setupshift [...,¹...] [...,²...,...]

1 NAME ^{OPT}
2 pokracovat = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
metoda = NUMMER
dy = NUMMER
zarovnani = inherits: \nastavzarovnani
pismo = STYLE BEFEHL
barva = COLOR

\setupsidebar [...,¹...] [...,²...,...]

1 NAME ^{OPT}
2 tloustkalinky = DIMENSION
barvalinky = COLOR
alternativa = NUMMER
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
vzdalenost = DIMENSION
vzdalenostlevehookraje = DIMENSION
uroven = NUMMER
misto = vlevo vpravo uvnitr vnejsi

\setupspellchecking [...,¹...,...]

* status = start stop
metoda = 1 2 3
seznam = NAME

\setupstacking [...,¹...] [...,²...,...]

1 NAME ^{OPT}
2 define = ano ne
kriterium = NAME
cislo = NUMMER

\setupstartstop [...,¹...] [...,²...,...]

1 NAME ^{OPT}
2 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
setups = NAME
vlevo = BEFEHL
vpravo = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR
arguments = ano ne

\setupstretched [...,¹...,...]

* inherits: \setupcharacterkerning

\setupstrut [...]

* ano ne auto kap ^{OPT}přizpusobive radek implicitni CHARACTER

\setupstyle [...,¹...] [...,²...,...]

1 NAME ^{OPT}
2 metoda = prikaz
pismo = STYLE BEFEHL
barva = COLOR

`\setupsubcolumnset` [...,¹...] [...,²...,...]

```
1  NAME                      OPT
2  vrsek                    = BEFEHL
   spodek                  = BEFEHL
   mezerapred              = radek
   mezeraza                = radek
   pred                    = BEFEHL
   po                      = BEFEHL
   language                = SPRACHE
   pismo                    = STYLE BEFEHL
   barva                   = COLOR
   zarovnni                = inherits: \nastavzarovnni
```

`\setupsubformula` [...,¹...] [...,²...,...]

```
1  NAME                      OPT
2  inherits: \setupsubformulas
```

`\setupsubformulas` [...,¹...] [...,²...,...]

```
1  NAME                      OPT
2  odsadpristi = ano ne auto
```

`\setupsymbols` [...,^{*}...,...]

```
*  stylealternative = text math
```

`\setupsynctex` [...,^{*}...,...]

```
*  status    = start stop opakovat
   metoda    = min max
   compress   = ano ne
```

`\setupsynchronize` [...,¹...] [...,²...,...]

```
1  NAME                      OPT
2  vzdalenost = DIMENSION
   seznam     = NAME
   split      = TEXT
   buffer     = NAME
   text       = TEXT
   pismo      = STYLE BEFEHL
   barva      = COLOR
```

`\setupsynchronizecontent` [...,¹...] [...,²...,...]

```
1  NAME                      OPT
2  vlevo      = BEFEHL
   vpravo     = BEFEHL
   language   = SPRACHE
   pismo      = STYLE BEFEHL
   barva      = COLOR
```

`\setups` {...,^{*}...,...}

```
*  NAME
```

```

\setupTABLE [...,1...] [...,2...] [...,3...,...]
1 r c x y row column OPTprvní poslední OPTstart zahlevi kazdy liche sude jedna NUMMER -NUMMER
2 první least kazdy dve liche sude NUMMER -NUMMER
3 extras = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  barvahlavicky = COLOR
  stylhlavicky = STYLE BEFEHL
  vzdalenostlevehookraje = DIMENSION
  vzdalenostpravehookraje = DIMENSION
  vzdalenostsloupcu = DIMENSION
  maxsirka = DIMENSION
  setups = NAME
  sirkatextu = DIMENSION lokalne
  split = ano ne opakovat stranka auto
  zahlevi = opakovat
  volba = natahnout tight
  pred = BEFEHL
  po = BEFEHL
  stejnastranka = pred po obe
  spaceinbetween = inherits: \preskoc
  splitoffset = DIMENSION
  aligncharacter = ano ne
  alignmentcharacter = TEXT number->TEXT text->TEXT
  vzdalenost = DIMENSION
  barva = COLOR
  pismo = math STYLE BEFEHL
  synchronize = pozadi
  smer = normalni reverse
inherits: \nastavoramovani

```

```

\setupTEXpage [...,*...]
* inherits: \setupfittingpage

```

```

\setuptabulatemove [...,1...] [...,2...,...]
1 NAME OPT
2 xoffset = DIMENSION
  yoffset = vyska podlehloubky DIMENSION
  orientation = NUMMER

```

```

\setuptagging [...,*...,...]
* status = start stop zap vyp
  metoda = auto
  prednastaveni = basic demo mkiv uac
  uroven = NUMMER
  comment = TEXT
  volba = interakce

```

```

1 NAME OPT
2 status = start stop
misto = text odstavec vzdy zadny
kriterium = NUMBER
alternativa = NUMBER
mp = NAME
metoda = NAME
pozadi = barevne
barvapozadi = COLOR
roh = pravouhly zaobleny
uroven = NUMBER
offsetpozadi = DIMENSION
pred = BEFEHL
po = BEFEHL
zarovnani = inherits: \nastavzarovnani
pomlcka = NUMBER
polomer = DIMENSION
ramecek = zap vyp
barvaramecku = COLOR
tloustkalinky = DIMENSION
voffset = DIMENSION
offsetramecku = DIMENSION
levyoffset = ano ne standardni DIMENSION
pravyoffset = ano ne standardni DIMENSION
offsetvrsku = male stredni velke radek DIMENSION
offsetspodku = male stredni velke radek DIMENSION
pismoeno = STYLE BEFEHL
barva = COLOR

```

```

1  NAME
2  pred    = BEFEHL
   po      = BEFEHL
   faktor  = NUMMER

```

```

1  NAME
2  sirka    =  DIMENSION
   pismo    =  STYLE BEFEHL
   barva    =  COLOR

```

```

1  NAME                                OPT
2  linka      =  NAME
   note      =  NAME
   n          =  * NUMMER
   prazdne    =  ano ne zadny cislo

```

```
1  NAME                                OPT
2  misto = vlevo nastred vpravo
   inherits: \nastavoramovani
```

```

1  NAME
2  define      = ano ne
   pismeno    = STYLE BEFEHL
   barva      = COLOR
   language    = SPRACHE
   vector     = NAME
   pred       = BEFEHL
   po         = BEFEHL
   vlevo      = BEFEHL
   vpravo     = BEFEHL

```

```

\setuptweakedfont    [...1...]    [...2...]
1  NAME
2  pismoen           = STYLE BEFEHL
   meritko           = NUMMER
   xmeritko           = NUMMER
   ymeritko           = NUMMER
   xoffset            = DIMENSION
   yoffset            = DIMENSION

```

```

\setupunit      [,...1,...]   [...,...2,...]
1 NAME          OPT
2 metoda        = 1 2 3 4 5 6
  language      = SPRACHE
  alternativa   = text matematika
  order         = reverse normalni
  oddelovac     = male stredni velke normalni zadny NAME
  mezera        = male stredni velke normalni zadny NAME
  pismo         = STYLE BEFEHL
  barva         = COLOR
  volba         = drzet

```

```

\setupuserdata    [...1...]    [...2...]
1  NAME           OPT
2  pred           = BEFEHL
   po             = BEFEHL
   zarovnnani     = inherits: \nastavzarovnnani
   setups         = NAME
   pismoeno       = STYLE BEFEHL
   barva          = COLOR
   alternativa    = implicitni NAME
   KEY            = VALUE

```

```
\setupuserdataalternative  [...1...]  [...2...]
1 NAME                      OPT
2 renderingsetup = NAME
   KEY           = VALUE
```

```
\setupuserpagenumber    [...,*=.,...]  
*   viewerprefix = TEXT  
    status       = start stop zadny drzet prazdne  
    popisek      = TEXT  
    inherits: \setupcounter
```

```
\setupversion    [...]
```

* koncept soubor docasne finalni NAME

```

\setupverticalbox    [...1...]    [...2...,...]
1  NAME              OPT              OPT
2  sirka              =  lokalne DIMENSION
   vyska              =  max DIMENSION
   smer              =  normalni reverse lefttoright righttoleft
   xoffset            =  DIMENSION
   yoffset            =  DIMENSION
   pismeno            =  STYLE BEFEHL
   barva              =  COLOR
   vrsek              =  BEFEHL
   spodek             =  BEFEHL
   strut              =  ano ne
   zarovnnani         =  inherits: \nastavzarovnnani
   odsazovani         =  inherits: \nastavodsazovani

```

```
\setupviewerlayer      [...,*=...,...]
*   titul              = TEXT
    status             = start stop
    export             = ano ne
    tisknutelne        = ano ne
    rozsah              = lokalne globalne
    metoda             = zadny prikaz
```

```
\setupvspacing [...,*...]
* inherits: \vspacing OPT
```


<pre> \setupwithargument {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setupwithargumentswapped {...} {...} 1 CONTENT 2 NAME </pre>
<pre> \setupxml [...,.*,...,...] * implicitni = skryte zadny text compress = ano ne entities = ano ne </pre>
<pre> \setupxtable [...,¹...] [...,.*²...,...] 1 NAME 2 sirkatextu = DIMENSION lokalne zakladnifont = inherits: \nastavzakladnifont spaceinbetween = inherits: \preskoc volba = tight max natahnout sirka vyska fixne vyskatextu = DIMENSION maxsirka = DIMENSION vzdalenostsloupcu = DIMENSION vzdalenostlevehookraje = DIMENSION vzdalenostpravehookraje = DIMENSION zahlavi = opakovat upati = opakovat tloustkalinky = DIMENSION split = ano ne opakovat auto splitoffset = DIMENSION stejnastranka = pred po obe vzdalenost = DIMENSION aligncharacter = ano ne alignmentleftsample = TEXT alignmentrightsample = TEXT alignmentleftwidth = DIMENSION alignmentrightwidth = DIMENSION alignmentcharacter = TEXT inherits: \nastavoramovani </pre>
<pre> \setuvalue {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setuxvalue {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setvalue {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setvariable {...} {...} {...} 1 NAME 2 KEY 3 VALUE </pre>
<pre> \setvariables [...]¹ [...,.*²...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE </pre>
<pre> \setvboxregister .¹ {...} 1 CSNAME NUMBER 2 CONTENT </pre>
<pre> \setvisualizerfont [...][*] * FONT </pre>

\setvtopregister ¹ ... { ² ...} 1 CSNAME NUMBER 2 CONTENT
\setwidthof ¹ ... \to \ ² ... 1 TEXT 2 CSNAME
\setxmeasure { ¹ ...} { ² ...} 1 NAME 2 DIMENSION
\setxvalue { ¹ ...} { ² ...} 1 NAME 2 CONTENT
\setxvariable { ¹ ...} { ² ...} { ³ ...} 1 NAME 2 KEY 3 VALUE
\setxvariables [¹ ...] [² ...,... ² ...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
\SHADOW { [*] ...} * CONTENT instances: shadowed
\shadowed { [*] ...} * CONTENT
\shapecorrection [[*] ...] * vlevo vpravo obe
\shapedhbox { [*] ...} * CONTENT
\shiftbox { ¹ ...} 1 CONTENT
\SHIFT { [*] ...} * CONTENT instances: shiftup shiftdown
\shiftdown { [*] ...} * CONTENT
\shiftup { [*] ...} * CONTENT
\showallmakeup
\showattributes
\showbalancepoints [[*] ...,... [*] ...,...] * inherits: \nastavsloupce OPT

\showboxes
\showbreakpoints [...,.. [*] ...,...] * inherits: \nastavsloupce OPT
\showbtxdatasetauthors [...,.. [*] ...,...] * specification = NAME OPT dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\showbtxdatasetauthors [...*] * NAME OPT
\showbtxdatasetcompleteness [...,.. [*] ...,...] * specification = NAME OPT dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\showbtxdatasetcompleteness [...*] * NAME OPT
\showbtxdatasetfields [...,.. [*] ...,...] * specification = NAME OPT dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\showbtxdatasetfields [...*] * NAME OPT
\showbtxfields [...,.. [*] ...,...] * rotace = NUMBER OPT specification = NAME
\showbtxfields [...*] * NAME OPT
\showbtxhashedauthors [...*] * TEXT OPT
\showbtxtables [...*] * TEXT OPT
\showcolorbar [...*] * COLOR
\showcolorcomponents [...*] * COLOR
\showcolorset [...*] * COLOR
\showcolorstruts

<code>\showcharfreq</code>
<code>\showcharratio {...}</code> <code>* TEXT</code>
<code>\showinjector [...,*,...]</code> <code>* NAME OPT</code>
<code>\showjustification</code>
<code>\showkerning {...}</code> <code>* TEXT</code>
<code>\showlayoutcomponents</code>
<code>\showligature {...}</code> <code>* TEXT</code>
<code>\showligatures [...]</code> <code>* FONT</code>
<code>\showlogcategories</code>
<code>\showluatables</code>
<code>\showmargins</code>
<code>\showmathstate [¹...] {²...}</code> <code>1 DIMENSION OPT</code> <code>2 C M P S r f n d</code>
<code>\showmathstyles</code>
<code>\showmessage {¹...} {²...} {³...,...}</code> <code>1 NAME</code> <code>2 NAME NUMBER</code> <code>3 TEXT</code>
<code>\showminimalbaseline</code>
<code>\shownextbox \¹... {²...}</code> <code>1 CSNAME</code> <code>2 CONTENT</code>
<code>\showotfcomposition {¹...} {²...} {³...}</code> <code>1 FONT</code> <code>2 -1 1 +1 l2r r2l</code> <code>3 TEXT</code>
<code>\showpageprogress [[*]...]</code> <code>* ano ne vse OPT</code>
<code>\showparentchain \¹... {²...}</code> <code>1 CSNAME</code> <code>2 NAME</code>
<code>\showparwrapperstate {...}</code> <code>* NAME</code>

\showraggedrules {...} * NUMMER
\showrivers [...,.. ¹ ...,...] * inherits: \addriversto86bx
\showsetupsdefinition {...} * NAME
\showtimer {...} * TEXT
\showtokens {...} * NAME
\showtrackers
\showvalue {...} * NAME
\showvariable {... ¹ } {... ² } 1 NAME 2 KEY
\showwarning {... ¹ } {... ² } {..., ³ ...} 1 NAME 2 NAME NUMMER 3 TEXT
\schovejbloky [..., ¹ ...] [..., ² ...] 1 NAME 2 NAME OPT
\signalcharacteralign {... ¹ } {... ² } 1 NUMMER 2 NUMMER
\signalrightpage
\similartokens {... ¹ } {... ² } 1 TEXT 2 TEXT
\simplealignedbox {... ¹ } {... ² } {... ³ } 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT
\simplealignedboxplus {... ¹ } {... ² } {... ³ } {... ⁴ } 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 TEXT 4 CONTENT
\simplealignedspreadbox {... ¹ } {... ² } {... ³ } 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT

<code>\simplegroupedcommand {...} {...}</code> 1 BEFEHL 2 BEFEHL
<code>\simplegroupedcommandcs \... \...</code> 1 CSNAME 2 CSNAME
<code>\simplereversealignedbox {...} {...} {...}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT
<code>\simplereversealignedboxplus {...} {...} {...} {...}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 TEXT 4 CONTENT
<code>\singlebond</code>
<code>\sixthofsixarguments {...} {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\skiphere [...]</code> * + - DIMENSION NUMMER stranka stejnastranka
<code>\sklonene</code>
<code>\sklonenetucne</code>
<code>\slantedface</code>
<code>\slashed [...] {...}</code> 1 vse begin end ^{OPT} unset ordinary operator binary relation open close punctuation variable active uvnitr under over fraction radical nastred prime accent fenced ghost vcenter explicit imaginary differential exponential integral ellipsis function digit division factorial wrapped construct dimension unary textpunctuation unspaced experimental fake numbergroup continuation 2 CONTENT
<code>\slicepages [...] [...,...²...,...]</code> <code>[...,...³...,...]</code> 1 FILE 2 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION sirka = DIMENSION vyska = DIMENSION n = NUMMER 3 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION sirka = DIMENSION vyska = DIMENSION n = NUMMER
<code>\sloupec [...,*,...]</code> * inherits: \columnbreak ^{OPT}
<code>\slovenianNumerals {...}</code> * NUMMER

<code>\sloveniannumerals {...}</code> * NUMBER
<code>\slovo {...}</code> * TEXT
<code>\slovovpravo [...] {...}</code> 1 vpravo DIMENSION OPT 2 CONTENT
<code>\smallbodyfont</code>
<code>\smallbreak</code>
<code>\smallcappedcharacters {...}</code> * NUMBER
<code>\smallcappedromannumerals {...}</code> * NUMBER
<code>\smaller</code>
<code>\smallinfofont</code>
<code>\smallinfofontbold</code>
<code>\smallmathsymbol {...}</code> * TEXT
<code>\smallskip</code>
<code>\smash [...] {...}</code> 1 w h d t b OPT 2 CONTENT
<code>\smashbox ...</code> * CSNAME NUMBER
<code>\smashboxed ...</code> * CSNAME NUMBER
<code>\smashedhbox ... {...}</code> 1 TEXT OPT 2 CONTENT
<code>\smashedvbox ... {...}</code> 1 TEXT OPT 2 CONTENT
<code>\snappedmath {...}</code> * CONTENT
<code>\snaptogrid [...] \^... {...}</code> 1 normalni standardni OPT ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred math math:radek math:pulradku math:-line math:-halflne NAME 2 CSNAME 3 CONTENT

\snaptogrid [... ¹ ,...] \... {... ³ .} 1 inherits: \definegrid snapping 2 CSNAME 3 CONTENT
\someheadnumber [... ¹] [... ² .] 1 ABSCHNITT 2 predchozi aktualni dalsi prvni posledni
\somekindoftab [... ¹ ,... ² ,...] * alternativa = horizontalne vertikálne sirka = DIMENSION vyska = DIMENSION n = NUMMER m = NUMMER
\somelocalfloat
\somenamedheadnumber {... ¹ .} {... ² .} 1 ABSCHNITT 2 predchozi aktualni dalsi prvni posledni
\someplace {... ¹ .} {... ² .} {... ³ .} {... ⁴ .} {... ⁵ .} [... ⁶ .] 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 REFERENCE
\SORTING [... ¹] {... ² .} 1 NAME OPT 2 CONTENT instances: logo
\logo [... ¹] {... ² .} 1 NAME OPT 2 CONTENT
\spaceddigits {... ¹ .} * NUMMER
\spaceddigitsmethod
\spaceddigitseparator
\spaceddigitssymbol
\spaceorpar
\spanishNumerals {... ¹ .} * NUMMER
\spanishnumerals {... ¹ .} * NUMMER
\splitatasterisk ... ¹ \... ² \... ³ 1 TEXT 2 CSNAME 3 CSNAME

\splitatcolon ¹ ... \ ² ... \ ³ ... 1 TEXT 2 CSNAME 3 CSNAME
\splitatcolons ¹ ... \ ² ... \ ³ ... 1 TEXT 2 CSNAME 3 CSNAME
\splitatcomma ¹ ... \ ² ... \ ³ ... 1 TEXT 2 CSNAME 3 CSNAME
\splitatperiod ¹ ... \ ² ... \ ³ ... 1 TEXT 2 CSNAME 3 CSNAME
\splitfilename { ¹ ...} * FILE
\splitoffbase
\splitofffull
\splitoffkind
\splitoffname
\splitoffpath
\splitoffroot
\splitofftokens ¹ ... \from ² ... \to \ ³ ... 1 TEXT 2 TEXT 3 CSNAME
\splitofftype
\splitsequence { ¹ ...} { ² ...} 1 ano ne TEXT 2 TEXT
\splitstring ¹ ... \at ² ... \to \ ³ ... \and \ ⁴ ... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
\splitsymbol { ¹ ...} * ano ne TEXT
\spreadhbox ¹ ... * CSNAME NUMBER

<code>\stacking</code> [¹ ...] { ² ...} 1 NUMBER 2 CONTENT
<code>\STACKING</code> [¹ ...] { ² ...} 1 NUMBER 2 CONTENT
<code>\stackrel</code> { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
<code>\stackscripts</code>
<code>\stanovcislonaadpisu</code> [...] * ABSCHNITT
<code>\stanovcharakteristikuseznamu</code> [...; ¹ ...] [...; ² ...; ² ...] 1 LISTE 2 inherits: \nastavseznam OPT
<code>\start</code> [...] ... \stop * NAME OPT
<code>\startalignment</code> [...*...] ... \stopalignment * inherits: \nastavzarovnani
<code>\startallmodes</code> [...*...] ... \stopallmodes * NAME
<code>\startalternate</code> [...; [*] ...] ... \stopalternate * text = TEXT
<code>\startanchoring</code> ... \stopanchoring
<code>\startasciimode</code> ... \stopasciimode
<code>\startATTACHMENT</code> [¹ ...] [...; ² ...; ² ...] ... \stopATTACHMENT 1 NAME OPT OPT 2 inherits: \setupattachment instances: attachment
<code>\startattachment</code> [¹ ...] [...; ² ...; ² ...] ... \stopattachment 1 NAME OPT OPT 2 inherits: \setupattachment
<code>\startbalancing</code> [¹ ...] [² ...] ... \stopbalancing 1 NAME OPT OPT 2 NUMBER
<code>\startbar</code> [...*] ... \stopbar * NAME
<code>\startbarva</code> [...] ... \stopbarva * COLOR
<code>\startbbordermatrix</code> ... \stopbbordermatrix

<pre> \startbitmapimage [...,..¹...,...] ... \stopbitmapimage * barva = rgb cmyk seda sirka = DIMENSION vyska = DIMENSION x = NUMMER y = NUMMER </pre>
<pre> \startbleeding [...¹] [...,..²...,...] ... \stopbleeding 1 NAME 2 inherits: \setupbleeding </pre>
<pre> \startbordermatrix ... \stopbordermatrix </pre>
<pre> \startboxanchoring [...] ... \stopboxanchoring * + NAME </pre>
<pre> \startboxexport [...,..¹...,...] ... \stopboxexport * inherits: \setupboxexport OPT </pre>
<pre> \startbtxrenderingdefinitions [...] ... \stopbtxrenderingdefinitions * NAME </pre>
<pre> \startbuffer [...] ... \stopbuffer * NAME </pre>
<pre> \startBUFFER ... \stopBUFFER instances: hiding </pre>
<pre> \starthiding ... \stophiding </pre>
<pre> \startcatcodetable \.* ... \stopcatcodetable * CSNAME </pre>
<pre> \startcenteraligned ... \stopcenteraligned </pre>
<pre> \startclipeffect ... \stopclipeffect </pre>
<pre> \startclipframed [...,..¹...,...] ... \stopclipframed * inherits: \nastavoramovani OPT </pre>
<pre> \startcollect ... \stopcollect </pre>
<pre> \startcollecting ... \stopcollecting </pre>
<pre> \startcolorintent [...] ... \stopcolorintent * knockout overprint zadny </pre>
<pre> \startcoloronly [...] ... \stopcoloronly * COLOR </pre>
<pre> \startcolorset [...] ... \stopcolorset * NAME </pre>
<pre> \startcolumnset [...¹] [...,..²...,...] ... \stopcolumnset 1 NAME 2 inherits: \setupcolumnset </pre>

<code>\startcolumnsethspan {¹...} {²...} ... \stopcolumnsethspan</code> 1 NUMBER 2 NUMBER
<code>\startcolumnsetsheet [¹...] [²...] [³...] ... \stopcolumnsetsheet</code> 1 NAME 2 NUMBER 3 stranka
<code>\startcolumnsetsheetdelayed [¹...] [²...] ... \stopcolumnsetsheetdelayed</code> 1 NAME 2 NUMBER
<code>\startcolumnsetspan [¹...] [...,²...,...] ... \stopcolumnsetspan</code> 1 NAME 2 inherits: \setcolumnset
<code>\startcolumnsetspanwidth {[*]...} ... \stopcolumnsetspanwidth</code> * NUMBER
<code>\startcolumnsetspreadsheets [¹...] [²...] ... \stopcolumnsetspreadsheets</code> 1 NAME 2 NUMBER
<code>\startCOLUMNSET [...,[*]...,...] ... \stopCOLUMNSET</code> * inherits: \setupcolumnset OPT
<code>\startcombination [¹...] [...,²...,...] ... \stopcombination</code> 1 NAME 2 inherits: \setupcombination
<code>\startcombination [¹...] [²...] ... \stopcombination</code> 1 NAME 2 N*M
<code>\startcomparingtext [[*]...] ... \stopcomparingtext</code> * reset NAME
<code>\startcontextcode ... \stopcontextcode</code>
<code>\startcontextdefinitioncode ... \stopcontextdefinitioncode</code>
<code>\startctxfunction [*]... ... \stopctxfunction</code> * NAME
<code>\startctxfunctiondefinition [*]... ... \stopctxfunctiondefinition</code> * NAME
<code>\startcurrentcolor ... \stopcurrentcolor</code>
<code>\startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper</code>
<code>\startdelimited [¹...] [²...] [...,³...,...] ... \stopdelimited</code> 1 NAME 2 SPRACHE 3 inherits: \startzuzeni

<code>\startexpanded ... \stopexpanded</code>
<code>\startexpandedcollect ... \stopexpandedcollect</code>
<code>\startextendedcatcodetable \.* ... \stopextendedcatcodetable</code> <code>* CSNAME</code>
<code>\startexternalfigurecollection [.*] ... \stopexternalfigurecollection</code> <code>* NAME</code>
<code>\startfacingfloat [.*] ... \stopfacingfloat</code> <code>* NAME</code>
<code>\startfittingpage [...]¹ [...,...²...,...]^{OPT} ... \stopfittingpage</code> <code>1 NAME</code> <code>2 inherits: \setupfittingpage</code>
<code>\startFITTINGPAGE [...,...[*]...,...]^{OPT} ... \stopFITTINGPAGE</code> <code>* inherits: \setupfittingpage</code> <code>instances: TEXpage MPpage</code>
<code>\startMPpage [...,...[*]...,...]^{OPT} ... \stopMPpage</code> <code>* inherits: \setupfittingpage</code>
<code>\startTEXpage [...,...[*]...,...]^{OPT} ... \stopTEXpage</code> <code>* inherits: \setupfittingpage</code>
<code>\startfixne [.*] ... \stopfixne</code> <code>* nizko nastred vys^{OPT}oko nivy implicitni</code>
<code>\startfloatcombination [...,...[*]...,...]^{OPT} ... \stopfloatcombination</code> <code>* inherits: \setupcombination</code>
<code>\startfloatcombination [.*] ... \stopfloatcombination</code> <code>* N*M NAME^{OPT}</code>
<code>\startFLOATtext [...,¹...] [...,²...] {...³} ... \stopFLOATtext</code> <code>1 split keeptogether vzdy v^{OPT}levo vpravo uvni^{OPT}tr vn^{OPT}jsi zpetnamezera cutspace ivlevo ivpravo naokraji lev^{OPT}yokraj prav^{OPT}yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append</code> <code>2 REFERENCE</code> <code>3 TEXT</code> <code>instances: chemical figure table intermezzo graphic</code>
<code>\startfiguretext [...,¹...] [...,²...] {...³} ... \stopfiguretext</code> <code>1 split keeptogether vzdy v^{OPT}levo vpravo uvni^{OPT}tr vn^{OPT}jsi zpetnamezera cutspace ivlevo ivpravo naokraji lev^{OPT}yokraj prav^{OPT}yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append</code> <code>2 REFERENCE</code> <code>3 TEXT</code>

<code>\startgraphictext [...¹,...] [...²,...] {...³} ... \stopgraphictext</code> 1 split keepetogether vzdy vlev^{OPT}o vpravo uvnitr^{OPT}vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append 2 REFERENCE 3 TEXT
<code>\startchemicaltext [...¹,...] [...²,...] {...³} ... \stopchemicaltext</code> 1 split keepetogether vzdy vlev^{OPT}vpravo uvnitr^{OPT}vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append 2 REFERENCE 3 TEXT
<code>\startintermezzotext [...¹,...] [...²,...] {...³} ... \stopintermezzotext</code> 1 split keepetogether vzdy vlev^{OPT}vpravo uvnitr^{OPT}vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append 2 REFERENCE 3 TEXT
<code>\starttabletext [...¹,...] [...²,...] {...³} ... \stoptabletext</code> 1 split keepetogether vzdy vlev^{OPT}vpravo uvnitr^{OPT}vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append 2 REFERENCE 3 TEXT
<code>\startfont [...[*]] ... \stopfont</code> * FONT OPT
<code>\startfontclass [...[*]] ... \stopfontclass</code> * kazdy NAME
<code>\startfontsolution [...[*]] ... \stopfontsolution</code> * NAME
<code>\startformulacombination [...[*],...[*],...] ... \stopformulacombination</code> * inherits: \setupcombination OPT
<code>\startformulacombination [...[*]] ... \stopformulacombination</code> * N*M OPT
<code>\startframedcell [...[*],...[*],...] ... \stopframedcell</code> * inherits: \nastavoramovani OPT
<code>\startframedcontent [...[*]] ... \stopframedcontent</code> * NAME vyp OPT
<code>\startframedrow [...[*],...[*],...] ... \stopframedrow</code> * inherits: \nastavoramovani OPT
<code>\startframedtable [...¹] [...²,...²,...] ... \stopframedtable</code> 1 NAME OPT OPT 2 inherits: \nastavoramovani

<code>\startgraphicgroup ... \stopgraphicgroup</code>
<code>\startgridcorrection [...] ... \stopgridcorrection</code> <code>* reset [+-]T [+-]L [+-]H [+-]^{OPT}Q [+-]Z [+-]I</code>
<code>\startgridsnapping [...] ... \stopgridsnapping</code> <code>* normalni standardni ano stříktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko</code> <code>zadny radek strut box min max nastred math math:radek math:pulradku math:-line math:-halflne NAME</code>
<code>\startgridsnapping [...]*...] ... \stopgridsnapping</code> <code>* inherits: \definegridsnapping^{OPT}</code>
<code>\starthangrange ... \stophangrange</code>
<code>\starthangrangestep ... \stophangrangestep</code>
<code>\starthboxestohbox ... \stophboxestohbox</code>
<code>\starthboxregister ... \stophboxregister</code> <code>* CSNAME NUMMER</code>
<code>\starthHELP [...] ... \stopHELP</code> <code>* REFERENCE ^{OPT}</code> <code>instances: helptext</code>
<code>\starthelptext [...] ... \stophelptext</code> <code>* REFERENCE ^{OPT}</code>
<code>\starthiddencontent ... \stophiddencontent</code>
<code>\starthhighlight [...] ... \stophighlight</code> <code>* NAME</code>
<code>\starthorizontalbox [¹] [²] ... \stophorizontalbox</code> <code>1 NAME ^{OPT}</code> <code>2 inherits: \setuphorizontalbox ^{OPT}</code>
<code>\starthyphenation [...]*...] ... \stophyphenation</code> <code>* original tex implicitni hyphenate expanded traditional zadny</code>
<code>\startcharacteralign [...]*...] ... \stopcharacteralign</code> <code>* inherits: \setupcharacteralign</code>
<code>\startcharacteralign [...] ... \stopcharacteralign</code> <code>* TEXT number->TEXT text->TEXT^{OPT}</code>
<code>\startcharactertable [...] ... \stopcharactertable</code> <code>* NAME</code>
<code>\startcheckedfences ... \stopcheckedfences</code>
<code>\startchemical [¹] [²] ... \stopchemical</code> <code>1 NAME ^{OPT}</code> <code>2 inherits: \setupchemical ^{OPT}</code>
<code>\startchemicalformula ... \stopchemicalformula</code>

<pre> \startchemistry [...,..[*]...,...] ... \stopchemistry * inherits: \setupchemistry ^{OPT} </pre>
<pre> \startimage [...,..[*]...,...] ... \stopimage * descriptiontext = TEXT alternativetext = TEXT </pre>
<pre> \startimath ... \stopimath </pre>
<pre> \startindentedtext [...] ... \stopindentedtext * NAME </pre>
<pre> \startINDENTEDTEXT ... \stopINDENTEDTEXT </pre>
<pre> \startinstallaligncommand [...] ... \stopinstallaligncommand * NAME </pre>
<pre> \startinterakce [...] ... \stopinterakce * skryte NAME </pre>
<pre> \startinteraktivnimenu [...] ... \stopinteraktivnimenu * NAME </pre>
<pre> \startinterface \stopinterface * vse SPRACHE </pre>
<pre> \startintertext ... \stopintertext </pre>
<pre> \startitemgroup [...¹] [...,²...] [...,³...,...] ... \stopitemgroup 1 NAME 2 inherits: \setupitemgroup 3 inherits: \setupitemgroup </pre>
<pre> \startITEMGROUptable [...,¹...] [...,²...,...] ... \stopITEMGROUptable 1 inherits: \setupitemgroup 2 inherits: \setupitemgroup instances: itemize </pre>
<pre> \startitemizetable [...,¹...] [...,²...,...] ... \stopitemizetable 1 inherits: \setupitemgroup 2 inherits: \setupitemgroup </pre>
<pre> \startITEMGROUP [...,¹...] [...,²...,...] ... \stopITEMGROUP 1 inherits: \setupitemgroup 2 inherits: \setupitemgroup instances: itemize </pre>
<pre> \startitemize [...,¹...] [...,²...,...] ... \stopitemize 1 inherits: \setupitemgroup 2 inherits: \setupitemgroup </pre>
<pre> \startJSCode ...¹ ...² ...³ ... \stopJSCode 1 NAME 2 uses 3 NAME </pre>
<pre> \startJSreamble ...¹ ...² ...³ ... \stopJSreamble 1 NAME 2 uzito 3 now later </pre>

* SPRACHE

* REFERENCE

```
\startknockout ... \stopknockout
```

\startkomentarstranky ... \stopkomentarstranky

```
1  TEXT                                OPT
2  inherits: \nastavkomentar
instances: comment
```

```
1 TEXT OPT
2 inherits: \nastavkomentar
```

* FILE *

* FILE *

* NAME

* SPRACHE

* NAME

* vlevo nastred vpravo max

```
*   prazdny inherits: \preskoc
```

```
1 filler NAME
2 inherits: \setuplinefiller
```

```
1  REFERENCE
2  TEXT
instances: linenote
```

```
1 REFERENCE
2 TEXT
```

```

1  NAME                                OPT
2  pokracovat = ano ne
   start      = NUMBER
   krok       = NUMBER
   metoda     = stranka prvni dalsi

```

```
1  NAME
2  pokračovat NUMMER
```

`\startlinetable ... \stoplinetable`

\startlinetablebody ... \stoplinetablebody

```
\startlinetablecell    [...,*=...,...] ... \stoplinetablecell
* inherits: \setuplinetable          OPT
```

\startlinetablehead ... \stoplinetablehead

```
\startlocalbox [...] ... \stoplocalbox
* NAME
```

```
\startlocalboxrange    [...] ... \stoplocalboxrange
*   NAME
```

\startlocalfootnotes ... \stoplocalfootnotes

```
\startlocalheadsetup ... \stoplocalheadsetup
```

```
\startlocallinecorrection    [...;...] ... \stoplocallinecorrection
*   prazdny inherits: \preskoc      OPT
```

```
\startlocalnotes    [...,*...] ... \stoplocalnotes
*   NAME
```

```
\startlocalsetups    [...] ... \stoplocalsetups
*   NAME
```

```
\startlocalsetups    ... .. \stoplocalsetups
*   NAME
```

\startlua ... \stoplua

`\startluacode ... \stopluacode`

```
\startluaparameterset    [...] ... \stopluaparameterset
*    NAME
```

```
\startluasetups    [...] ... \stopluasetups
* NAME
```

```
\startluasetups    ... .. \stopluasetups
*   NAME
```

```
\startMPclip    {...} ... \stopMPclip
*   NAME
```

```
\startMPcode  {...} ... \stopMPcode
*  metafun minifun exTrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost
    doublepost binarypost decimalpost simplefun
```

<pre> \startMPcode [...,*...,...] ... \stopMPcode * instance = metafun minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost doublepost binarypost decimalpost simplefun stacking = TEXT descriptiontext = TEXT alternativetext = TEXT </pre>
<pre> \startMPdefinitions {.*} ... \stopMPdefinitions * metafun minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost doublepost binarypost decimalpost simplefun </pre>
<pre> \startMPdrawing [...*] ... \stopMPdrawing * - OPT </pre>
<pre> \startMPenvironment [...*] ... \stopMPenvironment * reset globalne + OPT </pre>
<pre> \startMPextensions {...,*...} ... \stopMPextensions * metafun minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost doublepost binarypost decimalpost simplefun </pre>
<pre> \startMPimage [...,*...,...] ... \stopMPimage * descriptiontext = TEXT OPT alternativetext = TEXT </pre>
<pre> \startMPinclusions [...¹] {...²} ... \stopMPinclusions 1 + OPT OPT 2 metafun minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost doublepost binarypost decimalpost simplefun </pre>
<pre> \startMPinitializations ... \stopMPinitializations </pre>
<pre> \startMPoverlaydata ... \stopMPoverlaydata </pre>
<pre> \startMPpositiongraphic {...¹} {...²,...} ... \stopMPpositiongraphic 1 NAME OPT 2 KEY </pre>
<pre> \startMPpositionmethod {...*} ... \stopMPpositionmethod * NAME </pre>
<pre> \startMPrun {...*} ... \stopMPrun * NAME OPT </pre>
<pre> \startmarginalnilinka [...*] ... \stopmarginalnilinka * NUMMER OPT </pre>
<pre> \startmarginalnilinka [...,*...,...] ... \stopmarginalnilinka * inherits: \setupmarginrule OPT </pre>
<pre> \startmarginblock [...*] ... \stopmarginblock * NAME OPT </pre>
<pre> \startmarkedcontent [...*] ... \stopmarkedcontent * reset vse NAME OPT </pre>
<pre> \startmarkpages [...,*...] ... \stopmarkpages * NAME </pre>

<pre> \startmatematika [...] ... \stopmatematika * implicitni i:default i:half i:tight i:fixed NAME </pre>
<pre> \startMATHALIGNMENT [...,...[*]...,...] ... \stopMATHALIGNMENT * inherits: \setupmathalignment ^{OPT} instances: align mathalignment </pre>
<pre> \startalign [...,...[*]...,...] ... \stopalign * inherits: \setupmathalignment ^{OPT} </pre>
<pre> \startmathalignment [...,...[*]...,...] ... \stopmathalignment * inherits: \setupmathalignment ^{OPT} </pre>
<pre> \startMATHCASES [...,...[*]...,...] ... \stopMATHCASES * inherits: \setupmathcases ^{OPT} instances: cases mathcases </pre>
<pre> \startcases [...,...[*]...,...] ... \stopcases * inherits: \setupmathcases ^{OPT} </pre>
<pre> \startmathcases [...,...[*]...,...] ... \stopmathcases * inherits: \setupmathcases ^{OPT} </pre>
<pre> \startmathexport [...,...[*]...,...] ... \stopmathexport * inherits: \setupmathexport ^{OPT} </pre>
<pre> \startmathfenced [¹...] [...,...²...,...] ... \stopmathfenced 1 parenthesis bracket brace angle doubleangle bar doublebar triplebar solidus floor ceiling moustache uppercorner lowercorner group openbracket nothing mirroredparenthesis mirroredbracket mirroredbrace mirroredangle mirroreddoubleangle mirroredbar mirroreddoublebar mirroredtriplebar mirroredsolidus mirroredfloor mirroredceiling mirroredmoustache mirroreduppercorner mirroredlowercorner mirroredgroup mirroredopenbracket mirrorednothing interval openinterval leftopeninterval rightopeninterval NAME 2 inherits: \setupmathfences </pre>
<pre> \startMATHMATRIX [...,...[*]...,...] ... \stopMATHMATRIX * inherits: \setupmathmatrix ^{OPT} instances: matrix mathmatrix thematrix </pre>
<pre> \startmathmatrix [...,...[*]...,...] ... \stopmathmatrix * inherits: \setupmathmatrix ^{OPT} </pre>
<pre> \startmatrix [...,...[*]...,...] ... \stopmatrix * inherits: \setupmathmatrix ^{OPT} </pre>
<pre> \startthematrix [...,...[*]...,...] ... \stopthematrix * inherits: \setupmathmatrix ^{OPT} </pre>
<pre> \startmathmeaning ... \stopmathmeaning </pre>
<pre> \startmathmode ... \stopmathmode </pre>

`\startMATHOPERATOR` $[...,\dot{...}]$... `\stopMATHOPERATOR`
 * inherits: `\setupmathoperators` ^{OPT}
 instances: `integral iintegral iiintegral iiiintegral int iint iiint iiiint oint oint oiiint`
`intc ointc aointc sumint barint doublebarint slashint aoldownintc rectangularpoleintc`
`semicirclepoleintc circlepoleoutsideintc circlepoleinsideintc squareintc hookleftarrowint`
`timesint capint cupint upperint lowerint sum blackboardsum modtwosum prod coprod bigwedge`
`bigvee bigcap bigcup bigodot bigoplus bigotimes bigudot biguplus bigsqcap bigsqcup bigtimes`
`leftouterjoin rightouterjoin fullouterjoin bigbottom bigtop bigsolidus bigreversesolidus`
`bigdoublewedge bigdoublevee`

`\startaoldownintc` $[...,\dot{...}]$... `\stopaoldownintc`
 * inherits: `\setupmathoperators` ^{OPT}

`\startaointc` $[...,\dot{...}]$... `\stopaointc`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbarint` $[...,\dot{...}]$... `\stopbarint`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigbottom` $[...,\dot{...}]$... `\stopbigbottom`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigcap` $[...,\dot{...}]$... `\stopbigcap`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigcup` $[...,\dot{...}]$... `\stopbigcup`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigdoublevee` $[...,\dot{...}]$... `\stopbigdoublevee`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigdoublewedge` $[...,\dot{...}]$... `\stopbigdoublewedge`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigodot` $[...,\dot{...}]$... `\stopbigodot`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigoplus` $[...,\dot{...}]$... `\stopbigoplus`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigotimes` $[...,\dot{...}]$... `\stopbigotimes`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigreversesolidus` $[...,\dot{...}]$... `\stopbigreversesolidus`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigsolidus` $[...,\dot{...}]$... `\stopbigsolidus`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigsqcap` $[...,\dot{...}]$... `\stopbigsqcap`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigsqcup` $[...,\dot{...}]$... `\stopbigsqcup`
 * inherits: `\setupmathoperators` ^{OPT}

`\startbigtimes` $[...,\dot{...}]$... `\stopbigtimes`
 * inherits: `\setupmathoperators` ^{OPT}

$\backslash\mathrm{startbigtop} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopbigtop}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startbigudot} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopbigudot}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startbiguplus} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopbiguplus}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startbigvee} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopbigvee}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startbigwedge} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopbigwedge}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startblackboardsum} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopblackboardsum}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startcapint} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopcapint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startcirclepoleinsideintc} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopcirclepoleinsideintc}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startcirclepoleoutsideintc} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopcirclepoleoutsideintc}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startcoprod} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopcoprod}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startcupint} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopcupint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startdoublebarint} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopdoublebarint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startfullouterjoin} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopfullouterjoin}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{starthookleftarrowint} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stophookleftarrowint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startiiint} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopiiint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startiiintegral} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopiiintegral}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startiint} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopiint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startiiintegral} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopiiintegral}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startiint} \quad [\dots\overset{*}{=}\dots] \dots \backslash\mathrm{stopiint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$

$\backslash\mathrm{startiintegral} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopiintegral}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startint} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}$
$\backslash\mathrm{startintc} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopintc}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startintegral} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopintegral}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startleftouterjoin} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopleftouterjoin}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startlowerint} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stoplowerint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startmodtwosum} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopmodtwosum}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startoiint} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopoiint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startoiint} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopoiint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startoint} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopoint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startointc} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopointc}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startprod} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopprod}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startrectangularpoleintc} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stoprectangularpoleintc}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startrightouterjoin} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stoprightouterjoin}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startsemicirclepoleintc} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopsemicirclepoleintc}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startslashint} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopslashint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startsquareintc} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopsquareintc}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startsum} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopsum}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$
$\backslash\mathrm{startsumint} \quad [\dots,\dots^* \dots] \dots \backslash\mathrm{stopsumint}$ $\ast \quad \mathrm{inherits:} \backslash\mathrm{setupmathoperators}^{\mathrm{OPT}}$

$\backslash\starttimesint$ [...] $\backslash\stoptimesint$ * inherits: $\backslash\setupmathoperators$ ^{OPT}
$\backslash\startupperint$ [...] $\backslash\stopupperint$ * inherits: $\backslash\setupmathoperators$
$\backslash\startMATHSIMPLEALIGN$ [...] $\backslash\stopMATHSIMPLEALIGN$ * inherits: $\backslash\setupmathsimplealign$ ^{OPT} instances: equationsystem lequationsystem reequationsystem
$\backslash\startequationsystem$ [...] $\backslash\stopequationsystem$ * inherits: $\backslash\setupmathsimplealign$ ^{OPT}
$\backslash\startlequationsystem$ [...] $\backslash\stoplequationsystem$ * inherits: $\backslash\setupmathsimplealign$ ^{OPT}
$\backslash\startrequationsystem$ [...] $\backslash\stoprequationsystem$ * inherits: $\backslash\setupmathsimplealign$ ^{OPT}
$\backslash\startmathstyle$ [...] $\backslash\stopmathstyle$ * obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME
$\backslash\startmatrices$ [...] $\backslash\stopmatrices$ * inherits: $\backslash\setupmathmatrix$ ^{OPT}
$\backslash\startmatrixanchors$... $\backslash\stopmatrixanchors$
$\backslash\startmaxaligned$... $\backslash\stopmaxaligned$
$\backslash\startmiddlealigned$... $\backslash\stopmiddlealigned$
$\backslash\startmixedcolumns$ [...] $\backslash\stopmixedcolumns$ 1 NAME ^{OPT} ^{OPT} 2 inherits: $\backslash\setupmixedcolumns$
$\backslash\startMIXEDCOLUMNS$ [...] $\backslash\stopMIXEDCOLUMNS$ * inherits: $\backslash\setupmixedcolumns$ ^{OPT} instances: itemgroupcolumns boxedcolumns columns
$\backslash\startboxedcolumns$ [...] $\backslash\stopboxedcolumns$ * inherits: $\backslash\setupmixedcolumns$ ^{OPT}
$\backslash\startcolumns$ [...] $\backslash\stopcolumns$ * inherits: $\backslash\setupmixedcolumns$ ^{OPT}
$\backslash\startitemgroupcolumns$ [...] $\backslash\stopitemgroupcolumns$ * inherits: $\backslash\setupmixedcolumns$ ^{OPT}
$\backslash\startmode$ [...] $\backslash\stopmode$ * NAME
$\backslash\startmodeset$ [...] $\backslash\stopmodeset$ 1 NAME implicitni 2 CONTENT
$\backslash\startmodule$ [...] $\backslash\stopmodule$ * FILE

\startmoduletestsection ... \stopmoduletestsection
\startmodule [*] . . . \stopmodule * FILE
\startmulticolumns [..., [*] ...] ... \stopmulticolumns * inherits: \setupmulticolumns OPT
\startnadpis [...] { ² } ... \stopnadpis 1 REFERENCE OPT 2 TEXT
\startnamedformula [¹] [..., ² ,...] ... \stopnamedformula 1 NAME OPT 2 zhustene tight nastred podlehloubky radek pulradku -radek -pulradku ramecek male DIMENSION
\startnamedformula [¹] [..., ² ...,] ... \stopnamedformula 1 NAME OPT 2 inherits: \nastavrovnice
\startnamedmatrix [¹] [..., ² ...,] { ³ } ... \stopnamedmatrix 1 NAME 2 inherits: \setupmathmatrix 3 CONTENT
\startnamednotation [¹] [..., ² ,...] ... \stopnamednotation 1 NAME OPT 2 REFERENCE
\startnamednotation [¹] [..., ² ...,] ... \stopnamednotation 1 NAME 2 titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT
\startnamedsection [¹] [..., ² ...,] [..., ³ ...,] ... \stopnamedsection 1 ABSCHNITT 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT vlastnicislo = TEXT placeholder = TEXT 3 KEY = VALUE
\startnamedsubformulas [..., ¹ ,...] { ² } ... \stopnamedsubformulas 1 + - REFERENCE OPT 2 TEXT
\startnamedtyping [¹] [..., ² ...,] ... \stopnamedtyping 1 NAME OPT 2 inherits: \nastavopis
\startnamedtyping [¹] [..., ² ,...] ... \stopnamedtyping 1 NAME OPT 2 pokracovat
\startnaproti ... \stopnaproti

$\backslash$ startnarrower [...] [...] ... $\backslash$ stopnarrower * [-+]vlevo [-+]nastred [OPT]vpravo NUMBER*vlevo NUMBER*nastred NUMBER*vpravo reset reverse
$\backslash$ startNARROWER [...] [...] ... $\backslash$ stopNARROWER * [-+]vlevo [-+]nastred [OPT]vpravo NUMBER*vlevo NUMBER*nastred NUMBER*vpravo reset reverse
$\backslash$ startnegativ ... $\backslash$ stopnegativ
$\backslash$ startnicelyfilledbox [...] [...] ... $\backslash$ stopnicelyfilledbox * sirka = DIMENSION OPT vyska = DIMENSION offset = DIMENSION strut = ano ne
$\backslash$ startnointerference ... $\backslash$ stopnointerference
$\backslash$ startnotallmodes [...] [...] ... $\backslash$ stopnotallmodes * NAME
$\backslash$ startnotext ... $\backslash$ stopnotext
$\backslash$ startnotmode [...] [...] ... $\backslash$ stopnotmode * NAME
$\backslash$ startobrazek [...] [...] [...] [...] ... $\backslash$ stopobrazek 1 NAME OPT 2 FILE 3 inherits: \externiobraz
$\backslash$ startodlozit [...] [...] ... $\backslash$ stopodlozit * [-+]NUMBER OPT
$\backslash$ startodstavec [...] [...] [...] [...] ... $\backslash$ stopodstavec 1 NAME OPT OPT 2 inherits: \setupparagraph
$\backslash$ startoramovani [...] [...] [...] [...] ... $\backslash$ stoporamovani 1 NAME OPT OPT 2 inherits: \nastavoramovani
$\backslash$ startFRAMEDTEXT [...] [...] [...] [...] ... $\backslash$ stopFRAMEDTEXT 1 vlevo vpravo nastred začny OPT 2 inherits: \setupframedtext instances: framedtext
$\backslash$ startframedtext [...] [...] [...] [...] ... $\backslash$ stopframedtext 1 vlevo vpravo nastred začny OPT 2 inherits: \setupframedtext
$\backslash$ startoutputstream [...] [...] ... $\backslash$ stopoutputstream * NAME
$\backslash$ startoutputsubstream [...] [...] ... $\backslash$ stopoutputsubstream * NAME
$\backslash$ startoverlayMPgraphic {...} ... $\backslash$ stopoverlayMPgraphic * NAME
$\backslash$ startoverprint ... $\backslash$ stopoverprint

```
\startPDFalternativetext  {...} ... \stopPDFalternativetext
*   TEXT
```

```
\startPDFhighlight    [...]1    [...]2 ... \stopPDFhighlight
1  NAME                OPT
2  TEXT
```

```
\startpageblock    [...] ... \stoppageblock
*   NAME
```

```
\startpagecolumns    [...,*=...,...] ... \stoppagecolumns
* inherits: \setuppagecolumns    OPT
```

\startPAGECOLUMNS ... \stopPAGECOLUMNS

```
\startpagecolumns    [...] ... \stoppagecolumns
*   NAME                OPT
```

```
\startpagefigure    [^1]    [...,^2,...] ... \stoppagefigure
1  FILE                                OPT
2  offset = implicitni prekryv zadny DIMENSION
```

```
\startpagelayout    [...] ... \stoppagelayout
*   stranka levastranka pravastranka
```

```
\startpar    [.1.]    [...2...2...] ... \stoppar
1  NAME      OPT      OPT
2  inherits: \setupparagraph
```

```
\startparagraphs    [...] ... \stopparagraphs
*    NAME
```

```
\startparagraphcell ... \stopparagraphcell
```

```
\startparagraphshape    [... ] ... \stopparagraphshape
*   NAME
```

```
\startPARAGRAPHS ... \stopPARAGRAPHS
```

```
\startPARALLEL ... \stopPARALLEL
```

```
\startparbuilder [...] ... \stopparbuilder
* implicitni oneline basic NAME
```

```
\startpatterns    [...] ... \stoppatterns
*   SPRACHE           OPT
```

```

\startplacefloat    [...1]    [...2...2...]    [...3...3...] ... \stopplacefloat
1  SINGULAR
2  titul            = TEXT
   zalozka          = TEXT
   znaceni           = TEXT
   seznam           = TEXT
   misto            = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                     levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                     naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                     tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                     visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                     nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd append
   odkaz            = REFERENCE
   referencetext    = TEXT
3  KEY = VALUE

```

```

\startplacefloattext [...1]    [...2...2...]    [...3...3...] ... \stopplacefloattext
1  NAME
2  titul            = TEXT
   zalozka          = TEXT
   znaceni           = TEXT
   seznam           = TEXT
   misto            = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                     levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                     naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                     tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                     visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                     nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd append
   odkaz            = REFERENCE
   referencetext    = TEXT
3  KEY = VALUE

```

```

\startumistiFLOAttext [...1...1...]    [...2...2...] ... \stopumistiFLOAttext
1  titul            = TEXT
   zalozka          = TEXT
   znaceni           = TEXT
   seznam           = TEXT
   misto            = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                     levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                     naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                     tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                     visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                     nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd append
   odkaz            = REFERENCE
   referencetext    = TEXT
2  KEY = VALUE
instances: chemical figure table intermezzo graphic

```

```

\startumistifiguretext [...1...1...]    [...2...2...] ... \stopumistifiguretext
1  titul            = TEXT
   zalozka          = TEXT
   znaceni           = TEXT
   seznam           = TEXT
   misto            = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                     levyokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                     naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                     tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                     visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                     nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd append
   odkaz            = REFERENCE
   referencetext    = TEXT
2  KEY = VALUE

```

```

\startumistigraphictext  [...,\sfrac{1}{2}...,...]  [...,\sfrac{2}{2}...,...] ... \stopumistigraphictext
1  titul                 = TEXT
    zalozka              = TEXT
    znaceni              = TEXT
    seznam              = TEXT
    misto                = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                          lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                          naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                          tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                          visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                          nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd append

    odkaz                = REFERENCE
    referencetext        = TEXT
2  KEY = VALUE

```

```

\startumistichemicaltext  [...,\sfrac{1}{2}...,...]  [...,\sfrac{2}{2}...,...] ... \stopumistichemicaltext
1  titul                 = TEXT
    zalozka              = TEXT
    znaceni              = TEXT
    seznam              = TEXT
    misto                = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                          lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                          naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                          tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                          visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                          nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd append

    odkaz                = REFERENCE
    referencetext        = TEXT
2  KEY = VALUE

```

```

\startumistiintermezzotext  [...,\sfrac{1}{2}...,...]  [...,\sfrac{2}{2}...,...] ... \stopumistiintermezzotext
1  titul                 = TEXT
    zalozka              = TEXT
    znaceni              = TEXT
    seznam              = TEXT
    misto                = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                          lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                          naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                          tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                          visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                          nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd append

    odkaz                = REFERENCE
    referencetext        = TEXT
2  KEY = VALUE

```

```

\startumistitabletext  [...,\sfrac{1}{2}...,...]  [...,\sfrac{2}{2}...,...] ... \stopumistitabletext
1  titul                 = TEXT
    zalozka              = TEXT
    znaceni              = TEXT
    seznam              = TEXT
    misto                = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                          lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                          naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                          tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                          visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                          nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd append

    odkaz                = REFERENCE
    referencetext        = TEXT
2  KEY = VALUE

```

```

\startumistiFLOAT  [...,\sfrac{1}{2}...,...]  [...,\sfrac{2}{2}...,...] ... \stopumistiFLOAT
1  titul                 = TEXT
    zalozka              = TEXT
    znaceni              = TEXT
    seznam              = TEXT
    misto                = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                          lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                          naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                          tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                          visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                          nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd append

    odkaz                = REFERENCE
    referencetext        = TEXT
2  KEY = VALUE

instances: chemical figure table intermezzo graphic

```

```

\startumistifigure   [...,\sfrac{1}{2}...,...]   [...,\sfrac{2}{2}...,...] ... \stopumistifigure
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    misto             = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                        lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                        naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                        tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                        visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                        nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append

    odkaz             = REFERENCE
    referencetext     = TEXT
2  KEY = VALUE

```

```

\startumistigraphic [...,\sfrac{1}{2}...,...]   [...,\sfrac{2}{2}...,...] ... \stopumistigraphic
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    misto             = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                        lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                        naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                        tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                        visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                        nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append

    odkaz             = REFERENCE
    referencetext     = TEXT
2  KEY = VALUE

```

```

\startumistichemical [...,\sfrac{1}{2}...,...]   [...,\sfrac{2}{2}...,...] ... \stopumistichemical
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    misto             = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                        lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                        naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                        tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                        visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                        nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append

    odkaz             = REFERENCE
    referencetext     = TEXT
2  KEY = VALUE

```

```

\startumistiintermezzo [...,\sfrac{1}{2}...,...]   [...,\sfrac{2}{2}...,...] ... \stopumistiintermezzo
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    misto             = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                        lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                        naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                        tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                        visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                        nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append

    odkaz             = REFERENCE
    referencetext     = TEXT
2  KEY = VALUE

```

```

\startumistitable   [...,\sfrac{1}{2}...,...]   [...,\sfrac{2}{2}...,...] ... \stopumistitable
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    misto             = split keep together vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji
                        lev yokraj prav yokraj levahrana pravahrana innermargin outermargin inneredge outeredge text
                        naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive tight
                        tolerantni velmitolerantni 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
                        visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka odstavec
                        nekde effective zahlavi upati tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd append

    odkaz             = REFERENCE
    referencetext     = TEXT
2  KEY = VALUE

```


$\backslash\text{startplacepairedbox}$ [$\overset{1}{\dots}$] [$\dots,\dots,\overset{2}{\dots},\dots$] ... $\backslash\text{stopplacepairedbox}$ 1 NAME 2 inherits: $\backslash\text{setuppairedbox}$
$\backslash\text{startumistiPAIREDBOX}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopumistiPAIREDBOX}$ * inherits: $\backslash\text{setuppairedbox}$ instances: legend
$\backslash\text{startumistilegend}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopumistilegend}$ * inherits: $\backslash\text{setuppairedbox}$
$\backslash\text{startpolozka}$ [$\dots,\overset{*}{\dots}$] ... $\backslash\text{stoppolozka}$ * REFERENCE
$\backslash\text{startPOPIS}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopPOPIS}$ * titul = TEXT^{OPT} * zalozka = TEXT * seznam = TEXT * odkaz = REFERENCE * referencetext = TEXT
$\backslash\text{startPOPIS}$ [$\dots,\overset{1}{\dots}$] { $\dots$ } ... $\backslash\text{stopPOPIS}$ 1 REFERENCE OPT 2 TEXT OPT
$\backslash\text{startpositioning}$ [$\overset{1}{\dots}$] [$\dots,\dots,\overset{2}{\dots},\dots$] ... $\backslash\text{stoppositioning}$ 1 NAME OPT 2 inherits: $\backslash\text{nastavumistovani}$
$\backslash\text{startpositionoverlay}$ { $\dots$ } ... $\backslash\text{stoppositionoverlay}$ * NAME
$\backslash\text{startpositiv}$... $\backslash\text{stoppositiv}$
$\backslash\text{startpostponingnotes}$... $\backslash\text{stoppostponingnotes}$
$\backslash\text{startpozadi}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stoppozadi}$ * inherits: $\backslash\text{nastavpozadi}^{\text{OPT}}$
$\backslash\text{startPOZADI}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopPOZADI}$ * inherits: $\backslash\text{nastavpozadi}^{\text{OPT}}$ instances: pozadi
$\backslash\text{startNOTE}$ [$\dots,\overset{*}{\dots}$] ... $\backslash\text{stopNOTE}$ * REFERENCE OPT instances: footnote endnote mathnote publicationnote
$\backslash\text{startNOTE}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopNOTE}$ * titul = TEXT^{OPT} * zalozka = TEXT * seznam = TEXT * odkaz = REFERENCE * referencetext = TEXT instances: footnote endnote mathnote publicationnote
$\backslash\text{startendnote}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopendnote}$ * titul = TEXT OPT * zalozka = TEXT * seznam = TEXT * odkaz = REFERENCE * referencetext = TEXT

<code>\startfootnote</code> <code>[...,*...]</code> ... <code>\stopfootnote</code> * <code>titul</code> = TEXT OPT <code>zalozka</code> = TEXT <code>seznam</code> = TEXT <code>odkaz</code> = REFERENCE <code>referencetext</code> = TEXT
<code>\startmathnote</code> <code>[...,*...]</code> ... <code>\stopmathnote</code> * <code>titul</code> = TEXT OPT <code>zalozka</code> = TEXT <code>seznam</code> = TEXT <code>odkaz</code> = REFERENCE <code>referencetext</code> = TEXT
<code>\startpublicationnote</code> <code>[...,*...]</code> ... <code>\stoppublicationnote</code> * <code>titul</code> = TEXT OPT <code>zalozka</code> = TEXT <code>seznam</code> = TEXT <code>odkaz</code> = REFERENCE <code>referencetext</code> = TEXT
<code>\startendnote</code> <code>[...,*...]</code> ... <code>\stopendnote</code> * REFERENCE OPT
<code>\startfootnote</code> <code>[...,*...]</code> ... <code>\stopfootnote</code> * REFERENCE OPT
<code>\startmathnote</code> <code>[...,*...]</code> ... <code>\stopmathnote</code> * REFERENCE OPT
<code>\startpublicationnote</code> <code>[...,*...]</code> ... <code>\stoppublicationnote</code> * REFERENCE OPT
<code>\startprekryv</code> ... <code>\stopprekryv</code>
<code>\startprerollpageblock</code> <code>[...]</code> ... <code>\stopprerollpageblock</code> * NAME
<code>\startprocessassignmentcommand</code> <code>[...,*...]</code> ... <code>\stopprocessassignmentcommand</code> * KEY = VALUE
<code>\startprocessassignmentlist</code> <code>[...,*...]</code> ... <code>\stopprocessassignmentlist</code> * KEY = VALUE
<code>\startprocesscommacommand</code> <code>[...,*...]</code> ... <code>\stopprocesscommacommand</code> * BEFEHL
<code>\startprocesscommalist</code> <code>[...,*...]</code> ... <code>\stopprocesscommalist</code> * BEFEHL
<code>\startprodukt</code> <code>[...]</code> ... <code>\stopprodukt</code> * FILE *
<code>\startprodukt</code> <code>... ..</code> ... <code>\stopprodukt</code> * FILE *
<code>\startprofile</code> <code>[...]</code> ... <code>\stopprofile</code> * NAME OPT

<pre> \startprofile [...,..¹...,...] ... \stopprofile * inherits: \setupprofile ^{OPT} </pre>
<pre> \startPROFILE [...] ... \stopPROFILE * NAME ^{OPT} </pre>
<pre> \startPROFILE [...,..¹...,...] ... \stopPROFILE * inherits: \setupprofile ^{OPT} </pre>
<pre> \startprojekt [...] ... \stopprojekt * FILE * </pre>
<pre> \startprojekt \stopprojekt * FILE * </pre>
<pre> \startprostredi [...] ... \stopprostredi * FILE * </pre>
<pre> \startprostredi \stopprostredi * FILE * </pre>
<pre> \startprotectedcolors ... \stopprotectedcolors </pre>
<pre> \startpublikace [...¹] [...,..²...,...] ... \stoppublikace 1 NAME ^{OPT} ^{OPT} 2 tag = REFERENCE category = TEXT k = REFERENCE t = TEXT </pre>
<pre> \startradek [...] * REFERENCE </pre>
<pre> \startLINES [...,..¹...,...] ... \stopLINES * inherits: \nastavradky^{OPT} instances: lines </pre>
<pre> \startlines [...,..¹...,...] ... \stoplines * inherits: \nastavradky^{OPT} </pre>
<pre> \startrandomized ... \stoprandomized </pre>
<pre> \startrawsetups [...] ... \stoprawsetups * NAME </pre>
<pre> \startrawsetups \stoprawsetups * NAME </pre>
<pre> \startreadingfile ... \stopreadingfile </pre>
<pre> \startregime [...] ... \stopregime * inherits: \enableregime </pre>

\startregister [¹...] [²...] [³...] [⁴...] {..⁵..⁶} \stopregister [⁷...] [⁸...] 1 NAME 2 NAME 3 TEXT 4 TEXT PROCESSOR->TEXT 5 INDEX 6 CONTENT 7 NAME 8 NAME
\startreusableMPgraphic {..¹} {..²,...} ... \stopreusableMPgraphic 1 NAME 2 KEY
\starttrovnice [...,*...] ... \stoprovnice * zhustene tight nastred^{OPT} podlehloubky radek pulradku -radek -pulradku ramecek male DIMENSION
\starttrovnice [...,*=...,...] ... \stoprovnice * inherits: \nastavrovnice^{OPT}
\startFORMULAformula [...,*...] ... \stopFORMULAformula * zhustene tight nastred podlehloubky^{OPT} radek pulradku -radek -pulradku ramecek male DIMENSION instances: sp sd mp md
\startFORMULAformula [...,*=...,...] ... \stopFORMULAformula * inherits: \nastavrovnice^{OPT} instances: sp sd mp md
\startmdformula [...,*=...,...] ... \stopmdformula * inherits: \nastavrovnice^{OPT}
\startmpformula [...,*=...,...] ... \stopmpformula * inherits: \nastavrovnice^{OPT}
\startsdformula [...,*=...,...] ... \stopsdformula * inherits: \nastavrovnice^{OPT}
\startspformula [...,*=...,...] ... \stopspformula * inherits: \nastavrovnice^{OPT}
\startmdformula [...,*...] ... \stopmdformula * zhustene tight nastred^{OPT} podlehloubky radek pulradku -radek -pulradku ramecek male DIMENSION
\startmpformula [...,*...] ... \stopmpformula * zhustene tight nastred^{OPT} podlehloubky radek pulradku -radek -pulradku ramecek male DIMENSION
\startsdformula [...,*...] ... \stopsdformula * zhustene tight nastred^{OPT} podlehloubky radek pulradku -radek -pulradku ramecek male DIMENSION
\startspformula [...,*...] ... \stopspformula * zhustene tight nastred^{OPT} podlehloubky radek pulradku -radek -pulradku ramecek male DIMENSION
\startrows [¹] [...,²...,...] ... \stoprows 1 NAME 2 inherits: \setuprows
\startROWS [...,*=...,...] ... \stopROWS * inherits: \setuprows^{OPT}

\startrozbalene ... \stoprozbalene	
\startruby [...] ... \stopruby * NAME	
\startscript [...] ... \stopscrip * hangul hanzi nihongo ethiopic thai tibetan test NAME	
\startsectionblock [¹ ...] [..., ² ...,...] ... \stopsectionblock 1 NAME OPT 2 zalozka = TEXT inherits: \nastavbloksekce	
\startsectionblockenvironment [...] ... \stopsectionblockenvironment * NAME	
\startSECTIONBLOCK [..., [*] ...,...] ... \stopSECTIONBLOCK * zalozka = TEXT OPT inherits: \nastavbloksekce instances: frontmatter bodymatter appendices backmatter	
\startappendices [..., [*] ...,...] ... \stopappendices * zalozka = TEXT OPT inherits: \nastavbloksekce	
\startbackmatter [..., [*] ...,...] ... \stopbackmatter * zalozka = TEXT OPT inherits: \nastavbloksekce	
\startbodymatter [..., [*] ...,...] ... \stopbodymatter * zalozka = TEXT OPT inherits: \nastavbloksekce	
\startfrontmatter [..., [*] ...,...] ... \stopfrontmatter * zalozka = TEXT OPT inherits: \nastavbloksekce	
\startsectionlevel [¹ ...] [..., ² ...,...] [..., ³ ...,...] ... \stopsectionlevel 1 NAME OPT OPT OPT 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT vlastnicislo = TEXT placeholder = TEXT 3 KEY = VALUE	
\startSECTION [..., ¹ ...,...] [..., ² ...,...] ... \stopSECTION 1 titul = TEXT OPT OPT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT vlastnicislo = TEXT placeholder = TEXT 2 KEY = VALUE instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject	

```

\startchapter    [...,\sfrac{1}{2}...,...]    [...,\sfrac{2}{2}...,...] ... \stopchapter
1  titul         = TEXT      OPT
   zalozka       = TEXT
   znaceni       = TEXT
   seznam        = TEXT
   odkaz         = REFERENCE
   referencetext = TEXT
   vlastnicislo  = TEXT
   placeholder   = TEXT
2  KEY = VALUE

```

```

\startpart    [...,\sfrac{1}{2}...,...]    [...,\sfrac{2}{2}...,...] ... \stoppart
1  titul      = TEXT      OPT
   zalozka    = TEXT
   znaceni    = TEXT
   seznam     = TEXT
   odkaz      = REFERENCE
   referencetext = TEXT
   vlastnicislo = TEXT
   placeholder = TEXT
2  KEY = VALUE

```

```

\startsection  [...,\sfrac{1}{2}...,...]    [...,\sfrac{2}{2}...,...] ... \stopsection
1  titul       = TEXT      OPT
   zalozka     = TEXT
   znaceni     = TEXT
   seznam      = TEXT
   odkaz       = REFERENCE
   referencetext = TEXT
   vlastnicislo = TEXT
   placeholder  = TEXT
2  KEY = VALUE

```

```

\startsubject  [...,\sfrac{1}{2}...,...]    [...,\sfrac{2}{2}...,...] ... \stopsubject
1  titul       = TEXT      OPT
   zalozka     = TEXT
   znaceni     = TEXT
   seznam      = TEXT
   odkaz       = REFERENCE
   referencetext = TEXT
   vlastnicislo = TEXT
   placeholder  = TEXT
2  KEY = VALUE

```

```

\startsubsection [...,\sfrac{1}{2}...,...]    [...,\sfrac{2}{2}...,...] ... \stopsubsection
1  titul       = TEXT      OPT
   zalozka     = TEXT
   znaceni     = TEXT
   seznam      = TEXT
   odkaz       = REFERENCE
   referencetext = TEXT
   vlastnicislo = TEXT
   placeholder  = TEXT
2  KEY = VALUE

```

```

\startsubsubject [...,\sfrac{1}{2}...,...]    [...,\sfrac{2}{2}...,...] ... \stopsubsubject
1  titul       = TEXT      OPT
   zalozka     = TEXT
   znaceni     = TEXT
   seznam      = TEXT
   odkaz       = REFERENCE
   referencetext = TEXT
   vlastnicislo = TEXT
   placeholder  = TEXT
2  KEY = VALUE

```

```

\startsubsubsection [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsection
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    odkaz             = REFERENCE
    referencetext     = TEXT
    vlastnicislo      = TEXT
    placeholder       = TEXT
2  KEY = VALUE

```

```

\startsubsubsubject [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubject
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    odkaz             = REFERENCE
    referencetext     = TEXT
    vlastnicislo      = TEXT
    placeholder       = TEXT
2  KEY = VALUE

```

```

\startsubsubsubsection [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubsection
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    odkaz             = REFERENCE
    referencetext     = TEXT
    vlastnicislo      = TEXT
    placeholder       = TEXT
2  KEY = VALUE

```

```

\startsubsubsubsubject [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubsubject
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    odkaz             = REFERENCE
    referencetext     = TEXT
    vlastnicislo      = TEXT
    placeholder       = TEXT
2  KEY = VALUE

```

```

\startsubsubsubsubsection [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubsubsection
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    odkaz             = REFERENCE
    referencetext     = TEXT
    vlastnicislo      = TEXT
    placeholder       = TEXT
2  KEY = VALUE

```

```

\startsubsubsubsubsubject [...,\subscript{1}...,...] [...,\subscript{2}...,...] ... \stopsubsubsubsubsubject
1  titul             = TEXT
    zalozka          = TEXT
    znaceni           = TEXT
    seznam            = TEXT
    odkaz             = REFERENCE
    referencetext     = TEXT
    vlastnicislo      = TEXT
    placeholder       = TEXT
2  KEY = VALUE

```

```

\starttitle    [...,\stackrel{1}{=},...]    [...,\stackrel{2}{=},...] ... \stoptitle
1  titul       = TEXTOPT
    zalozka    = TEXT
    znaceni    = TEXT
    seznam     = TEXT
    odkaz      = REFERENCE
    referencetext = TEXT
    vlastnicislo = TEXT
    placeholder = TEXT
2  KEY = VALUE

```

```

\startsetcolumnset    [...,\stackrel{*}{=},...] ... \stopsetcolumnset
*  c      = NUMBER
    r      = NUMBER
    nc     = NUMBER
    nr     = NUMBER
    metoda = zde fixne vrsek spodek tblr lrtb tbrl rltb btlr lrbt btrl rlbt fxtb fxbt
    volba  = stranka
    nvrsek = NUMBER
    nspodek = NUMBER

```

```

\startsetcolumnsetsheet    [...,\stackrel{*}{=},...] ... \stopsetcolumnsetsheet
*  NUMMER

```

```

\startsetcolumnsetsht    [...,\stackrel{*}{=},...] ... \stopsetcolumnsetsht
*  c      = NUMBER
    r      = NUMBER
    nc     = NUMBER
    nr     = NUMBER
    metoda = zde fixne vrsek spodek tblr lrtb tbrl rltb btlr lrbt btrl rlbt fxtb fxbt
    volba  = stranka
    nvrsek = NUMBER
    nspodek = NUMBER

```

```

\startsetups    [...,\stackrel{*}{=},...] ... \stopsetups
*  NAME

```

```

\startsetups    ... ... \stopsetups
*  NAME

```

```

\startshadow    [...,\stackrel{*}{=},...] ... \stopshadow
*  NAME

```

```

\startshadow    [...,\stackrel{*}{=},...] ... \stopshadow
*  inherits: \setupshadow

```

```

\startshapedparagraph    [...,\stackrel{*}{=},...] ... \stopshapedparagraph
*  inherits: \setupshapedparagraphOPT

```

```

\startshapetext    [...,\stackrel{*}{=},...] ... \stopshapetext
*  NAME

```

```

\startshift    [...,\stackrel{*}{=},...] ... \stopshift
*  NAME

```

```

\startshift    [...,\stackrel{*}{=},...] ... \stopshift
*  inherits: \setupshift

```

```

\startshowbalancepoints    [...,\stackrel{*}{=},...] ... \stopshowbalancepoints
*  volba  = marginalie simpleOPT
    uroven = NUMBER
    seznam = TEXT
    offset = DIMENSION

```



```

\startshowbreakpoints [...,*=...,...] ... \stopshowbreakpoints
* volba = marginalie simple OPT
  uroven = NUMMER
  seznam = TEXT
  offset = DIMENSION

```

```

\startshowrivers [...,*=...,...] ... \stopshowrivers
* marginalie = DIMENSION OPT
  krok = DIMENSION
  vyska = DIMENSION
  hloubka = DIMENSION
  spaceinbetween = DIMENSION
  kriterium = NUMMER
  volba = test

```

```

\startsidebar [1.] [...,*=2...,...] ... \stopsidebar
1 NAME OPT
2 inherits: \setupsidebar

```

```

\startsimplecolumns [...,*=...,...] ... \stopsimplecolumns
* n = NUMMER OPT
  sirka = DIMENSION
  vzdalenost = DIMENSION
  radky = NUMMER

```

```

\startspecialitem [1.] [...,2...,...] ... \stopspecialitem
1 polozka OPT
2 REFERENCE

```

```

\startspecialitem [...*] ... \stopspecialitem
* pod pol ne

```

```

\startspecialitem [1.] {...2.} ... \stopspecialitem
1 sym rozsah mar txt
2 TEXT

```

```

\startsplitttext ... \stopsplitttext

```

```

\startspread ... \stopspread

```

```

\startstacking [...*] ... \stopstacking
* NUMMER

```

```

\startstackingsteps [...*,...] ... \stopstackingsteps
* NUMMER

```

```

\startSTACKING [...*] ... \stopSTACKING
* NUMMER

```

```

\startSTARTSTOP ... \stopSTARTSTOP

```

```

\startSTARTSTOP [...,*=...,...] ... \stopSTARTSTOP
* inherits: \setupstartstop OPT

```

```

\startstaticMPfigure {...*} ... \stopstaticMPfigure
* NAME

```

```

\startstaticMPgraphic {...1.} {...,2...,...} ... \stopstaticMPgraphic
1 NAME OPT
2 KEY

```

\STARTSTOP { ¹ ...} * CONTENT
\STARTSTOP [..., ¹ ... ² ...] { ² ...} 1 inherits: \setupstartstop 2 CONTENT
\startstrictinspectnextcharacter ... \stopstrictinspectnextcharacter
\startstructurepageregister [¹ ...] [² ...] [..., ³ ... ⁴ ...] [..., ⁴ ... ⁵ ...] ... \stopstructurepageregister [...] ⁶ [⁷ ...] ^{OPT} 1 NAME 2 NAME 3 popisek = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT processors = PROCESSOR keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternativa = TEXT processors:1 = PROCESSOR processors:2 = PROCESSOR processors:3 = PROCESSOR 4 KEY = VALUE 5 CONTENT 6 NAME 7 NAME
\startstyle [..., [*] ... [*] ...] ... \stopstyle * inherits: \setupstyle
\startstyle [...] ... \stopstyle * NAME FONT
\startSTYLE ... \stopSTYLE
\startsubcolumnset [¹ ...] [..., ² ... ² ...] ... \stopsubcolumnset 1 NAME ^{OPT} ^{OPT} 2 inherits: \setupsubcolumnset
\startsubcolumnsetgroup [¹ ...] [..., ² ... ² ...] ... \stopsubcolumnsetgroup 1 NAME ^{OPT} ^{OPT} 2 inherits: \setupsubcolumnset
\startsubformulas [..., [*] ...] ... \stopsubformulas * + - REFERENCE ^{OPT}
\startsubjectlevel [¹ ...] [..., ² ... ² ...] [..., ³ ... ³ ...] ... \stopsubjectlevel 1 NAME ^{OPT} ^{OPT} ^{OPT} 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT vlastnicislo = TEXT placeholder = TEXT 3 KEY = VALUE
\startsubnumberinghere ... \stopsubnumberinghere
\startsubparagraph ... \stopsubparagraph

<code>\starttabulky [...] ... \stoptabulky</code> <code>* NAME</code>
<code>\starttexcode ... \stoptexcode</code>
<code>\starttexdefinition ¹... ²... ³... \stoptexdefinition</code> <code>1 spaces nospaces globalne ^{DEF}tölerantni frozen^{OPT}permanent instance mutable immutable chranene semiprotected unexpanded</code> <code>expanded singleempty doubleempty tripleempty quadrupleempty quintupleempty sextupleempty singleargument doubleargument</code> <code>tripleargument quadrupleargument quintupleargument sextupleargument</code> <code>2 NAME</code> <code>3 TEMPLATE</code>
<code>\starttext ... \stoptext</code>
<code>\starttextbackground [¹...] [...,²...,...] ... \stoptextbackground</code> <code>1 NAME</code> <code>2 inherits: \setuptextbackground ^{OPT}</code>
<code>\starttextbackgroundmanual ... \stoptextbackgroundmanual</code>
<code>\startTEXTBACKGROUND [...,[*]...,...] ... \stopTEXTBACKGROUND</code> <code>* inherits: \setuptextbackground ^{OPT}</code>
<code>\starttextcolor [...] ... \stoptextcolor</code> <code>* COLOR</code>
<code>\starttextcolorintent ... \stoptextcolorintent</code>
<code>\startTEXTDISPLAY [...,[*]...,...] ... \stopTEXTDISPLAY</code> <code>* inherits: \setuptextdisplay ^{OPT}</code> <code>instances: textdisplay</code>
<code>\starttextdisplay [...,[*]...,...] ... \stoptextdisplay</code> <code>* inherits: \setuptextdisplay ^{OPT}</code>
<code>\starttextflow [...] ... \stoptextflow</code> <code>* NAME</code>
<code>\starttextnapovedy [...] ... \stoptextnapovedy</code> <code>* REFERENCE ^{OPT}</code>
<code>\starttextovalinka {...} ... \stoptextovalinka</code> <code>* TEXT</code>
<code>\startLABELtext [¹...] [²...] ... \stopLABELtext</code> <code>1 SPRACHE ^{OPT}</code> <code>2 KEY</code> <code>instances: head label mathlabel taglabel unit operator prefix suffix btxlabel</code>
<code>\startbtxlabeltext [¹...] [²...] ... \stopbtxlabeltext</code> <code>1 SPRACHE ^{OPT}</code> <code>2 KEY</code>
<code>\startheadtext [¹...] [²...] ... \stopheadtext</code> <code>1 SPRACHE ^{OPT}</code> <code>2 KEY</code>

$\backslash\text{startMP}$ [...,*,...] ... $\backslash\text{stopMP}$ * pokračovat OPT
$\backslash\text{startPARSEDXML}$ [...,*,...] ... $\backslash\text{stopPARSEDXML}$ * pokračovat OPT
$\backslash\text{startTEX}$ [...,*,...] ... $\backslash\text{stopTEX}$ * pokračovat OPT
$\backslash\text{starttyping}$ [...,*,...] ... $\backslash\text{stoptyping}$ * pokračovat OPT
$\backslash\text{startXML}$ [...,*,...] ... $\backslash\text{stopXML}$ * pokračovat OPT
$\backslash\text{startLUA}$ [...,*=,...] ... $\backslash\text{stopLUA}$ * inherits: $\backslash\text{nastavopT}^{\text{PS}}$
$\backslash\text{startMP}$ [...,*=,...] ... $\backslash\text{stopMP}$ * inherits: $\backslash\text{nastavop}^{\text{PS}}$
$\backslash\text{startPARSEDXML}$ [...,*=,...] ... $\backslash\text{stopPARSEDXML}$ * inherits: $\backslash\text{nastavopis}$ OPT
$\backslash\text{startTEX}$ [...,*=,...] ... $\backslash\text{stopTEX}$ * inherits: $\backslash\text{nastavop}^{\text{PS}}$
$\backslash\text{starttyping}$ [...,*=,...] ... $\backslash\text{stoptyping}$ * inherits: $\backslash\text{nastavopis}$ OPT
$\backslash\text{startXML}$ [...,*=,...] ... $\backslash\text{stopXML}$ * inherits: $\backslash\text{nastavop}^{\text{PS}}$
$\backslash\text{startumistirovnici}$ [...,* ¹ =,...] {... ² } ... $\backslash\text{stopumistirovnici}$ 1 titul = TEXT OPT OPT odkaz = + - REFERENCE zalozka = TEXT seznam = TEXT suffix = TEXT 2 TEXT
$\backslash\text{startumistirovnici}$ [...,*,...] ... $\backslash\text{stopumistirovnici}$ * + - REFERENCE OPT
$\backslash\text{startuniqueMPgraphic}$ {... ¹ } {..., ² ,...} ... $\backslash\text{stopuniqueMPgraphic}$ 1 NAME OPT 2 KEY
$\backslash\text{startuniqueMPpagegraphic}$ {... ¹ } {..., ² ,...} ... $\backslash\text{stopuniqueMPpagegraphic}$ 1 NAME OPT 2 KEY
$\backslash\text{startusableMPgraphic}$ {... ¹ } {..., ² ,...} ... $\backslash\text{stopusableMPgraphic}$ 1 NAME OPT 2 KEY
$\backslash\text{startuseMPgraphic}$ {... ¹ } {..., ² ,...} ... $\backslash\text{stopuseMPgraphic}$ 1 NAME OPT 2 KEY

\startusemathstyleparameter	* CSNAME
\startuserdata	1 NAME 2 KEY = VALUE
\startUSERDATA	* KEY = VALUE
\startusingbtxs specification	* NAME
\startuzky	1 NAME 2 inherits: \nastavzuzeni
\startuzky	1 inherits: \nastavzuzeni 2 [-+]vlevo [-+]nastred [-+]vpravo NUMBER*vlevo NUMBER*nastred NUMBER*vpravo reset reverse
\startuzky	1 NAME 2 [-+]vlevo [-+]nastred [-+]vpravo NUMBER*vlevo NUMBER*nastred NUMBER*vpravo reset reverse
\startvboxregister	* CSNAME NUMMER
\startvboxtohbox ... \stopvboxtohbox	
\startvboxtohboxseparator ... \stopvboxtohboxseparator	
\startverticalbox	1 NAME 2 inherits: \setupverticalbox
\startviewerlayer	* NAME
\startVIEWERLAYER ... \stopVIEWERLAYER	
\startvisici	1 inherits: \setuphanging 2 CONTENT
\startvisici	1 vlevo vpravo 2 CONTENT
\startvtopregister	* CSNAME NUMMER
\startVYCET	* titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE referencetext = TEXT

$\backslash\text{startVYCET}$ $[\dots,\overset{1}{\dots}]$ $\{\overset{2}{\dots}\}$... $\backslash\text{stopVYCET}$ 1 REFERENCE OPT OPT 2 TEXT
$\backslash\text{startxcell}$ $[\overset{1}{\dots}]$ $[\dots,\dots,\overset{2}{\dots},\dots]$... $\backslash\text{stopxcell}$ 1 NAME OPT OPT 2 nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxcellgroup}$ $[\overset{1}{\dots}]$ $[\dots,\dots,\overset{2}{\dots},\dots]$... $\backslash\text{stopxcellgroup}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxcolumn}$ $[\dots,\dots,\overset{*}{\dots},\dots]$... $\backslash\text{stopxcolumn}$ * inherits: $\backslash\text{setupxtable}$ OPT
$\backslash\text{startxcolumn}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxcolumn}$ * NAME OPT
$\backslash\text{startxgroup}$ $[\overset{1}{\dots}]$ $[\dots,\dots,\overset{2}{\dots},\dots]$... $\backslash\text{stopxgroup}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxmldisplayverbatim}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxmldisplayverbatim}$ * NAME
$\backslash\text{startxmllineverbatim}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxmllineverbatim}$ * NAME
$\backslash\text{startxmlraw}$... $\backslash\text{stopxmlraw}$
$\backslash\text{startxmlsetups}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxmlsetups}$ * NAME
$\backslash\text{startxmlsetups}$ $\overset{*}{\dots}$... $\backslash\text{stopxmlsetups}$ * NAME
$\backslash\text{startxrow}$ $[\overset{1}{\dots}]$ $[\dots,\dots,\overset{2}{\dots},\dots]$... $\backslash\text{stopxrow}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxrowgroup}$ $[\overset{1}{\dots}]$ $[\dots,\dots,\overset{2}{\dots},\dots]$... $\backslash\text{stopxrowgroup}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtable}$ $[\dots,\dots,\overset{*}{\dots},\dots]$... $\backslash\text{stopxtable}$ * inherits: $\backslash\text{setupxtable}$ OPT
$\backslash\text{startxtablebody}$ $[\dots,\dots,\overset{*}{\dots},\dots]$... $\backslash\text{stopxtablebody}$ * inherits: $\backslash\text{setupxtable}$ OPT
$\backslash\text{startxtablebody}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxtablebody}$ * NAME OPT
$\backslash\text{startxtablefoot}$ $[\dots,\dots,\overset{*}{\dots},\dots]$... $\backslash\text{stopxtablefoot}$ * inherits: $\backslash\text{setupxtable}$ OPT

\stoplinenote [...] * REFERENCE
\stopradek [...] * REFERENCE
\strana [...*,...] * inherits: \page ^{OPT} break
\strictdoifelsenextoptional {...} {...} 1 TRUE 2 FALSE
\strictdoifnextoptionalelse {...} {...} 1 TRUE 2 FALSE
\stripcharacter . ¹ \from . ² \to \. ³ 1 CHARACTER 2 TEXT 3 CSNAME
\strippedcsname \.* * CSNAME
\strippedcsname .* * TEXT
\stripspaces \from . ¹ \to \. ² 1 TEXT 2 CSNAME
\structurelistnumber
\structurelistrawnnumber {...} * LISTE
\structurelistrawpagenumber {...} * LISTE
\structurelistrawrealpagenumber {...} * LISTE
\structurelistrealpagenumber
\structurelistuserpagenumber
\structurelistuservariable {...} * KEY
\structurenumber
\structuretitle
\structureuservariable {...} * KEY

<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutgap</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...¹...²]{...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [...¹]{...²}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {...}</code> * TEXT
<code>\subpagenumber</code>
<code>\subparagraph</code>
<code>\subprescr [...¹]{...²}</code> 1 DIMENSION OPT 2 TEXT
<code>\subscr [...¹]{...²}</code> 1 DIMENSION OPT 2 TEXT
<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...¹} {...²} \...³</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subsupprescr [...¹]{...²} {...³}</code> 1 DIMENSION OPT 2 TEXT 3 TEXT

$\backslash\text{subsupscr}$ $[...^1]$ $\{...\}^2$ $\{...\}^3$ 1 DIMENSION OPT 2 TEXT 3 TEXT
$\backslash\text{subtractfeature}$ $[...\]$ * NAME
$\backslash\text{subtractfeature}$ $\{...\}$ * NAME
$\backslash\text{supprescr}$ $[...^1]$ $\{...\}^2$ 1 DIMENSION OPT 2 TEXT
$\backslash\text{supscr}$ $[...^1]$ $\{...\}^2$ 1 DIMENSION OPT 2 TEXT
$\backslash\text{supsubprescr}$ $[...^1]$ $\{...\}^2$ $\{...\}^3$ 1 DIMENSION OPT 2 TEXT 3 TEXT
$\backslash\text{supsubscr}$ $[...^1]$ $\{...\}^2$ $\{...\}^3$ 1 DIMENSION OPT 2 TEXT 3 TEXT
$\backslash\text{swapcounts}$ $\backslash...^1$ $\backslash...^2$ 1 CSNAME 2 CSNAME
$\backslash\text{swapdimens}$ $\backslash...^1$ $\backslash...^2$ 1 CSNAME 2 CSNAME
$\backslash\text{swapface}$
$\backslash\text{swapmacros}$ $\backslash...^1$ $\backslash...^2$ 1 CSNAME 2 CSNAME
$\backslash\text{swaptypeface}$
$\backslash\text{switchstyleonly}$ $[...\]$ * rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke
$\backslash\text{switchstyleonly}$ $\backslash...$ * CSNAME
$\backslash\text{switchtocolour}$ $[...\]$ * COLOR
$\backslash\text{switchtointerlinespace}$ $[...^1,...]$ $[...^2,...]$ 1 NAME OPT 2 inherits: \nastavmeziradkovoumezeru
$\backslash\text{switchtointerlinespace}$ $[...^*,...]$ * zap vyp reset auto male stredni veľke OPT NUMMER DIMENSION

<code>\switchtointerlinespace</code> [...] * NAME
<code>\symbol</code> [¹ ...] [² ...] 1 NAME OPT 2 NAME
<code>\symbolreference</code> [...] * REFERENCE
<code>\symbol</code> {...} * NAME
<code>\sync</code> { ¹ ...} ² ... 1 NAME 2 NUMMER
<code>\syncanchor</code> { ¹ ...} { ² ...} { ³ ...} 1 NAME 2 NUMMER 3 NUMMER
<code>\synctexblockfilename</code> {...} * FILE
<code>\synctexresetfilename</code>
<code>\synctexsetfilename</code> {...} * FILE
<code>\synchronizealignpass</code>
<code>\synchronizeblank</code>
<code>\synchronizeindenting</code>
<code>\synchronizelocalanchors</code> ... * CSNAME NUMMER
<code>\synchronizemarking</code> [¹ ...] [² ...] [³ ...] 1 BESCHRIFTUNG OPT 2 NUMMER 3 drzet
<code>\synchronizeoutputstreams</code> [...*,...] * NAME
<code>\synchronizestrut</code> {...} * ano ne auto kap prizpusobive radek implicitni CHARACTER
<code>\synchronizewhitespace</code>
<code>\SYNCHRONIZE</code> [..., ¹ ...,...] { ² ...} { ³ ...} 1 inherits: \setupsynchr ^{off} ize 2 CONTENT 3 CONTENT instances: paralleltext

<code>\paralleltext</code> [... ¹ ... ² ...] {...} {...} 1 inherits: \setupsynchroniz ^{92e} 2 CONTENT 3 CONTENT
<code>\synonymfirstuserpage</code> [... ¹] [... ²] 1 NAME 2 NAME
<code>\synonymmeaning</code> [... ¹] [... ²] 1 NAME 2 NAME
<code>\synonymname</code> [... ¹] [... ²] 1 NAME 2 NAME
<code>\synonympages</code> [... ¹] [... ²] 1 NAME 2 NAME
<code>\synonymuserpages</code> [... ¹] [... ²] 1 NAME 2 NAME
<code>\SYNONYM</code> [... ¹] [... ²] {... ³ } {... ⁴ } 1 NAME OPT OPT 2 TEXT 3 TEXT 4 CONTENT instances: abbreviation
<code>\abbreviation</code> [... ¹] [... ²] {... ³ } {... ⁴ } 1 NAME OPT OPT 2 TEXT 3 TEXT 4 CONTENT
<code>\systemlog</code> {... ¹ } {... ² } {... ³ } 1 FILE 2 TEXT 3 TEXT
<code>\systemlogfirst</code> {... ¹ } {... ² } {... ³ } 1 FILE 2 TEXT 3 TEXT
<code>\systemloglast</code> {... ¹ } {... ² } {... ³ } 1 FILE 2 TEXT 3 TEXT
<code>\systemsetups</code> {...} * NAME
<code>\TABLE</code>
<code>\TaBlE</code>
<code>\TEX</code>

<code>\TeX</code>
<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> <code>* BEFEHL</code>
<code>\taggedlabeltexts ¹... ²... ³...</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 CONTENT</code>
<code>\tamilnumerals {...}</code> <code>* NUMMER</code>
<code>\tbox {...}</code> <code>* CONTENT</code>
<code>\tcontainer ¹... ²...</code> <code>1 TEXT ^{OPT}</code> <code>2 CONTENT</code>
<code>\tecky [...]</code> <code>* NUMMER ^{OPT}</code>
<code>\tecky [,...[*]...,...]</code> <code>* inherits: \setup^{OPT}periods</code>
<code>\telugunumerals {...}</code> <code>* NUMMER</code>
<code>\tenkalinka</code>
<code>\tenkelinky [,...[*]...,...]</code> <code>* inherits: \nastavtenke^{OPT}linky</code>
<code>\testandsplitstring ¹... \at ²... \to \³... \and \⁴...</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 CSNAME</code> <code>4 CSNAME</code>
<code>\testcolumn [¹...] [²...]</code> <code>1 NUMMER ^{OPT}</code> <code>2 DIMENSION</code>

<code>\testfeature {...} {...}</code> 1 NUMBER 2 CONTENT
<code>\testfeatureonce {...} {...}</code> 1 NUMBER 2 CONTENT
<code>\testpage [...]¹ [...]²</code> 1 NUMBER 2 DIMENSION
<code>\testpageonly [...]¹ [...]²</code> 1 NUMBER 2 DIMENSION
<code>\testpagesync [...]¹ [...]²</code> 1 NUMBER 2 DIMENSION
<code>\testtokens [...]</code> * NAME
<code>\tex {...}</code> * CONTENT
<code>\texbuffer [...]</code> * BUFFER
<code>\texbuffer {...}</code> * BUFFER
<code>\texdefinition {...}</code> * NAME
<code>\texsetup {...}</code> * NAME
<code>\TEXTBACKGROUND {...}</code> * CONTENT
<code>\textcitation [...]¹ [...]²</code> 1 odkaz = REFERENCE ^{PT} alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE
<code>\textcitation [...]¹ [...]²</code> 1 implicitni category ^{OPT} entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE

<pre> \textcitation [...¹...²...] [...²...] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \textcite [...¹...²...] [...²] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>
<pre> \textcite [...¹] [...²] 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>
<pre> \textcite [...¹...²...] [...²...] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \textcontrolspace </pre>
<pre> \textflowcollector {.*} * NAME </pre>
<pre> \texthere [...¹] {...²} 1 vlevo vpravo před po mezi 2 CONTENT </pre>
<pre> \textmath {.*} * CONTENT </pre>
<pre> \textminus </pre>
<pre> \textnapovedy [...¹] {...²} {...³} 1 REFERENCE OPT 2 TEXT 3 TEXT </pre>
<pre> \textnote [...¹...²...] {...²} 1 inherits: \setuptextnote 2 TEXT </pre>
<pre> \textormathchar {.*} * NUMMER </pre>
<pre> \textormathchars {.*} * CHARACTER </pre>

$\backslash\text{textovalinka}$ [¹ ...] { ² ...} 1 vrsek nastred spodek ^{OPT} 2 TEXT
$\backslash\text{textplus}$
$\backslash\text{LABELtext}$ {...} * KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash\text{btxlabeltext}$ {...} * KEY
$\backslash\text{headtext}$ {...} * KEY
$\backslash\text{labeltext}$ {...} * KEY
$\backslash\text{mathlabeltext}$ {...} * KEY
$\backslash\text{operatorortext}$ {...} * KEY
$\backslash\text{prefixtext}$ {...} * KEY
$\backslash\text{suffixtext}$ {...} * KEY
$\backslash\text{taglabeltext}$ {...} * KEY
$\backslash\text{unittext}$ {...} * KEY
$\backslash\text{textstacker}$ [¹ ...] { ² ...} { ³ ...} { ⁴ ...} 1 reverse matematika ^{OPT} text chemistry 2 NUMBER 3 TEXT 4 TEXT
$\backslash\text{textvisiblespace}$
$\backslash\text{thainumerals}$ {...} * NUMMER
$\backslash\text{thedatavalue}$ {...} * NAME
$\backslash\text{thefirstcharacter}$ {...} * TEXT
$\backslash\text{thenormalizedbodyfontsize}$ {...} * DIMENSION

<code>\theorientation {...}</code> * normalni up down vlevo vpravo vrsek spodek NAME
<code>\theremainingcharacters {...}</code> * TEXT
<code>\thickspace</code>
<code>\thinspace</code>
<code>\thirddoffivearguments {.^1.} {.^2.} {.^3.} {.^4.} {.^5.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\thirddofffourarguments {.^1.} {.^2.} {.^3.} {.^4.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\thirddofsixarguments {.^1.} {.^2.} {.^3.} {.^4.} {.^5.} {.^6.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\thirddofthreearguments {.^1.} {.^2.} {.^3.}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\thirddofthreeunexpanded {.^1.} {.^2.} {.^3.}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\threedigitrounding {...}</code> * NUMMER
<code>\tibetannumerals {...}</code> * NUMMER
<code>\tightfitboundary</code>
<code>\tightfitcompensation</code>
<code>\tightlayer [...]</code> * NAME
<code>\time [...,..^{FF}...,...]</code> * metoda = start ^{FF} zde aktualni h = NUMMER m = NUMMER s = NUMMER
<code>\tinyfont</code>

<code>\tinyinfofont</code>
<code>\tinyinfofontbold</code>
<code>\tlacitko</code> [...,.. ¹ ...,..] {...} [...] 1 inherits: \setupbutton ^{OPT} 2 TEXT 3 REFERENCE
<code>\tlacitkomenu</code> [...,.. ¹ ...,..] {...} {...} 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\tlacitkomenu</code> [...] [...,.. ² ...,..] {...} {...} 1 NAME 2 inherits: \nastavinterakcnimenu 3 TEXT 4 REFERENCE
<code>\BUTTON</code> [...,.. ¹ ...,..] {...} [...] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE instances: button
<code>\tlap</code> {...} * CONTENT
<code>\tloustkacary</code>
<code>\tochar</code> {...} * e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
<code>\tolinenote</code> [...] * REFERENCE
<code>\topbox</code> {...} * CONTENT
<code>\topleftbox</code> {...} * CONTENT
<code>\toplinebox</code> {...} * CONTENT
<code>\toprightbox</code> {...} * CONTENT
<code>\topskippedbox</code> {...} * CONTENT
<code>\tracecatcodetables</code>
<code>\tracedfontname</code> {...} * FONT
<code>\tracedpagestate</code>

\traceoutputroutines
\tracepositions
\tracingall
\tracingnone
\tracingprocess
\tracingtypesetting
\transliterate [. ¹ .] {. ² .} 1 NAME 2 TEXT
\transliteratebuffer [. ¹ .] {. ² .} 1 NAME 2 BUFFER
\transliterated [. ¹ .] {. ² .} 1 NAME 2 TEXT
\transliteratedbuffer [. ¹ .] {. ² .} 1 NAME 2 BUFFER
\transliteration [. ¹ .] {. ² .} 1 NAME 2 TEXT
\transliterationexception [. ¹ .] {. ² .} {. ³ .} 1 NAME 2 TEXT 3 TEXT
\transliteration {. ¹ .} {. ² .} 1 NAME 2 TEXT
\transparencycomponents {.*.} * COLOR
\transparent [. ¹ .] {. ² .} 1 COLOR 2 CONTENT

$\backslash$ traverseblock $\{.^1.\}$ $\{.^2.\}$ 1 digitsarabicindic digitsbold digitsdoublestruck digitsextendedarabicindic digitslatin digitsmonospace digitsnormal digitssansserifbold digitssansserifnormal geometricshapes letterlikesymbols lowercasebold lowercaseboldfraktur lowercasebolditalic lowercaseboldscript lowercasedoublestruck lowercasefraktur lowercasegreekbold lowercasegreekbolditalic lowercasegreekitalic lowercasegreeknormal lowercasegreekssansserifbold lowercasegreekssansserifbolditalic lowercaseitalic lowercasemonospace lowercasenormal lowercasesansserifbold lowercasesansserifbolditalic lowercasesansserifitalic lowercasesansserifnormal lowercasescript mathematicalalphanumericsymbols mathematicaloperators miscellaneousmathematicalsymbolsa miscellaneousmathematicalsymbolsb miscellaneoussymbols miscellaneoussymbolsandarrows miscellaneoustechnical supplementalarrowsa supplementalarrowsb supplementalarrowsc supplementalmathematicaloperators uppercasebold uppercaseboldfraktur uppercasebolditalic uppercaseboldscript uppercasedoublestruck uppercasefraktur uppercasegreekbold uppercasegreekbolditalic uppercasegreekitalic uppercasegreeknormal uppercasegreekssansserifbold uppercasegreekssansserifbolditalic uppercaseitalic uppercasemonospace uppercasenormal uppercasesansserifbold uppercasesansserifbolditalic uppercasesansserifitalic uppercasesansserifnormal uppercasescript lowersecalligraphic uppersecalligraphic lowersecalligraphic lowercaseboldcalligraphic lowercasesansgreek uppercasesansgreek lowercaseitalicsansgreek uppercaseitalicsansgreek lowercaseblackboarditalic uppercaseblackboarditalic 2 BEFEHL
$\backslash$ traversemath $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ 1 pravidelne bezserifu monospaced fraktur script kaligraficke blackboard 2 normalni tucne tucnekurzivni kurziva 3 ucletters lcletters digits ucgreek lcgreek symbols 4 BEFEHL
$\backslash$ tref $\{.^1.\}$ $\{.^2.\}$ $[.^3.]$ 1 TEXT OPT OPT 2 TEXT 3 REFERENCE
$\backslash$ triggergroupedcommand $\{.^*.\}$ * BEFEHL
$\backslash$ triggergroupedcommandcs $\backslash.^*.$ * CSNAME
$\backslash$ triplebond
$\backslash$ truefilename $\{.^*.\}$ * FILE
$\backslash$ truefontname $\{.^*.\}$ * FONT
$\backslash$ ttraggedright
$\backslash$ tucne
$\backslash$ tucnekurzivni
$\backslash$ tucnesklonene
$\backslash$ tvrdamezera
$\backslash$ tvrdemezery
$\backslash$ TWEAKEDFONT
$\backslash$ twodigitrounding $\{.^*.\}$ * NUMMER
$\backslash$ tx

\txx
\typebuffer [..., ¹ ...] [...,... ² ...,...] 1 BUFFER OPT OPT 2 inherits: \nastavopis
\opisBUFFER [...,... [*] ...,...] [*] inherits: \nastavopis OPT
\typedefinedbuffer [... ¹ .] [...,... ² ...,...] 1 BUFFER OPT 2 inherits: \nastavopis
\typeface
\typeinlinebuffer [..., ¹ ...] [...,... ² ...,...] 1 BUFFER OPT OPT 2 inherits: \nastavtype
\typescriptone
\typescriptprefix {...} [*] NAME
\typescriptthree
\typescripttwo
\typesetbuffer [... ¹ .] [...,... ² ...,...] 1 * BUFFER OPT OPT 2 inherits: \setupeexternalfigure
\typesetbufferonly [... [*] .] [*] * BUFFER OPT
\typesetfile [... ¹ .] [... ² .] [...,... ³ ...,...] 1 NAME FILE OPT OPT 2 FILE TEXT 3 inherits: \setupeexternalfigure
\opisTYPINGbuffer [..., ¹ ...] [...,... ² ...,...] 1 BUFFER OPT OPT 2 inherits: \nastavopis instances: typing LUA MP PARSEDXML TEX XML
\opisLUAbuffer [..., ¹ ...] [...,... ² ...,...] 1 BUFFER OPT OPT 2 inherits: \nastavopis
\opisMPbuffer [..., ¹ ...] [...,... ² ...,...] 1 BUFFER OPT OPT 2 inherits: \nastavopis
\opisPARSEDXMLbuffer [..., ¹ ...] [...,... ² ...,...] 1 BUFFER OPT OPT 2 inherits: \nastavopis

```
1  BUFFER
2  inherits: \nastavopis
```

```
1  BUFFER
2  inherits: \nastavopis
```

```
1  BUFFER
2  inherits: \nastavopis
```

```
instances: typing LUA MP PARSEDXML TEX XML
```

```
1 inherits: \nastavopis OPT
2 FILE
```

```
1 inherits: \nastavopisOPT
2 FILE
```

```
1 inherits: \nastavopis
2 FILE
```

```
1 inherits: \nastavopis OPT
2 FILE
```

```
1 inherits: \nastavopis
2 FILE
```

```
1 inherits: \nastavopis OPT
2 FILE
```

```
1 inherits: \konvertujcislo
2 NUMMER
```

```

1 CSNAME
2 CHARACTER NUMMER
3 BEFEHL

```

* NUMMER

* NUMMER

* COLOR

* reset spodek vrsek ^{OPT} Zadny vse radky ramecek nonumber vpravo vlevo vnejsi uvnitr sloupce

<code>\ukaznastaveni</code> [...*...] * pt bp cm mm dd cc pc nd^{OPT}nc sp in
<code>\ukazpaletu</code> [...¹] [...²,...] 1 NAME OPT 2 horizontalne vertikálne cislo hodnota jmeno
<code>\ukazpodpery</code>
<code>\ukazpostredizakladnihofontu</code> [...*...] * inherits: \nastavzakladnifont
<code>\ukazramecek</code> [...¹,...] [...²,...] 1 vrsek zahlaví text up^{OPT}ati spodek OPT 2 levahrana levyokraj text pravyokraj pravahrana
<code>\ukazsadosymbolu</code> [...*...] * NAME
<code>\ukazskupinubarev</code> [...¹] [...²,...] 1 NAME OPT 2 horizontalne vertikálne cislo hodnota jmeno
<code>\ukazupravu</code> [...*...] * reset boxes zlom^{OPT}se hbox vbox vtop kern glue penalty fontkern strut whatsit glyph simple simplehbox simplevbox simplevtop user math kurziva origin discretionary expansion radek mezera podlehloubky marginkern mathkern dir par mathglue mark insert boundary vkern hkern vglue hglue vpenalty hpenalty
<code>\ukazvytisk</code> [...¹,...] [...²,...] [...³,...] 1 inherits: \nastavve^{OPT}tkostpapiru OPT OPT 2 inherits: \nastavvelikostpapiru 3 inherits: \nastavvzhled
<code>\ukazvzhled</code> [...*...] * pt bp cm mm dd cc p^{OPT}nd nc sp in NUMMER
<code>\ukazzakladnifont</code> [...*...] * inherits: \nastavzakladnifont
<code>\umistikombinovanyseznam</code> [...¹] [...²,...] 1 LISTE OPT 2 inherits: \nastavkombinovanyseznam
<code>\umistiCOMBINEDLIST</code> [...[*],...] * inherits: \nastavkombinovanyseznam^{OPT} instances: content
<code>\umisticontent</code> [...[*],...] * inherits: \nastavkombinovanyseznam^{OPT}
<code>\umistilokalnipoznamkypodcarou</code> [...[*],...] * inherits: \setupnote OPT
<code>\umistinadsebe</code> {...¹} {...²} 1 CONTENT 2 CONTENT

1 normalni standardni ^{opt} striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko
zadny radek strut box min max nastred math math:radek math:pulradku math:-line math:-halfline NAME
2 CONTENT

```
1 inherits: \definegridsnappingOPT
2 CONTENT
```

1	+ - REFERENCE	OPT	OPT
2	TEXT		

```
* inherits: \setupnote OPT
```

```
1  NAME OPT
2  inherits: \nastavrejstrik
```

```
* inherits: \nastavrejstrik OPT
instances: index
```

```
* inherits: \nastavrejstrikDPT
```

```

1  + - REFERENCE      OPT      OPT
2  TEXT

```

```
1  LISTE OPT
2  inherits: \nastavseznam
```

1 CONTENT

2 CONTENT

```

1  ABSCHNITT LISTE                                OPT                                OPT                                OPT
2  ABSCHNITT LISTE
3  inherits: \setupbookmark

```

* NAME

* CONTENT

1 TEXT
2 TEXT

```

1  TEXT
2  KEY  =  VALUE

```

* KEY

<code>\unhhbox ¹... \with ²{...}</code> 1 CSNAME NUMBER 2 BEFEHL
<code>\unicodehexnumber {...}</code> * NUMBER
<code>\unicodechar {...}</code> * TEXT
<code>\unicodenummer {...}</code> * NUMBER
<code>\unihex {...}</code> * NUMBER
<code>\uniqueMPgraphic ¹{...} ²{...,..._{OPT}...,...}</code> 1 NAME 2 KEY = VALUE
<code>\uniqueMPgraphic [..._{OPT}...,...] ²{...}</code> 1 instance = metafun minifun _{OPT} extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun metapost nofun scaledpost doublepost binarypost decimalpost simplefun descriptiontext = TEXT alternativetext = TEXT KEY = VALUE 2 NAME
<code>\uniqueMPpagegraphic ¹{...} ²{...,..._{OPT}...,...}</code> 1 NAME 2 KEY = VALUE
<code>\unknownchar</code>
<code>\unprotect ... \protect</code>
<code>\unprotected .* \par</code> * CONTENT
<code>\unregisterhyphenationpattern ¹[...] ²[...]</code> 1 SPRACHE 2 TEXT
<code>\unregisterparwrapper {...}</code> * NAME
<code>\unspaceafter \¹... ²{...}</code> 1 CSNAME 2 TEXT
<code>\unspaceargument ¹... \to ²...</code> 1 TEXT 2 CSNAME
<code>\unspaced {...}</code> * TEXT
<code>\unspacestring ¹... \to ²...</code> 1 TEXT 2 CSNAME

<code>\unstacking [...]</code> <code>* NUMBER</code>
<code>\unstackscripts</code>
<code>\untexargument {...} \to \^...</code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\untexcommand {...} \to \^...</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\upcomingnofitems {...}></code> <code>* NAME</code> <code>></code>
<code>\updateparagraphdemerits</code>
<code>\updateparagraphpenalties</code>
<code>\updateparagraphproperties</code>
<code>\updateparagraphshapes</code>
<code>\uppercased {...}</code> <code>* TEXT</code>
<code>\uppercasestring .^... \to \^...</code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\uppercasing</code>
<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\urcicharakteristikurejstriku [...]</code> <code>[...²...]</code> <code>1 NAME</code> <code>OPT</code> <code>2 language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-sc9 SPRACHE</code> <code> metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc</code> <code> numberorder = ciska</code> <code> compress = ano ne vse</code> <code> kriterium = lokalne text aktualni predchozi vse ABSCHNITT</code>

<code>\usedadaptiveline</code>
<code>\usedadaptivetotal</code>
<code>\usedadaptivewidth</code>
<code>\usedummycolorparameter {...}</code> <code>* KEY</code>
<code>\usedummystyleandcolor {...} {...}</code> <code>1 KEY</code> <code>2 KEY</code>
<code>\usedummystyleparameter {...}</code> <code>* KEY</code>
<code>\useenvironment [...]</code> <code>* FILE</code>
<code>\useexternalrendering [...] [...] [...] [...]</code> <code>1 NAME</code> <code>2 NAME</code> <code>3 FILE</code> <code>4 auto embed</code>
<code>\usefigurebase [...]</code> <code>* reset FILE</code>
<code>\usefile [...] [...] [...]</code> <code>1 NAME</code> <code>2 FILE</code> <code>3 TEXT</code>
<code>\usefontpath [...*,...]</code> <code>* PATH</code>
<code>\usegridparameter \...</code> <code>* CSNAME</code>
<code>\usehyphensparameter \...</code> <code>* CSNAME</code>
<code>\useindentingparameter \...</code> <code>* CSNAME</code>
<code>\useindentnextparameter \...</code> <code>* CSNAME</code>
<code>\useinterlinespaceparameter \...</code> <code>* CSNAME</code>
<code>\uselanguageparameter \...</code> <code>* CSNAME</code>
<code>\uselist [...] [...] [...]</code> <code>1 NAME</code> <code>2 FILE</code> <code>3 TEXT</code>

```
\uselua module    [...]
* FILE
```

```
\useluatable \.*
* CSNAME
```

```
\useMPenvironmentbuffer    [...]  
*    NAME
```

```

\useMPgraphic    {1...}    {2...,..=...,...}
1  NAME
2  KEY = VALUE

```

```
\useMPgraphic    [...1...,...]    {...2.}

1  instance      = metafunBPT minifun extrafun lessfun scaledfun doublefun binaryfun decimalfun positfun mprun
                  meta2post nofun scaledpost doublepost binarypost decimalpost simplefun
  descriptiontext = TEXT
  alternativetext  = TEXT
2  NAME
```

```
\useMPLibrary    [...]
* FILE
```

```
\useMPPrun      {1...}      {2...}
1  NAME
2  NUMMER
```

```
\useMPvariables    [...]1    [...]2, [...]
```

```
1  NAME
```

```
2  KEY
```

```
\usemathstyleparameter \dots
* CSNAME
```

```
\useproduct    [...]
*    FILE
```

```
\useprofileparameter \*...
* CSNAME
```

```
\useproject [...]
* FILE
```

```
\userreferenceparameter \dots
* CSNAME
```

```

\userregister    [.^.]    [.^.]    [.^.]    [.^.]
1  NAME
2  FILE
3  NAME
4  TEXT

```

\userpagenumber

```
\usesetupparameter \dots
* CSNAME
```

```
\usestaticMPfigure    [...,\u=...,...]    [...^2]
1 inherits: \setupscale      OPT
2 NAME
```

`\usesubpath` `[...,*,...]`

`\usetexmodule` [¹...] [...,²...] [...,³...,...]

`\usetransliteration` [...,*,...]

`\usetyescript` $[...]$ $[...]$ $[...]$

```
\usetypescriptfile [...]

```

`\usezipfile` [¹...] [²...]

\utfchar {...}

$$\backslash \text{utflower} \quad \{.\text{.*.}\}$$

\utfupper {.*.}

\utilityregisterlength

```
\uzijadresar    [...,*,...]
```

```
\uzijbloky    [...,1...]    [...,2...]    [...,3=.,...]

```

\uzijexternidokument [...] [...] [...]

```
\uzijexterniobraz    [...]1    [...]2    [...]3    [...]4=...,...]
```

```
\uzijJScripts    [...]1    [...,2...]
```

$$\backslash \text{uzijmodul} \quad [\dots] \quad [\dots, \dots] \quad [\dots, \dots, \dots]$$

\uzijsymbol [...] * FILE
\uzijURL [... ¹] [... ²] [... ³] [... ⁴] 1 NAME 2 URL 3 FILE 4 TEXT
\uzijurl [... ¹] [... ²] [... ³] [... ⁴] 1 NAME 2 URL 3 FILE 4 TEXT
\VerboseNumber {...} * NUMMER
\VSEDNIDEN {...} * NUMMER
\validassignment {...} * TEXT
\ vboxreference [... ¹ ,...] {... ² } 1 REFERENCE 2 CONTENT
\vbbreak
\vcontainer ... ¹ {... ² } 1 TEXT 2 CONTENT
\velke ... * CHARACTER
\verbatim {...} * CONTENT
\verbatimstring {...} * CONTENT
\verbosenummer {...} * NUMMER
\verticalbox [... ¹] [..., ² ...,...] {... ³ } 1 NAME 2 inherits: \setupverticalbox 3 CONTENT
\verticalgrowingbar [..., [*] ...,...] * inherits: \setuppositionbar
\verticalpositionbar [..., [*] ...,...] * inherits: \setuppositionbar
\veryraggedcenter

<code>\vsmashed {...}</code> <code>* CONTENT</code>
<code>\vspace [...]¹ [...]²</code> <code>1 NAME OPT OPT</code> <code>2 NAME</code>
<code>\vspacing [...]*...]</code> <code>* nastaveni stejnas¹franka max sila enable zablockovat zadnabila zhustene zpet prekryv vzdy drzet weak strong implicitni</code> <code>pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku halflinebefore halflineafter quarterline</code> <code>rovnice bily vyska podlehloubky standardni NUMMER*male NUMMER*stredni NUMMER*velke NUMMER*radek NUMMER*pulradku</code> <code>NUMMER*quarterline NUMMER*rovnice NUMMER*bily NUMMER*vyska NUMMER*podlehloubky category:NUMMER order:NUMMER</code> <code>penalty:NUMMER DIMENSION NAME</code>
<code>\vyberbloky [...]¹,... [...]²,... [...]³,...]</code> <code>1 NAME OPT OPT</code> <code>2 NAME</code> <code>3 kriterium = text ABSCHNITT</code>
<code>\VYCET [...]¹,... {...}² ...³ \par</code> <code>1 REFERENCE OPT OPT</code> <code>2 TEXT</code> <code>3 CONTENT</code>
<code>\vyplnenytext [...]¹,... {...}² {...}³</code> <code>1 inherits: \nastavvyplnovetlinky OPT OPT OPT</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\vyplnovelinky [...]¹,... {...}² {...}³</code> <code>1 inherits: \nastavvyplnovetlinky OPT OPT OPT</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\vyplnovyradek [...]¹,... {...}</code> <code>* inherits: \nastavvyplnoveradky</code>
<code>\vysoky {...}</code> <code>* CONTENT</code>
<code>\HIGH {...}</code> <code>* CONTENT</code> <code>instances: unitshigh</code>
<code>\unitshigh {...}</code> <code>* CONTENT</code>
<code>\WidthSpanningText {...}¹ {...}² {...}³</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 FONT</code>
<code>\wdofstring {...}</code> <code>* TEXT</code>
<code>\widthofstring {...}</code> <code>* TEXT</code>
<code>\widthspanningtext {...}¹ {...}² {...}³</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 FONT</code>

<code>\wipedtokens {...} {...}</code> 1 TEXT 2 TEXT
<code>\wipetokens {...} {...}</code> 1 TEXT 2 TEXT
<code>\withoutpt {...}</code> * DIMENSION
<code>\words {...}</code> * TEXT
<code>\wordtonumber {...} {...}</code> 1 jedna dve tri ctyri pet 2 TEXT
<code>\wrapupparinsert</code>
<code>\writedatatolist [...]¹ [...,...²...,...]^{OPT} [...,...³...,...]</code> 1 LISTE 2 inherits: \nastavseznam 3 KEY = VALUE
<code>\writestatus {...} {...}</code> 1 TEXT 2 TEXT
<code>\XETEX</code>
<code>\XeTeX</code>
<code>\xdefconvertedargument \¹... {...}²</code> 1 CSNAME 2 TEXT
<code>\xmladdindex {...}</code> * NODE
<code>\xmlafterdocumentsetup {...}¹ {...}² {...}³</code> 1 NAME 2 SETUP 3 SETUP
<code>\xmlafterssetup {...}¹ {...}²</code> 1 SETUP 2 SETUP
<code>\xmlall {...}¹ {...}²</code> 1 NODE 2 LPATH
<code>\xmlappenddocumentsetup {...}¹ {...}²</code> 1 NAME 2 SETUP
<code>\xmlappendsetup {...}</code> * SETUP

\xmlapplyselectors {...} * NODE
\xmlatt {...} {...} 1 NODE 2 NAME
\xmlattdef {...} {...} {...} 1 NODE 2 NAME 3 TEXT
\xmlattribute {...} {...} {...} 1 NODE 2 LPATH 3 NAME
\xmlattributedef {...} {...} {...} {...} 1 NODE 2 LPATH 3 NAME 4 TEXT
\xmlbadinclusions {...} * NODE
\xmlbeforedocumentssetup {...} {...} {...} 1 NAME 2 SETUP 3 SETUP
\xmlbeforesetup {...} {...} 1 SETUP 2 SETUP
\xmlcommand {...} {...} {...} 1 NODE 2 LPATH 3 XMLSETUP
\xmlconcat {...} {...} {...} 1 NODE 2 LPATH 3 TEXT
\xmlconcatrange {...} {...} {...} {...} {...} 1 NODE 2 LPATH 3 TEXT 4 FIRST 5 LAST
\xmlcontext {...} {...} 1 NODE 2 LPATH
\xmlcount {...} {...} 1 NODE 2 LPATH
\xmldata {...} * TEXT

\xmldefaulttotext {...} * NODE
\xmldelete {...} {...} 1 NODE 2 LPATH
\xmldepth {...} * NODE
\xmldirect {...} * NODE
\xmldirectives {...} * NODE
\xmldirectivesafter {...} * NODE
\xmldirectivesbefore {...} * NODE
\xmldisplayverbatim {...} * NODE
\xmldocument
\xmldoif {...} {...} {...} 1 NODE 2 LPATH 3 TRUE
\xmldoifatt {...} {...} {...} {...} 1 NODE 2 TEXT 3 TEXT 4 TRUE
\xmldoifelse {...} {...} {...} {...} 1 NODE 2 LPATH 3 TRUE 4 FALSE
\xmldoifelseatt {...} {...} {...} {...} {...} 1 NODE 2 TEXT 3 TEXT 4 TRUE 5 FALSE
\xmldoifelseempty {...} {...} {...} {...} 1 NODE 2 LPATH 3 TRUE 4 FALSE
\xmldoifelseselfempty {...} {...} {...} 1 NODE 2 TRUE 3 FALSE

```
\xmldoifelse text    {..}    {..}    {..}    {..}
1  NODE
2  LPATH
3  TRUE
4  FALSE
```

```
\xmldoifelse value   {..}    {..}    {..}    {..}
1  CATEGORY
2  NAME
3  TRUE
4  FALSE
```

```
\xmldoifempty        {..}    {..}    {..}
1  NODE
2  LPATH
3  TRUE
```

```
\xmldoifemptyelse    {..}    {..}    {..}    {..}
1  NODE
2  LPATH
3  TRUE
4  FALSE
```

```
\xmldoifnot          {..}    {..}    {..}
1  NODE
2  LPATH
3  TRUE
```

```
\xmldoifnotatt       {..}    {..}    {..}    {..}
1  NODE
2  TEXT
3  TEXT
4  TRUE
```

```
\xmldoifnotempty     {..}    {..}    {..}
1  NODE
2  LPATH
3  TRUE
```

```
\xmldoifnotselfempty {..}    {..}
1  NODE
2  TRUE
```

```
\xmldoifnottext      {..}    {..}    {..}
1  NODE
2  LPATH
3  TRUE
```

```
\xmldoifselfempty    {..}    {..}
1  NODE
2  TRUE
```

```
\xmldoifselfemptyelse {..}    {..}    {..}
1  NODE
2  TRUE
3  FALSE
```

```
\xmldoiftext         {..}    {..}    {..}
1  NODE
2  LPATH
3  TRUE
```

\xmldoiftextelse {...} {...} {...} {...} 1 NODE 2 LPATH 3 TRUE 4 FALSE
\xmldoifvalueelse {...} {...} {...} {...} 1 CATEGORY 2 NAME 3 TRUE 4 FALSE
\xmlelement {...} {...} 1 NODE 2 NUMMER
\xmlfileline {...} * NODE
\xmlfilename {...} * NODE
\xmlfilter {...} {...} 1 NODE 2 LPATH
\xmlfirst {...} {...} 1 NODE 2 LPATH
\xmlflush {...} * NODE
\xmlflushcontext {...} * NODE
\xmlflushdocumentsetups {...} {...} 1 NAME 2 SETUP
\xmlflushlinewise {...} * NODE
\xmlflushpure {...} * NODE
\xmlflushsetups {...} * NAME
\xmlflushspacewise {...} * NODE
\xmlflushtext {...} * NODE
\xmlfunction {...} {...} 1 NODE 2 NAME

\xmlchainatt {...} {...} 1 NODE 2 NAME
\xmlchainattdef {...} {...} {...} 1 NODE 2 NAME 3 TEXT
\xmlchecknamespace {...} {...} {...} 1 NODE 2 NAME 3 NAME
\xmlinclude {...} {...} {...} 1 NODE 2 LPATH 3 NAME
\xmlincludeoptions {...} {...} {...} {..., 1 NODE 2 LPATH 3 NAME 4 recurse prepare rootpath resolve basename
\xmlinclusion {...} * NODE
\xmlinclusionbase {...} * NODE
\xmlinclusions {...} * NODE
\xmlindex {...} {...} {...} 1 NODE 2 LPATH 3 NUMMER
\xmlinfo {...} * NODE
\xmlinjector {...} * NAME
\xmlinlineprettyprint {...} {...} 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
\xmlinlineprettyprinttext {...} {...} 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
\xmlinlineverbatim {...} * NODE
\xmlinstalldirective {...} {...} 1 NAME 2 CSNAME

\xmllast { ¹ ..} { ² ..} 1 NODE 2 LPATH
\xmllastatt
\xmllastmatch
\xmllastpar
\xmlload { ¹ ..} { ² ..} 1 NAME 2 FILE
\xmlloadbuffer { ¹ ..} { ² ..} 1 BUFFER 2 NAME
\xmlloaddata { ¹ ..} { ² ..} 1 NAME 2 TEXT
\xmlloaddirectives { [*] ..} * FILE
\xmlloadfile { ¹ ..} { ² ..} 1 NAME 2 FILE
\xmlloadonly { ¹ ..} { ² ..} { ³ ..} 1 NAME 2 FILE 3 XMLSETUP
\xmlmain { [*] ..} * NODE
\xmlmapval { ¹ ..} { ² ..} { ³ ..} 1 CATEGORY 2 NAME 3 TEXT
\xmlmapvalue { ¹ ..} { ² ..} { ³ ..} 1 CATEGORY 2 NAME 3 TEXT
\xmlmatch { [*] ..} * NODE
\xmlname { [*] ..} * NODE
\xmlnamespace { [*] ..} * NODE
\xmlnonspace { ¹ ..} { ² ..} 1 NODE 2 LPATH

<code>\xmlpar {...} {...}</code> 1 NODE 2 NAME
<code>\xmlparam {...} {...} {...}</code> 1 NODE 2 LPATH 3 NAME
<code>\xmlpath {...}</code> * NODE
<code>\xmlpos {...}</code> * NODE
<code>\xmlposition {...} {...} {...}</code> 1 NODE 2 LPATH 3 NUMMER
<code>\xmlprependdocumentsetup {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlprependsetup {...}</code> * SETUP
<code>\xmlprettyprint {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
<code>\xmlprettyprinttext {...} {...}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
<code>\xmlprocess {...} {...} {...}</code> 1 NAME 2 FILE 3 XMLSETUP
<code>\xmlprocessbuffer {...} {...} {...}</code> 1 BUFFER 2 NAME 3 XMLSETUP
<code>\xmlprocessdata {...} {...} {...}</code> 1 NAME 2 TEXT 3 XMLSETUP
<code>\xmlprocessfile {...} {...} {...}</code> 1 NAME 2 FILE 3 XMLSETUP
<code>\xmlpure {...} {...}</code> 1 NODE 2 LPATH
<code>\xmlpushmatch ... \xmlpopmatch</code>

\xmlraw {...} * NODE
\xmlrefatt {...} {...} 1 NODE 2 NAME
\xmlregisterdocumentsetup {...} {...} 1 NAME 2 SETUP
\xmlregistereddokumentsetups {...} {...} 1 NAME 2 SETUP
\xmlregisteredsetups
\xmlregisterns {...} {...} 1 NAME 2 URL
\xmlregistersetup {...} * SETUP
\xmlremapname {...} {...} {...} {...} 1 NODE 2 LPATH 3 NAME 4 NAME
\xmlremapnamespace {...} {...} {...} 1 NODE 2 NAME 3 NAME
\xmlremoveddocumentsetup {...} {...} 1 NAME 2 SETUP
\xmlremovesetup {...} * SETUP
\xmlresetdocumentsetups {...} * NAME
\xmlresetinjectors
\xmlresetsetups
\xmls {...} {...} 1 NODE 2 SETUP
\xmlsave {...} {...} 1 NODE 2 FILE
\xmlsetatt {...} {...} {...} 1 NODE 2 NAME 3 TEXT

```
\xmlsetattribute  {...}  {...}  {...}  {...}
1  NODE
2  LPATH
3  NAME
4  TEXT
```

```
\xmlsetentity  {...}  {...}
1  NAME
2  TEXT
```

```
\xmlsetfunction  {...}  {...}  {...}
1  NODE
2  LPATH
3  LUAFUNCTION
```

```
\xmlsetinjectors  [...*...]
*  NAME
```

```
\xmlsetpar  {...}  {...}  {...}
1  NODE
2  NAME
3  TEXT
```

```
\xmlsetparam  {...}  {...}  {...}  {...}
1  NODE
2  LPATH
3  NAME
4  TEXT
```

```
\xmlsetsetup  {...}  {...}  {...}
1  NAME
2  LPATH
3  SETUP
```

```
\xmlsetup  {...}  {...}
1  NODE
2  SETUP
```

```
\xmlshow  {...}
*  NODE
```

```
\xmlsnippet  {...}  {...}
1  NODE
2  NUMMER
```

```
\xmlstartraw ... \xmlstopraw
```

```
\xmlstarttiming ... \xmlstoptiming
```

```
\xmlstrip  {...}  {...}
1  NODE
2  LPATH
```

```
\xmlstripanywhere  {...}  {...}
1  NODE
2  LPATH
```

```
\xmlstripeverything  {...}  {...}
1  NODE
2  LPATH
```

\xmlstripnolines {...} {...} 1 NODE 2 LPATH
\xmlstripped {...} {...} 1 NODE 2 LPATH
\xmlstrippednolines {...} {...} 1 NODE 2 LPATH
\xmltag {...} * NODE
\xmltexatt {...} {...} 1 NODE 2 NAME
\xmltexentity {...} {...} 1 NAME 2 TEXT
\xmltext {...} {...} 1 NODE 2 LPATH
\xmltobuffer {...} {...} {...} 1 NODE 2 LPATH 3 BUFFER
\xmltobuffertextonly {...} {...} {...} 1 NODE 2 LPATH 3 BUFFER
\xmltobufferverbose {...} {...} {...} 1 NODE 2 LPATH 3 BUFFER
\xmltofile {...} {...} {...} 1 NODE 2 LPATH 3 FILE
\xmltoparameters {...} * NODE
\xmlval {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlverbatim {...} * NODE

\xmlw {...} {...} 1 SETUP 2 NODE
\xsplitstring \... {...} 1 CSNAME 2 TEXT
\xypos {...} * NAME
\yddishnumerals {...} * NUMMER
\Znak {...} * NUMMER
\Znaky {...} * NUMMER
\zadnamezera
\zadnebilemisto
\zadnehorniadolniradky
\zadnezahlaviaupati
\zadnyrozmer {...} * CONTENT
\zachovejbloky [... ¹ ,...] [... ² ,...] 1 NAME 2 NAME
\zalozka [... ¹] {... ² } 1 ABSCHNITT LISTE 2 TEXT
\zapisdoseznamu [... ¹] [... ² ,... ² ,...] {... ³ } {... ⁴ } 1 LISTE 2 inherits: \nastavseznam 3 NUMMER 4 TEXT
\zapismeziseznam [... ¹] [... ² ,... ² ,...] {... ³ } 1 LISTE 2 inherits: \nastavseznam 3 BEFEHL
\zaramovani [... ¹ ,... ¹ ,...] {... ² } 1 inherits: \nastavoramovani 2 CONTENT
\zarovnanonastred {...} * CONTENT
\zarovnanovlevo {...} * CONTENT

$\frac{...}{...}$ <code>\frac</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\hookrightarrow$ <code>\hookrightarrowtext</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\hookleftarrow$ <code>\hookrightarrowtext</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\leftarrow$ <code>\Leftarrow</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\rightarrow$ <code>\rightarrowtext</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\searrow$ <code>\leftharpoonowdown</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\nearrow$ <code>\leftharpoonouptext</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\leftrightarrow$ <code>\leftrightharpoonowdown</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\leftrightharpoonowdown$ <code>\leftrightharpoonowdown</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\mapsto$ <code>\mapstotext</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\rightarrow$ <code>\rightarrowtext</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT
$\rightarrowleftarrow$ <code>\rightarrowleftarrowtext</code> $[...]{...}$ ${...}$ 1 inherits: <code>\setupmathfractions</code> 2 CONTENT 3 CONTENT

$\backslash\mathrm{relfraction}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{reltext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{rightarrowtext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{rightharpoondowntext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{rightharpoonuptext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{rightleftarrowtext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{rightleftharpoonostext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{rightoverleftarrowtext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{sfrac}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{splitdfraction}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{splitfrac}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{tbinom}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT
$\backslash\mathrm{tfrac}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\mathrm{setupmathfractions}^{\mathrm{OPT}}$ 2 CONTENT 3 CONTENT

$\backslash\text{triplereltext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\text{setupmathfractions}$ 2 CONTENT 3 CONTENT
$\backslash\text{twoheadleftarrowtext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\text{setupmathfractions}$ 2 CONTENT 3 CONTENT
$\backslash\text{twoheadrightarrowtext}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\text{setupmathfractions}$ 2 CONTENT 3 CONTENT
$\backslash\text{vfrac}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\text{setupmathfractions}$ 2 CONTENT 3 CONTENT
$\backslash\text{xfrac}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\text{setupmathfractions}$ 2 CONTENT 3 CONTENT
$\backslash\text{xxfrac}$ $[...,\overset{1}{=},...]$ $\{...\}^2$ $\{...\}^3$ 1 inherits: $\backslash\text{setupmathfractions}$ 2 CONTENT 3 CONTENT
$\backslash\text{znaceni}$ $(...,\overset{1}{},...)$ $(...,\overset{2}{},...)$ $[...,\overset{3}{}]$ 1 POSITION 2 POSITION 3 REFERENCE
$\backslash\text{znak}$ $\{...\}^*$ * NUMBER
$\backslash\text{znaky}$ $\{...\}^*$ * NUMBER
$\backslash\text{zpracujbloky}$ $[...,\overset{1}{},...]$ $[...,\overset{2}{},...]$ $[...,\overset{3}{=},...]$ 1 NAME 2 NAME 3 $\text{kriterium} = \text{text ABSCHNITT}$
$\backslash\text{zrcadlit}$ $\{...\}^*$ * CONTENT
$\backslash\text{zref}$ $[...]$ * REFERENCE
$\backslash\text{zvysit}$ $\backslash...$ * CSNAME
$\backslash\text{zvysit}$ $(...,\overset{*}{},...)$ * CSNAME NUMBER



www.pragma-ade.nl
wiki.contextgarden.net
www.tug.org