

Keyboard shortcuts

Shortcut	Action
Shift+Tab	Cycle permission mode (Manual, acceptEdits, Plan)
Ctrl+0	Toggle verbose transcript
Ctrl+C	Interrupt generation
Esc	Cancel current action
↑ / ↓	Message history
Tab	Path completion
Ctrl+X Ctrl+K	Stop background subagents
Ctrl+Enter / Ctrl+X Ctrl+S	Send queued messages now

Core slash commands

/help	Help and available commands
/clear	Clear context (reset)
/compact	Compress history
/model	Choose model; Enter saves, s applies once
/cost	View session costs
/status	Account and active settings
sources	
/context	Context usage breakdown

Permission modes

claude	Interactive mode (default)
claude --dangerously-skip-permissions	Bypass permission prompts; requires isolation
claude --allowedTools "Edit,Read,Bash"	Pre-approve tools; --tools restricts availability

Quick start

# Launch Claude Code	claude
# CLAUDE.md is loaded automatically at startup	
# To add a file during the session:	@src/auth.ts Look at this function
# Non-interactive mode (scripts)	claude -p "Analyze this file" < input.txt
# Continue last session	claude --continue

Session commands

/new	New session (alias for /clear)
/resume	Resume a session (opens the picker)
/branch	Fork the conversation here (v2.1.77)

Context navigation

Command	Effect
/compact	Summarize and free up space

Command	Effect
/clear	Full reset
@file	Reference a file in the prompt

Custom slash commands

# Invoke a custom command	/command-name [args]
# Defined in:	.claude/skills/command-name/SKILL.md

Essential tips

Verbosity control: use `--verbose` at launch, or `Ctrl+0` in session, to see the full turn-by-turn transcript.

Multiline: `Shift+Enter` in the terminal to add a new line without submitting.

Vim mode: `/config` → Editor mode, or `{"editorMode": "vim"}` in `~/.claude/settings.json`. The `/vim` command was removed in v2.1.92.