

Template LATEX Wiki von BAzubis für BAzubis

Projektarbeit 1 (T2_2000)

im Rahmen der Prüfung zum Bachelor of Science (B.Sc.)

des Studienganges Angewandte Informatik

an der Dualen Hochschule Baden-Württemberg Karlsruhe

von

Vorname Nachname

Januar 2018

-Sperrvermerk-

Abgabedatum: 01. Februar 2018

Bearbeitungszeitraum: 01.10.2017 - 31.01.2018

Matrikelnummer, Kurs: 0000000, TINF15B1

Ausbildungsfirma: SAP SE

Dietmar-Hopp-Allee 16

69190 Walldorf, Deutschland

Betreuer der Ausbildungsfirma: B-Vorname B-Nachname

Gutachter der Dualen Hochschule: DH-Vorname DH-Nachname

Eidesstattliche Erklärung

Ich versichere hiermit, dass ich meine Projektarbeit 1 (T2_2000) mit dem Thema:

Template LATEX Wiki von BAzubis für BAzubis

gemäß § 5 der "Studien- und Prüfungsordnung DHBW Technik" vom 29. September 2017 selbstständig verfasst und keine anderen als die angegebenen Quellen und Hilfsmittel benutzt habe. Die Arbeit wurde bisher keiner anderen Prüfungsbehörde vorgelegt und auch nicht veröffentlicht.

Ich versichere zudem, dass die eingereichte elektronische Fassung mit der gedruckten Fassung übereinstimmt.

Karlsruhe,	den	15.	Februar	2023
Nachname	. Vo	rnar	ne	

Sperrvermerk

Die nachfolgende Arbeit enthält vertrauliche Daten der:

SAP SE
Dietmar-Hopp-Allee 16
69190 Walldorf, Deutschland

Sie darf als Leistungsnachweis des Studienganges Angewandte Informatik 2015 an der DHBW Karlsruhe verwendet und nur zu Prüfungszwecken zugänglich gemacht werden. Über den Inhalt ist Stillschweigen zu bewahren. Veröffentlichungen oder Vervielfältigungen der Projektarbeit 1 ($T2_2000$) - auch auszugsweise - sind ohne ausdrückliche Genehmigung der SAP SE nicht gestattet.

SAP und die SAP Logos sind eingetragene Warenzeichen der SAP SE. Die Wiedergabe von Gebrauchsnamen, Handelsnamen, Warenbezeichnungen usw. in dieser Arbeit berechtigt auch ohne besondere Kennzeichnung nicht zu der Annahme, dass solche Namen im Sinne der Warenzeichen- und Markenschutz-Gesetzgebung als frei zu betrachten wären und daher von jedem benutzt werden dürfen.

Abstract

- English -

This is the starting point of the Abstract. For the final bachelor thesis, there must be an abstract included in your document. So, start now writing it in German and English. The abstract is a short summary with around 200 to 250 words.

Try to include in this abstract the main question of your work, the methods you used or the main results of your work.

Abstract

- Deutsch -

Dies ist der Beginn des Abstracts. Für die finale Bachelorarbeit musst du ein Abstract in deinem Dokument mit einbauen. So, schreibe es am besten jetzt in Deutsch und Englisch. Das Abstract ist eine kurze Zusammenfassung mit ca. 200 bis 250 Wörtern.

Versuche in das Abstract folgende Punkte aufzunehmen: Fragestellung der Arbeit, methodische Vorgehensweise oder die Hauptergebnisse deiner Arbeit.

Inhaltsverzeichnis

Ab	okürzungsverzeichnis	VI				
Αb	Abbildungsverzeichnis					
Ta	bellenverzeichnis	VIII				
soı	urce-codeverzeichnis	IX				
1.	Fundamentals1.1. Heat Equation					
Lit	teraturverzeichnis	X				
	Appendix A.1. Deriving matrices for FEM using piecewise linear functions					

List of abbreviations

DE Differential Equation

DFT Discrete Fourier Transform

FEM Finite Element Method

FT Fourier Transform

FFT Fast Fourier Transform

IDFT Inverse Discrete Fourier Transform

IFFT Inverse Fast Fourier Transform

LS Least Squares

ODE Ordinary Differential Equation

PDE Partial Differential Equation

Abbildungsverzeichnis

Tabellenverzeichnis

source-codeverzeichnis

1. Fundamentals

1.1. Heat Equation

The conduction of heat within a medium can be described using the following partial differential equation (PDE):

$$\frac{\partial u}{\partial t} = \alpha \nabla^2 u \tag{1.1}$$

With u being a function of space and time and α being a positive constant. For this paper u will be defined in terms of one spacial dimension:

$$u \coloneqq u(x,t) \tag{1.2}$$

$$\frac{\partial u}{\partial t} = \alpha \frac{\partial^2 u}{\partial x^2} \tag{1.3}$$

$$x \in \chi \subset \mathbb{R} \quad t \in \tau \subset \mathbb{R} \tag{1.4}$$

$$x_0 \le x \le x_n \quad t_0 \le t \le t_n \tag{1.5}$$

[1]

In order to not only model the conduction of heat within a medium but also a heating process, a new function $h: \chi \times \tau \to \mathbb{R}$ is introduced:

$$\frac{\partial u}{\partial t} = \alpha \frac{\partial^2 u}{\partial x^2} + h(x, t) \tag{1.6}$$

For this paper it is assumed that initial and boundary values are known:

$$a, b \in \mathbb{R} \tag{1.7}$$

$$f: \chi \to \mathbb{R} \tag{1.8}$$

$$u(x_0, t) = a \quad u(x_n, t) = b$$
 (1.9)

$$u(x,t_0) = f(x) \tag{1.10}$$

Applying the Fourier transform (FT) w.r.t x to 1.6 yields the inhomogeneous ordinary differential equation (ODE):

$$\hat{u} = \mathfrak{F}(u) \quad \hat{h} = \mathfrak{F}(h) \tag{1.11}$$

$$\frac{d}{dt}\hat{u} = -\alpha\omega^2\hat{u} + \hat{h} \tag{1.12}$$

A solution to 1.12 is given by:

$$\hat{u} = \hat{u}_0 + \hat{u}_n \tag{1.13}$$

Where \hat{u}_0 is the homogeneous solution and \hat{u}_p is the particular integral. In order to solve this ODE for the particular integral \hat{h} has to be known. [2] The choice of h is, except to some restrictions, arbitrary. Therefore an approximate solution to 1.12 \hat{u}_a is obtained by the forward euler scheme:

$$\frac{d}{dt}\hat{u} \approx \frac{\Delta \hat{u}}{\Delta t} \tag{1.14}$$

$$\hat{u}_{t+1} = \hat{u}_t + \Delta t (-\alpha \omega^2 \hat{u} + \hat{h}) \tag{1.15}$$

$$\hat{u}_a = [\hat{u}_{t_0}, ..., \hat{u}_{t_n}] \tag{1.16}$$

In order to apply the euler scheme successfully an initial condition \hat{u}_0 has to be known. This initial condition is obtained by applying the discrete Fourier transform (DFT) to an initial temperature distribution along x:

$$\hat{u}_0 = \mathfrak{F}(f(x)) \tag{1.17}$$

[3]

The forward euler scheme is used here because it is fairly easy to implement. By applying the inverse discrete Fourier transform (IDFT) to \hat{u}_a an approximate solution to 1.6 can be obtained. To decrease computing time, the fast Fourier transform (FFT) and inverse fast Fourier transform (IFFT) is used instead of the DFT and IDFT.

1.2. Finite Element Method

The finite element method (FEM) is a method to approximate solutions for differential equations (DE) within a certain domain Ω . Assume that a DE is given by:

$$m, n \in \mathbb{N} \quad \zeta \in \Omega \subset \mathbb{R} \quad m \ge 1$$
 (1.18)

$$\frac{\partial^m y}{\partial \zeta^m} - g(y) = r(\zeta, t) \tag{1.19}$$

It is assumed that g is a linear function that can also contain partial derivatives of y w.r.t. time, y takes the value 0 at the boundary Γ and $y(\zeta,0)=f(\zeta)$. An approximate solution to y is given by μ , which is expressed as a sum of basis functions contained in the set ϕ :

$$\mu(\zeta,t) = \sum_{j=1}^{N} c_j(t)\phi_j(\zeta)$$
(1.20)

The residual is defined as:

$$\mathfrak{r} = \frac{\partial^m \mu}{\partial \zeta^m} - g(\mu) - r(\zeta, t) \tag{1.21}$$

Furthermore the residual is required to be orthogonal to all basis functions:

$$\langle \mathfrak{r}, \phi_k \rangle = 0 \quad \forall \phi_k \in \phi \tag{1.22}$$

Since the functions in ϕ are known, it is only required to find the coefficients $c_j(t)$ in 1.20. To find those coefficients 1.22 needs to be expressed as follows:

$$\int_{\Omega} \frac{\partial^{m} \mu}{\partial \zeta^{m}} \phi_{k} d\zeta - \int_{\Omega} g(\mu) \phi_{k} d\zeta = \int_{\Omega} r(\zeta, t) \phi_{k} d\zeta \quad \forall \phi_{k} \in \phi$$
 (1.23)

If μ is substituted with 1.20 the following is obtained:

$$\sum_{i=1}^{N} \left(\left(\int_{\Omega} \frac{\partial^{m} \phi_{j}}{\partial \zeta^{m}} \phi_{k} \, d\zeta \right) c_{j}(t) - g\left(\left(\int_{\Omega} \phi_{k} \phi_{j} d\zeta \right) c_{j}(t) \right) \right) = \int_{\Omega} r(\zeta, t) \phi_{k} \, d\zeta \quad \forall \phi_{k} \in \phi$$
 (1.24)

It is also necessary to apply divergence theorem to the first integral term taking into account that y at Γ is 0. Since ζ is one dimensional, the divergence theorem becomes integration by parts:

$$\int_{\Omega} \frac{\partial^{m} \phi_{j}}{\partial \zeta^{m}} \phi_{k} d\zeta = -\int_{\Omega} \frac{\partial^{m-1} \phi_{j}}{\partial \zeta^{m-1}} \frac{\partial \phi_{k}}{\partial \zeta} d\zeta \quad \forall \phi_{k} \in \phi$$
 (1.25)

Combining 1.24 and 1.25 yields:

$$-\sum_{j=1}^{N} \left(\left(\int_{\Omega} \frac{\partial^{m-1} \phi_{j}}{\partial \zeta^{m-1}} \frac{\partial \phi_{k}}{\partial \zeta} d\zeta \right) c_{j}(t) + g\left(\left(\int_{\Omega} \phi_{k} \phi_{j} d\zeta \right) c_{j}(t) \right) \right) = \int_{\Omega} r(\zeta, t) \phi_{k} d\zeta \quad \forall \phi_{k} \in \phi \quad (1.26)$$

This formulation leads to a system of ODEs or a system of linear equations that can be solved either analytically or numerically. This formulation of FEM can be applied to 1.6:

$$\Omega = \chi \quad \Gamma = \{x_0, x_n\} \tag{1.27}$$

$$y(\zeta, t) = -u(x, t)$$
 $g(u) = -\frac{1}{\alpha} \frac{\partial u}{\partial t}$ (1.28)

$$m = 2 \quad r(\zeta, t) = \frac{1}{\alpha} h(x, t) \tag{1.29}$$

$$u(x,0) = f(x)$$
 $u(x_0,t) = 0$ $u(x_n,t) = 0$ (1.30)

The set of basis functions is defined as a set of piecewise linear functions with constant step size Δx :

$$\phi_{j}(x) = \begin{cases} (x - x_{j-1})/\Delta x, & x_{j-1} \le x < x_{j} \\ (x_{j+1} - x)/\Delta x, & x_{j} \le x < x_{j+1} \\ 0, & \text{otherwise} \end{cases}$$
 (1.31)

[4] The stepsize Δx is defined by $\Delta x = \frac{x_n - x_0}{n-1}$. This results in the following system of ODEs:

$$\sum_{j=1}^{N} \left(-\int_{\chi} \phi_j \phi_k dx\right) \frac{dc_j}{dt} = \alpha \sum_{j=1}^{N} \left(-\int_{\chi} \frac{d\phi_j}{dx} \frac{d\phi_j}{dx} dx\right) c_j(t) + \int_{\chi} h(x, t) \phi_k dx \quad \forall \phi_k \in \phi$$
 (1.32)

Using matrix notation this becomes:

$$A^{N\times N}, B^{N\times N} \tag{1.33}$$

$$A\dot{c} = Bc + d \tag{1.34}$$

The matrices A and B can be easily computed (Appendix A.1):

$$a_{ij} = \begin{cases} \frac{2\Delta x}{3}, & k = j \\ \frac{\Delta x}{6}, & |k - j| = 1 \\ 0, & otherwise \end{cases} \qquad b_{ij} = \begin{cases} \frac{-2\alpha}{\Delta x}, & k = j \\ \frac{\alpha}{\Delta x}, & |k - j| = 1 \\ 0, & otherwise \end{cases}$$
(1.35)

However it is necessary to approximate d for each point in time using numerical integration schemes. Furthermore to solve this system of ODEs numerically an initial condition c_0 has to

be known. [3] It can be obtained using a least squares (LS) approach:

$$\sum_{j=1}^{N} \langle \phi_j, \phi_k \rangle c_j(0) = \langle f, \phi_k \rangle \quad \forall \phi_k \in \phi$$
 (1.36)

[5] Observe that 1.34 almost resembles a state-space representation. Multiplying this equation with A^{-1} (Appendix A.2) yields:

Literaturverzeichnis

- [1] Gustafsson, B. "Heat Conduction". In: Fundamentals of Scientific Computing. Berlin, Heidelberg: Springer Berlin Heidelberg, 2011, S. 255–262. URL: https://doi.org/10.1007/978-3-642-19495-5_16.
- [2] Papula, L. "Gewöhnliche Differentialgleichungen". In: Mathematik für Ingenieure und Naturwissenschaftler Band 2: Ein Lehr- und Arbeitsbuch für das Grundstudium. Wiesbaden: Springer Fachmedien Wiesbaden, 2015, S. 343–541. URL: https://doi.org/10.1007/978-3-658-07790-7_4.
- [3] Gustafsson, B. "Finite Element Methods". In: Fundamentals of Scientific Computing. Berlin, Heidelberg: Springer Berlin Heidelberg, 2011, S. 173–192. URL: https://doi.org/10.1007/978-3-642-19495-5_11.
- [4] Gustafsson, B. "Polynomial Expansions". In: Fundamentals of Scientific Computing. Berlin, Heidelberg: Springer Berlin Heidelberg, 2011, S. 117–123. URL: https://doi.org/10.1007/978-3-642-19495-5_7.
- [5] Gustafsson, B. "Least Square Problems". In: Fundamentals of Scientific Computing. Berlin, Heidelberg: Springer Berlin Heidelberg, 2011, S. 125–133. URL: https://doi.org/10.1007/978-3-642-19495-5_8.
- [6] D'Erchie, M. e. a. "Analysis Eins". In: Mathe für Nicht-Freaks. Serlo Education e. V., 2017, S. 111–113. URL: https://mathe-builds.serlo.org/analysis1_final/ analysis1_final.pdf.

A. Appendix

A.1. Deriving matrices for FEM using piecewise linear functions

The so called triangle function is defined as follows:

$$\phi_{j}(x) = \begin{cases} (x - x_{j-1})/\Delta x, & x_{j-1} \le x < x_{j} \\ (x_{j+1} - x)/\Delta x, & x_{j} \le x < x_{j+1} \\ 0, & \text{otherwise} \end{cases}$$
(A.1)

[4] The following integrals have to be evaluated:

$$\int_{\mathcal{X}} \phi_j \phi_k dx \quad \forall \phi_k \in \phi \tag{A.2}$$

$$-\int_{\mathcal{X}} \frac{d\phi_j}{dx} \frac{d\phi_k}{dx} dx \quad \forall \phi_k \in \phi \tag{A.3}$$

With $\chi \subset \mathbb{R}$. Note that the product of two functions ϕ_j and ϕ_k and their derivatives is only under two conditions not zero:

1. k = j

Considering this case the integral A.2 becomes:

$$\int_{x_{j-1}}^{x_j} \phi_j^2 dx + \int_{x_j}^{x_{j+1}} \phi_j^2 dx \tag{A.4}$$

Because of symmetry only one of the above integrals have to computed:

$$2\int_{x_{j-1}}^{x_j} \phi_j^2 dx \tag{A.5}$$

$$= \frac{2}{\Delta x^2} \int_{x_{j-1}}^{x_j} (x - x_{j-1})^2 dx \tag{A.6}$$

$$\frac{2}{3\Delta x^2} \left[(x - x_{j-1})^3 \right]_{x_{j-1}}^{x_j} = \frac{2}{3\Delta x^2} \Delta x^3 = \frac{2}{3} \Delta x \tag{A.7}$$

Integral A.3 for i = j taking symmetry into account becomes:

$$-\int_{x_{j-1}}^{x_{j+1}} \left(\frac{d\phi_j}{dx}\right)^2 dx = -\frac{1}{\Delta x^2} \int_{x_{j-1}}^{x_{j+1}} 1 dx \tag{A.8}$$

$$= -\frac{1}{\Delta x^2} \left[x \right]_{x_{j-1}}^{x_{j+1}} = -\frac{2}{\Delta x} \tag{A.9}$$

2. |j - k| = 1 A.2 becomes:

$$\frac{1}{\Delta x^2} \int_{x_j}^{x_{j+1}} (x - x_j)(x_{j+1} - x) dx \tag{A.10}$$

$$= \left[\frac{1}{2}x^2x_{j+1} - \frac{1}{3}x^3 - xx_{j+1}x_j + \frac{1}{2}x^2x_j\right]_{x_j}^{x_{x_j+1}} = \frac{1}{6\Delta x^2}\Delta x^3 = \frac{1}{6}\Delta x \tag{A.11}$$

Finally A.3 has to be evaluated for this condition:

$$-\int_{x_j}^{x_{j+1}} \frac{d\phi_j}{dx} \frac{d\phi_{j+1}}{dx} dx = \frac{1}{\Delta x^2} \int_{x_j}^{x_{j+1}} 1 dx = \frac{1}{\Delta x^2} \left[x \right]_{x_j}^{x_{j+1}} = \frac{1}{\Delta x}$$
 (A.12)

A.2. Proof that matrix A is invertible

Let A_n be a matrix with $A_n \in \mathbb{R}^{n \times n}$ given by:

$$a_{ij} = \begin{cases} a, & k = j \\ b, & |k - j| = 1 \\ 0, & otherwise \end{cases}$$
(A.13)

It's determinant is given by the Laplace expansion:

$$det(A_n) = \sum_{j=1}^{n} (-1)^{i+j} a_{ij} M_{ij} \quad \forall i$$
 (A.14)

 M_{ij} is the determinant of the matrix A' that is obtained by removing the i^{th} row and j^{th} column of A_n . This expression can be simplified using the definition of a_{ij} :

$$det(A_n) = aM_{11} - bM_{12} (A.15)$$

 M_{11} is equivalent to $det(A_{n-1})$, since the indices of rows and columns of A' are in consecutive order and A' is a $n-1 \times n-1$ matrix:

$$M_{11} = \det(A') \tag{A.16}$$

$$A' = \begin{bmatrix} a_{22} & \dots & a_{2n} \\ \vdots & \ddots & \vdots \\ a_{n2} & \dots & a_{nn} \end{bmatrix}$$
(A.17)

 M_{12} can be obtained by calculating the determinant of A' using the Laplace expansion:

$$A' = \begin{bmatrix} a_{21} & a_{23} & \dots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{n1} & a_{n3} & \dots & a_{nn} \end{bmatrix}$$
 (A.18)

$$det(A') = a_{21} \cdot det(A'') \tag{A.19}$$

$$A'' = \begin{bmatrix} a_{33} & \dots & a_{3n} \\ \vdots & \ddots & \vdots \\ a_{n3} & \dots & a_{nn} \end{bmatrix}$$
(A.20)

In A.19 only the stated term has to evaluated since all entries of the first column of the second submatrix are zero. Therefore the determinant is zero. The row and column indices of A'' are in consecutive order and it is a $n-2 \times n-2$ matrix. Therefore A'' is equivalent to A_{n-2} . A.15 becomes:

$$det(A_n) = a \cdot det(A_{n-1}) - b^2 \cdot det(A_{n-2})$$
(A.21)

Furthermore this implies $det(A_0) = 1$:

$$det(A_2) = a^2 - b^2 = a \cdot det(A_1) - b^2 \cdot 1$$
(A.22)

$$\Rightarrow det(A_0) = 1 \tag{A.23}$$

Using the definition of 1.35 and 1.2 this can be seen as the following sequence:

$$a_0 = 1, \ a_1 = \frac{2\Delta x}{3}$$
 (A.24)

$$a_{n+1} = \frac{2\Delta x}{3} \cdot a_n - \frac{\Delta x^2}{36} \cdot a_{n-1} \tag{A.25}$$

As described here [6] a recursive sequence converges if it is monotone and has a limit. A proof by induction shows that this sequence is monotone for $n \ge 1$.

Base case:

$$a_2 = \left(\frac{2\Delta x}{3}\right)^2 - \frac{\Delta x^2}{36} = \Delta x^2 \left(\frac{4}{9} - \frac{1}{36}\right) < \frac{2\Delta x}{3} = a_1$$
 (A.26)

Induction step: Assuming that $a_k < a_{k-1}$ holds, $a_{k+1} < a_k$ also holds:

$$a_{k+1} = \frac{2\Delta x}{3} \cdot a_k - \frac{\Delta x^2}{36} \cdot a_{k-1} < \frac{2\Delta x}{3} \cdot a_{k-1} - \frac{\Delta x^2}{36} \cdot a_{k-2} = a_k \tag{A.27}$$

The limit of this sequence is as follow:

$$\alpha = \lim_{n \to \infty} a_{n+1} = \lim_{n \to \infty} \Delta x \cdot \frac{2}{3} \cdot \lim_{n \to \infty} a_n - \lim_{n \to \infty} \Delta x^2 \cdot \frac{1}{36} \cdot \lim_{n \to \infty} a_{n-1} = 0 \cdot \alpha - 0 \cdot \alpha = 0$$
 (A.28)

Since this series is monotone and converges to zero as n goes to infinity, there is no $n \in \mathbb{N}$ for which $a_n = 0$. Therefore the determinant of the matrix A defined in 1.35 is not zero and A is invertible.