# Biscayne Bay-Cape Florida to Monroe County Line Aquatic Preserve SEACAR Habitat Analyses

# Last compiled on 14 March, 2024

# Contents

Threshold Filtering	2
Value Qualifiers	3
Water Quality - Continuous  Water Temperature - Continuous Water Quality	
Coral Reef	8

# Threshold Filtering

Threshold filters, following the guidance of Florida Department of Environmental Protection's (FDEP) Division of Environmental Assessment and Restoration (DEAR) are used to exclude specific results values from the SEACAR Analysis. Based on the threshold filters, Quality Assurance / Quality Control (QAQC) Flags are inserted into the  $SEACAR\_QAQCFlagCode$  and  $SEACAR\_QAQC\_Description$  columns of the export data. The Include column indicates whether the QAQC Flag will also indicate that data are excluded from analysis. No data are excluded from the data export, but the analysis scripts can use the Include column to exclude data (1 to include, 0 to exclude).

Table 1: Continuous Water Quality threshold values

Parameter Name	Units	Low Threshold	High Threshold	Sensor Type
Dissolved Oxygen	$\mathrm{mg/L}$	0	50	YSI EXOs
Dissolved Oxygen	$\mathrm{mg/L}$	0	50	Analysis Only - 2022-04-04
Dissolved Oxygen	mg/L	0	50	6600 Series
Salinity	ppt	0	70	6600 Series
Salinity	$\operatorname{ppt}$	0	70	YSI EXOs
Salinity	$\operatorname{ppt}$	0	70	Analysis Only - 2022-04-04
Water Temperature	Degrees C	-5	45	YSI EXOs
Water Temperature	Degrees C	-5	45	Analysis Only - 2022-04-04
Water Temperature	Degrees C	-5	45	6600 Series
pН	рН	2	14	Analysis Only - 2022-04-04
pH	рН	2	14	6600 Series
pН	рН	2	14	YSI EXOs
Dissolved Oxygen Saturation	%	0	500	YSI EXOs
Dissolved Oxygen Saturation	%	0	500	6600 Series
Dissolved Oxygen Saturation	%	0	500	Analysis Only - 2022-04-04
Specific Conductivity	mS/cm	0	100	6600 Series
Specific Conductivity	mS/cm	0	200	YSI EXOs
Turbidity	NTU	0	4000	YSI EXOs
Turbidity	NTU	0	1000	6600 Series
Turbidity	NTU	0	4000	Analysis Only - 2022-04-04

Table 2: Discrete Water Quality threshold values

Parameter Name	Units	$Low\ Threshold$	High Threshold
Dissolved Oxygen	mg/L	0.000001	22
Salinity	ppt	0	70
Water Temperature	Degrees C	3	40
pН		2	13
Dissolved Oxygen Saturation	%	0.000001	310
Specific Conductivity	mS/cm	0.005000001	100
Turbidity	NTU	0	-
Total Suspended Solids (TSS)	mg/L	0	-
Chlorophyll a uncorrected for pheophytin	ug/L	0	-
Chlorophyll a corrected for pheophytin	ug/L	0	-
Secchi Depth	m	0.000001	50
Light Extinction Coefficient	$m^1$	0	-
Colored dissolved organic matter, CDOM	PCU	0	-
Fluorescent dissolved organic matter, FDOM	QSE	0	-
Total Nitrogen	mg/L	0	-
Total Kjeldahl Nitrogen TKN	mg/L	0	-
NO2+3 Filtered	$\mathrm{mg/L}$	0	-
NH4 Filtered	mg/L	0	-
Total Phosphorus	mg/L	0	-

Parameter Name	Units	Low Threshold	High Threshold
PO4 Filtered	mg/L	0	_
Ammonia- Un-ionized (NH3)	mg/L	0	-
Nitrate (N)	mg/L	0	-
Nitrite (N)	mg/L	0	-
Nitrogen, organic	mg/L	0	-

Table 3: Quality Assurance Flags inserted based on threshold checks listed in Table 1 & 2

Include	$SEACAR\ QAQCF lagCode$
No	2Q
No	3Q
No	4Q
No	5Q
Yes	6Q
Yes	7Q
	No No No No Yes

### Value Qualifiers

Value qualifier codes included within the data are used to exclude certain results from the analysis. The data are retained in the data export files, but the analysis uses the *Include* column to filter the results.

#### STORET and WIN value qualifier codes

Value qualifier codes from *STORET* and *WIN* data are examined with the database and used to populate the *Include* column in data exports.

Table 4: Value Qualifier codes excluded from analysis

Qualifier Source	Value Qualifier	Include	MDL	Description
STORET-WIN	Н	No	0	Value based on field kit determination; results may not be accurate
STORET-WIN	J	No	0	Estimated value
STORET-WIN	V	No	0	Analyte was detected at or above method detection limit
STORET-WIN	Y	No	0	Lab analysis from an improperly preserved sample; data may be inaccurate

#### Discrete Water Quality Value Qualifiers

The following value qualifiers are highlighted in the Discrete Water Quality section of this report. An exception is made for **Program 476** - Charlotte Harbor Estuaries Volunteer Water Quality Monitoring Network and data flagged with Value Qualifier **H** are included for this program only.

- **H** Value based on field kit determiniation; results may not be accurate. This code shall be used if a field screening test (e.g., field gas chromatograph data, immunoassay, or vendor-supplied field kit) was used to generate the value and the field kit or method has not been recognized by the Department as equivalent to laboratory methods.
- I The reported value is greater than or equal to the laboratory method detection limit but less than the laboratory practical quantitation limit.
- **Q** Sample held beyond the accepted holding time. This code shall be used if the value is derived from a sample that was prepared or analyzed after the approved holding time restrictions for sample preparation or analysis.
- S Secchi disk visible to bottom of waterbody. The value reported is the depth of the waterbody at the location of the Secchi disk measurement.

U - Indicates that the compound was analyzed for but not detected. This symbol shall be used to indicate that the specified component was not detected. The value associated with the qualifier shall be the laboratory method detection limit. Unless requested by the client, less than the method detection limit values shall not be reported

#### Systemwide Monitoring Program (SWMP) value qualifier codes

Value qualifier codes from the SWMP continuous program are examined with the database and used to populate the Include column in data exports. SWMP Qualifier Codes are indicated by QualifierSource=SWMP.

Table 5: SWMP Value Qualifier codes

Qualifier Source	Value Qualifier	Include	Description
SWMP	-1	Yes	Optional parameter not collected
SWMP	-2	No	Missing data
SWMP	-3	No	Data rejected due to QA/QC
SWMP	-4	No	Outside low sensor range
SWMP	-5	No	Outside high sensor range
SWMP	0	Yes	Passed initial QA/QC checks
SWMP	1	No	Suspect data
SWMP	2	Yes	Reserved for future use
SWMP	3	Yes	Calculated data: non-vented depth/level sensor correction for changes in barometric pressure
SWMP	4	Yes	Historical: Pre-auto QA/QC
SWMP	5	Yes	Corrected data


# Water Quality - Continuous

The following files were used in the continuous analysis:

- $\bullet \ \ Combined\_WQ\_WC\_NUT\_cont\_Dissolved\_Oxygen\_SE\text{-}2024\text{-}Feb\text{-}22.txt$
- $\bullet \ \ Combined\_WQ\_WC\_NUT\_cont\_Dissolved\_Oxygen\_Saturation\_SE-2024\text{-}Feb-22.txt$
- $\bullet \ \ Combined\_WQ\_WC\_NUT\_cont\_pH\_SE\text{-}2024\text{-}Feb\text{-}22.txt$
- $\bullet \ \ Combined\_WQ\_WC\_NUT\_cont\_Salinity\_SE\text{-}2024\text{-}Feb\text{-}22.txt$
- $\bullet \ \ Combined\_WQ\_WC\_NUT\_cont\_Turbidity\_SE\text{-}2024\text{-}Feb\text{-}22.txt$
- $\bullet \ \ Combined\_WQ\_WC\_NUT\_cont\_Water\_Temperature\_SE-2024-Feb-22.txt$

Table 6: Water Temperature on Coral Reefs in the Florida Keys (986)

$\overline{ProgramLocationID}$	Years of Data	Use in Analysis	Parameters
6	10	TRUE	TempW




Map showing Continuous Water Quality Monitoring sampling locations within the boundaries of Biscayne Bay-Cape Florida to Monroe County Line Aquatic Preserve. Sites marked as *Use In Analysis* are featured in this report.

## Water Temperature - Continuous Water Quality

6

Water Temperature on Coral Reefs in the Florida Keys (986)

Biscayne Bay-Cape Florida to Monroe County Line Aquatic Preserve



p < 0.00005 appear as 0 due to rounding.


SennIntercept is intercept value at beginning of record for monitoring location

# Coral Reef

#### The data file used is: All\_CORAL\_Parameters-2024-Feb-23.txt


#### **Coral Percent Cover**

Biscayne Bay-Cape Florida to Monroe County Line Aquatic Preserve



LME\_p < 0.00005 appear as 0 due to rounding.

# Grazers and Reef-Dependent Species Richness Biscayne Bay-Cape Florida to Monroe County Line Aquatic Preserve



N_Years	EarliestYear	LatestYear	N_Data	Min	Max	Median	Mean	StDev	Year_MinRichness	Year_MaxRichness
4	2009	2015	5	2	218	2	88.4	118.31	2009	2014