

SEACAR Continuous Water Quality Analysis: NE Region for Water Temperature

Last compiled on 01 June, 2022

Contents

| | |
|---|-----------|
| Important Notes | 1 |
| Libraries | 1 |
| File Import | 2 |
| Data Filtering | 2 |
| Monitoring Location Statistics | 4 |
| Seasonal Kendall Tau Analysis | 5 |
| Appendix I: Dataset Summary Box Plots | 9 |
| Appendix II: Excluded Monitoring Locations | 15 |
| Appendix III: Monitoring Location Trendlines | 21 |
| Appendix IV: Monitoring Location Summary Box Plots | 28 |

Important Notes

All scripts and outputs can be found on the SEACAR GitHub repository:

https://github.com/FloridaSEACAR/SEACAR_Panzik

Note: The top 2% of data is excluded when computing mean and standard deviations in plotting sections solely for the purpose of getting y-axis scales. The exclusion of the top 2% is not used in any statistics that are exported.

Libraries

Loads libraries used in the script. The inclusion of `scipen` option limits how frequently R defaults to scientific notation.

```
library(knitr)
library(data.table)
library(dplyr)
library(lubridate)
library(ggplot2)
library(ggpubr)
library(scales)
library(EnvStats)
library(tidyr)
options(scipen = 999)
opts_chunk$set(warning=FALSE, message=FALSE)
```

File Import

Imports file that is determined in the WC_Continuous_parameter_ReportCompile.R script.

The command `fread` is used because of its improved speed while handling large data files. Only columns that are used by the script are imported from the file, and are designated in the `select` input.

The script then gets the name of the parameter as it appears in the data file and units of the parameter.

```
data <- fread(file_in, sep = "|", header = TRUE, stringsAsFactors = FALSE,
              select = c("ManagedAreaName", "ProgramID", "ProgramName",
                        "ProgramLocationID", "SampleDate", "Year", "Month",
                        "RelativeDepth", "ActivityType", "ParameterName",
                        "ResultValue", "ParameterUnits", "ValueQualifier",
                        "SEACAR_QAQCFlagCode", "Include"),
              na.strings = "")
parameter <- unique(data$ParameterName)
unit <- unique(data$ParameterUnits)
```

Data Filtering

Most data filtering is performed on export from the database, and is indicated by the `Include` variable. `Include` values of 1 indicate the data should be used for analysis, values of 0 indicate the data should not be used for analysis. Documentation on the database filtering is provided here: SEACAR Documentation-Analysis Filters and Calculations.docx

The filtering that is performed by the script at this point removes rows that are missing values for `ResultValue` and `RelativeDepth`, and removes any activity type that has “Blank” in the description. Data passes the filtering the process if it has an `Include` value of 1.

The script then gets the units of the parameter, sets the `SampleDate` as a date object, and creates various scales of the date to be used by plotting functions.

Because the continuous data is extensive and most measurements are taken every 15 minutes, a daily average is determined and used based on grouping `ManagedAreaName`, `ProgramID`, `ProgramName`, `ProgramLocationID`, and `SampleDate`. The new `ResultValue` is the mean of all values on that date from that specific monitoring location. Sets the `SampleDate` as a date object, and creates various scales of the date to be used by plotting functions.

Creates a variable for each `MonitoringID` which is defined as a unique combination of `ManagedAreaName`, `ProgramID`, `ProgramAreaName`, and `ProgramLocationID`.

After the initial filtering, a second filter variable is created to determine whether enough time is represented in the managed area, which is that each managed area has 5 year or more of unique year entries for observation that pass the initial filter. If data passes the first set of filtering criteria and the time criteria, they are used in the analysis.

```
data$Include <- as.logical(data$Include)
data <- data[data$Include==TRUE,]
data <- data[!is.na(data$ResultValue),]
data <- data[!is.na(data$RelativeDepth),]
data <- data[!grep("Blank", data$ActivityType),]

if(param_name == "Water_Temperature"){
  data <- data[data$ResultValue>=-5,]
} else{
  data <- data[data$ResultValue>=0,]
}

data <- data %>%
  group_by(ManagedAreaName, ProgramID, ProgramName, ProgramLocationID,
    SampleDate) %>%
  summarise(Year = unique(Year), Month = unique(Month),
    RelativeDepth = unique(RelativeDepth),
    ResultValue = mean(ResultValue), Include = unique(Include))

data <- merge.data.frame(MA_All[,c("AreaID", "ManagedAreaName")],
  data, by = "ManagedAreaName", all=TRUE)

data$SampleDate <- as.Date(data$SampleDate)
data$YearMonth <- paste0(data$Month, "-", data$Year)
data$YearMonthDec <- data$Year + ((data$Month-0.5) / 12)
data$DecDate <- decimal_date(data$SampleDate)

data <- data %>%
  group_by(ManagedAreaName, ProgramID, ProgramName, ProgramLocationID) %>%
  mutate(MonitoringID = cur_group_id())
# data <- data %>%
#   mutate(MonitoringID = group_indices(., ManagedAreaName, ProgramID,
#     ProgramName, ProgramLocationID))

Mon_Summ <- data %>%
  group_by(MonitoringID, AreaID, ManagedAreaName, ProgramID, ProgramName,
    ProgramLocationID) %>%
  summarise(ParameterName=parameter,
    RelativeDepth=unique(RelativeDepth),
    N_Data=length(ResultValue[Include==TRUE & !is.na(ResultValue)]),
    N_Years=length(unique(Year[Include==TRUE & !is.na(Year)])),
    EarliestYear=min(Year[Include==TRUE]),
    LatestYear=max(Year[Include==TRUE]),
    SufficientData=ifelse(N_Data>0 & N_Years>=10, TRUE, FALSE))

#
# Mon_Years <- data[data$Include == TRUE, ] %>%
#   group_by(MonitoringID) %>%
```

```

#   summarize(AreaID = unique(AreaID),
#             ManagedAreaName = unique(ManagedAreaName),
#             ProgramID = unique(ProgramID),
#             ProgramName = unique(ProgramName),
#             ProgramLocationID = unique(ProgramLocationID),
#             ParameterName = parameter,
#             RelativeDepth = unique(RelativeDepth),
#             Y = length(unique(Year)))
Mon_Summ <- as.data.table(Mon_Summ[order(Mon_Summ$MonitoringID), ])

data <- merge.data.frame(data, Mon_Summ[,c("MonitoringID", "SufficientData")],
                        by = "MonitoringID")
# data$Exclude_MonitoringID <- is.element(data$MonitoringID,
#                                         Mon_Years$MonitoringID[
#                                         Mon_Years$Enough_Time == FALSE])
data$Use_In_Analysis <- ifelse(data$Include == TRUE &
                              data$SufficientData == TRUE, TRUE, FALSE)

Mon_IDs <- unique(data$MonitoringID[data$Use_In_Analysis == TRUE])
Mon_IDs <- Mon_IDs[order(Mon_IDs)]
n <- length(Mon_IDs)

```

Monitoring Location Statistics

Gets summary statistics for each monitoring location. Excluded monitoring locations are not included into whether the data should be used or not. Uses piping from dplyr package to feed into subsequent steps. The following steps are performed:

1. Take the `data` variable and only include rows that have a `Use_In_Analysis` value of `TRUE`
2. Group data that have the same `ManagedAreaName`, `ProgramID`, `ProgramName`, `ProgramLocationID`, `Year`, and `Month`.
 - Second summary statistics consider the monitoring location grouping and `Year`.
 - Third summary statistics consider the monitoring location grouping and `Month`.
3. For each group, provide the following information: Earliest Sample Date (`EarliestSampleDate`), Latest Sample Date (`LastSampleDate`), Number of Entries (`N`), Lowest Value (`Min`), Largest Value (`Max`), Median, Mean, Standard Deviation, and a list of all Program IDs included in these measurements.
4. Sort the data in ascending (A to Z and 0 to 9) order based on `ManagedAreaName`, `ProgramID`, `ProgramName`, `ProgramLocationID`, `Year`, and `Month` in that order.
5. Write summary stats to a pipe-delimited `.txt` file in the output directory

```

Mon_YM_Stats <- data[data$Use_In_Analysis == TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, ProgramID, ProgramName, ProgramLocationID,
           Year, Month) %>%
  summarize(ParameterName = parameter,
            RelativeDepth = unique(RelativeDepth),
            EarliestSampleDate = min(SampleDate),
            LastSampleDate = max(SampleDate), N = length(ResultValue),
            Min = min(ResultValue), Max = max(ResultValue),
            Median = median(ResultValue), Mean = mean(ResultValue),
            StandardDeviation = sd(ResultValue))

```

```

Mon_YM_Stats <- as.data.table(Mon_YM_Stats[order(Mon_YM_Stats$ManagedAreaName,
                                                Mon_YM_Stats$ProgramID,
                                                Mon_YM_Stats$ProgramName,
                                                Mon_YM_Stats$ProgramLocationID,
                                                Mon_YM_Stats$Year,
                                                Mon_YM_Stats$Month), ])

fwrite(Mon_YM_Stats, paste0(out_dir, "/", param_name, "_", region,
                           "_MonitoringLoc_YearMonth_Stats.txt"), sep = "|")

Mon_Y_Stats <- data[data$Use_In_Analysis == TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, ProgramID, ProgramName, ProgramLocationID,
           Year) %>%
  summarize(ParameterName = parameter,
            RelativeDepth = unique(RelativeDepth),
            EarliestSampleDate = min(SampleDate),
            LastSampleDate = max(SampleDate), N = length(ResultSet),
            Min = min(ResultSet), Max = max(ResultSet),
            Median = median(ResultSet), Mean = mean(ResultSet),
            StandardDeviation = sd(ResultSet))
Mon_Y_Stats <- as.data.table(Mon_Y_Stats[order(Mon_Y_Stats$ManagedAreaName,
                                              Mon_Y_Stats$ProgramID,
                                              Mon_Y_Stats$ProgramName,
                                              Mon_Y_Stats$ProgramLocationID,
                                              Mon_Y_Stats$Year), ])

fwrite(Mon_Y_Stats, paste0(out_dir, "/", param_name, "_", region,
                           "_MonitoringLoc_Year_Stats.txt"), sep = "|")

Mon_M_Stats <- data[data$Use_In_Analysis == TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, ProgramID, ProgramName, ProgramLocationID,
           Month) %>%
  summarize(ParameterName = parameter,
            RelativeDepth = unique(RelativeDepth),
            EarliestSampleDate = min(SampleDate),
            LastSampleDate = max(SampleDate), N = length(ResultSet),
            Min = min(ResultSet), Max = max(ResultSet),
            Median = median(ResultSet), Mean = mean(ResultSet),
            StandardDeviation = sd(ResultSet))
Mon_M_Stats <- as.data.table(Mon_M_Stats[order(Mon_M_Stats$ManagedAreaName,
                                              Mon_M_Stats$ProgramID,
                                              Mon_M_Stats$ProgramName,
                                              Mon_M_Stats$ProgramLocationID,
                                              Mon_M_Stats$Month), ])

fwrite(Mon_M_Stats, paste0(out_dir, "/", param_name, "_", region,
                           "_MonitoringLoc_Month_Stats.txt"), sep = "|")

```

Seasonal Kendall Tau Analysis

Gets seasonal Kendall Tau statistics using the `kendallSeasonalTrendTest` from the `EnvStats` package. The `Trend` parameter is determined from a user-defined function based on the median, Senn slope, and p values from the data. Analysis modified from that performed at The Water Atlas: <https://sarasota.wateratlas.usf.edu/water-quality-trends/#analysis-overview>

The following steps are performed:

1. Define the trend function.
2. Take the `data` variable and only include rows that have a `Use_In_Analysis` value of `TRUE`
3. Group data that have the same `ManagedAreaName`, `ProgramID`, `ProgramName`, and `ProgramLocationID`.
4. For each group, provides the following information: Earliest Sample Date (`EarliestSampleDate`), Latest Sample Date (`LastSampleDate`), Number of Entries (`N`), Lowest Value (`Min`), Largest Value (`Max`), Median, Mean, Standard Deviation,
5. For each group, a temporary variable is created to run the `kendallSeasonalTrendTest` function using the `Year` values for year, and `Month` as the seasonal qualifier, and `Trend`.
 - An `independent.obs` value of `TRUE` indicates that the data should be treated as not being serially auto-correlated. An `independent.obs` value of `FALSE` indicates that it is treated as being serially auto-correlated, but also requires one observation per season per year for the full time of observation.
 - `tau`, Senn Slope (`SennSlope`), Senn Intercept (`SennIntercept`), and `p` are extracted from the model results.
6. The two stats tables are merged based on similar groups, and then `Trend` is determined from the user-defined function.
7. Write summary stats to a pipe-delimited `.txt` file in the output directory
 - [Click this text](#) to open Git directory with output files
8. Add the Monitoring IDS to `KT.Stats` for easier use while plotting.

```
tauSeasonal <- function(data, independent, stats.median, stats.minYear,
                        stats.maxYear) {
  tau <- NULL
  tryCatch({ken <- kendallSeasonalTrendTest(
    y = data$ResultValue,
    season = data$Month,
    year = data$Year,
    independent.obs = independent)

  tau <- ken$estimate[1]
  p <- ken$p.value[2]
  slope <- ken$estimate[2]
  intercept <- ken$estimate[3]
  trend <- trend_calculator(slope, stats.median, p)
  rm(ken)
}, warning = function(w) {
  print(w)
}, error = function(e) {
  print(e)
}, finally = {
  if (!exists("tau")) {
    tau <- NA
  }
  if (!exists("p")) {
    p <- NA
  }
})
```

```

    }
    if (!exists("slope")) {
      slope <- NA
    }
    if (!exists("intercept")) {
      intercept <- NA
    }
    if (!exists("trend")) {
      trend <- NA
    }
  })
  KT <- c(unique(data$MonitoringID),
        stats.median,
        independent,
        tau,
        p,
        slope,
        intercept,
        trend)
  return(KT)
}

runStats <- function(data) {
  data$Index <- as.Date(data$SampleDate) # , "%Y-%m-%d")
  data$ResultValue <- as.numeric(data$ResultValue)
  # Calculate basic stats
  stats.median <- median(data$ResultValue, na.rm = TRUE)
  stats.minYear <- min(data$Year, na.rm = TRUE)
  stats.maxYear <- max(data$Year, na.rm = TRUE)
  # Calculate Kendall Tau and Slope stats, then update appropriate columns and table
  KT <- tauSeasonal(data, TRUE, stats.median,
                    stats.minYear, stats.maxYear)
  if (is.null(KT[8])) {
    KT <- tauSeasonal(data, FALSE, stats.median,
                      stats.minYear, stats.maxYear)
  }
  if (is.null(KT.Stats) == TRUE) {
    KT.Stats <- KT
  } else {
    KT.Stats <- rbind(KT.Stats, KT)
  }
  return(KT.Stats)
}

trend_calculator <- function(slope, median_value, p) {
  trend <-
    if (p < .05 & abs(slope) > abs(median_value) / 10.) {
      if (slope > 0) {
        2
      }
      else {
        -2
      }
    }
  else if (p < .05 & abs(slope) < abs(median_value) / 10.) {

```

```

    if (slope > 0) {
      1
    }
    else {
      -1
    }
  }
  else
    0
  return(trend)
}
KT.Stats <- NULL
# Loop that goes through each managed area.
# List of managed areas stored in MA_Years$ManagedAreaName
c_names <- c("MonitoringID", "Median", "Independent", "tau", "p",
             "SennSlope", "SennIntercept", "Trend")
if(n==0){
  KT.Stats <- data.frame(matrix(ncol=length(c_names),
                               nrow=nrow(Mon_Summ)))
  colnames(KT.Stats) <- c_names
  KT.Stats[, c("MonitoringID")] <- Mon_Summ[, c("MonitoringID")]
} else{
  for (i in 1:n) {
    x <- nrow(data[data$Use_In_Analysis == TRUE &
                  data$MonitoringID == Mon_IDs[i], ])
    if (x>0) {
      KT.Stats <- runStats(data[data$Use_In_Analysis == TRUE &
                              data$MonitoringID == Mon_IDs[i], ])
    }
  }
  KT.Stats <- as.data.frame(KT.Stats)

  if(dim(KT.Stats)[2]==1){
    KT.Stats <- as.data.frame(t(KT.Stats))
  }
  colnames(KT.Stats) <- c_names
  rownames(KT.Stats) <- seq(1:nrow(KT.Stats))
  KT.Stats$tau <- round(as.numeric(KT.Stats$tau), digits=4)
  KT.Stats$p <- round(as.numeric(KT.Stats$p), digits=4)
  KT.Stats$SennSlope <- as.numeric(KT.Stats$SennSlope)
  KT.Stats$SennIntercept <- as.numeric(KT.Stats$SennIntercept)
  KT.Stats$Trend <- as.integer(KT.Stats$Trend)
}

KT.Stats <- merge.data.frame(Mon_Summ, KT.Stats,
                             by=c("MonitoringID"), all=TRUE)

KT.Stats <- as.data.table(KT.Stats[order(KT.Stats$MonitoringID), ])

KT.Stats$MonitoringID <- NULL
fwrite(KT.Stats, paste0(out_dir, "/", param_name, "_", region,
                        "_KendallTau_Stats.txt"), sep = "|")

```



```
KT.Stats$MonitoringID <- Mon_Summ$MonitoringID
data <- data[!is.na(data$ResultValue),]
```

Appendix I: Dataset Summary Box Plots

Box plots are created by using the entire data set and excludes any data that has been previously filtered out. The scripts that create plots follow this format

1. Use the data set that only has Use_In_Analysis of TRUE
2. Set what values are to be used for the x-axis, y-axis, and the variable that should determine groups for the box plots
3. Set the plot type as a box plot with the size of the outlier points
4. Create the title, x-axis, y-axis, and color fill labels
5. Set the y and x limits
6. Make the axis labels bold
7. Plot the arrangement as a set of panels

This set of box plots are grouped by year.

```
plot_theme <- theme_bw() + theme(text=element_text(family="Segoe UI"),
                                title=element_text(face="bold"),
                                plot.title=element_text(hjust=0.5,
                                                         size=14,
                                                         color="#314963"),
                                plot.subtitle=element_text(hjust=0.5,
                                                           size=10,
                                                           color="#314963"),
                                axis.text.x=element_text(face="bold"),
                                axis.text.y=element_text(face="bold"))

min_RV <- min(data$ResultValue[data$Include == TRUE])
mn_RV <- mean(data$ResultValue[data$Include == TRUE &
                               data$ResultValue <
                               quantile(data$ResultValue, 0.98)])
sd_RV <- sd(data$ResultValue[data$Include == TRUE &
                              data$ResultValue <
                              quantile(data$ResultValue, 0.98)])
y_scale <- mn_RV + 4 * sd_RV

p1 <- ggplot(data = data[data$Include == TRUE, ],
            aes(x = Year, y = ResultValue, group = Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
              outlier.size=3, outlier.color="#333333",
              outlier.fill="#cccccc", outlier.alpha=0.75) +
  labs(subtitle = "Autoscale", x = "Year",
       y = paste0("Values (", unit, ")")) +
  plot_theme

p2 <- ggplot(data = data[data$Include == TRUE, ],
            aes(x = Year, y = ResultValue, group = Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
```

```

        outlier.size=3, outlier.color="#333333",
        outlier.fill="#cccccc", outlier.alpha=0.75) +
labs(subtitle = "Scaled to 4x Standard Deviation", x = "Year",
     y = paste0("Values (", unit, ")")) +
ylim(0, y_scale) +
plot_theme

p3 <- ggplot(data = data[data$Include == TRUE, ],
            aes(x = as.integer(Year), y = ResultValue, group = Year)) +
geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
            outlier.size=3, outlier.color="#333333",
            outlier.fill="#cccccc", outlier.alpha=0.75) +
labs(subtitle = "Scaled to 4x Standard Deviation, Last 10 Years",
     x = "Year", y = paste0("Values (", unit, ")")) +
ylim(0, y_scale) +
scale_x_continuous(limits = c(max(data$Year) - 10.5, max(data$Year)+0.5),
                  breaks = seq(max(data$Year) - 10, max(data$Year), 2)) +
plot_theme

set <- ggarrange(p1, p2, p3, ncol = 1)

p0 <- ggplot() + labs(title = "Summary Box Plots for Entire Data",
                    subtitle = "By Year") + plot_theme +
  theme(panel.border = element_blank(), panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(), axis.line = element_blank())

Yset <- ggarrange(p0, set, ncol=1, heights = c(0.07, 1))

```

This set of box plots are grouped by year and month with the color being related to the month.

```

p1 <- ggplot(data = data[data$Include == TRUE, ],
            aes(x = YearMonthDec, y = ResultValue,
                group = YearMonth, color = as.factor(Month))) +
geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
labs(subtitle = "Autoscale", x = "Year",
     y = paste0("Values (", unit, ")"), color="Month") +
plot_theme +
theme(legend.position = "top", legend.box = "horizontal") +
guides(color = guide_legend(nrow = 1))

p2 <- ggplot(data = data[data$Include == TRUE, ],
            aes(x = YearMonthDec, y = ResultValue,
                group = YearMonth, color = as.factor(Month))) +
geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
labs(subtitle = "Scaled to 5x Standard Deviation",
     x = "Year", y = paste0("Values (", unit, ")")) +
ylim(0, y_scale) +
plot_theme +
theme(legend.position = "none")

p3 <- ggplot(data = data[data$Include == TRUE, ],
            aes(x = YearMonthDec, y = ResultValue,
                group = YearMonth, color = as.factor(Month))) +

```

```

geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
labs(subtitle = "Scaled to 5x Standard Deviation, Last 10 Years",
     x = "Year", y = paste0("Values (", unit, ")")) +
ylim(0, y_scale) +
scale_x_continuous(limits = c(max(data$Year) - 10.5, max(data$Year)+0.5),
                   breaks = seq(max(data$Year) - 10, max(data$Year), 2)) +

plot_theme +
theme(legend.position = "none")
leg <- get_legend(p1)
set <- ggarrange(leg, p1 + theme(legend.position = "none"), p2, p3, ncol = 1,
                 heights = c(0.1, 1, 1, 1))

p0 <- ggplot() + labs(title = "Summary Box Plots for Entire Data",
                     subtitle = "By Year & Month") + plot_theme +
  theme(panel.border = element_blank(), panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(), axis.line = element_blank())

YMset <- ggarrange(p0, set, ncol=1, heights = c(0.07, 1))

```

The following box plots are grouped by month with fill color being related to the month. This is designed to view potential seasonal trends.

```

p1 <- ggplot(data = data[data$Include == TRUE, ],
             aes(x = Month, y = ResultValue,
                 group = Month, fill = as.factor(Month))) +
geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
             outlier.color="#333333", outlier.alpha=0.75) +
labs(subtitle = "Autoscale", x = "Month",
     y = paste0("Values (", unit, ")"), fill="Month") +
scale_x_continuous(limits = c(0, 13), breaks = seq(3, 12, 3)) +
plot_theme +
theme(legend.position = "top", legend.box = "horizontal") +
guides(fill = guide_legend(nrow = 1))

p2 <- ggplot(data = data[data$Include == TRUE, ],
             aes(x = Month, y = ResultValue,
                 group = Month, fill = as.factor(Month))) +
geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
             outlier.color="#333333", outlier.alpha=0.75) +
labs(subtitle = "Scaled to 5x Standard Deviation",
     x = "Month", y = paste0("Values (", unit, ")")) +
ylim(0, y_scale) +
scale_x_continuous(limits = c(0, 13), breaks = seq(3, 12, 3)) +
plot_theme +
theme(legend.position = "none")

p3 <- ggplot(data = data[data$Include == TRUE &
                         data$Year >= max(data$Year) - 10, ],
             aes(x = Month, y = ResultValue,
                 group = Month, fill = as.factor(Month))) +
geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
             outlier.color="#333333", outlier.alpha=0.75) +
labs(subtitle = "Scaled to 5x Standard Deviation, Last 10 Years",

```

```

      x = "Month", y = paste0("Values (", unit, ")")) +
ylim(0, y_scale) +
scale_x_continuous(limits = c(0, 13), breaks = seq(3, 12, 3)) +
plot_theme +
theme(legend.position = "none")
leg <- get_legend(p1)
set <- ggarrange(leg, p1 + theme(legend.position = "none"), p2, p3, ncol = 1,
                 heights = c(0.1, 1, 1, 1))




p0 <- ggplot() + labs(title = "Summary Box Plots for Entire Data",
                     subtitle = "By Month") + plot_theme +
  theme(panel.border = element_blank(), panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(), axis.line = element_blank())

Mset <- ggarrange(p0, set, ncol=1, heights = c(0.07, 1))

```


Summary Box Plots for Entire Data


By Year



Summary Box Plots for Entire Data

By Year & Month





Appendix II: Excluded Monitoring Locations

Scatter plots of data values are created for monitoring locations that have fewer than 5 separate years of data entries.

```


Mon_Exclude <- Mon_Summ[Mon_Summ$N_Years<5 & Mon_Summ$N_Years>0,]
Mon_Exclude <- Mon_Exclude[order(Mon_Exclude$MonitoringID),]
z=nrow(Mon_Exclude)

if(z==0){
  print("There are no monitoring locations that qualify.")
} else {
  for(i in 1:z){
    MA_name <- unique(data$ManagedAreaName[
      data$MonitoringID==Mon_Exclude$MonitoringID[i]])
    Mon_name <- paste(unique(data$ProgramID[
      data$MonitoringID==Mon_Exclude$MonitoringID[i]]),
      unique(data$ProgramName[
        data$MonitoringID==Mon_Exclude$MonitoringID[i]]),
      unique(data$ProgramLocationID[
        data$MonitoringID==Mon_Exclude$MonitoringID[i]]),
      sep = " | ")


    p1<-ggplot(data=data[data$MonitoringID==Mon_Exclude$MonitoringID[i]&
      data$Include == TRUE, ],
      aes(x = SampleDate, y = ResultValue)) +
    geom_point(shape=21, size=3, color="#333333", fill="#cccccc",
      alpha=0.75) +
    labs(title=
      paste0("Scatter Plot of Excluded Monitoring Location ",
        MA_name, "\n", Mon_name, "\n(", Mon_Exclude$Y[i],
        " Unique Years)"),
      subtitle="Autoscale", x = "Year",
      y = paste0("Values (", unit, ")")) +
    plot_theme +
    scale_x_date(labels = date_format("%m-%Y"))
    print(p1)
  }
}

```



**Scatter Plot of Excluded Monitoring Location Banana River Aquatic Preserve
5061 | St. Johns River Water Management District Continuous Water Quality Programs | CMMerritt
(Unique Years)**




**Scatter Plot of Excluded Monitoring Location Guana River Marsh Aquatic Preserve
5062 | FDEP Bureau of Survey and Mapping Continuous Water Quality Program | 872-0494
(Unique Years)**




**Scatter Plot of Excluded Monitoring Location Guana Tolomato Matanzas National Estuarine Research Reserve
5062 | FDEP Bureau of Survey and Mapping Continuous Water Quality Program | 872-0494
(Unique Years)**




**Scatter Plot of Excluded Monitoring Location Jensen Beach to Jupiter Inlet Aquatic Preserve
7 | National Water Information System | 02253800
(Unique Years)**




**Scatter Plot of Excluded Monitoring Location Loxahatchee River-Lake Worth Creek Aquatic Preserve
7 | National Water Information System | 265645080055900
(Unique Years)**




**Scatter Plot of Excluded Monitoring Location Loxahatchee River-Lake Worth Creek Aquatic Preserve
7 | National Water Information System | 265656080063500
(Unique Years)**




**Scatter Plot of Excluded Monitoring Location Nassau River-St. Johns River Marshes Aquatic Preserv
7 | National Water Information System | 02231291
(Unique Years)**




**Scatter Plot of Excluded Monitoring Location Nassau River-St. Johns River Marshes Aquatic Preserv
5006 | Northeast Aquatic Preserves Continuous Water Quality Monitoring | NENR
(Unique Years)**



**Scatter Plot of Excluded Monitoring Location Nassau River-St. Johns River Marshes Aquatic Preserve
5061 | St. Johns River Water Management District Continuous Water Quality Programs | NCBARD16
(Unique Years)**



**Scatter Plot of Excluded Monitoring Location Tomoka Marsh Aquatic Preserve
10003 | Tomoka Marsh Aquatic Preserve Continuous Water Quality Monitoring | TMGR
(Unique Years)**



Appendix III: Monitoring Location Trendlines

The plots created in this section are designed to show the general trend of the data. Data is taken and grouped by `MonitoringID`. The trendlines on the plots are created using the Senn slope and intercept from the seasonal Kendall Tau analysis. The scripts that create plots follow this format

1. Use the data set that only has `Use_In_Analysis` of `TRUE` for the desired monitoring location
2. Determine the earliest and latest year of the data to create x-axis scale and intervals
3. Determine the minimum, mean, and standard deviation for the data to be used for y-axis scales
 - Excludes the top 2% of values to reduce the impact of extreme outliers on the y-axis scale
4. Set what values are to be used for the x-axis, y-axis, and the variable that should determine groups for the plots

5. Set the plot type as a point plot with the size of the points
6. Add the linear trend
7. Create the title, x-axis, y-axis, and color fill labels
8. Set the y and x limits
9. Make the axis labels bold
10. Plot the arrangement as a set of panels

```

if(n==0){
  print("There are no monitoring locations that qualify.")
} else {
  for (i in 1:n) {
    plot_data <- data[data$Use_In_Analysis == TRUE &
                      data$MonitoringID == Mon_IDs[i],]

    year_lower <- min(plot_data$Year)
    year_upper <- max(plot_data$Year)
    min_RV <- min(plot_data$ResultValue)
    mn_RV <- mean(plot_data$ResultValue[plot_data$ResultValue <
                                         quantile(plot_data$ResultValue, 0.98)])
    sd_RV <- sd(plot_data$ResultValue[plot_data$ResultValue <
                                       quantile(plot_data$ResultValue, 0.98)])

    x_scale <- ifelse(year_upper - year_lower > 30, 10, 5)
    y_scale <- mn_RV + 4 * sd_RV

    tau <- KT.Stats$tau[KT.Stats$MonitoringID == Mon_IDs[i]]
    s_slope <- KT.Stats$SennSlope[KT.Stats$MonitoringID == Mon_IDs[i]]
    s_int <- KT.Stats$SennIntercept[KT.Stats$MonitoringID == Mon_IDs[i]]
    trend <- KT.Stats$Trend[KT.Stats$MonitoringID == Mon_IDs[i]]
    p <- KT.Stats$p[KT.Stats$MonitoringID == Mon_IDs[i]]

    model <- lm(ResultValue ~ DecDate,
                data = plot_data)
    m_int <- coef(model)[[1]]
    m_slope <- coef(model)[[2]]
    rm(model)
    MA_name <- KT.Stats$ManagedAreaName[KT.Stats$MonitoringID == Mon_IDs[i]]
    Mon_name <- paste(KT.Stats$ProgramID[KT.Stats$MonitoringID == Mon_IDs[i]],
                     KT.Stats$ProgramName[KT.Stats$MonitoringID == Mon_IDs[i]],
                     KT.Stats$ProgramLocationID[KT.Stats$MonitoringID == Mon_IDs[i]],
                     sep = " | ")

    p1 <- ggplot(data = plot_data,
                 aes(x = DecDate, y = ResultValue)) +
      geom_point(shape=21, size=3, color="#333333", fill="#cccccc",
                 alpha=0.75) +
      geom_abline(aes(slope=s_slope, intercept=s_int),
                  color="#000099", size=1.2, alpha=0.7) +
      labs(subtitle = "Autoscale",
           x = "Year", y = paste0("Values (", unit, ")")) +
      plot_theme

    p2 <- ggplot(data = plot_data,
                 aes(x = DecDate, y = ResultValue)) +
      geom_point(shape=21, size=3, color="#333333", fill="#cccccc",
                 alpha=0.75) +

```

```

    geom_abline(aes(slope=s_slope, intercept=s_int),
                color="#000099", size=1.2, alpha=0.7) +
    ylim(min_RV-0.1*y_scale, y_scale) +
    labs(subtitle = "Scaled to 4x Standard Deviation",
         x = "Year", y = paste0("Values (", unit, ")")) +
    plot_theme

KTset <- ggarrange(p1, p2, ncol = 1, heights = c(1, 1))



p0 <- ggplot() + labs(title = paste0("Data Points with Trendlines for ",
                                     MA_name, "\n", Mon_name),
                     subtitle = paste0("Senn Slope = ", s_slope,
                                     "\nTrend = ", trend,
                                     "\nSenn Intercept = ", s_int,
                                     "\nTau = ", tau,
                                     "\nLinear Trendline: ",
                                     "y = ", m_slope, "x + ", m_int)) +
    plot_theme + theme(panel.border = element_blank(),
                      panel.grid.major = element_blank(),
                      panel.grid.minor = element_blank(),
                      axis.line = element_blank())

print(ggarrange(p0, KTset, ncol = 1, heights = c(0.20, 1)))
rm(plot_data)
rm(KTset, leg)
}
}

```



Data Points with Trendlines for Banana River Aquatic Preserve **5061 | St. Johns River Water Management District Continuous Water Quality Programs | IRLB04**

Senn Slope = 0.0376973684210528, Senn Intercept = -45.0288374999992
Trend = 1, tau = 0.0806, p = 0
Linear Trendline: $y = 0.0578602402056631x - 91.7660087935119$



Data Points with Trendlines for Guana River Marsh Aquatic Preserve **Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtn**

Senn Slope = 0.0418560606060603, Senn Intercept = -57.8348721590923
Trend = 1, tau = 0.0941, p = 0
Linear Trendline: $y = 0.0438060946428752x - 64.7846453161156$





Data Points with Trendlines for Guana Tolomato Matanzas National Estuarine Research Reserve **Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr**

Senn Slope = 0.0460227272727274, Senn Intercept = -61.0570572916664

Trend = 1, tau = 0.1097, p = 0

Linear Trendline: $y = 0.0497046652028155x - 77.2276964462051$





Data Points with Trendlines for Guana Tolomato Matanzas National Estuarine Research Reserve **Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr**

Senn Slope = 0.0478125000000002, Senn Intercept = -82.6274662186771



Trend = 1, tau = 0.0793, p = 0

Linear Trendline: $y = 0.0329024710204002x - 42.6710332499687$





Data Points with Trendlines for Guana Tolomato Matanzas National Estuarine Research Reserve Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtn

Senn Slope = 0.04185606060603, Senn Intercept = -57.8348721590923
Trend = 1, tau = 0.0941, p = 0
Linear Trendline: $y = 0.0438060946428752x + -64.7846453161156$




Data Points with Trendlines for Guana Tolomato Matanzas National Estuarine Research Reserve Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtn

Senn Slope = 0.0559027777777779, Senn Intercept = -82.282299536401
Trend = 1, tau = 0.131, p = 0
Linear Trendline: $y = 0.0551500653483625x + -88.1120359769245$




Data Points with Trendlines for Loxahatchee River-Lake Worth Creek Aquatic Preserve 7 | National Water Information System | 265906080093500

Senn Slope = 0.0900000000000002, Senn Intercept = -280.175
Trend = 1, tau = 0.1409, p = 0
Linear Trendline: $y = 0.101827437195152x - 183.988475608106$



Data Points with Trendlines for Pellicer Creek Aquatic Preserve Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtn

Senn Slope = 0.0478125000000002, Senn Intercept = -82.6274662186771
Trend = 1, tau = 0.0793, p = 0
Linear Trendline: $y = 0.0329024710204002x - 42.6710332499687$



Appendix IV: Monitoring Location Summary Box Plots

Data is taken and grouped by `MonitoringID`. The scripts that create plots follow this format

1. Use the data set that only has `Use_In_Analysis` of `TRUE` for the desired monitoring location
2. Determine the earliest and latest year of the data to create x-axis scale and intervals
3. Determine the minimum, mean, and standard deviation for the data to be used for y-axis scales
 - Excludes the top 2% of values to reduce the impact of extreme outliers on the y-axis scale
4. Set what values are to be used for the x-axis, y-axis, and the variable that should determine groups for the box plots
5. Set the plot type as a box plot with the size of the outlier points
6. Create the title, x-axis, y-axis, and color fill labels
7. Set the y and x limits
8. Make the axis labels bold
9. Plot the arrangement as a set of panels

The following plots are arranged by `MonitoringID` with data grouped by `Year`, then `Year` and `Month`, then finally `Month` only. Each program area will have 3 sets of plots, each with 3 panels in them. Each panel goes as follows:

1. Y-axis autoscaled
2. Y-axis set to be mean + 4 times the standard deviation
3. Y-axis set to be mean + 4 times the standard deviation for most recent 10 years of data

```
if(n==0){
  print("There are no monitoring locations that qualify.")
} else {
  for (i in 1:n) {
    year_lower <- min(data$Year[data$Use_In_Analysis == TRUE &
                               data$MonitoringID == Mon_IDs[i]])
    year_upper <- max(data$Year[data$Use_In_Analysis == TRUE &
                               data$MonitoringID == Mon_IDs[i]])
    min_RV <- min(data$ResultValue[data$Use_In_Analysis == TRUE &
                                     data$MonitoringID == Mon_IDs[i]])
    mn_RV <- mean(data$ResultValue[data$Use_In_Analysis == TRUE &
                                     data$MonitoringID == Mon_IDs[i] &
                                     data$ResultValue <
                                     quantile(data$ResultValue, 0.98)])
    sd_RV <- sd(data$ResultValue[data$Use_In_Analysis == TRUE &
                                   data$MonitoringID == Mon_IDs[i] &
                                   data$ResultValue <
                                   quantile(data$ResultValue, 0.98)])
    x_scale <- ifelse(year_upper - year_lower > 30, 10, 5)
    y_scale <- mn_RV + 4 * sd_RV
    MA_name <- KT.Stats$ManagedAreaName[KT.Stats$MonitoringID == Mon_IDs[i]]
    Mon_name <- paste(KT.Stats$ProgramID[KT.Stats$MonitoringID == Mon_IDs[i]],
                      KT.Stats$ProgramName[KT.Stats$MonitoringID == Mon_IDs[i]],
                      KT.Stats$ProgramLocationID[KT.Stats$MonitoringID == Mon_IDs[i]],
                      sep = " | ")

    ##Year plots
    p1 <- ggplot(data = data[data$Use_In_Analysis == TRUE &
```

```

                                data$MonitoringID == Mon_IDs[i], ],
                                aes(x = Year, y = ResultValue, group = Year)) +
geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
              outlier.size=3, outlier.color="#333333",
              outlier.fill="#cccccc", outlier.alpha=0.75) +
labs(subtitle = "Autoscale",
      x = "Year", y = paste0("Values (", unit, ")")) +
scale_x_continuous(limits = c(year_lower - 1, year_upper + 1),
                   breaks = rev(seq(year_upper,
                                     year_lower, -x_scale))) +
plot_theme

p2 <- ggplot(data = data[data$Use_In_Analysis == TRUE &
                          data$MonitoringID == Mon_IDs[i], ],
              aes(x = Year, y = ResultValue, group = Year)) +
geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
              outlier.size=3, outlier.color="#333333",
              outlier.fill="#cccccc", outlier.alpha=0.75) +
labs(subtitle = "Scaled to 4x Standard Deviation",
      x = "Year", y = paste0("Values (", unit, ")")) +
ylim(min_RV, y_scale) +
scale_x_continuous(limits = c(year_lower - 1, year_upper + 1),
                   breaks = rev(seq(year_upper,
                                     year_lower, -x_scale))) +
plot_theme

p3 <- ggplot(data = data[data$Use_In_Analysis == TRUE &
                          data$MonitoringID == Mon_IDs[i] &
                          data$Year>=year_upper-10, ],
              aes(x = Year, y = ResultValue, group = Year)) +
geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
              outlier.size=3, outlier.color="#333333",
              outlier.fill="#cccccc", outlier.alpha=0.75) +
labs(subtitle = "Scaled to 4x Standard Deviation, Last 10 Years",
      x = "Year", y = paste0("Values (", unit, ")")) +
ylim(min_RV, y_scale) +
scale_x_continuous(limits = c(year_upper - 10.5, year_upper + 1),
                   breaks = rev(seq(year_upper, year_upper - 10, -2))) +
plot_theme

Yset <- ggarrange(p1, p2, p3, ncol = 1)

p0 <- ggplot() + labs(title = paste0("Summary Box Plots for ",
                                     MA_name, "\n", Mon_name),
                     subtitle = "By Year") +
plot_theme + theme(panel.border = element_blank(),
                   panel.grid.major = element_blank(),
                   panel.grid.minor = element_blank(),
                   axis.line = element_blank())

## Year & Month Plots
p4 <- ggplot(data = data[data$Use_In_Analysis == TRUE &

```



```

        data$MonitoringID == Mon_IDs[i], ],
        aes(x = YearMonthDec, y = ResultValue,
            group = YearMonth, color = as.factor(Month))) +
    geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
    labs(subtitle = "Autoscale",
        x = "Year", y = paste0("Values (", unit, ")"), color = "Month") +
    scale_x_continuous(limits = c(year_lower - 1, year_upper + 1),
        breaks = rev(seq(year_upper,
            year_lower, -x_scale))) +
    plot_theme +
    theme(legend.position = "none")

p5 <- ggplot(data = data[data$Use_In_Analysis == TRUE &
    data$MonitoringID == Mon_IDs[i], ],
    aes(x = YearMonthDec, y = ResultValue,
        group = YearMonth, color = as.factor(Month))) +
    geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
    labs(subtitle = "Scaled to 4x Standard Deviation",
        x = "Year", y = paste0("Values (", unit, ")"), color = "Month") +
    ylim(min_RV, y_scale) +
    scale_x_continuous(limits = c(year_lower - 1, year_upper + 1),
        breaks = rev(seq(year_upper,
            year_lower, -x_scale))) +
    plot_theme +
    theme(legend.position = "top", legend.box = "horizontal") +
    guides(color = guide_legend(nrow = 1))

p6 <- ggplot(data = data[data$Use_In_Analysis == TRUE &
    data$MonitoringID == Mon_IDs[i], ],
    aes(x = YearMonthDec, y = ResultValue,
        group = YearMonth, color = as.factor(Month))) +
    geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
    labs(subtitle = "Scaled to 4x Standard Deviation, Last 10 Years",
        x = "Year", y = paste0("Values (", unit, ")"), color = "Month") +
    ylim(min_RV, y_scale) +
    scale_x_continuous(limits = c(year_upper - 10.5, year_upper + 1),
        breaks = rev(seq(year_upper, year_upper - 10, -2))) +
    plot_theme +
    theme(legend.position = "none")

leg1 <- get_legend(p5)
YMset <- ggarrange(leg1, p4, p5 + theme(legend.position = "none"), p6,
    ncol = 1, heights = c(0.1, 1, 1, 1))

p00 <- ggplot() + labs(title = paste0("Summary Box Plots for ",
    MA_name, "\n", Mon_name),
    subtitle = "By Year & Month") + plot_theme +
    theme(panel.border = element_blank(),
        panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(), axis.line = element_blank())

## Month Plots
p7 <- ggplot(data = data[data$Use_In_Analysis == TRUE &

```

```

      data$MonitoringID == Mon_IDs[i], ],
      aes(x = Month, y = ResultValue,
          group = Month, fill = as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
              outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle = "Autoscale",
       x = "Month", y = paste0("Values (", unit, ")"), fill = "Month") +
  scale_x_continuous(limits = c(0, 13), breaks = seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position = "none")

p8 <- ggplot(data = data[data$Use_In_Analysis == TRUE &
      data$MonitoringID == Mon_IDs[i], ],
      aes(x = Month, y = ResultValue,
          group = Month, fill = as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
              outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle = "Scaled to 4x Standard Deviation",
       x = "Month", y = paste0("Values (", unit, ")"), fill = "Month") +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits = c(0, 13), breaks = seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position = "top", legend.box = "horizontal") +
  guides(fill = guide_legend(nrow = 1))

p9 <- ggplot(data = data[data$Use_In_Analysis == TRUE &
      data$MonitoringID == Mon_IDs[i] &
      data$Year >= year_upper - 10, ],
      aes(x = Month, y = ResultValue,
          group = Month, fill = as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
              outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle = "Scaled to 4x Standard Deviation, Last 10 Years",
       x = "Month", y = paste0("Values (", unit, ")"), fill = "Month") +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits = c(0, 13), breaks = seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position = "none")

leg2 <- get_legend(p8)
Mset <- ggarrange(leg2, p7, p8 + theme(legend.position = "none"), p9,
                  ncol = 1, heights = c(0.1, 1, 1, 1))

p000 <- ggplot() + labs(title = paste0("Summary Box Plots for ",
                                     MA_name, "\n", Mon_name),
                       subtitle = "By Month") + plot_theme +
  theme(panel.border = element_blank(),
        panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(), axis.line = element_blank())

print(ggarrange(p0, Yset, ncol = 1, heights = c(0.1, 1)))
print(ggarrange(p00, YMset, ncol = 1, heights = c(0.1, 1)))
print(ggarrange(p000, Mset, ncol = 1, heights = c(0.1, 1)))




```

```


rm(plot_data)
rm(p1, p2, p3, p4, p5, p6, p7, p8, p9, p0, p00, p000, leg1, leg2,
  Yset, YMset, Mset)
}
}

```




**Summary Box Plots for Banana River Aquatic Preserve
5061 | St. Johns River Water Management District Continuous Water Quality Programs | IRLB04**
By Year






Summary Box Plots for Banana River Aquatic Preserve
5061 | St. Johns River Water Management District Continuous Water Quality Programs | IRLB04
 By Year & Month




Summary Box Plots for Banana River Aquatic Preserve
5061 | St. Johns River Water Management District Continuous Water Quality Programs | IRLB04
 By Month




Summary Box Plots for Guana River Marsh Aquatic Preserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Year






Summary Box Plots for Guana River Marsh Aquatic Preserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Year & Month




Summary Box Plots for Guana River Marsh Aquatic Preserve Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr By Month




Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Year






Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Year & Month




Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Month




Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtnr
 By Year






Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Year & Month



Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Month




Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Year



Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve

Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr


By Year & Month






Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve

Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr


By Month



Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtn
 By Year




Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtn By Year & Month






Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve

Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtn


By Month






Summary Box Plots for Loxahatchee River-Lake Worth Creek Aquatic Preserve
 7 | National Water Information System | 265906080093500
 By Year






Summary Box Plots for Loxahatchee River-Lake Worth Creek Aquatic Preserve
 7 | National Water Information System | 265906080093500
 By Year & Month




Summary Box Plots for Loxahatchee River-Lake Worth Creek Aquatic Preserve
 7 | National Water Information System | 265906080093500
 By Month



Summary Box Plots for Pellicer Creek Aquatic Preserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtnr
 By Year



Summary Box Plots for Pellicer Creek Aquatic Preserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Year & Month



Summary Box Plots for Pellicer Creek Aquatic Preserve
Guana Tolomato Matanzas National Estuarine Research Reserve System-Wide Monitoring Program | gtr
 By Month

