

```
import cv2
import numpy as np
from google.colab import files
from google.colab.patches import cv2_imshow

# Upload image
uploaded = files.upload()
image_path = list(uploaded.keys())[0]

# Read image
img = cv2.imread(image_path)

# Get image dimensions
rows, cols = img.shape[:2]

# Source points
src_points = np.float32([
    [0, 0],
    [cols - 1, 0],
    [0, rows - 1],
    [cols - 1, rows - 1]
])

# Destination points
dst_points = np.float32([
    [50, 50],
    [cols - 50, 20],
    [20, rows - 50],
    [cols - 80, rows - 20]
])

# Compute homography matrix using DLT method
H, status = cv2.findHomography(src_points, dst_points, cv2.RANSAC)

# Apply transformation
dlt_img = cv2.warpPerspective(img, H, (cols, rows))

# Display images
cv2_imshow(img)
cv2_imshow(dlt_img)

# Save output image
cv2.imwrite("DLT_Transformed_Image.jpg", dlt_img)

print("Output saved as DLT_Transformed_Image.jpg")
```

Choose files img1.jpeg

img1.jpeg(image/jpeg) - 14202 bytes, last modified: 20/07/2026 - 100% done

Saving img1.jpeg to img1 (2).jpeg



Output saved as DLT_Transformed_Image.jpg