

# Package ‘classyfireR’

December 17, 2020

**Type** Package

**Title** R Interface to the ClassyFire RESTful API

**Version** 0.3.6

**Date** 2020-12-16

**Description** Access to the ClassyFire RESTful API <<http://classyfire.wishartlab.com>>. Retrieve existing entity classifications and submit new entities for classification.

**Depends** magrittr

**Imports** httr,  
jsonlite,  
tibble,  
crayon,  
clisymbols,  
cli,  
purrr,  
dplyr,  
stringr,  
methods,  
rjson,  
tidyjson,  
tidyr

**Suggests** testthat,  
covr,  
knitr,  
rmarkdown

**License** GPL (>= 3)

**Encoding** UTF-8

**LazyData** true

**URL** <https://github.com/aberHRML/classyfireR>

**BugReports** <https://github.com/aberHRML/classyfireR/issues>

**RoxygenNote** 7.1.0

**Roxygen** list(markdown = TRUE)

**Collate** 'allGenerics.R'  
          'allClasses.R'  
          'accessor-methods.R'  
          'get\_classification.R'  
          'internals.R'  
          'query.R'  
          'show-method.R'  
          'zzz.R'

**VignetteBuilder** knitr

**R topics documented:**

alternative_parents . . . . .	2
chebi . . . . .	3
classification . . . . .	3
ClassyFire-class . . . . .	4
description . . . . .	4
descriptors . . . . .	5
direct_parent . . . . .	5
get_classification . . . . .	6
get_query . . . . .	6
meta . . . . .	7
Query-class . . . . .	7
show,ClassyFire-method . . . . .	8
submit_query . . . . .	8

<b>Index</b>	<b>10</b>
--------------	-----------

---

alternative_parents	<i>alternative_parents</i>
---------------------	----------------------------

---

**Description**

Get the alternative\_parents  
Get the alternative\_parents

**Usage**

alternative\_parents(object)  
  
## S4 method for signature 'ClassyFire'  
alternative\_parents(object)  
  
## S4 method for signature 'Query'  
alternative\_parents(object)

**Arguments**

object            a Query S4 object

---

chebi

*chebi*

---

**Description**

Get the predicted ChEBI identifications

Get the predicted ChEBI identifications

**Usage**

```
chebi(object)
```

```
## S4 method for signature 'ClassyFire'
```

```
chebi(object)
```

```
## S4 method for signature 'Query'
```

```
chebi(object)
```

**Arguments**

object            a Query S4 object

---

classification

*Accessor Methods for the ClassyFire S4 class*

---

**Description**

Get the ClassyFire classification results

Get the ClassyFire classification results

**Usage**

```
classification(object)
```

```
## S4 method for signature 'ClassyFire'
```

```
classification(object)
```

```
## S4 method for signature 'Query'
```

```
classification(object)
```

**Arguments**

object            a Query S4 object

---

ClassyFire-class	<i>ClassyFire Class</i>
------------------	-------------------------

---

**Description**

A S4 class to store the results from the ClassyFire RESTful API

**Slots**

meta a list of the input SMILE, InChI Key and classification version used  
classification a tibble of the ClassyFire classification results  
direct\_parent a list of the direct parent  
alternative\_parents a tibble of alternative parents  
predicted\_chebi a character vector of the predicted ChEBI terms  
external\_descriptors a tibble of any external identificatons  
description a character string of the compound description

---

description	<i>description</i>
-------------	--------------------

---

**Description**

Get the ClassyFire description

Get the ClassyFire description

**Usage**

```
description(object)
```

```
## S4 method for signature 'ClassyFire'  
description(object)
```

```
## S4 method for signature 'Query'  
description(object)
```

**Arguments**

object a Query S4 object

---

descriptors	<i>descriptors</i>
-------------	--------------------

---

**Description**

Get the external descriptors  
Get the external descriptors

**Usage**

```
descriptors(object)  
  
## S4 method for signature 'ClassyFire'  
descriptors(object)  
  
## S4 method for signature 'Query'  
descriptors(object)
```

**Arguments**

object            a Query S4 object

---

direct_parent	<i>direct_parent</i>
---------------	----------------------

---

**Description**

Get the direct\_parent  
Get the direct\_parent

**Usage**

```
direct_parent(object)  
  
## S4 method for signature 'ClassyFire'  
direct_parent(object)  
  
## S4 method for signature 'Query'  
direct_parent(object)
```

**Arguments**

object            a Query S4 object

---

get_classification	<i>Get Entity Classification</i>
--------------------	----------------------------------

---

**Description**

Retrieve entity classification from 'http://classyfire.wishartlab.com/entities/'

**Usage**

```
get_classification(inchi_key)
```

**Arguments**

inchi\_key          a character string of a valid InChIKey

**Value**

a ClassyFire S4 object.

**See Also**

ClassyFire-class

**Examples**

```
## Not run:

# Valid InChI key where all four classification levels are available
get_classification('BRMWTNUJHUMWMS-LURJTMIESA-N')

# Valid InChI key where only three classification levels are available
get_classification('MDHYEMXUFSJLGV-UHFFFAOYSA-N')

# Invalid InChI key
get_classification('MDHYEMXUFSJLGV-UHFFFAOYSA-B')

## End(Not run)
```

---

get_query	<i>Retrieves the classification results for a given query.</i>
-----------	--

---

**Description**

Retrieves the classification results for a given query.

**Usage**

```
get_query(query_id, format = c("json", "sdf", "csv"))
```

**Arguments**

query\_id            query\_id a numeric value for the ID of the query.  
format             a string of the format of the query (either JSON, CSV, or SDF)

**Value**

the parsed text output displaying the classification results for

---

meta	<i>meta</i>
------	-------------

---

**Description**

Get the ClassyFire meta data  
Get the ClassyFire meta data

**Usage**

```
meta(object)  
  
## S4 method for signature 'ClassyFire'  
meta(object)  
  
## S4 method for signature 'Query'  
meta(object)
```

**Arguments**

object            a Query S4 object

---

Query-class	<i>ClassyFire Query Class</i>
-------------	-------------------------------

---

**Description**

A S4 class to store the results from the ClassyFire RESTful API Queries

**Slots**

meta   a list of the input SMILE, InChI Key and classification version used  
classification   a list of tibbles of the ClassyFire classification results  
direct\_parent   a list of tibbles the direct parent  
alternative\_parents   a list of tibbles of alternative parents  
predicted\_chebi   a list of character vectors of the predicted ChEBI terms  
external\_descriptors   a list of tibbles of any external identifications  
description   a character string of the compound description

---

show,ClassyFire-method	
	<i>show-ClassyFire</i>

---

### Description

show-ClassyFire  
show-Query

### Usage

```
## S4 method for signature 'ClassyFire'  
show(object)  
  
## S4 method for signature 'Query'  
show(object)
```

### Arguments

object	a Query S4 object
--------	-------------------

---

submit_query	<i>Submits a ClassyFire query in a JSON format.</i>
--------------	---

---

### Description

Submits a ClassyFire query in a JSON format.

### Usage

```
submit_query(label, input, type = "STRUCTURE")
```

### Arguments

label	a string the label of the query.
input	a named list or vector of SMILES strings.
type	a string the type of the query.

### Value

A list of tibbles named by input name.



**Examples**

```
## Not run:
input <- c(MOL1 = 'CCCOCC', MOL2 = 'COCC=CCC')
submit_query(label = 'query_test', input = input, type = 'STRUCTURE')

## End(Not run)
```

# Index

alternative\_parents, [2](#)  
alternative\_parents, ClassyFire-method  
    (alternative\_parents), [2](#)  
alternative\_parents, Query-method  
    (alternative\_parents), [2](#)  
  
chebi, [3](#)  
chebi, ClassyFire-method (chebi), [3](#)  
chebi, Query-method (chebi), [3](#)  
classification, [3](#)  
classification, ClassyFire-method  
    (classification), [3](#)  
classification, Query-method  
    (classification), [3](#)  
ClassyFire-class, [4](#)  
  
description, [4](#)  
description, ClassyFire-method  
    (description), [4](#)  
description, Query-method (description),  
    [4](#)  
descriptors, [5](#)  
descriptors, ClassyFire-method  
    (descriptors), [5](#)  
descriptors, Query-method (descriptors),  
    [5](#)  
direct\_parent, [5](#)  
direct\_parent, ClassyFire-method  
    (direct\_parent), [5](#)  
direct\_parent, Query-method  
    (direct\_parent), [5](#)  
  
get\_classification, [6](#)  
get\_query, [6](#)  
  
meta, [7](#)  
meta, ClassyFire-method (meta), [7](#)  
meta, Query-method (meta), [7](#)  
  
Query-class, [7](#)  
  
show, ClassyFire-method, [8](#)  
show, Query-method  
    (show, ClassyFire-method), [8](#)  
submit\_query, [8](#)