

МИНИСТЕРСТВО ОБРАЗОВАНИЯ РЕСПУБЛИКИ БЕЛАРУСЬ
УЧРЕЖДЕНИЕ ОБРАЗОВАНИЯ
“БРЕСТСКИЙ ГОСУДАРСТВЕННЫЙ ТЕХНИЧЕСКИЙ УНИВЕРСИТЕТ”
КАФЕДРА ИНТЕЛЛЕКТУАЛЬНЫХ ИНФОРМАЦИОННЫХ ТЕХНОЛОГИЙ

ОТЧЁТ
по лабораторной работе №5

Выполнил студент
3 курса группы
ПО-9
Аксютин Демьян Александрович

Проверил:
Крощенко А. А.

Брест 2024

Цель работы: приобрести практические навыки в области объектноориентированного проектирования.

Вариант 4

Задание 1: реализовать абстрактные классы или интерфейсы, а также наследование и полиморфизм для следующих классов:

interface Учебное Заведение ← class Колледж

↑
class Университет

Код программы:

```
public interface EducationalInstitution {
    String getAddress();        void
    conductAdmissions();        void
    conductGraduation();
}

public class College implements EducationalInstitution {
    private String address;      private String name;

    public College(String name, String address){
        this.name = name;        this.address =
        address;
    }

    @Override
    public String getAddress() {
        return address;
    }

    @Override
    public void conductAdmissions() {
        System.out.println("Conduct admissions in college - "
            + name + " by the address " + address);
    }

    @Override
    public void conductGraduation() {
        System.out.println("Conduct graduation in college - "
            + name + " by the address " + address);
    }
}

public class University implements EducationalInstitution{
    private String address;      private String name;

    public University(String name, String address){
        this.name = name;        this.address = address;
    }

    @Override
```

```

    public String getAddress() {
return address;
    }

    @Override
    public void conductAdmissions() {
        System.out.println("Conduct admissions in university - "
            + name + " by the address " + address);
    }

    @Override
    public void conductGraduation() {
        System.out.println("Conduct graduation in university - "
            + name + " by the address " + address);
    }
}

```

Входные данные:

```

public class EducationalInstitutionTest {
public static void main(String[] args) {
    List<EducationalInstitution> educationalInstitutions = new ArrayList<>();
    educationalInstitutions.add(new College("MuchosranksiyColledg",
        "Muchosranks, yl. Pushkina, dom Kolatychkina "));
    educationalInstitutions.add(new University("KrutoiUniversitet",
        "Paris, pod EefelevoiBachnei"));

    for (EducationalInstitution educationalInstitution : educationalInstitutions){
        educationalInstitution.conductAdmissions();
    }
}
}

```

Результат работы программы:

```

D:\SDK\JDK\bin\java.exe "-javaagent:D:\JetBrains\IntelliJ IDEA 2023.3.4\lib\idea_rt.jar=51548:D:\JetBrains\Inte
Conduct admissions in college - MuchosranksiyColledg by the address Muchosranks, yl. Pushkina, dom Kolatychkina
Conduct admissions in university - KrutoiUniversitet by the address Paris, pod EefelevoiBachnei

```

Задание 2: требуется создать суперкласс (абстрактный класс, интерфейс) и определить общие методы для данного класса. Создать подклассы, в которых добавить специфические свойства и методы. Часть методов переопределить. Создать массив объектов суперкласса и заполнить объектами подклассов. Объекты подклассов идентифицировать конструктором по имени или идентификационному номеру. Использовать объекты подклассов для моделирования реальных ситуаций и объектов. Создать суперкласс Грузоперевозчик и подклассы Самолет, Поезд, Автомобиль. Определить время и стоимость перевозки для указанных городов и расстояний.

Код программы:

```

public class Position {
private float xPosition;
private float yPosition;

    Position(float xPosition, float yPosition){
this.xPosition = xPosition;        this.yPosition
= yPosition;
}
}

```

```

    }
    public static double getDistanceBetweenPositions(Position loc1, Position loc2){
        return Math.sqrt(Math.pow(loc1.xPosition - loc2.xPosition, 2) +
                           Math.pow(loc1.yPosition - loc2.yPosition, 2));
    }
    ...
}

public interface Positionable
{
    Position getPosition();
    void setPosition(Position position);
}

public class City implements Positionable {
    private Position position;    private
    String name;

    public City(String name, Position position){
        this.name = name;        this.position =
        position;
    }
    @Override
    public Position getPosition() {
        return position;
    }
    @Override
    public void setPosition(Position position) {
        this.position = position;
    }
    ...
}

public abstract class CargoCarrier implements Positionable {
    private static int nextPersonId = 1;    private String
    name;    private final int id;
    private Position currentPosition = new Position(0, 0);

    public CargoCarrier(String name){
        this.name = name;        id =
        nextPersonId++;
    }
    @Override
    public Position getPosition(){
        return currentPosition;
    }
    @Override
    public void setPosition(Position position){
        currentPosition = position;
    }
    public abstract double getTransportationTime(Positionable positionable);
    public abstract double getTransportationCost(Positionable positionable);
    ...
}

public class Car extends CargoCarrier {
    private double speed;    private
    double costPerKm;

```

```

        public Car(String name, double speed, double costPerKm) {
            super(name);
            this.speed = speed;
            this.costPerKm = costPerKm;
        }
        @Override
        public double getTransportationTime(Positionable positionable) {
            return Position.getDistanceBetweenPositions(positionable.getPosition(),
                this.getPosition()) / speed;
        }
        @Override
        public double getTransportationCost(Positionable positionable) {
            return Position.getDistanceBetweenPositions(positionable.getPosition(),
                this.getPosition()) * costPerKm;
        }
    }
}
...

```

Входные данные:

```

public class CargoCarrierTest {
    public static void main(String[] args) {
        ArrayList<CargoCarrier> cargoCarriers = new ArrayList<>();

        cargoCarriers.add(new Car("KrasivayaMachina", 50, 5));
        cargoCarriers.add(new Train("BistriyPoesd", 100, 1));
        cargoCarriers.add(new Plane("MedleniySamolët", 500, 10));
        City cityBrest = new City("Brest", new Position(500, 0));
        System.out.println(cityBrest.getName() + " " + cityBrest.getPosition() + ":");
        for (CargoCarrier cargoCarrier : cargoCarriers) {
            System.out.println("\t" + cargoCarrier.getName() + " "
                + cargoCarrier.getPosition() + ":");
            System.out.println("\t\t transportation time: "
                + cargoCarrier.getTransportationTime(cityBrest));
            System.out.println("\t\t transportation cost: "
                + cargoCarrier.getTransportationCost(cityBrest));
        }
    }
}

```

Результат работы программы:

```

D:\SDK\JDK\bin\java.exe "-javaagent:D:\JetBrains\Intel
Brest {xPosition= 500.0, yPosition= 0.0}:
    KrasivayaMachina {xPosition= 0.0, yPosition= 0.0}:
        transportation time: 10.0
        transportation cost: 2500.0
    BistriyPoesd {xPosition= 0.0, yPosition= 0.0}:
        transportation time: 5.0
        transportation cost: 500.0
    MedleniySamolët {xPosition= 0.0, yPosition= 0.0}:
        transportation time: 1.0
        transportation cost: 5000.0

```

Задание 3: В задании 3 ЛР №4, где возможно, заменить объявления суперклассов объявлениями абстрактных классов или интерфейсов.

Код программы:

```
abstract public class Person {
    private String name;        private
    final int id;
        private static int nextPersonId = 1;
        public Person(String
name){        this.name =
name;        id =
nextPersonId++;
    }
} public class Enrollee extends
Person{        public Enrollee(String
name) {        super(name);
    }
} public class Teacher extends
Person{        public Teacher(String
name) {        super(name);
    }
        public int getMark(){
            return (int) (Math.random() * 100);
        }
} public class Faculty
{        private String
name;
        private List<Subject> requiredExams = new ArrayList<>();
private List<EnrolleeData> registeredEnrolles = new ArrayList<>();
private List<EnrolleeData> evolvedEnrolles = new ArrayList<>();
        public static class EnrolleeData
{
            private Enrollee enrollee;
            private Map<Subject, Integer> examMarks = new HashMap<>();
            EnrolleeData(Enrollee enrollee){
this.enrollee = enrollee;
            }
            public void setExamMark(Subject subject, int mark){
if (!examMarks.containsKey(subject))
examMarks.put(subject, mark);
            }
            public int getExamScore(){
int examScore = 0;
            for (int examMark : examMarks.values()){
examScore += examMark;
            }
            return examScore / examMarks.size();
        }
    }
}

Faculty(String name, List<Subject> requiredExams){
this.name = name;
        this.requiredExams.addAll(requiredExams.stream().distinct().toList());
    }        public Faculty registerEnrollee(Enrollee
enrollee){        if
(!registeredEnrolles.contains(enrollee)){
```

```

        EnrolleeData enrolleeData = new EnrolleeData(enrollee);
registeredEnrolles.add(enrolleeData);
    }
    return this;
}

public Faculty conductExam(Subject subject, Teacher teacher){
if (requiredExams.contains(subject))
    for (EnrolleeData enrolleeData : registeredEnrolles)
if (!enrolleeData.havePassedExam(subject))
    enrolleeData.setExamMark(subject, teacher.getMark());
return this;
}
    public void evolveFromEnrolleeToStudent(int passingScore){
for (int i = 0; i < registeredEnrolles.size(); i++) {
EnrolleeData enrolleeData = registeredEnrolles.get(i);
    if
(enrolleeData.getExamMarks().size() == requiredExams.size()
&& enrolleeData.getExamScore() >= passingScore){
registeredEnrolles.remove(i--);
evolvedEnrolles.add(enrolleeData);
    }
}
}
}
}

```

Входные данные:

```

public static void main(String[] args) {
String facultyName = "CreativnoyeImya";
    List<Subject> requiredExams = new ArrayList<>(List.of(Subject.HISTORY,
Subject.MATHEMATICS));
    Faculty faculty = new Faculty(facultyName, requiredExams);
    faculty.registerEnrollee(new Enrollee("Petya"));
    faculty.registerEnrollee(new Enrollee("Kirill"));
    Teacher teacher = new Teacher("Prepodavatel");

    faculty.conductExam(Subject.HISTORY, teacher)
    faculty.conductExam(Subject.MATHEMATICS, teacher);
    System.out.println("All enrolles:");
    for (Faculty.EnrolleeData enrolleeData : faculty.getRegisteredEnrolles()) {
        System.out.println(enrolleeData);
    }
    faculty.evolveFromEnrolleeToStudent(70);

    System.out.println("\nEnrolled people:");
    for (Faculty.EnrolleeData enrolleeData : faculty.getEvolvedEnrolles()) {
        System.out.println(enrolleeData);
    }
}
}

```

Результат работы программы:

```
D:\SDK\JDK\bin\java.exe "-javaagent
```

```
All enrolles:
```

```
enrollee:
```

```
    id=1
```

```
    name='Petya'
```

```
    exams:
```

```
        история - 59
```

```
        математика - 5
```

```
enrollee:
```

```
    id=2
```

```
    name='Kirill'
```

```
    exams:
```

```
        история - 60
```

```
        математика - 82
```

```
Enrolled people:
```

```
enrollee:
```

```
    id=2
```

```
    name='Kirill'
```

```
    exams:
```

```
        история - 60
```

```
        математика - 82
```

```
Process finished with exit code 0
```

Вывод: я приобрёл практические навыки в области объектно-ориентированного проектирования.