

# **Assignment 1:**

# Memory-based CF for Rating Prediction

### **Overview**

- Programming
  - UCF or ICF for rating prediction
- Requirements
  - Project report
  - Executable source code
  - Prediction results

## **Project Report**

- Main content
  - Detailed implementation introduction
  - Key code explanation
  - Result analysis
    - Hyper-parameter influence
      - Table or plot
  - How to run your code
    - Environments (E.g., python 2.X or python 3.x, c++?)
    - Dependency libraries

## **Source Code**

- Programming language
  - Python is preferred.
- Terminal command
  - E.g., python2.7 xxx.py test.file output.file
- Source code files
  - How the method is implemented

### **Data Format**

- Train set
  - With rating scores

```
train.csv x

user_id,business_id,date,stars

A2JGzkvNjckSmps_4FbKWw,Xg5qEQiB-7L6kGJ5F4K3bQ,2014-03-18 01:14:10,5.0

rypcWiSNGM0suWsiSLh9xA,4RoTEeqB_MNn6yaqZmlZHg,2015-08-29 18:32:15,4.0

Dgk0Wdoh7HPjhKQEPBU_jQ,ZOmf-3NN4Z59b2Fw6VAM7g,2015-09-14 16:33:03,3.0

FIk4lQQu1eTe2EpzQ4xhBA,HK2Ki-PvnNN-YMTlX1uSVA,2012-09-29 02:03:42,4.0

VizhcyMWWPz3UDXEBeix4w,UPIYuRaZvknINOd1w8kqRQ,2011-06-10 20:35:42,3.0

ZEuPAGalYnP7eSxPgFCNDg,E83nSU_y9zedOzQnkTjV1g,2017-08-14 18:56:00,2.0

WXlxViTwXHPBvhioljN9PQ,IRzY7yoBqoHaZNNo8WiWQQ,2016-04-30 14:42:50,4.0

cMEtAiW60I5wE_vLfTxoJQ,DESv2ys6SjBKA4SyDtJvxw,2012-06-26 00:44:03,4.0
```

- Test set
  - Without rating scores

```
test.csv x

user_id,business_id,date

PfpRvMAESbC2bC8FUIMdNg,Kbbm6Vd5UdbP10dwjBghRw,2018/10/15 0:52

oaaEXgQ3x51cXE3GTXrT1Q,2GmGT-7QjowR1ihup3FbVA,2011/11/27 9:12

yT_QCcnq-QGipWWuzIpvtw,p0EL97ld-FJMK08Ki8JmYg,2016/3/11 19:09

fRVNHAl2RjosC67Y67G3cA,UkWme3kwg6L9rd4tCNB15w,2016/9/11 15:53

48vRThjhuhiSQINQ2KV8Sw,LNGBEEelQx4zbfWnlc66cw,2011/3/23 3:22

q5FQmuXxzPEsvEtA_Mvd1w,fSBhe0A6Dfa8JCYccfpMog,2013/8/9 22:06

W0VE9M7Dikrpol8j1_QqyQ,3oTVApC-eUzpGjr0VxIr5g,2017/9/7 2:27

avmRUkWovTsaDqKiNKdivQ,wUKzaS1MHg94RGM6z8u9mw,2012/10/25 19:31
```

### **Prediction Results**

- A file containing prediction results
  - Format: each line corresponds to one prediction tuple
    - User\_id, Business\_id, Rating\_score
    - E.g., A2JGzkvNjckSmps\_4FbKWw, Xg5qEQiB-7L6kGJ5F4K3bQ, 4.0

## **Submission**

- File name
  - zip file, named with 'Name+ID+Assignment No.'
- Submission URL
  - http://xzc.cn/Ne34O6sqWw



### How to evaluate?

- Code
  - Executable
  - Clear, easy-to-understood
- Prediction results
  - Effectiveness
    - How is the predicted score compared with ground-truth?
    - RMSE
- Report
  - Integrity
  - Readability
  - Highlights

## **Report Example**

#### 数据挖掘第一次编程作业

#### ——实现数据挖掘 Apriori 算法

2018年3月26日

#### 目录

| 1 | 升本     |   | • |
|---|--------|---|---|
|   | 1.1    | 简介  |   |
|   | 1.2    | 伪代码描述   |   |
|   | 1.3    | 实现过程描述  |   |
|   | 1.0    | 24-74-45-18-18-45-18-18-18-18-18-18-18-18-18-18-18-18-18- |   |
| 2 | 核心     | 代码注解  | : |
|   | 2.1    | 1-项集的产生   |   |
|   |        | 计时  |   |
|   |        |   |   |
|   | 2.3    | Apriori_gen 12/15   | 4 |
| 3 | 3 结果分析 |   |   |
|   | 3.1    | 频繁集发摇   |   |
|   | 3.2    | <b>美藤規則发掘</b>   |   |
|   | 0.2    | 大联郑州及纳  | • |
| 4 | 代码运行   |   |   |
|   |        | 环境  | į |
|   | 4.2    | 依赖  |   |
|   |        |   |   |
|   |        | 命令行命令   |   |
|   | 4.4    | Apriori.py  |   |
|   | 4.5    | asso_gen.py   |   |
| 5 | 48 -   | ケルカキ  |   |
| ð |        | 文件列表  | 1 |
|   | 5.1    | Apriori.py  |   |
|   | 5.2    | asso_gen.py   |   |
|   | 5.3    | out 目录  | 1 |
|   |        | 5.3.1 频繁集文件 out.dat                                       | 1 |
|   |        | 5.3.2 关联规则文件 association_rules.dat                        | 1 |
|   |        | 5.3.3 关联规则二进制中间文件 fdict.pkl                               |   |
|   |        |   |   |

#### 2 核心代码注解

以上的 Apriori 算法过程易于理解,但是实现时还是存在一些 python 语言层面的问题,比如,数据结构的选择,以及相应的操作选择。故以下对核心代码做必要说明,余下部分不做过多赘述。

#### 2.1 1-项集的产生

对于算法中项集 -频数形式的 k-v 对, 在 python 中采用 dict 存储, 但是 dict 中 key 值不能为 set 和 list 等无法哈希的数据类型, 放此处采用 forzenset 这一类似的集合结构。

```
i Gtimer
z def generate_l_items_dict(translit):
    """ insert and count 1-items occurrences in a hash tree """
4    11 = {}
    for trans in translit:
        for item in trans.
```

#### 不同支持度下各项集元素个数




图 2: 不同支持度下各项集元素个数变化。随着最小支持度的变大,各项集元素个数也总体下降。而当最小支持度较小时,项集元素个数会非常大,例如上图中最高点达到近 3500 项。


### **Data and Deadline**


### Kaggle url


https://www.kaggle.com/t/450e7cd913014ec28a26199 5d8c7b3d9

### Deadline

- 24:00, 2022-4-3
- Submission files after that time might be penalized







#### 数据集介绍

本次作业的数据集共分为三个文件,train.csv、test.csv和sample.csv。

数据集截取自推荐系统著名的公开数据集Amazon Dataset。如果有同学有兴趣作进一步探索可以参考here

#### **Files**

- train.csv the training set, 即训练集
- test.csv the test set, 即测试集
- sample\_submission.csv 你的提交样例,共两列数据: idx和overall。

#### Columns

- reviewerID 用户的id。
- asin 物品id。

