

Simplicial surfaces in GAP

Markus Baumeister

?? .08.2017

- 1 General polygonal complexes by incidence geometry
- 2 Edge colouring and group properties
- 3 Abstract folding

- 1 General polygonal complexes by incidence geometry
- 2 Edge colouring and group properties
- 3 Abstract folding

Motivation

Goal: simplicial surfaces (and generalisations) in GAP



⇝ examples of **polygonal complexes**

No embedding

We do not work with embeddings (mostly)

- is very hard to compute
- if often unknown for an abstractly constructed surface
- is different from *intrinsic structure*

⇒ lengths and angles are not important

↪ incidence structure is intrinsic




Incidence structure

- set of vertices \mathcal{V}

- set of edges \mathcal{E}

- set of faces \mathcal{F}

- transitive relation $\subseteq (\mathcal{V} \times \mathcal{E}) \uplus (\mathcal{V} \times \mathcal{F}) \uplus (\mathcal{E} \times \mathcal{F})$



Polygonal complexes

A **polygonal complex** is a two-dimensional incidence structure of vertices, edges and faces, such that:

① Every edge has exactly two vertices.



② Every face is a polygon.



③ Every vertex lies in an edge

④ Every edge lies in a face

Isomorphism testing

Incidence geometry allows "easy" isomorphism testing. Incidence structure can be interpreted as a coloured graph:



↪ reduce to graph isomorphism problem


Solved by NautyTracesInterface (by Gutsche, Niemeyer, Schweitzer)

General properties

Some properties can be computed for all polygonal complexes:

- Connectivity
- Euler–Characteristic

Orientability is **not** one of them. Counterexample:



⇒ every edge lies in at most two faces (for well-definedness)

⇔ **ramified polygonal surfaces**

- 1 General polygonal complexes by incidence geometry
- 2 Edge colouring and group properties
- 3 Abstract folding

- 1 General polygonal complexes by incidence geometry
- 2 Edge colouring and group properties
- 3 Abstract folding