

3D Printer Based Open Source Calibration Platform for Whisker Sensors

Liyou Zhou Omar Ali Soumo Emmanuel Arnaud
Eden Attenborough Jacob Swindell George Davies Charles Fox

Department of Computer Science, University of Lincoln

Introduction

- Whisker sensors are a type of tactile sensor increasingly used in robotics. [1]–[3]
- Calibration of sensors remains a cost prohibitive and time-consuming process. [1], [4], [5]
- We present a low-cost open-source calibration and testing platform for whisker sensors based on an off-the-shelf 3D printer

Hardware Components

- 3D Printer** A Prusa i3 (MK2) [6].
- Whisker Sensor Mount** secures the whisker onto the printer bed.
- Whisker Sensor** is of a similar design to [7].
- End Effector** a metal ruler.




Figure 1. Calibration Platform Overview

Software Components

- Printer Driver** Interface with 3D printer via GCode [8].
- Sensor Driver** Read whisker sensor via serial at 800 Hz.
- ROS integration** Publishes sensor data to ROS topics and controls the printer via a service interface. Uses foxglove for visualization and rosbag for data acquisition.




Figure 2. Live visualization of the sensor system via Foxglove

Open Source

All project artefacts are available at <https://github.com/FoR-Group1/OpenWhisker>. Would you like to know more? Do you have something we can collaborate on? Scan the QR code below.



SCAN ME

Calibration Results

Printer head is driven to make contact with the whisker sensor at a series of radial distances. Sensor data is recorded along with 3D locations of the printer head.




Figure 3. Raw Magnetometer (left) and 3D Printer Data (right) from 3 consecutive Calibration Routines

Taking the second derivative of the sensor data, a correlation between contact location and sensor reading can be regressed using a polynomial model.




Figure 4. Polynomial Regression of the relationship between 120th sample of y in each episode and the radial contact distance x

If a contact is made within 70mm from the tip of the whisker, the contact location can be accurately inferred to within 2mm by the model.

References

- [1] S. Fotouhi, S. Khayat-zadeh, W. X. Pui, M. Damghani, M. Bodaghi, and M. Fotouhi, "Detection of Barely Visible Impact Damage in Polymeric Laminated Composites Using a Biomimetic Tactile Whisker," *Polymers*, vol. 13, no. 20, p. 3587, Oct. 2021, ISSN: 2073-4360. DOI: 10.3390/polym13203587. (visited on 10/09/2023).
- [2] O. Struckmeier, K. Tiwari, M. Salman, M. J. Pearson, and V. Kyrki, "ViTa-SLAM: A Bio-inspired Visuo-Tactile SLAM for Navigation while Interacting with Aliased Environments," *2019 IEEE International Conference on Cyborg and Bionic Systems (CBS)*, pp. 97–103, Sep. 2019. DOI: 10.1109/CBS46900.2019.9114526. (visited on 10/10/2023).
- [3] C. Fox, M. Evans, M. Pearson, and T. Prescott, "Tactile SLAM with a biomimetic whiskered robot," *2012 IEEE International Conference on Robotics and Automation*, pp. 4925–4930, May 2012. DOI: 10.1109/ICRA.2012.6224813. (visited on 10/09/2023).
- [4] J. C. Sullivan, B. Mitchinson, M. J. Pearson, et al., "Tactile Discrimination Using Active Whisker Sensors," *IEEE Sensors Journal*, vol. 12, no. 2, pp. 350–362, Feb. 2012, ISSN: 1558-1748. DOI: 10.1109/JSEN.2011.2148114. (visited on 04/25/2024).
- [5] M. Evans, C. W. Fox, M. J. Pearson, N. F. Lepora, and T. J. Prescott, "Whisker-object contact speed affects radial distance estimation," in *2010 IEEE International Conference on Robotics and Biomimetics*, Dec. 2010, pp. 720–725. DOI: 10.1109/ROBIO.2010.5723415. (visited on 01/13/2024).
- [6] *Original Prusa i3 MK3S+ | Original Prusa 3D printers directly from Josef Prusa*, <https://www.prusa3d.com/category/original-prusa-i3-mk3s/>. (visited on 03/12/2024).
- [7] R. Stevenson, D. Paparas, O. Faris, et al., "Open source hardware whisker sensor," in *TAROS*, 2024.
- [8] T. R. Kramer, F. M. Proctor, and E. R. Messina, "The NIST RS274NGC Interpreter - Version 3," *NIST*, Aug. 2000. (visited on 04/20/2024).