Study Guide: Introduction to Finite Element Methods

Hans Petter Langtangen 1,2

 $^1{\rm Center}$ for Biomedical Computing, Simula Research Laboratory $^2{\rm Department}$ of Informatics, University of Oslo

Oct 28, 2013

Contents

0.1	Why fi	inite elements?
	0.1.1	Domain for flow around a dolphin
	0.1.2	The flow
	0.1.3	Basic ingredients of the finite element method
	0.1.4	Our learning strategy
0.2	Approx	ximation in vector spaces
	0.2.1	Approximation set-up
	0.2.2	How to determine the coefficients?
	0.2.3	Approximation of planar vectors; problem
	0.2.4	Approximation of planar vectors; vector space terminology 8
	0.2.5	The least squares method; principle
	0.2.6	The least squares method; calculations
	0.2.7	The projection (or Galerkin) method
	0.2.8	Approximation of general vectors
	0.2.9	The least squares method
	0.2.10	The projection (or Galerkin) method
0.3	Approx	ximation of functions
	0.3.1	The least squares method
	0.3.2	The projection (or Galerkin) method
	0.3.3	Example: linear approximation; problem
	0.3.4	Example: linear approximation; solution
	0.3.5	Example: linear approximation; plot
	0.3.6	Implementation of the least squares method; ideas
	0.3.7	Implementation of the least squares method; symbolic code
	0.3.8	Implementation of the least squares method; numerical code
	0.3.9	Implementation of the least squares method; plotting
	0.3.10	Implementation of the least squares method; application
	0.3.11	Perfect approximation; parabola approximating parabola
		Perfect approximation; the general result
	0.3.13	Perfect approximation; proof of the general result
	0.3.14	Finite-precision/numerical computations
		Ill-conditioning (1)
	0.3.16	Ill-conditioning (2)
		Fourier series approximation; problem and code
	0.3.18	Fourier series approximation; plot
		Fourier series approximation; improvements
		Fourier series approximation; final results
		Orthogonal basis functions

	0.3.22	The collocation or interpolation method; ideas and math
	0.3.23	The collocation or interpolation method; implementation
	0.3.24	The collocation or interpolation method; approximating a parabola by
		linear functions
	0.3.25	Lagrange polynomials; motivation and ideas
		Lagrange polynomials; formula and code
	0.3.27	Lagrange polynomials; successful example
	0.3.28	Lagrange polynomials; a less successful example
	0.3.29	Lagrange polynomials; oscillatory behavior
		Lagrange polynomials; remedy for strong oscillations
	0.3.31	Lagrange polynomials; recalculation with Chebyshev nodes
	0.3.32	Lagrange polynomials; less oscillations with Chebyshev nodes 2
0.4	Finite	element basis functions
	0.4.1	The basis functions have so far been global: $\psi_i(x) \neq 0$ almost everywhere 2
	0.4.2	In the finite element method we use basis functions with local support 2
	0.4.3	The linear combination of hat functions is a piecewise linear function 2
	0.4.4	Elements and nodes
	0.4.5	Example on elements with two nodes (P1 elements)
	0.4.6	Illustration of two basis functions on the mesh
	0.4.7	Example on elements with three nodes (P2 elements)
	0.4.8	Some corresponding basis functions (P2 elements)
	0.4.9	Examples on elements with four nodes per element (P3 elements) 2
		Some corresponding basis functions (P3 elements)
		The numbering does not need to be regular from left to right
		Interpretation of the coefficients c_i
		Properties of the basis functions
		How to construct quadratic φ_i (P2 elements)
		Example on linear φ_i (P1 elements)
		Example on cubic φ_i (P3 elements)
0.5		ating the linear system for c_i
	0.5.1	Computing a specific matrix entry (1)
	0.5.2	Computing a specific matrix entry (2)
	0.5.3	Calculating a general row in the matrix; figure
	0.5.4	Calculating a general row in the matrix; details
	0.5.5	Calculation of the right-hand side
	0.5.6	Specific example with two elements; linear system and solution
	0.5.7	Specific example with two elements; plot
0.0	0.5.8	Specific example: what about four elements?
0.6		bly of elementwise computations
	0.6.1	Split the integrals into elementwise integrals
	0.6.2	The element matrix
	0.6.3	Illustration of the matrix assembly: regularly numbered P1 elements 3
	0.6.4	Illustration of the matrix assembly: regularly numbered P3 elements 3
	0.6.5	Illustration of the matrix assembly: irregularly numbered P1 elements 3
0.7	0.6.6	Assembly of the right-hand side
0.7		ng to a reference element
	0.7.1	Affine mapping
	$0.7.2 \\ 0.7.3$	Integral transformation
	U. L.3	Advantages of the reference element

	0.7.4	Standardized basis functions for P1 elements
	0.7.5	Standardized basis functions for P2 elements
	0.7.6	Integration over a reference element; element matrix
	0.7.7	Integration over a reference element; element vector
	0.7.8	Tedious calculations! Let's use symbolic software
0.8	Implen	nentation
	0.8.1	Compute finite element basis functions in the reference element
	0.8.2	Compute the element matrix
	0.8.3	Example on symbolic vs numeric element matrix 4
	0.8.4	Compute the element vector
	0.8.5	Fallback on numerical integration if symbolic integration fails 4
	0.8.6	Linear system assembly and solution
	0.8.7	Linear system solution
	0.8.8	Example on computing symbolic approximations
	0.8.9	Example on computing numerical approximations
	0.8.10	The structure of the coefficient matrix
		General result: the coefficient matrix is sparse
		Exemplifying the sparsity for P2 elements
		Matrix sparsity pattern for regular/random numbering of P1 elements 4
		Matrix sparsity pattern for regular/random numbering of P3 elements 4
		Sparse matrix storage and solution
		Approximate $f \sim x^9$ by various elements; code
		Approximate $f \sim x^9$ by various elements; plot
0.9		arison of finite element and finite difference approximation 4
	0.9.1	Interpolation/collocation with finite elements
	0.9.2	Galerkin/project and least squares vs collocation/interpolation or finite
		differences
	0.9.3	Expressing the left-hand side in finite difference operator notation 4
	0.9.4	Treating the right-hand side; Trapezoidal rule
	0.9.5	Treating the right-hand side; Simpson's rule
	0.9.6	Finite element approximation vs finite differences
	0.9.7	Making finite elements behave as finite differences
0.10	Limita	tions of the nodes and element concepts
0.11	A gene	eralized element concept
		The concept of a finite element
		Implementation; basic data structures
	0.11.3	Implementation; example with P2 elements
	0.11.4	Implementation; example with P0 elements
		Example on doing the algorithmic steps
	0.11.6	Approximating a parabola by P0 elements
	0.11.7	Computing the error of the approximation; principles
	0.11.8	Computing the error of the approximation; details
	0.11.9	How does the error depend on h and d ?
	0.11.10	Cubic Hermite polynomials; definition
		Cubic Hermite polynomials; derivation
0.12		rical integration
		The Midpoint rule
		Newton-Cotes rules
		Gauss-Legendre rules with optimized points

0.13	Approximation of functions in 2D	53
	0.13.1 2D basis functions as tensor products of 1D functions	54
	0.13.2 Tensor products	54
	0.13.3 Double or single index?	54
	0.13.4 Example on 2D (bilinear) basis functions; formulas	54
	0.13.5 Example on 2D (bilinear) basis functions; plot	55
	0.13.6 Implementation; principal changes to the 1D code	55
	0.13.7 Implementation; 2D integration	55
	0.13.8 Implementation; 2D basis functions	55
	0.13.9 Implementation; application	56
	0.13.10 Implementation; trying a perfect expansion	56
	0.13.11 Generalization to 3D	56
0.14	Finite elements in 2D and 3D	56
0.11	0.14.1 Examples on cell types	57
	0.14.2 Rectangular domain with 2D P1 elements	57
	0.14.3 Deformed geometry with 2D P1 elements	57
	0.14.4 Rectangular domain with 2D Q1 elements	58
	0.14.5 Basis functions over triangles in the physical domain	58
	0.14.6 Basic features of 2D P1 elements	59
	0.14.7 Linear mapping of reference element onto general triangular cell	60
	0.14.7 Emean mapping of reference element onto general triangular cen 0.14.8 φ_i : pyramid shape, composed of planes	60
	0.14.8 φ_i : pyramid shape, composed of planes	61
		61
	0.14.10 Basis functions over triangles in the reference cell	61
	0.14.11 2D P1, P2, P3, P4, P3, and P0 elements	62
	0.14.13 P2 elements in 1D, 2D, and 3D	62
		62
	0.14.14 Affine mapping of the reference cell; formula	
	0.14.15 Affine mapping of the reference cell; figure	63
	0.14.16 Isoparametric mapping of the reference cell	63
	0.14.17 Computing integrals	63
0.15	0.14.18 Remark on going from 1D to 2D/3D	64
0.15	Differential equation models	64
	0.15.1 Abstract differential equation	64
	0.15.2 Abstract boundary conditions	65
	0.15.3 Reminder about notation	65
	0.15.4 Residual-minimizing principles	65
	0.15.5 The least squares method	66
	0.15.6 The Galerkin method	66
	0.15.7 The Method of Weighted Residuals	66
	0.15.8 Terminology: test and trial Functions	66
	0.15.9 The collocation method	67
0.16	Examples on using the principles	69
	0.16.1 The first model problem	69
	0.16.2 Boundary conditions	69
	0.16.3 The least squares method; principle	69
	0.16.4 The least squares method; equation system	70
	0.16.5 Orthogonality of the basis functions gives diagonal matrix	70
	0.16.6 Least squares method; solution	70
	0.16.7 The Galerkin method: principle	71


	0.16.8 The Galerkin method; solution	71
	0.16.9 The collocation method	71
	0.16.10 Comparison of the methods	71
0.17	Useful techniques	72
	0.17.1 Integration by parts	72
	0.17.2 Boundary function; principles	72
	0.17.3 Boundary function; example	72
	0.17.4 Abstract notation for variational formulations	72
	0.17.5 Example on abstract notation	73
	0.17.6 Bilinear and linear forms	73
	0.17.7 The linear system associated with abstract form	73
	0.17.8 Equivalence with minimization problem	74
0.18	Examples on variational formulations	74
	0.18.1 Variable coefficient; problem	74
	0.18.2 Variable coefficient; variational formulation (1)	75
	0.18.3 Variable coefficient; variational formulation (2)	75
	0.18.4 Variable coefficient; abstract notation	75
	0.18.5 Variable coefficient; linear system	75
	0.18.6 First-order derivative in the equation and boundary condition; problem .	76
	0.18.7 First-order derivative in the equation and boundary condition; details	76
	0.18.8 First-order derivative in the equation and boundary condition; observations	76
	0.18.9 First-order derivative in the equation and boundary condition; abstract	
	notation	77
	0.18.10 First-order derivative in the equation and boundary condition; linear system	77
	0.18.11 Terminology: natural and essential boundary conditions	77
	0.18.12 Nonlinear coefficient; problem	77
	0.18.13 Nonlinear coefficient; variational formulation	78
	0.18.14 Nonlinear coefficient; where does the nonlinearity cause challenges?	78
	0.18.15 Computing with Dirichlet and Neumann conditions; problem	78
	0.18.16 Computing with Dirichlet and Neumann conditions; details	78
	0.18.17 When the numerical method is exact	79
	0.18.18 Computation in the global physical domain; formulas	79
	0.18.19 Computation in the global physical domain; details	80
	0.18.20 Computation in the global physical domain; linear system	80
	0.18.21 Comparison with a finite difference discretization	80
	0.18.22 Cellwise computations; formulas	81
	0.18.23 Cellwise computations; details	81
	0.18.24 Cellwise computations; details of boundary cells	81
	0.18.25 Cellwise computations; assembly	82
0.19	Boundary conditions: specified nonzero value	82
	0.19.1 General construction of a boundary function	82
	0.19.2 Example with two Dirichlet values; variational formulation	82
	0.19.3 Example with two Dirichlet values; details	83
	0.19.4 Example with two Dirichlet values; cellwise computations	83
	0.19.5 Modification of the linear system; ideas	83
	0.19.6 Modification of the linear system; linear system	83
	0.19.7 Modification of the linear system; modifications	84
	0.19.8 Modification of the linear system; element matrix/vector	84
	0.19.9 Symmetric modification of the linear system; algorithm	84

	0.19.10 Symmetric modification of the linear system; example						8
	$0.19.11\mathrm{Modification}$ of the element matrix and vector $\ \ .\ \ .\ \ .$						85
0.20	Boundary conditions: specified derivative						8!


0.1 Why finite elements?

- \bullet Can with ease solve PDEs in domains with $complex\ geometry$
- \bullet Can with ease provide higher-order approximations
- Has (in simpler stationary problems) a rigorus mathematical analysis framework (not much considered here)

0.1.1 Domain for flow around a dolphin



0.1.2 The flow



0.1.3 Basic ingredients of the finite element method


- \bullet Transform the PDE problem to a $variational\ form$
- Define function approximation over finite elements
- Use a machinery to derive *linear systems*
- Solve linear systems

0.1.4 Our learning strategy

- Start with approximation of functions, not PDEs
- ullet Introduce finite element approximations
- See later how this is applied to PDEs

Reason: the finite element method has many concepts and a jungle of details. This strategy minimizes the mixing of ideas, concepts, and technical details.

0.2 Approximation in vector spaces



0.2.1 Approximation set-up

General idea of finding an approximation u(x) to some given f(x):

$$u(x) = \sum_{i=0}^{N} c_i \psi_i(x) \tag{1}$$

where

- $\psi_i(x)$ are prescribed functions
- $c_i, i = 0, \dots, N$ are unknown coefficients to be determined

0.2.2 How to determine the coefficients?

We shall address three approaches:

- The least squares method
- The projection (or Galerkin) method
- The interpolation (or collocation) method


Underlying motivation for our notation.

Our mathematical framework for doing this is phrased in a way such that it becomes easy to understand and use the FEniCS^a software package for finite element computing.

 $^a\mathtt{http://fenicsproject.org}$

0.2.3 Approximation of planar vectors; problem

Given a vector $\mathbf{f} = (3, 5)$, find an approximation to \mathbf{f} directed along a given line.



0.2.4 Approximation of planar vectors; vector space terminology

$$V = \operatorname{span} \{ \psi_0 \} \tag{2}$$

- ψ_0 is a basis vector in the space V
- Seek $\mathbf{u} = c_0 \boldsymbol{\psi}_0 \in V$
- Determine c_0 such that u is the "best" approximation to f
- Visually, "best" is obvious

Define

- the error e = f u
- the (Eucledian) scalar product of two vectors: (u, v)
- the norm of e: $||e|| = \sqrt{(e,e)}$

0.2.5 The least squares method; principle

- Idea: find c_0 such that ||e|| is minimized
- Actually, we always minimize $E = ||e||^2$

$$\frac{\partial E}{\partial c_0} = 0$$

0.2.6 The least squares method; calculations

$$E(c_0) = (\mathbf{e}, \mathbf{e}) = (\mathbf{f}, \mathbf{f}) - 2c_0(\mathbf{f}, \psi_0) + c_0^2(\psi_0, \psi_0)$$
(3)

$$\frac{\partial E}{\partial c_0} = -2(\mathbf{f}, \psi_0) + 2c_0(\psi_0, \psi_0) = 0 \tag{4}$$

$$c_0 = \frac{(\boldsymbol{f}, \boldsymbol{\psi}_0)}{(\boldsymbol{\psi}_0, \boldsymbol{\psi}_0)} \tag{5}$$

$$c_0 = \frac{3a + 5b}{a^2 + b^2} \tag{6}$$

Observation for later: the vanishing derivative (4) can be alternatively written as

$$(\boldsymbol{e}, \boldsymbol{\psi}_0) = 0 \tag{7}$$

0.2.7 The projection (or Galerkin) method

- Backgrund: minimizing $||e||^2$ implies that e is orthogonal to any vector v in the space V (visually clear, but can easily be computed too)
- Alternative idea: demand (e, v) = 0, $\forall v \in V$
- Equivalent statement: $(e, \psi_0) = 0$ (see notes for why)
- Insert $e = f c_0 \psi_0$ and solve for c_0
- Same equation for c_0 and hence same solution as in the least squares method

Approximation of general vectors

Given a vector f, find an approximation $u \in V$:

$$V = \operatorname{span} \{ \psi_0, \dots, \psi_N \}$$

- We have a set of linearly independent basis vectors ψ_0, \dots, ψ_N
- Any $\boldsymbol{u} \in V$ can then be written as $\boldsymbol{u} = \sum_{j=0}^N c_j \psi_j$

The least squares method

Idea: find c_0, \ldots, c_N such that $E = ||e||^2$ is minimized, e = f - u.

$$E(c_0, \dots, c_N) = (\boldsymbol{e}, \boldsymbol{e}) = (\boldsymbol{f} - \sum_j c_j \psi_j, \boldsymbol{f} - \sum_j c_j \psi_j)$$

$$= (\boldsymbol{f}, \boldsymbol{f}) - 2 \sum_{j=0}^N c_j (\boldsymbol{f}, \psi_j) + \sum_{p=0}^N \sum_{q=0}^N c_p c_q (\psi_p, \psi_q)$$

$$\frac{\partial E}{\partial c_i} = 0, \quad i = 0, \dots, N$$

After some work we end up with a linear system

$$\sum_{j=0}^{N} A_{i,j} c_j = b_i, \quad i = 0, \dots, N$$
 (8)

$$A_{i,j} = (\psi_i, \psi_j)$$

$$b_i = (\psi_i, \mathbf{f})$$

$$(10)$$

$$b_i = (\boldsymbol{\psi}_i, \boldsymbol{f}) \tag{10}$$

The projection (or Galerkin) method 0.2.10

Can be shown that minimizing ||e|| implies that e is orthogonal to all $v \in V$:

$$(\boldsymbol{e}, \boldsymbol{v}) = 0, \quad \forall \boldsymbol{v} \in V$$

which implies that e most be orthogonal to each basis vector:

$$(\boldsymbol{e}, \boldsymbol{\psi}_i) = 0, \quad i = 0, \dots, N \tag{11}$$

This orthogonality condition is the principle of the projection (or Galerkin) method. Leads to the same linear system as in the least squares method.

Approximation of functions

Let V be a function space spanned by a set of basis functions ψ_0, \ldots, ψ_N ,

$$V = \mathrm{span}\left\{\psi_0, \dots, \psi_N\right\}$$

Find $u \in V$ as a linear combination of the basis functions:

$$u = \sum_{j \in I} c_j \psi_j, \quad I = \{0, 1, \dots, N\}$$
 (12)

0.3.1The least squares method

- Extend the ideas from the vector case: minimize the (square) norm of the error.
- What norm? $(f,g) = \int_{\Omega} f(x)g(x) dx$

$$E = (e, e) = (f - u, f - u) = (f(x) - \sum_{j \in I} c_j \psi_j(x), f(x) - \sum_{j \in I} c_j \psi_j(x))$$
(13)

$$E(c_0, \dots, c_N) = (f, f) - 2\sum_{j \in I} c_j(f, \psi_i) + \sum_{p \in I} \sum_{q \in I} c_p c_q(\psi_p, \psi_q)$$
(14)

$$\frac{\partial E}{\partial c_i} = 0, \quad i = \in I$$

After computations identical to the vector case, we get a linear system

$$\sum_{j\in I}^{N} A_{i,j} c_j = b_i, \quad i \in I$$

$$\tag{15}$$

$$A_{i,j} = (\psi_i, \psi_j)$$

$$b_i = (f, \psi_i)$$
(16)
$$(17)$$

$$b_i = (f, \psi_i) \tag{17}$$

0.3.2The projection (or Galerkin) method

As before, minimizing (e, e) is equivalent to the projection (or Galerkin) method

$$(e, v) = 0, \quad \forall v \in V \tag{18}$$

which means, as before,

$$(e, \psi_i) = 0, \quad i \in I \tag{19}$$

With the same algebra as in the multi-dimensional vector case, we get the same linear system as arose from the least squares method.

0.3.3Example: linear approximation; problem

Approximate a parabola $f(x) = 10(x-1)^2 - 1$ by a straight line.

$$V = \operatorname{span}\{1, x\}$$

That is, $\psi_0(x) = 1$, $\psi_1(x) = x$, and N = 1. We seek

$$u = c_0 \psi_0(x) + c_1 \psi_1(x) = c_0 + c_1 x$$

0.3.4 Example: linear approximation; solution

$$A_{0,0} = (\psi_0, \psi_0) = \int_1^2 1 \cdot 1 \, dx = 1 \tag{20}$$

$$A_{0,1} = (\psi_0, \psi_1) = \int_1^2 1 \cdot x \, dx = 3/2 \tag{21}$$

$$A_{1,0} = A_{0,1} = 3/2 (22)$$

$$A_{1,1} = (\psi_1, \psi_1) = \int_1^2 x \cdot x \, dx = 7/3 \tag{23}$$


$$b_1 = (f, \psi_0) = \int_1^2 (10(x-1)^2 - 1) \cdot 1 \, dx = 7/3 \tag{24}$$

$$b_2 = (f, \psi_1) = \int_1^2 (10(x-1)^2 - 1) \cdot x \, dx = 13/3 \tag{25}$$

Solution of 2x2 linear system:

$$c_0 = -38/3, \quad c_1 = 10, \quad u(x) = 10x - \frac{38}{3}$$
 (26)

0.3.5 Example: linear approximation; plot



0.3.6 Implementation of the least squares method; ideas

Consider symbolic computation of the linear system, where

- f(x) is given as a sympy expression f (involving the symbol x),
- psi is a list of $\{\psi_i\}_{i\in I}$,
- ullet Omega is a 2-tuple/list holding the domain Ω

Carry out the integrations, solve the linear system, and return $u(x) = \sum_{j} c_{j} \psi_{j}(x)$

0.3.7 Implementation of the least squares method; symbolic code

Observe: symmetric coefficient matrix so we can halve the integrations.

0.3.8 Implementation of the least squares method; numerical code

- Symbolic integration may be impossible and/or very slow
- Turn to pure numerical computations in those cases
- Supply Python functions f(x), psi(x,i), and a mesh x

```
elif ...
    A[i,j] = A[j,i] = A_ij

if integration_method == 'scipy':
    b_i = scipy.integrate.quad(
        lambda x: f(x)*psi(x,i), Omega[0], Omega[1],
        epsabs=1E-9, epsrel=1E-9)[0]

elif ...
    b[i] = b_i

c = b/np.diag(A) if orthogonal_basis else np.linalg.solve(A, b)
u = sum(c[i]*psi(x, i) for i in range(N+1))
return u, c
```

0.3.9 Implementation of the least squares method; plotting

Compare f and u visually:


```
def comparison_plot(f, u, Omega, filename='tmp.pdf'):
    x = sm.Symbol('x')
    # Turn f and u to ordinary Python functions
    f = sm.lambdify([x], f, modules="numpy")
    u = sm.lambdify([x], u, modules="numpy")
    resolution = 401  # no of points in plot
    xcoor = linspace(Omega[0], Omega[1], resolution)
    exact = f(xcoor)
    approx = u(xcoor)
    plot(xcoor, approx)
    hold('on')
    plot(xcoor, exact)
    legend(['approximation', 'exact'])
    savefig(filename)
```

All code in module approx1D.py¹

0.3.10 Implementation of the least squares method; application

```
>>> from approx1D import *
>>> x = sm.Symbol('x')
>>> f = 10*(x-1)**2-1
>>> u, c = least_squares(f=f, psi=[1, x], Omega=[1, 2])
>>> comparison_plot(f, u, Omega=[1, 2])
```

¹http://tinyurl.com/jvzzcfn/fem/approx1D.py



0.3.11 Perfect approximation; parabola approximating parabola

- What if we add $\psi_2 = x^2$ to the space V?
- That is, approximating a parabola by any parabola?
- $\bullet \ \mbox{(Hopefully we get the exact parabola!)}$

```
>>> from approx1D import *
>>> x = sm.Symbol('x')
>>> f = 10*(x-1)**2-1
>>> u, c = least_squares(f=f, psi=[1, x, x**2], Omega=[1, 2])
>>> print u
10*x**2 - 20*x + 9
>>> print sm.expand(f)
10*x**2 - 20*x + 9
```

0.3.12 Perfect approximation; the general result

- What if we use $\psi_i(x) = x^i$ for $i = 0, \dots, N = 40$?
- The output from least_squares is $c_i = 0$ for i > 2

General result.

If $f \in V$, least squares and projection/Galerkin give u = f.

0.3.13 Perfect approximation; proof of the general result

If $f \in V$, $f = \sum_{j \in I} d_j \psi_j$, for some $\{d_i\}_{i \in I}$. Then

$$b_i = (f, \psi_i) = \sum_{j \in I} d_j(\psi_j, \psi_i) = \sum_{j \in I} d_j A_{i,j}$$

The linear system $\sum_{j} A_{i,j} c_j = b_i$, $i \in I$, is then

$$\sum_{j \in I} c_j A_{i,j} = \sum_{j \in I} d_j A_{i,j}, \quad i \in I$$

which implies that $c_i = d_i$ for $i \in I$ and u is identical to f.

0.3.14 Finite-precision/numerical computations

The previous computations were symbolic. What if we solve the linear system numerically with standard arrays?

exact	sympy	numpy32	numpy64
9	9.62	5.57	8.98
-20	-23.39	-7.65	-19.93
10	17.74	-4.50	9.96
0	-9.19	4.13	-0.26
0	5.25	2.99	0.72
0	0.18	-1.21	-0.93
0	-2.48	-0.41	0.73
0	1.81	-0.013	-0.36
0	-0.66	0.08	0.11
0	0.12	0.04	-0.02
0	-0.001	-0.02	0.002


- Column 2: sympy.mpmath.fp.matrix and sympy.mpmath.fp.lu_solve
- Column 3: numpy arrays with numpy.float32 entries
- Column 4: numpy arrays with numpy.float64 entries

0.3.15 Ill-conditioning (1)

Observations:

- Significant round-off errors in the numerical computations (!)
- \bullet But if we plot the approximations they look good (!)

Problem: The basis functions x^i become almost linearly dependent for large N.



0.3.16 Ill-conditioning (2)

- Almost linearly dependent basis functions give almost singular matrices
- Such matrices are said to be *ill conditioned*, and Gaussian elimination is severely affected by round-off errors
- The basis $1, x, x^2, x^3, x^4, \dots$ is a bad basis
- Polynomials are fine as basis, but the more orthogonal they are, $(\psi_i, \psi_j) \approx 0$, the better

0.3.17 Fourier series approximation; problem and code

Consider


$$V = \operatorname{span} \left\{ \sin \pi x, \sin 2\pi x, \dots, \sin(N+1)\pi x \right\}$$


```
N = 3
from sympy import sin, pi
psi = [sin(pi*(i+1)*x) for i in range(N+1)]
f = 10*(x-1)**2 - 1
Omega = [0, 1]
u, c = least_squares(f, psi, Omega)
comparison_plot(f, u, Omega)
```

0.3.18 Fourier series approximation; plot

```
N = 3 \text{ vs } N = 11:
```

21





0.3.19 Fourier series approximation; improvements


- Considerably improvement by N = 11
- But always discrepancy of f(0) u(0) = 9 at x = 0, because all the $\psi_i(0) = 0$ and hence u(0) = 0
- Possible remedy: add a term that leads to correct boundary values


$$u(x) = f(0)(1-x) + xf(1) + \sum_{j \in I} c_j \psi_j(x)$$
(27)

The extra term ensures u(0) = f(0) and u(1) = f(1) and is a strikingly good help to get a good approximation!

0.3.20 Fourier series approximation; final results

$$N=3$$
 vs $N=11$:





0.3.21 Orthogonal basis functions

This choice of sine functions as basis functions is popular because

- the basis functions are orthogonal: $(\psi_i, \psi_j) = 0$
- implying that $A_{i,j}$ is a diagonal matrix
- implying that we can solve for $c_i = 2 \int_0^1 f(x) \sin((i+1)\pi x) dx$

In general for an orthogonal basis, $A_{i,j}$ is diagonal and we can easily solve for c_i :

$$c_i = \frac{b_i}{A_{i,i}} = \frac{(f, \psi_i)}{(\psi_i, \psi_i)}$$

0.3.22 The collocation or interpolation method; ideas and math

Here is another idea for approximating f(x) by $u(x) = \sum_{j} c_{j} \psi_{j}$:

- Force $u(x_i) = f(x_i)$ at some selected collocation points $\{x_i\}_{i \in I}$
- \bullet Then u interpolates f
- The method is known as interpolation or collocation

$$u(x_i) = \sum_{i \in I} c_j \psi_j(x_i) = f(x_i) \quad i \in I, N$$
(28)

This is a linear system with no need for integration:

$$\sum_{j \in I} A_{i,j} c_j = b_i, \quad i \in I \tag{29}$$

$$A_{i,j} = \psi_j(x_i) \tag{30}$$

$$b_i = f(x_i) \tag{31}$$

No symmetric matrix: $\psi_j(x_i) \neq \psi_i(x_j)$ in general

0.3.23 The collocation or interpolation method; implementation


points holds the interpolation/collocation points


23

0.3.24 The collocation or interpolation method; approximating a parabola by linear functions

- Potential difficulty: how to choose x_i ?
- The results are sensitive to the points!

(4/3, 5/3) vs (1, 2):





0.3.25 Lagrange polynomials; motivation and ideas

Motivation:

- The interpolation/collocation method avoids integration
- With a diagonal matrix $A_{i,j} = \psi_j(x_i)$ we can solve the linear system by hand

The Lagrange interpolating polynomials ψ_j have the property that

$$\psi_i(x_j) = \delta_{ij}, \quad \delta_{ij} = \begin{cases} 1, & i = j \\ 0, & i \neq j \end{cases}$$

Hence, $c_i = f(x_i)$ and

$$u(x) = \sum_{i \in I} f(x_i)\psi_i(x) \tag{32}$$


- Lagrange polynomials and interpolation/collocation look convenient
- Lagrange polynomials are very much used in the finite element method


0.3.26 Lagrange polynomials; formula and code

$$\psi_i(x) = \prod_{j=0, j \neq i}^{N} \frac{x - x_j}{x_i - x_j} = \frac{x - x_0}{x_i - x_0} \cdots \frac{x - x_{i-1}}{x_i - x_{i-1}} \frac{x - x_{i+1}}{x_i - x_{i+1}} \cdots \frac{x - x_N}{x_i - x_N}$$
(33)


```
def Lagrange_polynomial(x, i, points):
    p = 1
    for k in range(len(points)):
        if k != i:
        p *= (x - points[k])/(points[i] - points[k])
    return p
```


0.3.27 Lagrange polynomials; successful example






0.3.28 Lagrange polynomials; a less successful example





0.3.29 Lagrange polynomials; oscillatory behavior

12 points, degree 11, plot of two of the Lagrange polynomials - note that they are zero at all points except one.



Problem: strong oscillations near the boundaries for larger N values.


0.3.30 Lagrange polynomials; remedy for strong oscillations


The oscillations can be reduced by a more clever choice of interpolation points, called the $Chebyshev\ nodes$:

$$x_i = \frac{1}{2}(a+b) + \frac{1}{2}(b-a)\cos\left(\frac{2i+1}{2(N+1)}pi\right), \quad i = 0..., N$$
 (34)

on an interval [a, b].


0.3.31 Lagrange polynomials; recalculation with Chebyshev nodes






0.3.32 Lagrange polynomials; less oscillations with Chebyshev nodes

12 points, degree 11, plot of two of the Lagrange polynomials - note that they are zero at all points except one.




0.4 Finite element basis functions

0.4.1 The basis functions have so far been global: $\psi_i(x) \neq 0$ almost everywhere




0.4.2 In the finite element method we use basis functions with local support

- Local support: $\psi_i(x) \neq 0$ for x in a small subdomain of Ω
- Typically hat-shaped
- u(x) based on these ψ_i is a piecewise polynomial defined over many (small) subdomains
- We introduce φ_i as the name of these finite element hat functions (and for now choose $\psi_i = \varphi_i$)



0.4.3 The linear combination of hat functions is a piecewise linear function



0.4.4 Elements and nodes

Split Ω into non-overlapping subdomains called *elements*:


$$\Omega = \Omega^{(0)} \cup \dots \cup \Omega^{(N_e)} \tag{35}$$

On each element, introduce points called *nodes*: x_0, \ldots, x_{N_n}

- The finite element basis functions are named $\varphi_i(x)$
- $\varphi_i = 1$ at node i and 0 at all other nodes
- φ_i is a Lagrange polynomial on each element
- ullet For nodes at the boundary between two elements, φ_i is made up of a Lagrange polynomial over each element


29

0.4.5 Example on elements with two nodes (P1 elements)




Data structure: nodes holds coordinates or nodes, elements holds the node numbers in each element

0.4.6 Illustration of two basis functions on the mesh




0.4.7 Example on elements with three nodes (P2 elements)




nodes = [0, 0.125, 0.25, 0.375, 0.5, 0.625, 0.75, 0.875, 1.0] elements = [[0, 1, 2], [2, 3, 4], [4, 5, 6], [6, 7, 8]]

0.4.8 Some corresponding basis functions (P2 elements)




0.4.9 Examples on elements with four nodes per element (P3 elements)




```
d = 3  # d+1 nodes per element
num_elements = 4
num_nodes = num_elements*d + 1
nodes = [i*0.5 for i in range(num_nodes)]
elements = [[i*d+j for j in range(d+1)] for i in range(num_elements)]
```

0.4.10 Some corresponding basis functions (P3 elements)



0.4.11 The numbering does not need to be regular from left to right



0.4.12 Interpretation of the coefficients c_i

Important property: c_i is the value of u at node i, x_i :


$$u(x_i) = \sum_{j \in I} c_j \varphi_j(x_i) = c_i \varphi_i(x_i) = c_i$$
(36)

because $\varphi_j(x_i) = 0$ if $i \neq j$

0.4.13 Properties of the basis functions


- $\varphi_i(x) \neq 0$ only on those elements that contain global node i
- $\varphi_i(x)\varphi_j(x) \neq 0$ if and only if i and j are global node numbers in the same element

Since $A_{i,j} = \int \varphi_i \varphi_j dx$, most of the elements in the coefficient matrix will be zero




33

0.4.14 How to construct quadratic φ_i (P2 elements)




- 1. Associate Lagrange polynomials with the nodes in an element
- 2. When the polynomial is 1 on the element boundary, combine it with the polynomial in the neighboring element

0.4.15 Example on linear φ_i (P1 elements)




$$\varphi_{i}(x) = \begin{cases} 0, & x < x_{i-1} \\ (x - x_{i-1})/h & x_{i-1} \le x < x_{i} \\ 1 - (x - x_{i})/h, & x_{i} \le x < x_{i+1} \\ 0, & x \ge x_{i+1} \end{cases}$$
(37)

0.4.16 Example on cubic φ_i (P3 elements)



0.5 Calculating the linear system for c_i

0.5.1 Computing a specific matrix entry (1)




 $A_{2,3}=\int_{\Omega}\varphi_{2}\varphi_{3}dx\colon\,\varphi_{2}\varphi_{3}\neq0$ only over element 2. There,

$$\varphi_3(x) = (x - x_2)/h, \quad \varphi_2(x) = 1 - (x - x_2)/h$$


$$A_{2,3} = \int_{\Omega} \varphi_2 \varphi_3 \, dx = \int_{x_2}^{x_3} \left(1 - \frac{x - x_2}{h} \right) \frac{x - x_2}{h} \, dx = \frac{h}{6}$$

0.5.2 Computing a specific matrix entry (2)



$$A_{2,2} = \int_{x_1}^{x_2} \left(\frac{x - x_1}{h} \right)^2 dx + \int_{x_2}^{x_3} \left(1 - \frac{x - x_2}{h} \right)^2 dx = \frac{h}{3}$$

0.5.3 Calculating a general row in the matrix; figure



$$A_{i,i-1} = \int_{\Omega} \varphi_i \varphi_{i-1} \, \mathrm{d}x = ?$$

0.5.4 Calculating a general row in the matrix; details


$$A_{i,i-1} = \int_{\Omega} \varphi_i \varphi_{i-1} \, \mathrm{d}x$$

$$= \underbrace{\int_{x_{i-1}}^{x_{i-1}} \varphi_i \varphi_{i-1} \, \mathrm{d}x}_{\varphi_i = 0} + \int_{x_{i-1}}^{x_i} \varphi_i \varphi_{i-1} \, \mathrm{d}x + \underbrace{\int_{x_i}^{x_{i+1}} \varphi_i \varphi_{i-1} \, \mathrm{d}x}_{\varphi_{i-1} = 0}$$

$$= \underbrace{\int_{x_{i-1}}^{x_i} \underbrace{\left(\frac{x - x_i}{h}\right)}_{\varphi_i(x)} \underbrace{\left(1 - \frac{x - x_{i-1}}{h}\right)}_{\varphi_{i-1}(x)} \, \mathrm{d}x = \frac{h}{6}$$

- $A_{i,i+1} = A_{i,i-1}$ due to symmetry
- $A_{i,i} = h/3$ (same calculation as for $A_{2,2}$)
- $A_{0,0} = A_{N,N} = h/3$ (only one element)

0.5.5 Calculation of the right-hand side



$$b_{i} = \int_{\Omega} \varphi_{i}(x) f(x) dx = \int_{x_{i-1}}^{x_{i}} \frac{x - x_{i-1}}{h} f(x) dx + \int_{x_{i}}^{x_{i+1}} \left(1 - \frac{x - x_{i}}{h}\right) f(x) dx$$
(38)

Need a specific f(x) to do more...


0.5.6 Specific example with two elements; linear system and solution

- f(x) = x(1-x) on $\Omega = [0,1]$
- \bullet Two equal-sized elements [0,0.5] and [0.5,1]


$$A = \frac{h}{6} \begin{pmatrix} 2 & 1 & 0 \\ 1 & 4 & 1 \\ 0 & 1 & 2 \end{pmatrix}, \quad b = \frac{h^2}{12} \begin{pmatrix} 2 - 3h \\ 12 - 14h \\ 10 - 17h \end{pmatrix}$$
$$c_0 = \frac{h^2}{6}, \quad c_1 = h - \frac{5}{6}h^2, \quad c_2 = 2h - \frac{23}{6}h^2$$

0.5.7 Specific example with two elements; plot

$$u(x) = c_0 \varphi_0(x) + c_1 \varphi_1(x) + c_2 \varphi_2(x)$$



0.5.8 Specific example: what about four elements?



0.6 Assembly of elementwise computations

0.6.1 Split the integrals into elementwise integrals

$$A_{i,j} = \int_{\Omega} \varphi_i \varphi_j dx = \sum_{e} \int_{\Omega^{(e)}} \varphi_i \varphi_j dx, \quad A_{i,j}^{(e)} = \int_{\Omega^{(e)}} \varphi_i \varphi_j dx$$
 (39)

Important:

• $A_{i,j}^{(e)} \neq 0$ if and only if i and j are nodes in element e (otherwise no overlap between the basis functions)

 \bullet all the nonzero elements in $A_{i,j}^{(e)}$ are collected in an $\mathit{element\ matrix}$


0.6.2 The element matrix

$$\tilde{A}^{(e)} = \{\tilde{A}_{r,s}^{(e)}\}, \quad \tilde{A}_{r,s}^{(e)} = \int_{\Omega^{(e)}} \varphi_{q(e,r)} \varphi_{q(e,s)} dx, \quad r, s \in I_d = \{0, \dots, d\}$$

- \bullet r, s run over local node numbers in an element; i, j run over global node numbers
- i = q(e, r): mapping of local node number r in element e to the global node number i (math equivalent to i=elements[e][r])
- Add $\tilde{A}_{r,s}^{(e)}$ into the global $A_{i,j}$ (assembly)

$$A_{q(e,r),q(e,s)} := A_{q(e,r),q(e,s)} + \tilde{A}_{r,s}^{(e)}, \quad r,s \in I_d$$
(40)


0.6.3 Illustration of the matrix assembly: regularly numbered P1 elements



Animation²

²http://tinyurl.com/k3sdbuv/pub/mov-fem/fe_assembly.html


0.6.4 Illustration of the matrix assembly: regularly numbered P3 elements



 ${\rm Animation^3}$

 $^{^3 {\}tt http://tinyurl.com/k3sdbuv/pub/mov-fem/fe_assembly.html}$

0.6.5 Illustration of the matrix assembly: irregularly numbered P1 elements



Animation⁴

0.6.6 Assembly of the right-hand side

$$b_i = \int_{\Omega} f(x)\varphi_i(x)dx = \sum_{e} \int_{\Omega^{(e)}} f(x)\varphi_i(x)dx, \quad b_i^{(e)} = \int_{\Omega^{(e)}} f(x)\varphi_i(x)dx \tag{41}$$

Important:

- $b_i^{(e)} \neq 0$ if and only if global node i is a node in element e (otherwise $\varphi_i = 0$)
- The d+1 nonzero $b_i^{(e)}$ can be collected in an element vector $\tilde{b}_r^{(e)} = \{\tilde{b}_r^{(e)}\}, r \in I_d$

Assembly:

$$b_{q(e,r)} := b_{q(e,r)} + \tilde{b}_r^{(e)}, \quad r, s \in I_d$$
 (42)

0.7 Mapping to a reference element

Instead of computing

$$\tilde{A}_{r,s}^{(e)} = \int_{\Omega^{(e)}} \varphi_{q(e,r)}(x) \varphi_{q(e,s)}(x) dx = \int_{x_L}^{x_R} \varphi_{q(e,r)}(x) \varphi_{q(e,s)}(x) dx$$

we now map $[x_L, x_R]$ to a standardized reference element domain [-1, 1] with local coordinate X

 $^{^4 {\}tt http://tinyurl.com/k3sdbuv/pub/mov-fem/fe_assembly.html}$

0.7.1 Affine mapping

$$x = \frac{1}{2}(x_L + x_R) + \frac{1}{2}(x_R - x_L)X \tag{43}$$

or rewritten as

$$x = x_m + \frac{1}{2}hX, \qquad x_m = (x_L + x_R)/2$$
 (44)

0.7.2 Integral transformation

Reference element integration: just change integration variable from x to X. Introduce local basis function

$$\tilde{\varphi}_r(X) = \varphi_{q(e,r)}(x(X)) \tag{45}$$

$$\tilde{A}_{r,s}^{(e)} = \int_{\Omega^{(e)}} \varphi_{q(e,r)}(x) \varphi_{q(e,s)}(x) dx = \int_{-1}^{1} \tilde{\varphi}_r(X) \tilde{\varphi}_s(X) \underbrace{\frac{dx}{dX}}_{\det J = h/2} dX = \int_{-1}^{1} \tilde{\varphi}_r(X) \tilde{\varphi}_s(X) \det J dX$$

$$(46)$$

$$\tilde{b}_r^{(e)} = \int_{\Omega^{(e)}} f(x)\varphi_{q(e,r)}(x)dx = \int_{-1}^1 f(x(X))\tilde{\varphi}_r(X) \det J \, dX \tag{47}$$

0.7.3 Advantages of the reference element

- Always the same domain for integration: [-1, 1]
- We only need formulas for $\tilde{\varphi}_r(X)$ over one element (no piecewise polynomial definition)
- $\tilde{\varphi}_r(X)$ is the same for all elements: no dependence on element length and location, which is "factored out" in the mapping and det J

0.7.4 Standardized basis functions for P1 elements

$$\tilde{\varphi}_0(X) = \frac{1}{2}(1 - X)$$
 (48)

$$\tilde{\varphi}_1(X) = \frac{1}{2}(1+X)$$
 (49)

0.7.5 Standardized basis functions for P2 elements

P2 elements:

$$\tilde{\varphi}_0(X) = \frac{1}{2}(X - 1)X\tag{50}$$

$$\tilde{\varphi}_1(X) = 1 - X^2 \tag{51}$$

$$\tilde{\varphi}_2(X) = \frac{1}{2}(X+1)X\tag{52}$$

Easy to generalize to arbitrary order!

0.7.6 Integration over a reference element; element matrix

P1 elements and f(x) = x(1-x).

$$\tilde{A}_{0,0}^{(e)} = \int_{-1}^{1} \tilde{\varphi}_{0}(X)\tilde{\varphi}_{0}(X)\frac{h}{2}dX
= \int_{-1}^{1} \frac{1}{2}(1-X)\frac{1}{2}(1-X)\frac{h}{2}dX = \frac{h}{8}\int_{-1}^{1}(1-X)^{2}dX = \frac{h}{3}$$

$$\tilde{A}_{1,0}^{(e)} = \int_{-1}^{1} \tilde{\varphi}_{1}(X)\tilde{\varphi}_{0}(X)\frac{h}{2}dX
= \int_{-1}^{1} \frac{1}{2}(1+X)\frac{1}{2}(1-X)\frac{h}{2}dX = \frac{h}{8}\int_{-1}^{1}(1-X^{2})dX = \frac{h}{6}$$

$$\tilde{A}_{0,1}^{(e)} = \tilde{A}_{1,0}^{(e)}$$

$$\tilde{A}_{0,1}^{(e)} = \int_{-1}^{1} \tilde{\varphi}_{1}(Y)\tilde{\varphi}_{1}(Y)\frac{h}{dY}$$
(55)

$$\tilde{A}_{1,1}^{(e)} = \int_{-1}^{1} \tilde{\varphi}_{1}(X)\tilde{\varphi}_{1}(X)\frac{h}{2}dX$$

$$= \int_{-1}^{1} \frac{1}{2}(1+X)\frac{1}{2}(1+X)\frac{h}{2}dX = \frac{h}{8}\int_{-1}^{1}(1+X)^{2}dX = \frac{h}{3}$$
(56)

0.7.7 Integration over a reference element; element vector

$$\tilde{b}_{0}^{(e)} = \int_{-1}^{1} f(x(X))\tilde{\varphi}_{0}(X) \frac{h}{2} dX
= \int_{-1}^{1} (x_{m} + \frac{1}{2}hX)(1 - (x_{m} + \frac{1}{2}hX)) \frac{1}{2}(1 - X) \frac{h}{2} dX
= -\frac{1}{24}h^{3} + \frac{1}{6}h^{2}x_{m} - \frac{1}{12}h^{2} - \frac{1}{2}hx_{m}^{2} + \frac{1}{2}hx_{m}$$

$$\tilde{b}_{1}^{(e)} = \int_{-1}^{1} f(x(X))\tilde{\varphi}_{1}(X) \frac{h}{2} dX
= \int_{-1}^{1} (x_{m} + \frac{1}{2}hX)(1 - (x_{m} + \frac{1}{2}hX)) \frac{1}{2}(1 + X) \frac{h}{2} dX
= -\frac{1}{24}h^{3} - \frac{1}{6}h^{2}x_{m} + \frac{1}{12}h^{2} - \frac{1}{2}hx_{m}^{2} + \frac{1}{2}hx_{m}$$
(58)

 x_m : element midpoint.

0.7.8 Tedious calculations! Let's use symbolic software

```
>>> import sympy as sm
>>> x, x_m, h, X = sm.symbols('x x_m h X')
>>> sm.integrate(h/8*(1-X)**2, (X, -1, 1))
h/3
>>> sm.integrate(h/8*(1+X)*(1-X), (X, -1, 1))
h/6
>>> x = x_m + h/2*X
>>> b_0 = sm.integrate(h/4*x*(1-x)*(1-X), (X, -1, 1))
>>> print b_0
-h**3/24 + h**2*x_m/6 - h**2/12 - h*x_m**2/2 + h*x_m/2
```

Can printe out in LATEX too (convenient for copying into reports):

```
>>> print sm.latex(b_0, mode='plain')
- \frac{1}{24} h^{3} + \frac{1}{6} h^{2} x_{m}
- \frac{1}{12} h^{2} - \frac{1}{2} h x_{m}^{2}
+ \frac{1}{2} h x_{m}
```

0.8 Implementation

- Coming functions appear in fe_approx1D.py⁵
- Functions can operate in symbolic or numeric mode
- The code documents all steps in finite element calculations!

0.8.1 Compute finite element basis functions in the reference element

Let $\tilde{\varphi}_r(X)$ be a Lagrange polynomial of degree d:

```
import sympy as sm
import numpy as np
def phi_r(r, X, d):
    if isinstance(X, sm.Symbol):
        h = sm.Rational(1, d) # node spacing
nodes = [2*i*h - 1 for i in range(d+1)]
    else:
         \mbox{\tt\#} assume \mbox{\tt X} is numeric: use floats for nodes
        nodes = np.linspace(-1, 1, d+1)
    return Lagrange_polynomial(X, r, nodes)
def Lagrange_polynomial(x, i, points):
    for k in range(len(points)):
         if k != i:
            p *= (x - points[k])/(points[i] - points[k])
    return p
def basis(d=1):
    """Return the complete basis."""
    X = sm.Symbol('X')
    phi = [phi_r(r, X, d) for r in range(d+1)]
    return phi
```

0.8.2 Compute the element matrix

```
def element_matrix(phi, Omega_e, symbolic=True):
    n = len(phi)
    A_e = sm.zeros((n, n))
    X = sm.Symbol('X')
    if symbolic:
        h = sm.Symbol('h')
    else:
        h = Omega_e[1] - Omega_e[0]
    detJ = h/2  # dx/dX
    for r in range(n):
        for s in range(r, n):
```

⁵http://tinyurl.com/jvzzcfn/fem/fe_approx1D.py

```
A_e[r,s] = sm.integrate(phi[r]*phi[s]*detJ, (X, -1, 1))
A_e[s,r] = A_e[r,s]
return A_e
```

0.8.3 Example on symbolic vs numeric element matrix

```
>>> from fe_approx1D import *
>>> phi = basis(d=1)
>>> phi
[1/2 - X/2, 1/2 + X/2]
>>> element_matrix(phi, Omega_e=[0.1, 0.2], symbolic=True)
[h/3, h/6]
[h/6, h/3]
>>> element_matrix(phi, Omega_e=[0.1, 0.2], symbolic=False)
[0.0333333333333333, 0.016666666666667]
[0.0166666666666667, 0.03333333333333]
```

0.8.4 Compute the element vector

```
def element_vector(f, phi, Omega_e, symbolic=True):
    n = len(phi)
    b_e = sm.zeros((n, 1))
    # Make f a function of X
    X = sm.Symbol('X')
    if symbolic:
        h = sm.Symbol('h')
    else:
        h = Omega_e[1] - Omega_e[0]
    x = (Omega_e[0] + Omega_e[1])/2 + h/2*X  # mapping
    f = f.subs('x', x)  # substitute mapping formula for x
    detJ = h/2  # dx/dX
    for r in range(n):
        b_e[r] = sm.integrate(f*phi[r]*detJ, (X, -1, 1))
    return b_e
```

Note f.subs('x', x): replace x by x(X) such that f contains X

0.8.5 Fallback on numerical integration if symbolic integration fails

- Element matrix: only polynomials and sympy always succeeds
- Element vector: $\int f \tilde{\varphi} dx$ can fail (sympy then returns an Integral object instead of a number)

```
def element_vector(f, phi, Omega_e, symbolic=True):
    ...
    I = sm.integrate(f*phi[r]*detJ, (X, -1, 1)) # try...
    if isinstance(I, sm.Integral):
        h = Omega_e[1] - Omega_e[0] # Ensure h is numerical
        detJ = h/2
        integrand = sm.lambdify([X], f*phi[r]*detJ)
        I = sm.mpmath.quad(integrand, [-1, 1])
    b_e[r] = I
    ...
```

0.8.6 Linear system assembly and solution

0.8.7 Linear system solution

```
if symbolic:
    c = A.LUsolve(b)  # sympy arrays, symbolic Gaussian elim.
else:
    c = np.linalg.solve(A, b)  # numpy arrays, numerical solve
```

Note: the symbolic computation of A and b and the symbolic solution can be very tedious.

0.8.8 Example on computing symbolic approximations

```
>>> h, x = sm.symbols('h x')
>>> nodes = [0, h, 2*h]
>>> elements = [[0, 1], [1, 2]]
>>> phi = basis(d=1)
>>> f = x*(1-x)
>>> A, b = assemble(nodes, elements, phi, f, symbolic=True)
>>> A
[h/3, h/6, 0]
[h/6, 2*h/3, h/6]
[ 0,
        h/6, h/3]
>>> b
       h**2/6 - h**3/12]
        h**2 - 7*h**3/6]
[5*h**2/6 - 17*h**3/12]
>>> c = A.LUsolve(b)
>>> c
                                    h**2/6]
[12*(7*h**2/12 - 35*h**3/72)/(7*h)]
[7*(4*h**2/7 - 23*h**3/21)/(2*h)]
```

0.8.9 Example on computing numerical approximations

```
>>> nodes = [0, 0.5, 1]
>>> elements = [[0, 1], [1, 2]]
>>> phi = basis(d=1)
>>> x = sm.Symbol('x')
>>> f = x*(1-x)
>>> A, b = assemble(nodes, elements, phi, f, symbolic=False)
```

0.8.10 The structure of the coefficient matrix

```
>>> d=1; N_e=8; Omega=[0,1] # 8 linear elements on [0,1]
>>> phi = basis(d)
>>> f = x*(1-x)
>>> nodes, elements = mesh_symbolic(N_e, d, Omega)
>>> A, b = assemble(nodes, elements, phi, f, symbolic=True)
>>> A
[h/3,
       h/6,
              h/6,
                       0,
[h/6, 2*h/3,
                              0,
                                      0,
                                                         0]
                     h/6,
                                     0,
[ 0,
[ 0,
[ 0,
       h/6, 2*h/3,
                                            0,
                                                         0]
                               Ο,
         0,
              h/6, 2*h/3,
                            h/6,
                                     Ο,
                                             Ο,
                                                         0]
              0,
                                            0,
         0,
                    h/6, 2*h/3,
                                   h/6,
                                                         0]
                     0,
]
                            h/6, 2*h/3,
        Ο,
                                                         0]
               0,
                       0,
                                                  h/6,
         0,
                             0, h/6, 2*h/3,
  0,
                                                         0]
  0,
         0,
                0,
                       0,
                              0,
                                     0,
                                          h/6, 2*h/3, h/6]
         0,
                       0,
                              0,
                                            0,
  0,
                Ο,
                                     Ο,
                                                  h/6, h/3]
```

Note: do this by hand to understand what is going on!

0.8.11 General result: the coefficient matrix is sparse

- Sparse = most of the entries are zeros
- Below: P1 elements

47


0.8.12 Exemplifying the sparsity for P2 elements


$$A = \frac{h}{30} \begin{pmatrix} 4 & 2 & -1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 2 & 16 & 2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ -1 & 2 & 8 & 2 & -1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 2 & 16 & 2 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & -1 & 2 & 8 & 2 & -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 2 & 16 & 2 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & -1 & 2 & 8 & 2 & -1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 2 & 16 & 2 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 2 & 16 & 2 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & -1 & 2 & 4 & 0 \end{pmatrix}$$

$$(60)$$

0.8.13 Matrix sparsity pattern for regular/random numbering of P1 elements


- Left: number nodes and elements from left to right
- Right: number nodes and elements arbitrarily






0.8.14 Matrix sparsity pattern for regular/random numbering of P3 elements

- Left: number nodes and elements from left to right
- Right: number nodes and elements arbitrarily





0.8.15 Sparse matrix storage and solution

The minimum storage requirements for the coefficient matrix $A_{i,j}$:

- P1 elements: only 3 nonzero entires per row
- P2 elements: only 5 nonzero entires per row
- P3 elements: only 7 nonzero entires per row
- It is important to utilize sparse storage and sparse solvers
- In Python: scipy.sparse package


0.8.16 Approximate $f \sim x^9$ by various elements; code

Compute a mesh with N_e elements, basis functions of degree d, and approximate a given symbolic expression f(x) by a finite element expansion $u(x) = \sum_j c_j \varphi_j(x)$:

```
import sympy as sm
from fe_approx1D import approximate
x = sm.Symbol('x')

approximate(f=x*(1-x)**8, symbolic=False, d=1, N_e=4)
approximate(f=x*(1-x)**8, symbolic=False, d=2, N_e=2)
approximate(f=x*(1-x)**8, symbolic=False, d=1, N_e=8)
approximate(f=x*(1-x)**8, symbolic=False, d=2, N_e=4)
```

0.8.17 Approximate $f \sim x^9$ by various elements; plot



0.9 Comparison of finite element and finite difference approximation

- Finite difference approximation of a function f(x): simply choose $u_i = f(x_i)$ (interpolation)
- Galerkin/projection and least squares method: must derive and solve a linear system
- What is *really* the difference in u?

0.9.1 Interpolation/collocation with finite elements

Let $\{x_i\}_{i\in I}$ be the nodes in the mesh. Collocation means

$$u(x_i) = f(x_i), \quad i \in I, \tag{61}$$

which translates to

$$\sum_{j \in I} c_j \varphi_j(x_i) = f(x_i),$$

but $\varphi_j(x_i) = 0$ if $i \neq j$ so the sum collapses to one term $c_i \varphi_i(x_i) = c_i$, and we have the result

$$c_i = f(x_i) (62)$$

Same result as the standard finite difference approach, but finite elements define u also between the x_i points

0.9.2 Galerkin/project and least squares vs collocation/interpolation or finite differences

- Scope: work with P1 elements
- Use projection/Galerkin or least squares (equivalent)
- Interpret the resulting linear system as finite difference equations

The P1 finite element machinery results in a linear system where equation no i is

$$\frac{h}{6}(u_{i-1} + 4u_i + u_{i+1}) = (f, \varphi_i) \tag{63}$$

Note:

- We have used u_i for c_i to make notation similar to finite differences
- The finite difference counterpart is just $u_i = f_i$

0.9.3 Expressing the left-hand side in finite difference operator notation

Rewrite the left-hand side of finite element equation no *i*:

$$h(u_i + \frac{1}{6}(u_{i-1} - 2u_i + u_{i+1})) = [h(u + \frac{h^2}{6}D_x D_x u)]_i$$
(64)

This is the standard finite difference approximation of

$$h(u + \frac{h^2}{6}u'')$$

0.9.4 Treating the right-hand side; Trapezoidal rule

$$(f,\varphi_i) = \int_{x_{i-1}}^{x_i} f(x) \frac{1}{h} (x - x_{i-1}) dx + \int_{x_i}^{x_{i+1}} f(x) \frac{1}{h} (1 - (x - x_i)) dx$$

Cannot do much unless we specialize f or use numerical integration.

Trapezoidal rule using the nodes:

$$(f,\varphi_i) = \int_{\Omega} f\varphi_i dx \approx h \frac{1}{2} (f(x_0)\varphi_i(x_0) + f(x_N)\varphi_i(x_N)) + h \sum_{j=1}^{N-1} f(x_j)\varphi_i(x_j)$$

 $\varphi_i(x_j) = \delta_{ij}$, so this formula collapses to one term:

$$(f, \varphi_i) \approx hf(x_i), \quad i = 1, \dots, N - 1.$$
 (65)

Same result as in collocation (interpolation) and the finite difference method!

0.9.5 Treating the right-hand side; Simpson's rule

$$\int_{\Omega} g(x)dx \approx \frac{h}{6} \left(g(x_0) + 2 \sum_{j=1}^{N-1} g(x_j) + 4 \sum_{j=0}^{N-1} g(x_{j+\frac{1}{2}}) + f(x_{2N}) \right),$$

Our case: $g = f\varphi_i$. The sums collapse because $\varphi_i = 0$ at most of the points.

$$(f, \varphi_i) \approx \frac{h}{3} (f_{i-\frac{1}{2}} + f_i + f_{i+\frac{1}{2}})$$
 (66)

Conclusions:

- While the finite difference method just samples f at x_i , the finite element method applies an average (smoothing) of f around x_i
- On the left-hand side we have a term $\sim hu''$, and u'' also contribute to smoothing
- There is some inherent smoothing in the finite element method

0.9.6 Finite element approximation vs finite differences

With Trapezoidal integration of (f, φ_i) , the finite element metod essentially solve

$$u + \frac{h^2}{6}u'' = f, \quad u'(0) = u'(L) = 0,$$
 (67)

by the finite difference method

$$[u + \frac{h^2}{6} D_x D_x u = f]_i \tag{68}$$

With Simpson integration of (f, φ_i) we essentially solve

$$[u + \frac{h^2}{6} D_x D_x u = \bar{f}]_i, (69)$$

where

$$\bar{f}_i = \frac{1}{3}(f_{i-1/2} + f_i + f_{i+1/2})$$

Note: as $h \to 0$, $hu'' \to 0$ and $\bar{f}_i \to f_i$.

0.9.7 Making finite elements behave as finite differences

- Can we adjust the finite element method so that we do not get the extra hu'' smoothing term and averaging of f?
- This is sometimes important in time-dependent problems to incorporate good properties of finite differences into finite elements

Result:

- Compute all integrals by the Trapezoidal method and P1 elements
- Specifically, the coefficient matrix becomes diagonal ("lumped") no linear system (!)
- Loss of accuracy? The Trapezoidal rule has error $\mathcal{O}(h^2)$, the same as the approximation error in P1 elements

0.10 Limitations of the nodes and element concepts

So far,

- Nodes: points for defining φ_i and computing u values
- Elements: subdomain (containing a few nodes)
- This is a common notion of nodes and elements

One problem:

- Our algorithms need nodes at the element boundaries
- This is often not desirable, so we need to throw the nodes and elements arrays away and find a more generalized element concept

0.11 A generalized element concept

- We introduce cell for the subdomain that we up to now called element
- A cell has *vertices* (interval end points)
- Nodes are, almost as before, points where we want to compute unknown functions
- Degrees of freedom is what the c_j represent (usually function values at nodes)

0.11.1 The concept of a finite element

- $1.\ a\ reference\ cell\ in\ a\ local\ reference\ coordinate\ system$
- 2. a set of basis functions $\tilde{\varphi}_i$ defined on the cell
- 3. a set of degrees of freedom (e.g., function values) that uniquely determine the basis functions such that $\tilde{\varphi}_i = 1$ for degree of freedom number i and $\tilde{\varphi}_i = 0$ for all other degrees of freedom
- 4. a mapping between local and global degree of freedom numbers (dof map)
- 5. a geometric mapping of the reference cell onto to cell in the physical domain: [-1,1] \Rightarrow $[x_L, x_R]$


0.11.2 Implementation; basic data structures

- Cell vertex coordinates: vertices equals nodes for P1 elements
- Element vertices: cell[e][r] holds global vertex number of local vertex no r in element e (same as elements for P1 elements)
- dof_map[e,r] maps local dof r in element e to global dof number (same as elements for Pd elements)

The assembly process applies dof_map (no more elements list!):

```
A[dof_map[e][r], dof_map[e][s]] += A_e[r,s]
b[dof_map[e][r]] += b_e[r]
```

0.11.3 Implementation; example with P2 elements



```
vertices = [0, 0.4, 1]
cells = [[0, 1], [1, 2]]
dof_map = [[0, 1, 2], [1, 2, 3]]
```

0.11.4 Implementation; example with P0 elements

Example: Same mesh, but u is piecewise constant in each cell (P0 element). Same vertices and cells, but

```
dof_map = [[0], [1], [2]]
```

May think of nodes in the middle of each element.

We will hereafter work with cells, vertices, and dof_map.

0.11.5 Example on doing the algorithmic steps


```
# Use modified fe_approx1D module
from fe_approx1D_numint import *

x = sm.Symbol('x')
f = x*(1 - x)

N_e = 10
# Create mesh
vertices, cells, dof_map = mesh_uniform(N_e, d=3, Omega=[0,1])

# Create basis functions on the mesh
phi = [basis(len(dof_map[e])-1) for e in range(N_e)]
```

0.11.6 Approximating a parabola by P0 elements



The approximate function automates the steps in the previous slide:

```
from fe_approx1D_numint import *
x=sm.Symbol("x")
for N_e in 4, 8:
    approximate(x*(1-x), d=0, N_e=N_e, Omega=[0,1])
```

0.11.7 Computing the error of the approximation; principles

$$L^2$$
 error: $||e||_{L^2} = \left(\int_{\Omega} e^2 dx\right)^{1/2}$

Accurate approximation of the integral:

- Sample u(x) at many points in each element
- u_glob does this and returns x and u
- Use the Trapezoidal rule based on the samples

0.11.8 Computing the error of the approximation; details

Note.

We need a version of the Trapezoidal rule valid for non-uniformly spaced points:

$$\int_{\Omega} g(x)dx \approx \sum_{j=0}^{n-1} \frac{1}{2} (g(x_j) + g(x_{j+1}))(x_{j+1} - x_j)$$

0.11.9 How does the error depend on h and d?

Theory and experiments show that the least squares or projection/Galerkin method in combination with Pd elements of equal length h has an error

$$||e||_{L^2} = Ch^{d+1} \tag{70}$$

where C depends on f, but not on h or d.

0.11.10 Cubic Hermite polynomials; definition

• Can we construct $\varphi_i(x)$ with continuous derivatives? Yes!

Consider a reference cell [-1,1]. We introduce two nodes, X=-1 and X=1. The degrees of freedom are

- 0: value of function at X = -1
- 1: value of first derivative at X = -1
- 2: value of function at X = 1
- 3: value of first derivative at X = 1

Derivatives as unknowns ensure the same $\varphi'_i(x)$ value at nodes and thereby continuous derivatives.

0.11.11 Cubic Hermite polynomials; derivation

4 constraints on $\tilde{\varphi}_r$ (1 for dof r, 0 for all others):

- $\tilde{\varphi}_0(X_{(0)}) = 1$, $\tilde{\varphi}_0(X_{(1)}) = 0$, $\tilde{\varphi}'_0(X_{(0)}) = 0$, $\tilde{\varphi}'_0(X_{(1)}) = 0$
- $\tilde{\varphi}'_1(X_{(0)}) = 1$, $\tilde{\varphi}'_1(X_{(1)}) = 0$, $\tilde{\varphi}_1(X_{(0)}) = 0$, $\tilde{\varphi}_1(X_{(1)}) = 0$
- $\tilde{\varphi}_2(X_{(1)}) = 1$, $\tilde{\varphi}_2(X_{(0)}) = 0$, $\tilde{\varphi}'_2(X_{(0)}) = 0$, $\tilde{\varphi}'_2(X_{(1)}) = 0$
- $\tilde{\varphi}_3'(X_{(1)}) = 1$, $\tilde{\varphi}_3'(X_{(0)}) = 0$, $\tilde{\varphi}_3(X_{(0)}) = 0$, $\tilde{\varphi}_3(X_{(1)}) = 0$

This gives 4 linear, coupled equations for each $\tilde{\varphi}_r$ to determine the 4 coefficients in the cubic polynomial. Result:

$$\tilde{\varphi}_0(X) = 1 - \frac{3}{4}(X+1)^2 + \frac{1}{4}(X+1)^3 \tag{71}$$

$$\tilde{\varphi}_1(X) = -(X+1)(1 - \frac{1}{2}(X+1))^2 \tag{72}$$

$$\tilde{\varphi}_2(X) = \frac{3}{4}(X+1)^2 - \frac{1}{2}(X+1)^3 \tag{73}$$

$$\tilde{\varphi}_3(X) = -\frac{1}{2}(X+1)(\frac{1}{2}(X+1)^2 - (X+1)) \tag{74}$$

(75)

0.12 Numerical integration

- $\int_{\Omega} f \varphi_i dx$ must in general be computed by numerical integration
- Numerical integration is often used for the matrix too

Common form:

$$\int_{-1}^{1} g(X)dX \approx \sum_{j=0}^{M} w_j \bar{X}_j,$$
 (76)

where

- \bar{X}_j are integration points
- w_i are integration weights
- Different rules correspond to different choices of points and weights

0.12.1 The Midpoint rule

Simplest possibility: the Midpoint rule,

$$\int_{-1}^{1} g(X)dX \approx 2g(0), \quad \bar{X}_{0} = 0, \ w_{0} = 2, \tag{77}$$

Exact for linear integrands

0.12.2 Newton-Cotes rules

- Idea: use a fixed, uniformly distributed set of points
- The points often coincides with nodes
- Very useful for making $\varphi_i \varphi_j = 0$ and get diagonal ("mass") matrices ("lumping").

The Trapezoidal rule:

$$\int_{-1}^{1} g(X)dX \approx g(-1) + g(1), \quad \bar{X}_{0} = -1, \ \bar{X}_{1} = 1, \ w_{0} = w_{1} = 1, \tag{78}$$

Simpson's rule:

$$\int_{-1}^{1} g(X)dX \approx \frac{1}{3} \left(g(-1) + 4g(0) + g(1) \right), \tag{79}$$

where

$$\bar{X}_0 = -1, \ \bar{X}_1 = 0, \ \bar{X}_2 = 1, \ w_0 = w_2 = \frac{1}{3}, \ w_1 = \frac{4}{3}$$
 (80)

0.12.3 Gauss-Legendre rules with optimized points

- Optimize the location of points to get higher accuracy
- Gauss-Legendre rules (quadrature) adjust points and weights to integrate polynomials exactly

$$M = 1: \quad \bar{X}_0 = -\frac{1}{\sqrt{3}}, \ \bar{X}_1 = \frac{1}{\sqrt{3}}, \ w_0 = w_1 = 1$$
 (81)

$$M = 2: \quad \bar{X}_0 = -\sqrt{\frac{3}{5}}, \ \bar{X}_0 = 0, \ \bar{X}_2 = \sqrt{\frac{3}{5}}, \ w_0 = w_2 = \frac{5}{9}, \ w_1 = \frac{8}{9}$$
 (82)

- M = 1: integrates 3rd degree polynomials exactly
- M=2: integrates 5th degree polynomials exactly
- In general, M-point rule integrates a polynomial of degree 2M + 1 exactly.

See numint.py⁶ for a large collection of Gauss-Legendre rules.

0.13 Approximation of functions in 2D

Extensibility of 1D ideas.

All the concepts and algorithms developed for approximation of 1D functions f(x) can readily be extended to 2D functions f(x,y) and 3D functions f(x,y,z). Key formulas stay the same.

Inner product in 2D:

$$(f,g) = \int_{\Omega} f(x,y)g(x,y)dxdy \tag{83}$$

Least squares and project/Galerkin lead to a linear system

$$\sum_{j \in I} A_{i,j} c_j = b_i, \quad i \in I$$
$$A_{i,j} = (\psi_i, \psi_j)$$
$$b_i = (f, \psi_i)$$

Challenge: How to construct 2D basis functions $\psi_i(x,y)$?

⁶http://tinyurl.com/jvzzcfn/fem/numint.py

0.13.1 2D basis functions as tensor products of 1D functions

Use a 1D basis for x variation and a similar for y variation:

$$V_x = \operatorname{span}\{\hat{\psi}_0(x), \dots, \hat{\psi}_{N_x}(x)\}$$
(84)

$$V_{y} = \text{span}\{\hat{\psi}_{0}(y), \dots, \hat{\psi}_{N_{y}}(y)\}$$
(85)

The 2D vector space can be defined as a tensor product $V = V_x \otimes V_y$ with basis functions

$$\psi_{p,q}(x,y) = \hat{\psi}_p(x)\hat{\psi}_q(y) \quad p \in I_x, q \in I_y.$$

0.13.2 Tensor products

Given two vectors $a = (a_0, \ldots, a_M)$ and $b = (b_0, \ldots, b_N)$, their outer tensor product, also called the dyadic product, is $p = a \otimes b$, defined through

$$p_{i,j} = a_i b_j, \quad i = 0, \dots, M, \ j = 0, \dots, N.$$

Note: p has two indices (as matrix or two-dimensional array)

2D basis as tensor product of 1D spaces:

$$\psi_{p,q}(x,y) = \hat{\psi}_p(x)\hat{\psi}_q(y), \quad p \in I_x, q \in I_y$$

0.13.3 Double or single index?

The 2D basis can employ a double index and double sum:

$$u = \sum_{p \in I_x} \sum_{q \in I_y} c_{p,q} \psi_{p,q}(x,y)$$

Or just a single index:

$$u = \sum_{i \in I} c_j \psi_i(x, y)$$

with

$$\psi_i(x,y) = \hat{\psi}_p(x)\hat{\psi}_q(y), \quad i = pN_y + q \text{ or } i = qN_x + p$$

0.13.4 Example on 2D (bilinear) basis functions; formulas

In 1D we use the basis

$$\{1, x\}$$

2D tensor product (all combinations):

$$\psi_{0,0} = 1$$
, $\psi_{1,0} = x$, $\psi_{0,1} = y$, $\psi_{1,1} = xy$


or with a single index:

$$\psi_0 = 1, \quad \psi_1 = x, \quad \psi_2 = y, \quad \psi_3 = xy$$

See notes for details of a hand-calculation.

0.13.5 Example on 2D (bilinear) basis functions; plot

Quadratic $f(x,y) = (1+x^2)(1+2y^2)$ (left), bilinear u (right):



0.13.6 Implementation; principal changes to the 1D code

Very small modification of approx1D.py:

- Omega = [[0, L_x], [0, L_y]]
- Symbolic integration in 2D
- Construction of 2D (tensor product) basis functions

0.13.7 Implementation; 2D integration

0.13.8 Implementation; 2D basis functions

Tensor product of 1D "Taylor-style" polynomials x^i :

```
def taylor(x, y, Nx, Ny):
    return [x**i*y**j for i in range(Nx+1) for j in range(Ny+1)]
```

Tensor product of 1D sine functions $\sin((i+1)\pi x)$:

Complete code in approx2D.py⁷

⁷http://tinyurl.com/jvzzcfn/fem/fe_approx2D.py

0.13.9 Implementation; application

```
f(x,y) = (1+x^2) * (1+2y^2)
```

```
>>> from approx2D import *
>>> f = (1+x**2)*(1+2*y**2)
>>> psi = taylor(x, y, 1, 1)
>>> Omega = [[0, 2], [0, 2]]
>>> u, c = least_squares(f, psi, Omega)
>>> print u
8*x*y - 2*x/3 + 4*y/3 - 1/9
>>> print sm.expand(f)
2*x**2*y**2 + x**2 + 2*y**2 + 1
```

0.13.10 Implementation; trying a perfect expansion

Add higher powers to the basis such that $f \in V$:

```
>>> psi = taylor(x, y, 2, 2)
>>> u, c = least_squares(f, psi, Omega)
>>> print u
2*x**2*y**2 + x**2 + 2*y**2 + 1
>>> print u-f
0
```

Expected: u = f when $f \in V$

0.13.11 Generalization to 3D

Key idea:

$$V = V_x \otimes V_y \otimes V_z$$

Repeated outer tensor product of multiple vectors.

$$a^{(q)} = (a_0^{(q)}, \dots, a_{N_q}^{(q)}, q = 0, \dots, m$$

$$p = a^{(0)} \otimes \dots \otimes a^{(m)}$$

$$p_{i_0, i_1, \dots, i_m} = a_{i_1}^{(0)} a_{i_1}^{(1)} \dots a_{i_m}^{(m)}$$

$$\begin{split} \psi_{p,q,r}(x,y,z) &= \hat{\psi}_p(x) \hat{\psi}_q(y) \hat{\psi}_r(z) \\ u(x,y,z) &= \sum_{p \in I_x} \sum_{q \in I_y} \sum_{r \in I_z} c_{p,q,r} \psi_{p,q,r}(x,y,z) \end{split}$$

0.14 Finite elements in 2D and 3D

The two great advantages of the finite element method:

- \bullet Can handle complex-shaped domains in 2D and 3D
- Can easily provide higher-order polynomials in the approximation

Finite elements in 1D: mostly for learning, insight, debugging

0.14.1 Examples on cell types


2D:


- \bullet triangles
- $\bullet \ \, {\rm quadrilaterals}$

3D:


- tetrahedra
- \bullet hexahedra

0.14.2 Rectangular domain with 2D P1 elements






0.14.3 Deformed geometry with 2D P1 elements




0.14.4 Rectangular domain with 2D Q1 elements




0.14.5 Basis functions over triangles in the physical domain

The P1 triangular 2D element: u is linear ax + by + c over each triangular cell




0.14.6 Basic features of 2D P1 elements

- $\varphi_r(X,Y)$ is a linear function over each element
- \bullet Cells = triangles
- Vertices = corners of the cells
- \bullet Nodes = vertices
- \bullet Degrees of freedom = function values at the nodes



0.14.8 φ_i : pyramid shape, composed of planes


- $\varphi_i(X,Y)$ varies linearly over an element
- $\varphi_i = 1$ at vertex (node) i, 0 at all other vertices (nodes)



0.14.9 Element matrices and vectors

- As in 1D, the contribution from one cell to the matrix involves just a few numbers, collected in the element matrix and vector
- $\varphi_i \varphi_j \neq 0$ only if i and j are degrees of freedom (vertices/nodes) in the same element
- $\bullet\,$ The 2D P1 has a 3×3 element matrix

0.14.10 Basis functions over triangles in the reference cell




$$\tilde{\varphi}_0(X,Y) = 1 - X - Y \tag{86}$$

$$\tilde{\varphi}_1(X,Y) = X \tag{87}$$


$$\tilde{\varphi}_2(X,Y) = Y \tag{88}$$

Higher-degree $\tilde{\varphi}_r$ introduce more nodes (dof = node values)


0.14.11 2D P1, P2, P3, P4, P5, and P6 elements



0.14.12 P1 elements in 1D, 2D, and 3D



0.14.13 P2 elements in 1D, 2D, and 3D



- ullet Interval, triangle, tetrahedron: simplex element (plural quick-form: simplices)
- Side of the cell is called *face*
- \bullet Thetrahedron has also edges

0.14.14 Affine mapping of the reference cell; formula

Mapping of local $\boldsymbol{X}=(X,Y)$ coordinates in the reference cell to global, physical $\boldsymbol{x}=(x,y)$ coordinates:


$$\boldsymbol{x} = \sum_{r} \tilde{\varphi}_{r}^{(1)}(\boldsymbol{X}) \boldsymbol{x}_{q(e,r)} \tag{89}$$

where

- \bullet r runs over the local vertex numbers in the cell
- x_i are the (x, y) coordinates of vertex i
- $\tilde{\varphi}_r^{(1)}$ are P1 basis functions

This mapping preserves the straight/planar faces and edges.

0.14.15 Affine mapping of the reference cell; figure




0.14.16 Isoparametric mapping of the reference cell

Idea: Use the basis functions of the element (not only the P1 functions) to map the element

$$\boldsymbol{x} = \sum_{r} \tilde{\varphi}_{r}(\boldsymbol{X}) \boldsymbol{x}_{q(e,r)} \tag{90}$$

Advantage: higher-order polynomial basis functions now map the reference cell to a $\it curved$ triangle or tetrahedron.



0.14.17 Computing integrals

Integrals must be transformed from $\Omega^{(e)}$ (physical cell) to $\tilde{\Omega}^r$ (reference cell):

$$\int_{\Omega^{(e)}} \varphi_i(\boldsymbol{x}) \varphi_j(\boldsymbol{x}) \, \mathrm{d}\boldsymbol{x} = \int_{\tilde{\Omega}^r} \tilde{\varphi}_i(\boldsymbol{X}) \tilde{\varphi}_j(\boldsymbol{X}) \, \mathrm{det} \, J \, \, \mathrm{d}\boldsymbol{X}$$
 (91)

$$\int_{\Omega^{(e)}} \varphi_i(\boldsymbol{x}) f(\boldsymbol{x}) \, \mathrm{d}\boldsymbol{x} = \int_{\tilde{\Omega}^r} \tilde{\varphi}_i(\boldsymbol{X}) f(\boldsymbol{x}(\boldsymbol{X})) \, \mathrm{det} \, J \, \, \mathrm{d}\boldsymbol{X}$$
(92)

where dx = dxdy or dx = dxdydz and det J is the determinant of the Jacobian of the mapping x(X).

$$J = \begin{bmatrix} \frac{\partial x}{\partial X} & \frac{\partial x}{\partial Y} \\ \frac{\partial y}{\partial X} & \frac{\partial y}{\partial Y} \end{bmatrix}, \quad \det J = \frac{\partial x}{\partial X} \frac{\partial y}{\partial Y} - \frac{\partial x}{\partial Y} \frac{\partial y}{\partial X}$$
(93)

Affine mapping (89): det $J=2\Delta,\,\Delta=$ cell volume !slide

0.14.18 Remark on going from 1D to 2D/3D

Finite elements in 2D and 3D builds on the same *ideas* and *concepts* as in 1D, but there is simply much more to compute because the specific mathematical formulas in 2D and 3D are more complicated and the book keeping with dof maps also gets more complicated. The manual work is tedious, lengthy, and error-prone so automation by the computer is a must.

0.15 Differential equation models

Our aim is to extend the ideas for approximating f by u, or solving

$$u = f$$

to real differential equations like

$$-u'' + bu = f$$
, $u(0) = 1$, $u'(L) = D$

Three methods are addressed:

- 1. least squares
- 2. Galerkin/projection
- 3. collocation (interpolation)

Method 2 will be totally dominating!

0.15.1 Abstract differential equation

$$\mathcal{L}(u) = 0, \quad x \in \Omega \tag{94}$$

Examples (1D problems):

$$\mathcal{L}(u) = \frac{d^2u}{dx^2} - f(x),\tag{95}$$

$$\mathcal{L}(u) = \frac{d}{dx} \left(\alpha(x) \frac{du}{dx} \right) + f(x), \tag{96}$$

$$\mathcal{L}(u) = \frac{d}{dx} \left(\alpha(u) \frac{du}{dx} \right) - au + f(x), \tag{97}$$

$$\mathcal{L}(u) = \frac{d}{dx} \left(\alpha(u) \frac{du}{dx} \right) + f(u, x) \tag{98}$$

0.15.2 Abstract boundary conditions

$$\mathcal{B}_0(u) = 0, \ x = 0, \quad \mathcal{B}_1(u) = 0, \ x = L$$
 (99)

Examples:

$$\mathcal{B}_i(u) = u - g,$$
 Dirichlet condition (100)

$$\mathcal{B}_i(u) = -\alpha \frac{du}{dx} - g,$$
 Neumann condition (101)

$$\mathcal{B}_i(u) = -\alpha \frac{du}{dx} - h(u - g), \qquad \text{Robin condition}$$
 (102)

0.15.3 Reminder about notation

- $u_e(x)$ is the symbol for the exact solution of $\mathcal{L}(u_e) = 0$
- u(x) denotes an approximate solution
- We seek $u \in V$
- $V = \operatorname{span}\{\psi_0(x), \dots, \psi_N(x)\}, V \text{ has basis } \{\psi_i\}_{i \in I}$
- $I = \{0, \dots, N\}$ is an index set
- $u(x) = \sum_{j \in I} c_j \psi_j(x)$
- Inner product: $(u, v) = \int_{\Omega} uv \, dx$
- Norm: $||u|| = \sqrt{(u,u)}$

0.15.4 Residual-minimizing principles

- When solving u = f we knew the error e = f u and could use principles for minimizing the error
- When solving $\mathcal{L}(u_e) = 0$ we do not know u_e and cannot work with the error $e = u_e u$
- \bullet We only have the error in the equation: the residual R

Inserting $u = \sum_{j} c_{j} \psi_{j}$ in $\mathcal{L} = 0$ gives a residual

$$R = \mathcal{L}(u) = \mathcal{L}(\sum_{j} c_{j} \psi_{j}) \neq 0$$
(103)

Goal: minimize R wrt $\{c_i\}_{i\in I}$ (and hope it makes a small e too)

$$R = R(c_0, \dots, c_N; x)$$

0.15.5 The least squares method

Idea: minimize

$$E = ||R||^2 = (R, R) = \int_{\Omega} R^2 dx \tag{104}$$

Minimization wrt $\{c_i\}_{i\in I}$ implies

$$\frac{\partial E}{\partial c_i} = \int_{\Omega} 2R \frac{\partial R}{\partial c_i} dx = 0 \quad \Leftrightarrow \quad (R, \frac{\partial R}{\partial c_i}) = 0, \quad i \in I$$
 (105)

N+1 equations for N+1 unknowns $\{c_i\}_{i\in I}$

0.15.6 The Galerkin method

Idea: make R orthogonal to V,

$$(R, v) = 0, \quad \forall v \in V \tag{106}$$

This implies

$$(R, \psi_i) = 0, \quad i \in I \tag{107}$$

N+1 equations for N+1 unknowns $\{c_i\}_{i\in I}$

0.15.7 The Method of Weighted Residuals

Generalization of the Galerkin method: demand R orthogonal to some space W, possibly $W \neq V$:

$$(R, v) = 0, \quad \forall v \in W \tag{108}$$

If $\{w_0, \ldots, w_N\}$ is a basis for W:

$$(R, w_i) = 0, \quad i \in I \tag{109}$$

- N+1 equations for N+1 unknowns $\{c_i\}_{i\in I}$
- Weighted residual with $w_i = \partial R/\partial c_i$ gives least squares

0.15.8 Terminology: test and trial Functions

- ψ_j used in $\sum_j c_j \psi_j$ is called *trial function*
- ψ_i or w_i used as weight in Galerkin's method is called test function

0.15.9 The collocation method


Idea: demand R = 0 at N + 1 points

$$R(x_i; c_0, \dots, c_N) = 0, \quad i \in I$$
 (110)

Note: The collocation method is a weighted residual method with delta functions as weights

$$0 = \int_{\Omega} R(x; c_0, \dots, c_N) \delta(x - x_i) dx = R(x_i; c_0, \dots, c_N)$$

property of
$$\delta(x)$$
: $\int_{\Omega} f(x)\delta(x-x_i)dx = f(x_i), \quad x_i \in \Omega$ (111)



0.16 Examples on using the principles

Goal.

Exemplify the least squares, Galerkin, and collocation methods in a simple 1D problem with global basis functions.

0.16.1 The first model problem

$$-u''(x) = f(x), \quad x \in \Omega = [0, L], \quad u(0) = 0, \ u(L) = 0$$
(112)

Basis functions:

$$\psi_i(x) = \sin\left((i+1)\pi\frac{x}{L}\right), \quad i \in I$$
(113)

The residual:

$$R(x; c_0, \dots, c_N) = u''(x) + f(x),$$

$$= \frac{d^2}{dx^2} \left(\sum_{j \in I} c_j \psi_j(x) \right) + f(x),$$

$$= -\sum_{j \in I} c_j \psi_j''(x) + f(x)$$
(114)

0.16.2 Boundary conditions

Since u(0) = u(L) = 0 we must ensure that all $\psi_i(0) = \psi_i(L) = 0$. Then

$$u(0) = \sum_{j} c_{j} \psi_{j}(0) = 0, \quad u(L) = \sum_{j} c_{j} \psi_{j}(L)$$

- \bullet u known: Dirichlet boundary condition
- u' known: Neumann boundary condition
- Must have $\psi_i = 0$ where Dirichlet conditions apply

0.16.3 The least squares method; principle

$$(R, \frac{\partial R}{\partial c_i}) = 0, \quad i \in I$$

$$\frac{\partial R}{\partial c_i} = \frac{\partial}{\partial c_i} \left(\sum_{j \in I} c_j \psi_j''(x) + f(x) \right) = \psi_i''(x)$$
(115)

Because:

$$\frac{\partial}{\partial c_i} \left(c_0 \psi_0'' + c_1 \psi_1'' + \dots + c_{i-1} \psi_{i-1}'' + c_i \psi_i'' + c_{i+1} \psi_{i+1}'' + \dots + c_N \psi_N'' \right) = \psi_i''$$

0.16.4 The least squares method; equation system

$$(\sum_{j} c_{j} \psi_{j}'' + f, \psi_{i}'') = 0, \quad i \in I$$
(116)

Rearrangement:

$$\sum_{i \in I} (\psi_i'', \psi_j'') c_j = -(f, \psi_i''), \quad i \in I$$
(117)

This is a linear system

$$\sum_{j \in I} A_{i,j} c_j = b_i, \quad i \in I$$

with

$$A_{i,j} = (\psi_i'', \psi_j'')$$

$$= \pi^4 (i+1)^2 (j+1)^2 L^{-4} \int_0^L \sin\left((i+1)\pi \frac{x}{L}\right) \sin\left((j+1)\pi \frac{x}{L}\right) dx$$

$$= \begin{cases} \frac{1}{2} L^{-3} \pi^4 (i+1)^4 & i=j\\ 0, & i\neq j \end{cases}$$
(118)

$$b_i = -(f, \psi_i'') = (i+1)^2 \pi^2 L^{-2} \int_0^L f(x) \sin\left((i+1)\pi \frac{x}{L}\right) dx$$
 (119)

0.16.5 Orthogonality of the basis functions gives diagonal matrix Useful property:

$$\int_{0}^{L} \sin\left((i+1)\pi\frac{x}{L}\right) \sin\left((j+1)\pi\frac{x}{L}\right) dx = \delta ij, \quad \Rightarrow (\psi_{i}'', \psi_{j}'') = \delta_{ij}, \quad \delta_{ij} = \begin{cases} \frac{1}{2}L & i=j\\ 0, & i\neq j \end{cases}$$
(120)

With diagonal $A_{i,j}$ we can easily solve for c_i :

$$c_i = \frac{2L}{\pi^2(i+1)^2} \int_0^L f(x) \sin\left((i+1)\pi \frac{x}{L}\right) dx$$
 (121)

0.16.6 Least squares method; solution

Let's sympy do the work (f(x) = 2):

```
from sympy import *
import sys

i, j = symbols('i j', integer=True)
x, L = symbols('x L')
f = 2
a = 2*L/(pi**2*(i+1)**2)
c_i = a*integrate(f*sin((i+1)*pi*x/L), (x, 0, L))
c_i = simplify(c_i)
print c_i
```

$$c_{i} = 4 \frac{L^{2} \left((-1)^{i} + 1 \right)}{\pi^{3} \left(i^{3} + 3i^{2} + 3i + 1 \right)}$$

$$u(x) = \sum_{k=0}^{N/2} \frac{8L^{2}}{\pi^{3} (2k+1)^{3}} \sin \left((2k+1)\pi \frac{x}{L} \right). \tag{122}$$

- Fast decay: $c_2 = c_0/27$, $c_4 = c_0/125$
- Only one term might be good enough

$$u(x) \approx \frac{8L^2}{\pi^3} \sin\left(\pi \frac{x}{L}\right) .$$

0.16.7 The Galerkin method; principle

$$(u'' + f, v) = 0, \quad \forall v \in V,$$

or

$$(u'', v) = -(f, v), \quad \forall v \in V \tag{123}$$

This is a variational formulation of the differential equation problem.

 $\forall v \in V$ means for all basis functions:

$$\left(\sum_{i \in I} c_j \psi_j'', \psi_i\right) = -(f, \psi_i), \quad i \in I$$
(124)

0.16.8 The Galerkin method; solution

Since $\psi_i'' \propto \psi_i$, Galerkin's method gives the same linear system and the same solution as the least squares method (in this particular example).

0.16.9 The collocation method

R=0 or the differential equation must be satisfied at N+1 points:

$$-\sum_{i\in I} c_j \psi_j''(x_i) = f(x_i), \quad i\in I$$
(125)

This is a linear system $\sum_{i} A_{i,j} = b_i$ with entries

$$A_{i,j} = -\psi_j''(x_i) = (j+1)^2 \pi^2 L^{-2} \sin\left((j+1)\pi \frac{x_i}{L}\right), \quad b_i = 2$$

Choose: $N = 0, x_0 = L/2$

$$c_0 = 2L^2/\pi^2$$

0.16.10 Comparison of the methods

- Exact solution: u(x) = x(L x)
- Galerkin or least squares (N=0): $u(x) = 8L^2\pi^{-3}\sin(\pi x/L)$
- Collocation method (N=0): $u(x) = 2L^2\pi^{-2}\sin(\pi x/L)$.
- Max error in Galerkin/least sq.: $-0.008L^2$
- Max error in collocation: $0.047L^2$

0.17 Useful techniques

0.17.1 Integration by parts

Second-order derivatives will hereafter be integrated by parts

$$\int_{0}^{L} u''(x)v(x)dx = -\int_{0}^{L} u'(x)v'(x)dx + [vu']_{0}^{L}$$

$$= -\int_{0}^{L} u'(x)v'(x)dx + u'(L)v(L) - u'(0)v(0)$$
(126)

Motivation:

- Lowers the order of derivatives
- Gives more symmetric forms (incl. matrices)
- Enables easy handling of Neumann boundary conditions
- Finite element basis functions φ_i have discontinuous derivatives (at cell boundaries) and are not suited for terms with φ_i''

0.17.2 Boundary function; principles

- What about nonzero Dirichlet conditions?
- E.g. u(L) = D
- Problem: $u(L) = \sum_{j} c_{j} \psi_{j}(L) = 0$ always
- Remedy: $u(x) = B(x) + \sum_{j} c_j \psi_j(x)$
- Construct B such that B(0) = u(0), B(L) = u(L)
- No restrictions of how B(x) varies in the interior of Ω

0.17.3 Boundary function; example

u(0) = C and u(L) = D. Choose

$$B(x) = L^{-1}(C(L-x) + Dx): B(0) = C, B(L) = D$$

$$u(x) = L^{-1}(C(L-x) + Dx) + \sum_{j \in I} c_j \psi_j(x), (127)$$

$$u(0) = C, \quad u(L) = 0$$

0.17.4 Abstract notation for variational formulations

The finite element literature (and much FEniCS documentation) applies an abstract notation for the variational formulation: *Find $(u - B) \in V$ such that

$$a(u,v) = L(v) \quad \forall v \in V$$

0.17.5 Example on abstract notation

Given a variational formulation for -u'' = f:

$$\int_{\Omega} u'v'dx = \int_{\Omega} fvdx \quad \text{or} \quad (u',v') = (f,v) \quad \forall v \in V$$

Abstract formulation: finn $(u - B) \in V$ such that

$$a(u, v) = L(v) \quad \forall v \in V$$

We identify

$$a(u, v) = (u', v'), L(v) = (f, v)$$

0.17.6 Bilinear and linear forms

- a(u, v) is a bilinear form
- L(v) is a linear form

Linear form means

$$L(\alpha_1 v_1 + \alpha_2 v_2) = \alpha_1 L(v_1) + \alpha_2 L(v_2),$$

Bilinear form means

$$a(\alpha_1 u_1 + \alpha_2 u_2, v) = \alpha_1 a(u_1, v) + \alpha_2 a(u_2, v),$$

$$a(u, \alpha_1 v_1 + \alpha_2 v_2) = \alpha_1 a(u, v_1) + \alpha_2 a(u, v_2)$$

In nonlinear problems: Find $(u - B) \in V$ such that $F(u; v) = 0 \ \forall v \in V$

0.17.7 The linear system associated with abstract form

$$a(u, v) = L(v) \quad \forall v \in V$$

is equivalent to

$$a(u, \psi_i) = L(\psi_i) \quad i \in I$$

Insert $u = \sum_{j} c_{j} \psi_{j}$ and use linearity:

$$\sum_{j \in I} a(\psi_j, \psi_i) c_j = L(\psi_i) \quad i \in I$$

This is a linear system

$$\sum_{j \in I} A_{i,j} c_j = b_i, \quad i \in I$$

with

$$A_{i,j} = a(\psi_j, \psi_i)$$
$$b_i = L(\psi_i)$$

0.17.8 Equivalence with minimization problem

If a(u, v) = a(v, u),

$$a(u, v) = L(v) \quad \forall v \in V,$$

is equivalent to minimizing the functional

$$F(v) = \frac{1}{2}a(v,v) - L(v)$$

over all functions $v \in V$. That is,

$$F(u) \le F(v) \quad \forall v \in V$$
.

- Much used in the early days of finite elements
- Still much used in structural analysis and elasticity
- Not as general as Galerkin's method (since a(u, v) = a(v, u))

0.18 Examples on variational formulations

Goal.

Derive variational formulations for many prototype differential equations in 1D that include

- variable coefficints
- mixed Dirichlet and Neumann conditions
- nonlinear coefficients

0.18.1 Variable coefficient; problem

$$-\frac{d}{dx}\left(\alpha(x)\frac{du}{dx}\right) = f(x), \quad x \in \Omega = [0, L], \ u(0) = C, \ u(L) = D.$$
 (128)

- Variable coefficient $\alpha(x)$
- Nonzero Dirichlet conditions at x = 0 and x = L
- Must have $\psi_i(0) = \psi_i(L) = 0$
- $V = \operatorname{span}\{\psi_0, \dots, \psi_N\}$
- $v \in V$: v(0) = v(L) = 0

$$u(x) = B(x) + \sum_{j \in I} c_j \psi_i(x)$$

$$B(x) = C + \frac{1}{L}(D - C)x$$

0.18.2 Variable coefficient; variational formulation (1)

$$R = -\frac{d}{dx} \left(a \frac{du}{dx} \right) - f$$

Galerkin's method:

$$(R, v) = 0, \quad \forall v \in V,$$

or with integrals:

$$\int_{\Omega} \left(\frac{d}{dx} \left(\alpha \frac{du}{dx} \right) - f \right) v \, \mathrm{d}x = 0, \quad \forall v \in V.$$

0.18.3 Variable coefficient; variational formulation (2)

Integration by parts:

$$-\int_{\Omega} \frac{d}{dx} \left(\alpha(x) \frac{du}{dx} \right) v \, dx = \int_{\Omega} \alpha(x) \frac{du}{dx} \frac{dv}{dx} \, dx - \left[\alpha \frac{du}{dx} v \right]_{0}^{L}.$$

Boundary terms vanish since v(0) = v(L) = 0

Variational formulation.

Find $(u - B) \in V$ such that

$$\int_{\Omega} \alpha(x) \frac{du}{dx} \frac{dv}{dx} dx = \int_{\Omega} f(x)v dx, \quad \forall v \in V,$$

Compact notation:

$$(\alpha u', v') = (f, v), \quad \forall v \in V$$

0.18.4 Variable coefficient; abstract notation

$$a(u, v) = L(v) \quad \forall v \in V,$$

$$a(u, v) = (\alpha u', v'), \quad L(v) = (f, v)$$

0.18.5 Variable coefficient; linear system

 $v = \psi_i$ and $u = B + \sum_j c_j \psi_j$:

$$(\alpha B' + \alpha \sum_{i \in I} c_j \psi'_j, \psi'_i) = (f, \psi_i), \quad i \in I.$$

Reorder to form linear system:

$$\sum_{j \in I} (\alpha \psi'_j, \psi'_i) c_j = (f, \psi_i) + (a(D - C)L^{-1}, \psi'_i), \quad i \in I.$$

This is $\sum_{i} A_{i,j} c_j = b_i$ with

$$A_{i,j} = (a\psi'_j, \psi'_i) = \int_{\Omega} \alpha(x)\psi'_j(x), \psi'_i(x) dx,$$

$$b_i = (f, \psi_i) + (a(D - C)L^{-1}, \psi'_i) = \int_{\Omega} \left(f(x)\psi_i(x) + \alpha(x)\frac{D - C}{L}\psi'_i(x) \right) dx.$$

0.18.6 First-order derivative in the equation and boundary condition; problem

$$-u''(x) + bu'(x) = f(x), \quad x \in \Omega = [0, L], \ u(0) = C, \ u'(L) = E$$
(129)

New features:

- first-order derivative u' in the equation
- boundary condition with u': u'(L) = E

Initial steps:

- Must force $\psi_i(0) = 0$ because of Dirichlet condition at x = 0
- Boundary function: B(x) = C(L-x)/L
- No requirements on $\psi_i(L)$ (no Dirichlet condition at x=L)

0.18.7 First-order derivative in the equation and boundary condition; details

$$u = \frac{C}{L}(L - x) + \sum_{j \in I} c_j \psi_i(x)$$

Galerkin's method: multiply by v, integrate over Ω , integrate by parts.

$$(-u'' + bu' - f, v) = 0, \quad \forall v \in V,$$

$$(u', v') + (bu', v) = (f, v) + [u'v]_0^L, \quad \forall v \in V,$$

$$(u'v') + (bu', v) = (f, v) + Ev(L), \quad \forall v \in V,$$

0.18.8 First-order derivative in the equation and boundary condition; observations

$$(u'v') + (bu', v) = (f, v) + Ev(L), \quad \forall v \in V,$$

Important:

- $[u'v]_0^L = u'(L)v(L) = Ev(L)$ because v(0) = 0 and u'(L) = E
- The boundary term can be used to implement Neumann conditions
- Forgetting the boundary term implies the condition u' = 0 (!)
- \bullet Such conditions are called $natural\ boundary\ conditions$

0.18.9 First-order derivative in the equation and boundary condition; abstract notation

Abstract notation:

$$a(u, v) = L(v) \quad \forall v \in V,$$

where

$$a(u, v) = (u', v') + (bu', v), \quad L(v) = (f + C, v) + Ev(L)$$

0.18.10 First-order derivative in the equation and boundary condition; linear system

Insert $u = B + \sum_{j} c_j \psi_j$ and $v = \psi_i$:

$$\sum_{j \in I} \underbrace{((\psi'_j, \psi'_i) + (b\psi'_j, \psi_i))}_{A_{i,j}} c_j = \underbrace{(f, \psi_i) + (bCL^{-1}, \psi'_i) + E\psi_i(L)}_{b_i}$$

Observation: $A_{i,j}$ is not symmetric because of the term

$$(b\psi'_j, \psi_i) = \int_{\Omega} b\psi'_j \psi_i dx \neq \int_{\Omega} b\psi'_i \psi_j dx = (\psi'_i, b\psi_j)$$

0.18.11 Terminology: natural and essential boundary conditions

$$(u', v') + (bu', v) = (f, v) + u'(L)v(L) - u'(0)v(0)$$

- Note: forgetting the boundary terms implies u'(L) = u'(0) = 0 (unless prescribe a Dirichlet condition)
- \bullet Conditions on u' are simply inserted in the variational form and called *natural conditions*
- Conditions on u at x = 0 requires modifying V (through $\psi_i(0) = 0$) and are known as essential conditions

Lesson learned.

It is easy to forget the boundary term when integrating by parts. That mistake may prescribe a condition on u'!

0.18.12 Nonlinear coefficient; problem

$$-(\alpha(u)u')' = f(u), \quad x \in [0, L], \ u(0) = 0, \ u'(L) = E.$$
(130)

- V: basis $\{\psi_i\}_{i\in I}$ with $\psi_i(0)=0$ because of u(0)=0
- How does the nonlinear coefficient $\alpha(u)$ impact the variational formulation?

0.18.13 Nonlinear coefficient; variational formulation

Galerkin: multiply by v, integrate, integrate by parts

$$\int_0^L \alpha(u) \frac{du}{dx} \frac{dv}{dx} dx = \int_0^L f(u)v dx + [\alpha(u)vu']_0^L \quad \forall v \in V$$

- $\alpha(u(0))v(0)u'(0) = 0$ since v(0)
- $\alpha(u(L))v(L)u'(L) = \alpha(u(L))v(L)E$ since u'(L) = E

$$\int_0^L \alpha(u) \frac{du}{dx} \frac{dv}{dx} v \, dx = \int_0^L f(u)v \, dx + \alpha(u(L))v(L)E \quad \forall v \in V$$

or

$$(\alpha(u)u', v') = (f(u), v) + \alpha(L)v(L)E \quad \forall v \in V$$

0.18.14 Nonlinear coefficient; where does the nonlinearity cause challenges?

- Abstract notation: no a(u, v) and L(v) because a and L are nonlinear
- Abstract notation: $F(u; v) = 0 \ \forall v \in V$
- What about forming a linear system? We get a nonlinear system of algebraic equations
- Must use methods like Picard iteration or Newton's method to solve nonlinear algebraic equations
- But: the variational formulation was not much affected by nonlinearities

0.18.15 Computing with Dirichlet and Neumann conditions; problem

$$-u''(x) = f(x), \quad x \in \Omega = [0, 1], \quad u'(0) = C, \ u(1) = D$$

- Use a global polynomial basis $\psi_i \sim x^i$ on [0,1]
- Because of u(1) = D: $\psi_i(1) = 0$
- Basis: $\psi_i(x) = (1-x)^{i+1}, i \in I$
- \bullet B(x) = Dx

0.18.16 Computing with Dirichlet and Neumann conditions; details

$$A_{i,j} = (\psi'_j, \psi'_i) = \int_0^1 \psi'_i(x)\psi'_j(x)dx = \int_0^1 (i+1)(j+1)(1-x)^{i+j}dx,$$

$$b_i = (2, \psi_i) - (D, \psi_i') - C\psi_i(0)$$

=
$$\int_0^1 (2(1-x)^{i+1} - D(i+1)(1-x)^i) dx - C\psi_i(0)$$

Can easily do the integrals with sympy. N = 1:

$$\begin{pmatrix} 1 & 1 \\ 1 & 4/3 \end{pmatrix} \begin{pmatrix} c_0 \\ c_1 \end{pmatrix} = \begin{pmatrix} -C+D+1 \\ 2/3-C+D \end{pmatrix}$$
$$c_0 = -C+D+2, \quad c_1 = -1,$$

$$u(x) = 1 - x^2 + D + C(x - 1)$$
 (exact solution)

0.18.17 When the numerical method is exact

Let

$$u = B + F$$
, $F \in Va(B + F, v) = L(v)$ $\forall v \in Vu_e = B + E$, $E \in Va(B + E, v) = L(v)$ $\forall v \in Vu_e = B + E$

Subtract: a(F - E, v) = 0 and E = F.

Apart from boundary conditions, u_e lies in the same as we seek u. Then $u = u_e$.

!split ====== Computing with finite elements ======

Tasks:

* Address the model problem -u''(x) = 2, u(0) = u(L) = 0 * Uniform finite element mesh with P1 elements * Show all finite element computations in detail

!split ====== Variational formulation, finite element mesh, and basis ======

$$-u''(x) = 2$$
, $x \in (0, L)$, $u(0) = u(L) = 0$,

Variational formulation:

$$(u', v') = (2, v) \quad \forall v \in V$$

Since u(0) = 0 and u(L) = 0, we must force

$$v(0) = v(L) = 0, \quad \psi_i(0) = \psi_i(L) = 0$$

Use finite element basis, but exclude φ_0 and φ_{N_n} since these are not 0 on the boundary:

$$\psi_i = \varphi_{i+1}, \quad i = 0, \dots, N = N_n - 2$$

$$u = \sum_{j \in I} c_j \varphi_{\nu(i)}, \quad i = 0, \dots, N, \quad \nu(j) = j + 1$$

Irregular numbering: more complicated $\nu(j)$ mapping


0.18.18 Computation in the global physical domain; formulas

$$A_{i,j} = \int_0^L \varphi'_{i+1}(x)\varphi'_{j+1}(x)dx, \quad b_i = \int_0^L 2\varphi_{i+1}(x)dx$$

 $i+1 \rightarrow i, j+1 \rightarrow j$

$$A_{i-1,j-1} = \int_0^L \varphi_i'(x)\varphi_j'(x) dx, \quad b_{i-1} = \int_0^L 2\varphi_i(x) dx$$

0.18.19 Computation in the global physical domain; details



$$\varphi_i = \pm h^{-1}$$

$$A_{i-1,i-1} = h^{-2}2h = 2h^{-1}, \quad A_{i-1,i-2} = h^{-1}(-h^{-1})h = -h^{-1}, \quad A_{i-1,i} = A_{i-1,i-2}$$

$$b_{i-1} = 2(\frac{1}{2}h + \frac{1}{2}h) = 2h$$

0.18.20 Computation in the global physical domain; linear system

0.18.21 Comparison with a finite difference discretization

- Recall: $c_i = u(x_{i+1}) \equiv u_{i+1}$
- Write out a general equation at node i-1, expressed by u_i

$$-\frac{1}{h}u_{i-1} + \frac{2}{h}u_i - \frac{1}{h}u_{i+1} = 2h \tag{132}$$

The standard finite difference method for -u'' = 2 is

$$-\frac{1}{h^2}u_{i-1} + \frac{2}{h^2}u_i - \frac{1}{h^2}u_{i+1} = 2$$

The finite element method and the finite difference method are identical in this example.

(Remains to study the equations involving boundary values)

0.18.22 Cellwise computations; formulas

- Repeat the previous example, but apply the cellwise algorithm
- Work with one cell at a time
- Thansform physical cell to reference cell $X \in [-1, 1]$

$$\begin{split} A_{i-1,j-1}^{(e)} &= \int_{\Omega^{(e)}} \varphi_i'(x) \varphi_j'(x) \, \mathrm{d}x = \int_{-1}^1 \frac{d}{dx} \tilde{\varphi}_r(X) \frac{d}{dx} \tilde{\varphi}_s(X) \frac{h}{2} \, \mathrm{d}X, \\ \tilde{\varphi}_0(X) &= \frac{1}{2} (1-X), \quad \tilde{\varphi}_1(X) = \frac{1}{2} (1+X) \\ &\frac{d\tilde{\varphi}_0}{dX} = -\frac{1}{2}, \quad \frac{d\tilde{\varphi}_1}{dX} = \frac{1}{2} \end{split}$$

From the chain rule

$$\frac{d\tilde{\varphi}_r}{dx} = \frac{d\tilde{\varphi}_r}{dX} \frac{dX}{dx} = \frac{2}{h} \frac{d\tilde{\varphi}_r}{dX}$$

0.18.23 Cellwise computations; details

$$A_{i-1,j-1}^{(e)} = \int_{\Omega^{(e)}} \varphi_i'(x) \varphi_j'(x) \, \mathrm{d}x = \int_{-1}^1 \frac{2}{h} \frac{d\tilde{\varphi}_r}{dX} \frac{2}{h} \frac{d\tilde{\varphi}_s}{dX} \frac{h}{2} \, \mathrm{d}X$$
$$b_{i-1}^{(e)} = \int_{\Omega^{(e)}} 2\varphi_i(x) \, \mathrm{d}x = \int_{-1}^1 2\tilde{\varphi}_r(X) \frac{h}{2} \, \mathrm{d}X, \quad i = q(e,r), \ r = 0, 1$$

Must run through all r, s = 0, 1 and r = 0, 1 and compute each entry in the element matrix and vector:

$$\tilde{A}^{(e)} = \frac{1}{h} \begin{pmatrix} 1 & -1 \\ -1 & 1 \end{pmatrix}, \quad \tilde{b}^{(e)} = h \begin{pmatrix} 1 \\ 1 \end{pmatrix}. \tag{133}$$

0.18.24 Cellwise computations; details of boundary cells

- The boundary cells involve only one unknown
- $\Omega^{(0)}$: left node value known, only a contribution from right node
- $\Omega^{(N_e)}$: right node value known, only a contribution from left node

$$\tilde{A}^{(e)} = \frac{1}{h} (1), \quad \tilde{b}^{(e)} = h (1), \quad e = 0, \ e = N_e$$

Only one degree of freedom ("node") in these cells (r = 0)

0.18.25 Cellwise computations; assembly

4 P1 elements:

```
vertices = [0, 0.5, 1, 1.5, 2]
cells = [[0, 1], [1, 2], [2, 3], [3, 4]]
dof_map = [[0], [0, 1], [1, 2], [2]]
```

Python code for the assembly algorithm:

Result: same linear system

0.19 Boundary conditions: specified nonzero value

0.19.1 General construction of a boundary function

- B(x) is not always easy to construct (extend to the interior of Ω), at least not in 2D and 3D
- With finite element φ_i , B(x) can be constructed in a completely general way
- I_b : set of indices with nodes where u is known
- U_i : Dirichlet value of u at node $i, i \in I_b$

$$B(x) = \sum_{j \in I_b} U_j \varphi_j(x), \tag{134}$$

1D: $I_b = \{1, N_n\}$

$$u(x) = U_0 \varphi_0(x) + U_{N_n} \varphi_{N_n}(x) + \sum_{j \in I} i e_j \varphi_{\nu(j)}, \quad \nu(j) = j + 1, \ N = N_n - 2$$
 (135)

0.19.2 Example with two Dirichlet values; variational formulation

$$-u'' = 2$$
, $u(0) = C$, $u(L) = D$

$$(u', v') = (2, v) \quad \forall v \in V$$

Insert $u = B + \sum_{j} c_{j} \psi_{j}$ in variational formulation:

$$A_{i,j} = \int_0^L \psi_i'(x)\psi_j'(x) dx, \quad b_i = \int_0^L (f(x) - B'(x))\psi_i(x) dx$$

0.19.3 Example with two Dirichlet values; details

$$\psi_i = \varphi_{i+1}, i = 0, \dots, N = N_n - 2$$

$$u(x) = \underline{0 \cdot \varphi_0 + D\varphi_{N_n}}_{B(x)} + \sum_{j \in I} c_j \varphi_{j+1} \qquad = D\varphi_{N_n} + c_0 \varphi_1 + c_1 \varphi_2 + \dots + c_N \varphi_{N_n-1}.$$

$$A_{i-1,j-1} = \int_0^L \varphi_i'(x)\varphi_j'(x) dx, \quad b_{i-1} = \int_0^L (f(x) - D\varphi_{N_n}'(x))\varphi_i(x) dx,$$

for $i, j = 1, \dots, N + 1 = N_n - 1$.

New boundary term from B': -D/2

0.19.4 Example with two Dirichlet values; cellwise computations

- Element matrices as in the previous example (with u=0 on the boundary)
- New element vector

$$\tilde{b}_0^{(e)} = \int_{-1}^1 \left(f - D \frac{2}{h} \frac{\tilde{\varphi}_1}{dX} \right) \tilde{\varphi}_0 \frac{h}{2} dX = \left(\frac{h}{2} (2 - D \frac{2}{h} \frac{1}{2}) \int_{-1}^1 \tilde{\varphi}_0 dX = h - D/2, \quad e = N_e = N_n - 1$$

0.19.5 Modification of the linear system; ideas

- Method 1: incorporate Dirichlet values through a B(x) function and demand $\psi_i = 0$ where Dirichlet values apply
- Method 2: drop B(x), drop demands to ψ_i , just assemble as if there were no Dirichlet conditions, and modify the linear system instead

Method 2: $\psi_i = \varphi_i$

$$u(x) = \sum_{j \in I} c_j \varphi_j(x), \quad I = \{0, \dots, N = N_n\}$$
 (136)

u is treated as unknown at x = 0 and x = L

0.19.6 Modification of the linear system; linear system

$$-u'' = 2$$
, $u(0) = 0$, $u(L) = D$

$$\frac{1}{h} \begin{pmatrix}
1 & -1 & 0 & \cdots & \cdots & \cdots & \cdots & 0 \\
-1 & 2 & -1 & \ddots & & & & \vdots \\
0 & -1 & 2 & -1 & \ddots & & & \vdots \\
\vdots & \ddots & \ddots & \ddots & \ddots & \ddots & \vdots \\
\vdots & & & 0 & -1 & 2 & -1 & \ddots & \vdots \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & \vdots \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & & \ddots & \ddots & \ddots & \ddots & -1 \\
0 & \cdots & \cdots & \cdots & \cdots & 0 & -1 & 1
\end{pmatrix}
\begin{pmatrix}
c_0 \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ c_N
\end{pmatrix} = \begin{pmatrix}
h \\ 2h \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ 2h \\ h
\end{pmatrix}$$
(137)

0.19.7 Modification of the linear system; modifications

- Dirichlet condition $u(x_i) = U_i$ means $c_i = U_i$ (since $c_i = u(x_i)$)
- Replace first row by $c_0 = 0$
- Replace last row by $c_N = D$

$$\frac{1}{h} \begin{pmatrix}
1 & 0 & 0 & \cdots & \cdots & \cdots & \cdots & 0 \\
-1 & 2 & -1 & \ddots & & & & \vdots \\
0 & -1 & 2 & -1 & \ddots & & & \vdots \\
\vdots & \ddots & & \ddots & \ddots & \ddots & \ddots & \vdots \\
\vdots & & & 0 & -1 & 2 & -1 & \ddots & \vdots \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & & \ddots & \ddots & \ddots & \ddots & -1 \\
0 & \cdots & \cdots & \cdots & \cdots & 0 & 0 & 1
\end{pmatrix}
\begin{pmatrix}
c_0 \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ c_N
\end{pmatrix} = \begin{pmatrix}
0 \\ 2h \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ 2h \\ D
\end{pmatrix}$$
(138)

0.19.8 Modification of the linear system; element matrix/vector

In cell 0 we know u for local node (degree of freedom) r=0 and replace the first cell equation by $\tilde{c}_0=0$:

$$\tilde{A}^{(0)} = A = \frac{1}{h} \begin{pmatrix} 1 & 0 \\ -1 & 1 \end{pmatrix}, \quad \tilde{b}^{(0)} = \begin{pmatrix} 0 \\ h \end{pmatrix}$$
 (139)

In cell N_e we know u for local node r=1 and replace the last equation in the cell system by $\tilde{c}_1=D$:

$$\tilde{A}^{(N_e)} = A = \frac{1}{h} \begin{pmatrix} 1 & -1 \\ 0 & 1 \end{pmatrix}, \quad \tilde{b}^{(N_e)} = \begin{pmatrix} h \\ D \end{pmatrix}$$
(140)

0.19.9 Symmetric modification of the linear system; algorithm

- The modification above destroys symmetry of the matrix: $A_{0,1} \neq A_{1,0}$)
- Symmetry is often important in 2D and 3D (faster computations)
- A more complex modification preserves symmetry

Algorithm for incorporating $c_i = U_i$:

- 1. Subtract column i times U_i from the right-hand side
- 2. Zero out column and row no i
- 3. Place 1 on the diagonal
- 4. Set $b_i = U_i$

0.19.10 Symmetric modification of the linear system; example

$$\begin{pmatrix}
1 & 0 & 0 & \cdots & \cdots & \cdots & \cdots & 0 \\
0 & 2 & -1 & \ddots & & & & \vdots \\
0 & -1 & 2 & -1 & \ddots & & & \vdots \\
\vdots & \ddots & \ddots & \ddots & \ddots & \ddots & \vdots \\
\vdots & & & 0 & -1 & 2 & -1 & \ddots & \vdots \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
\vdots & & & & & \ddots & \ddots & \ddots & \ddots & 0 \\
0 & \cdots & \cdots & \cdots & \cdots & \cdots & 0 & 0 & 1
\end{pmatrix}
\begin{pmatrix}
c_0 \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ c_N
\end{pmatrix}
=
\begin{pmatrix}
0 \\ 2h \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ 2h + D/h \\ D
\end{pmatrix}$$
(141)

0.19.11 Modification of the element matrix and vector

- Modification of the linear system can be done in the the element matrix and vector instead
- Exactly the same procedure

Last degree of freedom in the last element is prescribed:

$$\tilde{A}^{(N-1)} = A = \frac{1}{h} \begin{pmatrix} 1 & -1 \\ 0 & 1 \end{pmatrix}, \quad \tilde{b}^{(N-1)} = \begin{pmatrix} h \\ D \end{pmatrix}$$
 (142)

Or symmetric modification:

$$\tilde{A}^{(N-1)} = A = \frac{1}{h} \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}, \quad \tilde{b}^{(N-1)} = \begin{pmatrix} h + D/h \\ D \end{pmatrix}$$
 (143)

0.20 Boundary conditions: specified derivative

Focus: how to incorporate u'(0) = C with finite elements.

Index

```
approximation
                                                 sparse matrices, 44
    by sines, 16
                                                 test function, 66
    collocation, 18
                                                 test space, 66
    of functions, 9
                                                 Trapezoidal rule, 52
    of general vectors, 9
                                                 trial function, 66
cells list, 48
                                                 trial space, 66
collocation method (approximation), 18
                                                 vertices list, 48
dof map, 48
dof_map list, 48
edges, 62
faces, 62
finite element, definition, 48
Galerkin method, 9
Gauss-Legendre quadrature, 53
integration by parts, 72
isoparametric mapping, 63
Lagrange (interpolating) polynomial, 19
lumped mass matrix, 47
mapping of reference cells
    isoparametric mapping, 63
mass lumping, 47
mass matrix, 47
Midpoint rule, 52
numerical integration
    Midpoint rule, 52
    Simpson's rule, 52
    Trapezoidal rule, 52
projection, 9
simplex elements, 62
simplices, 62
Simpson's rule, 52
```