

# CS3315 Project: Random Forest Classifier

```
In [1]: import numpy as np
import pandas as pd
from sklearn.linear_model import Perceptron
```

```
In [2]: # import data
filename = 'data/2020.06.19.csv'
df = pd.read_csv(filename)

# sample small subset
# df = df.sample(500000, random_state=78)
df.info()
df.head(2)
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 765360 entries, 0 to 765359
Data columns (total 16 columns):
#   Column          Non-Null Count  Dtype
---  -
0   avg_ip_t        765360 non-null  float64
1   bytes_in        765360 non-null  int64
2   bytes_out       765360 non-null  int64
3   dest_ip         765360 non-null  int64
4   dest_port       740863 non-null  float64
5   entropy         765360 non-null  float64
6   num_pkts_out    765360 non-null  int64
7   num_pkts_in     765360 non-null  int64
8   proto           765360 non-null  int64
9   src_ip          765360 non-null  int64
10  src_port        740863 non-null  float64
11  time_end        765360 non-null  int64
12  time_start      765360 non-null  int64
13  total_entropy   765360 non-null  float64
14  label           765360 non-null  object
15  duration        765360 non-null  float64
dtypes: float64(6), int64(9), object(1)
memory usage: 93.4+ MB
```

```
Out[2]:
```

	avg_ip_t	bytes_in	bytes_out	dest_ip	dest_port	entropy	num_pkts_out	num_pkts_in	protc
0	7.5	342	3679	786	9200.0	5.436687	2	2	€
1	0.0	0	0	786	55972.0	0.000000	1	1	€

```
In [3]: # clean data
df.dropna(inplace=True)
df.isna().sum()

# need to clean for features that are 0 and don't make sense (bytes = 0?)
```

```
Out[3]: avg_ipt      0
        bytes_in    0
        bytes_out    0
        dest_ip      0
        dest_port    0
        entropy      0
        num_pkts_out 0
        num_pkts_in  0
        proto        0
        src_ip       0
        src_port     0
        time_end     0
        time_start   0
        total_entropy 0
        label        0
        duration     0
        dtype: int64
```

```
In [4]: print('label values:', df['label'].unique())

def ordinal_encoder(category):
    dict = {'benign':0, 'outlier':1, 'malicious':2}
    return dict[category]

print('benign', ordinal_encoder('benign'))
print('outlier', ordinal_encoder('outlier'))
print('malicious', ordinal_encoder('malicious'))
df['label'] = df['label'].apply(ordinal_encoder)

label values: ['benign' 'outlier' 'malicious']
benign 0
outlier 1
malicious 2
```

```
In [5]: features = ['avg_ipt',
                    'bytes_in',
                    'bytes_out',
                    'dest_ip',
                    'dest_port',
                    'entropy',
                    'num_pkts_in',
                    'num_pkts_out',
                    'proto',
                    'src_ip',
                    'src_port',
                    'time_end',
                    'time_start',
                    'total_entropy',
                    'duration']

X = df.loc[:, features]
y = df.loc[:, 'label']
```

```
In [13]: # test/train split

from sklearn.model_selection import train_test_split

# 80/20 training/validation split
X_train, X_val, y_train, y_val = train_test_split(X,y, train_size=.8, test_s

y_train = y_train.to_numpy()
y_val = y_val.to_numpy()

# should print number of shape: (num features, num entries)
print('Training set: ', 'X: ', X_train.shape, 'y: ', y_train.shape, 'Validat

Training set: X: (592690, 15) y: (592690,) Validation set: X: (148173,
15) printy: (148173,)
```

```
In [33]: from sklearn.ensemble import RandomForestClassifier

rfc = RandomForestClassifier(n_estimators=1000,
                             max_depth=30,
                             max_leaf_nodes=16,
                             n_jobs=-1,
                             min_samples_leaf=100,
                             min_samples_split=100)

rfc.fit(X_train, y_train)
```

```
Out[33]: ▼                                RandomForestClassifier

RandomForestClassifier(max_depth=30, max_leaf_nodes=16, min_samples
_leaf=100,
                        min_samples_split=100, n_estimators=1000, n_
jobs=-1)
```

```
In [34]: y_pred = rfc.predict(X_val)
```


```
In [35]: from sklearn.tree import export_graphviz

export_graphviz(rfc.estimators_[900], out_file='rfctree.dot',
                feature_names = features,
                class_names = ['benign', 'outlier', 'malicious'],
                rounded = True, proportion = False,
                precision = 2, filled = True)

from subprocess import call
call(['dot', '-Tpng', 'rfctree.dot', '-o', 'tree.png', '-Gdpi=600'])

# Display in jupyter notebook
from IPython.display import Image
Image(filename = 'tree.png')
```

Out [35]:



```
In [36]: # plot loss vs. accuracy (HOML p. 305)
#import matplotlib.pyplot as plt
#pd.DataFrame(history.history).plot()
#plt.grid(True)
#plt.gca().set_ylim(0,1)
#plt.show()
```

```
In [37]: from sklearn.metrics import *
print("Predicted labels:\t", y_pred)
print("Actual labels:\t\t", y_val)
print(classification_report(y_val, y_pred))
```

Predicted labels:	[0 1 0 ... 2 2 2]
Actual labels:	[0 1 0 ... 2 2 1]
	precision recall f1-score support
0	0.99 1.00 1.00 75511
1	1.00 0.42 0.59 24572
2	0.77 0.99 0.87 48090
accuracy	0.90 148173
macro avg	0.92 0.80 0.82 148173
weighted avg	0.92 0.90 0.89 148173

## Validate Model with Data from June 2022

```
In [38]: # import data
filename = 'data/2020.06.20.csv'
df2 = pd.read_csv(filename)

# sample small subset
#df2 = df2.sample(n=100000, random_state=78)
df2.info()
df2.head(2)
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 770853 entries, 0 to 770852
Data columns (total 16 columns):
#   Column                Non-Null Count  Dtype
---  -
0   avg_ipt                770853 non-null float64
1   bytes_in               770853 non-null int64
2   bytes_out              770853 non-null int64
3   dest_ip                770853 non-null int64
4   dest_port              770853 non-null int64
5   entropy                770853 non-null float64
6   num_pkts_out           770853 non-null int64
7   num_pkts_in            770853 non-null int64
8   proto                  770853 non-null int64
9   src_ip                 770853 non-null int64
10  src_port                770853 non-null int64
11  time_end                770853 non-null int64
12  time_start              770853 non-null int64
13  total_entropy           770853 non-null float64
14  label                   770853 non-null object
15  duration                770853 non-null float64
dtypes: float64(4), int64(11), object(1)
memory usage: 94.1+ MB
```

```
Out[38]:
```

	avg_ipt	bytes_in	bytes_out	dest_ip	dest_port	entropy	num_pkts_out	num_pkts_in	pro
0	34.57143	34	29	786	5900	5.040459	7	10	
1	37.00000	34	29	786	5900	5.127916	7	10	

```
In [39]: # clean data
df2.dropna(inplace=True)
df2.isna().sum()
```

```
Out[39]: avg_ipt      0
         bytes_in    0
         bytes_out    0
         dest_ip      0
         dest_port    0
         entropy      0
         num_pkts_out  0
         num_pkts_in  0
         proto        0
         src_ip       0
         src_port     0
         time_end     0
         time_start   0
         total_entropy 0
         label        0
         duration     0
         dtype: int64
```

```
In [40]: print('label values:', df2['label'].unique())

def ordinal_encoder(category):
    dict = {'benign':0, 'outlier':1, 'malicious':2}
    return dict[category]

print('benign', ordinal_encoder('benign'))
print('outlier', ordinal_encoder('outlier'))
print('malicious', ordinal_encoder('malicious'))
df2['label'] = df2['label'].apply(ordinal_encoder)

label values: ['malicious' 'benign' 'outlier']
benign 0
outlier 1
malicious 2
```

```
In [41]: features = ['avg_ipt',
                     'bytes_in',
                     'bytes_out',
                     'dest_ip',
                     'dest_port',
                     'entropy',
                     'num_pkts_in',
                     'num_pkts_out',
                     'proto',
                     'src_ip',
                     'src_port',
                     'time_end',
                     'time_start',
                     'total_entropy',
                     'duration']

X_22 = df2.loc[:, features]
y_22 = df2.loc[:, 'label']
```

```
In [42]: # change labels to numpy
         y_22 = y_22.to_numpy()
```

```
In [43]: # test predictions
X_test_new = X_22
test_pred_22 = rfc.predict(X_test_new)
```

```
In [44]: print("Predicted labels:\t", test_pred_22)
print("Actual labels:\t\t", y_22)
print(classification_report(y_22, test_pred_22))
```

```
Predicted labels:      [2 2 2 ... 2 2 2]
Actual labels:        [2 2 2 ... 1 1 2]

              precision    recall  f1-score   support

     0           0.99         1.00         0.99       366310
     1           0.30         0.13         0.18        69389
     2           0.84         0.93         0.88       335154

 accuracy                   0.89       770853
 macro avg           0.71         0.69         0.69       770853
 weighted avg        0.86         0.89         0.87       770853
```

```
In [ ]:
```