```
Last login: Sun Oct 12 18:55:22 2025
07:11 greg@xcf16 ~ ?
07:11 greg@xcf16 ~ ? res
Script started, output file is /Users/f16/16sessions/251013-071154-term-session.session
07:11 greg@xcf16 ~ ?
07:11 greg@xcf16 ~ ? ssh 172.18.250.1 -llbucsadmin
Unauthorized access prohibited. This product or the use of this
product is covered by one or more of the following U.S. Patents:
9,626,224; 9,613,071; 9,584,403; 9,549,048; 9,438,538; 9,397,951;
9,363,309; 9,363,248; 9,253,277; 9,191,342; 9,152,574; 9,143,455;
9.130,991; 9.092,342; 9.036,662; 8.930,650; 8.929,402; 8.929,380;
8,885,632; 8,811,431; 8,755,381; 8,743,683; 8,738,865; 8,732,423;
8,725,988; 8,595,314; 8,489,562; 8,473,714; 8,442,052; 8,392,684;
8,370,583; 8,312,226; 8,307,115; 8,225,072; 8,171,238; 8,095,774;
7,948,921; 7,945,736; 7,698,431; 7,644,230; 7,630,295; 7,571,344.
By using this product, you agree to be bound by the terms of Silver
Peak Systems Inc. End User License Agreement.
The End User License Agreement can be viewed at
```

http://www.silver-peak.com/download/latest/EULA.html

You are accessing a HPE Aruba Networking Information System (IS) that is provided for HPE Aruba Networking Simulated-authorized use only.

By using this IS (which includes any device attached to this IS), you consent to the following conditions:

- -HPE Aruba Networking routinely intercepts and monitors communications on this IS for purposes including, but not limited to, penetration testing, network operations and defense, and personnel misconduct (PM).
- -At any time, HPE Aruba Networking may inspect and seize data stored on this IS.
- -Communications using, or data stored on, this IS are not private, are subject to routine monitoring, interception, and search, and may be disclosed or used for any HPE Aruba Networking-authorized purpose.
- -This IS includes security measures (e.g., authentication and access controls) to protect HPE Aruba Networking interests--not for your personal benefit or privacy.
- -Notwithstanding the above, using this IS does not constitute consent to PM investigative searching or monitoring of the content of privileged communications, or work product, related to personal representation or services by attorneys, psychotherapists, or clergy, and their assistants. Such communications and work product are private and confidential. See User Agreement for details.

```
(lbucsadmin@172.18.250.1) Password:
```

Last login: Mon Oct 13 01:40:53 2025 from 172.18.250.2

You are accessing a HPE Aruba Networking Information System (IS) that is provided for HPE Aruba Networking Simulated-authorized use only.

By using this IS (which includes any device attached to this IS), you consent to the following conditions:

- -HPE Aruba Networking routinely intercepts and monitors communications on this IS for purposes including, but not limited to, penetration testing, network operations and defense, and personnel misconduct (PM).
- -At any time, HPE Aruba Networking may inspect and seize data stored on this IS.
- -Communications using, or data stored on, this IS are not private, are subject to routine monitoring, interception, and search, and may be disclosed or used for any HPE Aruba Networking-authorized purpose.

-This IS includes security measures (e.g., authentication and access controls) to protect HPE Aruba Networking interests--not for your personal benefit or privacy.

-Notwithstanding the above, using this IS does not constitute consent to PM investigative searching or monitoring of the content of privileged communications, or work product, related to personal representation or services by attorneys, psychotherapists, or clergy, and their assistants. Such communications and work product are private and confidential. See User Agreement for details.

KW-10106 >KW-10106 > enKW-10106 # sh interfaces Interface cpkt datapath state Admin up: yes Link up: IPv6 address: fe80::a8ce:61ff:fe2e:18a1/64 N/A Speed: Duplex: N/A Interface type: ethernet MTU: 1500 HW address: AA:CE:61:2E:18:A1 RX bytes: RX packets: RX mcast packets: 0 RX discards: RX errors: RX overruns: RX frame: TX bytes: TX packets: TX discards: TX errors: TX overruns: TX carrier: 0 TX collisions: 0 Interface ids tap0 state Admin up: yes Link up: IPv6 address: fe80::64d8:8eff:fe67:7bea/64 Speed: N/A Duplex: N/A
Interface type: ethernet MTU: 1526 HW address: 66:D8:8E:67:7B:EA RX bytes: RX packets: RX mcast packets: 0 RX discards: RX errors: RX overruns: RX frame: TX bytes: TX packets: 0 TX discards: TX errors: TX overruns: TX carrier:

```
TX collisions:
Interface ids tap1 state
   Admin up:
  Link up:
   IPv6 address:
                      fe80::a8a6:94ff:fe25:ad8d/64
   Speed:
                      N/A
   Duplex:
                      N/A
   Interface type:
                      ethernet
  MTU:
                      1526
   HW address:
                      AA:A6:94:25:AD:8D
   RX bytes:
   RX packets:
                      0
   RX mcast packets:
   RX discards:
   RX errors:
   RX overruns:
   RX frame:
                      0
   TX bytes:
   TX packets:
  TX discards:
  TX errors:
   TX overruns:
  TX carrier:
   TX collisions:
Interface ids tap4096 state
   Admin up:
   Link up:
                      fe80::18c1:ebff:fe9c:b78b/64
   IPv6 address:
   Speed:
                      N/A
                      N/A
   Duplex:
   Interface type:
                      ethernet
  MTU:
  HW address:
                      1A:C1:EB:9C:B7:8B
   RX bytes:
   RX packets:
   RX mcast packets:
  RX discards:
   RX errors:
   RX overruns:
   RX frame:
   TX bytes:
   TX packets:
   TX discards:
  TX errors:
   TX overruns:
   TX carrier:
  TX collisions:
Interface ids tap out0 state
  Admin up:
                      yes
   Link up:
                      fe80::e035:d3ff:fe9b:5833/64
   IPv6 address:
```

N/A

Speed:

```
Duplex:
                     N/A
  Interface type:
                     ethernet
  MTU:
                     1526
  HW address:
                    E2:35:D3:9B:58:33
  RX bytes:
  RX packets:
  RX mcast packets:
  RX discards:
  RX errors:
                     0
  RX overruns:
  RX frame:
                     0
  TX bytes:
  TX packets:
  TX discards:
  TX errors:
  TX overruns:
                     0
  TX carrier:
                     0
  TX collisions:
Interface ids tap out1 state
  Admin up:
  Link up:
                     fe80::c8c1:dcff:fe93:f3ca/64
  IPv6 address:
  Speed:
                     N/A
                     N/A
  Duplex:
  Interface type:
                     ethernet
  MTU:
                     1526
  HW address:
                     CA:C1:DC:93:F3:CA
  RX bytes:
  RX packets:
  RX mcast packets: 0
  RX discards:
  RX errors:
  RX overruns:
                     0
  RX frame:
                     0
  TX bytes:
  TX packets:
  TX discards:
  TX errors:
  TX overruns:
  TX carrier:
  TX collisions:
                     0
Interface ids tap out4096 state
  Admin up:
  Link up:
                     fe80::8cea:c9ff:fec9:919e/64
  IPv6 address:
  Speed:
                     N/A
  Duplex:
                     N/A
  Interface type:
                     ethernet
                     9000
  HW address:
                     8E:EA:C9:C9:91:9E
  RX bytes:
  RX packets:
                     0
```

```
RX mcast packets: 0
  RX discards:
  RX errors:
  RX overruns:
  RX frame:
  TX bytes:
  TX packets:
  TX discards:
  TX errors:
  TX overruns:
  TX carrier:
  TX collisions:
Interface ips tap0 state
  Admin up:
  Link up:
                     yes
  IPv6 address:
                     fe80::3496:dff:fe80:221f/64
  Speed:
                     N/A
  Duplex:
                     N/A
  Interface type:
                     ethernet
  MTU:
                     1526
  HW address:
                     36:96:0D:80:22:1F
  RX bytes:
  RX packets:
  RX mcast packets: 0
  RX discards:
  RX errors:
  RX overruns:
  RX frame:
  TX bytes:
  TX packets:
  TX discards:
  TX errors:
  TX overruns:
  TX carrier:
  TX collisions:
Interface ips tap1 state
  Admin up:
  Link up:
  IPv6 address:
                     fe80::90de:b5ff:fe93:da80/64
  Speed:
                     N/A
  Duplex:
                     N/A
  Interface type:
                     ethernet
  MTU:
                     1526
  HW address:
                     92:DE:B5:93:DA:80
  RX bytes:
  RX packets:
  RX mcast packets:
  RX discards:
  RX errors:
                     0
  RX overruns:
  RX frame:
  TX bytes:
```

```
TX packets:
  TX discards:
  TX errors:
  TX overruns:
  TX carrier:
                      0
  TX collisions:
                      0
Interface ips tap4096 state
  Admin up:
  Link up:
                      yes
                      fe80::c826:a7ff:fe76:98d0/64
  IPv6 address:
  Speed:
                     N/A
  Duplex:
                      N/A
  Interface type:
                      ethernet
  MTU:
                      9000
                      CA:26:A7:76:98:D0
  HW address:
  RX bytes:
  RX packets:
  RX mcast packets: 0
  RX discards:
  RX errors:
  RX overruns:
  RX frame:
                      0
  TX bytes:
  TX packets:
  TX discards:
                      0
  TX errors:
  TX overruns:
  TX carrier:
  TX collisions:
Interface ips tap out0 state
  Admin up:
  Link up:
  IPv6 address:
                      fe80::4c11:e8ff:fe97:b8c1/64
  Speed:
                     N/A
                      N/A
  Duplex:
  Interface type:
                      ethernet
  MTU:
                      1526
  HW address:
                      4E:11:E8:97:B8:C1
  RX bytes:
  RX packets:
  RX mcast packets:
                      0
  RX discards:
  RX errors:
  RX overruns:
  RX frame:
                      0
  TX bytes:
                      0
  TX packets:
  TX discards:
  TX errors:
                      0
  TX overruns:
  TX carrier:
  TX collisions:
```

```
Interface ips tap out1 state
   Admin up:
   Link up:
   IPv6 address:
                    fe80::3821:5eff:fe64:4e9/64
   Speed:
                     N/A
                     N/A
   Duplex:
   Interface type:
                     ethernet
  MTU:
                     1526
   HW address:
                     3A:21:5E:64:04:E9
   RX bytes:
   RX packets:
   RX mcast packets:
   RX discards:
   RX errors:
   RX overruns:
   RX frame:
   TX bytes:
   TX packets:
                     0
  TX discards:
  TX errors:
  TX overruns:
   TX carrier:
   TX collisions:
Interface ips tap out4096 state
   Admin up:
   Link up:
                     yes
   IPv6 address:
                   fe80::fc44:f7ff:fecf:8/64
   Speed:
                   N/A
   Duplex:
                     N/A
                     ethernet
   Interface type:
                     9000
  MTU:
                     FE:44:F7:CF:00:08
   HW address:
   RX bytes:
   RX packets:
   RX mcast packets: 0
   RX discards:
   RX errors:
   RX overruns:
   RX frame:
   TX bytes:
   TX packets:
   TX discards:
  TX errors:
   TX overruns:
  TX carrier:
  TX collisions:
Interface ipsec decrypt state
  Admin up:
                     yes
   Link up:
   IPv6 address:
                     fe80::c4c0:c8ff:fe01:dc17/64
   Speed:
                     N/A
   Duplex:
                     N/A
   Interface type:
                     ethernet
```

```
MTU:
                      1500
                      C6:C0:C8:01:DC:17
   HW address:
   RX bytes:
   RX packets:
   RX mcast packets:
   RX discards:
   RX errors:
   RX overruns:
   RX frame:
                      0
                      0
  TX bytes:
   TX packets:
   TX discards:
   TX errors:
   TX overruns:
   TX carrier:
   TX collisions:
Interface ipsec encrypt state
   Admin up:
   Link up:
   IPv6 address:
                      fe80::fc32:65ff:fe61:316a/64
                      N/A
   Speed:
   Duplex:
                      N/A
   Interface type:
                      ethernet
  MTU:
   HW address:
                      FE:32:65:61:31:6A
   RX bytes:
   RX packets:
   RX mcast packets:
  RX discards:
  RX errors:
   RX overruns:
   RX frame:
   TX bytes:
   TX packets:
   TX discards:
  TX errors:
  TX overruns:
   TX carrier:
  TX collisions:
Interface lan0 state
  Admin up:
                      yes
   Link up:
   IPv4 address:
                      192.168.21.1
   Netmask:
                      255.255.255.0
   Speed:
                      UNKNOWN
   Duplex:
                      UNKNOWN
   Interface type:
                      ethernet
  MTU:
   HW address:
                      00:1B:BC:29:35:4A
   PoE enabled:
                      yes
   RX bytes:
                      0
```

RX packets: RX mcast packets: 0 RX discards: RX errors: RX overruns: 0 RX frame: TX bytes: TX packets: TX discards: 0 TX errors: TX overruns: TX carrier: TX collisions: 0 Interface lan1 state Admin up: Link up: yes 172.18.1.1 IPv4 address: Netmask: 255.255.255.0 IPv6 address: fe80::21b:bcff:fe29:354b/64 Speed: 100Mb/s Duplex: full Interface type: ethernet MTU: 1500 HW address: 00:1B:BC:29:35:4B PoE enabled: yes RX bytes: 35304577 RX packets: 94453 RX mcast packets: 48525 RX discards: 48481 RX errors: Ω 0 RX overruns: RX frame: TX bytes: 30741546 TX packets: 45108 TX discards: TX errors: 0 TX overruns: 0 TX carrier: TX collisions: Interface lan2 state Admin up: yes Link up: Speed: UNKNOWN Duplex: UNKNOWN Interface type: ethernet MTU: 1500 HW address: 00:1B:BC:29:35:4C Combo port type: RJ45 0 RX bytes: RX packets: RX mcast packets:

RX discards: RX errors: RX overruns: RX frame: TX bytes: TX packets: TX discards: TX errors: TX overruns: 0 TX carrier: TX collisions: Interface lo state Admin up: yes Link up: yes IPv4 address: 127.0.0.1 Netmask: 255.0.0.0 ::1/128 IPv6 address: Speed: N/A Duplex: N/A Interface type: loopback MTU: 16436 HW address: N/A RX bytes: 168163 RX packets: 1011 RX mcast packets: RX discards: RX errors: 0 RX overruns: RX frame: TX bytes: 168163 TX packets: 1011 TX discards: TX errors: 0 TX overruns: TX carrier: TX collisions: Interface lo20000 state Admin up: yes Link up: IPv4 address: 10.250.28.131 Netmask: 255.255.255.255 fe80::90c5:f3ff:fe48:6255/64 IPv6 address: Speed: N/A Duplex: N/A Interface type: ethernet 1500 HW address: 92:C5:F3:48:62:55 RX bytes: RX packets: RX mcast packets: 0 RX discards: RX errors:

RX overruns:

```
RX frame:
                      0
   TX bytes:
   TX packets:
  TX discards:
  TX errors:
   TX overruns:
   TX carrier:
   TX collisions:
Interface mgmt0 state
   Admin up:
   Link up:
                      yes
   IPv4 address:
                      172.18.250.1
   Netmask:
                      255.255.255.0
                      fe80::21b:bcff:fe29:3548/64
   IPv6 address:
   Speed:
                      1000Mb/s
   Duplex:
                      full
   Interface type:
                      ethernet
  MTU:
                      1500
  HW address:
                      00:1B:BC:29:35:48
   RX bytes:
                      425782
                      5189
   RX packets:
   RX mcast packets:
                      0
   RX discards:
   RX errors:
                       Ω
   RX overruns:
                      0
   RX frame:
                      439269
   TX bytes:
                      2968
   TX packets:
   TX discards:
                      0
   TX errors:
  TX overruns:
   TX carrier:
   TX collisions:
                      0
Interface mgmt1 state
   Admin up:
                      yes
  Link up:
   IPv4 address:
                      169.254.0.1
  Netmask:
                      255.255.0.0
   Speed:
                      UNKNOWN
                      UNKNOWN
   Duplex:
                      ethernet
   Interface type:
                      1500
                      00:1B:BC:29:35:49
   HW address:
   RX bytes:
   RX packets:
   RX mcast packets:
   RX discards:
   RX errors:
   RX overruns:
                      0
   RX frame:
   TX bytes:
   TX packets:
```

```
TX discards:
   TX errors:
  TX overruns:
   TX carrier:
  TX collisions:
                      0
Interface pim0 state
   Admin up:
  Link up:
                      yes
   IPv4 address:
                      169.254.124.1
   Netmask:
                      255.255.255.0
                      fe80::84f4:17ff:fe82:9a9b/64
   IPv6 address:
   Speed:
                      N/A
   Duplex:
                      N/A
   Interface type:
                      ethernet
  MTU:
                      1500
   HW address:
                      86:F4:17:82:9A:9B
   RX bytes:
   RX packets:
   RX mcast packets:
   RX discards:
   RX errors:
                       0
   RX overruns:
   RX frame:
   TX bytes:
                      0
   TX packets:
   TX discards:
  TX errors:
  TX overruns:
  TX carrier:
  TX collisions:
Interface pim1 state
  Admin up:
   Link up:
                       yes
   IPv4 address:
                      169.254.125.1
                      255.255.255.0
   Netmask:
   IPv6 address:
                      fe80::b844:8cff:fe9d:a5a6/64
   Speed:
                      N/A
   Duplex:
                      N/A
   Interface type:
                      ethernet
                      1500
   HW address:
                      BA:44:8C:9D:A5:A6
   RX bytes:
   RX packets:
   RX mcast packets:
   RX discards:
   RX errors:
   RX overruns:
   RX frame:
                      0
   TX bytes:
   TX packets:
                      0
   TX discards:
                      0
   TX errors:
```

TX overruns:

```
TX carrier:
                      0
   TX collisions:
Interface pim2 state
   Admin up:
                      yes
  Link up:
                      yes
   IPv4 address:
                      169.254.126.1
  Netmask:
                      255.255.255.0
   IPv6 address:
                      fe80::b053:72ff:fe5d:77d9/64
   Speed:
                      N/A
   Duplex:
                      N/A
   Interface type:
                      ethernet
  MTU:
                      1500
  HW address:
                      B2:53:72:5D:77:D9
   RX bytes:
   RX packets:
   RX mcast packets:
   RX discards:
   RX errors:
  RX overruns:
   RX frame:
   TX bytes:
   TX packets:
   TX discards:
   TX errors:
   TX overruns:
                      0
   TX carrier:
  TX collisions:
Interface pimreg state
   Admin up:
   Link up:
                      yes
                      N/A
   Speed:
   Duplex:
                      N/A
   Interface type:
                      pim-register
                      1472
                      00:00:00:00:00:00
   HW address:
   RX bytes:
   RX packets:
   RX mcast packets:
   RX discards:
   RX errors:
   RX overruns:
                      0
   RX frame:
   TX bytes:
   TX packets:
  TX discards:
   TX errors:
  TX overruns:
   TX carrier:
   TX collisions:
                      0
Interface proxy wan0 state
  Admin up:
  Link up:
                      yes
```

IPv6 address: fe80::4031:6dff:feb7:12d6/64 Speed: N/A Duplex: N/A Interface type: ethernet MTU: 1500 HW address: 42:31:6D:B7:12:D6 RX bytes: RX packets: RX mcast packets: RX discards: RX errors: 0 RX overruns: RX frame: 0 TX bytes: TX packets: TX discards: TX errors: 0 TX overruns: TX carrier: TX collisions: Interface sp lan state Admin up: yes Link up: IPv6 address: fe80::942c:34ff:feb8:7f59/64 N/A Speed: Duplex: N/A Interface type: ethernet MTU: 96:2C:34:B8:7F:59 HW address: 156664270 RX bytes: RX packets: 443867 RX mcast packets: 0 RX discards: 0 0 RX errors: 0 RX overruns: RX frame: TX bytes: 121315655 TX packets: 412033 TX discards: TX errors: TX overruns: 0 TX carrier: TX collisions: Interface sp wan state Admin up: Link up: IPv6 address: fe80::d858:8dff:fec7:dbf0/64 Speed: N/A N/A Duplex: Interface type: ethernet 1500 MTU: DA:58:8D:C7:DB:F0 HW address:

```
RX bytes:
                     124293705
  RX packets:
                     412033
  RX mcast packets: 0
  RX discards:
  RX errors:
                     0
  RX overruns:
  RX frame:
  TX bytes:
                     159769534
  TX packets:
                     443837
  TX discards:
  TX errors:
  TX overruns:
  TX carrier:
                     0
  TX collisions:
Interface tpepd lan0 state
  Admin up:
  Link up:
  IPv6 address:
                     fe80::4cba:2aff:fe3e:9e39/64
  Speed:
                     N/A
  Duplex:
                     N/A
  Interface type:
                     ethernet
                     1500
  MTU:
  HW address:
                     4E:BA:2A:3E:9E:39
  RX bytes:
  RX packets:
  RX mcast packets: 0
  RX discards:
  RX errors:
  RX overruns:
  RX frame:
  TX bytes:
  TX packets:
  TX discards:
                     0
  TX errors:
  TX overruns:
  TX carrier:
  TX collisions:
Interface tpepd wan0 state
  Admin up:
  Link up:
                     yes
  IPv6 address:
                     fe80::fc54:c2ff:fee0:976e/64
  Speed:
                     N/A
                     N/A
  Duplex:
  Interface type:
                     ethernet
  MTU:
                     1500
  HW address:
                     FE:54:C2:E0:97:6E
  RX bytes:
  RX packets:
  RX mcast packets:
                     0
  RX discards:
  RX errors:
                     Ω
  RX overruns:
  RX frame:
```

TX bytes: TX packets: TX discards: TX errors: TX overruns: TX carrier: TX collisions: Interface wan0 state Admin up: yes Link up: yes IPv6 address: fe80::21b:bcff:fe29:354d/64 1000Mb/s Speed: Duplex: full Interface type: ethernet 1500 HW address: 00:1B:BC:29:35:4D RX bytes: 461832 RX packets: 2866 RX mcast packets: RX discards: 0 RX errors: RX overruns: RX frame: 3026089 TX bytes: TX packets: 11219 TX discards: 0 TX errors: TX overruns: TX carrier: TX collisions: Interface wan1 state Admin up: yes Link up: yes IPv4 address: 10.0.0.6 Netmask: 255.255.255.0 fe80::21b:bcff:fe29:354e/64 IPv6 address: Speed: 1000Mb/s Duplex: full Interface type: ethernet MTII: HW address: 00:1B:BC:29:35:4E RX bytes: 2669260 RX packets: 15624 RX mcast packets: 4511 4511 RX discards: RX errors: Ω RX overruns: 0 RX frame: TX bytes: 1730893 TX packets: 13713 TX discards: TX errors: 0

```
TX overruns:
                       0
   TX carrier:
   TX collisions:
Interface wan2 state
   Admin up:
                       yes
   Link up:
                       yes
   IPv4 address:
                       192.168.86.28
   Netmask:
                       255.255.255.0
   IPv6 address:
                       fe80::21b:bcff:fe29:354f/64
   Speed:
                       100Mb/s
   Duplex:
                       full
   Interface type:
                       ethernet
   MTU:
                       1500
   HW address:
                       00:1B:BC:29:35:4F
   Combo port type:
                       RJ45
   RX bytes:
                       247528745
   RX packets:
                       1121619
   RX mcast packets:
                       46592
   RX discards:
                       46398
   RX errors:
                       0
   RX overruns:
                       0
   RX frame:
   TX bytes:
                       283009592
   TX packets:
                       1058451
   TX discards:
   TX errors:
   TX overruns:
   TX carrier:
   TX collisions:
KW-10106 # sh sub
subif subnet
KW-10106 # sh subnet
Auto-subnet : enabled (use system auto-subnet to change)
Add-local : disabled, metric 50
OSPF Redistribution - disabled, metric 50, redist filter 0, local filter 0
Admin Distance: Local = 1, IBGP = 200, EBGP = 20, Sub-Shared = 10, BGP-Rem = 15, OSPF = 110, OSPF-REM = 15, System Default = 251
Route Table: 24/95536 entries
          prefix/len
                                               metric peer id
                                                                        community
                                                                                             AS path
                                                                                                                   details
                                  nexthop
                                                                 saas
      172.17.43.0/32
                                                   50 2074338
                                                                 Ω
                                                                                                                   LRN SPS HUB, 107.215.36.181
                                                                        N/A
                                                                                             N/A
    10.250.28.139/32
                                                  100 2074338
                                                                 0
                                                                        N/A
                                                                                             N/A
                                                                                                                   LRN SPS HUB, 107.215.36.181
                                                                                                                   LRN SPS HUB, 107.215.36.181
                                                   50 2074338
    10.250.28.132/32
                                                                 Ω
                                                                        N/A
                                                                                             N/A
                                                   50 2700616
                                                                        N/A
                                                                                                                   AUTO ADV LOCAL
    10.250.28.131/32
                                                                 0
                                                                                             N/A
    10.250.28.130/32
                                                 100 2074338
                                                                 0
                                                                        N/A
                                                                                             N/A
                                                                                                                   LRN SPS HUB, 107.215.36.181
                                                                 0
    192.168.86.0/24
                                                   50 2700616
                                                                        N/A
                                                                                             N/A
                                                                                                                   AUTO LOCAL
     192.168.86.0/24
                                                 100 2074338
                                                                 0
                                                                        N/A
                                                                                                                   LRN SPS HUB, 107.215.36.181
                                                                                             N/A
     192.168.21.0/24
                                                   50 2700616
                                                                 0
                                                                        N/A
                                                                                             N/A
                                                                                                                   AUTO ADV LOCAL
       172.28.1.0/24
                              198.15.99.8
                                                   1 2700616
                                                                 0
                                                                        N/A
                                                                                             N/A
                                                                                                                   AUTO ADV MGMT
       172.28.1.0/24
                                                 100 2074338
                                                                 0
                                                                        N/A
                                                                                             N/A
                                                                                                                   LRN SPS HUB, 107.215.36.181
                                                                        N/A
                                                                                                                   AUTO ADV LOCAL
      172.18.1.0/24
                                                   50 2700616
                                                                 0
                                                                                             N/A
      172.16.33.0/24
                                                   50 2074338
                                                                 0
                                                                        N/A
                                                                                             N/A
                                                                                                                   LRN SPS HUB, 107.215.36.181
    169.254.126.0/24
                                                   50 2700616
                                                                 0
                                                                        N/A
                                                                                             N/A
                                                                                                                   AUTO LOCAL
    169.254.125.0/24
                                                   50 2700616
                                                                 0
                                                                        N/A
                                                                                             N/A
                                                                                                                   AUTO LOCAL
                                                                 0
                                                                                                                   AUTO LOCAL
    169.254.124.0/24
                                                   50 2700616
                                                                        N/A
                                                                                             N/A
         12.0.0.0/24
                                 10.0.0.1
                                                   50 2700616
                                                                 0
                                                                        N/A
                                                                                             N/A
                                                                                                                   CFG ADV LOCAL
                                                                 0
                                                                        N/A
         12.0.0.0/24
                                                  100 2074338
                                                                                             N/A
                                                                                                                   LRN SPS HUB, 107.215.36.181
```

```
10.0.16.0/24
                                            100 2074338
                                                             N/A
                                                         0 N/A
        10.0.0.0/24
                                            100 2074338
                                                        0 N/A
        10.0.0.0/24
                                            50 2700616
         0.0.0.0/0 192.168.86.1
                                          1251 2700616 0 N/A
         0.0.0.0/0
                                                        0 N/A
                                            50 2074338
                                                        0 N/A
         0.0.0.0/0
                              10.0.0.1
                                           3655 2700616
                                           50 2074338 0 N/A
          fd::/128
KW-10106 # sh tunnel
Tunnel to Baton-Rouge-EC CaptWhite(bondedTunnel 208) state
 Admin:
 Oper:
                    Up - Idle
                    1d 1h 50m 56s
 Uptime:
 Type:
                    Bonded
 MTU:
                    1488
 Tag name:
                    CaptWhite
 ID:
                    16
 Bonded ID:
 Peer ID:
                    2074338
 Bound tunnels:
                    to Baton-Rouge-EC INET2-INET1(tunnel 222)(*)($)
 Tunnel black list
 Tunnel brown list
 Tunnel green list
                     0x1
 Tunnel current list 0x1
 Tunnel curr ids list (15)
 Bonded tunnel state brown 0
 Bonded tunnel state brown Latency 0
 Bonded tunnel state brown Loss 0
 Bonded tunnel state brown Jitter 0
LAN Rx Bytes: 260
   Tx Bytes:
   Rx Pkts:
                    5
   Tx Pkts:
   Tx Invalid Pkts: 0
WAN Rx Bytes:
   Tx Bytes:
                    720
   Rx Pkts:
                    Ω
   Tx Pkts:
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel to Baton-Rouge-EC DefaultOverlay(bondedTunnel 27) state
 Admin:
 Oper:
                    Up - Active
 Uptime:
                    1d 1h 50m 56s
                    Bonded
 Type:
 MTU:
                    1488
 Tag name:
                    DefaultOverlay
 ID:
 Bonded ID:
 Peer ID:
                    2074338
 Bound tunnels:
                     to Baton-Rouge-EC INET2-INET1 (tunnel 222) (*) ($)
 Tunnel black list
                     0x0
 Tunnel brown list
                     0x0
 Tunnel green list
 Tunnel current list 0x1
```

N/A

N/A

N/A

N/A

N/A

N/A

N/A

LRN SPS HUB, 107.215.36.181

LRN SPS HUB, 107.215.36.181

LRN SPS HUB, 107.215.36.181

LRN SPS HUB, 107.215.36.181

AUTO ADV LOCAL

AUTO FROM LAN

AUTO FROM WAN

```
Tunnel curr ids list (15)
  Bonded tunnel state brown 0
  Bonded tunnel state brown Latency 0
  Bonded tunnel state brown Loss 0
  Bonded tunnel state brown Jitter 0
LAN Rx Bytes: 29990560
                   29974134
   Tx Bytes:
   Rx Pkts:
                   43183
    Tx Pkts:
                     43181
    Tx Invalid Pkts: 0
                     32771808
WAN Rx Bytes:
    Tx Bytes:
                     33101440
    Rx Pkts:
                     41418
   Tx Pkts:
                     43083
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel to Baton-Rouge-EC CriticalApps (bondedTunnel 28) state
  Admin:
  Oper:
                     Up - Idle
                   1d 1h 50m 56s
  Uptime:
  Type:
                   Bonded
                    1488
  MTU:
  Tag name:
                   CriticalApps
  ID:
  Bonded ID:
  Peer ID:
                     2074338
  Bound tunnels:
                     to Baton-Rouge-EC INET2-INET1(tunnel 222)(*)($)
  Tunnel black list
                      0 \times 0
  Tunnel brown list
                       0 \times 0
  Tunnel green list
                       0x1
  Tunnel current list 0x1
  Tunnel curr ids list (15)
  Bonded tunnel state brown 0
  Bonded tunnel state brown Latency 0
  Bonded tunnel state brown Loss 0
  Bonded tunnel state brown Jitter 0
LAN Rx Bytes: 0
   Tx Bytes:
   Rx Pkts:
    Tx Pkts:
    Tx Invalid Pkts: 0
WAN Rx Bytes:
    Tx Bytes:
    Rx Pkts:
   Tx Pkts:
   Rx Invalid Pkts: 0
    Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel to Baton-Rouge-EC RealTime (bondedTunnel 29) state
  Admin:
                     Up - Idle
  Oper:
```

```
Uptime:
                     1d 1h 50m 56s
  Type:
                     Bonded
  MTU:
                     1488
                  RealTime
  Tag name:
  ID:
                     22
  Bonded ID:
  Peer ID:
                     2074338
  Bound tunnels:
                     to Baton-Rouge-EC INET2-INET1(tunnel 222)(*)($)
  Tunnel black list
  Tunnel brown list
  Tunnel green list
                      0x1
  Tunnel current list 0x1
  Tunnel curr ids list (15)
  Bonded tunnel state brown 0
  Bonded tunnel state brown Latency 0
  Bonded tunnel state brown Loss 0
  Bonded tunnel state brown Jitter 0
LAN Rx Bytes: 0
   Tx Bytes:
   Rx Pkts:
   Tx Pkts:
   Tx Invalid Pkts: 0
WAN Rx Bytes:
    Tx Bytes:
   Rx Pkts:
   Tx Pkts:
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel to Baton-Rouge-EC BulkApps (bondedTunnel 30) state
  Admin: up
                     Up - Idle
  Oper:
  Uptime:
                    1d 1h 50m 56s
                     Bonded
  Type:
  MTU:
                    1488
                 BulkApps
  Tag name:
  ID:
  Bonded ID:
  Peer ID:
                     2074338
  Bound tunnels:
                     to Baton-Rouge-EC INET2-INET1(tunnel 222)(*)($)
  Tunnel black list
  Tunnel brown list
  Tunnel green list
                      0x1
  Tunnel current list 0x1
  Tunnel curr ids list (15)
  Bonded tunnel state brown 0
  Bonded tunnel state brown Latency 0
  Bonded tunnel state brown Loss 0
  Bonded tunnel state brown Jitter 0
LAN Rx Bytes: 0
   Tx Bytes:
   Rx Pkts:
   Tx Pkts:
   Tx Invalid Pkts: 0
```

```
WAN Rx Bytes:
   Tx Bytes:
   Rx Pkts:
   Tx Pkts:
   Rx Invalid Pkts: 0
   Rx Lost Pkts: 0
   Rx Duplicate Pkts: 0
Tunnel Passthrough INET2 CaptWhite(passThrough 216) state
  Admin:
                     up
  Oper:
                     Up - Active
  Uptime:
                    1d 1h 51m 17s
  Tunnel ID:
  Local IP address: 192.168.86.28
  Remote IP address: 0.0.0.0
  Remote Appliance ID: 1
  MTU:
                     1500
LAN Rx Bytes:
   Tx Bytes:
   Rx Pkts:
   Tx Pkts:
   Tx Invalid Pkts: 0
WAN Rx Bytes:
   Tx Bytes:
   Rx Pkts:
   Tx Pkts:
   Rx Invalid Pkts: 0
   Rx Lost Pkts: 0
   Rx Duplicate Pkts: 0
Tunnel Passthrough INET2 wan2 (passThrough 217) state
  Admin:
  Oper:
                     Up - Active
  Uptime:
                     1d 1h 51m 17s
  Tunnel ID:
  Local IP address: 192.168.86.28
  Remote IP address: 0.0.0.0
  Remote Appliance ID: 1
                     1500
  MTU:
LAN Rx Bytes:
   Tx Bytes:
   Rx Pkts:
   Tx Pkts:
   Tx Invalid Pkts: 0
WAN Rx Bytes:
   Tx Bytes:
                     0
   Rx Pkts:
                     0
   Tx Pkts:
   Rx Invalid Pkts: 0
```

```
Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel Passthrough INET2 RealTime(passThrough 218) state
  Admin:
                      up
  Oper:
                      Up - Active
  Uptime:
                      1d 1h 51m 17s
  Tunnel ID:
  Local IP address: 192.168.86.28
  Remote IP address: 0.0.0.0
  Remote Appliance ID: 2
                      1500
LAN Rx Bytes:
                      28120
   Tx Bytes:
                      35328
   Rx Pkts:
                      370
    Tx Pkts:
                      368
    Tx Invalid Pkts: 0
WAN Rx Bytes:
                      35328
    Tx Bytes:
                      28120
   Rx Pkts:
                      368
   Tx Pkts:
                      370
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel Passthrough INET2 CriticalApps(passThrough 219) state
  Admin:
  Oper:
                      Up - Active
  Uptime:
                      1d 1h 51m 17s
  Tunnel ID:
  Local IP address: 192.168.86.28
  Remote IP address: 0.0.0.0
  Remote Appliance ID: 3
  MTU:
LAN Rx Bytes:
                      66547545
   Tx Bytes:
                      25420586
   Rx Pkts:
                      116810
    Tx Pkts:
                      85050
    Tx Invalid Pkts: 0
WAN Rx Bytes:
                      25420586
    Tx Bytes:
                      66547545
   Rx Pkts:
                      85050
   Tx Pkts:
                      116810
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel Passthrough INET2 BulkApps (passThrough 220) state
```

```
Local IP address: 192.168.86.28
  Remote IP address: 0.0.0.0
  Remote Appliance ID: 4
  MTU:
                     1500
LAN Rx Bytes:
   Tx Bytes:
                     0
   Rx Pkts:
    Tx Pkts:
    Tx Invalid Pkts: 0
WAN Rx Bytes:
    Tx Bytes:
   Rx Pkts:
   Tx Pkts:
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel Passthrough INET2 DefaultOverlay(passThrough 221) state
  Admin:
  Oper:
                     Up - Active
                    1d 1h 51m 17s
  Uptime:
  Tunnel ID:
                     14
  Local IP address: 192.168.86.28
  Remote IP address: 0.0.0.0
  Remote Appliance ID: 1
  MTU:
                     1500
LAN Rx Bytes:
   Tx Bytes:
   Rx Pkts:
    Tx Pkts:
    Tx Invalid Pkts: 0
WAN Rx Bytes:
    Tx Bytes:
    Rx Pkts:
   Tx Pkts:
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel Passthrough FSE lan0 (passThrough 225) state
  Admin:
                     up
  Oper:
                     Down
  Uptime:
                     0s
  Tunnel ID:
                     19
  Local IP address: 192.168.21.1
  Remote IP address: 0.0.0.0
  Remote Appliance ID: 1
  MTU:
                     1500
LAN Rx Bytes:
   Tx Bytes:
                     0
   Rx Pkts:
   Tx Pkts:
```

```
Tx Invalid Pkts: 0
WAN Rx Bytes:
    Tx Bytes:
    Rx Pkts:
   Tx Pkts:
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel Passthrough OVERLAY L1 lan1(passThrough 232) state
  Oper:
                     Up - Active
                     1d 1h 51m 15s
  Uptime:
  Tunnel ID:
                     31
  Local IP address: 172.18.1.1
  Remote IP address: 0.0.0.0
  Remote Appliance ID: 1
  MTU:
                     1500
LAN Rx Bytes:
                     168
   Tx Bytes:
                     208
   Rx Pkts:
                     2
    Tx Pkts:
    Tx Invalid Pkts: 0
                     208
WAN Rx Bytes:
    Tx Bytes:
                     168
   Rx Pkts:
   Tx Pkts:
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
   Rx Duplicate Pkts: 0
Tunnel Passthrough wan1 (passThrough 239) state
  Admin:
                     up
  Oper:
                     Up - Active
  Uptime:
                   21h 3m 10s
  Tunnel ID:
  Local IP address: 10.0.0.6
  Remote IP address: 0.0.0.0
  Remote Appliance ID: 1
  MTU:
                    1500
LAN Rx Bytes:
   Tx Bytes:
                     104
   Rx Pkts:
                     1
   Tx Pkts:
                     1
    Tx Invalid Pkts: 0
WAN Rx Bytes:
                     104
    Tx Bytes:
   Rx Pkts:
                     1
   Tx Pkts:
                     1
   Rx Invalid Pkts: 0
    Rx Lost Pkts:
    Rx Duplicate Pkts: 0
```

```
Tunnel to Baton-Rouge-EC INET2-INET1 (tunnel 222) state
  Admin:
  Oper:
                     Up - Active
                     1d 1h 50m 58s
  Uptime:
  Tunnel ID:
                     15
  Local IP address:
                     192.168.86.28
  Remote IP address: 107.215.36.181
  Remote Appliance ID: 2074338
  MTU:
                     1488
LAN Rx Bytes:
                     29990820
    Tx Bytes:
                     29790886
    Rx Pkts:
                     43188
    Tx Pkts:
                     41419
    Tx Invalid Pkts:
WAN Rx Bytes:
                     32771808
    Tx Bytes:
                     33102160
   Rx Pkts:
                     41418
   Tx Pkts:
                     43088
   Rx Invalid Pkts: 0
   Rx Lost Pkts:
                     0
    Rx Duplicate Pkts: 0
KW-10106 # sh management riu
% Unrecognized command "riu".
Type "sh management ?" for help.
KW-10106 # sh management route
Destination Mask Gateway
                                    Interface Metric Source
default
              /0 192.168.86.1
                                    wan2
                                             251
                                                     10.250.28.131
              /24 0.0.0.0
10.0.0.0
                                             100
                                                     0.0.0.0
                                    wan1
10.250.28.131 /32 0.0.0.0
                                   1020000 100
                                                    0.0.0.0
169.254.0.0 /16 0.0.0.0
                                   mamt1
                                             0
                                                    169.254.0.1
169.254.124.0 /24 0.0.0.0
                                    pim0
                                             100
                                                    0.0.0.0
169.254.125.0 /24 0.0.0.0
                                   pim1
                                                    0.0.0.0
                                             100
169.254.126.0 /24 0.0.0.0
                                                    0.0.0.0
                                   pim2
                                             100
172.16.33.1 /32 192.168.86.1
                                   wan2
                                            100
                                                    0.0.0.0
172.18.1.0
              /24 0.0.0.0
                                    lan1
                                            100
                                                    0.0.0.0
172.18.250.0
             /24 0.0.0.0
                                                     172.18.250.1
                                    mamt0
                                             0
             /24 0.0.0.0
192.168.21.0
                                    lan0
                                             100
                                                     0.0.0.0
192.168.86.0
             /24 0.0.0.0
                                    wan2
                                             100
                                                     0.0.0.0
KW-10106 # sh running-config ?
<cr>
full
                              Do not exclude commands that set default values
KW-10106 # sh running-config full ?
<cr>
KW-10106 # sh running-config full
## Network interface configuration
no interface lan0 dhcp
   interface lan0 label ""
   interface lan0 mtu 1500
   interface lan0 poe
   interface lan0 poe priority 0
   interface lan0 port-type RJ45
```

```
interface lan0 security-mode 0
no interface lan0 shutdown
   interface lan0 speed-duplex auto/auto
   interface lan0 zone 0
no interface lan1 dhcp
   interface lan1 ip address 172.18.1.1 /24
   interface lan1 label ""
   interface lan1 mtu 1500
   interface lan1 poe
   interface lan1 poe priority 0
   interface lan1 port-type RJ45
   interface lan1 security-mode 0
no interface lan1 shutdown
   interface lan1 speed-duplex auto/auto
   interface lan1 zone 0
no interface lan2 dhcp
   interface lan2 label ""
   interface lan2 mtu 1500
no interface lan2 poe
   interface lan2 poe priority 0
   interface lan2 port-type RJ45
   interface lan2 security-mode 0
no interface lan2 shutdown
   interface lan2 speed-duplex auto/auto
   interface lan2 zone 0
no interface lo dhcp
   interface lo ip address 127.0.0.1 /8
   interface lo label ""
   interface lo mtu 16436
no interface lo poe
   interface lo poe priority 0
   interface lo port-type NONE
   interface lo security-mode 0
no interface lo shutdown
   interface lo speed-duplex auto/auto
   interface lo zone 0
no interface mgmt0 dhcp
   interface mgmt0 ip address 172.18.250.1 /24
   interface mgmt0 label ""
   interface mgmt0 mtu 1500
no interface mgmt0 poe
   interface mgmt0 poe priority 0
   interface mgmt0 port-type RJ45
   interface mgmt0 security-mode 0
no interface mgmt0 shutdown
   interface mgmt0 speed-duplex auto/auto
   interface mgmt0 zone 0
no interface mgmt1 dhcp
   interface mgmt1 ip address 169.254.0.1 /16
   interface mgmt1 label ""
   interface mgmt1 mtu 1500
no interface mgmt1 poe
   interface mgmt1 poe priority 0
   interface mgmt1 port-type RJ45
   interface mgmt1 security-mode 0
no interface mgmt1 shutdown
   interface mgmt1 speed-duplex auto/auto
   interface mgmt1 zone 0
no interface wan0 dhcp
```

```
interface wan0 label ""
   interface wan0 mtu 1500
no interface wan0 poe
   interface wan0 poe priority 0
   interface wan0 port-type SFP
   interface wan0 security-mode 0
no interface wan0 shutdown
   interface wan0 speed-duplex 10000/full
   interface wan0 zone 0
no interface wan1 dhcp
   interface wan1 ip address 10.0.0.6 /24
   interface wan1 label ""
   interface wan1 mtu 1500
no interface wan1 poe
   interface wan1 poe priority 0
   interface wan1 port-type SFP
   interface wan1 security-mode 0
no interface wan1 shutdown
   interface wan1 speed-duplex 10000/full
   interface wan1 zone 0
no interface wan2 dhcp
  interface wan2 label ""
   interface wan2 mtu 1500
no interface wan2 poe
   interface wan2 poe priority 0
   interface wan2 port-type RJ45
   interface wan2 security-mode 0
no interface wan2 shutdown
   interface wan2 speed-duplex auto/auto
   interface wan2 zone 0
## Routing configuration
   ip route 12.0.0.0 /24 10.0.0.1 wan1 1 0.0.0.0
   ip route 172.28.1.0 /24 198.15.99.8 wan0 1 0.0.0.0
## Other IP configuration
   ip name-server 1.1.1.3
   ip name-server 1.1.1.2
   ip name-server 9.9.9.9
   hostname KW-10106
   ip host localhost 127.0.0.1
   ip mgmt-ip 10.250.28.131
## Logging configuration
   logging trap notice
   logging facility auditlog local0
   logging facility firewall local2
   logging facility ids local3
   logging facility system local1
   logging files rotation criteria size 50
   logging files rotation disklimit 2000
   logging files rotation max-num 30
   logging local notice
```

```
logging privacy-mask disable
   logging privacy-mask ipv4 prefix-length 24
   logging stateful-wan-drops disable
## Local user account configuration
   username admin capability admin
no username admin disable
   username lbucsadmin capability admin
no username lbucsadmin disable
   username monitor capability monitor
   username monitor disable
## AAA configuration
   aaa authentication login default local
   aaa authentication login password min-len 8
   aaa authorization map default-group admin
   aaa authorization map order remote-first
   radius-server kev
   radius-server retransmit 1
   radius-server timeout 3
   tacacs-server kev
   tacacs-server retransmit 1
   tacacs-server timeout 3
## System Config
   system stateful-snat-exceptions enable ""
## System Network Config
   dns cache iter 10
   system aggressive-path-fail disable
   system auto-ipid disable
   system auto-policy-lookup interval 60
no system auto-subnet add-lcl-communities
   system auto-subnet add-local metric 50
   system auto-subnet add-local-asn
   system auto-subnet add-local-lan enable
   system auto-subnet add-local-wan disable
   system auto-subnet enable
   system auto-subnet local-asn-filter
no system auto-subnet local-communities
   system auto-subnet local-communities ""
   system auto-subnet route-map default rtmap to subsh outbound
no system auto-subnet segment 0 add-lcl-communities
   system auto-subnet segment 0 add-local metric 50
   system auto-subnet segment 0 add-local-asn
   system auto-subnet segment 0 add-local-lan enable
   system auto-subnet segment 0 add-local-wan disable
   system auto-subnet segment 0 local-asn-filter
no system auto-subnet segment 0 local-communities
   system auto-subnet segment 0 local-communities ""
   system auto-subnet segment 0 route-map default rtmap to subsh outbound
```

```
system auto-syn disable
   system bandwidth if-rx-target disable
   system bandwidth inbound-max 100000
   system bandwidth outbound-max 35000
   system bandwidth wan0 max 35000
   system brnat-outif-number 24
   system brnat-rules-per-oif 256
   system contact ,
   system disk encryption enable
   system dpc tunnel-fail-behavior fail-stick
   system eclicense boost bandwidth 0
   system eclicense boost disable
   system eclicense plus disable
   system edgeha hasync enable
   system end2end-zfw enable
   system enforce-overlay enable
   system flow-del-wait-time 1000
   system int-hairpin enable
   system intersegment internal nat-subnet 129.127.0.1/24
no system ip-broadcast enable
   system ip-header-compression enable
   system ipsec-sa-delay-delete-time 5000
   system ipv6-frag enable
   system ipv6-frag-reassembly enable
   system kernel-icmpv4-err-gen disable
   system kernel-icmpv6-err-gen disable
   system location "San Diego, California, 92101, US"
   system max-tcp-mss 1328
   system network-memory media ram-and-disk
   system node-dns enable
   system node-dns ip 8.8.8.8
   system orch-id e5fd9f27e8f0488c858fcdb5dbe205c4
   system passthru-to-sender disable
   system poe power-mode 2
   system qdrc adj-slope 80
   system gdrc adj-slope-low 5
   system gdrc congestion-duration 60000
   system gdrc disable
   system qdrc mavg-weight 8
   system qdrc messages-interval 1000
   system gdrc min-flow-rate 100
   system qdrc mode smooth
   system gdrc gos-drop-threshold 5
   system gdrc gueue-wait-threshold 5
   system gdrc restriction-duration 10000
   system quies-tun-ka-intvl 60
   system router EC6 WAN1-ASLAN create interface wan1 lan
   system router EC6 WAN1-ASLAN ip 10.0.0.6 /24 nexthop 10.0.0.1 vlan 0
   system router EC6 WAN1-ASLAN ip 10.0.0.6 /24 nexthop 10.0.0.1 vlan 0
   system router EC6 WAN1-ASLAN ip 10.0.0.6 inbound-max-bw 0
   system router EC6 WAN1-ASLAN ip 10.0.0.6 outbound-max-bw 0
   system router EC6 WAN1-ASLAN ip 10.0.0.6 security-mode 0
   system router EC6 WAN1-ASLAN ip 10.0.0.6 segment 0
   system router EC6 WAN1-ASLAN ip 10.0.0.6 target-in-thres 95.000000000
   system router EC6 WAN1-ASLAN ip 10.0.0.6 target-out-thres 95.000000000
   system router EC6 WAN1-ASLAN ip 10.0.0.6 zone 0
   system router rtr1 create interface lan0 lan
   system router rtr1 ip 192.168.21.1 /24 nexthop 0.0.0.0 vlan 0
   system router rtr1 ip 192.168.21.1 /24 nexthop 0.0.0.0 vlan 0
```

```
system router rtr1 ip 192.168.21.1 inbound-max-bw 0
   system router rtr1 ip 192.168.21.1 label 25
   system router rtr1 ip 192.168.21.1 outbound-max-bw 0
  system router rtr1 ip 192.168.21.1 security-mode 0
   system router rtr1 ip 192.168.21.1 segment 0
   system router rtr1 ip 192.168.21.1 target-in-thres 95.000000000
   system router rtr1 ip 192.168.21.1 target-out-thres 95.000000000
   system router rtr1 ip 192.168.21.1 zone 0
   system router rtr2 create interface lan1 lan
   system router rtr2 ip 172.18.1.1 /24 nexthop 0.0.0.0 vlan 0
   system router rtr2 ip 172.18.1.1 /24 nexthop 0.0.0.0 vlan 0
   system router rtr2 ip 172.18.1.1 inbound-max-bw 0
   system router rtr2 ip 172.18.1.1 label 31
   system router rtr2 ip 172.18.1.1 outbound-max-bw 0
   system router rtr2 ip 172.18.1.1 security-mode 0
   system router rtr2 ip 172.18.1.1 segment 0
   system router rtr2 ip 172.18.1.1 target-in-thres 95.000000000
   system router rtr2 ip 172.18.1.1 target-out-thres 95.000000000
   system router rtr2 ip 172.18.1.1 zone 0
   system router rtr3 create interface wan2 wan
   system router rtr3 dhcp vlan 0 inbound-max-bw 100000
   system router rtr3 dhcp vlan 0 label 6
   system router rtr3 dhcp vlan 0 outbound-max-bw 35000
   system router rtr3 dhcp vlan 0 security-mode 3
  system router rtr3 dhcp vlan 0 segment 0
   system router rtr3 dhcp vlan 0 target-in-thres 95.000000000
   system router rtr3 dhcp vlan 0 target-out-thres 95.000000000
   system router rtr3 dhcp vlan 0 zone 0
   system routing inline
   system routing redundancy lan-native-vlan
   system smb-signing disable
   system smbv2-downgrade disable
   system ssl-ipsec-override disable
   system subnet allow-mgmt-routes
   system subnet redistribute enable
   system subnet redistribute enable
   system subnet redistribute increment 50
  system tcp-flow-inact-tout 1800
  system tcp-flow-rst-tout 1000
   system udp-flow-inact-tout 120
## Subnet Config
   subnet 12.0.0.0/24 segment Default nexthop 10.0.0.1 interface wan1 mac 00:00:00:00:00:00 vni 16777216
   subnet 12.0.0.0/24 segment Default nexthop 10.0.0.1 interface wan1 metric 50
   subnet 12.0.0.0/24 segment Default nexthop 10.0.0.1 interface wan1
   subnet 12.0.0.0/24 segment Default nexthop 10.0.0.1 interface wan1 comment "EC6-WAN1-VIA-LOCAL-WAN1"
   subnet 12.0.0.0/24 segment Default nexthop 10.0.0.1 interface wan1 dir any
  subnet 12.0.0.0/24 segment Default nexthop 10.0.0.1 interface wan1 zone 65534
## Shaper Config
   shaper inbound wan accuracy 5000
   shaper inbound wan dynamic-bandwidth disable
   shaper inbound wan enable
   shaper inbound wan max-bandwidth 100000
   shaper inbound wan traffic-class 1 excess-weight 100
```

```
shaper inbound wan traffic-class 1 flow-rate-limit 0
shaper inbound wan traffic-class 1 max-bandwidth 100
shaper inbound wan traffic-class 1 max-bandwidth-abs 25000000
shaper inbound wan traffic-class 1 max-wait 250
shaper inbound wan traffic-class 1 min-bandwidth 25
shaper inbound wan traffic-class 1 min-bandwidth-abs 0
shaper inbound wan traffic-class 1 priority 1
shaper inbound wan traffic-class 10 excess-weight 100
shaper inbound wan traffic-class 10 flow-rate-limit 0
shaper inbound wan traffic-class 10 max-bandwidth 100
shaper inbound wan traffic-class 10 max-bandwidth-abs 25000000
shaper inbound wan traffic-class 10 max-wait 500
shaper inbound wan traffic-class 10 min-bandwidth 0
shaper inbound wan traffic-class 10 min-bandwidth-abs 0
shaper inbound wan traffic-class 10 priority 10
shaper inbound wan traffic-class 2 excess-weight 100
shaper inbound wan traffic-class 2 flow-rate-limit 0
shaper inbound wan traffic-class 2 max-bandwidth 100
shaper inbound wan traffic-class 2 max-bandwidth-abs 25000000
shaper inbound wan traffic-class 2 max-wait 500
shaper inbound wan traffic-class 2 min-bandwidth 25
shaper inbound wan traffic-class 2 min-bandwidth-abs 0
shaper inbound wan traffic-class 2 priority 2
shaper inbound wan traffic-class 3 excess-weight 100
shaper inbound wan traffic-class 3 flow-rate-limit 0
shaper inbound wan traffic-class 3 max-bandwidth 80
shaper inbound wan traffic-class 3 max-bandwidth-abs 25000000
shaper inbound wan traffic-class 3 max-wait 500
shaper inbound wan traffic-class 3 min-bandwidth 0
shaper inbound wan traffic-class 3 min-bandwidth-abs 0
shaper inbound wan traffic-class 3 priority 3
shaper inbound wan traffic-class 4 excess-weight 100
shaper inbound wan traffic-class 4 flow-rate-limit 0
shaper inbound wan traffic-class 4 max-bandwidth 100
shaper inbound wan traffic-class 4 max-bandwidth-abs 25000000
shaper inbound wan traffic-class 4 max-wait 500
shaper inbound wan traffic-class 4 min-bandwidth 0
shaper inbound wan traffic-class 4 min-bandwidth-abs 0
shaper inbound wan traffic-class 4 priority 4
shaper inbound wan traffic-class 5 excess-weight 100
shaper inbound wan traffic-class 5 flow-rate-limit 0
shaper inbound wan traffic-class 5 max-bandwidth 100
shaper inbound wan traffic-class 5 max-bandwidth-abs 25000000
shaper inbound wan traffic-class 5 max-wait 500
shaper inbound wan traffic-class 5 min-bandwidth 0
shaper inbound wan traffic-class 5 min-bandwidth-abs 0
shaper inbound wan traffic-class 5 priority 5
shaper inbound wan traffic-class 6 excess-weight 100
shaper inbound wan traffic-class 6 flow-rate-limit 0
shaper inbound wan traffic-class 6 max-bandwidth 100
shaper inbound wan traffic-class 6 max-bandwidth-abs 25000000
shaper inbound wan traffic-class 6 max-wait 500
shaper inbound wan traffic-class 6 min-bandwidth 0
shaper inbound wan traffic-class 6 min-bandwidth-abs 0
shaper inbound wan traffic-class 6 priority 6
shaper inbound wan traffic-class 7 excess-weight 100
shaper inbound wan traffic-class 7 flow-rate-limit 0
shaper inbound wan traffic-class 7 max-bandwidth 100
shaper inbound wan traffic-class 7 max-bandwidth-abs 25000000
```

```
shaper inbound wan traffic-class 7 max-wait 500
shaper inbound wan traffic-class 7 min-bandwidth 0
shaper inbound wan traffic-class 7 min-bandwidth-abs 0
shaper inbound wan traffic-class 7 priority 7
shaper inbound wan traffic-class 8 excess-weight 100
shaper inbound wan traffic-class 8 flow-rate-limit 0
shaper inbound wan traffic-class 8 max-bandwidth 100
shaper inbound wan traffic-class 8 max-bandwidth-abs 25000000
shaper inbound wan traffic-class 8 max-wait 500
shaper inbound wan traffic-class 8 min-bandwidth 0
shaper inbound wan traffic-class 8 min-bandwidth-abs 0
shaper inbound wan traffic-class 8 priority 8
shaper inbound wan traffic-class 9 excess-weight 100
shaper inbound wan traffic-class 9 flow-rate-limit 0
shaper inbound wan traffic-class 9 max-bandwidth 100
shaper inbound wan traffic-class 9 max-bandwidth-abs 25000000
shaper inbound wan traffic-class 9 max-wait 500
shaper inbound wan traffic-class 9 min-bandwidth 0
shaper inbound wan traffic-class 9 min-bandwidth-abs 0
shaper inbound wan traffic-class 9 priority 9
shaper outbound default accuracy 1000
shaper outbound default disable
shaper outbound default dynamic-bandwidth disable
shaper outbound default max-bandwidth 0
shaper outbound default traffic-class 1 excess-weight 100
shaper outbound default traffic-class 1 flow-rate-limit 0
shaper outbound default traffic-class 1 max-bandwidth 100
shaper outbound default traffic-class 1 max-bandwidth-abs 25000000
shaper outbound default traffic-class 1 max-wait 500
shaper outbound default traffic-class 1 min-bandwidth 30
shaper outbound default traffic-class 1 min-bandwidth-abs 0
shaper outbound default traffic-class 1 priority 5
shaper outbound default traffic-class 10 excess-weight 100
shaper outbound default traffic-class 10 flow-rate-limit 0
shaper outbound default traffic-class 10 max-bandwidth 100
shaper outbound default traffic-class 10 max-bandwidth-abs 25000000
shaper outbound default traffic-class 10 max-wait 500
shaper outbound default traffic-class 10 min-bandwidth 30
shaper outbound default traffic-class 10 min-bandwidth-abs 0
shaper outbound default traffic-class 10 priority 5
shaper outbound default traffic-class 2 excess-weight 1000
shaper outbound default traffic-class 2 flow-rate-limit 0
shaper outbound default traffic-class 2 max-bandwidth 100
shaper outbound default traffic-class 2 max-bandwidth-abs 25000000
shaper outbound default traffic-class 2 max-wait 100
shaper outbound default traffic-class 2 min-bandwidth 30
shaper outbound default traffic-class 2 min-bandwidth-abs 0
shaper outbound default traffic-class 2 priority 1
shaper outbound default traffic-class 3 excess-weight 1000
shaper outbound default traffic-class 3 flow-rate-limit 0
shaper outbound default traffic-class 3 max-bandwidth 100
shaper outbound default traffic-class 3 max-bandwidth-abs 25000000
shaper outbound default traffic-class 3 max-wait 200
shaper outbound default traffic-class 3 min-bandwidth 20
shaper outbound default traffic-class 3 min-bandwidth-abs 0
shaper outbound default traffic-class 3 priority 2
shaper outbound default traffic-class 4 excess-weight 100
shaper outbound default traffic-class 4 flow-rate-limit 0
shaper outbound default traffic-class 4 max-bandwidth 100
```

```
shaper outbound default traffic-class 4 max-bandwidth-abs 25000000
shaper outbound default traffic-class 4 max-wait 500
shaper outbound default traffic-class 4 min-bandwidth 20
shaper outbound default traffic-class 4 min-bandwidth-abs 0
shaper outbound default traffic-class 4 priority 8
shaper outbound default traffic-class 5 excess-weight 100
shaper outbound default traffic-class 5 flow-rate-limit 0
shaper outbound default traffic-class 5 max-bandwidth 100
shaper outbound default traffic-class 5 max-bandwidth-abs 25000000
shaper outbound default traffic-class 5 max-wait 500
shaper outbound default traffic-class 5 min-bandwidth 30
shaper outbound default traffic-class 5 min-bandwidth-abs 0
shaper outbound default traffic-class 5 priority 5
shaper outbound default traffic-class 6 excess-weight 100
shaper outbound default traffic-class 6 flow-rate-limit 0
shaper outbound default traffic-class 6 max-bandwidth 100
shaper outbound default traffic-class 6 max-bandwidth-abs 25000000
shaper outbound default traffic-class 6 max-wait 500
shaper outbound default traffic-class 6 min-bandwidth 30
shaper outbound default traffic-class 6 min-bandwidth-abs 0
shaper outbound default traffic-class 6 priority 5
shaper outbound default traffic-class 7 excess-weight 100
shaper outbound default traffic-class 7 flow-rate-limit 0
shaper outbound default traffic-class 7 max-bandwidth 100
shaper outbound default traffic-class 7 max-bandwidth-abs 25000000
shaper outbound default traffic-class 7 max-wait 500
shaper outbound default traffic-class 7 min-bandwidth 30
shaper outbound default traffic-class 7 min-bandwidth-abs 0
shaper outbound default traffic-class 7 priority 5
shaper outbound default traffic-class 8 excess-weight 100
shaper outbound default traffic-class 8 flow-rate-limit 0
shaper outbound default traffic-class 8 max-bandwidth 100
shaper outbound default traffic-class 8 max-bandwidth-abs 25000000
shaper outbound default traffic-class 8 max-wait 500
shaper outbound default traffic-class 8 min-bandwidth 30
shaper outbound default traffic-class 8 min-bandwidth-abs 0
shaper outbound default traffic-class 8 priority 5
shaper outbound default traffic-class 9 excess-weight 100
shaper outbound default traffic-class 9 flow-rate-limit 0
shaper outbound default traffic-class 9 max-bandwidth 100
shaper outbound default traffic-class 9 max-bandwidth-abs 25000000
shaper outbound default traffic-class 9 max-wait 500
shaper outbound default traffic-class 9 min-bandwidth 30
shaper outbound default traffic-class 9 min-bandwidth-abs 0
shaper outbound default traffic-class 9 priority 5
shaper outbound wan accuracy 5000
shaper outbound wan dynamic-bandwidth disable
shaper outbound wan enable
shaper outbound wan max-bandwidth 35000
shaper outbound wan traffic-class 1 excess-weight 100
shaper outbound wan traffic-class 1 flow-rate-limit 0
shaper outbound wan traffic-class 1 max-bandwidth 100
shaper outbound wan traffic-class 1 max-bandwidth-abs 25000000
shaper outbound wan traffic-class 1 max-wait 250
shaper outbound wan traffic-class 1 min-bandwidth 25
shaper outbound wan traffic-class 1 min-bandwidth-abs 0
shaper outbound wan traffic-class 1 priority 1
shaper outbound wan traffic-class 10 excess-weight 100
shaper outbound wan traffic-class 10 flow-rate-limit 0
```

```
shaper outbound wan traffic-class 10 max-bandwidth 100
shaper outbound wan traffic-class 10 max-bandwidth-abs 25000000
shaper outbound wan traffic-class 10 max-wait 500
shaper outbound wan traffic-class 10 min-bandwidth 0
shaper outbound wan traffic-class 10 min-bandwidth-abs 0
shaper outbound wan traffic-class 10 priority 10
shaper outbound wan traffic-class 2 excess-weight 100
shaper outbound wan traffic-class 2 flow-rate-limit 0
shaper outbound wan traffic-class 2 max-bandwidth 100
shaper outbound wan traffic-class 2 max-bandwidth-abs 25000000
shaper outbound wan traffic-class 2 max-wait 500
shaper outbound wan traffic-class 2 min-bandwidth 25
shaper outbound wan traffic-class 2 min-bandwidth-abs 0
shaper outbound wan traffic-class 2 priority 2
shaper outbound wan traffic-class 3 excess-weight 100
shaper outbound wan traffic-class 3 flow-rate-limit 0
shaper outbound wan traffic-class 3 max-bandwidth 80
shaper outbound wan traffic-class 3 max-bandwidth-abs 25000000
shaper outbound wan traffic-class 3 max-wait 500
shaper outbound wan traffic-class 3 min-bandwidth 0
shaper outbound wan traffic-class 3 min-bandwidth-abs 0
shaper outbound wan traffic-class 3 priority 3
shaper outbound wan traffic-class 4 excess-weight 100
shaper outbound wan traffic-class 4 flow-rate-limit 0
shaper outbound wan traffic-class 4 max-bandwidth 100
shaper outbound wan traffic-class 4 max-bandwidth-abs 25000000
shaper outbound wan traffic-class 4 max-wait 500
shaper outbound wan traffic-class 4 min-bandwidth 0
shaper outbound wan traffic-class 4 min-bandwidth-abs 0
shaper outbound wan traffic-class 4 priority 4
shaper outbound wan traffic-class 5 excess-weight 100
shaper outbound wan traffic-class 5 flow-rate-limit 0
shaper outbound wan traffic-class 5 max-bandwidth 100
shaper outbound wan traffic-class 5 max-bandwidth-abs 25000000
shaper outbound wan traffic-class 5 max-wait 500
shaper outbound wan traffic-class 5 min-bandwidth 0
shaper outbound wan traffic-class 5 min-bandwidth-abs 0
shaper outbound wan traffic-class 5 priority 5
shaper outbound wan traffic-class 6 excess-weight 100
shaper outbound wan traffic-class 6 flow-rate-limit 0
shaper outbound wan traffic-class 6 max-bandwidth 100
shaper outbound wan traffic-class 6 max-bandwidth-abs 25000000
shaper outbound wan traffic-class 6 max-wait 500
shaper outbound wan traffic-class 6 min-bandwidth 0
shaper outbound wan traffic-class 6 min-bandwidth-abs 0
shaper outbound wan traffic-class 6 priority 6
shaper outbound wan traffic-class 7 excess-weight 100
shaper outbound wan traffic-class 7 flow-rate-limit 0
shaper outbound wan traffic-class 7 max-bandwidth 100
shaper outbound wan traffic-class 7 max-bandwidth-abs 25000000
shaper outbound wan traffic-class 7 max-wait 500
shaper outbound wan traffic-class 7 min-bandwidth 0
shaper outbound wan traffic-class 7 min-bandwidth-abs 0
shaper outbound wan traffic-class 7 priority 7
shaper outbound wan traffic-class 8 excess-weight 100
shaper outbound wan traffic-class 8 flow-rate-limit 0
shaper outbound wan traffic-class 8 max-bandwidth 100
shaper outbound wan traffic-class 8 max-bandwidth-abs 25000000
shaper outbound wan traffic-class 8 max-wait 500
```

```
shaper outbound wan traffic-class 8 min-bandwidth 0
   shaper outbound wan traffic-class 8 min-bandwidth-abs 0
   shaper outbound wan traffic-class 8 priority 8
  shaper outbound wan traffic-class 9 excess-weight 100
   shaper outbound wan traffic-class 9 flow-rate-limit 0
   shaper outbound wan traffic-class 9 max-bandwidth 100
   shaper outbound wan traffic-class 9 max-bandwidth-abs 25000000
   shaper outbound wan traffic-class 9 max-wait 500
   shaper outbound wan traffic-class 9 min-bandwidth 0
   shaper outbound wan traffic-class 9 min-bandwidth-abs 0
   shaper outbound wan traffic-class 9 priority 9
   traffic-class 1 name RealTime
   traffic-class 10 name UNUSED10
   traffic-class 2 name CriticalApps
  traffic-class 3 name BulkApps
   traffic-class 4 name Default
   traffic-class 5 name UNUSED5
   traffic-class 6 name UNUSED6
   traffic-class 7 name UNUSED7
   traffic-class 8 name UNUSED8
   traffic-class 9 name UNUSED9
## Tunnel Creation
   interface tunnel bondedTunnel 208 create bonded-tunnel tag-name CaptWhite bonded-id 7
   interface tunnel bondedTunnel 27 create bonded-tunnel tag-name DefaultOverlay bonded-id 4
   interface tunnel bondedTunnel 28 create bonded-tunnel tag-name CriticalApps bonded-id 2
   interface tunnel bondedTunnel 29 create bonded-tunnel tag-name RealTime bonded-id 1
   interface tunnel bondedTunnel 30 create bonded-tunnel tag-name BulkApps bonded-id 3
   interface tunnel passThrough 216 create 192.168.86.28 0.0.0.0 100 auto no encap
   interface tunnel passThrough 217 create 192.168.86.28 0.0.0.0 100 auto no encap
   interface tunnel passThrough 218 create 192.168.86.28 0.0.0.0 100 auto no encap
   interface tunnel passThrough 219 create 192.168.86.28 0.0.0.0 100 auto no encap
   interface tunnel passThrough 220 create 192.168.86.28 0.0.0.0 100 auto no encap
   interface tunnel passThrough 221 create 192.168.86.28 0.0.0.0 100 auto no encap
   interface tunnel passThrough 225 create 192.168.21.1 0.0.0.0 100 auto no encap
   interface tunnel passThrough 232 create 172.18.1.1 0.0.0.0 100 auto no encap
   interface tunnel passThrough 239 create 10.0.0.6 0.0.0.0 100 auto no encap
   interface tunnel tunnel 222 create 192.168.86.28 107.215.36.181 100 auto udp sp
## Tunnel Config
   interface tunnel bondedTunnel 208 admin up
   interface tunnel bondedTunnel 208 alias to Baton-Rouge-EC CaptWhite
   interface tunnel bondedTunnel 208 bind-tunnel tunnel 222
   interface tunnel bondedTunnel 208 control-packet dscp be
   interface tunnel bondedTunnel 208 gms-marked
   interface tunnel bondedTunnel 208 gre-protocol 2048
   interface tunnel bondedTunnel 208 max-bandwidth 35000
   interface tunnel bondedTunnel 208 nat-mode none
   interface tunnel bondedTunnel 208 packet coalesce enable
   interface tunnel bondedTunnel 208 packet coalesce wait 0
   interface tunnel bondedTunnel 208 packet fec disable
   interface tunnel bondedTunnel 208 packet fec ratio 1:10
   interface tunnel bondedTunnel 208 packet reorder wait 100
   interface tunnel bondedTunnel 208 peer-name ""
   interface tunnel bondedTunnel 208 threshold fastfail disable
```

```
interface tunnel bondedTunnel 208 threshold fastfail-wait base-ms 150
interface tunnel bondedTunnel 208 threshold fastfail-wait rtt-x 2
interface tunnel bondedTunnel 208 threshold jitter 0
interface tunnel bondedTunnel 208 threshold latency 0
interface tunnel bondedTunnel 208 threshold loss 0.000000
interface tunnel bondedTunnel 208 threshold retry-count 30
interface tunnel bondedTunnel 27 admin up
interface tunnel bondedTunnel 27 alias to Baton-Rouge-EC DefaultOverlay
interface tunnel bondedTunnel 27 bind-tunnel tunnel 222
interface tunnel bondedTunnel 27 control-packet dscp be
interface tunnel bondedTunnel 27 gms-marked
interface tunnel bondedTunnel 27 gre-protocol 2048
interface tunnel bondedTunnel 27 max-bandwidth 35000
interface tunnel bondedTunnel 27 nat-mode none
interface tunnel bondedTunnel 27 packet coalesce enable
interface tunnel bondedTunnel 27 packet coalesce wait 0
interface tunnel bondedTunnel 27 packet fec disable
interface tunnel bondedTunnel 27 packet fec ratio 1:10
interface tunnel bondedTunnel 27 packet reorder wait 100
interface tunnel bondedTunnel 27 peer-name ""
interface tunnel bondedTunnel 27 threshold fastfail disable
interface tunnel bondedTunnel 27 threshold fastfail-wait base-ms 150
interface tunnel bondedTunnel 27 threshold fastfail-wait rtt-x 2
interface tunnel bondedTunnel 27 threshold jitter 0
interface tunnel bondedTunnel 27 threshold latency 0
interface tunnel bondedTunnel 27 threshold loss 0.000000
interface tunnel bondedTunnel 27 threshold retry-count 30
interface tunnel bondedTunnel 28 admin up
interface tunnel bondedTunnel 28 alias to Baton-Rouge-EC CriticalApps
interface tunnel bondedTunnel 28 bind-tunnel tunnel 222
interface tunnel bondedTunnel 28 control-packet dscp be
interface tunnel bondedTunnel 28 gms-marked
interface tunnel bondedTunnel 28 gre-protocol 2048
interface tunnel bondedTunnel 28 max-bandwidth 35000
interface tunnel bondedTunnel 28 nat-mode none
interface tunnel bondedTunnel 28 packet coalesce enable
interface tunnel bondedTunnel 28 packet coalesce wait 0
interface tunnel bondedTunnel 28 packet fec disable
interface tunnel bondedTunnel 28 packet fec ratio 1:10
interface tunnel bondedTunnel 28 packet reorder wait 100
interface tunnel bondedTunnel 28 peer-name ""
interface tunnel bondedTunnel 28 threshold fastfail disable
interface tunnel bondedTunnel 28 threshold fastfail-wait base-ms 150
interface tunnel bondedTunnel 28 threshold fastfail-wait rtt-x 2
interface tunnel bondedTunnel 28 threshold jitter 0
interface tunnel bondedTunnel 28 threshold latency 0
interface tunnel bondedTunnel 28 threshold loss 0.000000
interface tunnel bondedTunnel 28 threshold retry-count 30
interface tunnel bondedTunnel 29 admin up
interface tunnel bondedTunnel 29 alias to Baton-Rouge-EC RealTime
interface tunnel bondedTunnel 29 bind-tunnel tunnel 222
interface tunnel bondedTunnel 29 control-packet dscp be
interface tunnel bondedTunnel 29 gms-marked
interface tunnel bondedTunnel 29 gre-protocol 2048
interface tunnel bondedTunnel 29 max-bandwidth 35000
interface tunnel bondedTunnel 29 nat-mode none
interface tunnel bondedTunnel 29 packet coalesce enable
interface tunnel bondedTunnel 29 packet coalesce wait 0
interface tunnel bondedTunnel 29 packet fec disable
```

```
interface tunnel bondedTunnel 29 packet fec ratio 1:10
interface tunnel bondedTunnel 29 packet reorder wait 100
interface tunnel bondedTunnel 29 peer-name ""
interface tunnel bondedTunnel 29 threshold fastfail disable
interface tunnel bondedTunnel 29 threshold fastfail-wait base-ms 150
interface tunnel bondedTunnel 29 threshold fastfail-wait rtt-x 2
interface tunnel bondedTunnel 29 threshold jitter 0
interface tunnel bondedTunnel 29 threshold latency 0
interface tunnel bondedTunnel 29 threshold loss 0.000000
interface tunnel bondedTunnel 29 threshold retry-count 30
interface tunnel bondedTunnel 30 admin up
interface tunnel bondedTunnel 30 alias to Baton-Rouge-EC BulkApps
interface tunnel bondedTunnel 30 bind-tunnel tunnel 222
interface tunnel bondedTunnel 30 control-packet dscp be
interface tunnel bondedTunnel 30 gms-marked
interface tunnel bondedTunnel 30 gre-protocol 2048
interface tunnel bondedTunnel 30 max-bandwidth 35000
interface tunnel bondedTunnel 30 nat-mode none
interface tunnel bondedTunnel 30 packet coalesce enable
interface tunnel bondedTunnel 30 packet coalesce wait 0
interface tunnel bondedTunnel 30 packet fec disable
interface tunnel bondedTunnel 30 packet fec ratio 1:10
interface tunnel bondedTunnel 30 packet reorder wait 100
interface tunnel bondedTunnel 30 peer-name ""
interface tunnel bondedTunnel 30 threshold fastfail disable
interface tunnel bondedTunnel 30 threshold fastfail-wait base-ms 150
interface tunnel bondedTunnel 30 threshold fastfail-wait rtt-x 2
interface tunnel bondedTunnel 30 threshold jitter 0
interface tunnel bondedTunnel 30 threshold latency 0
interface tunnel bondedTunnel 30 threshold loss 0.000000
interface tunnel bondedTunnel 30 threshold retry-count 30
interface tunnel passThrough 216 admin up
interface tunnel passThrough 216 alias Passthrough INET2 CaptWhite
interface tunnel passThrough 216 control-packet dscp be
interface tunnel passThrough 216 qms-marked
interface tunnel passThrough 216 gre-protocol 2048
interface tunnel passThrough 216 max-bandwidth 0
interface tunnel passThrough 216 nat-mode none
interface tunnel passThrough 216 packet coalesce enable
interface tunnel passThrough 216 packet coalesce wait 0
interface tunnel passThrough 216 packet fec disable
interface tunnel passThrough 216 packet fec ratio 1:10
interface tunnel passThrough 216 packet reorder wait 100
interface tunnel passThrough 216 peer-name unassigned
interface tunnel passThrough 216 tag-name 6-7
interface tunnel passThrough 216 threshold fastfail disable
interface tunnel passThrough 216 threshold fastfail-wait base-ms 150
interface tunnel passThrough 216 threshold fastfail-wait rtt-x 2
interface tunnel passThrough 216 threshold jitter 0
interface tunnel passThrough 216 threshold latency 0
interface tunnel passThrough 216 threshold loss 0.000000
interface tunnel passThrough 216 threshold retry-count 30
interface tunnel passThrough 216 udp-flow 256
interface tunnel passThrough 216 udp-port 4163
interface tunnel passThrough 217 admin up
interface tunnel passThrough 217 alias Passthrough INET2 wan2
interface tunnel passThrough 217 control-packet dscp be
interface tunnel passThrough 217 gms-marked
interface tunnel passThrough 217 gre-protocol 2048
```

```
interface tunnel passThrough 217 max-bandwidth 0
interface tunnel passThrough 217 nat-mode none
interface tunnel passThrough 217 packet coalesce enable
interface tunnel passThrough 217 packet coalesce wait 0
interface tunnel passThrough 217 packet fec disable
interface tunnel passThrough 217 packet fec ratio 1:10
interface tunnel passThrough 217 packet reorder wait 100
interface tunnel passThrough 217 peer-name unassigned
interface tunnel passThrough 217 tag-name wan2
interface tunnel passThrough 217 threshold fastfail disable
interface tunnel passThrough 217 threshold fastfail-wait base-ms 150
interface tunnel passThrough 217 threshold fastfail-wait rtt-x 2
interface tunnel passThrough 217 threshold jitter 0
interface tunnel passThrough 217 threshold latency 0
interface tunnel passThrough 217 threshold loss 0.000000
interface tunnel passThrough 217 threshold retry-count 30
interface tunnel passThrough 217 udp-flow 256
interface tunnel passThrough 217 udp-port 4163
interface tunnel passThrough 218 admin up
interface tunnel passThrough 218 alias Passthrough INET2 RealTime
interface tunnel passThrough 218 control-packet dscp be
interface tunnel passThrough 218 gms-marked
interface tunnel passThrough 218 gre-protocol 2048
interface tunnel passThrough 218 max-bandwidth 0
interface tunnel passThrough 218 nat-mode none
interface tunnel passThrough 218 packet coalesce enable
interface tunnel passThrough 218 packet coalesce wait 0
interface tunnel passThrough 218 packet fec disable
interface tunnel passThrough 218 packet fec ratio 1:10
interface tunnel passThrough 218 packet reorder wait 100
interface tunnel passThrough 218 peer-name Overlay RealTime Primary
interface tunnel passThrough 218 tag-name 6-1
interface tunnel passThrough 218 threshold fastfail disable
interface tunnel passThrough 218 threshold fastfail-wait base-ms 150
interface tunnel passThrough 218 threshold fastfail-wait rtt-x 2
interface tunnel passThrough 218 threshold jitter 0
interface tunnel passThrough 218 threshold latency 0
interface tunnel passThrough 218 threshold loss 0.000000
interface tunnel passThrough 218 threshold retry-count 30
interface tunnel passThrough 218 udp-flow 256
interface tunnel passThrough 218 udp-port 4163
interface tunnel passThrough 219 admin up
interface tunnel passThrough 219 alias Passthrough INET2 CriticalApps
interface tunnel passThrough 219 control-packet dscp be
interface tunnel passThrough 219 qms-marked
interface tunnel passThrough 219 gre-protocol 2048
interface tunnel passThrough 219 max-bandwidth 0
interface tunnel passThrough 219 nat-mode none
interface tunnel passThrough 219 packet coalesce enable
interface tunnel passThrough 219 packet coalesce wait 0
interface tunnel passThrough 219 packet fec disable
interface tunnel passThrough 219 packet fec ratio 1:10
interface tunnel passThrough 219 packet reorder wait 100
interface tunnel passThrough 219 peer-name Overlay CriticalApps Primary
interface tunnel passThrough 219 tag-name 6-2
interface tunnel passThrough 219 threshold fastfail disable
interface tunnel passThrough 219 threshold fastfail-wait base-ms 150
interface tunnel passThrough 219 threshold fastfail-wait rtt-x 2
interface tunnel passThrough 219 threshold jitter 0
```

```
interface tunnel passThrough 219 threshold latency 0
interface tunnel passThrough 219 threshold loss 0.000000
interface tunnel passThrough 219 threshold retry-count 30
interface tunnel passThrough 219 udp-flow 256
interface tunnel passThrough 219 udp-port 4163
interface tunnel passThrough 220 admin up
interface tunnel passThrough 220 alias Passthrough INET2 BulkApps
interface tunnel passThrough 220 control-packet dscp be
interface tunnel passThrough 220 gms-marked
interface tunnel passThrough 220 gre-protocol 2048
interface tunnel passThrough 220 max-bandwidth 0
interface tunnel passThrough 220 nat-mode none
interface tunnel passThrough 220 packet coalesce enable
interface tunnel passThrough 220 packet coalesce wait 0
interface tunnel passThrough 220 packet fec disable
interface tunnel passThrough 220 packet fec ratio 1:10
interface tunnel passThrough 220 packet reorder wait 100
interface tunnel passThrough 220 peer-name Overlay BulkApps Primary
interface tunnel passThrough 220 tag-name 6-3
interface tunnel passThrough 220 threshold fastfail disable
interface tunnel passThrough 220 threshold fastfail-wait base-ms 150
interface tunnel passThrough 220 threshold fastfail-wait rtt-x 2
interface tunnel passThrough 220 threshold jitter 0
interface tunnel passThrough 220 threshold latency 0
interface tunnel passThrough 220 threshold loss 0.000000
interface tunnel passThrough 220 threshold retry-count 30
interface tunnel passThrough 220 udp-flow 256
interface tunnel passThrough 220 udp-port 4163
interface tunnel passThrough 221 admin up
interface tunnel passThrough 221 alias Passthrough INET2 DefaultOverlay
interface tunnel passThrough 221 control-packet dscp be
interface tunnel passThrough 221 gms-marked
interface tunnel passThrough 221 gre-protocol 2048
interface tunnel passThrough 221 max-bandwidth 0
interface tunnel passThrough 221 nat-mode none
interface tunnel passThrough 221 packet coalesce enable
interface tunnel passThrough 221 packet coalesce wait 0
interface tunnel passThrough 221 packet fec disable
interface tunnel passThrough 221 packet fec ratio 1:10
interface tunnel passThrough 221 packet reorder wait 100
interface tunnel passThrough 221 peer-name unassigned
interface tunnel passThrough 221 tag-name 6-4
interface tunnel passThrough 221 threshold fastfail disable
interface tunnel passThrough 221 threshold fastfail-wait base-ms 150
interface tunnel passThrough 221 threshold fastfail-wait rtt-x 2
interface tunnel passThrough 221 threshold jitter 0
interface tunnel passThrough 221 threshold latency 0
interface tunnel passThrough 221 threshold loss 0.000000
interface tunnel passThrough 221 threshold retry-count 30
interface tunnel passThrough 221 udp-flow 256
interface tunnel passThrough 221 udp-port 4163
interface tunnel passThrough 225 admin up
interface tunnel passThrough 225 alias Passthrough FSE lan0
interface tunnel passThrough 225 control-packet dscp be
interface tunnel passThrough 225 qms-marked
interface tunnel passThrough 225 gre-protocol 2048
interface tunnel passThrough 225 max-bandwidth 0
interface tunnel passThrough 225 nat-mode none
interface tunnel passThrough 225 packet coalesce enable
```

```
interface tunnel passThrough 225 packet coalesce wait 0
interface tunnel passThrough 225 packet fec disable
interface tunnel passThrough 225 packet fec ratio 1:10
interface tunnel passThrough 225 packet reorder wait 100
interface tunnel passThrough 225 peer-name unassigned
interface tunnel passThrough 225 tag-name lan0
interface tunnel passThrough 225 threshold fastfail disable
interface tunnel passThrough 225 threshold fastfail-wait base-ms 150
interface tunnel passThrough 225 threshold fastfail-wait rtt-x 2
interface tunnel passThrough 225 threshold jitter 0
interface tunnel passThrough 225 threshold latency 0
interface tunnel passThrough 225 threshold loss 0.000000
interface tunnel passThrough 225 threshold retry-count 30
interface tunnel passThrough 225 udp-flow 256
interface tunnel passThrough 225 udp-port 4163
interface tunnel passThrough 232 admin up
interface tunnel passThrough 232 alias Passthrough OVERLAY L1 lan1
interface tunnel passThrough 232 control-packet dscp be
interface tunnel passThrough 232 gms-marked
interface tunnel passThrough 232 gre-protocol 2048
interface tunnel passThrough 232 max-bandwidth 0
interface tunnel passThrough 232 nat-mode none
interface tunnel passThrough 232 packet coalesce enable
interface tunnel passThrough 232 packet coalesce wait 0
interface tunnel passThrough 232 packet fec disable
interface tunnel passThrough 232 packet fec ratio 1:10
interface tunnel passThrough 232 packet reorder wait 100
interface tunnel passThrough 232 peer-name unassigned
interface tunnel passThrough 232 tag-name lan1
interface tunnel passThrough 232 threshold fastfail disable
interface tunnel passThrough 232 threshold fastfail-wait base-ms 150
interface tunnel passThrough 232 threshold fastfail-wait rtt-x 2
interface tunnel passThrough 232 threshold jitter 0
interface tunnel passThrough 232 threshold latency 0
interface tunnel passThrough 232 threshold loss 0.000000
interface tunnel passThrough 232 threshold retry-count 30
interface tunnel passThrough 232 udp-flow 256
interface tunnel passThrough 232 udp-port 4163
interface tunnel passThrough 239 admin up
interface tunnel passThrough 239 alias Passthrough wan1
interface tunnel passThrough 239 control-packet dscp be
interface tunnel passThrough 239 gms-marked
interface tunnel passThrough 239 gre-protocol 2048
interface tunnel passThrough 239 max-bandwidth 0
interface tunnel passThrough 239 nat-mode none
interface tunnel passThrough 239 packet coalesce enable
interface tunnel passThrough 239 packet coalesce wait 0
interface tunnel passThrough 239 packet fec disable
interface tunnel passThrough 239 packet fec ratio 1:10
interface tunnel passThrough 239 packet reorder wait 100
interface tunnel passThrough 239 peer-name unassigned
interface tunnel passThrough 239 tag-name wan1
interface tunnel passThrough 239 threshold fastfail disable
interface tunnel passThrough 239 threshold fastfail-wait base-ms 150
interface tunnel passThrough 239 threshold fastfail-wait rtt-x 2
interface tunnel passThrough 239 threshold jitter 0
interface tunnel passThrough 239 threshold latency 0
interface tunnel passThrough 239 threshold loss 0.000000
interface tunnel passThrough 239 threshold retry-count 30
```

```
interface tunnel passThrough 239 udp-flow 256
   interface tunnel passThrough 239 udp-port 4163
   interface tunnel tunnel 222 admin up
   interface tunnel tunnel 222 alias to Baton-Rouge-EC INET2-INET1
   interface tunnel tunnel 222 control-packet dscp be
   interface tunnel tunnel 222 gms-marked
   interface tunnel tunnel 222 gre-protocol 2048
   interface tunnel tunnel 222 max-bandwidth 35000
   interface tunnel tunnel 222 nat-mode none
   interface tunnel tunnel 222 packet coalesce enable
   interface tunnel tunnel 222 packet coalesce wait 0
   interface tunnel tunnel 222 packet fec auto
   interface tunnel tunnel 222 packet fec ratio 1:10
   interface tunnel tunnel 222 packet reorder wait 100
   interface tunnel tunnel 222 peer-name unassigned
   interface tunnel tunnel 222 tag-name 6-2
   interface tunnel tunnel 222 threshold fastfail enable
   interface tunnel tunnel 222 threshold fastfail-wait base-ms 150
   interface tunnel tunnel 222 threshold fastfail-wait rtt-x 5
   interface tunnel tunnel 222 threshold jitter 0
   interface tunnel tunnel 222 threshold latency 0
   interface tunnel tunnel 222 threshold loss 0.000000
   interface tunnel tunnel 222 threshold retry-count 30
   interface tunnel tunnel 222 udp-flow 256
   interface tunnel tunnel 222 udp-port 4163
   interface tunnel tunnel 222 ipsec enable
   interface tunnel tunnel 222 ipsec auth-algorithm default
   interface tunnel tunnel 222 ipsec crypto-algorithm aes128
   interface tunnel tunnel 222 ipsec dhgroup 14
   interface tunnel tunnel 222 ipsec dpd-delay 10
   interface tunnel tunnel 222 ipsec esn enable
   interface tunnel tunnel 222 ipsec exchange-mode default
   interface tunnel tunnel 222 ipsec ike-auth-algo default
   interface tunnel tunnel 222 ipsec ike-crypto-algo default
   interface tunnel tunnel 222 ipsec ike-id-local
   interface tunnel tunnel 222 ipsec ike-id-remote
   interface tunnel tunnel 222 ipsec ike-lifetime 360
   interface tunnel tunnel 222 ipsec ike-prf auto
   interface tunnel tunnel 222 ipsec ike-version 1
   interface tunnel tunnel 222 ipsec lifebyte 0
   interface tunnel tunnel 222 ipsec lifetime 360
   interface tunnel tunnel 222 ipsec pfs enable
   interface tunnel tunnel 222 ipsec pfsgroup 14
   interface tunnel tunnel 222 ipsec replay-check-window 1024
## Pass-Through Config
   interface pass-through max-bandwidth 1000000000
   interface pass-through min-bandwidth 1000000000
## Application Config
   application-group citrix citrix-bcast, citrix-cqp, citrix-ica, citrix-ima
   application-group encrypted ddm ssl, https, imap4s, ipsec, nntps, pop3s, smtps, ssh, telnets
   application-group interactive pcanywhere, pcoip, ssh, telnet, telnets, vnc, xwindows
   application-group real-time cisco skinny, h 323, rtcp, rtp, rtp mux, rtp video, rtp voice, rtsp, sip, sip tls, t 120
```

application-group replication app assure replication, app assure svr backup, aspera, avamar, bluearc, celerra, centera, commvault, datadomain, doubletake, netvault replication, recoverpoint, snapmirror, vplex, vsphere replication ini, vsphere replication ong, vvr, zerto mgmt, zerto replication ## DNS Config dns cache dns-snoop enable dns cache http enable dns cache src-ip disable ## Access-List Config access-list Overlay BulkApps 1000 comment "" access-list Overlay BulkApps 1000 permit matchstr application: Box access-list Overlay BulkApps 1010 comment "" access-list Overlay BulkApps 1010 permit matchstr application:Dropbox access-list Overlay BulkApps 1020 comment "" access-list Overlay BulkApps 1020 permit matchstr application: Github access-list Overlay BulkApps 1030 comment "" access-list Overlay BulkApps 1030 permit matchstr app group: Replication access-list Overlay BulkApps 1040 comment "" access-list Overlay BulkApps 1040 permit matchstr application: Ftp access-list Overlay BulkApps 1050 comment "" access-list Overlay BulkApps 1050 permit matchstr application:Sftp access-list Overlay BulkApps 1060 comment "" access-list Overlay BulkApps 1060 permit matchstr application: Rsync-file-synchronization access-list Overlay CriticalApps 1000 comment "" access-list Overlay Critical Apps 1000 permit matchstr application: Webex access-list Overlay CriticalApps 1010 comment "" access-list Overlay Critical Apps 1010 permit matchstr application: Salesforce access-list Overlay CriticalApps 1020 comment "" access-list Overlay Critical Apps 1020 permit matchstr application: Share Point Online access-list Overlay CriticalApps 1030 comment "" access-list Overlay Critical Apps 1030 permit matchstr application: Office 365 Exchange access-list Overlay CriticalApps 1040 comment "" access-list Overlay Critical Apps 1040 permit matchstr application: Slack access-list Overlay Critical Apps 1050 comment "" access-list Overlay Critical Apps 1050 permit matchstr application: Workday access-list Overlay Critical Apps 1060 comment "" access-list Overlay Critical Apps 1060 permit matchstr application: Adp access-list Overlay CriticalApps 1070 comment "" access-list Overlay Critical Apps 1070 permit matchstr application: Service Now access-list Overlay CriticalApps 1080 comment "" access-list Overlay Critical Apps 1080 permit matchstr application: GoToMeeting access-list Overlay CriticalApps 1090 comment "" access-list Overlay CriticalApps 1090 permit matchstr application: Atlassian access-list Overlay CriticalApps 1100 comment "" access-list Overlay CriticalApps 1100 permit matchstr application: Marketo access-list Overlay CriticalApps 1110 comment "" access-list Overlay Critical Apps 1110 permit matchstr application: Tableau access-list Overlay CriticalApps 1120 comment "" access-list Overlay CriticalApps 1120 permit matchstr application:Citrix access-list Overlay CriticalApps 1130 comment "" access-list Overlay Critical Apps 1130 permit matchstr application: SAP access-list Overlay CriticalApps 1140 comment ""

access-list Overlay CriticalApps 1140 permit matchstr application: Ms terminal services

access-list Overlay CriticalApps 1150 comment ""

```
access-list Overlay Critical Apps 1150 permit matchstr application: Pcoip
   access-list Overlay Critical Apps 1160 comment ""
   access-list Overlay CriticalApps 1160 permit matchstr app group:SilverPeak
   access-list Overlay CriticalApps 1170 comment ""
   access-list Overlay Critical Apps 1170 permit matchstr application: Dns
   access-list Overlay DefaultOverlay 1000 comment "Default overlay for all other traffic."
   access-list Overlay DefaultOverlay 1000 permit matchstr any
   access-list Overlay RealTime 1010 comment ""
   access-list Overlay RealTime 1010 permit matchstr dscp:ef
   access-list Overlay RealTime 1020 comment ""
   access-list Overlay RealTime 1020 permit matchstr application: RingCentral
   access-list Overlay RealTime 1030 comment ""
   access-list Overlay RealTime 1030 permit matchstr application: 8X8
   access-list Overlay RealTime 1040 comment ""
   access-list Overlay RealTime 1040 permit matchstr application: SkypeForBusiness
   access-list Overlay RealTime 1050 comment ""
   access-list Overlay RealTime 1050 permit matchstr application: BlueJeans
   access-list Overlay RealTime 1060 comment ""
   access-list Overlay RealTime 1060 permit matchstr application: Zoom
   access-list Overlay RealTime 1070 comment ""
   access-list Overlay RealTime 1070 permit matchstr application: Rtp
   access-list Overlay RealTime 1080 comment ""
   access-list Overlay RealTime 1080 permit matchstr application: Rtp mux
   access-list Overlay RealTime 1090 comment ""
   access-list Overlay RealTime 1090 permit matchstr application: Rtp video
   access-list Overlay RealTime 1100 comment ""
   access-list Overlay RealTime 1100 permit matchstr application: Rtp voice
   access-list Overlay RealTime 1110 comment ""
   access-list Overlay RealTime 1110 permit matchstr application: Sip
   access-list Overlay RealTime 1120 comment ""
   access-list Overlay RealTime 1120 permit matchstr application: Sip tls
   access-list Overlay RealTime 1130 comment ""
   access-list Overlay RealTime 1130 permit matchstr application: H 323
   access-list Overlay RealTime 1140 comment ""
   access-list Overlay RealTime 1140 permit matchstr application:Rtcp
   access-list Overlay RealTime 1150 comment ""
   access-list Overlay RealTime 1150 permit matchstr app group: Voice
   access-list Overlay RealTime 1160 comment ""
   access-list Overlay RealTime 1160 permit matchstr app group:Real-Time
## Policy Config
   nat-map map1 65535 comment ""
   nat-map map1 65535 set nat-type no-nat direction none nat-ip auto fallback disable
   nat-map map1 activate
no opt-map map1 10000
no opt-map map1 10010
   opt-map map1 10020 comment ""
   opt-map map1 10020 match matchstr protocol:tcp,either port:443
no opt-map map1 10021
no opt-map map1 10030
no opt-map map1 10040
   opt-map map1 10070 comment ""
   opt-map map1 10070 match matchstr protocol:tcp,either port:9100
   opt-map map1 10070 set advanced-tcp e2e-fin-handling 0
   opt-map map1 10070 set advanced-tcp max-12w-buffer 256
   opt-map map1 10070 set advanced-tcp max-w21-buffer 256
no opt-map map1 10071
```

```
opt-map map1 65535 comment ""
opt-map map1 activate
gos-map map1 20000 comment "Generated by system for overlay: RealTime"
qos-map map1 20000 match matchstr overlay:1
gos-map map1 20000 set traffic-class 1 lan-gos trust-lan wan-gos trust-lan
qos-map map1 20001 comment "Generated by system for overlay: CaptWhite"
qos-map map1 20001 match matchstr overlay:7
gos-map map1 20001 set traffic-class 1 lan-gos trust-lan wan-gos be
qos-map map1 20002 comment "Generated by system for overlay: CriticalApps"
qos-map map1 20002 match matchstr overlay:2
gos-map map1 20002 set traffic-class 2 lan-gos trust-lan wan-gos trust-lan
qos-map map1 20003 comment "Generated by system for overlay: BulkApps"
gos-map map1 20003 match matchstr overlav:3
qos-map map1 20003 set traffic-class 3 lan-qos trust-lan wan-qos trust-lan
gos-map map1 20004 comment "Generated by system for overlay: DefaultOverlay"
qos-map map1 20004 match matchstr overlay:4
gos-map map1 20004 set traffic-class 4 lan-gos trust-lan wan-gos trust-lan
qos-map map1 20005 comment "RealTime overlay"
gos-map map1 20005 match acl Overlay RealTime
qos-map map1 20005 set traffic-class 1 lan-qos trust-lan wan-qos trust-lan
gos-map map1 20006 comment "CaptWhite overlay"
gos-map map1 20006 match matchstr vlan:25
qos-map map1 20006 set traffic-class 1 lan-qos trust-lan wan-qos be
gos-map map1 20007 comment "CriticalApps overlay"
gos-map map1 20007 match acl Overlay CriticalApps
qos-map map1 20007 set traffic-class 2 lan-qos trust-lan wan-qos trust-lan
qos-map map1 20008 comment "BulkApps overlay"
gos-map map1 20008 match acl Overlay BulkApps
qos-map map1 20008 set traffic-class 3 lan-qos trust-lan wan-qos trust-lan
qos-map map1 20009 comment "DefaultOverlay overlay"
gos-map map1 20009 match acl Overlay DefaultOverlay
qos-map map1 20009 set traffic-class 4 lan-qos trust-lan wan-qos trust-lan
gos-map map1 65535 comment ""
qos-map map1 65535 set traffic-class 1 lan-qos trust-lan wan-qos trust-lan
qos-map map1 activate
route-map map1 20000 comment "Generated by system for overlay: RealTime"
route-map map1 20000 match matchstr overlay:1
route-map map1 20000 set auto-opt-overlay 1 if-down pass-through
route-map map1 20001 comment "Generated by system for overlay: CaptWhite"
route-map map1 20001 match matchstr overlay:7
route-map map1 20001 set auto-opt-overlay 7 if-down pass-through
route-map map1 20002 comment "Generated by system for overlay: CriticalApps"
route-map map1 20002 match matchstr overlay:2
route-map map1 20002 set auto-opt-overlay 2 if-down pass-through
route-map map1 20003 comment "Generated by system for overlay: BulkApps"
route-map map1 20003 match matchstr overlay:3
route-map map1 20003 set auto-opt-overlay 3 if-down pass-through
route-map map1 20004 comment "Generated by system for overlay: DefaultOverlay"
route-map map1 20004 match matchstr overlay:4
route-map map1 20004 set auto-opt-overlay 4 if-down pass-through
route-map map1 20005 comment "RealTime overlay"
route-map map1 20005 match acl Overlay RealTime
route-map map1 20005 set auto-opt-overlay 1 if-down pass-through
route-map map1 20006 comment "CaptWhite overlay"
route-map map1 20006 match matchstr vlan:25
route-map map1 20006 set auto-opt-overlay 7 if-down pass-through
route-map map1 20007 comment "CriticalApps overlay"
route-map map1 20007 match acl Overlay CriticalApps
route-map map1 20007 set auto-opt-overlay 2 if-down pass-through
```

```
route-map map1 20008 comment "BulkApps overlay"
route-map map1 20008 match acl Overlay BulkApps
route-map map1 20008 set auto-opt-overlay 3 if-down pass-through
route-map map1 20009 comment "DefaultOverlay overlay"
route-map map1 20009 match acl Overlay DefaultOverlay
route-map map1 20009 set auto-opt-overlay 4 if-down pass-through
route-map map1 65535 comment ""
route-map map1 65535 set auto-optimize if-down pass-through
route-map map1 activate
rtmap default rtmap bgp inbound br 65535 comment ""
rtmap default rtmap bgp inbound br 65535 enable
rtmap default rtmap bgp inbound br 65535 match matchstr src proto:bgp
rtmap default rtmap bgp inbound br 65535 set setstr action:permit,bgp lcl pref:100
rtmap default rtmap bgp inbound pe 65535 comment ""
rtmap default rtmap bgp inbound pe 65535 enable
rtmap default rtmap bgp inbound pe 65535 match matchstr src proto:bgp
rtmap default rtmap bgp inbound pe 65535 set setstr action:permit,bgp lcl pref:100
rtmap default rtmap bgp outbound br 65485 comment ""
rtmap default rtmap bgp outbound br 65485 enable
rtmap default rtmap bgp outbound br 65485 match matchstr src proto:ss-ospf
rtmap default rtmap bgp outbound br 65485 set setstr action:permit
rtmap default rtmap bgp outbound br 65495 comment ""
rtmap default rtmap bgp outbound br 65495 enable
rtmap default rtmap bqp outbound br 65495 match matchstr src proto:ss-bqp
rtmap default rtmap bgp outbound br 65495 set setstr action:permit
rtmap default rtmap bgp outbound br 65505 comment ""
rtmap default rtmap bgp outbound br 65505 enable
rtmap default rtmap bgp outbound br 65505 match matchstr src proto:local
rtmap default rtmap bgp outbound br 65505 set setstr action:permit
rtmap default rtmap bgp outbound br 65515 comment ""
rtmap default rtmap bgp outbound br 65515 enable
rtmap default rtmap bgp outbound br 65515 match matchstr src proto:subshare
rtmap default rtmap bgp outbound br 65515 set setstr action:permit
rtmap default rtmap bgp outbound br 65525 comment ""
rtmap default rtmap bgp outbound br 65525 enable
rtmap default rtmap bgp outbound br 65525 match matchstr src proto:ospf
rtmap default rtmap bgp outbound br 65525 set setstr action:permit
rtmap default rtmap bgp outbound br 65535 comment ""
rtmap default rtmap bgp outbound br 65535 enable
rtmap default rtmap bgp outbound br 65535 match matchstr src proto:bgp
rtmap default rtmap bgp outbound br 65535 set setstr action:permit
rtmap default rtmap bgp outbound pe 65485 comment ""
rtmap default rtmap bgp outbound pe 65485 enable
rtmap default rtmap bqp outbound pe 65485 match matchstr src proto:ss-ospf
rtmap default rtmap bgp outbound pe 65485 set setstr action:deny
rtmap default rtmap bgp outbound pe 65495 comment ""
rtmap default rtmap bgp outbound pe 65495 enable
rtmap default rtmap bgp outbound pe 65495 match matchstr src proto:ss-bgp
rtmap default rtmap bgp outbound pe 65495 set setstr action:deny
rtmap default rtmap bgp outbound pe 65505 comment ""
rtmap default rtmap bgp outbound pe 65505 enable
rtmap default rtmap bgp outbound pe 65505 match matchstr src proto:local
rtmap default rtmap bgp outbound pe 65505 set setstr action:permit
rtmap default rtmap bgp outbound pe 65515 comment ""
rtmap default rtmap bgp outbound pe 65515 enable
rtmap default rtmap bgp outbound pe 65515 match matchstr src proto:subshare
rtmap default rtmap bgp outbound pe 65515 set setstr action:deny
rtmap default rtmap bgp outbound pe 65525 comment ""
rtmap default rtmap bgp outbound pe 65525 enable
```

```
rtmap default rtmap bgp outbound pe 65525 match matchstr src proto:ospf
   rtmap default rtmap bgp outbound pe 65525 set setstr action:permit
   rtmap default rtmap bgp outbound pe 65535 comment ""
   rtmap default rtmap bgp outbound pe 65535 enable
   rtmap default rtmap bgp outbound pe 65535 match matchstr src proto:bgp
   rtmap default rtmap bgp outbound pe 65535 set setstr action:permit
   rtmap default rtmap to ospf 65505 comment ""
   rtmap default rtmap to ospf 65505 enable
   rtmap default rtmap to ospf 65505 match matchstr src proto:local
   rtmap default rtmap to ospf 65505 set setstr action:deny
   rtmap default rtmap to ospf 65515 comment ""
   rtmap default rtmap to ospf 65515 enable
   rtmap default rtmap to ospf 65515 match matchstr src proto:subshare
   rtmap default rtmap to ospf 65515 set setstr action:permit
   rtmap default rtmap to ospf 65535 comment ""
   rtmap default rtmap to ospf 65535 enable
   rtmap default rtmap to ospf 65535 match matchstr src proto:bgp
   rtmap default rtmap to ospf 65535 set setstr action:deny
   rtmap default rtmap to subsh 65505 comment ""
   rtmap default rtmap to subsh 65505 enable
   rtmap default rtmap to subsh 65505 match matchstr src proto:local
   rtmap default rtmap to subsh 65505 set setstr action:permit
   rtmap default rtmap to subsh 65525 comment ""
   rtmap default rtmap to subsh 65525 enable
   rtmap default rtmap to subsh 65525 match matchstr src proto:ospf
   rtmap default rtmap to subsh 65525 set setstr action:deny
   rtmap default rtmap to subsh 65535 comment ""
   rtmap default rtmap to subsh 65535 enable
   rtmap default rtmap to subsh 65535 match matchstr src proto:bgp
   rtmap default rtmap to subsh 65535 set setstr action:deny
## Cluster and Flow-Redirection Config
   cluster interface mgmt1
   flow-redirection disable
   flow-redirection wait-time 50
## Flow-debug Config
   flow-debug disable
##
## Excess Flow Config
   excess-flow drop
## Redundancy Server Config
   vrrp vmac enable
## WCCP Service Config
   wccp disable
   wccp multicast-ttl 5
```

```
## CDP Configuration
   cdp holdtime 180
   cdp timer 60
   interface lan1 cdp enable
   interface wan1 cdp enable
## LLDP Configuration
   interface lan1 cdp enable
   interface wan0 cdp enable
   interface wan1 cdp enable
   lldp holdtime 120
   lldp timer 60
## TCA Configuration
   tca appliance-capacity total-flows rising raise-threshold 95 clear-threshold 0
   tca total-flows default rising raise-threshold 90 clear-threshold 85 sample-count 5
   tca appliance-capacity total-flows enable
   tca total-flows default enable
##
## SaaS Configuration
   saas disable
   saas ping-src-interface none
   saas rtt-interval 3600
   saas rtt-num-req-per-host 5
## SSL Configuration
   ssl builtin-signing enable
   ssl cert-substitution disable
## Interface Labels Configuration
##
   iflabel add lan-label 24
   iflabel add lan-label 25
   iflabel add lan-label 31
   iflabel add lan-label 4
   iflabel add lan-label 5
   iflabel add lan-label 9
   iflabel add wan-label 1
   iflabel add wan-label 16
   iflabel add wan-label 17
   iflabel add wan-label 18
   iflabel add wan-label 19
   iflabel add wan-label 2
   iflabel add wan-label 20
   iflabel add wan-label 21
   iflabel add wan-label 28
   iflabel add wan-label 29
   iflabel add wan-label 3
```

```
iflabel add wan-label 30
   iflabel add wan-label 32
  iflabel add wan-label 6
  iflabel add wan-label 7
## Overlay Configuration
  overlay BulkApps bonding-policy high-quality
  overlay BulkApps disqualify-behavior on-overlay-brownout
  overlav BulkApps fec-wait-time 80
  overlay BulkApps internet-traffic policy local-breakout backup
   overlay BulkApps internet-traffic policy local-breakout primary passThrough 220
   overlay BulkApps internet-traffic policy-list 0
   overlay BulkApps internet-traffic policy-list 0
  overlay BulkApps internet-traffic policy-list 0.000000000
   overlay BulkApps internet-traffic policy-list 1
  overlay BulkApps internet-traffic policy-list 1
   overlay BulkApps internet-traffic policy-list 80
  overlay BulkApps internet-traffic policy-list false
  overlay BulkApps internet-traffic policy-list local breakout, backhaul via overlay, drop
   overlay BulkApps load-balance-policy waterfall-by-quality
  overlay BulkApps max-fec-pct 20.000000000
   overlay BulkApps min-fec-pct 2.000000000
  overlay BulkApps poc-wait-time-max 100
  overlay BulkApps poc-wait-time-min 5
  overlay BulkApps reorder-speed 2
  overlay BulkApps topo node type non-hub
  overlay BulkApps wan-label INET1 boundary-behavior on-brownout
  overlay BulkApps wan-label INET1 cost 0
  overlay BulkApps wan-label INET1 priority 0
  overlay BulkApps wan-label INET2 boundary-behavior on-brownout
   overlav BulkApps wan-label INET2 cost 0
  overlay BulkApps wan-label INET2 priority 0
  overlay BulkApps wan-label LTE boundary-behavior on-blackout
  overlay BulkApps wan-label LTE cost 0
   overlay BulkApps wan-label LTE priority 2
   overlay BulkApps wan-label MPLS1 boundary-behavior on-brownout
   overlay BulkApps wan-label MPLS1 cost 0
  overlay BulkApps wan-label MPLS1 priority 0
   overlay BulkApps wan-label MPLS2 boundary-behavior on-brownout
   overlay BulkApps wan-label MPLS2 cost 0
  overlay BulkApps wan-label MPLS2 priority 0
  overlay BulkApps zone add 0
  overlay CaptWhite bonding-policy high-quality
   overlay CaptWhite disqualify-behavior on-overlay-brownout
  overlay CaptWhite fec-wait-time 80
   overlay CaptWhite internet-traffic policy local-breakout backup
  overlay CaptWhite internet-traffic policy local-breakout primary
   overlay CaptWhite internet-traffic policy-list 0
   overlay CaptWhite internet-traffic policy-list 0
  overlay CaptWhite internet-traffic policy-list 0.000000000
   overlay CaptWhite internet-traffic policy-list 1
  overlay CaptWhite internet-traffic policy-list 1
   overlay CaptWhite internet-traffic policy-list 80
  overlay CaptWhite internet-traffic policy-list backhaul via overlay, drop
  overlay CaptWhite internet-traffic policy-list false
   overlay CaptWhite load-balance-policy waterfall-by-quality
   overlay CaptWhite max-fec-pct 20.000000000
```

```
overlay CaptWhite min-fec-pct 2.000000000
overlay CaptWhite poc-wait-time-max 100
overlay CaptWhite poc-wait-time-min 5
overlay CaptWhite reorder-speed 2
overlay CaptWhite topo node type non-hub
overlay CaptWhite wan-label INET1 boundary-behavior on-brownout
overlay CaptWhite wan-label INET1 cost 0
overlay CaptWhite wan-label INET1 priority 0
overlay CaptWhite wan-label INET2 boundary-behavior on-brownout
overlay CaptWhite wan-label INET2 cost 0
overlay CaptWhite wan-label INET2 priority 0
overlay CaptWhite wan-label Starlink1 boundary-behavior on-blackout
overlay CaptWhite wan-label Starlink1 cost 0
overlay CaptWhite wan-label Starlink1 priority 1
overlay CaptWhite wan-label Starlink2 boundary-behavior on-blackout
overlay CaptWhite wan-label Starlink2 cost 0
overlay CaptWhite wan-label Starlink2 priority 1
overlay CaptWhite wan-label Starlink3 boundary-behavior on-brownout
overlay CaptWhite wan-label Starlink3 cost 0
overlay CaptWhite wan-label Starlink3 priority 0
overlay CaptWhite wan-label Starlink4 boundary-behavior on-brownout
overlay CaptWhite wan-label Starlink4 cost 0
overlay CaptWhite wan-label Starlink4 priority 0
overlay CaptWhite wan-label Starlink5 boundary-behavior on-brownout
overlay CaptWhite wan-label Starlink5 cost 0
overlay CaptWhite wan-label Starlink5 priority 0
overlay CaptWhite wan-label Starlink6 boundary-behavior on-brownout
overlay CaptWhite wan-label Starlink6 cost 0
overlay CaptWhite wan-label Starlink6 priority 0
overlay CaptWhite zone add 0
overlay CriticalApps bonding-policy high-quality
overlay Critical Apps disqualify-behavior on-overlay-brownout
overlay CriticalApps fec-wait-time 80
overlay CriticalApps internet-traffic policy local-breakout backup
overlay CriticalApps internet-traffic policy local-breakout primary passThrough 219
overlay CriticalApps internet-traffic policy-list 0
overlay CriticalApps internet-traffic policy-list 0
overlay CriticalApps internet-traffic policy-list 0.000000000
overlay CriticalApps internet-traffic policy-list 1
overlay CriticalApps internet-traffic policy-list 1
overlay CriticalApps internet-traffic policy-list 80
overlay CriticalApps internet-traffic policy-list false
overlay CriticalApps internet-traffic policy-list local breakout, backhaul via overlay, drop
overlay CriticalApps load-balance-policy waterfall-by-quality
overlay CriticalApps max-fec-pct 20.000000000
overlay CriticalApps min-fec-pct 2.000000000
overlay CriticalApps poc-wait-time-max 100
overlay CriticalApps poc-wait-time-min 5
overlay CriticalApps reorder-speed 2
overlay CriticalApps topo node type non-hub
overlay CriticalApps wan-label INET1 boundary-behavior on-brownout
overlay CriticalApps wan-label INET1 cost 0
overlay CriticalApps wan-label INET1 priority 0
overlay CriticalApps wan-label INET2 boundary-behavior on-brownout
overlay CriticalApps wan-label INET2 cost 0
overlay CriticalApps wan-label INET2 priority 0
overlay CriticalApps wan-label LTE boundary-behavior on-blackout
overlay CriticalApps wan-label LTE cost 0
overlay CriticalApps wan-label LTE priority 2
```

```
overlay CriticalApps wan-label MPLS1 boundary-behavior on-brownout
overlay CriticalApps wan-label MPLS1 cost 0
overlay CriticalApps wan-label MPLS1 priority 0
overlay CriticalApps wan-label MPLS2 boundary-behavior on-brownout
overlay CriticalApps wan-label MPLS2 cost 0
overlay CriticalApps wan-label MPLS2 priority 0
overlay CriticalApps zone add 0
overlay DefaultOverlay bonding-policy high-quality
overlay DefaultOverlay disqualify-behavior on-overlay-brownout
overlay DefaultOverlay fec-wait-time 80
overlay DefaultOverlay internet-traffic policy local-breakout backup
overlay DefaultOverlay internet-traffic policy local-breakout primary
overlay DefaultOverlay internet-traffic policy-list 0
overlay DefaultOverlay internet-traffic policy-list 0
overlay DefaultOverlay internet-traffic policy-list 0.00000000
overlay DefaultOverlay internet-traffic policy-list 1
overlay DefaultOverlay internet-traffic policy-list 1
overlay DefaultOverlay internet-traffic policy-list 80
overlay DefaultOverlay internet-traffic policy-list backhaul via overlay, drop
overlay DefaultOverlay internet-traffic policy-list false
overlay DefaultOverlay load-balance-policy waterfall-by-quality
overlay DefaultOverlay max-fec-pct 20.000000000
overlay DefaultOverlay min-fec-pct 2.000000000
overlav DefaultOverlav poc-wait-time-max 100
overlay DefaultOverlay poc-wait-time-min 5
overlay DefaultOverlay reorder-speed 2
overlay DefaultOverlay topo node type non-hub
overlay DefaultOverlay wan-label INET1 boundary-behavior on-brownout
overlay DefaultOverlay wan-label INET1 cost 0
overlay DefaultOverlay wan-label INET1 priority 0
overlay DefaultOverlay wan-label INET2 boundary-behavior on-brownout
overlay DefaultOverlay wan-label INET2 cost 0
overlav DefaultOverlav wan-label INET2 priority 0
overlay DefaultOverlay wan-label LTE boundary-behavior on-blackout
overlay DefaultOverlay wan-label LTE cost 0
overlay DefaultOverlay wan-label LTE priority 2
overlay DefaultOverlay wan-label MPLS1 boundary-behavior on-brownout
overlay DefaultOverlay wan-label MPLS1 cost 0
overlay DefaultOverlay wan-label MPLS1 priority 0
overlay DefaultOverlay wan-label MPLS2 boundary-behavior on-brownout
overlay DefaultOverlay wan-label MPLS2 cost 0
overlay DefaultOverlay wan-label MPLS2 priority 0
overlay DefaultOverlay zone add 0
overlay RealTime bonding-policy high-availability
overlay RealTime disqualify-behavior on-overlay-brownout
overlav RealTime fec-wait-time 2
overlay RealTime internet-traffic policy local-breakout backup
overlay RealTime internet-traffic policy local-breakout primary passThrough 218
overlay RealTime internet-traffic policy-list 0
overlay RealTime internet-traffic policy-list 0
overlay RealTime internet-traffic policy-list 0.000000000
overlay RealTime internet-traffic policy-list 1
overlay RealTime internet-traffic policy-list 1
overlay RealTime internet-traffic policy-list 80
overlay RealTime internet-traffic policy-list false
overlay RealTime internet-traffic policy-list local breakout, backhaul via overlay, drop
overlay RealTime load-balance-policy waterfall-by-quality
overlay RealTime max-fec-pct 100.000000000
overlay RealTime min-fec-pct 100.000000000
```

```
overlay RealTime poc-wait-time-max 100
   overlay RealTime poc-wait-time-min 5
   overlay RealTime reorder-speed 2
   overlay RealTime topo node type non-hub
   overlay RealTime wan-label INET1 boundary-behavior on-brownout
   overlay RealTime wan-label INET1 cost 0
   overlay RealTime wan-label INET1 priority 0
   overlay RealTime wan-label INET2 boundary-behavior on-brownout
   overlay RealTime wan-label INET2 cost 0
   overlay RealTime wan-label INET2 priority 0
   overlay RealTime wan-label LTE boundary-behavior on-blackout
   overlay RealTime wan-label LTE cost 0
   overlay RealTime wan-label LTE priority 2
   overlay RealTime wan-label MPLS1 boundary-behavior on-brownout
   overlay RealTime wan-label MPLS1 cost 0
   overlay RealTime wan-label MPLS1 priority 0
   overlay RealTime wan-label MPLS2 boundary-behavior on-brownout
   overlay RealTime wan-label MPLS2 cost 0
   overlay RealTime wan-label MPLS2 priority 0
   overlay RealTime zone add 0
   overlay add BulkApps 3
   overlay add CaptWhite 7
   overlay add CriticalApps 2
   overlav add DefaultOverlav 4
   overlay add RealTime 1
   overlay common internal-subnets 224.0.0.0/4,169.254.0.0/16,192.168.0.0/16,172.16.0.0/12,10.0.0.0/8
   overlay common internal-subnetsv6 ""
   overlay common route-match enable
##
##
   bfd segment 0 detect-multiplier 3
no bfd segment 0 enable
   bfd segment 0 rx-interval 300
   bfd segment 0 tx-interval 300
## BGP Router Configuration
   bgp ecmp enable
no bgp segment 0 as-path-advertise enable
   bgp segment 0 asn 65534
no bgp segment 0 graceful-restart enable
   bgp segment 0 graceful-restart max-restart-time 120
   bgp segment 0 graceful-restart stale-path-time 150
   bgp segment 0 log-nbr-msgs enable
   bgp segment 0 router-id 0.0.0.0
   router adv-loop count 10
   router adv-loop interval 900
## OSPF Router Configuration
   ospf disable
   ospf opaque enable
   ospf redistribute route-map default rtmap to ospf outbound
   ospf segment 0 opaque enable
   ospf segment 0 redistribute route-map default rtmap to ospf outbound
```

```
ospf segment 0 router-id 0.0.0.0
```

vxlan vtep-interface ""

```
## IP Tracking Operation Configuration
   ip-tracking action DN ACTION tun-dn om passThrough 218 attributes type=tun-dn; tun-alias=Passthrough INET2 RealTime
   ip-tracking action DN ACTION tun-dn om passThrough 219 attributes type=tun-dn; tun-alias=Passthrough INET2 CriticalApps
   ip-tracking action DN ACTION tun-dn om passThrough 220 attributes type=tun-dn;tun-alias=Passthrough INET2 BulkApps
   ip-tracking action UP ACTION tun-up om passThrough 218 attributes type=tun-up; tun-alias=Passthrough INET2 RealTime
   ip-tracking action UP ACTION tun-up om passThrough 219 attributes type=tun-up; tun-alias=Passthrough INET2 CriticalApps
   ip-tracking action UP ACTION tun-up om passThrough 220 attributes type=tun-up; tun-alias=Passthrough INET2 BulkApps
   ip-tracking manager MGR ip-monitor om passThrough 218 attributes operation=OPERATION om passThrough 218;up-action=UP ACTION tun-
up om passThrough 218;dn-action=DN ACTION tun-dn om passThrough 218;interval=30
   ip-tracking manager MGR ip-monitor om passThrough 218 comment generated by overlay manager
   ip-tracking manager MGR ip-monitor om passThrough 219 attributes operation=OPERATION om passThrough 219;up-action=UP ACTION tun-
up om passThrough 219;dn-action=DN ACTION tun-dn om passThrough 219;interval=30
   ip-tracking manager MGR ip-monitor om passThrough 219 comment generated by overlay manager
   ip-tracking manager MGR ip-monitor om passThrough 220 attributes operation=OPERATION om passThrough 220;up-action=UP ACTION tun-
up om passThrough 220;dn-action=DN ACTION tun-dn om passThrough 220;interval=30
   ip-tracking manager MGR ip-monitor om passThrough 220 comment generated by overlay manager
   ip-tracking operation OPERATION om passThrough 218 attributes type=ip-monitor; ka=1; ip-monitor-ip=sp-ipsla.silverpeak.cloud, 8.8.8.8.8.8.4.4; up-
thresh=3;dn-thresh=30;port-label=6;sample-int=300;loss-up-thresh=0;loss-dn-thresh=0;rtt-up-thresh=0;rtt-dn-thresh=0;metric-combination=metric-or
   ip-tracking operation OPERATION om passThrough 219 attributes type=ip-monitor; ka=1; ip-monitor-ip=sp-ipsla.silverpeak.cloud, 8.8.8.8.8.8.4.4; up-
thresh=3;dn-thresh=30;port-label=6;sample-int=300;loss-up-thresh=0;loss-dn-thresh=0;rtt-up-thresh=0;rtt-dn-thresh=0;metric-combination=metric-or
   ip-tracking operation OPERATION om passThrough 220 attributes type=ip-monitor; ka=1; ip-monitor-ip=sp-ipsla.silverpeak.cloud, 8.8.8.8.8.8.4.4; up-
thresh=3;dn-thresh=30;port-label=6;sample-int=300;loss-up-thresh=0;rtt-up-thresh=0;rtt-dn-thresh=0;metric-combination=metric-or
## Virtual Interface Configuration
   interface 1o20000 virtual loopback ipaddress 10.250.28.131 netmask 255.255.255.255
   interface pim0 virtual pim ipaddress 169.254.124.1 netmask 255.255.255.0
   interface pim1 virtual pim ipaddress 169.254.125.1 netmask 255.255.255.0
   interface pim2 virtual pim ipaddress 169.254.126.1 netmask 255.255.255.0
## PIM SM Configuration
   igmp interface lan0 enable
   multicast enable
  multicast filtername ""
   pim interface lan0 enable
   pim rp ip 172.16.33.1
## Segment Configuration
   segment id 0 Default
   segment id 0 zone 0 idx 0
   segment id 0 zone 1 idx 1
   segment id 0 zone 2 idx 2
   segment id 0 zone 65535 idx 255
   segmentation enable
   vxlan port 4789
   vxlan segment Default role-id 0
   vxlan segment Default vni 4294967295
   vxlan segment Default zone 0
```

```
## Express apps configuration
   app express * tunnel * add real cost ""
   app express * tunnel * add synthetic cost ""
   app express * tunnel * deduct real cost ""
   app express * tunnel * deduct synthetic cost ""
##
##
   system auto-mac-configure disable
   system bypass mode default
## Network management configuration
   banner login "You are accessing a HPE Aruba Networking Information System (IS) that is provided for HPE Aruba Networking Simulated-authorized use
only.
By using this IS (which includes any device attached to this IS), you consent to the following conditions:
-HPE Aruba Networking routinely intercepts and monitors communications on this IS for purposes including, but not limited to, penetration testing,
network operations and defense, and personnel misconduct (PM).
-At any time, HPE Aruba Networking may inspect and seize data stored on this IS.
-Communications using, or data stored on, this IS are not private, are subject to routine monitoring, interception, and search, and may be disclosed
or used for any HPE Aruba Networking-authorized purpose.
-This IS includes security measures (e.g., authentication and access controls) to protect HPE Aruba Networking interests--not for your personal
benefit or privacy.
-Notwithstanding the above, using this IS does not constitute consent to PM investigative searching or monitoring of the content of privileged
communications, or work product, related to personal representation or services by attorneys, psychotherapists, or clergy, and their assistants. Such
communications and work product are private and confidential. See User Agreement for details."
   banner motd "You are accessing a HPE Aruba Networking Information System (IS) that is provided for HPE Aruba Networking Simulated-authorized use
only.
By using this IS (which includes any device attached to this IS), you consent to the following conditions:
-HPE Aruba Networking routinely intercepts and monitors communications on this IS for purposes including, but not limited to, penetration testing,
network operations and defense, and personnel misconduct (PM).
-At any time, HPE Aruba Networking may inspect and seize data stored on this IS.
-Communications using, or data stored on, this IS are not private, are subject to routine monitoring, interception, and search, and may be disclosed
or used for any HPE Aruba Networking-authorized purpose.
-This IS includes security measures (e.g., authentication and access controls) to protect HPE Aruba Networking interests -- not for your personal
benefit or privacy.
-Notwithstanding the above, using this IS does not constitute consent to PM investigative searching or monitoring of the content of privileged
communications, or work product, related to personal representation or services by attorneys, psychotherapists, or clergy, and their assistants. Such
communications and work product are private and confidential. See User Agreement for details."
   cli default allow-all-show disable
   cli default auto-logout 15.0
   clock timezone UTC
   flow-export active-flow-timeout 1
   flow-export destination 1 0.0.0.0 2055 netflow5
   flow-export destination 2 0.0.0.0 2055 netflow5
   flow-export disable
   flow-export engine-id 1
   flow-export engine-type 1
   flow-export ipfix template refresh-timeout 10
   flow-export optional-ies app-perf disable
   flow-export optional-ies zbf disable
```

```
flow-export privacy-mask disable
   flow-export privacy-mask ipv4 prefix-length 24
no flow-export traffic-type lan-rx
no flow-export traffic-type lan-tx
no flow-export traffic-type wan-rx
   flow-export traffic-type wan-tx
no ntp disable
no ntp server pool.ntp.org disable
   ntp server pool.ntp.org version 4
no ntp server time.nist.gov disable
   ntp server time.nist.gov version 4
   portal airgap mode disable
   portal websocket enable
no security certificate verify orchestrator
   security certificate verify portal
no security certificate verify stats-collector
   security csrf enable
   snmp-server community public ro
no snmp-server enable
no snmp-server enable traps
   snmp-server listen enable
   snmp-server traps event raise-alarm
   snmp-server user admin
no snmp-server user admin v3 enable
   snmp-server user admin v3 encrypted auth sha "" priv aes-128 ""
   web apidocs disable
   web appliance-tag 1
   web appliance-tag 2
   web appliance-tag 3
   web appliance-tag 4
   web appliance-tag 5
   web appliance-tag 6
   web appliance-tag 7
   web appliance-tag 8
   web auto-logout 15
   web http disable
   web https enable
   web session max 10
   web ssl-cipher-list TLSv1.2+FIPS:!kRSA:!eNULL:!aNULL:!3DES
   websocket orchestrator 50.211.133.114
   websocket orchestrator 50.211.133.114 options
{\"type\":\"Orchestrator\",\"ws count\":1,\"wsPingTime\":20000,\"wsIdleTime\":120000,\"wsFailoverMode\":\"c\"}
##
## SSH and Key configuration
   ssh client global host-key-check no
   ssh client global known-hosts-file /dev/null
   ssh server ca-sign-algos-accepted ecdsa-sha2-nistp256 ecdsa-sha2-nistp384 ecdsa-sha2-nistp521 ssh-ed25519 rsa-sha2-512 rsa-sha2-256
   ssh server enable
   ssh server encryption-algos aes128-cbc aes192-cbc aes256-cbc aes128-gcm@openssh.com aes256-gcm@openssh.com
   ssh server host-key-algos ecdsa-sha2-nistp256-cert-v01@openssh.com ecdsa-sha2-nistp384-cert-v01@openssh.com ecdsa-sha2-nistp521-cert-
v01@openssh.com ssh-ed25519-cert-v01@openssh.com rsa-sha2-512-cert-v01@openssh.com rsa-sha2-256-cert-v01@openssh.com ecdsa-sha2-nistp256 ecdsa-sha2-
nistp384 ecdsa-sha2-nistp521 ssh-ed25519 rsa-sha2-512 rsa-sha2-256
   ssh server key-exchange-algos diffie-hellman-group14-sha256 diffie-hellman-group16-sha512 diffie-hellman-group18-sha512 diffie-hellman-group-
exchange-sha256 ecdh-sha2-nistp256 ecdh-sha2-nistp384 ecdh-sha2-nistp521 curve25519-sha256 curve25519-sha256@libssh.org
   ssh server mac-algos hmac-sha2-256 hmac-sha2-512
   ssh server ports 22
```

ssh server pub-key-algos-accepted ecdsa-sha2-nistp256-cert-v01@openssh.com ecdsa-sha2-nistp384-cert-v01@openssh.com ecdsa-sha2-nistp521-cert-v01@openssh.com ssh-ed25519-cert-v01@openssh.com rsa-sha2-256-cert-v01@openssh.com ecdsa-sha2-nistp256 ecdsa-sha2-nistp384 ecdsa-sha2-nistp521 ssh-ed25519 rsa-sha2-512 rsa-sha2-256

```
##
##
   ipsec authentication-algos sha1, sha256, sha384, sha512, aes128gmac, aes256gmac
   ipsec dh-groups 1,2,5,14,15,16,17,18,19,20,21,26,31
   ipsec encryption-algos aes256, aes128, aes128gcm16, aes256gcm16
   ipsec ike-authentication-algos shal, sha256, sha384, sha512
   ipsec ike-encryption-algos aes256,aes128,aes128gcm16,aes256gcm16
   ipsec ike-prf-algos prfsha256,prfsha384,prfsha512
   ipsec pfs-groups 1,2,5,14,15,16,17,18,19,20,21,26,31
## Miscellaneous other settings
   internal set modify - /cn/mrtrd/confiq/pim/intf/lan0/dr priority value uint32 1
   internal set modify - /cn/mrtrd/config/pim/intf/lan0/hello interval value uint32 30
   internal set modify - /cn/mrtrd/config/pim/intf/lan0/join prune interval value uint32 30
   internal set modify - /cn/tunneld/user profile/config/defer secmap for unknown role value bool false
   internal set modify - /cn/user role/config/id/0 value uint8 0
   internal set modify - /cn/user role/config/id/0/qpid value uint16 0
   internal set modify - /cn/user role/config/id/0/role str value string default
   internal set modify - /cn/user role/config/id/1 value uint8 1
   internal set modify - /cn/user role/config/id/1/gpid value uint16 65535
   internal set modify - /cn/user role/config/id/1/role str value string unknown
   internal set modify - /cn/user role/config/id/2 value uint8 2
   internal set modify - /cn/user role/config/id/2/gpid value uint16 1
   internal set modify - /cn/user role/config/id/2/role str value string VIP
   internal set modify - /mgmt/config/vrf/apps/other/displayname value string "Other VRF mgmt Apps"
   internal set modify - /net/if2/config/virtual/loopback/lo20000 value string lo20000
   internal set modify - /net/if2/config/virtual/loopback/lo20000/admin value bool true
   internal set modify - /net/if2/config/virtual/loopback/lo20000/label value string 9
   internal set modify - /net/if2/config/virtual/loopback/lo20000/vrf id value uint16 0
   internal set modify - /net/if2/config/virtual/loopback/lo20000/zone value uint16 0
   internal set modify - /ntp/auth algs value string SHA256, SHA384, SHA512
   internal set modify - /ntp/selkey value uint32 1
   internal set modify - /pm/process/certd/launch path value string /sbin/certd wrapper.sh
   internal set modify - /pm/process/mrtrd/launch enabled value bool true
   internal set modify - /pm/process/snmpd/launch enabled value bool true
   internal set modify - /tls/config/tls server/cipher suite value string
TLS AES 128 GCM SHA256,TLS AES 256 GCM SHA384,TLS AES 128 CCM SHA256,TLS ECDHE ECDSA WITH AES 128 GCM SHA256,TLS ECDHE ECDSA WITH AES 256 GCM SHA384,
TLS ECDHE RSA WITH AES 128 GCM SHA256,TLS ECDHE RSA WITH AES 256 GCM SHA384,TLS DHE RSA WITH AES 128 GCM SHA256,TLS DHE RSA WITH AES 256 GCM SHA384
KW-10106 #
```