-- P-1 FastEthernet0/0 to P-2 FastEthernet0/0

Apply a display filter ... <⌘/>

No.	Time	Delta	Type	L2 SRC	L2 DST	Length	What	DSCP	L3 SRC	L3 DST	SRC SCK	DST SCK	Info
241	2023-0...	0.044	MPLS	ca:07:0b:7b:00:...	ca:08:0b:82:00:70	164	ICMP	0x00,0x...	41.0.0.1	51.0.0.1			Echo (ping) reply id=0x000a, seq=9...

Frame 211: 164 bytes on wire (1312 bits), 164 bytes captured (1312 bits) on interface -, id 0
Ethernet II, Src: ca:01:04:5a:00:08 (ca:01:04:5a:00:08), Dst: ca:02:04:6a:00:08 (ca:02:04:6a:00:08)
  > Destination: ca:02:04:6a:00:08 (ca:02:04:6a:00:08)
  > Source: ca:01:04:5a:00:08 (ca:01:04:5a:00:08)
    Type: MPLS label switched packet (0x8847)
MultiProtocol Label Switching Header, Label: 20, Exp: 5, S: 0, TTL: 254
    0000 0000 0000 0001 0100 .... = MPLS Label: 20 (0x00014)
    .... 101. .... = MPLS Experimental Bits: 5
    ....0 .... = MPLS Bottom Of Label Stack: 0
    .... 1111 1110 = MPLS TTL: 254
MultiProtocol Label Switching Header, Label: 23, Exp: 5, S: 1, TTL: 255
    0000 0000 0000 0001 0111 .... = MPLS Label: 23 (0x00017)
    .... 101. .... = MPLS Experimental Bits: 5
    ....1 .... = MPLS Bottom Of Label Stack: 1
    .... 1111 1111 = MPLS TTL: 255
PW Ethernet Control Word
Ethernet II, Src: ca:07:0b:7b:00:70 (ca:07:0b:7b:00:70), Dst: ca:08:0b:82:00:70 (ca:08:0b:82:00:70)
  > Destination: ca:08:0b:82:00:70 (ca:08:0b:82:00:70)
  > Source: ca:07:0b:7b:00:70 (ca:07:0b:7b:00:70)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 172.17.0.41, Dst: 172.17.0.51
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
  > Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 124
    Identification: 0x00b6 (182)
  > 000. .... = Flags: 0x0
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 255
    Protocol: Generic Routing Encapsulation (47)
    Header Checksum: 0x621e [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 172.17.0.41
    Destination Address: 172.17.0.51
Generic Routing Encapsulation (IP)
  > Flags and Version: 0x0000
    Protocol Type: IP (0x0800)
Internet Protocol Version 4, Src: 41.0.0.1, Dst: 51.0.0.1
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
  > Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 100
    Identification: 0x032c (812)
  > 000. .... = Flags: 0x0
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 255
    Protocol: ICMP (1)
    Header Checksum: 0x5c6b [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 41.0.0.1
    Destination Address: 51.0.0.1
Internet Control Message Protocol