

№1

Vagrant Rocky Linux

box- client, Rocky Linux VirtualBox Vagrant Rocky Linux: Packer, server provision-

№1

:

1. box- Rocky Linux VirtualBox Packer;
2. server client box- ;
3. (, , NAT server client) provision;
4. (box- , Packer Vagrant)
5. ; , .

Vagrant

Vagrantfile

Box- —

. Vagrantfile —

Vagrant

: , , , , provision- .

box- Packer. :

.

Rocky Linux ks.cfg Kickstart.
provision- Vagrant.

Linux Packer Vagrant:

```
mkdir -p /var/tmp/rbabaev/packer  
mkdir -p /var/tmp/rbabaev/vagrant
```

, /var/tmp/user_name, user_name —
rbabaev.
/var/tmp/rbabaev/packer ISO- Rocky Linux:

```
Rocky-9.4-x86_64-minimal.iso
```

Packer Vagrant:

- vagrant-rocky.pkr.hcl — Packer box- ;
- http/ ks.cfg — kickstart- ;
- vagrant/ Vagrantfile Makefile Vagrant.

box- **Packer**

packer Packer :

```
cd /var/tmp/rbabaev/packer  
make init
```

init Makefile .config/packer virtualbox
vagrant.

box- :

```
make box
```

```
make box      packer build      vagrant-rocky.pkr.hcl. Packer
               VirtualBox,      Rocky Linux,
box- vagrant-virtualbox-rocky-9-x86_64.box.
```

```
box-          Vagrant
```

```
box- vagrant-virtualbox-rocky-9-x86_64.box      /var/tmp/rbabaev/vagrant:
```

```
cp /var/tmp/rbabaev/packer/vagrant-virtualbox-rocky-9-x86_64.box \
/var/tmp/rbabaev/vagrant/
```

```
vagrant      Vagrant:
```

```
cd /var/tmp/rbabaev/vagrant
make addbox
```

```
make addbox      vagrant box add rocky9 vagrant-virtualbox-rocky-9-
x86_64.box,      rocky9.
```

```
Vagrant-      provision-
```

```
/var/tmp/rbabaev/vagrant      provision:
```

```
mkdir -p provision/default
mkdir -p provision/server
mkdir -p provision/client
```

```
default, server  client      :
```

```
provision/default/01-dummy.sh
provision/default/01-user.sh
provision/default/01-hostname.sh
provision/server/01-dummy.sh
provision/server/02-forward.sh
provision/client/01-dummy.sh
provision/client/01-routing.sh
```

```
default      ,      ;      server  client —
.
```

server client

server Linux :

```
cd /var/tmp/rbabaev/vagrant
make server-up
```

vagrant up server VirtualBox;
server rocky9.

client:

```
make client-up
```

vagrant (vagrant, vagrant)

provision/default/01-user.sh wheel (sudo).
rbabaev:

```
#!/bin/bash
echo "Provisioning script $0"
username=rbabaev
userpassword=123456
encpassword=`openssl passwd -1 ${userpassword}`
id -u $username
if [[ $? ]]
then
adduser -G wheel -p ${encpassword} ${username}
homedir=`getent passwd ${username} | cut -d: -f6`
echo "export PS1='[\u@\H \W]\\$ '" >> ${homedir}/.bashrc
fi
```

rbabaev 123456, wheel .

provision/default/01-hostname.sh :

```
#!/bin/bash
username=rbabaev
hostnamectl set-hostname "${HOSTNAME%%.*}.${username}.net
```

server.rbabaev.net client.rbabaev.net.

NAT

provision/server/02-forward.sh

NAT:

```
#!/bin/bash
echo "Provisioning script $0"
echo "Enable forwarding"
echo "net.ipv4.ip_forward = 1" > /etc/sysctl.d/90-forward.conf
sysctl -w net.ipv4.ip_forward=1
echo "Configure masquerading"
firewall-cmd --add-masquerade --permanent
firewall-cmd --reload
restorecon -vR /etc
```

(NAT)

provision/client/01-routing.sh

```
#!/bin/bash
echo "Provisioning script $0"
nmcli connection modify "System eth1" ipv4.gateway "192.168.1.1"
nmcli connection up "System eth1"
nmcli connection modify eth0 ipv4.never-default true
nmcli connection modify eth0 ipv6.never-default true
nmcli connection down eth0
nmcli connection up eth0
```

(192.168.1.1)

;

eth0

:

```
ping 192.168.1.1
```

:

```
ping 8.8.8.8
curl https://www.google.com/
```

ping

HTML-

NAT

.

1. vagrant-rocky.pkr.hcl:

```
<< vagrant-rocky.pkr.hcl >>
```

2. ks.cfg:

```
<< ks.cfg >>
```

3. Vagrantfile server client:

```
<< Vagrantfile >>
```

4. Makefile Packer:

```
<< Makefile (packer) >>
```

5. Makefile Vagrant:

```
<< Makefile (vagrant) >>
```

6. provision/default/01-user.sh, 01-hostname.sh, 01-dummy.sh, provision/server/02-forward.sh provision/client/01-routing.sh:

```
<< PROVISION- >>
```

Rocky Linux.

box-

— server client.

Rocky Linux,

NAT

provision

Vagrant
Vagrant,

box-