



南方科技大学
SOUTHERN UNIVERSITY OF SCIENCE AND TECHNOLOGY

C/C++ Program Design

CS205

Prof. Shiqi Yu (于仕琪)

yusq@sustech.edu.cn

<http://faculty.sustech.edu.cn/yusq/>



About me



Prof. Shiqi Yu (于仕琪)

- Department of Computer Science and Engineering in Southern University of Science and Technology(南方科技大学计算机科学与工程系)
- **Office** : Room 312, South Tower, CoE Building
- **Email** : yusq@sustech.edu.cn
- Homepage: <http://faculty.sustech.edu.cn/yusq/>





My Open Source Project



ShiqiYu/libfacedetection: An op

https://github.com/ShiqiYu/libfacedetection

Search or jump to...

Pulls

Issues

Marketplace

Explore

+

ShiqiYu / libfacedetection

Unwatch546

Unstar10.4k

Fork2.8k

Code

Issues39

Pull requests3

Actions

Projects

Wiki

master

Go to file

Add file

Code

About

fengyuentau update changelog10 days ago173

example	remove legacy	10 days ago
images	Delete qrcode_for_yu.jpg	14 months ago
mobile	update apk for bgr	2 years ago
opencv_dnn	remove legacy; reorganize repo structure	10 days ago
src	enable different _MALLOC_ALIGN for dif...	2 months ago

An open source library for face detection in images. The face detection speed can reach 1000FPS.

armcnnface-detection

Readme

View license





南方科技大学
SOUTHERN UNIVERSITY OF SCIENCE AND TECHNOLOGY

About the Course



Grade Component

- Quiz: 5% (the best N-1 scores)
- Lab Attendance and Exercise: 5% (the best N-1 scores)
- Project: 65%
 - ~5 projects, some are easy projects
 - Grading standard:
 - 90-100: Finish all tasks almost perfectly
 - 80-90: Finish all tasks well
 - 70-80: Finish all tasks
- Exam: 25%



Honesty

- Get code from the internet for labs/assignments is perfectly **OK**
 - When you borrow, just say it.
 - You don't need to reinvent the wheel


不必造轮子



- **DON'T** pretend that you are the author of something that you didn't write. Otherwise, the score will be **ZERO**!

Resources

- **Blackboard:**
 - C/C++ Program Design
- **Useful websites:**
 - <https://en.cppreference.com/w/>
 - <https://www.w3schools.com/cpp/>
 - <http://cpp.sh/>
 - <https://www.onlinegdb.com/>





南方科技大学
SOUTHERN UNIVERSITY OF SCIENCE AND TECHNOLOGY

The First Example



hello.cpp

```
//C++ example in C++11
```

```
#include <iostream>
```

```
#include <vector>
```

```
#include <string>
```

```
using namespace std;
```

```
int main()
```

```
{
```

```
    vector<string> msg {"Hello", "C++", "World", "!"};
```

```
    for (const string& word : msg)
```

```
    {
```

```
        cout << word << " ";
```

```
    }
```

```
    cout << endl;
```

```
}
```



Compile and run the program

- Compile hello.cpp

```
g++ hello.cpp
```

C: gcc hello.c
./a.out

- Initialization of `msg` is a C++11 extension. We need

```
g++ hello.cpp --std=c++11
```

--std=c++11

- Executable file can be generated as a.out. Change the output filename by -o option

```
g++ hello.cpp --std=c++11 -o hello
```

- Execute

```
./hello
```

C:
gcc hello.c -o hello
./hello.out



南方科技大学
SOUTHERN UNIVERSITY OF SCIENCE AND TECHNOLOGY

Different Programming Languages




Binary Instructions for CPU

- The instructions for CPU to run are binary.
 - 10110000 01100001
- Programming on punched tapes

machine language

0, 1 code





Assembly languages

MONITOR FOR 6802 1.4 9-14-80 TSC ASSEMBLER PAGE 2

```
C000          ORG    ROM+$0000 BEGIN MONITOR
C000 8E 00 70  START  LDS    #STACK

*****
* FUNCTION: INITA - Initialize ACIA
* INPUT: none
* OUTPUT: none
* CALLS: none
* DESTROYS: acc A

0013          RESETA EQU    %00010011
0011          CTLREG EQU    %00010001

C003 86 13          INITA  LDA A  #RESETA  RESET ACIA
C005 B7 80 04          STA A  ACIA
C008 86 11          LDA A  #CTLREG  SET 8 BITS AND 2 STOP
C00A B7 80 04          STA A  ACIA

C00D 7E C0 F1          JMP    SIGNON  GO TO START OF MONITOR

*****
* FUNCTION: INCH - Input character
* INPUT: none
* OUTPUT: char in acc A
* DESTROYS: acc A
* CALLS: none
* DESCRIPTION: Gets 1 character from terminal

C010 B6 80 04  INCH    LDA A  ACIA      GET STATUS
C013 47          ASR A      SHIFT RDRF FLAG INTO CARRY
C014 24 FA          BCC  INCH  RECIEVE NOT READY
C016 B6 80 05          LDA A  ACIA+1  GET CHAR
C019 84 7F          AND A  #$7F  MASK PARITY
C01B 7E C0 79          JMP    OUTCH  ECHO & RTS

*****
* FUNCTION: INHEX - INPUT HEX DIGIT
* INPUT: none
* OUTPUT: Digit in acc A
* CALLS: INCH
* DESTROYS: acc A
* Returns to monitor if not HEX input

C01E 8D F0          INHEX  BSR    INCH  GET A CHAR
C020 81 30          CMP A  #'0      ZERO
C022 2B 11          BMI  HEXERR  NOT HEX
C024 81 39          CMP A  #'9      NINE
C026 2F 0A          BLE  HEXRTS  GOOD HEX
C028 81 41          CMP A  #'A
C02A 2B 09          BMI  HEXERR  NOT HEX
C02C 81 46          CMP A  #'F
C02E 2E 05          BGT  HEXERR
C030 80 07          SUB A  #7      FIX A-F
C032 84 0F          HEXRTS  AND A  #$0F  CONVERT ASCII TO DIGIT
C034 39          RTS

C035 7E C0 AF  HEXERR  JMP    CTRL    RETURN TO CONTROL LOOP
```

Assembly languages are more human readable

• 10110000 01100001



• **MOV AL, 61h** ; *Load AL with 97 decimal (61 hex)*

https://en.wikipedia.org/wiki/Assembly_language



High Level Languages

- C: 1973

- Developed by Dennis Ritchie and Ken Thompson at Bell Labs between 1969 and 1973.

- C++: 1979

- Created by Bjarne Stroustrup as an extension of the C programming language
- C with Classes
- Renamed to C++
- Now it's C+++++

C++98, 03, 11, 14, 17, 20...



Higher Level Languages

- Java: 1995 自动垃圾回收

- I hate memory management in C/C++!
- I want "Write once, run anywhere", not "write once, compile anywhere".
- Grammar is similar with C++.
- A Java compiler generates *.class files, not executable files.



JVM 虚拟机

C/C++ 需重新
编译

字节码

- Python: 1990

- I hate strict grammar!
- I hate too many data types!



Cython




Even higher

- Scratch: 2002
 - I don't like to type a keyboard



可视化编程语言




without keyboard



But...

- The grammar is complex, and **pointer ..**

C
Language



Year	C Standard ^[9]
1972	Birth
1978	K&R C
1989/1990	ANSI C and ISO C
1999	C99
2011	C11
2017	C17
TBD	C2x

Year	C++ Standard	Informal name
1998	ISO/IEC 14882:1998 ^[29]	C++98
2003	ISO/IEC 14882:2003 ^[30]	C++03
2011	ISO/IEC 14882:2011 ^[31]	C++11, C++0x
2014	ISO/IEC 14882:2014 ^[32]	C++14, C++1y
2017	ISO/IEC 14882:2017 ^[33]	C++17, C++1z
2020	ISO/IEC 14882:2020 ^[12]	C++20, C++2a



Advantages of C/C++

- Development language of most fundamental computer systems
 - Linux
 - MySQL
 - OpenCV
 - Backend of TensorFlow, PyTorch
 - ...
- High efficiency
 - Widely optimized compilers
 - Access memory directly
 - Excellent on computing
 - Important language for AI algorithm implementation



Similar languages

- C, C++ and Java

```
#include <stdio.h>
int main()
{
    printf("Hello World!\n");
    return 0;
}
```

```
#include <iostream>
int main()
{
    std::cout << "Hello World!" << std::endl;
    return 0;
}
```

```
public class Hello{
    public static void main(Str){
        System.out.println("Hello World!");
    }
}
```



南方科技大学
SOUTHERN UNIVERSITY OF SCIENCE AND TECHNOLOGY

Compile and Link



```
#include <iostream>
```

```
using namespace std;
```

```
int mul(int a, int b)
```

```
{
```

```
    return a * b;
```

```
}
```

```
int main()
```

```
{
```

```
    int a, b;
```

```
    int result;
```

```
    cout << "Pick two integers:";
```

```
    cin >> a;
```

```
    cin >> b;
```

```
    result = mul(a, b);
```

```
    cout << "The result is " << result << endl;
```

```
    return 0;
```

```
}
```

Two functions

- main(): called by startup code
- mul() is called in main()



Function prototypes and definitions

- function prototypes normally are put into head files (*.h; *.hpp)

```
int mul(int a, int b);
```

声明放入头文件中

- function definitions normally are in source files (*.c; *.cpp)

```
int mul(int a, int b)
{
    return a * b;
}
```

函数实现放入源文件中



Separate the source code into multiple files

main.cpp

```
#include <iostream>
#include "mul.hpp"

using namespace std;
int main()
{
    int a, b;
    int result;

    cout << "Pick two integers:";
    cin >> a;
    cin >> b;

    result = mul(a, b);

    cout << "The result is " << result << endl;
    return 0;
}
```

mul.hpp

```
#pragma once


int mul(int a, int b);
```

mul.cpp

```
#include "mul.hpp"
int mul(int a, int b)
{
    return a * b;
}
```



Compile and link





Compilation errors

编译错误

- Normally caused by grammar error
- Please check the source code!

```
9
10 cout << "Pick two integers:";
11 cin >> a;
12 cin >> b;
13
14 result = mul(a, b)
15
16 cout << "The result is " << result << endl;
17 return 0;
18 }
```

PROBLEMS 1 OUTPUT DEBUG CONSOLE TERMINAL

yushiqi@MacBook-Air-2 ch01 % g++ main.cpp -c

main.cpp:14:23: error: expected ';' after expression

result = mul(a, b)

^
;

1 error generated.



Link errors

链接错误

- "Symbol not found"
- Function mul() is misspelled to Mul()

code > ch01 >  mul.cpp > ...

```
1  #include "mul.hpp"
2
3  int Mul(int a, int b)
4  {
5      return a * b;
6  }
7  |
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

 zsh

```
yushiqi@MacBook-Air-2 ch01 % g++ main.cpp -c
yushiqi@MacBook-Air-2 ch01 % g++ mul.cpp -c
yushiqi@MacBook-Air-2 ch01 % g++ main.o mul.o -o mul
Undefined symbols for architecture x86_64:
```

```
  "mul(int, int)", referenced from:
```

```
    main in main.o
```

```
ld: symbol(s) not found for architecture x86_64
```

```
clang: error: linker command failed with exit code 1 (use -v to see invocation)
```



Runtime errors

运行错误

code > ch01 >  mul.cpp >  mul(int, int)

```
1  #include "mul.hpp"
2
3  int mul(int a, int b)
4  {
5      int c = a / b;
6      return a * b;
7  }
8
```

- The source code can be successfully compiled and linked.
- The floating point exception (divided by 0) will kill the program.
- It is a typical runtime error.

PROBLEMS OUTPUT DEBUG CONSOLE TE

```
yushiqi@MacBook-Air-2 41 % ./mul
Pick two integers:2 0
zsh: floating point exception ./mul
```



南方科技大学
SOUTHERN UNIVERSITY OF SCIENCE AND TECHNOLOGY

Preprocessor and Macros



Preprocessor

- The preprocessor is executed before the compilation.
- Preprocessing directives begin with a # character 预处理指令 #
- Each directive occupies one line
- preprocessing instruction
(define, undef, include, if, ifdef, ifndef, else, elif, endif, line, error, pragma)

```
#include <iostream>
```

```
#define PI 3.1415926535
```

```
#if defined(_OPENMP)
```

```
#include <omp.h>
```

```
#endif
```



include directive 预处理先于编译

Preprocess

Compile

main.cpp

```
#include "mul.hpp"
int main()
{
    //
}
```

```
int mul(int a, int b);
int main()
{
    //
}
```

main.o

Binary object
file



Macros

Preprocess

Compile

circle.cpp

```
#define PI 3.14
double len(double r)
{
    return 2.0 * PI * r;
}
```

```
double len(double r)
{
    return 2.0 * 3.14 * r;
}
```

circle.o

Binary object
file

PI不是变量是宏



Simple Output and Input



C++ Style Output

- What is cout?

std::ostream

```
std::ostream cout;
```

- cout is an object of data type ostream in namespace std.

```
cout << "hello." << endl;
```

- << is an operator which is defined as follows

链式调用

```
std::basic_ostream<CharT,Traits>::operator<<
```

```
basic_ostream& operator<<( short value );  
basic_ostream& operator<<( unsigned short value );
```

```
basic_ostream& operator<<( int value );  
basic_ostream& operator<<( unsigned int value );
```

- endl, an output-only I/O manipulator. It will output a new line character and flushes.

'\n'



C++ Style Input

```
int a;  
float b;  
cin >> a;  
cin >> b;
```

- Similarly, cin is an object of type std::istream. *std::istream*
- >> is an operator



C Style Output

```
int v = 100;  
printf("Hello, value = %d\n", v);
```

- `int printf(const char *format, ...);` is a function
- `format`: a string specifying how to interpret the data
- `%d` will let the function interpret `v` as an integer



C Style Input

```
int v;
```

```
int ret = scanf("%d", &v);
```

— 取地址

- scanf reads data from stdin, and interpret the input as an integer and store it into v;



Why the examples have no GUI?

- The programs I used all have GUI. Why the examples have no GUI?
- GUI (graphical user interface) is not mandatory.
- GUI is for human beings to interact with computers.
- No all programs interact with human beings.
- We can also interact with the program in a command line window.
- We can call a GUI library to create a graphic window by many programming languages. Surely C/C++ can create a GUI window.



Command line arguments

- ```
int main()
{
 /* ... */
}
```

- ```
int main(int argc, char *argv[])  
{ ...  
}
```

- ```
int main(int argc, char **argv)
{ ...
}
```

- Do you still remember?

```
g++ hello.cpp -o hello
```

- g++ is an executable program/file
- There are three command line arguments



# Command line arguments

argument.cpp

```
#include <iostream>
```

```
using namespace std;
```

```
int main(int argc, char * argv[])
```

```
{
```

```
 for (int i = 0; i < argc; i++)
```

```
 cout << i << ": " << argv[i] << endl;
```

```
}
```

命令行参数

```
yushiqi: ch01 $./argument mul.cpp -o main
```

```
0: ./argument
```

```
1: mul.cpp
```

```
2: -o
```

```
3: main
```



# But

- I don't like to compile a program in a command window
- IDE: Integrated development environment
  - Microsoft Visual Studio
  - Apple Xcode
  - Eclipse
  - Clion
  - ...



- Visual Studio Code (VSCode) is an integrated development environment made by Microsoft for Windows, Linux and macOS