

# Multi-purpose Library of Recommender System Algorithms for the Item Prediction Task

Presentation of my Bachelor Thesis

Julius Kolbe

L3S Research Center / Leibniz University of Hanover  
Hannover, Germany

July 1, 2013

# Contents

Item Prediction Task and Implicit Feedback

Recsyslab

Recommendation Algorithms

Evaluation

Demonstration of recsyslab

Conclusions

# Contents

Item Prediction Task and Implicit Feedback

Recsyslab

Recommendation Algorithms

Evaluation

Demonstration of recsyslab

Conclusions

## Implicit Feedback

	Anna	Berta	Claudia	Dagmar
The Shawshank Redemption	1		1	
The Godfather		1	1	
The Godfather: Part II		1		1
Pulp Fiction	1	1		1
The Good, the Bad and the Ugly	1		1	

## Item Prediction Task

	Anna	Berta	Claudia	Dagmar
The Shawshank Redemption	1		1	?
The Godfather		1	1	?
The Godfather: Part II		1		1
Pulp Fiction	1	1		1
The Good, the Bad and the Ugly	1		1	?

## Notation

	Anna	Berta	Claudia	Dagmar
The Shawshank Redemption	1		1	
The Godfather		1	1	
The Godfather: Part II		1		1
Pulp Fiction	1	1		1
The Good, the Bad and the Ugly	1		1	

Items

Users

Interactions

Basket of  $u$

# Contents

Item Prediction Task and Implicit Feedback

Recsyslab

Recommendation Algorithms

Evaluation

Demonstration of recsyslab


Conclusions

## Motivation for recsyslab

- ▶ Python for easy readable source code
- ▶ Simple usage
- ▶ For education
- ▶ For research
- ▶ Open source license: GPLv3



# General Structure



## Get recsyslab

`github.com/Foolius/recsyslab`

`github.com/Foolius/recsyslab/archive/master.zip`

```
$ git clone  
  https://github.com/Foolius/recsyslab.git
```

# Contents

Item Prediction Task and Implicit Feedback

Recsyslab

Recommendation Algorithms

Evaluation

Demonstration of recsyslab

Conclusions

# Recommender Algorithms in recsyslab

- ▶ Non-Personalized
  - ▶ Constant
  - ▶ Random
- ▶ k-Nearest-Neighbor
  - ▶ Item-Based
  - ▶ User-Based
- ▶ Matrix Factorization
  - ▶ Bayesian Personalized Ranking (BRPMF)
  - ▶ RankMFX
  - ▶ Ranking SVD
- ▶ Other
  - ▶ Slope One

## Matrix Factorization [mat13]

	Anna	Berta	Claudia	Dagmar
The Shawshank Redemption	1	0	1	0
The Godfather	0	1	1	0
The Godfather: Part II	0	1	0	1
Pulp Fiction	1	1	0	1
The Good, the Bad and the Ugly	1	0	1	0

Find  $W$  and  $H$  so:  $\hat{M} = W H^T$ .

$$\text{Score}(u, i) = W_u I_i^T. \quad (1)$$

## Matrix Factorization, Training

```
U = randomly chosen user
I = randomly chosen item U interacted with
J = randomly chosen item U did not interact with

X=H[i] - H[j]
wx = dot product of W[u] and X
dloss = (derivative of the
         loss function of wx and 1) *
         learningRate

W[u] += dloss * (H[i] - H[j]) #These three lines
H[i] += dloss * W[u]          #have to be
H[j] += dloss * -W[u]         #executed at once
```

```

u = random.choice(R.keys())

userItems = [x[0] for x in R[u]]
# the positive example
i = userItems[np.random.random_integers(0, len(userItems) - 1)]
# the negative example
j = np.random.random_integers(0, m_items)
# if j is also relevant for u we continue
# we need to see a negative example to contrast the positive one
while j in userItems:
    j = np.random.random_integers(0, m_items)

X = H[i] - H[j]
wx = np.dot(W[u], X)
dloss = dlossF(wx, y)

# temp
wu = W[u]
hi = H[i]
hj = H[j]
if dloss != 0.0:
    # Updates
    eta_dloss = learningRate * dloss
    W[u] += eta_dloss * (hi - hj)
    H[i] += eta_dloss * wu
    H[j] += eta_dloss * (-wu)
    W[u] *= scaling_factorU
    H[i] *= scaling_factorI
    H[j] *= scaling_factorJ

```

## k-Nearest-Neighbor [Kar01]

1. Compute similarity of each item, item pair
2. For each item, save the  $k$  items with the highest similarity (= neighbors)
3. Compute the union of the neighbors of the basket of  $u$
4. For each item in this set compute the sum of similarities to the basket of  $u$
5. Sort by this score and return the first  $N$  items

$$\text{sim}(i, j) = \cos(\vec{i}, \vec{j}) = \frac{\vec{i} \cdot \vec{j}}{\|\vec{i}\|_2 \|\vec{j}\|_2} \quad (2)$$



## k-Nearest-Neighbor [Kar01]

	Anna	Berta	Claudia	Dagmar
The Shawshank Redemption	1	0	1	0
The Godfather	0	1	1	0
The Godfather: Part II	0	1	0	1
Pulp Fiction	1	1	0	1
The Good, the Bad and the Ugly	1	0	1	0

$$\text{sim}(i, j) = \cos(\vec{i}, \vec{j}) = \frac{\vec{i} \cdot \vec{j}}{\|\vec{i}\|_2 \|\vec{j}\|_2} = \frac{0}{2} = 0$$

## k-Nearest-Neighbor [Kar01]

	Anna	Berta	Claudia	Dagmar
The Shawshank Redemption	1	0	1	0
The Godfather	0	1	1	0
The Godfather: Part II	0	1	0	1
Pulp Fiction	1	1	0	1
The Good, the Bad and the Ugly	1	0	1	0

$$\text{sim}(i, j) = \cos(\vec{i}, \vec{j}) = \frac{\vec{i} \cdot \vec{j}}{\|\vec{i}\|_2 \|\vec{j}\|_2} = \frac{2}{\sqrt{2}\sqrt{3}}$$

# Contents

Item Prediction Task and Implicit Feedback

Recsyslab

Recommendation Algorithms

Evaluation

Demonstration of recsyslab

Conclusions

## Leave-one-out Protocol

1. Randomly choose one interaction per user and hide them
2. Train the recommender system with the remaining interactions
3. Get recommendations for every user
4. Compute the chosen evaluation metric with the hidden items and the recommendations

## Evaluation Metrics in recsyslab

- ▶ Hitrate/Recall@N
- ▶ Precision
- ▶ F1
- ▶ Mean Reciprocal Hitratea (MRHR)
- ▶ Area under the ROC (AUC)

## Hitrate/Recall@N [Kar01, SKKR00]

$$\text{Recall@N} = \frac{\sum_{u \in U} |H_u \cap \text{topN}_u|}{|H|} \quad (3)$$

$H$  hidden interactions

$H_u$  the hidden interaction of  $u$

$U$  set of users

$\text{topN}_u$   $N$  recommendations for  $u$

# Contents

Item Prediction Task and Implicit Feedback

Recsyslab

Recommendation Algorithms

Evaluation

Demonstration of recsyslab

Conclusions

# Contents

Item Prediction Task and Implicit Feedback

Recsyslab

Recommendation Algorithms

Evaluation

Demonstration of recsyslab

Conclusions



## Conclusions

- ▶ Python for easy readable source code
- ▶ Simple usage
- ▶ For education
- ▶ For research
- ▶ Open source license: GPLv3

## Conclusions

- ▶ Python for easy readable source code ✓
- ▶ Simple usage
- ▶ For education
- ▶ For research
- ▶ Open source license: GPLv3

## Conclusions

- ▶ Python for easy readable source code ✓
- ▶ Simple usage ✓
- ▶ For education
- ▶ For research
- ▶ Open source license: GPLv3

## Conclusions

- ▶ Python for easy readable source code ✓
- ▶ Simple usage ✓
- ▶ For education ✓
- ▶ For research
- ▶ Open source license: GPLv3

## Conclusions

- ▶ Python for easy readable source code ✓
- ▶ Simple usage ✓
- ▶ For education ✓
- ▶ For research ✓
- ▶ Open source license: GPLv3

## Conclusions

- ▶ Python for easy readable source code ✓
- ▶ Simple usage ✓
- ▶ For education ✓
- ▶ For research ✓
- ▶ Open source license: GPLv3 ✓



George Karypis.

Evaluation of item-based top-n recommendation algorithms.

In *Proceedings of the tenth international conference on Information and knowledge management*, CIKM '01, pages 247–254, New York, NY, USA, 2001. ACM.

URL: <http://doi.acm.org/10.1145/502585.502627>,  
doi:10.1145/502585.502627.



Matrix factorization, June 2013.

URL:

[http://en.wikipedia.org/wiki/Matrix\\_factorization](http://en.wikipedia.org/wiki/Matrix_factorization).



Badrul M. Sarwar, George Karypis, Joseph A. Konstan, and John T. Riedl.

Application of dimensionality reduction in recommender system – a case study.

In *IN ACM WEBKDD WORKSHOP*, 2000.

