

Tavily MCP Server

[العربية](#) · [Full guide \(EN\)](#) · [الدليل الشامل \(AR\)](#)

An MCP server (stdio, TypeScript) that gives the assistant live web access through [Tavily](#): `search`, `extract`, `map` and `crawl`.

Tools

- `tavily_search`: web search with optional answer, news/finance topics, date and domain filters
- `tavily_extract`: clean content from up to 20 URLs, with query-based chunk filtering
- `tavily_map`: discover a site's URL structure (no content)
- `tavily_crawl`: crawl a site and return page content

A simpler single-tool Python alternative (`server.py` , tool `web_search`) is also included.

Setup

```
npm install && npm run build
cp .env.example .env      # then put your real key in .env (never commit it)
```

Get a key at <https://app.tavily.com>.

CLI client

```
<client-cli> mcp add tavily -e TAVILY_API_KEY=tvly-xxxx -- node
/absolute/path/to/tavily-mcp-server/dist/index.js
```

Desktop client

Edit `<client config file>` (see [mcp_client_config.example.json](#)), then quit with `Cmd+Q` and reopen.

The TypeScript server does **not** read `.env` ; pass the key through the client's `env` setting as above.

Test

```
TAVILY_API_KEY=tvly-xxxx npx @modelcontextprotocol/inspector node dist/index.js
```

Python alternative

```
uv venv --python 3.12 .venv  
uv pip install --python .venv/bin/python -r requirements.txt  
.venv/bin/mcp dev server.py
```

Security

Never commit `.env`, a real `mcp_client_config.json`, or `*.bak` files. See the checklist in the [guide](#).