

Daniel Walter
fordprfkt@googlemail.com

Sheet: /
File: HPDriver.sch

Title: High Power Stepper Driver

Size: A4	Date: 2019-12-19	**Rev: 1.0**
KiCad E.D.A. kicad (5.1.10)-1		Id: 1/5

Typical Application, Basic Step-Down Regulator



Type 1 Output Ripple Configuration shown

Type 2 Reduced Ripple Configuration



Step 9. Summary				
R_{FB2} =	2.49	kohms	These two resistors set
R_{FB1} =	2.49	kohms	the output voltage.
R_T =	300	kohms	Sets the switching frequency.
L1 =	1000	uH	Determines the ripple current.
R_{ON} =	750	kohms	Sets the off-time in current limit.
Output Ripple Configuration =	Type 2		Affects the amount of ripple at V_{OUT}.
R3 =	1.5	Ohms	Sets the ripple amplitude at Vout.
Cff =	10000	pF	Ripple bypass for Type 2
C_{OUT} =	5	uF	
C_{IN} =	3.3	uF	
C_{BYP} =	0.1	uF	See Note 1.
C_{VCC} =	0.47	uF	
C_{BST} =	0.01	uF	
V_{OUT} =	5.00	Volts	
Nominal Switching Frequency =	133	kHz	

Notes: 1) Values shown for C_{BYP}, C_{VCC}, and C_{BST} are default values, and do not require calculation.



Daniel Walter
fordprfkt@googlemail.com

Sheet: /Supply/
File: Supply.sch

Title: High Power Stepper Driver

Size: A4	Date: 2019-12-19	**Rev: 1.0**
KiCad E.D.A. kicad (5.1.10)-1		Id: 2/5



Daniel Walter
fordprfkt@googlemail.com

Sheet: /Driver/
File: Driver.sch

Title: High Power Stepper Driver

Size: A4	Date: 2019-12-19	**Rev: 1.0**
KiCad E.D.A. kicad (5.1.10)-1		Id: 3/5



Daniel Walter
fordprfkt@googlemail.com

Sheet: /Connector/
File: Connector.sch

Title: High Power Stepper Driver

Size: A4	Date: 2019-12-19	**Rev: 1.0**
KiCad E.D.A. kicad (5.1.10)-1		Id: 4/5



Daniel Walter
fordprfkt@googlemail.com

Sheet: /Controller/
File: Controller.sch

Title: High Power Stepper Driver

Size: A4	Date: 2019-12-19	**Rev: 1.0**
KiCad E.D.A. kicad (5.1.10)-1		Id: 5/5