AFRICAST

TIDY TIME SERIES & FORECASTING IN R

Time series patterns and basic graphics

Session 2 of 10



Outline

- Time series patterns
- Time plots
- Seasonal plots
- Seasonal or cyclic?
- Lag plots and autocorrelation
- White noise

SECTION 1 OF 6

Time series Patterns

1 **Time series Patterns** 2 Time plots 3 Seasonal plots 4 Seasonal or cyclic? 5 Lag plots and autocorrelation
6 White noise



Key patterns of time series

- Level
- Underlying trend
- Seasonal/cycle
- Autocorrelation
- Unpredictable patterns/Noise
- Different types of events and driving factors (i.e. predictors) may affect the time series

Time series patterns

Level

The *level* of a time series describes the centre of the series.

Trend

A *trend* describes predictable increases or decreases in the level of a series.


Seasonal


Seasonality is a consistent pattern that repeats over a fixed period of time. pattern exists when a series is influenced by seasonal factors (e.g., the quarter of the year, the month, or day of the week).

Cyclic


pattern exists when data exhibit rises and falls that are *not of fixed period* (duration usually of at least 2 years).


Level


140
120
100
80
60
Demand
Level
2016
2018
2020
2022
Quarter



120
110
100
90
80
2016
2018
2020
2022
Quarter

Trend



Demand
130
120
110
100
2016
2018
2020
2022
Quarter



100
90
80
70
Demand
Trend
2016
2018
2020
2022
Quarter

Seasonality




Additive versus multiplicative seasonality





Cycles


Cement Production
1.5
2.0
2.5
1980
1985
1990
1995
2000
2005
2010
2015
Time

SECTION 2 OF 6


Time plots

1 Time series Patterns
2 **Time plots**
3 Seasonal plots
4 Seasonal or cyclic?
5 Lag plots and autocorrelation
6 White noise




Time plots

```
ansett |>
  filter(Airports=="MEL-SYD", Class=="Economy") |>
  autoplot(Passengers)
```




Time plots

```
PBS |> filter(ATC2 == "A10") |>
  summarise(Cost = sum(Cost)/1e6) |> autoplot(Cost) +
  labs(x = "Year", y = "$ million", title = "Antidiabetic drug sales")
```



Horizon plots



SECTION 3 OF 6

Seasonal plots


1 Time series Patterns
2 Time plots
3 **Seasonal plots**
4 Seasonal or cyclic?
5 Lag plots and autocorrelation
6 White noise



Seasonal plots


- Data plotted against the individual “seasons” in which the data were observed. (In this case a “season” is a month.)
- Something like a time plot except that the data from each season are overlapped.
- Enables the underlying seasonal pattern to be seen more clearly, and also allows any substantial departures from the seasonal pattern to be easily identified.
- In R: `gg_season()` (ggtime)

Building a seasonal plot



Quarterly Australian Beer Production

```
beer |> gg_season(Beer, labels = "right")
```




Multiple seasonal periods

```
vic_elec
```

```
# A tsibble: 52,608 x 5 [30m] <Australia/Melbourne>
   Time                Demand Temperature Date       Holiday
   <dttm>               <dbl>       <dbl> <date>     <lgl>
 1 2012-01-01 00:00:00  4383.        21.4 2012-01-01 TRUE
 2 2012-01-01 00:30:00  4263.        21.0 2012-01-01 TRUE
 3 2012-01-01 01:00:00  4049.        20.7 2012-01-01 TRUE
 4 2012-01-01 01:30:00  3878.        20.6 2012-01-01 TRUE
 5 2012-01-01 02:00:00  4036.        20.4 2012-01-01 TRUE
 6 2012-01-01 02:30:00  3866.        20.2 2012-01-01 TRUE
 7 2012-01-01 03:00:00  3694.        20.1 2012-01-01 TRUE
 8 2012-01-01 03:30:00  3562.        19.6 2012-01-01 TRUE
 9 2012-01-01 04:00:00  3433.        19.1 2012-01-01 TRUE
10 2012-01-01 04:30:00  3359.        19.0 2012-01-01 TRUE
# i 52,598 more rows
```


Multiple seasonal periods

```
vic_elec |> gg_season(Demand)
```




Multiple seasonal periods

```
vic_elec |> gg_season(Demand, period = "week")
```



Multiple seasonal periods


```
vic_elec |> gg_season(Demand, period = "day")
```



Seasonal subseries plots

- Data for each season collected together in time plot as separate time series.
- Enables the underlying seasonal pattern to be seen clearly, and changes in seasonality over time to be visualised.
- In R: `gg_subseries()` (ggtime)

Building a seasonal subseries plot




Australian holidays

```
holidays <- tourism |>
  filter(Purpose == "Holiday") |>
  group_by(State) |>
  summarise(Trips = sum(Trips))
```

```
# A tsibble: 640 x 3 [1Q]
# Key:       State [8]
   State Quarter Trips
   <chr>   <qtr> <dbl>
 1 ACT   1998 Q1  196.
 2 ACT   1998 Q2  127.
 3 ACT   1998 Q3  111.
 4 ACT   1998 Q4  170.
 5 ACT   1999 Q1  108.
 6 ACT   1999 Q2  125.
 7 ACT   1999 Q3  178.
 8 ACT   1999 Q4  218.
 9 ACT   2000 Q1  158.
10 ACT   2000 Q2  155.
# i 630 more rows
```


Australian holidays

```
holidays |> autoplot(Trips) +
  labs(y = "thousands of trips", title = "Australian domestic holiday trips")
```




Seasonal plots

```
holidays |> gg_season(Trips) +
  labs(y = "thousands of trips", title = "Australian domestic holiday trips")
```



Seasonal subseries plots

```
holidays |> gg_subseries(Trips) +
  labs(y = "thousands of trips", title = "Australian domestic holiday trips")
```




Calendar plots

```
library(ggtime)
vic_elec |>
  filter(year(Date) == 2014) |>
  as_tibble() |>
  ggplot(aes(x = Time, y = Demand)) +
  geom_line() +
  coord_calendar(rows = month(1L), cols = NULL) +
  scale_x_mixtime(
    time_breaks = mixtime::days(1L),
    time_labels = "{cyc(day, cal_isoweek$week, label = TRUE, abbreviate = TRUE)}"
  ) +
  theme(axis.text.y = element_blank(), axis.ticks.y = element_blank())
```

- `coord_calendar()` cuts a time axis into a calendar-like grid of rows/columns
- each row above is a month, and each cell within it a day

Calendar plots



SECTION 4 OF 6

Seasonal or cyclic?

1 Time series Patterns
2 Time plots
3 Seasonal plots
4 **Seasonal or cyclic?**
5 Lag plots and autocorrelation
6 White noise



Time series patterns

Trend

pattern exists when there is a long-term increase or decrease in the data.

Seasonal

pattern exists when a series is influenced by seasonal factors (e.g., the quarter of the year, the month, or day of the week).

Cyclic


pattern exists when data exhibit rises and falls that are *not of fixed period* (duration usually of at least 2 years).

Time series components

Differences between seasonal and cyclic patterns:

- seasonal pattern constant length; cyclic pattern variable length
- average length of cycle longer than length of seasonal pattern
- magnitude of cycle more variable than magnitude of seasonal pattern

Time series patterns




Seasonal	**0**	0%
Cyclic	**0**	0%
Both	**0**	0%
Neither	**0**	0%

poll.nectric.com.au/s/africast-graphics

0 responses

● CLOSED 0 connected

Time series patterns




Seasonal	**0**	0%
Cyclic	**0**	0%
Both	**0**	0%
Neither	**0**	0%

poll.nectric.com.au/s/africast-graphics

0 responses

● **CLOSED** 0 connected

Time series patterns



Seasonal **0** 0%

Cyclic **0** 0%

Both **0** 0%


Neither **0** 0%

poll.nectric.com.au/s/africast-graphics

0 responses

● **CLOSED** 0 connected

Time series patterns



Seasonal **0** 0%

Cyclic **0** 0%

Both **0** 0%

Neither **0** 0%

poll.nectric.com.au/s/africast-graphics

0 responses

● **CLOSED** 0 connected

Time series patterns



Seasonal	**0**	0%
Cyclic	**0**	0%
Both	**0**	0%
Neither	**0**	0%

poll.nectric.com.au/s/
africast-graphics

0 responses

● CLOSED 0 connected

Seasonal or cyclic?

Differences between seasonal and cyclic patterns:

- seasonal pattern constant length; cyclic pattern variable length
- average length of cycle longer than length of seasonal pattern
- magnitude of cycle more variable than magnitude of seasonal pattern

The timing of peaks and troughs is predictable with seasonal data, but unpredictable in the long term with cyclic data.

SECTION 5 OF 6

Lag plots and autocorrelation

1 Time series Patterns 2 Time plots 3 Seasonal plots 4 Seasonal or cyclic? **5 Lag plots and autocorrelation**

6 White noise




Example: Beer production

```
new_production <- aus_production |>
  filter(year(Quarter) >= 1992)
new_production
```

```
# A tsibble: 74 x 7 [1Q]
   Quarter  Beer Tobacco Bricks Cement Electricity   Gas
     <qtr> <dbl>   <dbl>  <dbl>  <dbl>       <dbl> <dbl>
 1 1992 Q1   443    5777    383   1289       38332   117
 2 1992 Q2   410    5853    404   1501       39774   151
 3 1992 Q3   420    6416    446   1539       42246   175
 4 1992 Q4   532    5825    420   1568       38498   129
 5 1993 Q1   433    5724    394   1450       39460   116
 6 1993 Q2   421    6036    462   1668       41356   149
 7 1993 Q3   410    6570    475   1648       42949   163
 8 1993 Q4   512    5675    443   1863       40974   138
 9 1994 Q1   449    5311    421   1468       40162   127
10 1994 Q2   381    5717    475   1755       41199   159
# i 64 more rows
```


Example: Beer production

```
new_production |> gg_lag(Beer)
```



Example: Beer production


```
new_production |> gg_lag(Beer, geom = "point")
```



Lagged scatterplots

- Each graph shows y_t plotted against y_{t-k} for different values of k.
- The autocorrelations are the correlations associated with these scatterplots.
- ACF (autocorrelation function):
  - $r_1 = \text{Correlation}(y_t, y_{t-1})$
  - $r_2 = \text{Correlation}(y_t, y_{t-2})$
  - $r_3 = \text{Correlation}(y_t, y_{t-3})$
  - etc.
- If there is **seasonality**, the ACF at the seasonal lag (e.g., 12 for monthly data) will be **large and positive**.

From lag plots to the ACF



Autocorrelation

Results for first 9 lags for beer data:


```
new_production |> ACF(Beer, lag_max = 9)
```

```
# A tsibble: 9 x 2 [1Q]
       lag     acf
  <cf_lag>   <dbl>
1       1Q -0.102
2       2Q -0.657
3       3Q -0.0603
4       4Q  0.869
5       5Q -0.0892
6       6Q -0.635
7       7Q -0.0542
8       8Q  0.832
9       9Q -0.108
```

Autocorrelation


Results for first 9 lags for beer data:

```
new_production |>
  ACF(Beer, lag_max = 9) |>
  autoplot()
```



ACF

```
new_production |>
  ACF(Beer) |>
  autoplot()
```




Australian holidays

```
holidays |> ACF(Trips)
```

```
# A tsibble: 152 x 3 [1Q]
# Key:       State [8]
   State      lag      acf
   <chr> <cf_lag>    <dbl>
 1 ACT         1Q  0.0877
 2 ACT         2Q  0.252
 3 ACT         3Q -0.0496
 4 ACT         4Q  0.300
 5 ACT         5Q -0.0741
 6 ACT         6Q  0.269
 7 ACT         7Q -0.00504
 8 ACT         8Q  0.236
 9 ACT         9Q -0.0953
10 ACT        10Q  0.0750
# i 142 more rows
```

Australian holidays

```
holidays |> ACF(Trips) |> autoplot()
```




Trend and seasonality in ACF plots

- When data have a trend, the autocorrelations for small lags tend to be large and positive.
- When data are seasonal, the autocorrelations will be larger at the seasonal lags (i.e., at multiples of the seasonal frequency)
- When data are trended and seasonal, you see a combination of these effects.


US retail trade employment

```
retail <- us_employment |>
  filter(Title == "Retail Trade", year(Month) >= 1980)
retail |> autoplot(Employed)
```



US retail trade employment

```
retail |>
  ACF(Employed, lag_max = 48) |>
  autoplot()
```



Google stock price

```
google_2015 <- gafa_stock |>
  filter(Symbol == "GOOG", year(Date) == 2015) |>
  select(Date, Close)
google_2015
```

```
# A tsibble: 252 x 2 [!]
   Date       Close
   <date>     <dbl>
 1 2015-01-02  522.
 2 2015-01-05  511.
 3 2015-01-06  499.
 4 2015-01-07  498.
 5 2015-01-08  500.
 6 2015-01-09  493.
 7 2015-01-12  490.
 8 2015-01-13  493.
 9 2015-01-14  498.
10 2015-01-15  499.
# i 242 more rows
```


Google stock price

```
google_2015 |> autoplot(Close)
```




Google stock price

```
google_2015 |>
  ACF(Close, lag_max = 100) |>
  autoplot()
```



Which is which?



1A, 2B, 3C, 4D	0	0%
1B, 2A, 3D, 4C	0	0%
1B, 2D, 3A, 4C	0	0%
1C, 2A, 3D, 4B	0	0%

poll.nectric.com.au/s/africast-graphics

0 responses

● **CLOSED** 0 connected

SECTION 6 OF 6

White noise

1 Time series Patterns
2 Time plots
3 Seasonal plots
4 Seasonal or cyclic?
5 Lag plots and autocorrelation
6 **White noise**



Example: White noise

```
set.seed(4)
wn <- tsibble(t = seq(36), y = rnorm(36), index = t)
wn |> autoplot(y)
```




White noise data is uncorrelated across time with zero mean and constant variance.

(Technically, we require independence as well.)

Example: White noise

```
wn |> ACF(y)
```

r_1	r_2	r_3	r_4	r_5	r_6	r_7	r_8	r_9	r_{10}
0.001	-0.216	-0.144	0.033	0.126	-0.039	0.100	-0.051	-0.198	-0.198



- Sample autocorrelations for white noise series.
- Expect each autocorrelation to be close to zero.
- Blue lines show 95% critical values.

Example: Pigs slaughtered

```
pigs <- aus_livestock |>
  filter(State == "Victoria", Animal == "Pigs", year(Month) >= 2014)
pigs |> autoplot(Count / 1e3) +
  labs(x = "Year", y = "Thousands",
       title = "Number of pigs slaughtered in Victoria")
```



Example: Pigs slaughtered



Yes **0** 0%

No **0** 0%

poll.nectric.com.au/s/africast-graphics

0 responses

CLOSED 0 connected

Example: Pigs slaughtered

Monthly total number of pigs slaughtered in the state of Victoria, Australia, from January 2014 through December 2018 (Source: Australian Bureau of Statistics.)

- Difficult to detect pattern in time plot.
- ACF shows significant autocorrelation for lag 2 and 12.
- Indicate some slight seasonality.

These show the series is **not a white noise series**.