

Official list of papiNet® codes maintained by agency SDC

This document is maintained up to papiNet version 2.40 build 20211013 and considering Biometria reference documents as stated in the table below.

Biometria reference document	Version	Document date
VIOL koder	9.8	2021-12-06
FU Handbok Följdrutinutgångar	2.1	2014-12-05
Prislisteadministration Textkoder	3.3	2016-12-06
Tillägg och avdrag i transportsystemet	1.14	2016-03-07

Copyright © 2014-2022 Biometria ekonomisk förening, Sweden. All rights reserved.

Changes since previous document version

A change to the version history requires an update of date and version in the page header.

The numbering format is Revision.Version, where Revision is an official document release and Version exceeding 0 is an internal work document. Please note that only if the document version has suffix 0 it is an official **Biometria** version, e.g 1.0, 2.0, 3.0, but NEITHER 0.1, 1.2 nor 1.10. The version suffix is initialized for each new revision level.

Version	Date	Change	Sign
55.0	22-02-09	On cover page updated considered Biometria Reference Document “VIOL koder” to version 9.8 and updated latest copyright year to 2022. In section 1 Legal Notice updated latest copyright year to 2022. In table 4.1 AdditionalItemInfo added Code OriginalLogisticsSupplierFrom. Further added CodeValue SKM1 to Code DeliveryTerm and CodeValue 0 to Code LoadTransferRequirementType. In section 4.8 “DocumentReferenceID” added initial text on purpose with the section. In the tables of section 4.8 changed second column into “Format in DocumentReferenceID string” to communicate usage within possible S255. Further in subsection 4.8.2 “DocumentReferenceID in VIOL 3” stated that the table refers to what may be included in documents issued by the VIOL 3 system and amended table with DocumentReferenceIDTypes BusinessChainNumber, CompensationCalculationID, CompensationChainNumber, ContractNumber, DeliverySourceNumber, GoodsArrivalNumber, MeasuringInstructionNumber, MeasuringNumber, ProductOriginIdentifier, ProductReferenceNumber, QuantityCalculationID and TransportArrivalNumber. In section 4.10 DownGradingReasonCode added DownGradingReasonCode 15 for use with VIOL 3 only. In table 4.22.3 RoadClassificationCode for Code VehicleCombinationConstraint added CodeValues BK1 (64 Ton), BK2 (51,4 Ton), BK3 (37 Ton), BK4 (74 Ton) and Standard (64 Ton), further deprecated its CodeValues 1, 2, 3, 4 and Standard. In section 4.26 SupplyPointPropertyCode updated the table header and deprecated SupplyPointPropertyCode AggravatedLoadingCondition including its SupplyPointPropertyCodeValues.	JeNo

Table of Contents

Changes since previous document version.....	2
1 Legal Notice	6
2 Usage	6
3 Table of elements with a code list maintained by agency SDC	7
4 Code tables	9
4.1 AdditionalItemInfo	9
4.1.1 VIOL 2	30
4.1.2 VIOL 3	32
4.2 BusinessPartyProperty	33
4.3 ClassificationCode	33
4.3.1 VIOL 2	33
4.3.2 VIOL 3	33
4.4 CostComponentCode	34
4.4.1 VIOL 2	38
4.4.2 VIOL 3	38
4.5 CreditDebitNoteReasonCode	39
4.6 DeliverySourceProperty	40
4.7 DiameterClassCode	42
4.7.1 VIOL 3	42
4.8 DocumentReferenceID	42
4.8.1 VIOL 2	42
4.8.2 VIOL 3	42
4.9 DocumentRejectionReason	43
4.10 DownGradingReasonCode	44
4.11 ErrorCode	45
4.12 LocationProperty	46
4.12.1 VIOL 2	46
4.12.2 VIOL 3	47
4.13 MeasuringCodeInfo with Agency=SDC	47
4.13.1 VIOL 2	51
4.13.2 VIOL 3	52
4.14 MeasuringEquipmentCode	53
4.15 Attribute MeasuringMethod, valid with MeasuringAgency=SDC.....	54
4.15.1 VIOL 2	55
4.15.2 VIOL 3	56



4.16	MeasuringUnitIdentifier	56
4.17	MonetaryAdjustmentComponent	57
4.18	PartyIdentifier	59
4.18.1	VIOL 2	59
4.18.2	VIOL 3	60
4.19	ProductIdentifier	61
4.19.1	VIOL 2	61
4.19.2	VIOL 3	61
4.20	PropertyType	62
4.20.1	VIOL 2	62
4.20.2	VIOL 3	62
4.21	ResourceTypeCode	64
4.22	RoadClassificationCode	64
4.22.1	VIOL 2	64
4.22.2	VIOL 3	64
4.23	RoadMaintenanceCodeInfo	65
4.23.1	VIOL 2	65
4.24	ShipmentIncidentCode	66
4.25	SupplyPointCode is assigned by Agency=SDC	66
4.25.1	VIOL 2	67
4.25.2	VIOL 3	67
4.26	SupplyPointPropertyCode	67
4.26.1	VIOL 2	69
4.26.2	VIOL 3	69
4.27	TransportInstructionCode	69
4.28	TransportModeCode	69
4.28.1	VIOL 2	70
4.29	TransportUnitCode	70
4.30	TransportUnitIdentifier	70
4.31	TransportUnloadingCode	70
4.31.1	VIOL 3	70
4.32	TransportVehicleCode	71
4.32.1	VIOL 2	71
4.33	TransportVehicleEquipmentCode	71
4.33.1	VIOL 2	71
4.33.2	VIOL 3	71
4.34	TransportVehicleIdentifier	73
4.34.1	VIOL 2	73
4.35	TreeSpeciesGroupCode	73

4.35.1	VIOL 2	74
4.36	VersionReason	74
4.36.1	VIOL 2	74
5	Mapping of papiNet enumeration values to Viol codes	75
6	Practical guidelines on some elements	76
6.1	MeasuringType attribute of element MeasuringSpecification	76
6.1.1	VIOL 2	76
6.2	Attributes of InformationalQuantity and Quantity	77
6.2.1	Attributes in documents with VIOL 2 data issued by Biometria	77
6.2.2	Attributes in documents with VIOL 3 data issued by Biometria	80
7	Complete document version history	91

1 Legal Notice

Copyright © 2014-2022 Biometria ekonomisk förening, Sweden. All rights reserved.

papiNet® is a registered trademark of IDEAlliance on behalf of a global partnership between AF&PA, IDEAlliance and papiNet GIE.

2 Usage

In the papiNet standard, there are many elements with attribute Agency, which describes the agency maintaining the list of codes of a particular element. Whenever the Agency attribute value is SDC, the code lists of this document should be used to set and interpret the element codes properly. Please notice that the attribute value is SDC, although Biometria is the organisation maintaining the codes.

Only the elements of this document may have SDC as attribute value of Agency and MeasuringAgency. For each element the codes are listed below with a short description.

The elements are described in the papiNet Data Dictionary, which is publicly available for download at official papiNet web site <http://www.papiNet.org>. There the definition of Agency attribute value SDC reads:

SDC

Agency maintaining codes for the Swedish wood supply segment (www.biometria.se).

3 Table of elements with a code list maintained by agency SDC

Below the elements supported by agency SDC are listed. If the SDC identifiers are dynamically changed over time, there is a 'Yes' in table column Dynamic list. An example is organizational codes such as PartyIdentifier.

Element	Dynamic list of SDC identifiers
AdditionalItemInfo	Some codes have predefined list of values and others have a dynamic list of values.
BusinessPartyProperty	Yes
ClassificationCode	
CostComponentCode	Yes for VIOL 3, but not dynamic in VIOL 2
CreditDebitNoteReasonCode	
DeliverySourceProperty	
DiameterClassCode	
DocumentReferenceld	Yes
DocumentRejectionReason	No
DownGradingReasonCode	
ErrorCode	Yes
ForestWoodClassCode – not described yet	Corresponds to VIOL 2 values K for QualityClass and O for ReasonClass
LocationProperty	
MeasuringCodeInfo	
MeasuringEquipmentCode	
MeasuringMethod	
MeasuringUnitIdentifier	Yes
MonetaryAdjustmentComponent	Yes
PartyIdentifier	Yes
ProductIdentifier	Yes, in particular for VIOL 3
PropertyType	
ResourceTypeCode	
RoadClassificationCode	
RoadMaintenanceCodeInfo	
ShipmentIncidentCode	
SupplyPointCode	Yes
SupplyPointPropertyCode	
TransportInstructionCode	
TransportModeCode	
TransportUnitCode	
TransportUnitIdentifier	Yes
TransportUnloadingCode	
TransportVehicleCode	
TransportVehicleEquipmentCode	
TransportVehicleIdentifier	Yes

Element	Dynamic list of SDC identifiers
TreeSpeciesGroupCode	
VersionReason	

Following elements are not yet supported by agency SDC.

Element	Comment
CommodityGoodsCode	Low priority
DeductionReason	
DeviationReasonCode	DeliveryPlanning
InventoryClassCode	
MeasuringTicketReasonCode	
PackagingCode	Virkesskyddsklass t ex presenning etc
ProcessingCode	
PropertyCode	Yes
ResourceIdentifier	Dynamic for ResourceTypeCode = LASTARE
ResourceShiftCode	DeliveryPlanning
TransportLoadingCode	
TransportUnitEquipmentCode	

4 Code tables

The code tables for elements supported by agency SDC are provided below with the valid values. Please notice that the value <N/A> implies that a value is not applicable and should not be entered here.

At Biometria there are two core systems VIOL 2 and VIOL 3. VIOL 3 is being developed. In many code tables there are columns VIOL 2 and VIOL 3, where the symbol √ indicates that the Code or CodeValue is used in the integration with respective system.

4.1 AdditionalItemInfo

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “sNow” and “SNOW” are the same.

The CodeValue is alphanumeric and must use element TextValue and NOT NumericValue, unless otherwise is indicated in the table.

Code	CodeValue	CodeDescription in language code 'swe'	VIOL	
			2	3
AggravatedLoadingCondition	<TextValue> with one character	Beskriver i förekommande fall vilka försvårade förhållanden som rått vid lastning. Endast ett tecken.		√
	0	Ingen uppgift om försvårad lastning		√
	1	Försvårad lastning pga svåra förhållanden vid hämtning		√
	2	Försvårad lastning pga virke illa placerat		√
	3	Försvårad lastning pga små partier		√
	4	Försvårad lastning pga egen lastning med lånad truck		√
AVSTTYP	1	LKF virkesorder	√	
	2	LKF mätning	√	
	3	Transportkilometer virkesorder	√	
	4	Transportkilometer mätning	√	
	5	Vägdistrikt virkesorder	√	
	6	Vägdistrikt mätning	√	
	7	Viapunkt virkesorder	√	
	8	Mottagningsplats virkesorder	√	
	9	Transportkilometer leverantör	√	
	A	Transportkilometer justerad	√	
	B	KröntVägval	√	
	C	KröntVägval+verkl. avlastn.plats	√	
	D	KröntVägval+avlastn.plats 0	√	
	E	KröntVägval (ej samlast)	√	
	F	KröntVägval+verkl. avlastn.plats (ej samlast)	√	

Code	CodeValue	CodeDescription in language code 'swe'	VIOL	
			2	3
AVSTTYP (continued)	G	KröntVägval+avlastn.plats 0 (ej samlast)	√	
BasedOnTemplatePriceComponent	<TextValue>	The CodeDescription is the actual description associated with the CodeValue of this template price component. CodeValue is the ID of the Biometria template price component used as the price component was created. (sv: standardkomponent)		√
BefraktarKoder	<TextValue>	Följdrutinkod BKODER för befraktare, max 9 tecken. Företagsorienterad kod för befraktare. Används och disponeras av befraktaren för bearbetning och redovisning i dess följsystem.	√	
BETGRUNDVIKT	<NumericValue>	SCAs begrepp betalningsgrundande vikt	√	
BFAARK	<TextValue>	Accounting year for buyer party.	√	
BFAARS	<TextValue>	Accounting year for supplier party.	√	
BoundBasisToBeCreated	N/A to provide CodeValue	Biometria ombeds förmedla destineringsunderlag till destineringsansvarig part.		√
	No	Deprecated. Do not use. Instead skip the Code, as skipping the Code means the same as CodeValue "No" did.		√
	Yes	Deprecated. Do not use. Instead use the Code but without any CodeValue, as it means the same as CodeValue "Yes" did.		√
BuyerRelationContractedObject	<TextValue>	Anskaffningsform, dvs förstaledsköparens legala relation till samtliga avtalsobjekt i ett förstaledskontrakt.		√
	AO	Annan organisation enligt förstaledsköparens definition av säljaren		√
	CK	Deprecated. Do not use. Use code value AO instead.		

BuyerRelationContractedObject (continued)	ER	Egen resurs enligt förstaledsköparens definition av säljaren		✓
	ES	Deprecated. Do not use. Use code value ER instead.		✓
	NI	Deprecated. Do not use. Use code value PA instead.		
	PA	Privat ägare enligt förstaledsköparens definition av säljaren		✓
CALC_ID	<TextValue>	Codes used for retrieving a transport distance from NationalForestRoadDatabase. One character.	✓	
CALC_NAME	<TextValue>	Used for retrieving a transport distance from NationalForestRoadDatabase. Maximum 64 characters.	✓	
CERT	<TextValue>	2 last positions of Environmental certification.	✓	
ChargesAndMonetaryAdjustmentsID		Deprecated. Do not use.		✓
CompensatedAddtlEndDistance	<NumericValue> UOM="Kilometer"	Avslutande tilläggsavstånd som används vid beräkning av ersättningen i transportaffären		✓
CompensatedAddtlStartDistance	<NumericValue> UOM="Kilometer"	Inledande tilläggsavstånd som används vid beräkning av ersättningen i transportaffären		✓
CompensatedPrincipalDistance	<NumericValue> UOM="Kilometer"	Transportens basavstånd som används vid beräkning av ersättningen i transportaffären		✓
ContractedCurrency_VIOL2	<TextValue>	Currency to be used in the entire contract. To be deprecated in VIOL 3.	✓	
	EUR	Euro	✓	
	GBP	Brittiska pund	✓	
	NOK	Norska kronor	✓	
	SEK	Svenska kronor	✓	
	USD	US dollar	✓	
ContractedCurrency_VIOL3	<TextValue>	Kontraktsvaluta formaterat enligt ISO 4217.		✓
ContractLinePricingTerm	PriceAtContractDate	Pris vid kontraktstillfälle		✓
	PriceAtDeliveryDate	Pris vid leveranstillfälle		✓
DeliveryOriginAreaID	<TextValue> Max 30 characters	Transportområde The identifier of a grouping of one or many territorial districts where carriers pick up deliveries. Its value is unique to a DeliveryOriginAreaIDAssigner.		✓

DeliveryOriginAreaIDAssigner	<TextValue> formatted NNNNN-NNNNN	Transportområdesdefinierare The PartyIdentifier assigned by Biometria of the party that has created the DeliveryOriginAreaID. Refer to section PartyIdentifier assigned by agency SDC.		✓
DeliveryQtyShareAtTrptArrival	<NumericValue> UOM="Percentage"	Leveransens andel av leveransstillfallets kvantitet i det transportprisgrundande måttslaget		✓
DeliveryTerm	<TextValue>	Avtalsform		✓
	AU	Deprecated. Do not use. Use code value AU1 instead.		✓
	AU1	Avverkningsuppdrag		✓
	LEV1	Leverans		✓
	LRK	Deprecated. Do not use. Consider to use code value LRK1 or LRK2 instead.		
	LRK1	Leveransrotköp – Fast pris		✓
	LRK2	Leveransrotköp – Pris per sortiment		✓
	LV	Deprecated. Do not use. Use code value LEV1 instead.		
	ROT1	Rotpost		✓
	RP	Deprecated. Do not use. Use code value ROT1 instead.		
FinalLoadingStatusFromCarrier	SKM1	Skördarmätt uppdrag		✓
	1	Alla handelssortiment slut på avtalsobjekt		✓
	2	Handelssortiment slut på avtalsobjekt		✓
	3	Handelssortiment slut på avlägget		✓
	4	Handelssortiment slut på avtalsobjekt, skotning återstår		✓
FKODVO	5	Handelssortiment slut på avlägget, skotning återstår		✓
	<TextValue>	Code transferred from field LEVKOD of the "Virkesorder" in VIOL 2. In Production Ticket and ShipmentAdvice it is StanForD:SubObjectUserID if it is known to Viol and otherwise LEVKOD. The code will be deprecated in VIOL 3.	✓	

ForestForwardingIsCompleted	BooleanValue	Indicates whether the forest forwarding is completed for all products from a delivery source.		✓
ForestHarvestingIsCompleted	BooleanValue	Indicates whether the harvesting is completed for all products from a delivery source.		✓
FRAAN	<TextValue>	Value of the transport origin in accordance with the transport origin type provided as FRAANTYP.	✓	
FRAANTYP	1	Vägdistrikt	✓	
	2	Viapunkt	✓	
	3	Län, kommun, församling	✓	
	4	Mottagningsplats	✓	
	5	Leverantör	✓	
	6	Valfri uppgift	✓	
	7	Väggkod	✓	
FRITERM-###	<TextValue>	Various codes defined by different Biometria customers for their own purposes. Each code has three digits at the end of the code, such as FRITERM-034 or FRITERM-350. The CodeValue is a TextValue. These codes will be deprecated in VIOL 3.	✓	
FRITERM-KO-###	<TextValue>	Fri term put from "förstaledskontrakt" to OriginalContract or from "köparekontrakt" to TradingContract. Various codes defined by different Biometria customers for their own purposes. Each code has three digits at the end of the code, such as FRITERM-KO-034 or FRITERM-KO-350. The CodeValue is a TextValue. These codes will be deprecated in VIOL 3.	✓	
FRITERM-VO-###	<TextValue>	Fri term put from "virkesorder" to OriginalContract. Various codes defined by different Biometria customers for their own purposes. Each code has three digits at the end of the code, such as FRITERM-VO-034 or FRITERM-VO-350. The CodeValue is a TextValue. These codes will be deprecated in VIOL 3.	✓	

FSEDEL1	<TextValue>	Usage: May only be used in output from Biometria. Följesedel 1 in legacy system.	✓	
FSEDEL2	<TextValue>	Följesedel 2 in legacy system	✓	
HereUsedVIOLMeasurgOrderOprNum	<TextValue> Non-negative integer, max 6 digits	Mätorderrad i VIOL som redovisas i denna MeasuringTicketSequence		✓
IMPEXP	<TextValue>	Indicates direction of cross-border transport (also from/to EES country).	✓	
	‘ ‘ (space character)	Transporten passerar ej svensk landsgräns.	✓	✓
	1	Införsel till Sverige från annat land.	✓	✓
	2	Utförsel från Sverige till annat land.	✓	✓
InconvenientTransportReason	<TextValue> with one character	Beskriver i förekommande fall vilka försvårade förhållanden som rått vid transporten.		✓
	0	Ingen uppgift om försvårad transport		✓
	1	Försvårad transport pga dåligt väglag		✓
	2	Försvårad transport pga specifikt beordrat vägval		✓
	3	Försvårad transport pga rutt genom storstad		✓
InputMethodUsedForLoggingData	<TextValue>	Indicator that reports which method is used for entering data about logging.		✓
	RAPPapplication	Biometria application RAPP		✓
	StanForDFile	File formatted in the StanForD standard		✓
IsLogisticsValueInputRequested	BooleanValue	Flagga som visar om Biometria för transportaffärens parter ska tillhandahålla transportvärdegrundande avstånd och transportvärdegrundande kvantitet.		✓
IsPresenceOfCraneConfirmed	<TextValue> "Yes" or "No"	Usage: The CodeValue is "Yes" if there was an answer to the question "Does the vehicle carry a crane?", regardless of the answer. Otherwise the CodeValue is "No".	✓	
IsSetOfVehiclesFullyLoaded	BooleanValue	Ekipaget bedöms vara volymmässigt fullastat		✓
KIGEN	<TextValue> 0-99	Kontraktets generation i VIOL 2.	✓	
KKODER		User-specific codes for buyer, max 9 positions.	✓	
LastningOchLossning	0	Travers – gripare	✓	

LastningOchLossning (continued)	1	Travers – sling	✓	
	2	Truck hela lägg	✓	
	3	Truck delade lägg	✓	
	4	Egen kran	✓	
	5	Egen kran – specialpris	✓	
	6	Järnvägstravers (lastning på järnvägsvagn)	✓	
	7	Egen kran (lastning på järnvägsvagn)	✓	
	8	Ruslossning	✓	
	9	Buntlossning	✓	
LASTVIKT	<NumericValue> UOM="MetricTon"	SCAs begrepp Lastvikt	✓	
LED	<TextValue>	Must only be used in DeliveryMessage. The data of the document are valid in this link of a business chain with many links. The CodeValue is an integer in text format. LED=1 is the first link, which includes the Original Supplier.	✓	
LED1-BUYER-HKODK-INTNRK		To be deprecated, do not use.	✓	
LED1-ContractIdentifier	<TextValue>	The ContractIdentifier assigned by SDC referring to the contract in the FIRST link in a business chain for the product. When used for VIOL 2, the identity is given by three codes; [55.KINUM]-[55.HKODS]-[55.HKODK], e.g. 354264327-00043-08990.	✓	
LED2-BUYER-HKODK-INTNRK		To be deprecated, do not use.	✓	
LED2-ContractIdentifier	<TextValue>	The ContractIdentifier assigned by SDC referring to the contract in the SECOND link in a business chain for the product. When used for VIOL 2, the identity is given by three codes; [55.KINUM]-[55.HKODS]-[55.HKODK], e.g. 354264327-00043-08990.	✓	
LED3-BUYER-HKODK-INTNRK		To be deprecated, do not use.	✓	
LED3-ContractIdentifier	<TextValue>	The ContractIdentifier assigned by SDC referring to the contract in the THIRD link in a business chain for the product. When used for VIOL 2, the identity is given by three codes; [55.KINUM]-[55.HKODS]-[55.HKODK], e.g. 6453254321-08990-03131.	✓	
LED4-BUYER-HKODK-INTNRK		To be deprecated, do not use.	✓	

LED4-ContractIdentifier	<TextValue>	The ContractIdentifier assigned by SDC referring to the contract in the FOURTH link in a business chain for the product. When used for VIOL 2, the identity is given by three codes; [55.KINUM]-[55.HKODS]-[55.HKODK], e.g. 6453254321-08990-03131.	✓	
LED5-BUYER-HKODK-INTNRK		To be deprecated, do not use.	✓	
LED5-ContractIdentifier	<TextValue>	The ContractIdentifier assigned by SDC referring to the contract in the FIFTH link in a business chain for the product. When used for VIOL 2, the identity is given by three codes; [55.KINUM]-[55.HKODS]-[55.HKODK], e.g. 6453254321-08990-03131.	✓	
LED6-BUYER-HKODK-INTNRK		To be deprecated, do not use.	✓	
LED6-ContractIdentifier	<TextValue>	The ContractIdentifier assigned by SDC referring to the contract in the SIXTH link in a business chain for the product. When used for VIOL 2, the identity is given by three codes; [55.KINUM]-[55.HKODS]-[55.HKODK], e.g. 6453254321-08990-03131.	✓	
LED7-BUYER-HKODK-INTNRK		To be deprecated, do not use.	✓	
LED7-ContractIdentifier	<TextValue>	The ContractIdentifier assigned by SDC referring to the contract in the SEVENTH link in a business chain for the product. When used for VIOL 2, the identity is given by three codes; [55.KINUM]-[55.HKODS]-[55.HKODK], e.g. 6453254321-08990-03131.	✓	
LEDTR	<TextValue>	To be deprecated, do not use.	✓	
LEVAR	TextValue with four characters	Leveransår	✓	
LimitingRoadBearingCapClassNO	TextValue with one character	Begränsande norsk bärighetsklass för hela vägsträckan		✓
	1	?		✓
	2	Max 40 tons bruttovikt		✓
	3	Max 50 tons bruttovikt		✓
	4	Max 50 tons bruttovikt		✓
	5	Max 56 tons bruttovikt		✓
	6	Max 60 tons bruttovikt		✓
LimitingRoadBearingCapClassSE	TextValue with one character	Begränsande svensk bärighetsklass för hela vägsträckan		✓
	1	Max 64 tons bruttovikt		✓

LimitingRoadBearingCapClassSE (continued)	2	Max 51,4 tons bruttovikt	✓
	3	Max 37,5 tons bruttovikt	✓
	4	Max 74 tons bruttovikt	✓
LineItem1FinalShipmtIndicator (N.B. The CodeValue has no spaces)	FinalShipmentOf TheProductFromThis SupplyPoint	Deprecated. Do not use this CodeValue.	✓
	FinalShipmentOf TheProductToThis SupplyPoint	Detta är den sista skotningen av handelssortimentet i leveransrad 1 till just det avlägget.	✓
	NotConfirmingFinalS hipmentOfTheProdu ct	Det är i leveransrad 1 inte bekräftat att handelssortimentet i leveransrad 1 är slutskotat.	✓
LoggingMachineGroup	<TextValue> with max 25 characters	Maskinlag (grupp av maskiner som arbetar tillsammans)	✓
LogisticGrossWeightAtArrival	<NumericValue> UOM="MetricTon"	Ekipagets tågvikt före lossning av någon last vid platsen	✓
LogisticGrossWeightAtDeparture	<NumericValue> UOM="MetricTon"	Ekipagets tågvikt efter lossning av samtliga leveranser vid platsen	✓
LogisticGrossWghtPostUnloading	<NumericValue> UOM="MetricTon"	Deprecated. Do not use. Ekipagets tågvikt efter lossning av ett handelssortiment i en leverans	✓
LogisticGrossWghtPreUnloading	<NumericValue> UOM="MetricTon"	Deprecated. Do not use. Ekipagets tågvikt före lossning av ett handelssortiment i en leverans	✓
LogisticsServicePriceSource	LoadTenderSegment	Priset har hämtats från transportunderlag	✓
	LogisticsServicePrice List	Priset har hämtats från transportprislista	✓
	NoValueCalculationR equested	Deprecated. Do not use this CodeValue.	✓
	PreviousSequenceOf BusinessChain	Priset har hämtats från föregående led	✓
MaxWeightConfiguredVehicleSet	<NumericValue> UOM="MetricTon"	Ekipagets tillåtna maxvikt	✓
MeasureUsabilityCountedObjects	<TextValue>		✓
	1	Kvalitet på kvantitetsvärde för antal mätenheter tillräckligt bra för Råvaruredovisning enligt VML	✓
	2	Kvalitet på kvantitetsvärde för antal mätenheter tillräckligt bra för Råvaruredovisning BusinessToBusiness	✓
	3	Kvalitet på kvantitetsvärde för antal mätenheter tillräckligt bra för Transportredovisning	✓
	4	Kvalitet på kvantitetsvärde för antal mätenheter tillräckligt bra för Statistik	✓
MeasureUsabilityM3Loose	<TextValue>		✓

MeasureUsabilityM3Loose (continued)	1	Kvalitet på kvantitetsvärde för kubikmeter skrymvolym tillräckligt bra för Råvaruredovisning enligt VML		✓
	2	Kvalitet på kvantitetsvärde för kubikmeter skrymvolym tillräckligt bra för Råvaruredovisning BusinessToBusiness		✓
	3	Kvalitet på kvantitetsvärde för kubikmeter skrymvolym tillräckligt bra för Transportredovisning		✓
	4	Kvalitet på kvantitetsvärde för kubikmeter skrymvolym tillräckligt bra för Statistik		✓
MeasureUsabilityM3NarrowEnd	<TextValue>			✓
	1	Kvalitet på kvantitetsvärde för kubikmeter toppcylindervolym tillräckligt bra för Råvaruredovisning enligt VML		✓
	2	Kvalitet på kvantitetsvärde för kubikmeter toppcylindervolym tillräckligt bra för Råvaruredovisning BusinessToBusiness		✓
	3	Kvalitet på kvantitetsvärde för kubikmeter toppcylindervolym tillräckligt bra för Transportredovisning		✓
	4	Kvalitet på kvantitetsvärde för kubikmeter toppcylindervolym tillräckligt bra för Statistik		✓

MeasureUsabilityM3Solid	<TextValue>			✓
	1	Kvalitet på kvantitetsvärde för kubikmeter fastvolym tillräckligt bra för Råvaruredovisning enligt VML		✓
	2	Kvalitet på kvantitetsvärde för kubikmeter fastvolym tillräckligt bra för Råvaruredovisning BusinessToBusiness		✓
	3	Kvalitet på kvantitetsvärde för kubikmeter fastvolym tillräckligt bra för Transportredovisning		✓
	4	Kvalitet på kvantitetsvärde för kubikmeter fastvolym tillräckligt bra för Statistik		✓
MeasureUsabilityMetricTon	<TextValue>			✓
	1	Kvalitet på kvantitetsvärde för ton tillräckligt bra för Råvaruredovisning enligt VML		✓
	2	Kvalitet på kvantitetsvärde för ton tillräckligt bra för Råvaruredovisning BusinessToBusiness		✓
	3	Kvalitet på kvantitetsvärde för ton tillräckligt bra för Transportredovisning		✓
	4	Kvalitet på kvantitetsvärde för ton tillräckligt bra för Statistik		✓
MeasureUsabilityMinutesTime	<TextValue>			✓
	1	Kvalitet på kvantitetsvärde för minuter tillräckligt bra för Råvaruredovisning enligt VML		✓
	2	Kvalitet på kvantitetsvärde för minuter tillräckligt bra för Råvaruredovisning BusinessToBusiness		✓
	3	Kvalitet på kvantitetsvärde för minuter tillräckligt bra för Transportredovisning		✓
	4	Kvalitet på kvantitetsvärde för minuter tillräckligt bra för Statistik		✓

MeasureUsabilityMWhEnergy	<TextValue>			✓
	1	Kvalitet på kvantitetsvärde för energiinnehåll i MWh tillräckligt bra för Råvaruredovisning enligt VML		✓
	2	Kvalitet på kvantitetsvärde för energiinnehåll i MWh tillräckligt bra för Råvaruredovisning BusinessToBusiness		✓
	3	Kvalitet på kvantitetsvärde för energiinnehåll i MWh tillräckligt bra för Transportredovisning		✓
	4	Kvalitet på kvantitetsvärde för energiinnehåll i MWh tillräckligt bra för Statistik		✓
MeasureUsabilityTonneBoneDry	<TextValue>			✓
	1	Kvalitet på kvantitetsvärde för ton torrsvikt tillräckligt bra för Råvaruredovisning enligt VML		✓
	2	Kvalitet på kvantitetsvärde för ton torrsvikt tillräckligt bra för Råvaruredovisning BusinessToBusiness		✓
	3	Kvalitet på kvantitetsvärde för ton torrsvikt tillräckligt bra för Transportredovisning		✓
	4	Kvalitet på kvantitetsvärde för ton torrsvikt tillräckligt bra för Statistik		✓
MMA	1-9, T	See MeasuringCodeInfo – MeasuringMethodService (4.11) for further details.	✓	
MMB	1-9, T	See MeasuringCodeInfo – MeasuringMethodService (4.11) for further details.	✓	
MMC	1-9, T	See MeasuringCodeInfo – MeasuringMethodService (4.11) for further details.	✓	
MMD	1-9, T	See MeasuringCodeInfo – MeasuringMethodService (4.13) for further details.	✓	
MSLAG_KO	<TextValue>	Virkeskollektivets måttslag. To be deprecated in VIOL 3.	✓	
MSLAGT	<TextValue>	Unit of measure used in the quantity for calculating transport charges.	✓	
NumberOfFerryCrossingsMade	NumericValue UOM="Piece"	Antal färjeöverfarter för transporten		✓
NumberOfTollroadLegsTravelled	NumericValue UOM="Piece"	Antal avgiftsbelagda vägsträckor som passerats av transporten		✓
Omlastning	<empty>	<empty> or "Omlastning från bil till släp krävs ej"	✓	
	0	Omlastning från bil till släp krävs ej	✓	
	1	Omlastning från bil till släp krävs ej	✓	
	2	Omlastning från bil till släp nödvändigt	✓	
	3	Omlastning från bil till släp nödvändigt	✓	

Omlastning (continued)	4	Omlastning från bil till släp nödvändigt	✓	
	5	Vägen omklassad av VMF	✓	
	6	Omklassning begärd av lev/distrikt	✓	
	7	Tillfällig väg	✓	
	8	Väg med backe	✓	
OMRFLIS	<TextValue>	Indicator controlling functionality in the sample management module of VIOL 2 system. To be deprecated in VIOL 3.	✓	
	X	Fliskollektiv, kollektivomräkning sker för flis.	✓	
OriginalBuyerAgentHierarchyID	<TextValue> formatted NNNNN-NNNNN	Förste köpare Identity of an organisational hierarchy of original buyer agents potentially including the original buyer. The value is the PartyIdentifier assigned by Biometria to the Buyer or BuyerAgent being the top node in this hierarchy. Refer to section PartyIdentifier assigned by agency SDC.		✓
OriginalLogisticsSupplierFrom	ProvidedAtPreBooking	Ansvarigt transportföretag i första affärsledet hämtas från transportunderlaget		✓
	ShpmntEventCostBasisCompleted	Ansvarigt transportföretag i första affärsledet hämtas från uppgift angiven då transporten slutförs		✓
PERIOD	<TextValue> with 1 or 2 characters	Period inom leveransår.	✓	
PGEN	<NumericValue> UOM="None"	Prisgeneration (always an integer)	✓	
PKOD1	<TextValue>	Customer-defined one-digit code used for pricing and compensation calculation.	✓	
PKOD2	<TextValue>	Customer-defined one-digit code used for pricing and compensation calculation.	✓	
PKOD3	<TextValue>	Customer-defined one-digit code used for pricing and compensation calculation.	✓	
PKOD4	<TextValue>	Customer-defined one-digit code used for pricing and compensation calculation.	✓	

PKOD5	<TextValue>	Customer-defined one-digit code used for pricing and compensation calculation.	√	
PKODT	<TextValue>	Customer-defined one-digit code used for pricing and compensation calculation of the logistics service.	√	
PopulationMeasuringIsRequired	N/A to provide CodeValue	Virkeskollektiv krävs vid mätning.		√
PopulationMeasuringRequired	<BooleanValue>	Deprecated, do not use.		√
PreliminaryEndUser		PartyIdentifier (using value assigned by agency SDC) of the party that prior to firm decision was planned to be EndUser in the transaction.		√
PrelOriginalLogisticsBuyer		PartyIdentifier (using value assigned by agency SDC) of the party that prior to firm decision was planned to be OriginalLogisticsBuyer in the transaction.		√
PrelOriginalLogisticsBuyerAgnt		PartyIdentifier (using value assigned by agency SDC) of the party that prior to firm decision was planned to be OriginalLogisticsBuyerAgent in the transaction.		√
PrelOriginalLogisticsSupplier		PartyIdentifier (using value assigned by agency SDC) of the party that prior to firm decision was planned to be OriginalLogisticsSupplier in the transaction.		√
PriceBasedOnPopulation	<TextValue> One digit	Anger huruvida priset kommer från virkeskollektiv. CodeValue avser ett kodvärde och är inte något monetärt värde.		√
	1	Pris från kollektiv		√
PriceListDeterminedUsingParty	N/A to provide CodeValue	Råvaruvärdet ska beräknas med prislistehänvisning		√
	No	Deprecated. Do not use. Instead skip the Code, as skipping the Code means the same as CodeValue "No" did.		√

PriceListDeterminedUsingParty (continued)	Yes	Deprecated. Do not use. Instead use the Code but without providing any CodeValue, as it means the same as CodeValue "Yes" did.		✓
PrincipalDistanceSourceType	<TextValue>	Källa till transportens ersättningsgrundande basavstånd		✓
	1	Korrigerat avstånd		✓
	2	Aviserat KV-avstånd		✓
	3	TU KV-avstånd		✓
	4	TU angivet avstånd		✓
	5	Åkarangivet avstånd		✓
PRISTYP	<TextValue>	Kod för pristräkning	✓	
ProductValueCalculatedBySDC	N/A to provide CodeValue	Råvaruaffären ska värdeberäknas av Biometria		✓
	No	Deprecated. Do not use. Instead skip the Code, as skipping the Code means the same as CodeValue "No" did.		✓
	Yes	Deprecated. Do not use. Instead use the Code but without providing any CodeValue, as it means the same as CodeValue "Yes" did.		✓
ProduktID	<TextValue>	ProductIdentifier of a log assigned by the forest harvester as a stem is harvested and it is not a ManufacturingGradeCode.		✓
PropellantIndexPeriodStartDate	<TextValue> formatted YYYYMMDD	Startdatum för drivmedelsprisindexperiod		✓
PropellantPriceIndex	<TextValue> Max 50 characters	Drivmedelsprisindex		✓
PropellantPriceIndexIssuerID	<TextValue> formatted NNNNN-NNNNN	Ägare av drivmedelsprisindex The value is the PartyIdentifier assigned by Biometria to the organisation that owns and manages the propellant index. Refer to section PartyIdentifier assigned by agency SDC.		✓

PropellantPriceValueCoefftUsed	<NumericValue> UOM="None"	Drivmedelsfaktor The coefficient value that has been used in the propellant price component when calculating the transportation compensation value.		√
REDOVHANV	X	'Redovisningshänvisning' is used.	√	
	' '	'Redovisningshänvisning' is not used.	√	
ReportedExtraTransportTime	<NumericValue> UOM="Minute"	Extra tidsåtgång för transport		√
RequiredVIOLMeasurgOrderOprNum	<TextValue> Non-negative integer, max 6 digits	Mätorderrad i VIOL som har krävts för leveransen		√
RETRO	<TextValue>	Retroaktiv pristräkning	√	
RETUR	<NumericValue> UOM="Kilometer"	Inbesparad tomkörning vid returtransport.	√	√
RNRPERLAST	<TextValue>	Redovisningsnummer per lastid	√	
RUTTID_TR	<TextValue>	Ruttidentitet transport	√	
SCA_OMRVERDEPLTR	<NumericValue> UOM="None"	Conversion coefficient for term "Lastvikt" of SCA Skog AB. To be deprecated in VIOL 3.	√	
SCA_SAMLAST_FEL	J	Weight distribution of all CoLoaded deliveries is calculated. To be deprecated in VIOL 3.	√	
	N	Weight distribution of CoLoaded deliveries is not calculated yet, but will be calculated. To be deprecated in VIOL 3.	√	
	-	No weight distribution will be made for the CoLoaded deliveries. To be deprecated in VIOL 3.	√	
	' ' (character space)	The delivery is not CoLoaded. To be deprecated in VIOL 3.	√	
SDCAccountingReferenceID	<TextValue>	Deprecated. Do not use. Instead use reference type CompensationChainNumber. Biometrias ID för en redovisningshänvisning.		√

SDCBasePriceCompExtRefIssuerID	<TextValue> formatted NNNNN-NNNNN	Biometrias ID på ägare av grundpriskomponent. The value is the PartyIdentifier assigned by Biometria to the organisation that owns and manages the contracted base price component (Swedish: <i>grundpriskomponent</i>). For proper identifiers refer to section PartyIdentifier assigned by agency SDC.	✓
SDCBasePriceComponent	<NumericValue> UOM="None"	The CodeDescription is NOT a description but instead the actual ID of the contracted base price component (Swedish: <i>grundpriskomponent</i>). N.B. CodeValue is not required. CodeValue is the price to provide to the " <i>grundpriskomponent</i> ". The currency is provided with Code ContractedCurrency_VIOL3. Study section 4.1.2 for guidance on proper usage.	✓
SDCBasePriceComponentExternRef	<TextValue>	Det ID som tilldelats grundpriskomponenten av dess ägare. N.B. This code requires that code SDCBasePriceCompExtRefIssuerID is provided in the document too.	✓
SDCBasePriceComponentGroup	<TextValue>	Biometrias grupp av grundpriskomponenter baserat på använd standardkomponent	✓
SDCBasePriceComponentID	<TextValue>	The text in CodeDescription is a customer-defined description of the base price component. N.B. The CodeValue is the Biometria ID of the base price component.	✓
SDCBasePriceComponentName	<TextValue>	Deprecated. Instead use code BasedOnTemplatePriceComponent	✓

SDCBasePriceComponentType	<TextValue>	Biometrias typning av grundpriskomponenten The Biometria type classification of the base price component		✓
SDCBasePriceComponentVersion	<TextValue>	Version av grundpriskomponenten		✓
SDCChargesAndAdjustments	<NumericValue> UOM="None"	The CodeDescription is NOT a description but instead the actual ID of a contracted Charge/Monetary adjustment component. (Swedish: <i>Tilläggs-/Avdragskomponent</i>). N.B. CodeValue is not required. CodeValue is the price used for the "T/A-komponent". A negative price is indicated with a leading minus sign (-) in CodeValue. The currency is provided with Code ContractedCurrency_VIOL3. Study section 4.1.2 for guidance on proper usage.		✓
SenderSoftwareVersion	<TextValue>	Mjukvara inklusive version som använts vid filöverföring från skogsmaskin	✓	✓
Site	<TextValue> Max 6 characters	Id på (Fysisk) plats/område för hantering av råvaruleverans		✓
SiteName	<TextValue>	Namn på (Fysisk) plats/område för hantering av råvaruleverans		✓
SKODER		User specific codes for seller, max 9 positions.	✓	
Slutkort	1	Beordrad kvantitet slutkörd. Avlägget tömt.	✓	
	2	Beordrad kvantitet slutkörd. På avlägget finns andra sortiment kvar.	✓	
	3	Beordrad kvantitet och sortiment slutkört. Skotning återstår.	✓	
SnowRemoval	1	Snöplogning regelbunden	✓	
	2	Snöplogning okänd	✓	
SourceMaxWeightConfVehicleSet	<TextValue>	Data source of CodeValue for Code MaxWeightConfiguredVehicleSet		✓
	1	Ekipagets maxvikt angiven vid inmätning		✓
	2	Ekipagets i förväg lagrade maxvikt hos Biometria		✓

SourceMaxWeightConfVehicleSet (continued)	3	Ekipagets maxvikt begränsad av vid inmätningen angiven bärighetsklass		✓
	4	Ekipagets maxvikt kan ej fastställas		✓
	5	Ekipagets maxvikt ska ej fastställas		✓
SourcingAreaGroupAssigner	<TextValue> formatted NNNNN-NNNNN	Försörjningsområdesdefinierare The PartyIdentifier assigned by Biometria of the party that has created the SourcingAreaGroupID. Refer to section PartyIdentifier assigned by agency SDC.		✓
SourcingAreaGroupID	<TextValue> Max 50 characters	Försörjningsområde The identifier of a grouping of one or many supplying territorial districts. It is uniquely assigned by a SourcingAreaGroupAssigner.		✓
StanForDBarkFunction	<TextValue>	Mathematical function used by forest harvester and provided in a StanForD file.	✓	✓
StanForDFileName	<TextValue>	The name of the StanForD file.		✓
StanForDFileType	<TextValue>	File type of a StanForD file with 3 characters.	✓	✓
StanForDObjectGroupID	<TextValue>	ObjectGroupID from a StanForD file.	✓	✓
StanForDPRIFileSequenceNumber	<TextValue>	File sequence number of a StanForD PRI file with only numeric digits. It has maximum three characters.	✓	✓
StanForDProductVersion	TextValue with max 20 characters. For usage with VIOL 2 max 6 characters.	Version of the StanForD Product instruction (ProductUserID) used by the forest harvester as communicated in the StanForD file. The version has been assigned by the ForestHarvestingRequestor.	✓	✓
StanForDSubObjectUserID	TextValue with max 5 characters	Identity of sub harvesting object in a StanForD file as defined by user of data, normally by the ForestHarvestingRequestor.		✓
Stickvag	<empty> or 1	Virket ligger vid stickväg om värdet är 1.	✓	
SupplyingRegistrationDistrict	TextValue with six digits	Försörjningsområdets distriktskod. I Sverige nyttjas den indelning som definierats av Lantmäteriet.		✓
TEMP_AVLPL	<TextValue>	Avlastningsplats/lossningsplats inom mätplats To be deprecated in VIOL 3.	✓	

TEMP_RNRGEN	<TextValue>	Version of the measurement in VIOL 2. To be deprecated in VIOL 3.	✓	
TEMP_TRPKM_KORR	<NumericValue> UOM="Kilometer"	Value overrides measured transport distance in price calculation. To be deprecated in VIOL 3.	✓	
TRADALDER	<NumericValue> UOM="Year"	Age in years of tree to be forested.	✓	
TradingPartnerSequencelsFixed	N/A to provide CodeValue	Kedjans affärsled måste bevaras med köparna och säljarna i denna ordning.		✓
TransportMode	None	Ingen transport ska ske		✓
	Rail	Järnvägstransport		✓
	Road	Transport på väg		✓
TransportResourceCircumstance	<TextValue>	The CodeValue indicates a special transport resource circumstance identified as a transport assignment was carried out.		✓
	0	Ej angivet transportresurs		✓
	1	Andelsbil		✓
	2	Ej andelsbil		✓
	3	Ingår i projekt		✓
	4	Ingår i treskift		✓
	5	Marginalresurs		✓
	6	Ny chaufför		✓
	7	Resurs geografiskt flexibel		✓
	8	Resurs vid brand		✓
	9	Resurs vid storm		✓
	10	Resurs vintertid		✓
	11	Resurs utökat ansvar		✓
TransprtAvailableToMeasureDate	<TextValue> formatted as a timestamp with UTC offset	Tidpunkt då chauffören anmäler ekipagets ankomst till mätplatsen då det är redo att bli mottagningskontrollerat. N.B. The TextValue must be formatted YYYYMMDDThhmmss+hh:mm, where T is the character T and +hh:mm is the offset in hours and minutes from UTC.		✓

TransprtCompletelyMeasuredDate	<TextValue> formatted as a timestamp with UTC offset	Tidpunkt enligt det mätande företaget för den sista mätningstjänsten som utförs vid avlämning. N.B. The TextValue must be formatted YYYYMMDDThhmmss+hh:mm, where T is the character T and +hh:mm is the offset in hours and minutes from UTC.		✓
TRPALT	<TextValue>	Codes used for transport cost calculation. One character.	✓	
TSKOD	001	FAST AVGIFT	✓	
	002	LASTNINGLOSSNING	✓	
	003	TIMLÖN	✓	
	004	SKOTNINGVIRKE	✓	
	005	INMÄTT TIMMER O MASSAVED	✓	
	006	VÄNTETID	✓	
	007	DIVERSE LASTNING LOSSN	✓	
	008	LOSSNING MED EGEN KRAN	✓	
	009	DIVERSE TRANSPORT	✓	
	010	UPPLÄGG.VIRKE	✓	
	011	LASTNING BILAR	✓	
	012	HELGERS LÖRDAG	✓	
	013	EXTRA HELGERSÄTNING	✓	
	014	TRAKTAM	✓	
	015	JUSTERI:APRIS	✓	
	016	SMÅPOST.< 100 M3F	✓	
	017	LASTNINGJÄRNVÄG	✓	
	018	NATT TÖVA	✓	
	019	SNÖRÖJN	✓	
	020	UTLAST BRÄNSLE TÅG	✓	
	021	STORMKOSTNADER	✓	
T_METOD	VTG_RE50	Redovisa nymätning	✓	
	VTG_RE51	Redovisa korrigerig kredittransaktion	✓	
	VTG_RE52	Redovisa korrigerig debettransaktion	✓	
	VTG_RE53	Redovisa retroaktiv pristräkning	✓	
	VTG_RE54	Redovisa kollektivtransaktion	✓	
	VTG_RE55	Redovisa kollektivtransaktion retroaktiv pristräkning	✓	
	VTG_RE56	Redovisa kollektivtransaktion kreditering	✓	

T_METOD (continued)	VTG_RE60	Redovisa nymätning transport	✓	
	VTG_RE61	Redovisa korrigerig kredit transport	✓	
	VTG_RE62	Redovisa korrigerig debet transport	✓	
	VTG_RE63	Redovisa retroaktiv pristräkning transport	✓	
T_USER	<TextValue> with 7 or 8 characters	User ID in VIOL 2 that updated the object. It is either a person or a system. Typical objects are order and contract.	✓	
Uppdrag	<TextValue> 0-9 and A-Z only one character	<Depending on legacy system>	✓	
URNR	<TextValue>	A reference to a corresponding measurement (MeasuringNumber). The reference will be deprecated in VIOL 3.	✓	
Ursprung	1	Virke från egen skog	✓	
	2	Virke från rotpost	✓	
	3	Leveransvirke	✓	
	4	Leveransrotposter/Avverkningsuppdrag	✓	
	5	Leveransrotposter/Avverkningsuppdrag	✓	
	6	Leveransrotposter/Avverkningsuppdrag	✓	
	7	Leveransrotposter/Avverkningsuppdrag	✓	
	8	Reserv	✓	
	9	Okänt ursprung	✓	
UsePopulationPriceList	N/A to provide CodeValue	Pris från kollektiv ska användas		✓
	No	Deprecated. Do not use. Instead skip the Code, as skipping the Code means the same as CodeValue "No" did.		✓
	Yes	Deprecated. Do not use. Instead use the Code but without providing any CodeValue, as it means the same as CodeValue "Yes" did.		✓
VAGKL2	<NumericValue> UOM="Kilometer"	Väggklass 2 i kilometer	✓	
VAGKL3	<NumericValue> UOM="Kilometer"	Väggklass 3 i kilometer	✓	

VAGKL4	<NumericValue> UOM="Kilometer"	Väggklass 4 i kilometer	✓	
VDISTR	<TextValue>	Väggdistriktet som är från begrepp i transportavräkning	✓	
VIOL2_AnySubentityMaySupplyToo	No	Indicates whether any entity of the Supplier company may supply to fulfil the TradingContract in VIOL 2. "Yes" sets the VIOL 2 system indicator "Öppen säljare". To be deprecated in VIOL 3.	✓	
	Yes		✓	
VMFusedForOtherPurpose	<TextValue> 60, 69, 70, 72, 77, 96 and 99	Legacy VMF code in VIOL 2, which is not a MeasuringParty. To be deprecated in VIOL 3.	✓	
VML	N/A to provide CodeValue	Omfattas av svensk virkesmättningslag		✓
	<TextValue> with one space (' ').	Påverkas ej av svensk virkesmättningslag	✓	
	NO	Deprecated. Do not use. For VIOL 2 use CodeValue " " instead, the space character. For VIOL 3 instead skip the Code entirely. It has the same meaning.	✓	✓
	X	Omfattas av svensk virkesmättningslag	✓	
	YES	Deprecated. Do not use. For VIOL 2 use CodeValue X instead. For VIOL 3 use instead the Code but without providing a CodeValue.	✓	✓
VOGEN	<TextValue> 0-99	Virkesorderns generation i VIOL 2.	✓	
VO_STATUS_HUVUD	<TextValue> ' ','M'	Status of "Virkesorder".	✓	
VO_STATUS_RAD	<TextValue> 'Klar', 'Vilande', 'Makulerad'	Status of line of "Virkesorder".	✓	
WeekendTransportDueToRequest	<TextValue> Yes	Transporten rapporteras ha utförts som en beordrad helgkörning		✓

4.1.1 VIOL 2

For code AVSTTP refer to table "Avståndstyp" in "FU Handbok Följdrutinutgångar" for further details.

For codes FRAAN and FRAANTYP refer to table "FRÅN- OCH TILLBEGREPP" in "VIOL Koder" for further details.

For code CERT refer to table “CERTIFIERING” in “VIOL Koder” for further details.

For code FSEDEL2 the usage is not harmonized.

For code FRITERM-####, “#### “ is the value of TERMNR in VIOL 2. Please see the codes for TERMNR and their set of code values in application VIOL 2, using its menu choice “Tjänster → Fria Termer → Fria Termer”. They are not documented elsewhere.

For code GRANSOTRP refer to table ”GRÄNSÖVERSKRIDANDE TRANSPORT” in “VIOL Koder” for further details.

For code IMPEXP refer to table “IMPORT/EXPORT” in “VIOL Koder” for further details.

For code LastningOchLossning refer to table “KODER FÖR LASTNING OCH LOSSNING” in “VIOL Koder” for further details.

For code Omlastning refer to table “OMLASTNING” in “VIOL Koder” for further details.

For code RETUR the receiver may round the value to 0 km, 10 km , 20 km, 30 km,...

For code Slutkort refer to table “SLUTKÖRT” in “VIOL Koder” for further details.

For code SnowRemoval refer to table “SNÖ” in “VIOL Koder” for further details.

For code T_METOD refer to table “Systemtjänst = Metod” in “FU Handbok Följdrutinutgångar”, for further details.

For code Ursprung refer to table “URSPRUNG” in “VIOL Koder”, for further details.

Notice that code VIOL2_AnySubentityMaySupplyToo was introduced in version 23.0 of this document. It has by mistake been misspelled with a space between “VIOL” and “2_Any” from version 25.0 to version 38.0 making the code 31 characters long although it must not exceed 30 characters to pass schema validation. The space between VIOL and 2_Any was removed in version 39.0. Since the misspelled code could not pass schema validation it cannot have been used successfully in integrations. Biometria requires that a papiNet document must pass schema validation successfully before it is sent.

4.1.2 VIOL 3

Code `DeliveryOriginAreaIDAssigner` must be included in a document if code `DeliveryOriginAreaID` is provided in a document. A particular `CodeValue` of `DeliveryOriginAreaID` typically refers to different sets of territorial districts for different assigners.

Detailed usage of code `SDCBasePriceComponent`: If an `AdditionalItemInfo/CodeValue` is supplied, it is the price to use in the base price component. The `CodeDescription` of this code is the Biometria ID of the contracted base price component. The currency for the price is communicated as `CodeValue` in `AdditionalItemInfo` with `Code = "ContractedCurrency_VIOL3"`. For possible values of the `CodeDescription` of code `SDCBasePriceComponent` refer to "*Priskomponent*" of type "*Grundpris*" in system VIOL 3.

The currency is the same for the price of the `SDCBasePriceComponent` and all instances of `SDCChargesAndAdjustments`. It is supplied as `CodeValue` in an `AdditionalItemInfo` with `Code = "ContractedCurrency_VIOL3"`.

The Biometria ID of a base price component in VIOL 3 can be supplied with code `SDCBasePriceComponentID`. For possible values of `SDCBasePriceComponentID` refer to "*Priskomponent*" of type "*Grundpris*" in system VIOL 3.

Detailed usage of code `SDCChargesAndAdjustments`: The ID of this component in VIOL 3 is supplied in `AdditionalItemInfo/CodeDescription`. For possible values of `CodeDescription` refer to "*Priskomponent*" of type "*T/A*" in system VIOL 3. If an `AdditionalItemInfo/CodeValue` is supplied, it is the price to use in the component. The currency for the price is communicated as `CodeValue` in the `AdditionalItemInfo` with `Code = "ContractedCurrency_VIOL3"`.

Code `SourcingAreaGroupAssigner` must be included in a document if code `SourcingAreaGroupID` is provided in a document. A particular `CodeValue` of `SourcingAreaGroupID` typically refers to different sets of territorial districts for different assigners.

If code `TradingPartnerSequenceIsFixed` is true, all buyers, buyer agents, sellers and suppliers of the business chain must remain in the business chain and in the current order. This is typical to any compensation chain that uses Biometria population variant 1. The code is indifferent to contracts that are allocated in the business chain as long as the parties mentioned above remain the same and in the current sequence. If the code is false, the above mentioned parties of the business chain may be removed or changed.

Code `TransportResourceCircumstance` refers to the VIOL 3 term "*Transportresurs*" and is used to communicate a particular transport resource circumstance that was identified as a transport was carried out. Several different circumstances may be simultaneously communicated and may have individual impact on financial compensation calculation.

4.2 BusinessPartyProperty

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “sdCIDofSuperiorOrganisation” and “SDCIDofSUPERIORORGANISATION” are the same.

The CodeValue is alphanumeric and must use element TextValue and NOT NumericValue, unless otherwise is indicated in the table.

Code	CodeValue	CodeDescription in language code 'swe'	VIOL	
			2	3
SDCIDofSuperiorOrganisation	<TextValue> 11 characters formatted NNNNN-NNNNN	Biometrias ID på organisationsföräldern The value is the single PartyIdentifier assigned by Biometria to the organisation unit indicated as directly superior to the business party. Refer to section PartyIdentifier assigned by agency SDC.		✓

4.3 ClassificationCode

Code	ClassificationCodeType	ClassificationDescription in Swedish	VIOL	
			2	3
	CatalogueNumber			✓
	GradeCode		✓	✓
	ManufacturingGradeCode		✓	✓

4.3.1 VIOL 2

The same codes are possible as for ProductIdentifier to show SSTE code of Biometria for ”inmätt” and ”fördelat” product respectively. The ClassificationDescriptions are not published by Biometria, but are the same as those used for ProductDescription.

ClassificationCodeType must be either GradeCode for ”SDC fördelat sortiment” or ManufacturingGradeCode for ”SDC inmätt sortiment” and products transported from a forest or a production facility.

Refer to tables 7, 8, 10 and 12 in “VIOL Koder”, for details on SSTE codes. Please notice that there are no official Biometria values of ProductDescription.

4.3.2 VIOL 3

ClassificationCodeType must be either CatalogueNumber for “SDC sortimentskategori”, ManufacturingGradeCode for ”SDC handelssortiment” or GradeCode for ”SDC produkt” and products transported from a forest or a production facility.

4.4 CostComponentCode

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “XMIXED” and “xMixed” are the same.

CostComponentCode	Usage	VIOL	
		2	3
AdditionalTrnsprtRelatedCharge	ID of an Additional transport related charge. CostComponentCodeValue is a TextValue with four digits as specified in separate section on VIOL 3 below.		✓
AgreedTrptChargePricedPerLoad	Transportation charge that has been agreed in advance and is priced per load. CostComponentDescription should be “Agreed transportation charge priced per load” It must not have a CostComponentCodeValue.		✓
AgreedTrptChargePricedPerUnit	Transportation charge that has been agreed in advance and is priced per unit of measurement. CostComponentDescription should be “Agreed transportation charge priced per unit” It must not have a CostComponentCodeValue.		✓
BasedOnTemplatePriceComponent	CostComponentCodeValue is a TextValue. The TextValue is the ID of the Biometria template price component that was used as the parallel cost component was created. The CostComponentDescription is the actual description associated with the CodeValue of this template price component. For additional usage details refer to section 4.4.2 VIOL 3, below this table. (sv: standardkomponent)		✓

CostComponentCode	Usage	VIOL	
		2	3
ChargeAndAdjustmExtRefIssuerID	CostComponentDescription in Swedish is “Biometrias ID på ägare av T/A-priskomponent”. CostComponentCodeValue is a TextValue formatted NNNNN-NNNNN. The latter TextValue is the PartyIdentifier assigned by Biometria to the organisation that owns and manages the CostComponentCodeValue provided in CostComponentCode SDCChargesAndAdjustmentsExtRef. For proper identifiers refer to section PartyIdentifier assigned by agency SDC.		V
LogBasePriceCompExtRefIssuerID	CostComponentDescription in Swedish is “Biometrias ID på ägare av grundpriskomponent”. CostComponentCodeValue is a TextValue formatted NNNNN-NNNNN The latter TextValue is the PartyIdentifier assigned by Biometria to the organisation that owns and manages the CostComponentCodeValue provided in CostComponentCode LogisticsBasePriceCompExtRef. For proper identifiers refer to section PartyIdentifier assigned by agency SDC.		V
LogisticsBasePriceCompExtRef	CostComponentDescription in Swedish is “Det ID som tilldelats grundpriskomponenten av dess ägare”. CostComponentCodeValue is a TextValue. The customers own reference to the base price component of a logistics service. N.B. This code requires that code LogBasePriceCompExtRefIssuerID is provided in the document too.		V

CostComponentCode	Usage	VIOL	
		2	3
RejectPriceBasedOnPopulation	CostComponentDescription in Swedish is "Den vrakade kvantitetens pris kommer från kollektivet." Indication that the price of the rejected quantity is based on the statistic population. CostComponentCodeValue is a TextValue.		✓
SDCChargesAndAdjustments	The CostComponentDescription is the actual description associated with the CodeValue of this price component. CostComponentCodeValue is a TextValue. The TextValue is the ID of a quantity-based charge or deduction. The cost can be calculated by Biometria.		✓
SDCChargesAndAdjustmentsExtRef	CostComponentDescription in Swedish is "Det ID som tilldelats T/A-priskomponenten av dess ägare". CostComponentCodeValue is a TextValue. The customers own reference to the quantity-based charge or deduction. N.B. This code requires that CostComponentCode ChargeAndAdjustmExtRefIssuerID is provided too.		✓
SDCChargesAndAdjustmentsGroup	CostComponentDescription in Swedish is "Komponentgrupp från Biometrias standardkomponent". CostComponentCodeValue is a TextValue. The Biometria group of the quantity-based charge or deduction.		✓
SDCChargesAndAdjustmentsName	Deprecated, do not use. Instead use CostComponentDescription of CostComponentCode SDCChargesAndAdjustments.		✓

CostComponentCode	Usage	VIOL	
		2	3
SDCChargesAndAdjustmentsType	CostComponentDescription in Swedish is "Biometrias typning av T/A-komponenten". CostComponentCodeValue is a TextValue. The Biometria type classification of the quantity-based charge or deduction.		✓
SDCChargesAndAdjustmntsVersion	CostComponentDescription in Swedish is "Version på T/A-komponenten". CostComponentCodeValue is a TextValue. The version of a quantity-based charge or deduction.		✓
SDCLOGISTICS	The charged cost relates to logistics and can be calculated by Biometria. The CostComponentCodeValue is a logistics charge code (TA-kod) explained in Biometria reference document "Tillägg och avdrag i transportsystemet".	✓	
SDCLogisticsBasePriceCompGroup	CostComponentDescription in Swedish is "Biometrias grupp av grundpriskomponenter baserat på använd standardkomponent". CostComponentCodeValue is a TextValue. The Biometria group of the base price component for a logistics service.		✓
SDCLogisticsBasePriceCompName	Deprecated, do not use. Instead use CostComponentDescription of CostComponentCode SDCLogisticsBasePriceComponent.		✓
SDCLogisticsBasePriceComponent	ID of a base price component of a logistics service. It can be used by Biometria when calculating the cost of a logistics service. CostComponentCodeValue is a TextValue.		✓
SDCLogisticsBasePriceCompType	CostComponentDescription in Swedish is "Biometrias typning av grundpriskomponenten". CostComponentCodeValue is a TextValue. The Biometria type classification of the base price component for a logistics service.		✓

CostComponentCode	Usage	VIOL	
		2	3
SDCLogisticsBasePriceCompVersn	CostComponentDescription in Swedish is "Version av grundpriskomponenten". CostComponentCodeValue is a TextValue. The version of the base price component for a logistics service.		✓
SDCPRODUCT	The charged cost relates to the product and can be calculated by Biometria. The CostComponentCodeValue is a product charge code (textkod) detailed in Biometria reference document "Prislisteadministration Textkoder".	✓	
XMIXED	The charge is NOT calculated by Biometria. This is an external charge, where agency SDC provides a separate list of CostComponentCodeValues.	✓	

4.4.1 VIOL 2

Biometria has three reference documents with the valid CostComponentCodeValues and their CostComponentDescriptions. There is one reference document for each CostComponentCode of VIOL 2. The CostComponentCodeValue must be provided in element TextValue only.

4.4.2 VIOL 3

The valid CostComponentCodeValues for CostComponentCode SDCChargesAndAdjustments can be found in the VIOL 3 system itself as the ID of PRISKOMPONENT where Komponentform = "T/A". This is a dynamic code because additional CostComponentCodeValues will frequently be created by users of VIOL 3.

In the VIOL 3 system itself the valid CostComponentCodeValues for CostComponentCode SDCLogisticsBasePriceComponent may be found as the ID of an applicable PRISKOMPONENT. The selection criteria required to find valid base price components of logistics services in VIOL 3 have not yet been determined. It is a dynamic code because additional CostComponentCodeValues will frequently be created by users of VIOL 3.

Notice that every new price component in VIOL 3 is created as a copy of some existing template price component provided by Biometria (Swedish: standardkomponent) and the copy is then modified by the user. The CostComponentCodeValue of CostComponentCode BasedOnTemplatePriceComponent communicates the ID of the template price component that was used as template for creating the price component with CostComponentCode SDCChargesAndAdjustments identified with its ID in the CostComponentCodeValue.

The only valid CostComponentCodeValue for CostComponentCode RejectPriceBasedOnPopulation is 1 which means that the price of the rejected quantity is

based on a statistic population. The proper CostComponentDescription in Swedish is “Den vrakade kvantitetens pris kommer från kollektivet.”.

The valid CostComponentCodeValues for CostComponentCode AdditionalTrnsprtRelatedCharge can be found in the table below. The code value is the same value as in VIOL 3 term “Huvudkonto”.

CostComponentCodeValue (Huvudkonto in VIOL 3)	CostComponentDescription in Swedish
0001	Bomkörning
0002	Helgersättning
0003	Garantilassersättning
0004	Justering-Apris
0005	Lastning/lossning(truck o traktor)
0006	Lastning tåg biobränsle
0007	Lastning tåg rundvirke
0008	Lossning med egen kran
0009	Lunning
0010	Maskinflytt
0011	Nattersättning
0012	TMA bil
0013	Traktamente
0014	Transport
0015	Transport av utrustning
0016	Transport från importbåt/pråm
0017	Småposter
0018	Snöröjning
0019	Städning
0020	Vägunderhåll
0021	Väntetid
0022	Lastning separatlastare
0023	Flisningsarbete

4.5 CreditDebitNoteReasonCode

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “Unspecified” and “UNSPECIFIED” are the same.

SDC Code Value	ReasonDescription in language code ‘swe’	VIOL	
		2	3
NegativeInvoice	Kreditnota ty totalt fakturerat belopp är negativt	√	
Unspecified	Orsak ej specificerad	√	
WrongPrice	Fel pris i tidigare faktura	√	

4.6 DeliverySourceProperty

This element is used in VIOL 3 and not with VIOL 2.

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes "averageTreeAge" and "AverageTreeAge" are the same.

Code	CodeValue	CodeDescription in language code 'swe'	VIOL 3
AverageTreeAge	Numeric Value UOM="Year"	Genomsnittlig trädålder	√
CountryOfHarvest	TextValue	Landskod, enligt ISO 3166-1 alpha-2, där träden till produkten har avverkats	√
FirstReleaseOnEUMarket	Boolean Value	Sant om det är det första gången som produktens avverkade träd görs tillgängliga på EU:s inre marknad	√
LoggingForm	<TextValue>	Beskriver den avverkningsåtgärd som får utföras på avtalsobjektet	√
	AVVINSEKTS	Avverkning insektsskadat bestånd	
	AVVSKATR	Avverkning av skärmträd	
	AVVVINDF	Avverkning av vindfällan	
	FGALLR	Förstagallring	
	FinalFellg	<i>Deprecated. Do not use. Use code value SLUTAVV instead.</i>	
	FROTRST	Avverkning, ställande av fröträd	
	GALLR	Gallring	
	NATVAVV	Naturvårdsavverkning	
	SLUTAVV	Slutavverkning	
	Thinning	<i>Deprecated. Do not use. Use code value GALLR instead.</i>	
	OVRIGAVV	Övrig avverkning	
PriceListControlParameter	TextValue Max 10 char	Fri text för referens till parameter inom angiven prislista	√
RuleForQuantityConversionRatio	TextValue	Regelverk för omvandlingstal från något måttslag till m3f	√
	Nord	Regelverk för råvara från norra Sverige	
	Qbera	Regelverk för råvara från mellersta Sverige	
	Syd	Regelverk för råvara från södra Sverige	

Code	CodeValue	CodeDescription in language code 'swe'	VIOL 3
TypeOfLoggingCost	TextValue	Används för att hitta regel för en priskomponent för eventuellt avdrag mot säljaren baserat på produktionskostnad.	v
	A	Fast. I kontraktet med leverantören avtalad fast kostnad per enhet för drivning.	
	B	Rörlig. Kostnad baserad på entreprenörens fakturering. Kostnad kan vara baserad på olika enheter, tex timmar eller m3f.	
	C	Kostnadsprislista. Inköpsbolaget har en lista, vanligtvis med medelstam och skotningsavstånd som variabler, som bestämmer avverkningskostnaden för säljaren. Detta är inte den enskilda entreprenörens bortsättningsmall som avgör priset (dessa kan skilja från entreprenör till entreprenör) som det normalt är fallet vid rörlig produktionskostnad, utan en "normaliserad" lista.	
	D	Garantipris. En kombination av A och B där kostnaden är rörlig upp till en viss avtalad nivå, dvs ett tak för avverkningskostnaden gentemot säljaren.	

4.7 DiameterClassCode

4.7.1 VIOL 3

The valid values for agency SDC are displayed in the table below.

PropertyType	TextValue	Explanation	VIOL 3
DiameterClassCode	BreastHeight###	The three digits ### show the lowest allowed tree diameter in millimeters at breast height. Values valid for different breast height diameters: BreastHeight000 from 0 to 9 mm @ breast height, BreastHeight010 from 10 to 19 mm, BreastHeight020 from 20 to 29 mm, BreastHeight030 from 30 to 39 mm, and so on until BreastHeight090 from 90 to 99 mm, then BreastHeight100 from 100 to 119 mm, BreastHeight120 from 120 to 139 mm, BreastHeight140 from 140 to 159 mm, , and so on where each value is 20 mm higher than previous class code value until BreastHeight980 from 980 to 999 mm.	√

4.8 DocumentReferenceID

The papiNet XML schema formats the element DocumentReferenceID as S255, which permits a string of maximum 255 characters in XSD schema validation. However, the maximum allowed string length in reality depends on the DocumentReferenceIDType. The sub sections below show allowed field length for DocumentReferenceIDTypes used in integrations with Biometria is indicated for VIOL 3 and VIOL 2.

4.8.1 VIOL 2

Only the listed DocumentReferenceIDType may be used with attribute AssignedBy="ServiceProvider", where SDC is party Service Provider in the papiNet document. The format of the value of DocumentReferenceID is detailed in the table below.

DocumentReferenceIDType	Format in DocumentReferenceID string	VIOL 2
EnergyCalculationReferenceNumber	Max 4 numeric characters	√

The valid values for EnergyCalculationReferenceNumber can be found in the VIOL 2 client service "*Energiberäkningsregister*". For further details on specific values contact Biometria Customer Service.

4.8.2 VIOL 3

The valid values are displayed in the table below. In documents generated by the VIOL 3 system only the listed entries of DocumentReferenceIDType may be used with attribute AssignedBy="ServiceProvider", where Biometria is party Service Provider. The format of the

value of DocumentReferenceID is different depending on DocumentReferenceIDType as detailed in the table.

DocumentReferenceIDType	Format in DocumentReferenceID string	VIOL 3
BusinessChainNumber	S30 as in papiNet schema declaration	✓
CompensationCalculationID	Not yet determined	✓
CompensationChainNumber	S30 as in papiNet schema declaration	✓
ContractNumber	S30 as papiNet Business Rule FWS_CT_005	✓
DeliverySourceNumber	S60 as in papiNet schema declaration	✓
EnergyCalculationReferenceNumber	Not yet determined	✓
GoodsArrivalNumber	Not yet determined	✓
MeasuringInstructionNumber	S30 as papiNet Business Rule FWS_MI_004	✓
MeasuringNumber	S60 as in papiNet schema declaration	✓
PriceList	Minimum 6 and maximum 10 alphanumeric characters. Valid characters are capital A-Z and numerics 0-9. No special characters are allowed.	✓
ProductOriginIdentifier	Not yet determined	✓
ProductReferenceNumber	Not yet determined	✓
QuantityCalculationID	Not yet determined	✓
TransportArrivalNumber	Not yet determined	✓

4.9 DocumentRejectionReason

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “ReasonAsStatedByBusinessSystem” and “ReasonAsStatedByBUSINESSSystem” are the same.

Code	CodeValue (TextValue)	CodeDescription with language code 'swe'	VIOL 2	3
ReasonAsStatedByBusinessSystem	VIOL3	<i>The text in CodeDescription is the actual description produced by a business system within VIOL 3 as the document was rejected during processing of its content.</i> <i>The text will be different depending on what deviation or error occurred as the document was processed.</i>		✓

Code ReasonAsStatedByBusinessSystem is provided if there is no predefined DocumentRejectionReason for the reason this document was rejected, but instead there is a CodeDescription which is the description generated by the rejecting business system.

Biometria dynamically adds new DocumentRejectionReason codes as reasons are identified and classified.

4.10 DownGradingReasonCode

DownGradingReasonCode	Description in language code 'swe'	VIOL	
		2	3
0	Korrigerad vrakvolym	✓	
1	Fel trädslag/sortiment	✓	
2	Krök	✓	
3	Skogsröta	✓	✓
4	Diameter	✓	
5	Längd	✓	
6	Kvalitetsfel eller rötavdrag	✓	
7	Upparbetning	✓	
8	Föroreningar	✓	
9	Lagringsröta	✓	
10	Fel trädslag, torrstock		✓
11	Kvist, klyka, dimension		✓
12	Övergrovt		✓
13	Nedsmutsade stockar		✓
14	Främmande material		✓
15	Fel trädslag		✓

Refer to table “ORSAK TILL NEDKLASSNING (NK) OCH VRAKNING (VR) in “VIOL Koder”, for further details on codes for VIOL 2. There the meaning of CodeValue 6 is described further.

4.11 ErrorCode

The ErrorCode is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “SDC0003” and “sdc0003” are the same.

ErrorCode	ErrorSeverity	ErrorDescription in language code ‘swe’	VIOL	
			2	3
SDC0001	23_TECHNICAL_ERROR	Kunde inte bearbeta Leveransavisering	✓	
SDC0002	13_BUSINESS_CONTENT	Status måste vara "Original"	✓	
SDC0003	23_TECHNICAL_ERROR	Tekniskt fel.	✓	
SDC0004	22_DOC_NOT_VALID	Kunde inte tolka papiNet Envelope	✓	
SDC0005	22_DOC_NOT_VALID	Kunde inte tolka papiNet Dokument	✓	
SDC0006	13_BUSINESS_CONTENT	Refererat DeliveryMessage saknas	✓	
SDC0007	13_BUSINESS_CONTENT	<i>Texten i ErrorDescription är det faktiska felmeddelandet från VIOL 2. Det blir olika texter beroende på vilket fel som har inträffat i VIOL 2.</i>	✓	
SDC0008	23_TECHNICAL_ERROR	<i>To be deprecated, do not use</i>		
SDC0009	23_TECHNICAL_ERROR	<i>To be deprecated, do not use</i>		
SDC0010	13_BUSINESS_CONTENT	<i>To be deprecated, do not use</i>		
SDC0011	13_BUSINESS_CONTENT	<i>To be deprecated, do not use</i>		✓
SDC0012	13_BUSINESS_CONTENT	<i>Texten i ErrorDescription är det faktiska felmeddelandet från VIOL 3 då dokumentet presenterades. Det blir olika texter beroende på vilket fel som har inträffat i VIOL 3.</i>		✓
SDC0013	22_DOC_NOT_VALID	<i>To be deprecated, do not use</i>		✓
SDC0014	13_BUSINESS_CONTENT	<i>Texten i ErrorDescription är det faktiska felmeddelandet från ett system som inte tillhör Biometria. Det blir olika texter beroende på vilket fel som har inträffat i det systemet.</i>		✓
SDC0015	13_BUSINESS_CONTENT	Det dokument som BusinessAcceptance avser får inte bekräftas av den som utfärdat BusinessAcceptance.		✓

ErrorCode	ErrorSeverity	ErrorDescription in language code ‘eng’	VIOL	
			2	3
SDC0001	23_TECHNICAL_ERROR	Could not process Advance Shipment Notice	✓	
SDC0002	13_BUSINESS_CONTENT	Status must be "Original"	✓	
SDC0003	23_TECHNICAL_ERROR	Technical error.	✓	
SDC0004	22_DOC_NOT_VALID	Could not parse papiNet Envelope.	✓	
SDC0005	22_DOC_NOT_VALID	Could not parse papiNet Document.	✓	
SDC0006	13_BUSINESS_CONTENT	Referred DeliveryMessage is missing.	✓	
SDC0007	13_BUSINESS_CONTENT	<i>The text in ErrorDescription is the actual error description from VIOL 2. The text will be different depending on which error occurred in VIOL 2.</i>	✓	
SDC0008	23_TECHNICAL_ERROR	<i>To be deprecated, do not use</i>		
SDC0009	23_TECHNICAL_ERROR	<i>To be deprecated, do not use</i>		
SDC0010	13_BUSINESS_CONTENT	<i>To be deprecated, do not use</i>		
SDC0011	13_BUSINESS_CONTENT	<i>To be deprecated, do not use</i>		✓
SDC0012	13_BUSINESS_CONTENT	<i>The text in ErrorDescription is the actual error description from VIOL 3 as the document was presented. The text will be different depending on which error occurred in VIOL 3.</i>		✓

ErrorCode	ErrorSeverity	ErrorDescription in language code 'eng'	VIOL	
			2	3
SDC0013	22_DOC_NOT_VALID	<i>To be deprecated, do not use</i>		√
SDC0014	13_BUSINESS_CONTENT	<i>The text in ErrorDescription is the actual error description from a non-Biometria system. This text will be different depending on which error occurred in the system.</i>		√
SDC0015	13_BUSINESS_CONTENT	The document referred in the BusinessAcceptance may not be confirmed by the party issuing this BusinessAcceptance.		√

Biometria dynamically adds new error codes as new errors are encountered and classified.

4.12 LocationProperty

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes "SITE" and "Site" are the same.

Code	CodeValue	CodeDescription with language code 'swe'	VIOL	
			2	3
AverageTreeAge	NumericValue UOM="Year"	Genomsnittlig trädålder		√
AVVFORM	1-6 or empty	Avverkningsform	√	
LoggingForm	TextValue	Beskriver den avverkningsåtgärd som får utföras		
	AVVINSEKTS	Avverkning insektsskadat bestånd		√
	AVVSKATR	Avverkning av skärmtred		√
	AVVVINDF	Avverkning av vindfällan		√
	FGALLR	Förstagallring		√
	FinalFellg	<i>Deprecated. Do not use. Use code value SLUTAVV instead.</i>		√
	FROTRST	Avverkning, ställande av fröträd		√
	GALLR	Gallring		√
	NATVAVV	Naturvårdsavverkning		√
	OVRIGAVV	Övrig avverkning		√
	SLUTAVV	Slutavverkning		√
	Thinning	<i>Deprecated. Do not use. Use code value GALLR instead.</i>		√
RegistrationDistrict	TextValue with six digits	Platsens distriktskod		√
Site	TextValue with max 6 characters	Id på (Fysisk) plats/område för hantering av råvaruleverans		√
SiteName	TextValue	Namn på (Fysisk) plats/område för hantering av råvaruleverans		√

4.12.1 VIOL 2

Refer to table "AVVERKNINGSFORM" in "VIOL Koder", for details on Code AVVFORM.

4.12.2 VIOL 3

The registration district is the smallest geographical administrative subdivision for population registration (Swedish: *distrikt*). The valid values of code RegistrationDistrict for locations in Sweden are defined by Lantmäteriet – the Swedish National Land Survey.

4.13 MeasuringCodeInfo with Agency=SDC

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “MottKtrl” and “mottktrl” are the same.

MeasuringCodeType	Code	Code Value	CodeDescription	VIOL	
				2	3
MeasuringLocationType	MPLTYP	1-9	Mätplatstyp	√	
MeasuringMethodService	ang_brutto	N/A	Entered gross volume including sum of net quantity, deducted quantity and quality rejects.		√
	AVVBESTP		Period when AVVBESTT will be active. 1 position.	√	
	AVVBESTT		Instruction for deviation from standard output report in contract. 1 position.	√	
	bildtag	N/A	Take picture(s)		√
	fraktionsb	N/A	Chip fraction analysis		√
	MeasuringMethodMayDeviate	N/A	MeasuringMethod of measuring instruction and MeasuringTicket may be different than in the Contract		√
	MM	1-9, T	Mätmetod	√	
	MMA	1-9, T	Mätmetod för fas A	√	
	MMB	1-9, T	Mätmetod för fas B	√	
	MMC	1-9, T	Mätmetod för fas C	√	
	MMD	1-9, T	Mätmetod för fas D	√	
	mottktrl	N/A	Goods receipt check procedure		√
	provtag	N/A	Draw sample		√
	rekning	N/A	Count wood stacks		√

MeasuringCodeType	Code	Code Value	CodeDescription	VIOL	
				2	3
MeasuringMethodService (continued)	skattning	N/A	DO NOT USE. It is deprecated. Use ang_brutto instead.		✓
	skeppm	N/A	Measure loose volume products in container		✓
	stockm	N/A	Properties and measurements of individual logs		✓
	torrhaltsb	N/A	Bone dry ratio analysis		✓
	travm	N/A	Properties and measurements of individual stacks		✓
	vegning	N/A	Measure weight		✓
MeasuringPurpose	MS	1	Mätsyfte: Vederlagsmätning	✓	
		2	Mätsyfte: Ommätning	✓	
		3	Mätsyfte: Intern lagermätning	✓	
		4	Mätsyfte: Mätning av stickprovsenhet	✓	
		5	Mätsyfte: Ankomstmätning	✓	
		6	Mätsyfte: Begärd kontroll	✓	
		7	Mätsyfte: Funktionskontroll	✓	
		8	Mätsyfte: Kompetenskontroll	✓	
		9	Mätsyfte: Uppföljning av mätning	✓	
		S2	Mätsyfte: Skotarmätning	✓	
		S3	Mätsyfte: Skördarmätning sortimentsfördelad	✓	
		S6	Mätsyfte: Skördarmätning stamfördelad	✓	

MeasuringCodeType	Code	Code Value	CodeDescription	VIOL	
				2	3
MeasuringPurpose (continued)	MS	T	Mätsyfte: Transportsedel	√	
MeasuringRegulation	METNB_VO		Measuring regulations according to measuring agency. 6 positions.	√	
	REDOVKOST	K	Buyer responsible for the accounting cost.	√	
		S	Seller responsible for the accounting cost.	√	
MeasuringReportType	FORETOA		Period for Measuring Result ordered by FORETOT.	√	
	FORETOT		Type of Measuring Result ordered.	√	
	METNTYP		Mätningstyp	√	
MeasuringScope	MO	0-9	Mätningens omfattning	√	
	CoveredByVML	No	Påverkas ej av svensk virkesmätningsslag		√
		Yes	Omfattas av svensk virkesmätningsslag		√
	LogMeasuringRequired	No	Stockmätning krävs inte		√
		Yes	Stockmätning krävs		√
	QualityClassification	N/A	The product must be classified according to quality.		√
		No	Deprecated. Do not use.		
		Yes	Deprecated. Do not use.		
	VML	J	Omfattas av svensk virkesmätningsslag	√	
		N	Påverkas ej av svensk virkesmätningsslag	√	
Other	Not yet supported by Biometria				
PopulationScope	KOLLFAS		Kollektivfas	√	

MeasuringCodeType	Code	Code Value	CodeDescription	VIOL	
				2	3
PopulationScope (continued)	KOLLTYP		Kollektivtyp	√	
	MARK_2FAS		Markering 2-fas-kollektiv	√	
	OMRTAL_ENERGI_ST1	Numeric Value UOM="None"	Omräkningstal för volym till energiinnehåll steg 1		√
	OMRTAL_ENERGI_ST2	Numeric Value UOM="None"	Omräkningstal för volym till energiinnehåll steg 2		√
	OMRTAL_PRISKORR_ST1	Numeric Value UOM="None"	Priskorrektion omräkningstal steg 1		√
	OMRTAL_PRISKORR_ST2	Numeric Value UOM="None"	Priskorrektion omräkningstal steg 2		√
	OMRTAL_TORRHALT_ST1	Numeric Value UOM="None"	Omräkningstal för torrhalt steg 1		√
	OMRTAL_TORRHALT_ST2	Numeric Value UOM="None"	Omräkningstal för torrhalt steg 2		√
	OMRTALB_ST1	Numeric Value UOM="None"	Brutto omräkningstal steg 1	√	√
	OMRTALB_ST2	Numeric Value UOM="None"	Brutto omräkningstal steg 2	√	√
	OMRTALN_ST1	Numeric Value UOM="None"	Netto omräkningstal steg 1	√	√
	OMRTALN_ST2	Numeric Value UOM="None"	Netto omräkningstal steg 2	√	√

MeasuringCodeType	Code	Code Value	CodeDescription	VIOL	
				2	3
PopulationScope (continued)	PopulationVariant	TextValue	Variant av virkeskollektiv för olika affärsbehov		✓
		1	Rundved med möjlighet till pris från kollektiv		✓
		2	Rundved utan möjlighet till pris från kollektiv		✓
		3	Rundved, endast bruttoomräknad kvantitet		✓
		4	Rundved, begränsade populationer		✓
		5	Sönderdelat, torrhalts- och fraktionsbestämning		✓
		6	Sönderdelat, begränsade populationer med torrhalts- och fraktionsbestämning		✓
		7	Sönderdelat, skäppmätning och fraktionsbestämning		✓
		8	Sönderdelat, torrhaltsbestämning		✓
		9	Sönderdelat, torrhaltsbestämning och energiberäkning		✓
		10	Sönderdelat, räkning med torrhalts- och fraktionsbestämning		✓
	TimeSeriesEndDate	TextValue formatted yyyyymmdd	The last calendar date of the applied time period being a sub period of the entire timespan of the statistical population.		✓
	TimeSeriesStartDate	TextValue formatted yyyyymmdd	The oldest calendar date in the applied time period being a sub period of the entire timespan of the statistical population.		✓

4.13.1 VIOL 2

Refer to table “MÄTPLATS- OCH MOTTAGNINGSPLATSTYPER” in “VIOL Koder”, for further details on MeasuringLocationType.

Refer to table “MÄTMETODER” in “VIOL Koder”, for further details on code values for MeasuringMethodService. Codes MMA, MMB, MMC and MMD will be deprecated in VIOL 3.

Refer to table “MÄTSYFTE” in “VIOL Koder”, for further details on MeasuringPurpose. Codes of this document starting with a capital “S” refers to the right column in that table.

Refer to table “MÄTNINGSOMFATTNING” in “VIOL Koder”, for further details on MeasuringScope.

Refer to section 3.5.11.4 “METNTYP” in “FU Handbok Följdrutingutgångar” for further details on MeasuringReportType.

4.13.2 VIOL 3

In VIOL 3 a statistic population comprise a data set with many measurements within a long time period. The time period is divided into one or several sub periods, each one having a start date and an end date. Codes TimeSeriesStartDate and TimeSeriesEndDate are formatted as a calendar date yyyyymmdd in the local time zone of Sweden, e.g 20330630.

4.14 MeasuringEquipmentCode

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “sOftware” and “Software” are the same.

Code	CodeValue	Explanation	VIOL	
			2	3
CompensationMeasuringApprovalStatus	Approved	Status code indicating if the forest harvester machine is approved for compensation measuring		√
	FailedApproval			
	NotYetDetermined			
FileTransferApplication	TextValue	Name of application used for file transfer from the forest machine computer.		√
FileTransferApplicationVersion	TextValue	Version of the application used for file transfer from the forest machine computer.		√
HarvesterMachineHead	N/A	Indicates that element MeasuringEquipment refers to the machine head of a forest harvester		√
HarvesterOperatingSystem	TextValue	Operating system of the forest harvester computer		√
MeasuringAccuracyAsAudited	Approved	Measuring accuracy of the measuring equipment determined by the auditor, where value ApprovedWithDistinction expresses best accuracy.		√
	ApprovedWithDistinction			
	FailedApproval			
	NotYetDetermined			
Software	N/A	Styrsystemsversion i skogsmaskin	√	
StanForDApplicationVersion	TextValue	Name of control system in the forest machine and its version		√
StemCoordinateRecordedAt	CraneTip	As the stem is cut, the MapCoordinates have been recorded as either the crane tip position or as a machine position. The code value indicates whether the recorded coordinates refer to the position of the crane tip or the machine chassis.		√
	OperatorCabin			

Code CompensationMeasuringApprovalStatus has MeasuringEquipmentDescription = ”Maskinens godkännande för ersättningsgrundande skördarmätning” in Swedish.

Code MeasuringAccuracyAsAudited has MeasuringEquipmentDescription = ”Maskinens mätnoggrannhet administrerad av maskinrevisorn” in Swedish.

In VIOL 2 the software version is provided in element MeasuringEquipment/MeasurementSystem, if Code is Software.

4.15 Attribute MeasuringMethod, valid with MeasuringAgency=SDC

Measuring Method	Explanation	VIOL	
		2	3
M3CONT	Deprecated, do not use.		√
M3F	Solid wood volume is determined by any means.		√
M3FPB		√	
M3FUB		√	
M3MI	Deprecated, do not use.		√
M3MIPB		√	
M3MIUB		√	
M3S	Loose item volume is determined by any means.	√	√
M3SK		√	
M3SLICE	Deprecated, do not use.		√
M3STACK	Deprecated, do not use.		√
M3T		√	
M3TO	Individual log volume calculated using measurement(s) at its narrow end		√
M3TOUB		√	
M3TPB		√	
M3TR	Deprecated, do not use.		√
M3TRPB		√	
M3TRUB		√	
M3TUB		√	
M3TVOLT		√	
MIN	Duration in minutes		√
MWH	Energy content determination	√	√
OnBark	The property is measured including the bark.	√	√
ST	Number of items or packages are counted and is hence always an integer.		√
STYCK		√	
TIM		√	
TOInOut	Deprecated, do not use.		√
TOLoaded	Deprecated, do not use.		√
TON	Weight is determined by any means.	√	√
TTV	Product dry weight calculation using weight and dry substance ratio.	√	√
UnderBark	The property is measured excluding the bark.	√	√

N.B. These values of MeasuringMethod are NOT case sensitive, hence a sender can enter each character in either lower or UPPER case for human readability purpose or other purpose. The receiver must be able to convert the code value to the case used in its own system, i.e. code values MWh, MWH and mwh must be treated as equal by the receiver.

MeasuringMethod values OnBark and UnderBark may only be used in connection with papiNet element PropertyType.

4.15.1 VIOL 2

The table below shows how to determine which MeasuringMethod to use for different values of VIOL 2 code Måttslagskod. If there is no table entry in MeasuringMethod, it must be omitted.

Description	Måttslagskod	Måttslag	UOM	QuantityType	MeasuringMethod	VIOL 2
Hours	02	TIM	Hour	Time	TIM	✓
Days	03	DAG	Day	Time		✓
Standing volume	10	M3SK	CubicMeter	Volume	M3SK	✓
Solid volume by top-butt-measurement on bark	11	M3TRPB	CubicMeter	WoodVolume	M3TRPB	✓
Cubic meter	13	M3	CubicMeter	Volume		✓
Solid volume by top-butt-measurement under bark	15	M3TRUB	CubicMeter	SolidWoodVolume	M3TRUB	✓
Hectare	17	HA	Hectare	Area		✓
Kilometer	19	KM	Kilometer	Distance		✓
Swedish mile	20	MIL	TenKilometer	Distance		✓
Volume by mid-point measurement on bark	21	M3MIPB	CubicMeter	WoodVolume	M3MIPB	✓
Volume by mid-point measurement under bark	25	M3MIUB	CubicMeter	SolidWoodVolume	M3MIUB	✓
Volume by top measurement on bark	31	M3TPB	CubicMeter	WoodVolume	M3TPB	✓
Volume by top measurement under bark	35	M3TOUB	CubicMeter	SolidWoodVolume	M3TOUB	✓
Logpile volume on bark	41	M3T	CubicMeter	LogPileVolume	M3T	✓
Logpile volume under bark	45	M3T (under bark)	CubicMeter	LogPileVolume	M3TUB	✓
Solid Wood volume on bark	51	M3FPB	CubicMeter	WoodVolume	M3FPB	✓

Description	Måttslagskod	Måttslag	UOM	QuantityType	MeasuringMethod	VIOL 2
Solid Wood volume under bark	55	M3FUB	CubicMeter	SolidWoodVolume	M3FUB	✓
Loose volume	60	M3S	CubicMeter	TippedLooseVolume	M3S	✓
Product Weight	70	TON	MetricTon	NetNetWeight	TON	✓
Energy	73	MWh	MegaWattHour	Energy	MWH	✓
Count	80	Styck	Piece	Count	STYCK	✓
Product Dry Weight	90	TTV	MetricTon	BoneDry	TTV	✓

4.15.2 VIOL 3

The table below shows how to determine which QuantityType and UOM to use for different values of VIOL 3 field *Måttslagskod*.

<i>Måttslagskod</i>	Description	UOM	QuantityType	VIOL 3
m3f	Solid Wood volume	CubicMeter	SolidWoodVolume	✓
m3s	Loose volume	CubicMeter	TippedLooseVolume	✓
m3to	Volume by top measurement	CubicMeter	SolidWoodVolume	✓
min	Minutes	Minute	Time	✓
MWh	Energy	MegaWattHour	Energy	✓
St	Count	Piece	Count	✓
tim	Hours	Hour	Time	✓
ton	Product Weight	MetricTon	NetNetWeight	✓
ttv	Product Dry Weight	MetricTon	BoneDry	✓

4.16 MeasuringUnitIdentifier

SDC value	VIOL	
	2	3
7-character string	✓	✓

For forest harvester machines, the string begins with GPX and continues with four digits.
Example: GPX1234.

4.17 MonetaryAdjustmentComponent

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence codes “sdcADJUSTMENTS” and “SDCadjustments” are the same.

Code	Usage	VIOL	
		2	3
BasedOnTemplatePriceComponent	CodeValue is a TextValue. The TextValue is the ID of the Biometria template price component that was used as the parallel MonetaryAdjustmentComponent was created. The CodeDescription is the actual description associated with the CodeValue of this template price component. For additional usage details refer to the text below this table. (Swedish: standardkomponent)		v
ChargeAndAdjustmExtRefIssuerID	CodeDescription in Swedish is “Biometrias ID på ägare av T/A-priskomponent”. CodeValue is a TextValue formatted NNNNN-NNNN. The latter TextValue is the PartyIdentifier assigned by Biometria to the organisation that owns and manages the CodeValue provided in Code SDCChargesAndAdjustmentsExtRef of element MonetaryAdjustmentComponent. For proper identifiers refer to section PartyIdentifier assigned by agency SDC.		v
SDCChargesAndAdjustments	The CodeDescription is the actual description associated with the CodeValue of this Monetary adjustment component. CodeValue is a TextValue. The TextValue is the ID of a charge or deduction that is NOT based on quantity. The adjustment can be calculated by Biometria.		v

Code	Usage	VIOL	
		2	3
SDCChargesAndAdjustmentsExtRef	CodeDescription in Swedish is “Det ID som tilldelats T/A-priskomponenten av dess ägare”. The customers own reference to the monetary adjustment component. CodeValue is a TextValue. N.B. This code requires that Code ChargeAndAdjustmExtRefIssuerID is provided in the document too.		✓
SDCChargesAndAdjustmentsGroup	CodeDescription in Swedish is “Komponentgrupp från Biometrias standardkomponent”. The Biometria group of this monetary adjustment component. CodeValue is a TextValue.		✓
SDCChargesAndAdjustmentsName	Deprecated, do not use. Instead use CodeDescription of Code SDCChargesAndAdjustments.		✓
SDCChargesAndAdjustmentsType	CodeDescription in Swedish is “Biometrias typning av T/A-komponenten”. CodeValue is a TextValue. The Biometria type classification of the monetary adjustment component.		✓
SDCChargesAndAdjustmntsVersion	CodeDescription in Swedish is “Version på T/A-komponenten”. CodeValue is a TextValue. The version of the monetary adjustment component.		✓

The valid CodeValues for Code SDCChargesAndAdjustments can be found in the VIOL 3 system itself as all ID of PRISKOMPONENT where Komponentform = “T/A”.

Notice on code BasedOnTemplatePriceComponent: Every new price component in VIOL 3 is created as a copy of some existing template price component provided by Biometria (in Swedish: standardkomponent) and the copy may then be modified by the user. The CodeValue of the MonetaryAdjustmentComponent with Code BasedOnTemplatePriceComponent communicates the ID of the template price component that was used as template for creating the price component with Code SDCChargesAndAdjustments identified with its ID in the CodeValue.

4.18 PartyIdentifier

SDC PartyIdentifier value	VIOL	
	2	3
There are different sets of values for different PartyTypes.	v	v

4.18.1 VIOL 2

The following explains how to set the PartyIdentifier if the assigning Agency is SDC for PartyTypes Buyer, BuyerAgent, EndUser, Forwarder, LogisticsBuyer, LogisticsBuyerAgent, LogisticsSupplier, Seller and Supplier. It is formatted HUVUDKOD-INTERNKOD, which is an 11-digit string such as 88595-00123 or 00504-00000.

For PartyType PlaceFinalDestination it is a 5-digit string such as 39612.

For PartyType PlaceOfMeasuring it is a 6-digit string such as MST999.

For PartyType MeasuringParty it is in format VMF-INTNRVMF5, such as 99-9.

For PartyType Measurer it is in format VMF-INTNRVMF5-INTNR2VMF, such as 99-9-091.

For PartyType OriginalSupplier it is in format HKODS-INTNRS-INTNR2S-URSP-UPPDR.

A PartyIdentifier assigned by SDC is unique regardless of PartyType. If an e-document has two parties with different party types but with the same value of the PartyIdentifier assigned by SDC, it is the same party in different roles and it must have the same Name and Address. As an example, a party can occur as both Buyer and LogisticsBuyer in an e-document.

Please notice that the PartyIdentifier code value does NOT carry any structure in itself. The reader must NOT design their system so that there needs to be a logic in the identifier and decode different digits of the PartyIdentifier into different fields. The identifier value of a certain party might be different in VIOL 2 and VIOL 3 when it is assigned by agency SDC.

4.18.2 VIOL 3

4.18.2.1 PartyIdentifier assigned by agency SDC

N.B. PartyIdentifiers for living persons are defined in section 4.18.2.2.

Biometria assigns identifiers to organisations upon request. The following explains how to set the PartyIdentifier for organisations if the assigning Agency is SDC for PartyTypes Buyer, BuyerAgent, EndUser, Forwarder, LogisticsBuyer, LogisticsBuyerAgent, LogisticsSupplier, Seller and Supplier. It is an 11-digit string formatted xxxxx-yyyyy, where xxxxx is a positive integer with five digits depicting HUVUDKOD and yyyyy is a non-negative integer with five digits depicting INTNR. If an integer is less than 10000, then the substring has leading zeros making it a five digit substring. Examples of this 11-digit string are 88595-00123 and 00504-00000.

PartyIdentifier for party types Mill, PlaceFinalDestination, PlaceOfAccept, PlaceOfLoading, PlaceOfMeasuring, PlaceOfReloading, ShipTo and Terminal assigned by agency SDC has maximum 10 characters.

For any use of a PartyIdentifier where PartyIdentifierType="AssignedByAgency" and Agency="SDC", the identifier must be identical to the corresponding identifier of the party provided by Biometria as a distribution of parties using a papiNet e-document. See SDC Use Case G for further details.

4.18.2.2 PartyIdentifier for living persons

If a person has a *Swedish national identification number* (Swedish: personnummer) or a *Swedish co-ordination number* (Swedish: samordningsnummer), no PartyIdentifier is assigned by agency SDC, instead the PartyIdentifierType papiNetGlobalPartyIdentifier is used with following format: 1.3.6.1.4.1.29504.15.MC>NNNNNNNNNN, where MC is 19 or 20. MC is 19 if the person was born in the 20th century and 20 if the person was born in the 21st century.

NNNNNNNNNN is the Swedish national identification number or co-ordination number formatted to a ten digit string NNNNNNNNNN without any hyphen.

Please notice that proper Swedish national identification numbers and co-ordination numbers according to Swedish legislation (SFS 1991:481 § 18) have neither the century nor millennium digit of a year. 331122-9995 and 000216-9920 have proper format, but 19331122-9995 and 20000216-9920 are not correct. After a person with a Swedish national identification number is deceased, the identifier may later be reused for another person.

The format MC>NNNNNNNNNN is in compliance with amendment to (SFS 1991:481 § 18) as stipulated by Swedish law (2009:272).

Examples:

Co-ordination number 701083-9993 is identified

1.3.6.1.4.1.29504.15.197010839993

Personnummer 331122-9995 is identified 1.3.6.1.4.1.29504.15.193311229995

Personnummer 000216-9920 is identified 1.3.6.1.4.1.29504.15.200002169920

Personnummer 180101+9710 is identified 1.3.6.1.4.1.29504.15.191801019710

Currently the papiNet integrations at Biometria do not identify people that have no postal address in Sweden known to "Statens personadressregister SPAR". Hence, a supplier in an Original Contract can neither be a person without an address known to SPAR nor a deceased person.

4.19 ProductIdentifier

4.19.1 VIOL 2

SDC Code Value	VIOL 2
Code with three or four characters, detailed in tables 7, 8, 10 and 12 of "VIOL Koder".	✓

Refer to tables 7, 8, 10 and 12 in "VIOL Koder", for details. Please notice that there are no official Biometria values of ProductDescription. ProductIdentifierType must be ManufacturingGradeCode for "SDC inmätt sortiment" and products transported from the forest and GradeCode for "SDC fördelat sortiment".

4.19.2 VIOL 3

The valid values are displayed in the table below. Only these ProductIdentifierType can be used with Agency = "SDC". The actual values are yet to be defined but have the maximum field length shown below.

ProductIdentifierType	Value	VIOL 3
CatalogueNumber	Code with max 20 characters.	✓
GradeCode	Code with max 20 characters.	✓
ManufacturingGradeCode	Code with max 20 characters.	✓

In Biometria systems CatalogueNumber is used for Biometria term "Sortimentskategori", GradeCode is used for Biometria term "Produkt", ManufacturingGradeCode is used for Biometria term "Handelssortiment".

4.20 PropertyType

4.20.1 VIOL 2

SDC Code	Description in Swedish	VIOL 2	3
BarkClassCode	Barktyp	✓	
DateProduction	Avverkningsår & fällningsvecka	✓	
DiameterClassCode	Diameterklass	✓	
IsBioEnergyAdaptedHarvesting	GROTflisanpassad skördning	✓	
LoggingDamage	Avverkningskada	✓	
QualityClassCode	Inmätt kvalitet	✓	
TreeProcessingCategory	Bearbetningssätt vid skördning	✓	
TreeSpeciesGroupCode	Trädslagskod	✓	

4.20.2 VIOL 3

The valid values for properties that have text values provided by Biometria are displayed in the table below. Only these PropertyType with TextValue may be used with Agency="SDC" and MeasuringAgency = "SDC".

PropertyType	TextValue	Explanation	VIOL 3
BarkFunction	SG Skogforsk Gran		✓
	ST Skogforsk Tall		✓
	Z Zacco		✓
ButtEndProfileExtrapolationFunction	Poikela 2007		✓
DiameterClassCode		See separate section in this document	✓
QualityClassCode	0	Not classified. It is a composition of all valid quality grades for the product. (Swedish: Oklassat)	✓
	1	Grade 1 as defined in the Biometria instructions for timber measurement regarding saw logs.	✓
	2	Grade 2 as defined in the Biometria instructions for timber measurement regarding saw logs.	✓
	3	Grade 3 as defined in the Biometria instructions for timber measurement regarding saw logs.	✓
	4	Grade 4 as defined in the Biometria instructions for timber measurement	✓

PropertyType	TextValue	Explanation	VIOL 3
QualityClassCode (continued)		regarding saw logs.	
	8	Downgraded, which means the product does not fulfil the quality defined for the product, but is yet considered deliverable. (Swedish: Nedklassat)	✓
	9	Product must be considered as not deliverable. (Swedish: Vrak)	✓
	P	Grade P – Prima – is defined in the Biometria instructions for timber measurement regarding pulpwood.	✓
	S	Grade S – Sekunda – is defined in the Biometria instructions for timber measurement regarding pulpwood.	✓
	U	Grade U – Utskott – is defined in the Biometria instructions for timber measurement regarding pulpwood.	✓
TreeProcessingCategory	EB	Single tree processing	✓
	EF	Single tree felling	✓
	FB	Multi tree processing	✓
	FF	Multi tree felling	✓
TreeSpeciesGroupCode		See separate section in this document	✓

4.21 ResourceTypeCode

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “LoggingMachineGroup” and “loggingMACHinegroup” are the same.

Code	Description in Swedish (typically ResourceTypeDescription)	VIOL	
		2	3
CarrierResourceVIOL	VIOL:s resurstyp transportenhet inom ett utförande transportföretag. (Den används för önskemål om resurs i transportinstruktion och uppföljning av utförda transporter.)		√
Loader	Lastare	√	
LoadingResourceVIOL	VIOL:s resurstyp transportenhet inom ett lastande företag. (Den används för uppföljning av utförd lastning av transporter.)		√
LoggingMachineGroup	Maskinlag (grupp av maskiner som arbetar tillsammans)		√
Unloader	Lossare	√	

4.22 RoadClassificationCode

4.22.1 VIOL 2

RoadClassificationCode	VIOL	
	2	3
Code with four characters, detailed in table 24 of “VIOL Koder”.	√	

Refer to table “VÄGSTANDARD” in “VIOL Koder”, for details.

4.22.2 VIOL 3

The CodeValue is a TextValue unless otherwise indicated.

RoadClassificationCode	CodeValue	RoadClassificationDescription	VIOL 3
VehicleCombinationConstraint	1	Deprecated Do not use this CodeValue.	√
	2	Deprecated Do not use this CodeValue.	√
	3	Deprecated Do not use this CodeValue.	√
	4	Deprecated Do not use this CodeValue.	√

RoadClassificationCode	CodeValue	RoadClassificationDescription	VIOL 3
VehicleCombinationConstraint (continued)	BK1 (64 Ton)	BK1 (64 Ton)	✓
	BK2 (51,4 Ton)	BK2 (51,4 Ton)	✓
	BK3 (37 Ton)	BK3 (37 Ton)	✓
	BK4 (74 Ton)	BK4 (74 Ton)	✓
	Standard	Deprecated Do not use this CodeValue.	✓
	Standard (64 Ton)	Standard (64 Ton)	✓

VehicleCombinationConstraint is equivalent to the VIOL 3 term “Tygbil”. It is used as input parameter to the Biometria service “Krönt vägval” when requesting a distance using the National Forest Road database of Biometria. E.g CodeValue BK3 (37 Ton) implies that the vehicle or road train meets BK3 requirements of the Swedish Transport Administration agency and CodeValue Standard (64 Ton) implies that the vehicle or road train meets the Biometria requirements of a vehicle combination with loaded weight 64 tonnes.

N.B. The RoadClassificationCode for VIOL 3 is itself at least five characters in length.

4.23 RoadMaintenanceCodeInfo

SDC Code Value	VIOL 2 3	
Code with one digit, detailed in table 25 of “VIOL Koder”.	✓	

4.23.1 VIOL 2

Refer to table “SNÖ” in “VIOL Koder”, for details.

4.24 ShipmentIncidentCode

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “BusinessServiceREJECTIONreason” and “BusinessServiceRejectionReason” are the same.

Code	CodeValue (TextValue)	CodeDescription with language code 'swe'	VIOL	
			2	3
BusinessServiceRejectionReason	ATFE	Ansvarigt transportföretag felaktigt		√
	ATSA	Ansvarigt transportföretag saknas		√
	BISA	Befraktarinställning saknas		√
	BKSA	Befraktarkontrakt saknas		√
	EKSF	Ekipage saknas/felaktigt		√
	FTFE	Förmedlande transportföretag felaktigt		√
	FTSA	Förmedlande transportföretag saknas		√
	KPHS	Kvantitetsprioritering för handelssortimentet saknas		√
	LESA	Lastande enhet felaktig		√
	LFEE	Lastande företag felaktigt		√
	LFSA	Lastande företag saknas		√
	PKSA	Prioriterad kvantitet kan inte hittas för leveransen		√
	SAFE	Objekt felaktigt i stödregister		√
	SASA	Objekt saknas i stödregister		√
	TESF	Transportenhet saknas/felaktig		√
	TMSA	Tillåten maxvikt saknas		√
	TMSF	Transportmedel saknas/felaktigt		√
	TPAS	Transportprisgrundande avstånd saknas		√
	TUSA	Transportunderlag saknas		√
	UTFE	Utförande transportföretag felaktigt		√
	UTSA	Utförande transportföretag saknas		√

Code BusinessServiceRejectionReason is provided if Biometria cannot create a MeasuringTicket in the LogisticsService context due to that data is missing or incorrect. The CodeValue gives information on why the MeasuringTicket will not be created, due to that information is missing or inadequate.

4.25 SupplyPointCode is assigned by Agency=SDC

SDC Code	VIOL	
	2	3
The one digit string of AVLPL in VIOL 2. It is unique within the ShipToParty (MOTTPL). An example is 0.	√	
A string with maximum 10 characters.		√

4.25.1 VIOL 2

Both MOTTPL and AVLPL are fields of VIOL. The reader must be able to manage strings in format s60.

4.25.2 VIOL 3

The value of SupplyPointCode is unique within a location, but NOT within VIOL 3. Hence there may be two locations in different geographical areas far away from each other with the same value of their respective local supply points. A supply point code must be provided in a context with its superior location.

4.26 SupplyPointPropertyCode

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes "Deadendroad" and "DeadEndRoad" are the same.

The SupplyPointPropertyCodeValue is a TextValue unless explicitly stated otherwise in column CodeValue below. Only if attribute UOM is provided in the table, the CodeValue is a NumericValue.

SupplyPointPropertyCode	CodeValue (TextValue)	CodeDescription with language code 'swe'	VIOL	
			2	3
AccessRoadAccessibilityType		Typ av tillgänglighet för sträcka från avlägg till nationellt vägnät		√
	1	Lastbilstrafik hela året om		√
	2	Lastbilstrafik hela året utom vid svår tjällossning		√
	3	Lastbilstrafik hela året utom vid svår tjällossning och ihållande regnperioder		√
	4	Lastbilstrafik i huvudsak under vinterhalvåret.		√
AccessRoadAvailabilityType		Framkomlighetsklass för sträcka från avlägg till nationellt vägnät		√
	0	God framkomlighet för trailerekipage		√
	1	God framkomlighet för lastbil med släp		√
	2	Begränsad framkomlighet för lastbil med släp		√
	3	Endast framkomlig med lastbil		√
	4	Ej framkomlig för lastbil		√
AccessRoadBearingCapacityClass		Bärighetsklass för sträcka från avlägg till nationellt vägnät		√
	1	Max 64 tons bruttovikt		√

SupplyPointPropertyCode	CodeValue (TextValue)	CodeDescription with language code 'swe'	VIOL	
			2	3
AccessRoadBearingCapacityClass (continued)	2	Max 51,4 tons bruttovikt		√
	3	Max 37,5 tons bruttovikt		√
	4	Max 74 tons bruttovikt		√
AggravatedLoadingCondition		Deprecated. Do not use.		√
	0	Ingen uppgift om försvårad lastning Deprecated. Do not use.		
	1	Försvårad lastning pga svåra förhållanden vid hämtning Deprecated. Do not use.		√
	2	Försvårad lastning pga virke illa placerat Deprecated. Do not use.		√
	3	Försvårad lastning pga små partier Deprecated. Do not use.		√
	4	Försvårad lastning pga egen lastning med lånad truck Deprecated. Do not use.		√
		Deprecated. Do not use.		
BiometriaSupplyPointIntegerID	NumericValue UOM="None" An integer greater than 0.	Avläggets heltals-ID i Biometrias system. Det är unikt inom en <i>Location</i> .		√
DeadendRoad	1-2 or empty	Stickväg	√	
DeadEndRoadExist	Boolean	Sant om stickväg finns vid avlägget		√
DistanceLocationToSupplyPoint	NumericValue UOM="Kilometer"	Avstånd mellan mät- / mottagnings- / hämt- / omlastningsplats och lastplats		√
LoadTransferRequirementType		Typ av omlastning då detta är nödvändigt		√
	0	Ingen omlastning		
	1	Omlastning bil till släp - tillfälligt dåliga förhållanden		
	2	Omlastning bil till släp - bristfälliga förhållanden på hämtplats		
	3	Omlastning bil till släp - halvfullt släp		
	4	Begränsningar allmän väg		

SupplyPointPropertyCode	CodeValue (TextValue)	CodeDescription with language code 'swe'	VIOL	
			2	3
	5	Lunning till farbar väg		
Reloading	1-8 or empty	Omlastning	√	
RoadClass	TextValue with four characters.	Vägstandard	√	
SnowPlowingWillBePerformed	Boolean	Deprecated Do not use the code.		√
SnowRemoval	TextValue with one integer digit	Snöröjning	√	√
	1	Snöplogning regelbunden	√	√
	2	Snöplogning okänd	√	√

4.26.1 VIOL 2

For code Reloading refer to table “OMLASTNING” in “VIOL Koder”, for further details.

For code RoadClass refer to table “VÄGSTANDARD” in “VIOL Koder”, for details.

For code DeadendRoad refer to table “STICKVÄG” in “VIOL Koder”, for details.

For code SnowRemoval refer to table “SNÖ” in “VIOL Koder”, for details.

4.26.2 VIOL 3

Code BiometriaSupplyPointIntegerID may not be used for a SupplyPoint having LocationType=”ViaLocation”.

4.27 TransportInstructionCode

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “GoToMeasur” and “gotoMEASUR” are the same.

SDC Code	TransportInstructionText in Swedish	VIOL	
		2	3
GoToMeasur	Last skall mätas på mätplats	√	√
ScaleOut	Utvägning krävs	√	
VIAPKT	Ekipaget ska passera angiven plats	√	

4.28 TransportModeCode

SDC Code	Description in Swedish	@TransportModeType	VIOL	
			2	3
1	Bil eller traktor	Road	√	
2	Järnvägsvagn	Rail	√	
3	Båt	Sea	√	

SDC Code	Description in Swedish	@TransportModeType	VIOL	
			2	3
4	Flottning	Floating	✓	
5	Havsbogsering	Sea	✓	

4.28.1 VIOL 2

Notice that the table shows the proper value for attribute TransportModeType for each code. Refer to table “TRANSPORTMEDEL” in “VIOL Koder”, for further details.

4.29 TransportUnitCode

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “FirstTrailer” and “FIRSTtrailer” are the same.

SDC Code	Description	VIOL	
		2	3
FirstTrailer	The transport unit is the trailer that is closest to pulling truck.	✓	
SecondTrailer	The transport unit is the trailer that is second closest to pulling truck.	✓	

4.30 TransportUnitIdentifier

SDC TransportUnitIdentifier value		VIOL	
		2	3
Max 12 characters for ForestryForwarderUnits			✓

4.31 TransportUnloadingCode

Code	TransportUnloadingCodeDescription as AdditionalText in Swedish	Attribute TransportUnloadingType	VIOL	
			2	3
0	Ingen uppgift om försvårande lossning			✓
1	Lossning med egen kran, försvårande omständigheter	ByUnloadingCode		✓
2	Försvårad lossning med egen kran, delade lass	ByUnloadingCode		✓
3	Försvårad lossning med egen kran till järnväg	ByUnloadingCode		✓
4	Försvårad lossning med egen kran till mark	ByUnloadingCode		✓
5	Försvårad lossning vid stickprov	ByUnloadingCode		✓

4.31.1 VIOL 3

Notice that the TransportUnloadingCode is used to communicate an aggravating condition at unloading of a transport.

4.32 TransportVehicleCode

SDC Code	Biometria text description TransportVehicleText in language code 'swe'	VIOL	
		2	3
0	Gruppbil	✓	
1	Kranbil med kran	✓	
2	Kranbil utan kran	✓	
3	Flisbil	✓	
4	Containerbil	✓	
5	Grotbil/Träddelsbil	✓	
6	Separatlastare	✓	
7	Huggbil	✓	
9	Övrigt	✓	

4.32.1 VIOL 2

Refer to table “FORDONSKOMBINATION 1” in “VIOL Koder”, for further details. Value 8 is intentionally skipped.

4.33 TransportVehicleEquipmentCode

4.33.1 VIOL 2

Code	TransportVehicleEquipmentDescription in language code 'swe'	VIOL	
		2	3
0	<empty>	✓	
1	Fordonsdator	✓	
2	CTI	✓	
3	Kran	✓	
4	Lastväxlarekipage	✓	
5	Komprimeringsutrustning	✓	
6	Framkomlighetsutrustning	✓	

Refer to table “FORDONSKOMBINATION 1” in “VIOL Koder”, for further details.

4.33.2 VIOL 3

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “cRane” and “CRANE” are the same.

The CodeValue is alphanumeric and must use element TextValue and NOT BooleanValue, unless otherwise is indicated in the table.

Code	CodeValue	Explanation
CarrierResourceVIOL	TextValue	VIOL term “transportenhet” with CodeValue assigned by the Carrier.
FileTransferApplication	TextValue	Name of application used for file transfer from the transport vehicle.
FileTransferApplicationVersion	TextValue	Version of the application used for file

Code	CodeValue	Explanation
		transfer from the transport vehicle.
ForestForwarderOperatingSystem	TextValue	Operating system of the computer in the forest forwarder machine
SetOfVehiclesEquippedWithCrane	Yes (TextValue)	The set of vehicles is equipped with at least one crane
StanForDApplicationVersion	TextValue	Name of control system in the forest machine and its version

4.34 TransportVehicleIdentifier

SDC TransportVehicleIdentifier value	VIOL	
	2	3
7 characters	✓	
Max 12 characters for Forest Forwarders		✓

4.34.1 VIOL 2

It is the 7-digit value of VIOL 2 field INTNR2TRP and DORIS field TRANSP. The Biometria common name used by the business is “Transportör”. The usage of TRANSP is not harmonized and is used differently by different parties.

Please do not confuse the value assigned by SDC and the TransportVehicleIdentifier with attributes TransportVehicleIdentifierType=”LicencePlateNumber” and ISOCountryCode. The latter identifier value is obviously not assigned by SDC.

4.35 TreeSpeciesGroupCode

Code	TreeSpeciesGroupDescription in language code ‘eng’	TreeSpeciesGroupDescription in language code ‘swe’	VIOL	
			2	3
0	Conifers	Barrträd	✓	✓
1	Pine	Tall	✓	✓
2	Spruce	Gran	✓	✓
3	Eudicots	Lövträd	✓	✓
4	Birch	Björk	✓	✓
5	Aspen	Asp	✓	✓
6	Beech	Bok	✓	✓
7	Alder	Al	✓	✓
8	Oak	Ek	✓	✓
9	Conifers and eudicots	Barr- och lövträd	✓	✓
A	Larch	Lärk	✓	✓
B	Silver fir	Silvergran	✓	✓
C	White spruce	Vitgran	✓	
D	Elm	Alm	✓	
E	Ash	Ask	✓	✓
F	Linden	Lind	✓	
G	Maple	Lönn	✓	
H	Hornbeam	Vitbok	✓	
J	Douglas-fir	Douglasgran		✓
K	Northern red oak	Rödek	✓	✓
L	Sitka spruce	Sitkagran	✓	✓
M	Lodgepole pine	Pinus Contorta	✓	✓
N	Radiata pine	Pinus Radiata	✓	
P	Poplar	Poppel	✓	
R	Eucalyptus	Eucalyptus	✓	✓
S	Sallow	Sälg	✓	

Code	TreeSpeciesGroupDescription in language code 'eng'	TreeSpeciesGroupDescription in language code 'swe'	VIOL	
			2	3
T	Rowan/Swedish whitebeam	Rönn/Oxel	✓	✓
U	Bird cherry	Hägg/Fågelbär	✓	
V	Conifers of poor quality	Sekunda Barr	✓	
W	Hornbeam/Hazel	Avenbok/Hassel	✓	
X	Other	Övriga	✓	
Y	Caribbean pine	Pinus Caribea	✓	
Z	Willow	Pil	✓	

4.35.1 VIOL 2

Refer to table “TRÄDSLÄG” in document “VIOL Koder”, for further details on tree species.

4.36 VersionReason

The Code is NOT case sensitive, so the receiver must interpret UPPER and lower case characters as equal. Hence the codes “RNRGEN” and “RNRgen” are the same.

Code	CodeDescription in language code 'swe'	CodeValue	VIOL	
			2	3
IsMeasuringNumberCancelled	Makuleringsflagga för mätningen	TextValue with value Yes or No	✓	
KGEN	Kollektivgeneration VIOL 2	A NumericValue	✓	
KORRKOD	Korrigeringskod	A TextValue	✓	
PGEN	Is deprecated. Don't use, read note below! (earlier “Prisräkningsgeneration”)	A NumericValue	✓	
RNRGEN	Redovisningsgeneration VIOL 2	A NumericValue	✓	
TRSTATUS	Status för transportredovisning	A TextValue	✓	

4.36.1 VIOL 2

Where the CodeValue is a NumericValue with UOM=”None”, the DetailValue is an integer in the range 0 – 99. As Biometria reports a measuring event in VIOL 2, it always has a value in RNRGEN and KGEN at the MeasuringNumber level and PRISGEN at the product level. PGEN has only been applicable to the MeasuringTicket of type InvoiceSpecification, since that is the only MeasuringTicketType with monetary values.

Please notice that PGEN will be deprecated as VersionReason code. Instead use MeasuringTicketSequenceLineItem/AdditionalItemInfo with Code PGEN. The reason is that the “Prisräkningsgeneration” must not be included at the MeasuringTicketSequence level. Amounts are determined and calculated per Product, which is provided at level MeasuringTicketSequenceLineItem.

5 Mapping of papiNet enumeration values to Viol codes

There are currently no papiNet enumeration values that have been mapped to codes in Biometria system Viol.

papiNet EnumerationValue	Viol Code	Viol text

Future versions of this document may include such mappings.

6 Practical guidelines on some elements

Below some guidelines on how to set correct values for some selected elements.

6.1 MeasuringType attribute of element MeasuringSpecification

Attribute MeasuringType	Allowed with this VIOL value for "Mätmetoder"	VIOL description in Swedish	VIOL	
			2	3
ByItem	2	Stockmätning	✓	
ByLoad	5	Bedömning av volym och fastvolymprocent	✓	
	6	Bedömning av volym	✓	
	7	Vägning	✓	
ByPackage	3	Travmätning med bedömning av fastvolymprocent	✓	
	4	Travmätning (skäppmätning)	✓	
ByPackageAndItem	Enumeration value ByPackageAndItem is not used at Biometria	<N/A>	✓	
ByTransportUnit	5	Bedömning av volym och fastvolymprocent	✓	
	6	Bedömning av volym	✓	
	7	Vägning	✓	

6.1.1 VIOL 2

If the Biometria values for "Mätmetoder" in table 5 of "VIOL Koder" should be entered into a MeasuringTicket of type InvoiceSpecification, attribute MeasuringCodeType must be "MeasuringMethodService" and the mapping rules in the table above must be obeyed for element MeasuringSpecification. Codes for MeasuringMethodService are available in section 4.13 above.

6.2 Attributes of InformationalQuantity and Quantity

6.2.1 Attributes in documents with VIOL 2 data issued by Biometria

In documents DeliveryMessage and MeasuringTicket issued by Biometria with VIOL 2 data, the attributes AdjustmentType, MeasuringMethodType and QuantityTypeContext are assigned attribute values according to the criteria described below. Please be aware that these criteria will probably be different when Biometria issues the documents with VIOL 3 data.

The papiNet FWS&B business rule FWS_GE_015 must be obeyed for attribute QuantityType.

The papiNet FWS&B business rule FWS_MT_015 must be obeyed for element PackageMeasuringInfo.

6.2.1.1 Document MeasuringTicket with VIOL 2 data issued by Biometria

Value of KVANTKOD in VIOL 2	Is the value calculated considering measuring population statistics?	Is it a reduced quantity or a quantity with deductions? (mapped from field AVDRVOL or AVDRVOLSTOCK in VIOL 2)	QuantityTypeContext in papiNet document	Measuring-MethodType in papiNet document	AdjustmentType in papiNet document
I	No	No	Measured		(Attribute always skipped)
I	No	Yes	Measured		QualityRejectsAndDeductions
K	No	No	Measured		None
K	No	Yes	Measured		Reduction
O	No	No	Measured	ConvertedUOM	(Attribute always skipped)
O	No	Yes	Measured	ConvertedUOM	QualityRejectsAndDeductions
O	Yes	No	MeasuredCorrected	Calculated	(Attribute always skipped)
O	Yes	Yes	MeasuredCorrected	Calculated	QualityRejectsAndDeductions

If the Quantity is provided in MeasuringTicket type InvoiceSpecification, then the invoiced quantity (Swedish: prisräknad kvantitet) has attribute QuantityTypeContext = “Invoiced”.

The information below does not relate to quantities provided in MeasuringTicketSequence/PackageMeasuringInfo/ItemInfo/QuantityInformation, where attribute ItemType=”LogPile”. In this case attribute QuantityTypeContext is always Measured.

Please notice that “None” is a defined value for attribute AdjustmentType. Consider that the attribute values might be different when the data is provided by VIOL 3.

Notes on how to interpret the attribute MeasuringMethodType:

- The attribute is used in order to specify information about how the measurement value was created, as far as it is known by the issuing party.
- A specified attribute value indicates that Biometria will always provide the attribute in that way.
- Where no attribute value is specified in the table, the attribute might or might not be provided. When provided, the attribute value used is according to the best knowledge at the time.
- MeasuringMethodType should NOT be provided if the KVANTKOD value in VIOL 2 is O and it is unknown to the issuing party whether the InformationalQuantity value has been created considering measuring population statistics or not.
- MeasuringMethodType should NOT be provided if the KVANTKOD value in VIOL 2 is K and it is unknown to the issuing party whether the InformationalQuantity value is created considering measuring population statistics or not. In this case the QuantityTypeContext is Measured.

6.2.1.2 Document DeliveryMessage with VIOL 2 data issued by Biometria

KVANTKOD in VIOL 2	Måttslagskod in VIOL 2	QuantityType in papiNet document	MeasuringMethodType in papiNet document	AdjustmentType in papiNet document
I	70	NetNetWeight		N/A
I	55	SolidWoodVolume	ConvertedUOM* or VisualEstimated	N/A
O	55	SolidWoodVolume	ConvertedUOM	N/A
K	70	NetNetWeight		None
N/A†	70	NetNetWeight		N/A

* If the QuantityType NetNetWeight is provided in a ShipmentAdvice, then the MeasuringMethodType=ConvertedUOM of the Quantity with QuantityType=SolidWoodVolume.

† The data of this row is provided in element InformationalQuantity only.

Forest forwarders report data to Biometria. The data is then processed by VIOL 2 at Biometria. Data from the forest forwarder report are distributed with papiNet document DeliveryMessage issued by Biometria.

In this DeliveryMessage attribute QuantityTypeContext is Delivered and attribute AdjustmentType is always skipped unless the KVANTKOD=K in VIOL 2.

KVANTKOD I is provided in Quantity and KVANTKOD K and O are provided in InformationalQuantity.

For Quantity and InformationalQuantity with QuantityType=SolidWoodVolume, the attribute value of attribute MeasuringMethodType is set depending on whether there is any Quantity or InformationalQuantity with QuantityType=NetNetWeight.

The reason is that if the forest forwarder has reported the NetNetWeight to Biometria, then the NetNetWeight has been converted into SolidWoodVolume by the forest forwarder computer. Otherwise the SolidWoodVolume has been visually estimated.

Notes on how to interpret the attribute MeasuringMethodType:

- The attribute is used in order to specify information about how the measurement value was created, as far as it is known by the issuing party.
- A specified attribute value indicates that Biometria will always provide the attribute in that way.
- Where no attribute value is specified in the table, the attribute might or might not be provided. When provided, the attribute value used is according to the best knowledge at the time.

6.2.2 Attributes in documents with VIOL 3 data issued by Biometria

In documents DeliveryMessage and MeasuringTicket issued by Biometria with VIOL 3 data, the attributes AdjustmentType, MeasuringMethodType and QuantityTypeContext are assigned attribute values according to the criteria described below. Please be aware that these criteria are **different** than in the documents Biometria issues with VIOL 2 data.

The papiNet FWS&B business rule FWS_GE_015 must be obeyed for attribute QuantityType.

The papiNet FWS&B business rule FWS_MT_015 must be obeyed for element PackageMeasuringInfo.

6.2.2.1 Document MeasuringTicket of type ArrivalTicket in context Product with VIOL 3 data issued by Biometria

In MeasuringTicket documents of type ArrivalTicket with MeasuringTicketContextType = “Product” that Biometria issues with VIOL 3 data, the attributes AdjustmentType, MeasuringMethod, MeasuringMethodType, QuantityType, QuantityTypeContext and UOM in Quantity and InformationalQuantity are assigned attribute values according to the criteria described below. If the table column AdjustmentType has no value, this attribute should typically not be included in the MeasuringTicket. However it would be set to “None” if AdjustmentType is a required attribute in an Integration Subset Specification (ISS).

In particular notice that ONLY if “Kvantitetstyp” is *Brutto* in the VIOL 3 system the related quantity can be provided in the MeasuringTicket. Consider that the attribute values might be different when the data is provided by VIOL 3 compared to VIOL 2.

Notice that a specific combination [*Kvantitetstyp*, *Måttslag*, *Måttslagsmetod*] in VIOL 3 may have a different set of attribute values in the Product context than in the LogisticsService context. Please notice that “None” is a defined value for attribute AdjustmentType.

If the value of VIOL 3 field *Mätmetod* is “mottktrl”, then this table shows how to appropriately set attributes MeasuringMethod, MeasuringMethodType, QuantityType, QuantityTypeContext and UOM.

Value of Kvantitetstyp in VIOL 3	Value of Måttslag in VIOL 3	Value of Måttslagsmetod in VIOL 3	QuantityType in papiNet document	QuantityTypeContext in papiNet document	MeasuringMethodType in papiNet document	Measuring Method	UOM
Brutto	m3f	visuell	SolidWoodVolume	Rejected	VisualEstimated	M3F	CubicMeter
Brutto	m3s	visuell	TippedLooseVolume	Rejected	VisualEstimated	M3S	CubicMeter

If the value of VIOL 3 field *Mätmetod* is NOT “mottktrl”, then the table below shows how to appropriately set attributes MeasuringMethod, MeasuringMethodType, QuantityType, QuantityTypeContext and UOM. Attribute AdjustmentType should not be used, unless it is required in an Integrations Subset Specification. In such case it should be set to “None”.

Value of Kvantitetstyp in VIOL 3	Value of Måttslag in VIOL 3	Value of Måttslagsmetod in VIOL 3	QuantityType in papiNet document	QuantityTypeContext in papiNet document	MeasuringMethodType in papiNet document	Measuring Method	UOM
Brutto	m3f	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated	M3F	CubicMeter
Brutto	m3f	omvandling	SolidWoodVolume	Measured	ConvertedUOM	M3F	CubicMeter
Brutto	m3f	stock_mitt	SolidWoodVolume	Measured		M3F	CubicMeter
Brutto	m3f	stock_sekt	SolidWoodVolume	Measured		M3F	CubicMeter
Brutto	m3f	stock_tr	SolidWoodVolume	Measured		M3F	CubicMeter
Brutto	m3f	travm	SolidWoodVolume	Measured	Calculated	M3F	CubicMeter
Brutto	m3f	travm_auto	SolidWoodVolume	Measured	Automatic	M3F	CubicMeter
Brutto	m3f	visuell	SolidWoodVolume	Measured	VisualEstimated	M3F	CubicMeter
Brutto	m3s	skeppm	TippedLooseVolume	Measured		M3S	CubicMeter
Brutto	m3s	visuell	TippedLooseVolume	Measured	VisualEstimated	M3S	CubicMeter
Brutto	m3to	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated	M3TO	CubicMeter
Brutto	m3to	stock_topp	SolidWoodVolume	Measured		M3TO	CubicMeter
Brutto	MWh	energiber	Energy	Measured	ConvertedUOM	MWH	MegaWattHour
Brutto	MWh	kollomr	Energy	MeasuredCorrected	Calculated	MWH	MegaWattHour
Brutto	St	kollomr	Count	MeasuredCorrected	Calculated	ST	Piece
Brutto	St	rekning	Count	Measured		ST	Piece
Brutto	ton	vegning	NetNetWeight	Measured		TON	MetricTon
Brutto	Ttv	kollomr	BoneDry	MeasuredCorrected	Calculated	TTV	MetricTon
Brutto	Ttv	torrhalt	BoneDry	Measured		TTV	MetricTon

Notes on how to interpret the attribute MeasuringMethodType:

- The attribute is used in order to specify information about how the measurement value was created, as far as it is known by the issuing party.
- A specified attribute value indicates that Biometria will always provide the attribute in that way.
- Where no attribute value is specified in the table, the attribute might or might not be provided. When provided, the attribute value used is according to the best knowledge at the time of issue.

6.2.2.2 Document MeasuringTicket of type MeasuringTicket in context Product with VIOL 3 data issued by Biometria

In MeasuringTicket documents of type MeasuringTicket with MeasuringTicketContextType = “Product” that Biometria issues with VIOL 3 data, the attributes AdjustmentType, MeasuringMethod, MeasuringMethodType, QuantityType, QuantityTypeContext and UOM in Quantity and InformationalQuantity are assigned attribute values according to the criteria described below. If the table column AdjustmentType has no value, this attribute should not be communicated in the MeasuringTicket. However it would be set to “None” if AdjustmentType is a required attribute in an Integration Subset Specification.

N.B. If “Kvantitetstyp” is *Brutto* in the VIOL 3 system, the quantity is sometimes not applicable to provide in a document. It depends on the criteria detailed in the table.

Value of Kvantitetstyp in VIOL 3	Value of Måttslag in VIOL 3	Value of Måttslagsmetod in VIOL 3	QuantityType in papiNet document	QuantityTypeContext in papiNet document	MeasuringMethodType in papiNet document	AdjustmentType in papiNet document	Measuring Method	UOM
Avdrag	m3f	omvandling	SolidWoodVolume	Measured	ConvertedUOM	Deduction	M3F	CubicMeter
Avdrag	m3f	stock_mitt	SolidWoodVolume	Measured		Deduction	M3F	CubicMeter
Avdrag	m3f	stock_sekt	SolidWoodVolume	Measured		Deduction	M3F	CubicMeter
Avdrag	m3f	stock_tr	SolidWoodVolume	Measured		Deduction	M3F	CubicMeter
Avdrag	m3to	stock_topp	SolidWoodVolume	Measured		Deduction	M3TO	CubicMeter
Brutto	m3f	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated	NetAndDeductions	M3F	CubicMeter
Brutto	m3f	omvandling	SolidWoodVolume	Measured	ConvertedUOM	NetAndDeductions	M3F	CubicMeter
Brutto	m3f	stock_mitt	SolidWoodVolume	Measured		NetAndDeductions	M3F	CubicMeter
Brutto	m3f	stock_sekt	SolidWoodVolume	Measured		NetAndDeductions	M3F	CubicMeter
Brutto	m3f	stock_tr	SolidWoodVolume	Measured		NetAndDeductions	M3F	CubicMeter
Brutto	m3f	travm	SolidWoodVolume	Measured	Calculated	NetAndDeductions	M3F	CubicMeter
Brutto	m3f	travm_auto	SolidWoodVolume	Measured	Automatic	NetAndDeductions	M3F	CubicMeter
Brutto	m3f	visuell	SolidWoodVolume	Measured	VisualEstimated	NetAndDeductions	M3F	CubicMeter
Brutto	m3s	skeppm	TippedLooseVolume	Measured		NetAndDeductions	M3S	CubicMeter
Brutto	m3s	visuell	TippedLooseVolume	Measured	VisualEstimated	NetAndDeductions	M3S	CubicMeter
Brutto	m3to	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated	NetAndDeductions	M3TO	CubicMeter
Brutto	m3to	stock_topp	SolidWoodVolume	Measured		NetAndDeductions	M3TO	CubicMeter
Brutto	MWh	energiber	Not applicable to provide					
Brutto	MWh	kollomr	Not applicable to provide					
Brutto	St	kollomr	Not applicable to provide					
Brutto	St	rekning	Not applicable to provide					
Brutto	ton	vegning	NetNetWeight	Measured		NetAndDeductions	TON	MetricTon
Brutto	Ttv	kollomr	Not applicable to provide					
Brutto	Ttv	torrhaltstb	Not applicable to provide					
Netto	m3f	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated		M3F	CubicMeter
Netto	m3f	omvandling	SolidWoodVolume	Measured	ConvertedUOM		M3F	CubicMeter
Netto	m3f	stock_mitt	SolidWoodVolume	Measured			M3F	CubicMeter
Netto	m3f	stock_sekt	SolidWoodVolume	Measured			M3F	CubicMeter
Netto	m3f	stock_tr	SolidWoodVolume	Measured			M3F	CubicMeter
Netto	m3f	travm	SolidWoodVolume	Measured	Calculated		M3F	CubicMeter
Netto	m3f	travm_auto	SolidWoodVolume	Measured	Automatic		M3F	CubicMeter
Netto	m3s	skeppm	TippedLooseVolume	Measured			M3S	CubicMeter
Netto	m3to	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated		M3TO	CubicMeter
Netto	m3to	stock_topp	SolidWoodVolume	Measured			M3TO	CubicMeter
Netto	MWh	energiber	Energy	Measured	ConvertedUOM		MWH	MegaWattHour
Netto	MWh	kollomr	Energy	MeasuredCorrected	Calculated		MWH	MegaWattHour
Netto	St	kollomr	Count	MeasuredCorrected	Calculated		ST	Piece
Netto	St	rekning	Count	Measured			ST	Piece
Netto	ton	vegning	NetNetWeight	Measured			TON	MetricTon
Netto	Ttv	kollomr	BoneDry	MeasuredCorrected	Calculated		TTV	MetricTon
Netto	Ttv	torrhaltstb	BoneDry	Measured			TTV	MetricTon
Vrak	m3f	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated		M3F	CubicMeter
Vrak	m3f	omvandling	SolidWoodVolume	Measured	ConvertedUOM		M3F	CubicMeter
Vrak	m3f	stock_mitt	SolidWoodVolume	Measured			M3F	CubicMeter
Vrak	m3f	stock_sekt	SolidWoodVolume	Measured			M3F	CubicMeter
Vrak	m3f	stock_tr	SolidWoodVolume	Measured			M3F	CubicMeter
Vrak	m3f	travm	SolidWoodVolume	Measured	Calculated		M3F	CubicMeter
Vrak	m3f	travm_auto	SolidWoodVolume	Measured	Automatic		M3F	CubicMeter
Vrak	m3s	skeppm	TippedLooseVolume	Measured			M3S	CubicMeter
Vrak	m3to	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated		M3TO	CubicMeter
Vrak	m3to	stock_topp	SolidWoodVolume	Measured			M3TO	CubicMeter
Vrak	MWh	energiber	Energy	Measured	ConvertedUOM		MWH	MegaWattHour
Vrak	MWh	kollomr	Energy	MeasuredCorrected	Calculated		MWH	MegaWattHour
Vrak	St	kollomr	Count	MeasuredCorrected	Calculated		ST	Piece
Vrak	St	rekning	Count	Measured			ST	Piece
Vrak	ton	vegning	NetNetWeight	Measured			TON	MetricTon
Vrak	Ttv	kollomr	BoneDry	MeasuredCorrected	Calculated		TTV	MetricTon
Vrak	Ttv	torrhaltstb	BoneDry	Measured			TTV	MetricTon

Notice that a specific combination [*Kvantitetstyp, Måttslag, Måttslagsmetod*] in VIOL 3 may have a different set of attribute values in the Product context than in the LogisticsService context.

The information below does not relate to quantities provided in MeasuringTicketSequence/PackageMeasuringInfo/ItemInfo/QuantityInformation, where attribute ItemType="LogPile". In this case attribute QuantityTypeContext is always Measured.

Please notice that "None" is a defined value for attribute AdjustmentType. Consider that the attribute values might be different when the data is provided by VIOL 3 compared to VIOL 2.

Notes on how to interpret the attribute MeasuringMethodType:

- The attribute is used in order to specify information about how the measurement value was created, as far as it is known by the issuing party.
- A specified attribute value indicates that Biometria will always provide the attribute in that way.
- Where no attribute value is specified in the table, the attribute might or might not be provided. When provided, the attribute value used is according to the best knowledge at the time of issue.

6.2.2.3 Document MeasuringTicket of type MeasuringTicket in context LogisticsService with VIOL 3 data issued by Biometria

In MeasuringTicket documents of type MeasuringTicket with MeasuringTicketContextType = “LogisticsService” that Biometria issues with VIOL 3 data, the attributes AdjustmentType, MeasuringMethod, MeasuringMethodType, QuantityType, QuantityTypeContext and UOM in Quantity and InformationalQuantity are assigned attribute values according to the criteria described below. If the table column AdjustmentType has no value, this attribute should not be communicated in the MeasuringTicket. However it would be set to “None” if AdjustmentType is a required attribute in an Integration Subset Specification. In particular notice that ONLY if “Kvantitetstyp” is *Brutto* in the VIOL 3 system the related quantity can be provided in the MeasuringTicket.

Notice that a specific combination [*Kvantitetstyp*, *Måttslag*, *Måttslagsmetod*] in VIOL 3 may have a different set of attribute values in the LogisticsService context than in the Product context.

Value of Kvantitetstyp in VIOL 3	Value of Måttslag in VIOL 3	Value of Måttslagsmetod in VIOL 3	QuantityType in papiNet document	QuantityTypeContext in papiNet document	MeasuringMethodType in papiNet document	AdjustmentType in papiNet document	Measuring Method	UOM
Brutto	m3f	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated		M3F	CubicMeter
Brutto	m3f	omvandling	SolidWoodVolume	Measured	ConvertedUOM		M3F	CubicMeter
Brutto	m3f	visuell	SolidWoodVolume	Measured	VisualEstimated		M3F	CubicMeter
Brutto	m3f	stock_mitt	SolidWoodVolume	Measured			M3F	CubicMeter
Brutto	m3f	stock_sekt	SolidWoodVolume	Measured			M3F	CubicMeter
Brutto	m3f	stock_tr	SolidWoodVolume	Measured			M3F	CubicMeter
Brutto	m3f	travm	SolidWoodVolume	Measured	Calculated		M3F	CubicMeter
Brutto	m3f	travm_auto	SolidWoodVolume	Measured	Automatic		M3F	CubicMeter
Brutto	m3s	visuell	TippedLooseVolume	Measured	VisualEstimated		M3S	CubicMeter
Brutto	m3s	skeppm	TippedLooseVolume	Measured			M3S	CubicMeter
Brutto	m3to	kollomr	SolidWoodVolume	MeasuredCorrected	Calculated		M3TO	CubicMeter
Brutto	m3to	stock_topp	SolidWoodVolume	Measured			M3TO	CubicMeter
Brutto	MWh	energiber	Energy	Measured	ConvertedUOM		MWH	MegaWattHour
Brutto	MWh	kollomr	Not applicable to provide					
Brutto	St	kollomr	Count	MeasuredCorrected	Calculated		ST	Piece
Brutto	St	rekning	Count	Measured			ST	Piece
Brutto	ton	vegning	NetNetWeight	Measured			TON	MetricTon
Brutto	Ttv	kollomr	Not applicable to provide					
Brutto	Ttv	torrhaltsb	BoneDry	Measured			TTV	MetricTon

The information below does not relate to quantities provided in MeasuringTicketSequence/PackageMeasuringInfo/ItemInfo/QuantityInformation, where attribute ItemType=”LogPile”. In this case attribute QuantityTypeContext is always Measured.

Please notice that “None” is a defined value for attribute AdjustmentType. Consider that the attribute values might be different when the data is provided by VIOL 3 compared to VIOL 2.

Notes on how to interpret the attribute MeasuringMethodType:

- The attribute is used in order to specify information about how the measurement value was created, as far as it is known by the issuing party.
- A specified attribute value indicates that Biometria will always provide the attribute in that way.
- Where no attribute value is specified in the table, the attribute might or might not be provided. When provided, the attribute value used is according to the best knowledge at the time of issue.

6.2.2.4 Document MeasuringTicket of type InvoiceSpecification in context Product with VIOL 3 data issued by Biometria

In MeasuringTicket documents of type InvoiceSpecification with MeasuringTicketContextType = "Product" that Biometria issues with VIOL 3 data, the attributes AdjustmentType, MeasuringMethod, QuantityType and UOM in Quantity and InformationalQuantity are assigned attribute values according to the criteria in the table below. The MeasuringAgency is SDC if MeasuringMethod is provided.

In this MeasuringTicket the attribute MeasuringMethodType is not provided and attribute QuantityTypeContext has attribute value "Invoiced", except if attribute AdjustmentType="Excess".

Quantities with *Kvantitetstyp* "Brutto" in VIOL 3 are treated in two different ways depending on whether the quantity relates to the BaseNetAmount in a MeasuringTicketSequenceLineItem where the Product/ProductIdentifier/@ProductIdentifierType is ManufacturingGradeCode or the quantity relates to some other element.

If a quantity in VIOL 3 has the attribute *Kvantitetstyp*="Brutto" and the quantity is reported on MeasuringTicketSequenceLineItem/QuantityInformation/Quantity in a MeasuringTicketSequenceLineItem where the Product/ProductIdentifier/@ProductIdentifierType is ManufacturingGradeCode then the following table should be used to appropriately set the attributes QuantityType, MeasuringMethod and UOM depending on the value of *Måttslag* in VIOL 3. In this case attribute AdjustmentType is not provided since there is no adjustment.

Value of Måttslag in VIOL 3	ProductIdentifierType in MeasuringTicketSequenceLineItem/Product/ProductIdentifier	QuantityType in papiNet document	Measuring Method	UOM
m3f	ManufacturingGradeCode	SolidWoodVolume	M3F	CubicMeter
m3s	ManufacturingGradeCode	TippedLooseVolume	M3S	CubicMeter
m3to	ManufacturingGradeCode	SolidWoodVolume	M3TO	CubicMeter
MWh	ManufacturingGradeCode	Energy	MWH	MegaWattHour
st	ManufacturingGradeCode	Count	ST	Piece
ton	ManufacturingGradeCode	NetNetWeight	TON	MetricTon
ttv	ManufacturingGradeCode	BoneDry	TTV	MetricTon

In all other cases the following table should be used to appropriately set the attributes QuantityType, AdjustmentType, MeasuringMethod and UOM depending on the value of *Kvantitetstyp* and *Måttslag* in VIOL 3.

Value of Kvantitetstyp in VIOL 3	Value of Måttslag in VIOL 3	QuantityType in papiNet document	AdjustmentType in papiNet document	Measuring Method	UOM
Avdrag	m3f	SolidWoodVolume	Deduction	M3F	CubicMeter
Avdrag	m3to	SolidWoodVolume	Deduction	M3TO	CubicMeter
Brutto	m3f	SolidWoodVolume	NetAndDeductions	M3F	CubicMeter
Brutto	m3s	TippedLooseVolume	NetAndDeductions	M3S	CubicMeter
Brutto	m3to	SolidWoodVolume	NetAndDeductions	M3TO	CubicMeter
Brutto	MWh	Energy	NetAndDeductions	MWH	MegaWattHour
Brutto	st	Count	NetAndDeductions	ST	Piece
Brutto	ton	NetNetWeight	NetAndDeductions	TON	MetricTon
Brutto	ttv	BoneDry	NetAndDeductions	TTV	MetricTon
Modul	m3f	SolidWoodVolume		M3F	CubicMeter
Modul	m3to	SolidWoodVolume		M3TO	CubicMeter
Netto	m3f	SolidWoodVolume	None or NetAndExcess, refer to text for explanation	M3F	CubicMeter
Netto	m3s	TippedLooseVolume		M3S	CubicMeter
Netto	m3to	SolidWoodVolume	None or NetAndExcess, refer to text for explanation	M3TO	CubicMeter
Netto	MWh	Energy		MWH	MegaWattHour
Netto	st	Count		ST	Piece
Netto	ton	NetNetWeight		TON	MetricTon
Netto	ttv	BoneDry		TTV	MetricTon
Vrak	m3f	SolidWoodVolume	QualityRejectsAndDeductions	M3F	CubicMeter
Vrak	m3s	TippedLooseVolume	QualityRejectsAndDeductions	M3S	CubicMeter
Vrak	m3to	SolidWoodVolume	QualityRejectsAndDeductions	M3TO	CubicMeter
Vrak	MWh	Energy	QualityRejectsAndDeductions	MWH	MegaWattHour
Vrak	st	Count	QualityRejectsAndDeductions	ST	Piece
Vrak	ton	NetNetWeight	QualityRejectsAndDeductions	TON	MetricTon
Vrak	ttv	BoneDry	QualityRejectsAndDeductions	TTV	MetricTon

If a volume has been calculated by VIOL 3 using the fixed scaling lengths of logs stipulated in the price list (*Kvantitetstyp* in VIOL 3: *Modul*), it may only be provided as Quantity (never InformationalQuantity) and in this case the *kvantitetstyp* “Netto” may only be provided in InformationalQuantity with AdjustmentType=“NetAndExcess”. In all other cases *kvantitetstyp* “Netto” is provided in Quantity without any AdjustmentType.

If there is a determined excess quantity in VIOL 3 (*Kvantitetstyp* in VIOL 3: *Övermå*) then this quantity is provided in InformationalQuantity with attribute AdjustmentType=“Excess”, QuantityTypeContext=“NotBillable” and the same attribute values of QuantityType, MeasuringAgency, MeasuringMethod and UOM as provided in Quantity (*Kvantitetstyp* in VIOL 3: *Modul*). Hence with VIOL 3 there can NEVER be financial compensation for an excess quantity.

If the table column AdjustmentType has no value or “None”, this attribute should typically not be communicated in the MeasuringTicket. However it would be set to “None” if AdjustmentType is a required attribute in an Integration Subset Specification.

If there is an InformationalQuantity with QuantityType=“Distance”, then it has UOM=“Kilometer”.

Consider that the attribute values might be different when the data is provided by VIOL 3 compared to VIOL 2.

6.2.2.5 Document MeasuringTicket of type InvoiceSpecification in context LogisticsService with VIOL 3 data issued by Biometria

In MeasuringTicket documents of type InvoiceSpecification with MeasuringTicketContextType = "LogisticsService" that Biometria issues with VIOL 3 data, the attributes MeasuringMethod, MeasuringMethodType, QuantityType, and UOM are assigned attribute values according to the criteria described in the table below. The MeasuringAgency is SDC if MeasuringMethod is provided. AdjustmentType is not provided as there are no adjustment quantities in the LogisticsService context.

There are cases where the quantity is expressed as an integer number of loads. In such case the QuantityType is Count, MeasuringMethodType is Automatic, UOM is Load, but there is no attribute MeasuringMethod. It may be provided where QuantityTypeContext is Transported as well as Invoiced.

N.B. The value in VIOL 3 field "Transporterad kvantitet" may be provided as a Quantity with QuantityTypeContext="Measured". The value in VIOL 3 field "Transportprisgrundande kvantitet" must be provided as Quantity with QuantityTypeContext="Invoiced".

Value of Måttslag in VIOL 3	Value of Måttslagsmetod in VIOL 3	QuantityType in papiNet document	MeasuringMethodType in papiNet document	Measuring Method	UOM
m3f	kollomr	SolidWoodVolume	Calculated	M3F	CubicMeter
m3f	metningsv	The lefthand combination is not allowed in this document.			
m3f	omvandling	SolidWoodVolume	ConvertedUOM	M3F	CubicMeter
m3f	stock_mitt	SolidWoodVolume		M3F	CubicMeter
m3f	stock_sekt	SolidWoodVolume		M3F	CubicMeter
m3f	stock_tr	SolidWoodVolume		M3F	CubicMeter
m3f	travm	SolidWoodVolume	Calculated	M3F	CubicMeter
m3f	travm_auto	SolidWoodVolume	Automatic	M3F	CubicMeter
m3f	visuell	SolidWoodVolume	VisualEstimated	M3F	CubicMeter
m3s	metningsv	The lefthand combination is not allowed in this document.			
m3s	skeppm	TippedLooseVolume		M3S	CubicMeter
m3s	visuell	TippedLooseVolume	VisualEstimated	M3S	CubicMeter
m3to	kollomr	SolidWoodVolume	Calculated	M3TO	CubicMeter
m3to	stock_topp	SolidWoodVolume		M3TO	CubicMeter
min	This value of "Måttslag" is not allowed in this document.				
MWh	energiber	Energy	ConvertedUOM	MWH	MegaWattHour
MWh	kollomr	Energy	Calculated	MWH	MegaWattHour
st	rekning	Count		ST	Piece
ton	fordelning	NetNetWeight	VisualEstimated	TON	MetricTon
ton	omvandling	NetNetWeight	ConvertedUOM	TON	MetricTon
ton	vegning	NetNetWeight		TON	MetricTon
ttv	kollomr	BoneDry	Calculated	TTV	MetricTon
ttv	torrhaltb	BoneDry		TTV	MetricTon

Consider that the attribute values might be different when the data is provided by VIOL 3 compared to VIOL 2.

Notes on how to interpret the attribute MeasuringMethodType:

- The attribute is used in order to specify information about how the measurement value was created, as far as it is known by the issuing party.
- A specified attribute value indicates that Biometria will always provide the attribute in that way.
- Where no attribute value is specified in the table, the attribute might or might not be provided. When provided, the attribute value used is according to the best knowledge at the time of issue.

6.2.2.6 Document MeasuringTicket of type ProductionTicket with VIOL 3 data issued by Biometria

In MeasuringTicket documents of type ProductionTicket that Biometria issues with VIOL 3 data, the attributes AdjustmentType, MeasuringMethod, MeasuringMethodType, QuantityType and UOM are assigned attribute values according to the field name in VIOL 3 as detailed in the table below. Notice that the element (Level) to use within a ProductionTicket varies with the field name, as indicated below in column Level.

Fieldname in VIOL 3	Level ItemMeasuringInfo, PackageMeasuringInfo or MeasuringTicketLineItem	QuantityType in papiNet document	MeasuringMethodType in papiNet document	AdjustmentType in papiNet document	Measuring Method	UOM
Antal stammar	PackageMeasuringInfo	Count	Automatic	N/A	ST	Piece
m ³ f stam mätt	PackageMeasuringInfo	SolidWoodVolume	Automatic	N/A	M3F	CubicMeter
m ³ f topp	PackageMeasuringInfo	SolidWoodVolume	Automatic	QualityRejectsAndDeductions	M3F	CubicMeter
Antal stammar	MeasuringTicketLineItem	Count	Automatic	N/A	ST	Piece
Antal stockar	MeasuringTicketLineItem	Count	Automatic	N/A	ST	Log
Energiinnehåll MWh	MeasuringTicketLineItem	Energy	Calculated	N/A	MWH	MegaWattHour
Ton råvikt	MeasuringTicketLineItem	NetNetWeight	Calculated	N/A	TON	MetricTon
Ton torrvikt	MeasuringTicketLineItem	BoneDry	Calculated	N/A	TON	MetricTon
Total m ³ f stam mätt	MeasuringTicketLineItem	SolidWoodVolume	Calculated	N/A	M3F	CubicMeter
Volym m ³ f omvandlad	MeasuringTicketLineItem	SolidWoodVolume	ConvertedUOM	N/A	M3F	CubicMeter
Volym m ³ s	MeasuringTicketLineItem	TippedLooseVolume	Calculated	N/A	M3S	CubicMeter
Antal stammar	ItemMeasuringInfo	Count	Automatic	N/A	ST	Piece
Volym m ³ to	ItemMeasuringInfo	SolidWoodVolume	Automatic	N/A	M3TO	CubicMeter
Volym m ³ f omvandlad	ItemMeasuringInfo	SolidWoodVolume	ConvertedUOM	N/A	M3F	CubicMeter

The QuantityTypeContext in the MeasuringTicket of type ProductionTicket will always be Measured. Notice that the second column shows possible elements for a Quantity or an InformationalQuantity.

Notes on how to interpret the attribute MeasuringMethodType:

- The attribute is used in order to specify information about how the measurement value was created, as far as it is known by the issuing party.
- A specified attribute value indicates that Biometria will provide the attribute in that way.
- Where no attribute value is specified in the table, the attribute might or might not be provided. When provided, the attribute value used is according to the best knowledge at the time. N/A is not a valid value, but indicates that the attribute will not be provided.

6.2.2.7 Document DeliveryMessage of type ShipmentAdvice with VIOL 3 data issued by Biometria

In DeliveryMessage documents of type ShipmentAdvice that Biometria issues with VIOL 3 data, the attributes MeasuringMethod, MeasuringMethodType and QuantityType are assigned attribute values according to the field name in VIOL 3 as detailed in the table below. Notice that the column VIOL 2 is provided for information only to compare with papiNet attributes used in documents created with VIOL 2 data.

Fieldname in VIOL 3	QuantityType in papiNet document	MeasuringMethodType in papiNet document	Measuring Method	VIOL 2	VIOL 3
Vedvikt ton †	NetNetWeight		TON	√	√
Volym m ³ fub (omvandlad)	SolidWoodVolume	ConvertedUOM* or VisualEstimated	M3F	√	√
Volym m ³ s †	TippedLooseVolume	VisualEstimated	M3S		√

* If QuantityType value NetNetWeight or TippedLooseVolume is provided in a ShipmentAdvice, then the MeasuringMethodType=ConvertedUOM of the Quantity with attribute QuantityType=SolidWoodVolume.

† The data of this row is provided in element InformationalQuantity only.

Forest forwarders report data to Biometria. The data is then processed by VIOL 3 at Biometria. Data from the forest forwarder report are distributed with papiNet document DeliveryMessage of type ShipmentAdvice issued by Biometria.

In this type of DeliveryMessage attribute QuantityTypeContext is Delivered and attribute AdjustmentType is always skipped.

SolidWoodVolume is provided in Quantity, but NetNetWeight and TippedLooseVolume may only be provided in InformationalQuantity.

For Quantity with QuantityType=SolidWoodVolume, the attribute value of attribute MeasuringMethodType is set depending on whether there is any InformationalQuantity or not. The reason is that if the forest forwarder has reported either NetNetWeight or TippedLooseVolume to Biometria, then this value has been converted into SolidWoodVolume later on. Otherwise the SolidWoodVolume reported by the forest forwarder computer has been visually estimated by the operator.

Notes on how to interpret the attribute MeasuringMethodType:

- The attribute is used in order to specify information about how the measurement value was created, as far as it is known by the issuing party.
- A specified attribute value indicates that Biometria will always provide the attribute in that way.
- Where no attribute value is specified in the table, the attribute might or might not be provided. When provided, the attribute value used is according to the best knowledge at the time.

7 Complete document version history

A change to the version history requires an update of date and version in the page header.

The numbering format is Revision.Version, where Revision is an official document release and Version exceeding 0 is an internal work document. Please note that only if the document version has suffix 0 it is an official Biometria version, e.g 1.0, 2.0, 3.0, but NEITHER 0.1, 1.2 nor 1.10. The version suffix is initialized for each new revision level.

Version	Date	Change	Signature
55.0	22-02-09	On cover page updated considered Biometria Reference Document “VIOL koder” to version 9.8 and updated latest copyright year to 2022. In section 1 Legal Notice updated latest copyright year to 2022. In table 4.1 AdditionalItemInfo added Code OriginalLogisticsSupplierFrom. Further added CodeValue SKM1 to Code DeliveryTerm and CodeValue 0 to Code LoadTransferRequirementType. In section 4.8 “DocumentReferenceID” added initial text on purpose with the section. In the tables of section 4.8 changed second column into “Format in DocumentReferenceID string” to communicate usage within possible S255. Further in subsection 4.8.2 “DocumentReferenceID in VIOL 3” stated that the table refers to what may be included in documents issued by the VIOL 3 system and amended table with DocumentReferenceIDTypes BusinessChainNumber, CompensationCalculationID, CompensationChainNumber, ContractNumber, DeliverySourceNumber, GoodsArrivalNumber, MeasuringInstructionNumber, MeasuringNumber, ProductOriginIdentifier, ProductReferenceNumber, QuantityCalculationID and TransportArrivalNumber. In section 4.10 DownGradingReasonCode added DownGradingReasonCode 15 for use with VIOL 3 only. In table 4.22.3 RoadClassificationCode for Code VehicleCombinationConstraint added CodeValues BK1 (64 Ton), BK2 (51,4 Ton), BK3 (37 Ton), BK4 (74 Ton) and Standard (64 Ton), further deprecated its CodeValues 1, 2, 3, 4 and Standard. In section 4.26 SupplyPointPropertyCode updated the table header and deprecated SupplyPointPropertyCode AggravatedLoadingCondition including its SupplyPointPropertyCodeValues.	JeNo



Version	Date	Change	Signature
54.0	21-12-09	On cover page changed papiNet build to 20211013. In chapter 3 added element DocumentRejectionReason in the table of elements with a code list maintained by agency SDC. In table 4.1 AdditionalItemInfo added Codes SourceMaxWeightConfVehicleSet and TransportResourceCircumstance. Added section 4.9 DocumentRejectionReason to use with VIOL 3 only. In table 4.11 ErrorCode added Code SDC0015 and updated ErrorDescription of Code SDC0012. In section 4.18.2.1 "PartyIdentifier assigned by agency SDC" added maximum length of PartyIdentifier where party type is PlaceOfAccept. In table 4.33.2 TransportVehicleEquipmentCode for VIOL 3 added Code CarrierResourceVIOL.	JeNo
53.0	21-10-16	On cover page updated considered Biometria Reference Document "VIOL koder" to version 9.5. In table 4.1 AdditionalItemInfo added codes PopulationMeasuringIsRequired, TradingPartnerSequencesFixed and TransportMode and deprecated codes LogisticGrossWghtPostUnloading, LogisticGrossWghtPreUnloading and PopulationMeasuringRequired. In table 4.10 ErrorCode indicated that codes SDC0003, SDC0004 and SDC0005 are removed for VIOL 3 and deprecated codes SDC0011 and SDC0013. The latter two were specified for use with VIOL 3 only.	JeNo
52.0	21-08-23	In section 6.2.2.2 "Document MeasuringTicket of type MeasuringTicket in context Product with VIOL 3 data issued by Biometria" removed entries QualityRejectsAndDeductions in column "AdjustmentType in papiNet document" for the table rows with "Value of Kvantitetstyp in VIOL 3" = Vrak, since in these cases there is no adjustment quantity.	JeNo



Version	Date	Change	Signature
51.0	21-06-09	In table 4.1 AdditionalItemInfo added Code BasedOnTemplatePriceComponent, deprecated Code SDCBasePriceComponentName and amended CodeDescription of Codes SDCBasePriceCompExtRefIssuerID, SDCBasePriceComponentExternRef, SDCBasePriceComponentGroup and SDCBasePriceComponentType. In section 4.4 “CostComponentCode” changed left-most column header into CostComponentCode, added CostComponentCode BasedOnTemplatePriceComponent, deprecated CostComponentCodes SDCChargesAndAdjustmentsName and SDCLogisticsBasePriceCompName and in column Usage added CostComponentDescription for CostComponentCodes ChargeAndAdjustmExtRefIssuerID, LogBasePriceCompExtRefIssuerID, LogisticsBasePriceCompExtRef, RejectPriceBasedOnPopulation, SDCChargesAndAdjustments, SDCChargesAndAdjustmentsExtRef, SDCChargesAndAdjustmentsGroup, SDCChargesAndAdjustmentsType, SDCChargesAndAdjustmntsVersion, SDCLogisticsBasePriceCompGroup, SDCLogisticsBasePriceCompType and SDCLogisticsBasePriceCompVersn. In subsection 4.4.2 “CostComponentCode for VIOL 3” added a text detailing usage of CostComponentCode BasedOnTemplatePriceComponent. In section 4.16 “MonetaryAdjustmentComponent” added Code BasedOnTemplatePriceComponent, deprecated Code SDCChargesAndAdjustmentsName, in table column Usage added CodeDescription to use for Codes ChargeAndAdjustmExtRefIssuerID, SDCChargesAndAdjustments, SDCChargesAndAdjustmentsExtRef, SDCChargesAndAdjustmentsGroup, SDCChargesAndAdjustmentsType and SDCChargesAndAdjustmntsVersion and below the table added a text detailing usage of Code BasedOnTemplatePriceComponent.	JeNo
50.0	21-04-19	On cover page changed papiNet build to 20210324 and updated considered Biometria Reference Document “VIOL koder” to version 9.4. In table 4.1 AdditionalItemInfo for Code LinelItem1FinalShipmtIndicator deprecated its CodeValue FinalShipmentOfTheProductFromThisSupplyPoint and pointed out that for Code SCA_SAMLAST_FEL the existing CodeValue ‘ ‘ is the space character. In section 4.4.2 CostComponentCode for VIOL 3, the table concerning code AdditionalTrnsprtRelatedCharge was amended with CostComponentCodeValues 0022 & 0023 and updated with a new CostComponentDescription for CostComponentCodeValue 0016. In table 4.12 MeasuringCodeInfo improved layout of the table by cumulating cells of column MeasuringCodeType. In table 4.34 TreeSpeciesGroupCode changed the English and Swedish TreeSpeciesGroupDescriptions of Code V. In section 6.1 “MeasuringType attribute of element MeasuringSpecification”, improved layout of the table by cumulating cells of column MeasuringType.	JeNo



Version	Date	Change	Signature
49.0	21-02-11	On cover page updated latest copyright year to 2021 and considered Biometria Reference Document “VIOL koder” to version 9.2. In section 1 Legal notice updated latest copyright year to 2021. In table 4.1 AdditionalItemInfo added codes PropellantPriceValueCoeffUsed and SDCBasePriceCompExtRefIssuerID, amended description of code SDCBasePriceComponentExternRef and for code LogisticsServicePriceSource deprecated its CodeValue “NoValueCalculationRequested”. In table 4.4 CostComponentCode added codes ChargeAndAdjustmExtRefIssuerID, LogBasePriceCompExtRefIssuerID and LogisticsBasePriceCompExtRef and amended description of code SDCChargesAndAdjustmentsExtRef. In table 4.16 MonetaryAdjustmentComponent added code ChargeAndAdjustmExtRefIssuerID and amended description of code SDCChargesAndAdjustmentsExtRef. In section 6.2.2.3 “Document MeasuringTicket of type MeasuringTicket in context LogisticsService with VIOL 3 data issued by Biometria” for the table rows where “Måttslagsmetod in VIOL 3” is <i>energiber</i> or <i>torrhaltisb</i> provided data in the righthand columns detailing mapping to papiNet document. In section 6.2.2.5 “Document MeasuringTicket of type InvoiceSpecification in context LogisticsService with VIOL 3 data issued by Biometria” added a text describing that UOM Load might be provided in an InvoiceSpecification.	JeNo



Version	Date	Change	Signature
48.0	20-12-08	On cover page changed papiNet build to 20201021 and updated considered Biometria Reference Document “VIOL koder” to version 9.0. In section 4.6 DeliverySourceProperty stated that CodeValue of codes LoggingForm, RuleForQuantityConversionRatio and TypeOfLoggingCost is a TextValue. In section 4.11 LocationProperty stated that CodeValue of code LoggingForm is a TextValue, added code RegistrationDistrict and subsection 4.11.2 VIOL 3. In section 4.13 MeasuringEquipmentCode added Code HarvesterMachineHead for use with VIOL 3 only. In section 6.2.1 “Attributes in documents with VIOL 2 data issued by Biometria” removed table columns indicating whether table row is applicable to VIOL2 and/or 3, since all table rows are relevant to VIOL 2. In all tables of section 6.2.2 “Attributes in documents with VIOL 3 data issued by Biometria” changed phrase “Not applicable to send” into “Not applicable to provide.” In section 6.2.2.1 “Document MeasuringTicket of type ArrivalTicket in context Product with VIOL 3 data issued by Biometria” removed table column AdjustmentType, deleted the single table row where VIOL 3 field <i>Måttslag</i> is “ton” and added a new table detailing valid attribute combinations in an ArrivalTicket if VIOL 3 field <i>Mätvärde</i> is NOT “mottktrl”.	JeNo



Version	Date	Change	Signature
47.0	20-11-02	Cover page updated to show that version 8.9 of Biometria reference document “VIOL koder” has been considered. In chapter 2 added text with papiNet Data Dictionary definition of Agency SDC. In chapter 3 added element BusinessPartyProperty in the table of elements with a code list maintained by agency SDC. In table 4.1 AdditionalItemInfo added code LoggingMachineGroup, changed CodeDescription of code SDCBasePriceComponent as it carries the ID of a “grundpriskomponent” and updated CodeDescription of code SDCChargesAndAdjustments. Further updated CodeDescription and deprecated use of CodeValue with codes BoundBasisToBeCreated, PriceListDeterminedUsingParty, ProductValueCalculatedBySDC, UsePopulationPriceList and VML for VIOL 3. Regarding code VML amended CodeValues “X” and “ ” for use with VIOL 2 only and deprecated its CodeValues YES and NO. The latter values were not implemented in VIOL 2. Section 4.1.2 VIOL 3 updated to detail usage of code SDCBasePriceComponent. Added section 4.2 BusinessPartyProperty including the code SDCIDOfSuperiorOrganisation. In section 4.14.2 VIOL 3 added table row with <i>Måttslagskod</i> = tim. In table 4.20 ResourceTypeCode amended existing Swedish description of Code LoggingMachineGroup and in the existing descriptions of codes CarrierResourceVIOL and LoadingResourceVIOL separated the ResourceTypeDescription from its usage with parantheses.	JeNo,SuRa



Version	Date	Change	Signature
46.0	20-08-27	In chapter 3 “Table of elements with a code list maintained by agency SDC” moved element ShipmentIncidentCode to its first table from the latter table with elements not yet supported by agency SDC. In table 4.1 AdditionalItemInfo added codes FinalLoadingStatusFromCarrier, LineItem1FinalShipmtIndicator, LogisticGrossWeightAtArrival, LogisticGrossWeightAtDeparture, LogisticGrossWghtPostUnloading, LogisticGrossWghtPreUnloading, LogisticsServicePriceSource, NumberOfFerryCrossingsMade, NumberOfTollroadLegsTravelled, ReportedExtraTransportTime, TransprtAvailableToMeasureDate, TransprtCompletelyMeasuredDate and WeekendTransportDueToRequest. Further updated CodeDescription of code SDCChargesAndAdjustments as it carries the ID of a “T/A-komponent”. In table 4.11 MeasuringCodeInfo added codes TimeSeriesEndDate and TimeSeriesStartDate with attribute MeasuringCodeType=PopulationScope to use with VIOL 3 and for Code QualityClassification indicated that CodeValue is not applicable and deprecated its CodeValue No and Yes. Further amended ‘UOM=”None” ’ to column CodeValue for codes OMRTAL_ENERGI_ST1, OMRTAL_ENERGI_ST2, OMRTAL_PRISKORR_ST1, OMRTAL_PRISKORR_ST2, OMRTAL_TORRHALT_ST1 and OMRTAL_TORRHALT_ST2. Added section 4.11.2 VIOL 3 concerning MeasuringCodeInfo. In section 4.18.2 PropertyType with VIOL 3, corrected spelling into ButtEndProfileExtrapolationFunction, which since 32.0 read invalid ButtEndExtrapolationFunction. In table 4.19 ResourceTypeCode added code LoadingResourceVIOL. Inserted new section 4.22 ShipmentIncidentCode to use with VIOL 3. Currently only Code BusinessServiceRejectionReason is supported. In section 4.31.2 TransportVehicleEquipmentCode for VIOL 3 deleted text saying that the codes only refer to forest forwarders and added code SetOfVehiclesEquippedWithCrane. In section 6.2.2.4 “Document MeasuringTicket of type InvoiceSpecification in context Product with VIOL 3 data issued by Biometria”, in its general second table added the two initial rows where <i>Kvantitetstyp in VIOL 3</i> is Avdrag.	JeNo



Version	Date	Change	Signature
45.0	20-05-08	On cover page changed papiNet build to 20200326 and updated Biometria Reference Document “VIOL koder” to version 8.6. In table 4.1 AdditionalItemInfo updated CodeDescription for CodeValue No of Code PriceListDeterminedUsingParty and indicated that Code VML can be used with VIOL 3 too. In section 4.8 DownGradingReasonCode renamed column header Code into DownGradingReasonCode, added column VIOL 3, indicated code 3 for use with VIOL 3 too and added codes 10, 11, 12, 13 and 14. In section 4.16.2.1 “PartyIdentifier assigned by agency SDC” explained that the substrings xxxxx and yyyyy have leading zeros if a generating integer is less than 10 000. In section 4.20 RoadClassificationCode moved existing table to 4.20.1 VIOL 2 with renamed column header “RoadClassificationCode” replacing “SDC Code” and added subsection 4.20.2 VIOL 3. Inserted new section 6.2.2.1 Document MeasuringTicket of type ArrivalTicket in context Product with VIOL 3 data issued by Biometria. In section 6.2.2.2 “Document MeasuringTicket of type MeasuringTicket in context Product with VIOL 3 data issued by Biometria” deleted the table rows with QuantityTypeContext = “Rejected”, which were the rows with <i>Måttslagsmetod</i>=”metningsv”.	JeNo
44.0	20-03-13	In table 4.1 AdditionalItemInfo added code PriceBasedOnPopulation. In table 4.3 CostComponentCode added code RejectPriceBasedOnPopulation and in section 4.3.2 VIOL 3 added its CostComponentDescription and valid CostComponentCodeValue. In section 4.13 Attribute MeasuringMethod added an explanation for MeasuringMethod MIN.	JeNo

Version	Date	Change	Signature
43.0	20-02-10	In table 4.1 AdditionalItemInfo added codes HereUsedVIOLMeasurgOrderOprNum, RequiredVIOLMeasurgOrderOprNum, SDCBasePriceComponentExternalRef, SDCBasePriceComponentGroup, SDCBasePriceComponentID, SDCBasePriceComponentName, SDCBasePriceComponentType and SDCBasePriceComponentVersion, updated CodeDescription for codes SDCBasePriceComponent and StanForDProductVersion and changed number of characters for CodeValue of code StanForDProductVersion. Updated text in section 4.1.2 VIOL 3 regarding usage of code SDCBasePriceComponent and explained SDCBasePriceComponentID. In table 4.3 CostComponentCode added codes SDCChargesAndAdjustmentsExtRef, SDCChargesAndAdjustmentsGroup, SDCChargesAndAdjustmentsName, SDCChargesAndAdjustmentsType, SDCChargesAndAdjustmntsVersion, SDCLogisticsBasePriceCompGroup, SDCLogisticsBasePriceCompName, SDCLogisticsBasePriceCompType and SDCLogisticsBasePriceCompVersn. In section 4.7.1 DocumentReferenceID with VIOL 3, the value for PriceList is updated to 6-10 alphanumeric characters with limitations. Earlier it allowed max 6 characters. In table 4.15 MonetaryAdjustmentComponent added codes SDCChargesAndAdjustmentsExtRef, SDCChargesAndAdjustmentsGroup, SDCChargesAndAdjustmentsName, SDCChargesAndAdjustmentsType and SDCChargesAndAdjustmntsVersion. In table 4.23 SupplyPointPropertyCode updated code SnowRemoval for use with VIOL 3 and indicated that the CodeValue is a TextValue with one integer digit, explaining valid code values. In this table code SnowPlowingWillBePerformed is deprecated Section 6.2.2.3 "Document MT of of type InvoiceSpecification in context Product with VIOL 3 data issued by Biometria" updated as follows: Stated in initial text the exception that QuantityTypeContext is not Invoiced if the AdjustmentType is Excess. Added a text describing that if "<i>Kvantitetstyp</i>" is Brutto in VIOL 3, then there are two cases in setting the attributes of Quantity. Added a table to use for Quantity when ProductIdentifierType is ManufacturingGradeCode. Deleted the text stating that a quantity with "<i>Kvantitetstyp</i>" Brutto in VIOL 3 may only be used in element ChargeInformation.	JeNo

Version	Date	Change	Signature
42.0	20-01-13	In table 4.1 AdditionalItemInfo added codes PropellantIndexPeriodStartDate, PropellantPriceIndex and PropellantPriceIndexIssuerID. In table 6.2.2.1 “Document MeasuringTicket of type MeasuringTicket in context Product with VIOL 3 data issued by Biometria” changed AdjustmentType Deductions into Deduction. In section 6.2.2.2 “Document MeasuringTicket of type MeasuringTicket in context LogisticsService with VIOL 3 data issued by Biometria”, the text was updated to reflect that only quantities where Kvantitetstyp is “Brutto” will be provided. The table rows with Kvantitetstyp=“Vrak” were deleted accordingly. Further, the table rows with <i>Måttslagsmetod</i>=“metningsv” were deleted. In table 6.2.2.3 “Document MeasuringTicket of type InvoiceSpecification in context Product with VIOL 3 data issued by Biometria” changed AdjustmentType NetAndDeduction into NetAndDeductions. In section 6.2.2.4 “Document MeasuringTicket of type InvoiceSpecification in context LogisticsService with VIOL 3 data” changed the QuantityTypeContext to “Measured” for field “<i>Transporterad kvantitet</i>”. In section 6.2.2.5 “MeasuringTicket of type ProductionTicket with VIOL 3 data” all entries with <i>fub</i> and <i>toub</i> are replaced by <i>f</i> and <i>to</i> respectively. Table rows are added for “Fieldname in VIOL 3” with “Energiinnehåll MWh”, “Ton råvikt”, “Ton torrvikt” and “Volym m³s”. Fieldname “Total m³f stam mätt” renamed from “Stamvolym m³fub total”.	JeNo

Version	Date	Change	Signature
41.0	19-11-27	In table 4.1 AdditionalItemInfo added codes CompensatedAddtlEndDistance, CompensatedAddtlStartDistance, CompensatedPrincipalDistance, DeliveryQtyShareAtTrptArrival, IsSetOfVehiclesFullyLoaded, MaxWeightConfiguredVehicleSet, PrincipalDistanceSourceType and SiteName. In table 4.10 LocationProperty added code SiteName. In table 4.23 SupplyPointPropertyCode amended Code LoadTransferRequirementType with CodeValue 4 and 5. In section 6.2.2.1 “Document MeasuringTicket of type MeasuringTicket in context Product with VIOL 3 data” the attribute value None will typically not be communicated and both text and table are updated accordingly. In table changed AdjustmentType for kvantitetstyp “Vrak” to QualityRejectsAndDeductions. In section 6.2.2.2 “Document MeasuringTicket of type MeasuringTicket in context LogisticsService with VIOL 3 data” the attribute value None will typically not be communicated and both text and table is updated accordingly. In table changed AdjustmentType for kvantitetstyp “Vrak” to QualityRejectsAndDeductions. In section 6.2.2.3 “Document MeasuringTicket of type InvoiceSpecification in context Product with VIOL 3 data” the attribute value None will typically not be communicated and both text and table is updated accordingly. Added explanation on when to provide AdjustmentType “NetAndExcess” and changed QuantityTypeContext to “NotBillable” for AdjustmentType=”Excess”. In table changed AdjustmentType for kvantitetstyp “Vrak”. Added table rows with <i>kvantitetstyp</i>=”Brutto” for use in ChargeInformation only. In section 6.2.2.4 “Document MeasuringTicket of type InvoiceSpecification in context LogisticsService with VIOL 3 data” indicated that field “<i>Transporterad kvantitet</i>” may be provided in Quantity and deleted text stating that price determining distance is provided.	JeNo, MiSc

Version	Date	Change	Signature
40.0	19-10-18	On cover page changed papiNet build to 20191003 and updated Biometria Reference Document "VIOL koder" to version 8.3. In section 4.1 AdditionalItemInfo added Codes DeliveryOriginAreaID, DeliveryOriginAreaIDAssigner, OriginalBuyerAgentHierarchyID, Site, SourcingAreaGroupAssigner and SourcingAreaGroupID for VIOL 3, for codes SDCBasePriceComponent and SDCChargesAndAdjustments updated the CodeDescription and changed the type of their respective CodeValue to NumericValue. In section 4.1.2 VIOL 3 detailed the usage of codes DeliveryOriginAreaID, DeliveryOriginAreaIDAssigner, SDCBasePriceComponent, SDCChargesAndAdjustments, SourcingAreaGroupAssigner and SourcingAreaGroupID. In table 4.3 CostComponentCode added Codes AdditionalTrnsprtRelatedCharge, AgreedTrptChargePricedPerLoad and AgreedTrptChargePricedPerUnit. In section 4.3.1 VIOL 3 added a table with valid CostComponentCode values for Code AdditionalTrnsprtRelatedCharge. In table 4.8 DownGradingReasonCode renamed column header to CodeValue, amended "eller rötavdrag" to the Swedish description of CodeValue 6, updated Swedish description of CodeValue 8 to "Förening" from "Metall etc" and created sub section 4.8.1 VIOL 2. In table 4.11 MeasuringCodeInfo indicated that Codes OMRTALB_ST1, OMRTALB_ST2, OMRTALN_ST1 and OMRTALN_ST2 may be used in VIOL 3 and their CodeValue must have attribute UOM="None". Further added Code ang_brutto for VIOL 3 and deprecated Code skattning. Section 4.22.2 SupplyPointCode in VIOL 3, clarified that the code is not unique within VIOL 3 (earlier not within Biometria). In 4.23 SupplyPointPropertyCode added code BiometriaSupplyPointIntegerID and added section 4.23.2 VIOL 3. Section 6.1.1 "MeasuringType attribute of element MeasuringSpecification for VIOL 2", now explicitly refers to the mapping in preceding table of section 6.1. In section 6.2.2 "Attributes in documents with VIOL 3 data issued by Biometria" the value "visuell" has replaced "skattning" in all table columns labelled "Value of Mättningsmetod in VIOL 3". Changed header of section 6.2.2.1 to "Document MeasuringTicket of type MeasuringTicket in context Product with VIOL 3 data issued by Biometria" as the section now relates to the product business only. In section 6.2.2.1 added information that mapping rules applies both to Quantity and InformationalQuantity, the text now states that if AdjustmentType is None in the table, it does not necessarily need to be communicated. The column QuantityType is updated to comply with recently updated papiNet FWS&B Business Rule FWS_GE_015. The combination [Brutto, ton] now has AdjustmentType="NetAndDeductions" and for all rows with Kvantitetstyp = Avdrag the AdjustmentType is changed to Deductions. Added text saying that if AdjustmentType is None in the table, it does not necessarily need to be communicated. The table is updated with value None where applicable in column AdjustmentType. Inserted section 6.2.2.2 "Document MeasuringTicket of type MeasuringTicket in context LogisticsService with VIOL 3 data issued by Biometria", since there are differences depending on context type. In section 6.2.2.3 "Document MeasuringTicket of type InvoiceSpecification in context Product with VIOL 3 data" added mapping rules when "Value of Kvantitetstyp in VIOL 3" is Modul and how to communicate an excess quantity. The AdjustmentType is changed to NetAndExcess for combinations [Netto, m3f] and [Netto, m3to]. The text now states that an excess quantity cannot be compensated in amount calculations of VIOL 3. In section 6.2.2.4 "Document MeasuringTicket of type InvoiceSpecification in context Product with VIOL 3" clarified that in VIOL 3 attribute AdjustmentType is not used in InvoiceSpecifications of LogisticsService context. The text now states that it refers to the "table below". In section 6.2.2.5 "MeasuringTicket of type ProductionTicket with VIOL 3 data" mapping if "Fieldname in VIOL 3" is "Antal stammar" is added to the table and table entries in column QuantityType is changed to SolidWoodVolume for level PackageMeasuringInfo to comply with updated business rule FWS_GE_015.	HaHe, JeNo

Version	Date	Change	Signature
39.0	19-08-23	In section 4.1 AdditionalItemInfo corrected spelling of Code VIOL2_AnySubentityMaySupplyToo by removing a space between characters 1 and 2. This code was introduced in version 23.0, but has been misspelled since version 25.0 making it 31 characters long although a Code must not exceed 30 characters to pass XSD schema validation. Hence the misspelled code cannot exist in successful production use. A notice is provided at end of section 4.1.1 VIOL 2. In section 4.1 AdditionalItemInfo added Codes AggravatedLoadingCondition, InconvenientTransportReason, IsLogisticsValueInputRequested, LimitingRoadBearingCapClassNO and LimitingRoadBearingCapClassSE for VIOL 3. In section 4.18.1 PropertyType in VIOL 2 truncated a column header to "Description in Swedish". In section 4.19 ResourceTypeCode added Code CarrierResourceVIOL for use with VIOL 3 only. In table 4.23 SupplyPointPropertyCode added description of Code AggravatedLoadingCondition itself and for Code AccessRoadAvailabilityType added CodeValue 1 for VIOL 3 only and changed descriptions of its existing CodeValue 0, 2, 3 and 4. In section 6.2.2.5 "Document DeliveryMessage of type ShipmentAdvice with VIOL 3 data issued by Biometria" now states that values with QuantityType=TippedLooseVolume may only be provided in InformationalQuantity and the table and text is updated accordingly. In previous version it could only be provided in Quantity.	JeNo
38.0	19-06-24	Updated name of section 4.5 to DeliverySourceProperty and for its Code LoggingForm deprecated code values FinalFellg and Thinning, added code values AVVINSEKTS, AVVSKATR, AVVVINDF, FGALLR, FROTRST, GALLR, OVRIGAVV, NATVAVV and SLUTAVV. Chapter 3 updated accordingly. In section 4.10 LocationProperty added Code AverageTreeAge for VIOL 3 only and for Code LoggingForm deprecated its code values FinalFellg and Thinning, added code values AVVINSEKTS, AVVSKATR, AVVVINDF, FGALLR, FROTRST, GALLR, OVRIGAVV, NATVAVV and SLUTAVV. Clarified that 4.10.1 refers to Code AVVFORM. In section 6.2.2.1 Document MeasuringTicket of type MeasuringTicket with VIOL 3 data issued by Biometria, the table is amended the rows where "Kvantitetstyp in VIOL 3" is Vrak and changed UOM to MegaWattHour for rows where "Kvantitetstyp in VIOL 3" is Netto and "Måttslag in VIOL 3" is MWh. Previously the UOM was CubicMeter in the latter rows. All texts regarding InvoiceSpecification are removed from section 6.2.2.1. Inserted new section 6.2.2.2 Document MeasuringTicket of type InvoiceSpecification in context Product with VIOL 3 data issued by Biometria. Inserted new section 6.2.2.3 Document MeasuringTicket of type InvoiceSpecification in context LogisticsService with VIOL 3 data issued by Biometria.	JeNo

Version	Date	Change	Signature
37.0	19-05-03	In section 4.3 CostComponentCode added code SDCLogisticsBasePriceComponent for VIOL 3 only. In section 4.3.1 VIOL 2 clarified that the reference documents are only available for CostComponentCode that are used for VIOL 2. In section 4.3.2 VIOL 3 added a text regarding CostComponentCode SDCLogisticsBasePriceComponent.	JeNo
36.0	19-04-30	On cover page changed papiNet build to 20190327. In section 6.2.2.1 “Document MT of type MeasuringTicket with VIOL 3 data issued by Biometria” removed all table rows with Kvantitetstyp “Vrak*” and added explaining text above the table. Added section 6.2.2.2 Document MT of type ProductionTicket with VIOL 3 data. Added section 6.2.2.3 Document DeliveryMessage of type ShipmentAdvice with VIOL 3 data.	JeNo
35.0	19-04-15	In chapter 3 indicated that there are code lists for MonetaryAdjustmentComponent and TransportUnloadingCode maintained by agency SDC. Clarified that element CostComponentCode has a dynamic list of SDC identifier values for VIOL 3, but not for VIOL 2. In section 4.1 AdditionalItemInfo, updated the CodeDescription of code SDCChargesAndAdjustments. Further, the code RETUR may now also be used with VIOL 3. In section 4.3 CostComponentCode added a text stating that the Code is not case sensitive, added code SDCChargesAndAdjustments for VIOL 3 only and added subsections 4.3.1 VIOL 2 & 4.3.2 VIOL 3. In section 4.11 deleted doublespace in the CodeDescription for the code MeasuringMethodMayDeviate and added a text stating that the Code is not case sensitive. Added section 4.15 MonetaryAdjustmentComponent. In section 4.23 SupplyPointPropertyCode added a text stating that the Code is not case sensitive and the code value is typically a TextValue, which now also is indicated in the column header. In table 4.23 added code AggravatedLoadingCondition, edited code DistanceLocationToSupplyPoint to capital P in “Point” and for the latter Code indicated that UOM=”Kilometer”. Added section 4.28 TransportUnloadingCode. Sections 4.4, 4.5, 4.9, 4.10, 4.12, 4.24, 4.26, 4.30.2 and 4.33 are updated with a text telling that the Code is not case sensitive and must hence be implemented accordingly.	JeNo MiSc

Version	Date	Change	Signature
34.0	19-02-22	Copyright owner changed to Biometria and changed latest copyright year to 2019. Page header updated with Biometria logo and removed header title “Public version” as it is implied by the .0 in Version. Page footer updated with Biometria contact details. On cover page changed header line two to “maintained by agency SDC”, which earlier read “maintained by SDC” and changed papiNet build to 20181017. Text “SDC” is changed to “Biometria” in entire document where applicable. Removed version 33.0 from page 2, as previous version history is kept in chapter 7 only. Section 2 Usage now explains that Biometria maintains the codes of agency SDC. In table 4.1 AdditionalItemInfo added codes PreliminaryEndUser, PrelOriginalLogisticsBuyer, PrelOriginalLogisticsBuyerAgnt, PrelOriginalLogisticsSupplier and ProduktID. In table 4.6 DeliverySourcePropertyCode updated CodeDescription for all code values of codes RuleForQuantityConversionRatio and TypeOfLoggingCost. In table 4.11 MeasuringCodeInfo added code MeasuringMethodMayDeviate and for existing code PopulationVariant the code values with their CodeDescription in the Swedish language. In section 4.12 MeasuringEquipmentCode added codes CompensationMeasuringApprovalStatus and MeasuringAccuracyAsAudited in table and their related MeasuringEquipmentDescription below the table. In section 4.13 Attribute MeasuringMethod the MeasuringMethod values M3CONT, M3MI, M3SLICE, M3STACK, M3TR, TOInOut and TOLoaded are deprecated and should not be used. The values M3F, M3S and TON in the same table are revived for use with VIOL 3. In section 4.17.2 PropertyType VIOL 3 indicated that it is used with MeasuringAgency=”SDC”, amended column header Explanation and added PropertyType BarkFunction, DiameterClassCode, QualityClassCode, TreeProcessingCategory and TreeSpeciesGroupCode. In table 4.30 TreeSpeciesGroupCode added English TreeSpeciesGroupDescription and allocation to VIOL 3 for codes 0, 3 and 9. Added sub section 6.2.2 “Attributes in documents with VIOL 3 data issued by Biometria”.	JeNo
33.0	18-12-17	In table 4.9 ErrorCode indicated that code SDC0003 can be used with VIOL 3 too and added codes SDC0013 and SDC0014 for VIOL 3 only. Moved existing VIOL 2 content in section 6.2 into new sub section 6.2.1 “Attributes in documents with VIOL 2 data issued by SDC.”	JeNo



Version	Date	Change	Signature
32.0	18-11-07	Cover page updated to show that version 8.0 of SDC reference document “VIOL koder” has been considered in version 32.0. In table 4.1 AdditionalItemInfo added codes MeasureUsabilityCountedObjects, MeasureUsabilityM3Loose, MeasureUsabilityM3NarrowEnd, MeasureUsabilityM3Solid, MeasureUsabilityMetricTon, MeasureUsabilityMinutesTime, MeasureUsabilityMWhEnergy and MeasureUsabilityTonneBoneDry, changed to Swedish descriptions for code IMPEXP and indicated that its CodeValues ‘ ‘, 1 and 2 can be used in VIOL 3, deprecated code SDCAccountingReferenceID and finally clarified that code SupplyingRegistrationDistrict uses values defined by Lantmäteriet. In section 4.6.1 updated the text since it incorrectly referred to DocumentReferenceIDType. In section 4.10 LocationProperty added code LoggingForm. In section 4.11 MeasuringCodeInfo added code PopulationVariant as MeasuringCodeType PopulationScope. In table 4.13 Attribute MeasuringMethod, the measuring methods OnBark and UnderBark are indicated to use with VIOL 3 and their explanations are provided. Section 4.13.2 VIOL 3 has a table indicating which UOM to use for different values of “Måttslagskod” in VIOL 3 and its columns are regrouped. The UOM is now corrected to Minute (earlier invalid Minutes) for Måttslagskod min. In section 4.15.2.1 PartyIdentifier assigned by agency SDC, the reference to section for living persons is changed 4.15.2.2. Added subsection 4.17.2 concerning VIOL 3 in section 4.17 PropertyType. In section 4.28 TransportVehicleEquipmentCode moved VIOL 2 table to subsection 4.28.1 and added subsection 4.28.2 VIOL 3.	HaHe, JeNo



Version	Date	Change	Signature
31.0	18-09-24	Section 2 now states that SDC may only be used with attribute MeasuringAgency for elements that are included in this document. In section 3, element DiameterClassCode is added to the table and ForestWoodClassCode is updated as the latter is explicitly used for VIOL 2 only. In table 4.1 AdditionalItemInfo added codes ForestHarvestingIsCompleted, PopulationMeasuringRequired and SupplyingRegistrationDistrict and clarified that code StanForDPRFileSequenceNumber has only numeric digits as characters. The code UsePopulationPriceList was updated by deleting redundant word "från" in the CodeDescription of CodeValue Yes. Added table 4.6 DiameterClassCode. Section 4.7 DocumentReferenceID amended with section 4.7.2 regarding VIOL 2. In both sections 4.7.1 VIOL 3 and 4.7.2 VIOL 2 type EnergyCalculationReferenceNumber is added. Table 4.11 MeasuringCodeInfo added codes of MeasuringCodeType MeasuringMethodService and PopulationScope for VIOL 3. In table 4.12 MeasuringEquipmentCode added column CodeValue and codes FileTransferApplication, FileTransferApplicationVersion, HarvesterOperatingSystem and StanForDApplicationVersion. In table 4.13 Attribute MeasuringMethod added column "Explanation" as well as measuring methods M3CONT, M3MI, M3SLICE, M3STACK and M3TR. Indicated that measuring methods M3F, M3S and TON will be deprecated in VIOL 3. In table 4.13.2 VIOL 3 column MeasuringMethod is deleted and the initial text is updated since MeasuringMethod is NOT depending on value of VIOL 3 field <i>Mättslagskod</i>. Table 4.30 TreeSpeciesGroupCode updated with codes for VIOL 3 and English TreeSpeciesGroupDescriptions.	JeNo
30.0	18-06-28	Cover page updated to support papiNet version 2.40 build 2018-03-22. Put codes of table 4.1 AdditionalItemInfo into alphabetical order and added codes ForestForwardingIsCompleted, SDCAccountingReferenceID and StanForDSubObjectUserID In table 4.1 AdditionalItemInfo code BuyerRelationContractedObject code value ES was deprecated and replaced by new code value ER. In table 4.1 code DeliveryTerm code value AU was deprecated and replaced by new code value AU1. In table 4.1 it is clarified that code StanForDFileType has three characters. In table 4.12 Attribute MeasuringMethod, values M3F, M3TO, MIN and ST are amended for use with VIOL 3 only and values M3FUB and M3TOUB are deprecated for use with VIOL 3. Updated the example with MWh (previously m3fub) below table 4.12 to explain that the codes are not case sensitive. Updated support for VIOL 3 in section 4.22 TransportInstructionCode.	HaHe, JeNo, MiSc



Version	Date	Change	Signature
29.0	18-05-28	Cover page updated to show that version 7.9 of SDC reference document “VIOL koder” has been considered in version 29.0. In table 4.1 AdditionalItemInfo added code InputMethodUsedForLoggingData. In table 4.1 code BuyerRelationContractedObject code values CK and NI were deprecated and replaced by new code values AO and PA. In table 4.1 code DeliveryTerm code values LRK, LV and RP were deprecated and replaced by new code values LEV1, LRK1, LRK2 and ROT1. The section 4.1.2 now has a reference for code SDCChargesAndAdjustments. It should have been updated already in version 27.0 as code ChargesAndMonetaryAdjustmentsID was deprecated. Introductory text added in section 4.5 to describe that it is used in VIOL 3. In table 4.8 ErrorCode the existing codes SDC0004 and SDC0005 are included to be used with VIOL 3. Updated sub section 4.14.2.2 so the papiNetGlobalPartyIdentifier includes the century a person was born to comply with Swedish law (2009:272). Added code LoggingMachineGroup to table 4.17 ResourceTypeCode. Added table 4.25 TransportUnitIdentifier. Amended table 4.28 TransportVehicleIdentifier with row for Forest Forwarders to be used in VIOL 3. In table 4.29 TreeSpeciesGroupCode the TreeSpeciesGroupDescription of CodeValue V is updated to “Sekunda gran” from “Gran Barkborre”.	JeNo
28.0	18-05-07	In table 3 added that DeliverySourcePropertyCode is an element supported by SDC. Section 4.14.2 VIOL 3 is split into sub sections 4.14.2.1 “PartyIdentifier assigned by agency SDC” and 4.14.2.2 “PartyIdentifier for living persons”. Section 4.14.2.1 is updated with identifiers for various party types instead of referencing to SDC Use Case G. Section 4.14.2.2 details how people known to SPAR (Swedish acronym for <i>Statens person- och adressregister</i>) are identified and in particular that people unknown to SPAR are not identified at all with a PartyIdentifier. Added section 4.20.2 on SupplyPointCode for VIOL 3.	JeNo
27.0	18-03-28	In section 3 “Table of elements with a code list maintained by agency SDC” added elements DocumentReferenceld and PropertyType. Indicated that element ProductIdentifier can be considered to have a dynamic list of values in VIOL 3. In table 4.1 AdditionalItemInfo added codes BoundBasisToBeCreated, SDCBasePriceComponent and SDCChargesAndAdjustments, further deprecated code ChargesAndMonetaryAdjustmentsID as it is replaced by the added code SDCChargesAndAdjustments, updated description of the code DeliveryTerm. Added new code table 4.5 DeliverySourcePropertyCode with codes AverageTreeAge, CountryOfHarvest, FirstReleaseOnEUMarket, LoggingForm, PriceListControlParameter, RuleForQuantityConversionRatio and TypeOfLoggingCost. In table 4.9 LocationProperty added code Site. In table 4.21 SupplyPointPropertyCode added codes AccessRoadAccessibilityType, AccessRoadAvailabilityType, AccessRoadBearingCapacityClass, DeadEndRoadExist, DistanceLocationToSupplypoint, LoadTransferRequirementType and SnowPlowingWillBePerformed for use with VIOL 3.	HaHe JeNo MaHa MiSc

Version	Date	Change	Signature
26.0	18-01-22	Updates the copyright © to new calendar year 2018. Updates to papiNet version to papiNet version 2.40 build 20171018 In table 4.1 AdditionalItemInfo added codes BuyerRelationContractedObject, ChargesAndMonetaryAdjustmentsID, ContractedCurrency_VIOL3, ContractLinePricingTerm, PriceListDeterminedUsingParty, ProductValueCalculatedBySDC and UsePopulationPriceList, updated code descriptions of codes DeliveryTerm and indicated VIOL 3. Added section 4.1.2 VIOL 3 In section 4.11 Attribute MeasuringMethod, valid with MeasuringAgency=SDC added new values for VIOL 3, added new section for 4.11.1 VIOL 2 and removed column in table for VIOL 3 and added new section for 4.11.2 VIOL 3. Added section 4.13.2, describing specific use of PartyIdentifier in VIOL 3. 4.14 ProductIdentifier added 4.14.2 VIOL 3 and moved table in to 4.14.1 VIOL 2 from 4.13 ProductIdentifier Added section 4.5 DocumentReferenceID In table 4.9 MeasuringCodeInfo added Code LogMeasuringRequired, QualityClassification, CoveredByVML and indicated VIOL 3.	HaHe JeNo MaHa MiSc



Version	Date	Change	Signature
25.0	17-09-22	All text occurrences of “Viol2” and “Viol 2” changed to “VIOL 2”. All text occurrences of “Viol3” and “Viol 3” changed to “VIOL 3”. 4.1 Code table header updated with new columns “VIOL 2” and “VIOL 3”. Added ContractedCurrency_VIOL2 to table 4.1 AdditionalItemInfo for VIOL 2. Added DeliveryTerm to table 4.1 AdditionalItemInfo for VIOL 3. Allocated codes SenderSoftwareVersion, StanForDBarkFunction, StanForDFileName, StanForDFileType, StanForDObjectGroupID, StanForDPRIFileSequenceNumber and StanForDProductVersion to column VIOL 3 in table 4.1 AdditionalItemInfo. 4.2 Code table header updated with new columns “VIOL 2” and “VIOL 3”. Put previous text of 4.2 into new section 4.2.1 VIOL 2. Added section 4.2.2 VIOL 3. 4.3 – 4.5 Code table header updated with new columns “VIOL 2” and “VIOL 3”. 4.6 Code table header updated with new columns “VIOL 2” and “VIOL 3”. Updated error descriptions in English so that they correspond with the Swedish error descriptions. Added error codes SDC0011 and SDC0012. Updated ErrorDescription for Error Code SDC0007 to describe that it is dynamic. Updated ErrorDescription for Error Code SDC0007 to describe that it is dynamic. 4.7 – 4.8 Code table header updated with new columns “VIOL 2” and “VIOL 3”. 4.9 Code table header updated with new columns “VIOL 2” and “VIOL 3”. Removed text ”There is no similar table in Viol.” 4.10 – 4.11 Code table header updated with new columns “VIOL 2” and “VIOL 3”. 4.12 Code table header updated with new columns “VIOL 2” and “VIOL 3”. Allocated PartyIdentifier to column VIOL 3. 4.13 – 4.14 Code table header updated with new columns “VIOL 2” and “VIOL 3”. 4.15 Code table header updated with new columns “VIOL 2” and “VIOL 3”. Removed text ”There is no similar table in Viol.” 4.16 – 4.19 Code table header updated with new columns “VIOL 2” and “VIOL 3”. 4.20 Code table header updated with new columns “VIOL 2” and “VIOL 3”. Removed text ”There is no similar table in Viol.” 4.21 Code table header updated with new columns “VIOL 2” and “VIOL 3”. 4.22 Code table header updated with new columns “VIOL 2” and “VIOL 3”. Removed text ”There is no similar table in Viol.” 4.23 – 4.27 Code table header updated with new columns “VIOL 2” and “VIOL 3”. 6.1 – 6.2 Code table header updated with new columns “VIOL 2” and “VIOL 3”.	DaLi HaHe MaHa
24.0	17-04-24	In table 4.27 VersionReason, the CodeValue is updated to be a TextValue for Code KORRKOD. It must NOT be a NumericValue. In table 4.27 the CodeDescription of Code PGEN is changed for better readability.	JeNo
23.0	17-03-24	Added code VIOL 2_AnySubentityMaySupplyToo to code table 4.1 AdditionalItemInfo.	HaHe
22.0	17-03-13	In table 4.6 ErrorCode, the code SDC0003 is deprecated by adding description “To be deprecated, do not use”.	MiSc
21.0	17-03-06	Added AVSTTYP, T_METOD, TEMP_RNRGEN and TSKOD to table 4.1 AdditionalItemInfo.	MiSc MaHo



Version	Date	Change	Signature
20.0	17-02-27	On cover page updated to version 7.7 of reference document "VIOL koder". In section 3 added RoadMaintenanceCodeInfo to "Table of elements with a code list maintained by agency SDC" and removed it from the table showing elements not supported by agency SDC. Added section 4.17 RoadMaintenanceCodeInfo. Hence all subsequent tables of section 4 "Code tables" have new subdigits (previous 4.17 is now 4.18 etc). Added code SnowRemoval to table 4.19 SupplyPointPropertyCode.	HaHe MaHa
19.0	17-02-15	Added TEMP_TRPKM_KORR to table 4.1 AdditionalItemInfo	MiSc
18.0	17-02-13	On cover page updated to version 3.3 of reference document "Prislisteadministration Textkoder". Added code TEMP_AVLPL to table 4.1 AdditionalItemInfo. Added two table rows "Cubic meter" and "Hectare" to second table of section 4.10 Attribute MeasuringMethod. In section 4.20 TransportModeCode, the table is amended with column @TransportModeType.	JeNo
17.0	17-02-06	On cover page updated to version 7.6 of reference document "VIOL koder". Added code SCA_SAMLAST_FEL to table 4.1 AdditionalItemInfo. Added UOM="MetricTon" to LASTVIKT in table 4.1 AdditionalItemInfo. Added table 4.11 MeasuringUnitIdentifier. Hence all subsequent tables of section 4 "Code tables" have new subdigits (previous 4.11 is now 4.12 etc).	MaHa MiSc JeNo
16.0	17-01-23	Added more details of how SDC provides the attribute MeasuringMethodType (section 6.2.1 and 6.2.2).	MiSc
15.0	17-01-16	Translated code description of code FRAAN into English, provided code descriptions of code IMPEXP and deleted CodeValue ' ' (space) from code OMRFLIS in table 4.1 AdditionalItemInfo. X remains the only valid code value for code OMRFLIS. There is now a separate table 4.5 DownGradingReason Code. It was previously by mistake included as a second table in section 4.4. CreditDebitNoteReasonCode. Hence all subsequent tables of section 4 "Code tables" have new subdigits (previous 4.6 is now 4.7 etc). In table 4.6 ErrorCode, English description is provided for Code SDC0007. In table 4.8 MeasuringCodeInfo a spelling mistake is corrected concerning CodeDescription for MeasuringPurpose with Code MS and CodeValue = S3. In table 4.11 PartyIdentifier format of PartyType OriginalSupplier is added. Locations are swapped for tables 4.18 TransportInstructionCode and 4.19 TransportModeCode, to be in alphabetic order. Inserted section 4.23 TransportVehicle Identifier.	JeNo
14.0	16-12-29	Updated version and date of SDC reference document VIOL Koder. Added codes LED1-ContractIdentifier, LED4-ContractIdentifier, LED5-ContractIdentifier, LED6-ContractIdentifier and LED7-ContractIdentifier to table 4.1 AdditionalItemInfo. In section 4.9 MeasuringMethod added value M3SK to table MeasuringMethod and added rows for Måttslagskod 03, 10, 19 and 21 to second table of 4.9.	JeNo
13.0	16-12-12	Added code GRANSOTRP to table 4.1 AdditionalItemInfo.	HaHe
12.0	16-11-28	Added code MSLAG_KO to table 4.1 AdditionalItemInfo and updated CodeDescription for code OMRFLIS in the same table.	StEd



Version	Date	Change	Signature
11.0	16-11-14	On cover page updated to most recent build of papiNet version 2.40. Added codes CALC_ID, CALCNAME, OMRFLIS, PGEN and TRPALT to table 4.1 AdditionalItemInfo and updated both code description and UOM for existing code SCA_OMRVERDEPLTR in the same table. Updated description of code LED in table 4.1, to let it be used in document DeliveryMessage. Deprecated and removed code TOMKM from table 4.1 AdditionalItemInfo. In table 4.6 ErrorCode updated description of code SDC0007 and deprecated its codes SDC0008 – SDC0010, by adding description “To be deprecated, do not use”. Added code VIAPKT to table 4.19 TransportInstructionCode. Added code IsMeasuringNumberCancelled to table 4.24 VersionReason and deprecated its code PGEN by adding description “To be deprecated, do not use”. New mapping path is provided for PGEN.	HaHe JeNo MiSc StEd
10.0	16-09-29	Added codes FKODVO, PRISTYP, RETRO, SenderSoftwareVersion, StanForDBarkFunction, StanForDFileType, StanForObjectGroupID, StanForDPRIFileSequenceNumber, StanForDProductVersion and URNR to table 4.1 AdditionalItemInfo. Deprecated code LEDTR in table 4.1 AdditionalItemInfo, by adding description “To be deprecated, do not use”. In section 4.8 clarified the codes for MeasuringCodeInfo having MeasuringCodeType=”MeasuringPurpose”. Added code table 4.9 MesuringEquipmentCode. Added MeasuringMethod TIM and its corresponding “Måttslagskod” 02 in table of section 4.10. Added PlaceFinalDestination in section 4.11 PartyIdentifier. Added table 4.13 PropertyType. Added text in section 6.2.1 on QuantityTypeContext in PackageMeasuringInfo, where ItemType is LogPile. Updated table in sections 6.2.1 and 6.2.2 regarding attributes for InformationalQuantity and Quantity in MeasuringTicket and DeliveryMessage. Column on AVDRVOL & AVDRVOLSTOCK added. Reworked section 6.2.2 on how to use attributes for quantities in a DeliveryMessage.	AnOh JeNo MiSc
9.0	16-08-25	Added code MSLAGT to table 4.1 AdditionalItemInfo. Updated text (but not the table) in section 4.2 Classification Code.	JeNo MiSc
8.0	16-06-03	Added codes BETGRUNDVIKT, MMA, MMB, MMC, MMD, LASTVIKT, LEDTR and SCA_OMRVERDEPLTR to table 4.1 AdditionalItemInfo. Deprecated codes LED and LED1-BUYER-HKODK-INTNRK to LED7-BUYER-HKODK-INTNRK in table 4.1 AdditionalItemInfo by changing their CodeDescription into “To be deprecated, do not use”. Added code DeadendRoad to table 4.15 SupplyPointPropertyCode. Added codes TRSTATUS and KORRKOD to table 4.22 VersionReason and updated code description of code PGEN in code table 4.22 VersionReason. Described below table 4.22 which MeasuringTicketType that carries PGEN.	JeNo AnOh MiSc DaLi



Version	Date	Change	Signature
7.0	16-04-13	Added codes BFAARK, BFAARS, CERT, FORETOA, FORETOT, KKODER, IMPEXP, REDOVHANV, RUTTID_TR, SKODER, TRADALDER, VO_STATUS_HUVUD, VO_STATUS_RAD and VMFusedForOtherPurpose to code table 4.1 AdditionalItemInfo. Added codes AVVBESTP, AVVBESTT, FORETOA, FORETOT, METNB_VO, REDOVKOST and VML to code table 4.8 MeasuringCodeInfo. Added codes SDC0007, SDC0008 and SDC0009 to table 4.6 ErrorCodes. Codes SDC0001 – SDC0006 of table 4.6 will be deprecated and should not be used in new implementations. Updated table in section 6.2.1 “Document MeasuringTicket with VIOL 2 data issued by SDC” by swapping MeasuringMetodType “ConvertedUOM” and Calculated for rows with KVANTKOD = O. The section 6.2.1. also has a text on when MeasuringMethodType should be omitted if KVANTKOD = O. Added section 6.2 “Attributes of InformationalQuantity and Quantity”	HaHe JeNo DaLi AnOh
6.0	16-03-04	Added code PKODT to code table 4.1 AdditionalItemInfo. Added ErrorCodes to table 4.6. Corrected spelling errors for UOM enumeration value “Kilometer” throughout the document	JeNo
5.0	16-01-19	Added code table 4.7 Location Property including code AVVFORM. Added code table 4.15 SupplyPointPropertyCode with codes Reloading and RoadClass. Added codes FRITERM-FK-###, FRITERM-VO-###, KIGEN, LEVAR, PERIOD, RNRPERLAST, TOMKM, VAGKL2, VAGKL3, VAGKL4, VML and VOGEN to code table 4.1 AdditionalItemInfo. Updated typography of code Uppdrag in code table AdditionalItemInfo to Uppdrag from UPPDRAG, which however has no impact in the interface. Updated version of document “VIOL koder” on the cover page.	JeNo
4.0	15-09-29	Added “FU Handbok Följdrutinutgångar” on cover page. Updated both tables in section 3 to show codes and ID supported. Code table 4.1 AdditionalItem is updated with codes FRITERM-###, LED, LED1-BUYER-HKODK-INTNRK to LED7-BUYER-HKODK-INTNRK, and PKOD1 – PKOD5. Added code table 4.2 ClassificationCode. Updated section 4.7 MeasuringCodeInfo by adding code for MeasuringReportType and removing code for Other. 4.8 Table Attribute MeasuringMethod.appended with attribute value M3TVOLT. Updated sections 4.9 PartyIdentifier and 4.13 SupplyPointCode.	JeNo



Version	Date	Change	Signature
3.0	15-07-03	Updated document references on cover page. Changed references to codes in SDC reference document “VIOL koder”. The references now point to the name of the Code in that document instead of the chapter number. Changed to SDC Code Value instead of SDC Code in some code table headers. Added codes BefraktarKoder, FSEDEL1, IsPresenceOfCraneConfirmed and T_USER to code table AdditionalItemInfo. Added code table Supply Point Code. Completely updated MeasuringCodeInfo and the VIOL references below that table was updated. Updated section PartyIdentifier. Section “Attribute MeasuringMethod valid with MeasuringAgency SDC”: Changed column headers to QuantityType and UOM. The explanatory text of code table 4.19 VersionReason now refers to current “VIOL 2” instead of “Viol”. Amended code table TransportInstructionCode with Code “ScaleOut” and changed its Code “3” to “GoToMeasur” including a minor change to its description.	JeNo
2.0	14-12-23	Updated with new code tables to support new SDC Use Case C – E-Invoicing of Roundwood. Amended existing code tables after external review.	JeNo
1.0	14-06-11	Initial public version	JeNo

END OF DOCUMENT.