Lecture 12: evaluation

> 第 12 讲：评测

- So far: we've covered everything for training an LM (architecture, training, systems, scaling).

> 到目前为止：训练一个语言模型所需的内容我们都讲过了（架构、训练、系统、缩放）。

- Missing piece: what **data** do you train on?

> 缺失的一块：你用什么数据训练?

- Data shapes model behavior (code? multilingual? DNA?).

> 数据塑造模型行为（代码？多语言？DNA？）。

- Before talking about data, need to talk about what behavior we want from a model.

> 在谈数据之前，需要先谈我们希望模型具备什么行为。

Evaluation: given a model, how "**good**" is it?

> 评测：给定一个模型，它到底有多“好”?

Takeaways:

> 要点：

- There is no one true evaluation; choose the evaluation depending on what you're trying to measure.

> 不存在唯一正确的评测；要根据你想测量什么来选择评测。

- Clearly state the rules of the game (methods versus models versus agents).

> 清楚地说明游戏规则（方法 vs 模型 vs 智能体）。

- Considerations: difficulty, realism, validity.

> 考量因素：难度、真实性、效度。

Evaluation might appear to be a mechanical process:

> 评测看起来也许是一个机械的过程：

1. Define some prompts

> 定义一些提示词

2. Send prompts to a model and get back responses

> 把提示词发给模型并拿回回复

3. Compute accuracy

> 计算准确率

But actually, evaluation is a deep and important topic...

> 但实际上，评测是一个深刻而重要的话题……

...which shapes the development of AI.

> ……它塑造着 AI 的发展。


Core challenge: abstract construct → concrete metric

> 核心挑战：抽象构念 → 具体指标

Maybe a model is good if it does well on benchmarks...


> 也许一个模型在 benchmark 上表现好就算好……

[Artificial Analysis]



Maybe a model is good if it does well on benchmarks and is cheap to run...

> 也许一个模型在 benchmark 上表现好、运行又便宜才算好……



Maybe a model is good if people prefer its responses...

> 也许人们更偏好它的回复就算好……

[Arena AI (formerly Chatbot Arena)]

> [Arena AI（原 Chatbot Arena）]

Text — 4 days ago

Rank	Model	Score
1	claude-opus-4-7-thinking	1503
2	claude-opus-4-6-thinking	1502
3	claude-opus-4-6	1497
4	gemini-3.1-pro-preview	1493
5	claude-opus-4-7	1491
6	muse-spark	1491
7	gpt-5.5-high	1488
8	gemini-3-pro	1486
9	grok-4.20-beta1	1480
10	grok-4.20-beta-0309-reasoning	1477

Maybe a model is good if people simply choose to use (and pay for) it...

> 也许人们愿意选用（并为之付费）就算好……

[OpenRouter]

Compare the most popular models on OpenRouter

1.	Hy3 preview (free) by tencent	3.66T tokens ↑298%	11.	Gemini 2.5 Flash Lite by google	624B tokens ↓3%
2.	Kimi K2.6 by moonshotai	1.8T tokens ↓11%	12.	Gemini 2.5 Flash by google	602B tokens ↓0%
3.	Claude Sonnet 4.6 by anthropic	1.34T tokens ↓0%	13.	DeepSeek V4 Pro by deepseek	577B tokens ↑616%
4.	Gemini 3 Flash Preview by google	974B tokens ↓5%	14.	Nemotron 3 Super (free) by nvidia	546B tokens ↓17%
5.	Claude Opus 4.7 by anthropic	919B tokens ↓21%	15.	Ling-2.6-1T (free) by inclusionai	467B tokens ↑10%
6.	DeepSeek V4 Flash by deepseek	819B tokens ↑158%	16.	Claude Opus 4.6 by anthropic	418B tokens ↓36%
7.	DeepSeek V3.2 by deepseek	815B tokens ↓33%	17.	gpt-oss-120b by openai	391B tokens ↑1%
8.	MiniMax M2.7 by minimax	738B tokens ↓4%	18.	GLM 5.1 by z-ai	362B tokens ↓8%
9.	Grok 4.1 Fast by x-ai	706B tokens ↓6%	19.	Gemini 3.1 Pro Preview by google	318B tokens ↓4%
10.	Step 3.5 Flash by stepfun	663B tokens ↓19%	20.	Gemini 3.1 Flash Lite Previ... by google	312B tokens ↑12%

- Recall: that a language model is a probability distribution **p(x)** over sequences of tokens.

> 回顾：语言模型是 token 序列上的概率分布 p(x)。

- Perplexity (1/p(D))^(1/|D|) measures whether p assigns high probability to some dataset D.

> 困惑度 (1/p(D))^(1/|D|) 度量 p 是否给某个数据集 D 分配了高概率。

- In pre-training, you minimize perplexity on the training set.

> 在预训练中，我们在训练集上最小化困惑度。

- The obvious thing is to measure perplexity on the test set.

> 显而易见的做法是在测试集上度量困惑度。

- This is what people did traditionally in language modeling research.

> 这正是传统语言建模研究的做法。

Standard datasets:

> 标准数据集：

- Penn Treebank (WSJ)
- WikiText-103 (Wikipedia)

> WikiText-103（维基百科）

- One Billion Word Benchmark (from machine translation WMT11 - EuroParl, UN, news)

> One Billion Word Benchmark（来自机器翻译 WMT11 - EuroParl、UN、新闻）

Classic paradigm: in-distribution evaluation: train on train split and evaluate on test split of some dataset.

> 经典范式：分布内评测：在某个数据集的训练 split 上训练，在其测试 split 上评测。

Pure CNNs+LSTMs on the One Billion Word Benchmark (perplexity 51.3 → 30.0) [Jozefowicz+ 2016]

> 在 One Billion Word Benchmark 上的纯 CNN+LSTM（困惑度 51.3 → 30.0） [Jozefowicz+ 2016]

GPT-2:

- Trained on WebText (40GB text, websites linked from Reddit)

> 在 WebText 上训练（40GB 文本，来自 Reddit 上被链接的网站）

- Zero-shot on standard datasets (**out-of-distribution** evaluation)

> 在标准数据集上做 zero-shot（分布外评测）

Language Models are Unsupervised Multitask Learners

	LAMBADA (PPL)	LAMBADA (ACC)	CBT-CN (ACC)	CBT-NE (ACC)	WikiText2 (PPL)	PTB (PPL)	enwik8 (BPB)	text8 (BPC)	WikiText103 (PPL)	1BW (PPL)
SOTA	99.8	59.23	85.7	82.3	39.14	46.54	0.99	1.08	18.3	**21.8**
117M	**35.13**	45.99	**87.65**	**83.4**	**29.41**	65.85	1.16	1.17	37.50	75.20
345M	**15.60**	55.48	**92.35**	**87.1**	**22.76**	47.33	1.01	**1.06**	26.37	55.72
762M	**10.87**	**60.12**	**93.45**	**88.0**	**19.93**	**40.31**	**0.97**	**1.02**	22.05	44.575
1542M	**8.63**	**63.24**	**93.30**	**89.05**	**18.34**	**35.76**	**0.93**	**0.98**	**17.48**	42.16

- Works better on small datasets (PTB) where transfer is helpful, but not larger datasets (1BW)

> 在迁移有所帮助的小数据集（PTB）上效果更好，但在更大的数据集（1BW）上则不然

Perplexity is all you need (more faith than science):

> Perplexity is all you need（与其说是科学，不如说是信仰）：

- True distribution is t, model is p.

> 真实分布是 t，模型是 p。

- Best possible perplexity is H(t) obtained iff p = t.

> 可能达到的最优困惑度是 H(t)，当且仅当 p = t 时取得。

- If p = t, then solve all the tasks: p(solution | problem)

> 若 p = t，则可解决所有任务：p(solution | problem)

- So by pushing down on perplexity, we will eventually "reach AGI".

> 所以只要把困惑度压下去，我们最终就会“实现 AGI”。

Perplexity is maybe more than you need:

> 困惑度也许超出了你的需要：

- Example: *Stanford was founded in 1885*

> 例如：斯坦福大学创立于 1885 年

- Perplexity penalizes prediction on all tokens, some (e.g., *founded*) of which might not be relevant

> 困惑度对所有 token 上的预测都施加惩罚，其中一些 token（如 founded）可能并不相关

- Solution: measure conditional perplexity p(response | prompt)^(1/|response|)

> 解决办法：度量条件困惑度 p(response | prompt)^(1/|response|)

Some benchmarks are perplexity in disguise:

> 有些 benchmark 不过是换了外衣的困惑度：

- Cloze tasks (fill in the blank): LAMBADA [Paperno+ 2016]

> 完形填空任务：LAMBADA [Paperno+ 2016]

---

(1) *Context:* “Yes, I thought I was going to lose the baby.” “I was scared too,” he stated, sincerity flooding his eyes. “You were ?” “Yes, of course. Why do you even ask?” “This baby wasn’t exactly planned for.”
Target sentence: “Do you honestly think that I would want you to have a _____ ?”
Target word: miscarriage

---

(2) *Context:* “Why?” “I would have thought you’d find him rather dry,” she said. “I don’t know about that,” said Gabriel. “He was a great craftsman,” said Heather. “That he was,” said Flannery.
Target sentence: “And Polish, to boot,” said _____.
Target word: Gabriel

---

(3) *Context:* Preston had been the last person to wear those chains, and I knew what I’d see and feel if they were slipped onto my skin-the Reaper’s unending hatred of me. I’d felt enough of that emotion already in the amphitheater. I didn’t want to feel anymore. “Don’t put those on me,” I whispered. “Please.”
Target sentence: Sergei looked at me, surprised by my low, raspy please, but he put down the _____.
Target word: chains


- Multiple choice sentence completion: HellaSwag [Zellers+ 2019]

> 多选题式句子补全：HellaSwag [Zellers+ 2019]



A woman is outside with a bucket and a dog. The dog is running around trying to avoid a bath. She…

A. rinses the bucket off with soap and blow dry the dog's head.
B. uses a hose to keep it from getting soapy.
C. gets the dog wet, then it runs away again.
D. gets into a bath tub with the dog.



Come to a complete halt at a stop sign or red light. At a stop sign, come to a complete halt for about 2 seconds or until vehicles that arrived before you clear the intersection. If you're stopped at a red light, proceed when the light has turned green. …

A. Stop for no more than two seconds, or until the light turns yellow. A red light in front of you indicates that you should stop.
B. After you come to a complete stop, turn off your turn signal. Allow vehicles to move in different directions before moving onto the sidewalk.
C. Stay out of the oncoming traffic. People coming in from behind may elect to stay left or right.
D. If the intersection has a white stripe in your lane, stop before this line. Wait until all traffic has cleared before crossing the intersection.

Warning (if you're running a perplexity leaderboard):

> 警告（如果你在运营一个困惑度排行榜）：

- People submit `LM` and you compute `log_prob = LM(test_data)`

> 人们提交 LM，你来计算 log_prob = LM(test_data)

- You need to trust that the probabilities are valid (sum to 1)

> 你需要相信这些概率是合法的（加和为 1）

- For downstream tasks, `response = LM(prompt)` and compute accuracy on `response`

> 对于下游任务，response = LM(prompt)，然后在 response 上计算准确率

Summary:

> 总结：

- Perplexity is still used heavily in language model development (smooth scaling laws)

> 困惑度在语言模型开发中仍被大量使用（平滑的缩放定律）

- Still need benchmarks that capture real-world situations (for the non-believers)…

> 仍然需要能捕捉真实世界情形的 benchmark（给不信的人）……

Exams are a useful way to test language models (as with humans):

> 考试是测试语言模型的一种有效方式（对人类也是如此）：

- Have control over the subject and difficulty

> 可以控制科目和难度

- Design to have unambiguous correct answer, easy to grade

> 设计成正确答案明确无歧义、易于评分

Massive Multitask Language Understanding (MMLU) [Hendrycks+ 2020]

> 大规模多任务语言理解（MMLU） [Hendrycks+ 2020]

- 57 subjects (e.g., math, US history, law, morality), multiple-choice

> 57 个科目（如数学、美国历史、法律、道德），多选题

- "collected by graduate and undergraduate students from freely available sources online"

> “由研究生和本科生从网上免费可得的来源收集”

- Despite the name, MMLU is really about testing knowledge, not language understanding

> 尽管名字如此，MMLU 实际考察的是知识，而非语言理解

- Evaluated on GPT-3 using few-shot prompting

> 在 GPT-3 上用 few-shot 提示进行评测


Few Shot Prompt and Predicted Answer

The following are multiple choice questions about high school mathematics.

How many numbers are in the list 25, 26, ..., 100?
(A) 75 (B) 76 (C) 22 (D) 23
Answer: B

Compute $i + i^2 + i^3 + \cdots + i^{258} + i^{259}$.
(A) -1 (B) 1 (C) i (D) -i
Answer: A

If 4 daps = 7 yaps, and 5 yaps = 3 baps, how many daps equal 42 baps?
(A) 28 (B) 21 (C) 40 (D) 30
Answer: C



[https://llm-stats.com/benchmarks/mmlu]

[HELM MMLU for visualizing predictions]

> [HELM MMLU，用于可视化预测]

MMLU-Pro [Wang+ 2024]

- Removed noisy/trivial questions from MMLU

> 从 MMLU 中移除有噪声/过于简单的题目

- Expanded 4 choices to 10 choices


> 把 4 个选项扩展为 10 个选项

- Evaluated using chain of thought (gives model more of a chance)

> 使用思维链（chain of thought）评测（给模型更多机会）

- Accuracy of models drop by 16% to 33% (not as saturated)

> 模型准确率下降 16% 到 33%（没那么饱和）



[https://llm-stats.com/benchmarks/mmlu-pro]

[HELM MMLU-Pro for visualizing predictions]


> [HELM MMLU-Pro，用于可视化预测]

Graduate-Level Google-Proof Q&A (GPQA) [Rein+ 2023]

> 研究生水平的防谷歌问答（GPQA） [Rein+ 2023]

- Questions written by 61 PhD contractors from Upwork

> 题目由来自 Upwork 的 61 位博士承包者撰写



- PhD experts achieve 65% accuracy

> 博士专家达到 65% 的准确率

- Non-experts achieve 34% over 30 minutes with access to Google

> 非专家在 30 分钟内且可使用 Google 的情况下达到 34%

- GPT-4 achieves 39%

> GPT-4 达到 39%

[https://llm-stats.com/benchmarks/gpqa]
[HELM GPQA for visualizing predictions]

> [HELM GPQA，用于可视化预测]

Humanity's Last Exam (HLE) [Phan+ 2025]

> Humanity's Last Exam（人类的最后考试，HLE） [Phan+ 2025]

- 2500 questions: multimodal, many subjects, multiple-choice + short-answer

> 2500 道题：多模态、众多学科、多选题 + 简答题

Classics

Question:



Here is a representation of a Roman inscription, orginally found on a tombstone. Provide a translation for the Palmyrene script.
A transliteration of the text is provided: RGYNᵓ BT HRY BR ᶜTᵓ HBL

Henry T
Merton College, Oxford

Ecology

Question:

Hummingbirds within Apodiformes uniquely have a bilaterally paired oval bone, a sesamoid embedded in the caudolateral portion of the expanded, cruciate aponeurosis of insertion of m. depressor caudae. How many paired tendons are supported by this sesamoid bone? Answer with a number.

Edward V
Massachusetts Institute of Technology

Mathematics

Question:
The set of natural transformations between two functors $F, G : C \to D$ can be expressed as the end

$$Nat(F, G) \cong \int_A Hom_D(F(A), G(A)).$$

Define set of natural cotransformations from F to G to be the coend

$$CoNat(F, G) \cong \int^A Hom_D(F(A), G(A)).$$

Let:
- $F = B_\bullet(\Sigma_4)_{*/}$ be the under ∞-category of the nerve of the delooping of the symmetric group Σ_4 on 4 letters under the unique 0-simplex $*$ of $B_\bullet\Sigma_4$.
- $G = B_\bullet(\Sigma_7)_{*/}$ be the under ∞-category nerve of the delooping of the symmetric group Σ_7 on 7 letters under the unique 0-simplex $*$ of $B_\bullet\Sigma_7$.

How many natural cotransformations are there between F and G?

Emily S
University of São Paulo

Computer Science

Question:
Let G be a graph. An edge-indicator of G is a function $a : \{0, 1\} \to V(G)$ such that $\{a(0), a(1)\} \in E(G)$.

Consider the following Markov Chain $M = M(G)$:
The statespace of M is the set of all edge-indicators of G, and the transitions are defined as follows:
Assume $M_t = a$.
1. pick $b \in \{0, 1\}$ u.a.r.
2. pick $v \in N(a(1-b))$ u.a.r. (here $N(v)$ denotes the open neighbourhood of v)
3. set $a'(b) = v$ and $a'(1-b) = a(1-b)$
4. Set $M_{t+1} = a'$

We call a class of graphs $\mathcal{G}$ well-behaved if, for each $G \in \mathcal{G}$ the Markov chain $M(G)$ converges to a unique stationary distribution, and the unique stationary distribution is the uniform distribution.

Which of the following graph classes is well-behaved?

Answer Choices:
A. The class of all non-bipartite regular graphs
B. The class of all connected cubic graphs
C. The class of all connected graphs
D. The class of all connected non-bipartite graphs
E. The class of all connected bipartite graphs.


Marc R
Queen Mary University of London


- Awarded $500K prize pool + co-authorship to question creators

> 为出题者提供 $500K 奖金池 + 共同作者身份

- Filtered by frontier LLMs, multiple stages of review

> 由前沿 LLM 过滤，并经过多轮评审





[https://llm-stats.com/benchmarks/hle]

Summary:

> 总结：

- Trend towards harder questions as models improve and saturate existing benchmarks

> 随着模型变强并在既有 benchmark 上趋于饱和，题目越来越难

- Multiple-choice format can be as difficult as one wants

> 多选题格式想要多难就能多难

- Does not capture real usage (open-ended, doesn't necessarily exist correct answer)

> 无法捕捉真实使用（开放式、不一定存在正确答案）

- So far, we've been evaluating on well-defined multiple-choice tasks.

> 到目前为止，我们都是在定义明确的多选题任务上做评测。

- Most people don't ask multiple-choice exam questions to their AI assistant.

> 大多数人并不会拿多选题考试题去问他们的 AI 助手。

Example:

> 示例：

Prompt: *I would like to make a beet salad with goat cheese. What kind of herbs would work well and what would not work well?*

> 提示词：我想做一份甜菜根配山羊奶酪的沙拉。哪些香草会比较搭，哪些不太搭?

Response: *Here’s a breakdown of herbs that work well (and some that don’t) in a beet + goat cheese salad, based on how their flavors interact with the sweet-earthiness of beets and the tangy creaminess of goat cheese...

> *下面梳理一下哪些香草适合（以及哪些不适合）甜菜根 + 山羊奶酪沙拉，依据是它们的风味如何与甜菜根的甜-土气息和山羊奶酪的酸-奶油质感相互作用.....

Challenge: how to evaluate an open-ended response?

> 挑战：如何评测开放式回复?

Chatbot Arena [Chiang+ 2024]

Data collection:

> 数据收集：

- Random person from the Internet types in prompt


> 互联网上的随机用户输入提示词

- They get response from two random (anonymized) models

> 他们收到来自两个随机（匿名化）模型的回复

- They rate which one is better

> 他们评判哪个更好



Compute ELO rankings based on pairwise comparisons:

> 基于成对比较计算 ELO 排名：

- Define model: p(A wins against B) = 1 / (1 + 10^((ELO_B - ELO_A)/400))

> 定义模型：p(A 战胜 B) = 1 / (1 + 10^((ELO_B - ELO_A)/400))

- Fit this model to maximize probability of pairwise comparisons

> 拟合该模型，使成对比较的概率最大化

[Arena AI (formerly Chatbot Arena)]

> [Arena AI（原 Chatbot Arena）]

Text — 4 days ago

Rank	Model	Score
1	claude-opus-4-7-thinking	1503
2	claude-opus-4-6-thinking	1502
3	claude-opus-4-6	1497
4	gemini-3.1-pro-preview	1493
5	claude-opus-4-7	1491
6	muse-spark	1491
7	gpt-5.5-high	1488
8	gemini-3-pro	1486
9	grok-4.20-beta1	1480
10	grok-4.20-beta-0309-reasoning	1477

Properties:

> 特性：

- Real-world prompts (free for users, incentives to actually use it)

> 真实世界的提示词（对用户免费，有真正去用的激励）

- But who are these people? biases? spammers?

> 但这些人都是谁？有没有偏见？有没有水军？

- Binary preference but conflates style and correctness

> 二元偏好，但把风格与正确性混为一谈

- How does the human even assess correctness? Prone to sycophancy?

> 人类究竟是如何评估正确性的？容易偏好谄媚式的回答？

- Feature: don't need to feed same prompts to all models (important because human is rating)

> 特性：不需要给所有模型喂相同的提示词（这点很重要，因为是人在打分）

- Dynamic: incorporates new prompts and models over time

> 动态：随时间不断纳入新的提示词与模型

AlpacaEval (2023)[leaderboard]

> AlpacaEval (2023)[排行榜]

- 805 instructions from various sources

> 来自多种来源的 805 条指令

- Metric: win rate against baseline model (GPT-4 preview) as judged by GPT-4 preview (potential bias?)

> 指标：以 GPT-4 preview 为评判、相对基线模型（GPT-4 preview）的胜率（潜在偏见？）

- Problem: LLM judges favor longer responses, resulted in leaderboard gaming

> 问题：LLM 评判偏爱更长的回复，导致排行榜被刷分

- Alpaca Eval 2.0 used regression to debias the metric [Dubois+ 2024]


> AlpacaEval 2.0 用回归为该指标去偏 [Dubois+ 2024]

- How do we evaluate the metric?

> 我们如何评测这个指标本身?

- Correlation with Chatbot Arena (humans) is high:

> 与 Chatbot Arena（人类）的相关性很高：



AlpacaEval Leaderboard

An Automatic Evaluator for Instruction-following Language Models

Length-controlled (LC) win rates alleviate length biases of GPT-4, but it may favor models finetuned on its outputs.

Version: AlpacaEval | AlpacaEval 2.0 Filter: Community | Verified

Baseline: GPT-4 Preview (11/06) | Auto-annotator: GPT-4 Preview (11/06)

Rank	Model Name	LC Win Rate	Win Rate
1	GPT-4 Omni (05/13)	57.5%	51.3%
2	GPT-4 Turbo (04/09)	55.0%	46.1%
3	Yi-Large Preview	51.9%	57.5%
4	GPT-4o Mini (07/18)	50.7%	44.7%
5	GPT-4 Preview (11/06)	50.0%	50.0%
6	Claude 3 Opus (02/29)	40.5%	29.1%
7	Llama 3.1 405B Instruct	39.3%	39.1%
8	GPT-4	38.1%	23.6%
9	Qwen2 72B Instruct	38.1%	29.9%
10	Llama 3.1 70B Instruct	38.1%	39.1%

WildBench [Lin+ 2024]

- Sourced 1024 examples from 1M human-chatbot conversations


> 从 100 万段人机对话中选取 1024 个示例

- Uses GPT-4 turbo as a judge with a checklist (like CoT for judging) + GPT-4 as a judge

> 使用带检查清单的 GPT-4 turbo 做评判（类似评判用的 CoT）+ 用 GPT-4 做评判

- Well-correlated with Chatbot Arena (seems to be the de facto sanity check)

> 与 Chatbot Arena 高度相关（这似乎已成为事实上的 sanity check）



[HELM WildBench for visualizing predictions]

> [HELM WildBench，用于可视化预测]

Summary:

> 总结：

- Challenge: how to evaluate open-ended responses?

> 挑战：如何评测开放式回复？

- Pairwise comparisons between similar responses provide higher signal

> 对相似回复做成对比较能提供更高的信号

- Beware of biases (both from humans and LLM judges)

> 警惕偏见（人类和 LLM 评判的偏见都要防）

- Checklist/rubric improves reliability (regardless of human or LLM judge)

> 检查清单/评分细则能提升可靠性（无论人类还是 LLM 评判）

Previously: evaluate what LMs say (chat)

> 之前：评测语言模型说什么（聊天）

Now: evaluate what LMs do (agents)

> 现在：评测语言模型做什么（智能体）

Agent = language model + agent scaffold (logic for deciding how to use the LM)

> 智能体 = 语言模型 + 智能体脚手架（决定如何使用语言模型的逻辑）

Consider tasks that require tool use (e.g., running code) and iterating over a period of time

> 考虑需要使用工具（如运行代码）并在一段时间内迭代的任务

SWEBench [Jimenez+ 2023]

- 2294 tasks across 12 Python repositories

> 覆盖 12 个 Python 代码库的 2294 个任务

- Given codebase + issue description, submit a PR

> 给定代码库 + issue 描述，提交一个 PR

- Evaluation metric: unit tests

> 评测指标：单元测试

Model Input

▼ **Instructions** • 1 line

You will be provided with a partial code base and an issue statement explaining a problem to resolve.

▼ **Issue** • 67 lines

napoleon_use_param should also affect "other parameters" section Subject: napoleon_use_param should also affect "other parameters" section

Problem

Currently, napoleon always renders the Other parameters section as if napoleon_use_param was False, see source

```
def _parse_other_parameters_section(self, se...
    # type: (unicode) -> List[unicode]
    return self._format_fields(_('Other Para...

def _parse_parameters_section(self, section):
    # type: (unicode) -> List[unicode]
    fields = self._consume_fields()
    if self._config.napoleon_use_param: ...
```

▼ **Code** • 1431 lines

► **README.rst** • 132 lines

► **sphinx/ext/napoleon/docstring.py** • 1295 lines

► **Additional Instructions** • 57 lines

Gold Patch

sphinx/ext/napoleon/docstring.py

```
    def _parse_other_parameters_section(self, section: str) -> List[str]:
-       return self._format_fields(_('Other Parameters'), self._consume_fields())
+       if self._config.napoleon_use_param:
+           # Allow to declare multiple parameters at once (ex: x, y: int)
+           fields = self._consume_fields(multiple=True)
+           return self._format_docutils_params(fields)
+       else:
+           fields = self._consume_fields()
+           return self._format_fields(_('Other Parameters'), fields)
```

Generated Patch

sphinx/ext/napoleon/docstring.py

```
    def _parse_other_parameters_section(self, section: str) -> List[str]:
-       return self._format_fields(_('Other Parameters'), self._consume_fields())
+       return self._format_docutils_params(self._consume_fields())
```


Generated Patch Test Results

```
PASSED  NumpyDocstringTest (test_yield_types)
PASSED  TestNumpyDocstring (test_escape_args_and_kwargs 1)
PASSED  TestNumpyDocstring (test_escape_args_and_kwargs 2)
PASSED  TestNumpyDocstring (test_escape_args_and_kwargs 3)
PASSED  TestNumpyDocstring (test_pep526_annotations)
FAILED  NumpyDocstringTest (test_parameters_with_class_reference)
FAILED  TestNumpyDocstring (test_token_type_invalid)
===== 2 failed, 45 passed, 8 warnings in 5.16s =====
```

[https://llm-stats.com/benchmarks/swe-bench-verified]

TerminalBench [Merrill+ 2026][website]

> TerminalBench [Merrill+ 2026][网站]



- Computer terminal environments: simple and universal

> 计算机终端环境：简单且通用

- 229 tasks crowdsourced from 93 contributors, 89 tasks constitute Terminal-Bench 2.0


> 由 93 位贡献者众包的 229 个任务，其中 89 个任务构成 Terminal-Bench 2.0

	<1 hour	1 hour – 1 day (24h)	1 day (24h) – 1 week (168h)	>1 week (168h)
Expert	36 (48.6%)	35 (47.3%)	3 (4.1%)	0 (0.0%)
Junior	6 (8.1%)	53 (71.6%)	12 (16.2%)	3 (4.1%)

Rank	Agent	Model	Date	Agent Org	Model Org	Accuracy
1 ✓	Codex CLI	GPT-5.5	2026-04-23	OpenAI	OpenAI	**82.0%** ± 2.2
2	ForgeCode	GPT-5.4	2026-03-12	ForgeCode	OpenAI	**81.8%** ± 2.0
3	TongAgents	Gemini 3.1 Pro	2026-03-13	BIGAI	Google	**80.2%** ± 2.6
4	ForgeCode	Claude Opus 4.6	2026-03-12	ForgeCode	Anthropic	**79.8%** ± 1.6
5	SageAgent	GPT-5.3-Codex	2026-03-13	OpenSage	OpenAI	**78.4%** ± 2.2
6	ForgeCode	Gemini 3.1 Pro	2026-03-02	ForgeCode	Google	**78.4%** ± 1.8
7	Droid	GPT-5.3-Codex	2026-02-24	Factory	OpenAI	**77.3%** ± 2.2
8	Capy	Claude Opus 4.6	2026-03-12	Capy	Anthropic	**75.3%** ± 2.4
9 ✓	Simple Codex	GPT-5.3-Codex	2026-02-06	OpenAI	OpenAI	**75.1%** ± 2.4
10	Terminus-KIRA	Gemini 3.1 Pro	2026-02-23	KRAFTON AI	Google	**74.8%** ± 2.6

[https://llm-stats.com/benchmarks/terminal-bench]

CyBench [Zhang+ 2024]




- 40 Capture the Flag (CTF) tasks

> 40 个夺旗（CTF）任务

- Use first-solve time as a measure of difficulty

> 用首次解出时间作为难度的度量




Model	Unguided % Solved	Subtask-Guided % Solved	Subtasks % Solved	Most Difficult Task Solved (First Solve Time by Humans)	
				Unguided	Subtask-Guided
Claude Mythos Preview [6]	100%	--	--	--	--
Claude Opus 4.7 [8]	96%	--	--	--	--
Claude Opus 4.6 [5]	93%	--	--	--	--
Claude Opus 4.5 [3]	82%	--	--	--	--
Muse Spark [7]	65.4%	--	--	--	--
Claude Sonnet 4.5 [3]	60%	--	--	--	--
Grok 4 [4]	43%	--	--	--	--
Claude Opus 4.1 [3]	42%	--	--	--	--
Grok 4.1 Thinking [4]	39%	--	--	--	--
Claude Opus 4 [2]	38%	--	--	--	--
Claude Sonnet 4 [2]	35%	--	--	--	--
Grok 4 Fast [4]	30%	--	--	--	--
OpenAI o3-mini [1]†	22.5%	--	--	42 min	--
Claude 3.7 Sonnet [1]	20%	--	--	11 min	--
GPT-4.5-preview [1]	17.5%	--	--	11 min	--
Claude 3.5 Sonnet	17.5%	15%	43.9%	11 min	11 min
GPT-4o	12.5%	17.5%	28.7%	11 min	52 min
OpenAI o1-mini [1]†	10%	--	--	11 min	--
Claude 3 Opus	10%	12.5%	36.8%	11 min	11 min
OpenAI o1-preview	10%	10%	46.8%	11 min	11 min
Llama 3.1 405B Instruct	7.5%	15%	20.5%	9 min	11 min
Mixtral 8x22b Instruct	7.5%	5%	15.2%	9 min	7 min
Gemini 1.5 Pro	7.5%	5%	11.7%	9 min	6 min
Llama 3 70b Chat	5%	7.5%	8.2%	9 min	11 min

[https://llm-stats.com/benchmarks/cybench]

MLEBench [Chan+ 2024]

- 75 Kaggle competitions (require training models, processing data, etc.)


> 75 个 Kaggle 竞赛（需要训练模型、处理数据等）



AGENT	LLM	LOW/LITE	MEDIUM	HIGH	OVERALL	TIME	DATE	REPORTS	SOURCE
Famou-Agent 2.0	Gemini-3-Pro-Preview	80.3 ± 1.52	64.04 ± 2.32	42.22 ± 2.22	**64.44 ± 1.18**	24h	2026-02-23	-	Available
AIBuildAI	Claude-Opus-4.6	77.27 ± 0.00	61.40 ± 0.88	46.67 ± 0.00	**63.11 ± 0.44**	24h	2026-03-06	-	Available
CAIR MARS+	Gemini-3-Pro-Preview	78.79 ± 1.52	60.53 ± 1.52	44.44 ± 2.22	**62.67 ± 0.77**	24h	2026-02-17	-	Available
MLEvolve	Gemini-3-Pro-Preview	80.30 ± 1.52	57.89 ± 1.52	42.22 ± 2.22	**61.33 ± 1.33**	12h	2026-02-14	Available	Available
PiEvolve (Fractal AI Research)	Gemini-3-Pro-Preview	80.30 ± 1.52	58.77 ± 0.88	40.0 ± 0.00	**61.33 ± 0.77**	24h	2026-01-05	-	Available
Famou-Agent 2.0	Gemini-2.5-Pro	75.76 ± 1.52	57.89 ± 1.52	40.00 ± 0.00	**59.56 ± 0.89**	24h	2025-12-27	-	Available
ML-Master 2.0	Deepseek-V3.2-Speciale	75.76 ± 1.51	50.88 ± 3.51	42.22 ± 2.22	**56.44 ± 2.47**	24h	2025-12-16	-	Available
CAIR MARS	Gemini-3-Pro-Preview	74.24 ± 1.52	52.63 ± 3.04	37.78 ± 2.22	**56.0 ± 1.54**	24h	2026-01-25	-	Available
PiEvolve (Fractal AI Research)	Gemini-3-Pro-Preview	74.24 ± 3.03	45.61 ± 0.88	35.55 ± 2.22	**52.0 ± 0.77**	12h	2026-01-05	-	Available

Agent scaffolds [post]

> 智能体脚手架 [帖子]



- Explicit planning: keep a todo list that gets checked off

> 显式规划：维护一份可以逐项勾掉的待办清单

- Hierarchical delegation: agents calling other sub-agents (clean context)

> 分层委派：智能体调用其他子智能体（干净的上下文）

- Persistent memory: read/write files

> 持久记忆：读/写文件

- Extreme context engineering: explicit more instructions on process

> 极致的上下文工程：对流程给出更明确的指示

Summary:

> 总结：

- Agents dramatically enhance the capability surface of language models

> 智能体极大地扩展了语言模型的能力面

- Agent scaffolds are very important

> 智能体脚手架非常重要

- Evaluating agents = evaluating agent scaffold + language model

> 评测智能体 = 评测智能体脚手架 + 语言模型

- All of the tasks so far require linguistic and world knowledge.

> 到目前为止的所有任务都依赖语言知识和世界知识。

- Can we isolate **reasoning** from knowledge?

> 我们能把推理与知识分离开来吗?

- Arguably, reasoning captures a more pure form of intelligence (isn't just about memorizing facts).

> 可以说，推理捕捉的是一种更纯粹的智能形式（不只是记住事实）。

ARC-AGI [website]

> ARC-AGI [网站]

- 100% solvable by humans, but challenging for AI


> 人类可 100% 解出，但对 AI 有挑战

- Each task is unique, so memorization doesn't help.

> 每个任务都是独一无二的，死记硬背帮不上忙。

- ARC-AGI-1 (2019): first iteration


> ARC-AGI-1（2019）：第一版



- ARC-AGI-2 (March 2025): more multi-step reasoning

> ARC-AGI-2（2025 年 3 月）：更多多步推理





- Pretrained language models didn't move the needle

> 预训练语言模型没能让成绩有起色

- Reasoning models (o1, o3) started making things take off

> 推理模型（o1、o3）开始让成绩起飞

- ARC-AGI-3 (March 2026): interactive environments [post]

> ARC-AGI-3（2026 年 3 月）：交互式环境 [帖子]



Provider	Model	Score
Anthropic	Opus 4.6 (Max)	0.50%
Google	Gemini 3.1 Pro Preview	0.40%
OpenAI	GPT 5.4 (High)	0.20%
xAI	Grok-4.20 (Beta 0309 Reasoning)	0.10%

Summary:

> 总结：

- Goal is to disentangle reasoning from knowledge (difficult to do!)

> 目标是把推理与知识解耦（这很难做到！）

- Constrained to human reasoning (not superhuman reasoning)

> 限定于人类推理（而非超人类推理）

- Clearly exposes gaps in current models

> 清晰地暴露当前模型的短板



What does safety mean for AI?

> 对 AI 而言，安全意味着什么?

HarmBench [Mazeika+ 2024]

- Based on 510 harmful behaviors that violate laws or norms

> 基于 510 种违反法律或规范的有害行为

[HarmBench on HELM]

> [HELM 上的 HarmBench]

[Example of safety failure]

> [安全失效示例]


AIR-Bench [Zeng+ 2024]

- Based on regulatory frameworks and company policies

> 基于监管框架与公司政策

- Taxonomized into 314 risk categories, 5694 prompts

> 按分类体系划分为 314 个风险类别、5694 条提示词



[HELM AIR-Bench]

Jailbreaking:

> 越狱：

- Language models are trained to refuse harmful instructions


> 语言模型经训练后会拒绝有害指令

- Greedy Coordinate Gradient (GCG) automatically optimizes prompts to bypass safety [Zou+ 2023]

> Greedy Coordinate Gradient（GCG）自动优化提示词以绕过安全防护 [Zou+ 2023]

- Transfers from open-weight models (Llama) to closed models (GPT-4)

> 可从开源权重模型（Llama）迁移到闭源模型（GPT-4）



What is safety?

> 什么是安全?

- Many aspects of safety are strongly contextual (politics, law, social norms - which vary across countries)

> 安全的许多方面高度依赖语境（政治、法律、社会规范——各国不尽相同）

- Many risks are quite varied (hallucinations, sycophancy, abetting crimes, inequality, losing critical thinking)

> 风险也非常多样（幻觉、谄媚、协助犯罪、不平等、丧失批判性思维）

Dual-use: capable cybersecurity agents (Mythos) can be used to hack into a system or to do penetration testing

> 双重用途：强大的网络安全智能体（Mythos）既能用来入侵系统，也能用来做渗透测试

Ecological validity: how well does an evaluation capture real-world use?

> 生态效度：一项评测对真实世界使用场景的捕捉程度如何?

- Exam benchmarks (e.g., GPQA) are far away from real-world use.

> 考试类 benchmark（如 GPQA）离真实使用很远。

- Chatbot Arena prompts are from real people, but distribution is uncontrolled.

> Chatbot Arena 的提示词来自真实用户，但分布不受控。


GDPVal (OpenAI) [Patwardhan+ 2025]

- 44 occupations from top 9 sectors according to US GDP

> 来自按美国 GDP 排名前 9 的行业的 44 种职业

- Tasks come from professionals with ~14 years of experience

> 任务来自拥有约 14 年经验的专业人士




MedHELM [Bedi+ 2025]

- Previous medical benchmarks were based on standardized exams

> 以往的医疗 benchmark 基于标准化考试

- 121 clinical tasks sourced from 29 clinicians, mixture of private and public datasets

> 121 个临床任务，来自 29 位临床医生，私有与公开数据集混合



[MedHELM]


Clio (Anthropic) [Tamkin+ 2024]

- Use language models to analyze real user data

> 用语言模型分析真实用户数据

- Share general patterns of what people are asking

> 分享人们在问什么的一般性模式



Unfortunately, realism and privacy are sometimes at odds with each other.

> 遗憾的是，真实性与隐私有时会相互冲突。

How do we know our evaluations are valid?

> 我们如何知道自己的评测是有效的?

Train-test overlap

> 训练-测试重叠

- Machine learning 101: don't train on your test set

> 机器学习 101：不要在测试集上训练

- Pre-foundation models (ImageNet, SQuAD): well-defined train-test splits

> 基础模型出现之前（ImageNet、SQuAD）：定义良好的训练-测试划分

- Today: train on the Internet and don't tell people about your data


> 如今：在互联网上训练，而且不透露你的数据

Route 1: try to infer train-test overlap from model

> 路线 1：尝试从模型推断训练-测试重叠

- Exploit exchangeability of data points [Oren+ 2023]

> 利用数据点的可交换性 [Oren+ 2023]



Route 2: encourage reporting norms (e.g., people report confidence intervals)

> 路线 2：鼓励报告规范（例如让人们报告置信区间）

- Model providers should report train-test overlap [Zhang+ 2024]

> 模型提供方应报告训练-测试重叠 [Zhang+ 2024]

Route 3: use fresh evals

> 路线 3：使用新推出的评测

- LiveCodeBench, UncheatableEval: scrape new webpages

> LiveCodeBench、UncheatableEval：抓取新网页

- Timestamps aren't always safe due to copying either

> 而且由于内容会被转载，时间戳也并不总是安全

Route 4: use private evals

> 路线 4：使用私有评测

- Companies use internal code bases that aren't on the Internet

> 公司使用不在互联网上的内部代码库

- Use your personal writings

> 使用你个人的写作

- Easiest for perplexity

> 对困惑度来说最容易

Dataset quality

> 数据集质量

- Fixed up SWE-Bench to produce SWE-Bench Verified [post]

> 修正 SWE-Bench 得到 SWE-Bench Verified [帖子]

- Create Platinum versions of benchmarks [Vendrow+ 2025]

> 为 benchmark 制作 Platinum 版本 [Vendrow+ 2025]

(a) Mislabeled question, *SVAMP*

Question: You had 14 bags with equal number of cookies. If you had 28 cookies and 86 candies in total, how many bags of cookies do you have?
Solution: 2

There are 14 bags, not 2.

(b) Logical contradiction, *GSM8K*

Ten stalls have 20 cows each. Mr. Sylas buys 40 cows and divides them equally, putting an equal number of the new cows into each of the twenty stalls. How many cows are in 8 of the stalls?

There are both ten and twenty stalls.

(c) Ambiguity, *VQA v2.0*



Question: Does the baby have socks on?[2]

There is no way to tell.

(d) Clear flaw / ill-posed, *MMLU HS Math*

A curve is given parametrically by the equations
Options:
A) $\pi/2$ B) π C) $2+\pi$ D) 2π

The equations for the curve are missing.

	SingleOp	SingleEq	MultiArith	SVAMP	GSM8K	MMLU HS Math	Logic Ded. 3-Obj	Object Counting	Navigate	TabFact	HotpotQA	SQuAD2.0	DROP	Winograd WSC
Avg # errors, original	2.5	1.1	3.5	18.8	10.1	20.5	2.4	6.3	5.9	17.3	26.4	56.2	28.4	16.6
Avg # errors, cleaned	0.3	0.1	0.4	4.3	5.2	19.5	2.4	4.8	5.9	4.3	2.3	9.9	6.6	15.0
% errors caused by benchmark errors	90%	93%	89%	77%	48%	5%	0%	24%	0%	75%	91%	82%	77%	10%

- Problems with agentic benchmarks: insufficient test cases, trivial agent can solve task [Zhu+ 2025]

> 智能体 benchmark 的问题：测试用例不足，平凡的智能体就能解决任务 [Zhu+ 2025]

- Docent: use LLM to inspect agent traces to detect problems [post]

> Docent：用 LLM 检查智能体轨迹来发现问题 [帖子]

What's the point of evaluation?

> 评测的意义何在?

There is no one true evaluation; it depends on what question you're trying to answer.

> 不存在唯一正确的评测；这取决于你想回答什么问题。

1. User or company wants to make a purchase decision (model A or model B) for their use case (e.g., customer service chatbots).

> 用户或公司想为自己的使用场景（如客服聊天机器人）做采购决策（选模型 A 还是模型 B）。

2. Researchers want to measure the raw capabilities of a model (e.g., intelligence).

> 研究者想测量一个模型的原始能力（例如智能）。

3. We want to understand the benefits + harms of a model (for business and policy reasons).

> 我们想理解一个模型的收益 + 危害（出于商业和政策原因）。

4. Model developers want to get feedback to improve the model.

> 模型开发者想获得反馈以改进模型。

What are we evaluating?

> 我们在评测什么?

- Pre-foundation models, we evaluated **methods** (standardized train-test splits).

> 基础模型出现之前，我们评测的是方法（标准化的训练-测试划分）。

- Today, we're (mostly) evaluating **models/systems** (anything goes).


> 如今，我们（主要）评测的是模型/系统（怎么做都行）。

There are some exceptions...

> 也有一些例外.....

- nanogpt speedrun: fixed data, compute time to get to a particular validation loss

> nanogpt speedrun：固定数据，以达到特定验证损失所需的计算时间为指标



[post]

Evaluating methods encourage algorithmic innovation from researchers.

> 评测方法能鼓励研究者做算法创新。

Evaluating models/systems is useful for downstream users.

> 评测模型/系统对下游用户有用。

Either way, we need to define the rules of the game!

> 无论哪种，我们都需要把游戏规则定义清楚！