Telegram Mini App and bot

English version of ../TELEGRAM_BOT.md.

Telegram features are disabled by default. To enable them, create a bot through BotFather and set in `.env`:

```
AEZA_TELEGRAM_BOT_ENABLED=1
AEZA_TELEGRAM_BOT_TOKEN=...
AEZA_TELEGRAM_WEBHOOK_SECRET=...
AEZA_TELEGRAM_MINI_APP_URL=https://app.example.com/mini-app
AEZA_TELEGRAM_WEBHOOK_URL=https://app.example.com/api/v1/telegram/webhook
```

The webhook must be reachable at a public HTTPS address. A one-time code e-mail is sent only when a mail provider is configured; see the e-mail guide (EMAIL.md).

After the API starts, register the webhook with an authorised request:

```
curl -X POST http://localhost:8000/api/v1/telegram/webhook/register -H "Authorization: Bearer $ACCESS_TOKEN"
```

The state is available through `GET /api/v1/telegram/diagnostics`. The remaining parameters, including session and one-time-code lifetimes, are listed in `.env.example`.

Mini App

After entering the e-mail and the code the bot offers to enable reminders and shows a button to open the Mini App. On the first open the Telegram Mini App exchanges the signed Telegram data for a client session automatically — no code needs to be entered again. The Mini App offers account data, services, reminder settings and a support conversation. An open support screen refreshes every 10 seconds.