Module map: what to borrow for another project

English version of ../../modules/module-map.md.

The table answers "what to take if I need X": the minimal set of files, the dependencies, and what has to be replaced.

Need	Files to take	External dependencies	Replace
Risk and revenue computation without I/O	`backend/app/domain/` (`risk.py`, `revenue.py`, `money.py`, `provenance.py`)	—	the factor set and the rules
Money without float	`backend/app/domain/money.py`	—	currency and precision
Provenance of numbers	`backend/app/domain/provenance.py`	—	the source-reference format
Schema application and migrations	`backend/app/schema.py`	SQLAlchemy	the migration registry
JWT authentication in a separate database	`backend/auth/`, `backend/auth_schema.sql`	`PyJWT[crypto]`	tables and roles
A tool layer for LLMs	`backend/app/ai/tools/`	`httpx`	the tools themselves
An LLM provider with a mock implementation	`backend/app/ai/providers/`	`httpx`	the call and the response parsing
Prometheus metrics per route	`backend/app/metrics.py`	`prometheus_client`	the metric list
Token-protected snapshot ingestion	`backend/app/api/routes_source.py`	FastAPI	the snapshot format
Adapters for external channels	`backend/app/integrations/`, `backend/app/telegram/`	SMTP, Telegram API	the providers

Transfer rules

1. The domain knows nothing about HTTP, databases or the network — it can be taken whole and tested without containers.
2. Adapters (`providers`, `integrations`) hide an external system behind an interface: the implementation is replaced, not the calling code.
3. Tests are part of the module: domain → `backend/tests/test_domain.py`, auth → `tests/test_auth.py`, AI → `backend/tests/test_ai.py`.
4. Configuration goes through `backend/app/config.py` (`Settings`) only, with safe defaults.

What is not here

- No ORM domain models: data is read from a snapshot, not row by row from tables.
- No task queue: background recalculations live in the process.