Deployment

English version of ../../operations/deployment.md.

The main path is Docker Compose (`docker-compose.yml`, the `./run.sh` helper or `make compose-up`). Detailed upgrade and backup steps are in the existing DEPLOYMENT_PART_B.md; this page is a checklist.

Procedure

```
cp .env.example .env
# mandatory: POSTGRES_PASSWORD (compose deliberately fails without it)
make doctor
make compose-up
make smoke-test API_URL=http://localhost:8000
make create-user EMAIL=analyst@example.com
```

UI: `http://localhost:8080`, API: `http://localhost:8000/api/v1/docs`.

Decisions required before production

1. **Secrets.** `POSTGRES_PASSWORD`, `AUTH_PRIVATE_KEY` (JWT), `AEZA_SOURCE_INGEST_TOKEN`, `AEZA_METRICS_TOKEN`, `AEZA_TELEGRAM_WEBHOOK_SECRET`. None has a production-grade default.
2. **Fail closed.** Compose requires `POSTGRES_PASSWORD` (`:?`) — checked by a dedicated CI job. Do not weaken this protection.
3. **TLS.** `AUTH_COOKIE_SECURE=true` and HTTPS termination at the proxy.
4. **CORS.** `AEZA_CORS_ORIGINS` — an explicit list, not `*`.
5. **Backups.** Two databases mean two backups: PostgreSQL and SQLite (`AUTH_DATABASE`). `make backup` covers both; the restore check runs in CI.
6. **AI.** `AEZA_AI_ENABLED=0` by default. Enable it deliberately: it is an external call with a timeout up to `AEZA_AI_TIMEOUT_SECONDS` (420 s by default).

Role separation

Role	Ports	Access
`web` (nginx + static)	8080	public
`api` (FastAPI)	8000	internal only, reached through web or a proxy
`db` (PostgreSQL)	5432	internal only

Do not publish `api` directly: `/metrics` and service routes are protected by a token, but a network boundary is cheaper than trusting configuration.

After deployment

```
make smoke-test API_URL=http://localhost:8000
./scripts/smoke-test.sh http://localhost:8080   # through web or the proxy
```