Data storage

English version of ../database.md.

SQLite, path from `DB_PATH` (default `data.db`). The schema is created at start-up idempotently: `CREATE TABLE IF NOT EXISTS` plus `ALTER TABLE ... ADD COLUMN` inside `try/except`. All of it lives in `app/db.py`.

Tables

Table	Contents	Owner
`users`	phone, nickname, password hash, role	authentication
`sessions`	session token, user, expiry	authentication
`quiz_submissions`	quiz request (contacts, room parameters, status)	quiz/admin

Rules

1. **Passwords are stored hashed only** (`hash_password`), at least 8 characters and at least one letter (`validate_password`) — enforced by tests.
2. **A session is an HttpOnly cookie** `session_id`, `SameSite=lax`, 7 days.
3. **The role changes only through admin sign-in with a code from the environment**; without `ADMIN_CODE` the route answers 503 (fail closed).
4. **Tests never touch the production database**: `DB_PATH` points to a temporary file.

Backup

```
sqlite3 data.db ".backup 'backups/interio-$(date -u +%Y%m%dT%H%M%SZ).db'"
```

Restore: stop the application, replace the file, start it, run `make smoke-test`. On Render use a disk or re-create the database from the request export.

Verification

Claim	How it is checked
The schema is created on an empty database	every test boots the app on an empty `DB_PATH`
Re-running the initialisation is safe	`init_db()` runs on every start and in tests
The password is never stored in clear text	`tests/test_auth.py` and review of `hash_password`