Module map: what to borrow for another project

Russian version: ../ru/modules/module-map.md.

The table answers "what to take if I need X": the minimal set of files, the dependencies, and what has to be replaced. The module specifications are in capture.md and protocol.md.

Need	Files to take	External dependencies	Replace
PCAP/PCAPNG and TCP session parsing	`src/capture/parser.py`, `src/capture/session.py`	`dpkt`	the list of supported link layers
Stream reassembly with gap and overlap diagnostics	`src/capture/reassembly.py`, `src/capture/fragment.py`	—	the policy for conflicting overlaps
Byte-to-packet provenance	`src/capture/provenance.py`, `src/capture/stream.py`	—	the "offset → packet" index model
A normalised JSON contract between stages	`src/capture/export_*.py`, `docs/schemas/`	`jsonschema` (for validation)	the contract field set
Message framing (4 strategies)	`src/protocol/framing.py`	—	your own boundary strategies
A declarative rule engine with field types	`src/protocol/engine.py`, `src/protocol/rule.py`	`PyYAML`	the type and operator sets
Result classification and counterexamples	`src/hypothesis/`	—	the `matched`/`mismatched` criteria
Rule versioning and version comparison	`src/hypothesis/versioning.py`	—	the version storage scheme
A portable project with a manifest and sha256	`src/project/`	stdlib (`zipfile`, `sqlite3`)	the manifest contents
Reports in Markdown and self-contained HTML	`src/report/`	—	the template and the section set
A hex view linked to packets	`src/ui/hex_view.py`	PySide6	— (the widget is self-contained)
A local web interface over the same engines	`src/web/`	FastAPI, uvicorn, Jinja2	the page templates
Bilingual documentation with parity	`tools/docs_pdf.py`, `Makefile` (`docs-check`)	markdown, weasyprint	the document set and the languages

Transfer rules

1. The core (`capture`, `protocol`, `hypothesis`, `project`, `report`) depends on neither Qt nor the network: it can be taken whole and verified with `make test-core` without graphics.
2. An external system always sits behind an adapter: `dpkt` is isolated in `parser.py` and the file storage in `project/storage.py`; the implementation is replaced, not the calling code.
3. The "fact ≠ hypothesis" invariant is part of the contract: a rule application result carries a status and a byte linkage, so it cannot be "improved" silently.

4. Tests are part of the module: every module has a directory of the same name under `tests/`.
5. Application settings are one dialogue and one key set (docs/SETTINGS.md), with no "magic" environment variables.