API error code catalogue

English version of ../ERROR_CODES.md. Requirement NFT-3 of the specification: errors must have stable codes so the frontend can show a clear message by code, not only by HTTP status.

Error response format:

```
{
  "detail": "Human-readable message",
  "code": "MACHINE_READABLE_CODE"
}
```

Code	HTTP	When it occurs	Example message
AUTH_INVALID_CREDENTIALS	401	Wrong e-mail or password	"Wrong e-mail or password"
AUTH_TOKEN_EXPIRED	401	The JWT expired or is malformed	"The session has expired, sign in again"
FORBIDDEN_ROLE	403	The role lacks the rights	"Insufficient permissions"
ACCOUNT_DISABLED	403	The account is disabled	"The account is disabled"
RESOURCE_NOT_FOUND	404	The entity was not found	"University not found"
STATUS_HAS_ACTIVE_REQUESTS	409	Deleting a stage that has requests	"The stage has N interactions. Specify a transfer"
DUPLICATE_INTERACTION	409	A duplicate university/product pair	"This interaction is already registered"
DUPLICATE_VUZ_NAME	409	A duplicate university on import	"The university already exists"
MAX_PARALLEL_INTERACTIONS	409	More than 2 active interactions for a university	"The university already has 2 active interactions"
WORKFLOW_SCOPE_MISMATCH	409	A stage from another workflow	"The stage belongs to another workflow"
VALIDATION_FAILED	422	A Pydantic schema error	"Field X is required"
IMPORT_FILE_CORRUPTED	422	Broken encoding or file structure	"The file is corrupted, check the encoding"
RATE_LIMITED	429	The sign-in attempt limit was exceeded	"Too many attempts, try again in a minute"
INTERNAL_ERROR	500	An unexpected error	"Internal error, try again later"

Implementation

- MAX_PARALLEL_INTERACTIONS and WORKFLOW_SCOPE_MISMATCH are returned in backend/api/interactions.py.
- RATE_LIMITED — in backend/middleware/rate_limit.py.
- VALIDATION_FAILED — the global RequestValidationError handler in backend/main.py.