Module map: what to borrow for another project

English version of ../../modules/module-map.md.

The table answers "what to take if I need X": the minimal set of files, the dependencies, and what has to be replaced. The specifications of the individual modules are in interactions.md, reports.md, integrations.md.

Need	Files to take	External dependencies	Replace
A Kanban workflow with stages and task transfer on stage deletion	`backend/api/stages.py`, `backend/api/interactions.py`, `frontend/src/components/kanban/`, `frontend/src/hooks/useStages.ts`	dnd-kit	the stage set and the `scope` rule
An audit of modifying operations (152-FZ, FSTEC No. 117)	`backend/middleware/audit.py`, `backend/api/audit.py`	SQLAlchemy	the list of redacted fields
RBAC and a single object-level access check by id	`backend/auth/security.py`, `backend/api/access.py`	python-jose, passlib	the roles and the visibility rule
Keycloak sign-in (OIDC + PKCE, RS256/JWKS)	`backend/auth/keycloak.py`, `keycloak/realm-export.json`	Keycloak	the realm, the client, the role mapping
Security headers and CORS without a wildcard	`backend/middleware/security_headers.py`, `backend/main.py` (CORS)	FastAPI	the origin list
Sign-in attempt limiting	`backend/middleware/rate_limit.py`	Redis (optional)	the limit and the window
XLS/XLSX/JSON import with dialogue-based column mapping	`backend/services/excel_import.py`, `backend/services/import_report.py`, `frontend/src/pages/DirectoryPage.tsx`	openpyxl, xlrd, jsonschema	the reference-data schema
Report export to XLSX/XLS/PDF/JSON from one column config	`backend/services/excel_export.py`, `backend/services/report_columns.py`, `config/report_columns.json`	openpyxl, xlwt, reportlab	the column set
A report aggregate cache	`backend/services/report_cache.py`	Redis/KeyDB	the TTL and the keys
Files in S3/MinIO with a local fallback	`backend/services/file_storage.py`, `backend/api/files.py`	minio	the bucket and the limits
An optional AI feature that degrades without a key	`backend/services/gigachat.py`	httpx	the provider and the prompt
Health probes and metrics	`backend/main.py` (`/healthz`, `/readyz`), `/metrics`	prometheus-fastapi-instrumentator	the set of checks
Reproducible documentation with language parity	`tools/docs_pdf.py`, `scripts/docs-check.sh`, `Makefile`	markdown, weasyprint	the document set

Transfer rules

1. A router holds no business rules: limits and invariants live in `api/*` next to the access check, and the services (`services/`) know nothing about HTTP.

2. An external system always sits behind an adapter: `gigachat.py`, `integration.py`, `file_storage.py` are replaced by an implementation of the same interface.
3. Every optional feature degrades instead of breaking start-up: without GigaChat, Keycloak, Redis and MinIO the product works.
4. Tests are part of the module and need no network or external database: SQLite and an httpx transport substitution.
5. Configuration goes through `backend/core/config.py` (`Settings`) only, and mandatory secrets are declared with `:?` in compose.