Deployment

English version of ../../operations/deployment.md. Existing detail: DEPLOYMENT.md, architecture/deployment-yandex-cloud.md, architecture/deployment-current.md. This page is the checklist and an honest description of the contours.

Contours

Contour	What is used	Where it is described
Local	`docker compose up` (backend, frontend, nginx, keycloak, redis, minio)	this file, `docker-compose.yml`
Main production	Yandex Cloud: VM + nginx + Managed PostgreSQL + Object Storage	`infra/yandex-cloud/`
Alternative	Render + Vercel + Supabase	`render.yaml`, `frontend/vercel.json`

Important: the base `docker-compose.yml` brings up Keycloak, Redis and MinIO as well. If you need a minimal set, start a subset:

```
make compose-up SERVICES="backend frontend nginx"
```

Keycloak is not mandatory for sign-in: local JWT sign-in remains the fallback (see KEYCLOAK.md).

Mandatory `.env` values

Variable	Without it
`SECRET_KEY`	compose does not start (fail closed)
`MINIO_ROOT_PASSWORD`	compose does not start
`KEYCLOAK_ADMIN_PASSWORD`	compose does not start
`DATABASE_URL`	compose does not start

Optional: `GIGACHAT_*` (without them the "Summary" tab reports that the service is not configured), `NOTIFICATIONS_*`, `CORS_ORIGINS`.

First deployment

```
cp .env.example .env      # fill in the mandatory values
make doctor               # check the host
make compose-up
make alembic-upgrade DATABASE_URL='...'    # if the database is empty and migrations were not applied automatically
make seed                 # optional: demo data
make smoke-test
```

Before production

1. TLS on nginx, `CORS_ORIGINS` — an exact list of domains, not `*`.
2. `SECRET_KEY` — outside the repository and outside configuration copies.
3. Backups of PostgreSQL and the bucket; a restore that has been tested.
4. Keycloak: a dedicated realm and client, the public URL matching `KEYCLOAK_PUBLIC_URL`.
5. The demo passwords from the README (`admin123` and others) must not exist in production — `scripts/anonymize_case_data.py` for anonymising case data.