Getting Started Guide

Configure PingOne Advanced Identity Cloud (Ping AIC) / ForgeRock Identity Cloud with LexisNexis InstantID Question and Answer (IIDQA) Nodes

Version 1.3.0

August 2026

LexisNexis® RISK SOLUTIONS

Table of Contents

SCOPE 3

Document Organization 3

LEXISNEXIS INSTANTID QUESTION AND ANSWERS NODES 4

LexisNexis InstantID Get Quiz 4

Input 4

Configuration 4

Output 5

Callbacks 5

Outcomes 6

LexisNexis InstantID Quiz Collector 6

Input 6

Configuration 6

Output 6

Callbacks 7

Outcomes 7

LexisNexis InstantID Quiz Decision 7

Input 8

Configuration 8

Output 8

Callbacks 9

Outcomes 9

DYNAMIC DECISION PLATFORM PORTAL CONFIGURATION 10

Retrieve OrgID and API Key 10

Dynamic Decision Platform Portal Policy 11

FORGEROCK-LEXISNEXIS JOURNEY 13

Journey: Registration-LNRS-IIDQA 13

SCOPE

LexisNexis Risk Solutions (LNRS) Dynamic Decision Platform (DDP) hosts the Authentication Hub's InstantID® Question and Answer (IIDQA) product. LexisNexis IIDQA helps support speedy consumer onboarding, prevent and detect identity theft, and fortify compliance via question-based authentication tools, effectively helping organizations protect their business. The IIDQA nodes provide the capability for administrators to integrate Knowledge Based Authentication (KBA). This document contains the detailed steps and supporting information required to install and configure PingOne Advanced Identity Cloud (Ping AIC), formerly ForgeRock Identity Cloud with LexisNexis IIDQA Nodes. This guide is intended to install a simple configuration to support testing.

The following are architecture assumptions and limitations:

- Ping AIC / ForgeRock Identity Cloud tenant is configured
- Ping AIC / ForgeRock Identity Cloud has default configuration for the Identity Store where the Alpha realm will be utilized for the test user

Document Organization

This document is divided into four sections as follows:

- **Scope.** Defines the purpose of this document.
- **LexisNexis IIDQA Nodes**. Provides an overview of the nodes available for authentication journeys.
- **LexisNexis Dynamic Decision Platform Portal.** Provides detailed information regarding the configuration of LexisNexis Dynamic Decision Platform (DDP) to include configuration of a simple policy and how to access configuration parameters required for the authentication journey.
- **Authentication Journey Configuration.** Provides detailed steps to configure a authentication journey with LexisNexis IIDQA Nodes to perform Multi-Factor Authentication (MFA).

LEXISNEXIS INSTANTID QUESTION AND ANSWERS NODES

LexisNexis InstantID® Question and Answer (IIDQA) supports speedy consumer onboarding, prevent and detect identity theft, and fortify compliance via question-based authentication tools, effectively helping organizations protect their business. The IIDQA nodes provide the capability for administrators to integrate Knowledge Based Authentication (KBA) into PingOne Advanced Identity Cloud (Ping AIC), formerly ForgeRock Identity Cloud.

LexisNexis IIDQA is primarily integrated into the following orchestration journeys:

- Login Multi-Factor Authentication (MFA) for medium to high-risk transactions
- New Account Origination to prevent synthetic accounts, as well as validating the account is linked to a physical person with high fidelity

To include a LexisNexis IIDQA node in an authentication journey, enter LexisNexis into the Filter nodes to get a listing of available capabilities. For IIDQA, the following nodes are available:

- LexisNexis InstantID Get Quiz
- LexisNexis InstantID Quiz Collector
- LexisNexis InstantID Quiz Decision

LexisNexis InstantID Get Quiz

The LexisNexis IIDQA Get Quiz node calls the LexisNexis Dynamic Decision Platform (DDP) Authentication Hub to generate an IIDQA quiz based on the identity data provided to the node. There is no interface displayed to the user by this node. The LexisNexis IIDQA Get Quiz node is configured with an attribute mapping to gather parameters for the API Request to send to the DDP Authentication Hub for generating a knowledge based answer (KBA) quiz. The Attribute Source defines where the attribute mapping information will be fetched at runtime, mainly either User Directory or Shared State. When the user directory is configured as the source for attributes, the node will assume that the username is contained in shared state from a previous node in the authentication tree/journey and use that username to query the user directory for user parameters and fulfill the attribute mapping. When the shared state is configured as the source for attributes, the node will inspect shared state for the user parameters to fulfill the attribute mapping.

Input

The LexisNexis IIDQA Get Quiz node retrieves the following from the journey shared state based upon the configuration of the Attribute Source parameter.

- **AM Username (`username`)** - Required in shared state, or `objectAttributes`, to resolve the desired AM identity when the Attribute Source = User Directory.
    - When **Query Attributes** are defined and the **Add Attributes to API Request** is enabled, the node will fetch user attributes based on the attribute name configured from the AM Identity of the corresponding username.
- **`objectAttributes`** - Required when the Attribute Source = Shared State.
    - When **Query Attributes** are defined and the **Add Attributes to API Request** is enabled, the node will fetch user attributes from shared state.

Configuration

The LexisNexis IIDQA Get Quiz node has the following configuration parameters:

- **Org ID** - Org ID is the unique id associated with DDP generated for your organization.
- **API Key** - This is the unique API key generated by DDP associated to your Org ID.
- **Base URL** - Defines the domain URL for the DDP region where IIDQA API Requests are to be sent. The default value is the global region.
- **Policy** - The DDP Portal policy to be used to integrate the DDP Authentication Hub with IIDQA
- **Attribute Source** - This determines where the LexisNexis IIDQA Get Quiz node will inspect and gather user parameters to be mapped into the attributes of the IIDQA API Request to get a quiz. This can be configured for User Directory or form Shared State. User Directory is typically configured in a orchestration where IIDQA is used for Multi-Factor Authentication (MFA) since the information for the user should be in the directory. The Shared State specification is typically configured in an orchestration where IIDQA is used for identity proofing for use cases such as new account origination since the user account does not exist. When Shared State is used there should be an interface in the tree/journey to collect the information which stores the data in shared state.
- **Attribute List** - Defines a mapping of user parameters to IIDQA API attributes. The user parameters will be fetched based on the Attribute Source. The "Key" defines the IIDQA attribute and the "Value" defines the parameter to fetch. For example, Attribute Source=Shared State, with attribute list key=`account_first_name` and value=`givenName` would signal the LexisNexis IIDQA Get Quiz node to fetch the user parameter `givenName` from shared state and then set the IIDQA attribute `account_first_name` for the API Request. The attributes to send to IIDQA should include `account_first_name`, `account_last_name`, `account_address_street1`, `account_address_city`, `account_address_state` and `account_address_zip` as this will have a good probably to match a record in the LexisNexis system resulting in a generated quiz.

Output

The LexisNexis IIDQA Get Quiz node has the following outputs placed into shared state:

- **IIDQA Quiz** - When the get quiz operation is successful, the quiz from the API response will be contained in the state variable `iidqa.quiz`. This JSONObject value is further processed by the LexisNexis IIDQA Quiz Collector node.
- **IIDQA Request ID** - The Request ID (e.g. attribute `request_id`) associated to the DDP Authentication Hub API Response for IIDQA will be placed into state variable `iidqa.request_id`. This String value is used by the LexisNexis IIDQA Decision node to invoke an API Request with quiz answers for validation.
- **Failure Reason** - If an error outcome is generated, the state variable `iidqa.failure_reason` will contain text associated with the error condition.

Callbacks

The LexisNexis IIDQA Get Quiz node does not have any callbacks as there is no user interface displayed.

Outcomes

The LexisNexis IIDQA Get Quiz Node has the following outcomes:

- **Success** - This outcome is triggered when the API Request results in a physical match to a person based on the Attribute List and a quiz is generated. The quiz is placed into Shared State for the IIDQA Quiz Collector Node, which will display the user interface for the quiz to collect the answers.
- **API Error** - This outcome is triggered when there is an issue with the API Request such as a network timeout or the service is unavailable.
- **Discovery Error** - This outcome is triggered when a physical match to a person cannot be made based on the attribute list provided in the IIDQA API Request. In this scenario, the journey/tree may display a secondary interface to collect additional user parameters such as DOB or SSN enabling a higher probability for an identity match.
- **Velocity Error** - This outcome is triggered based on the IIDQA policy configured within LexisNexis. Typically, we configure the system to only allow 3 quiz requests over a 30 minute period to prevent guessing attacks.
- **Error** - This outcome is triggered when there is a fundamental integration error. First attempt to fix the integration error by looking at debug log files for the node to determine if the integration error is due to configuration. If the configuration looks accurate, then open a support case with LexisNexis Risk Solutions.

LexisNexis InstantID Quiz Collector

This node displays the user interface for a quiz generated by the LexisNexis IIDQA Get Quiz Node. The quiz questions are passed through shared state from the get quiz node to the quiz collector node. Once received, the interface will be displayed to the user for knowledge-based questions to be answered. Once submitted, the answers are placed into shared memory for the LexisNexis IIDQA Decision Node.

Input

The LexisNexis IIDQA Quiz Collector node retrieves the following from the journey shared state:

- **IIDQA Quiz** - Required in shared state that is rendered by the LexisNexis IIDQA Quiz Collector node to generate the user interface. The quiz is contained in the state variable named `iidqa.quiz`.

Configuration

The LexisNexis IIDQA Quiz Collector Node has the following configuration parameters:

- **N/A** - There are no configuration parameters for this node.

Output

The LexisNexis IIDQA Quiz Collector node has the following outputs placed into shared state:

- **IIDQA Quiz Answers** - When the user completes the quiz, the associated answer JSONObject is placed into state variable `iidqa.quiz_answers`. This value is further processed by the LexisNexis IIDQA Decision node.
- **Failure Reason** - If an error outcome is generated, the state variable `iidqa.failure_reason` will contain text associated with the error condition.

Callbacks

he LexisNexis IIDQA Quiz Collector node has the following callbacks:

- When a valid IIDQA Quiz is contained in the state variable `iidqa.quiz`, the following callbacks for the user interface are returned:
    - `TextOutputCallback` - When an error occurs and needs to be displayed to the user, the first `TextOutputCallback` container will contain the error message to display to the user. The container will be marked as `TextOutputCallback.ERROR`.
    - For each Quiz Question contained in the **IIDQA Quiz** state variable named `iidqa.quiz`, the following callback structures will be created:
        - `TextOutputCallback` - Contains the Question that the user must respond with a selection.
        - `TextOutputCallback` - Contains help text with respect to the question to help the user make a selection.
        - `ChoiceCallback` - Contains an array of choices that are displayed to the user to select a specific answer.
    - `ConfirmationCallback` - Contains buttons for the user interface, mainly Submit and Cancel buttons.
    - `HiddenValueCallback` - Container that persists the quiz between callbacks. This information is used to build up the quiz answers.

Outcomes

The LexisNexis IIDQA Quiz Collector Node has the following outcomes:

- **Next** - This outcome triggers when quiz answers are complete and the submit button is selected by the user.
- **Cancel** - This outcome is triggered when the user selects the cancel button to abort the quiz.
- **Error** - This outcome is triggered when there is a fundamental integration error. First attempt to fix the integration error by looking at debug log files for the node to determine if the integration error is due to configuration. If the configuration looks accurate, then open a support case with LexisNexis Risk Solutions.

LexisNexis InstantID Quiz Decision

This node will invoke the LexisNexis Dynamic Decision Platform (DDP) Authentication Hub for InstantID Question and Answer (IIDQA). The main purpose of this node is to call the DDP Authentication Hub to validate answers for a quiz. There is no interface displayed to the user by this node. The quiz answers are passed through shared state from the quiz collector node to the quiz decision node. Once received, the DDP Authentication Hub IIDQA API Request is generated and API Response inspected for success or failure.

Input

The LexisNexis IIDQA Quiz Decision node retrieves the following from the journey shared state:

- **IIDQA Quiz Answers** - Required in shared state. The quiz answers from the LexisNexis IIDQA Quiz Collector node is fetched from the state variable named `iidqa.quiz_answers`. This JSONObject is used by the LexisNexis IIDQA Decision node to invoke an API Request with quiz answers for validation.
- **IIDQA Request ID** - Required in shared state. The Request ID (e.g. attribute `request_id`) associated to the DDP Authentication Hub API Response from the IIDQA Get Quiz node is fetched from the state variable `iidqa.request_id`. This String value is used by the LexisNexis IIDQA Decision node to invoke an API Request with quiz answers for validation.

Configuration

The LexisNexis IIDQA Quiz Decision node has the following configuration parameters:

- **Org ID** - Org ID is the unique id associated with DDP generated for your organization.
- **API Key** - This is the unique API key generated by DDP associated to the Org ID.
- **Base URL** - Defines the domain URL for the DDP region where API Requests are to be sent. The default value is the global region.
- **Policy** - The DDP Portal policy to be used to integrate the DDP Authentication Hub with IIDQA. This policy configuration should be the same as the LexisNexis IIDQA Get Quiz node configuration.
- **Store IIDQA API Response** - If enabled, the API Response from the IIDQA decision will be in the state variable named `iidqa.api_response`.

Output

The LexisNexis IIDQA Quiz Decision node has the following outputs placed into shared state:

- **IIDQA API Response** - When enabled, the API Response from the IIDQA decision will be in the state variable named `iidqa.api_response`.
- **Failure Reason** - If an error outcome is generated, the state variable `iidqa.failure_reason` will contain text associated with the error condition.

The LexisNexis IIDQA Quiz Decision node will keep the following information within shared state:

- **IIDQA Request ID** - The Request ID associated to the DDP Authentication Hub API Response from the IIDQA Get Quiz node contained state variable `iidqa.request_id`.

The LexisNexis IIDQA Quiz Decision node cleans up and removes IIDQA data from shared state:

- **IIDQA Quiz** - Removes state variable `iidqa.quiz`.
- **IIDQA Quiz Answers** - Removes state variable `iidqa.quiz_answers`.

Callbacks

The LexisNexis IIDQA Quiz Decision node does not have any callbacks as there is no user interface displayed.

Outcomes

The LexisNexis IIDQA Quiz Decision Node has the following outcomes:

- **Pass** - This outcome is triggered when answers to a quiz are all passing according the DDP IIDQA policy
- **Fail** - This outcome is triggered when answers to a quiz are not passing according the DDP IIDQA policy
- **API Error** - This outcome is triggered when there is an issue with the API Request such as a network timeout or the service is unavailable.
- **Error** - This outcome is triggered when there is a fundamental integration error. First attempt to fix the integration error by looking at debug log files for the node to determine if the integration error is due to configuration. If the configuration looks accurate, then open a support case with LexisNexis Risk Solutions.

DYNAMIC DECISION PLATFORM PORTAL CONFIGURATION


This section defines the high-level LexisNexis Dynamic Decision Platform (DDP) Portal configuration items that will be needed for the overall configuration. There are two main categories of configuration, mainly,

- Organization ID and API Key for the REST API interfaces. This information is needed by the LexisNexis IIDQA Nodes and will be entered as part of configuration.
- LexisNexis IIDQA Portal Policy. The configured policy within DDP provides the configuration for the Authentication Hub to access IIDQA services. For the purposes of the getting started guide and to have a simple test configuration for different outcomes, the "IIDQA" policy will be configured to directly integrate the Authentication Hub without any further policy rules.


Retrieve OrgID and API Key

To retrieve the DDP Portal values for Organization ID and API Key, perform the following steps.

1. Access **DDP Portal** over the internet by logging into your administrative account with credentials provided by LexisNexis Risk Solutions.
2. From the **DDP Portal** home page, select the user information dropdown that will display username, OrgName and OrgID. This will be the OrgID to enter into the configuration of the LexisNexis IIDQA Nodes.




3. Within the **DDP Portal** home page, select **Admin** followed by selecting the **API Keys** tile. Retrieve the value for API Key. In the event no API Key is listed, select the **Create New API Key** button to generate a new key. This will be the API Key to enter into the configuration of the LexisNexis IIDQA Nodes. The API Key is to be protected. Do not email or keep this value in cleartext on any computer system.




Dynamic Decision Platform Portal Policy

For the purposes of the getting started guide and to have a simple test configuration for different outcomes, the "IIDQA" policy will be configured to directly integrate the Authentication Hub without any further policy rules. Perform the following steps.


1. Access **DDP Portal** over the internet by logging into your administrative account with credentials provided by LexisNexis.
2. From the **DDP Portal** home page, select **Policies** from the menu bar. This will provide a listing of available policies. The first step is to select the **Create** dropdown menu followed by **New Policy (Standard)**.




3. On the Policy Summary, the **Properties** interface tab will be displayed. Enter Policy Name = IIDQA, select the Active button, and update the Status Thresholds for Reject = -20 and Review = 20.



4. To create the policy rules, select the **Rules** interface tab. The IIDQA policy will be a single **Authentication** rule to integrate the Authentication Hub as follows.



5. The **Authentication Rule Editor** can follow the template shown here. Within this interface, the **Product Configuration** is the Authentication Hub configuration that is established via LexisNexis Professional Services. The services configure the LexisNexis IIDQA service as an interface associated to the customer account.




6. Save the policy.
7. Consult with LexisNexis professional services for a more comprehensive policy configuration.

FORGEROCK-LEXISNEXIS JOURNEY

Journey: Registration-LNRS-IIDQA

This section provides the steps to configure a PingAIC / ForgeRock Authentication Tree with LexisNexis IIDQA nodes from the marketplace. LexisNexis IIDQA Nodes are used for Identity Proofing as well as a multi-factor authentication (MFA) of a user. This example workflow documented in this section will build Registration Identity Proofing using the LexisNexis Risk Solutions IIDQA nodes. The journey includes collection of data from the user, generation of the quiz, collecting quiz answers and then validation of the answers.




The flow is as follows:


- Page Node. Gathers information from the user for the purposes of showing how registration identity proofing will operate with LexisNexis InstantID Question and Answer. Note that his flow is a happy path data flow to get starting using the nodes. More complex use cases involve data mapping and data flow mapping along with IIDQA policy configuration.
- LexisNexis IIDQA Get Quiz Node. The configuration determines whether to pull user parameters from: (i) a user credential store, or (ii) from shared state in the journey/tree. The node then uses the information to generate an API Request. If insufficient information is available, LexisNexis risk Solutions physical identity matching will fail and a discovery error will be thrown by the node. More complex journeys may implement page nodes to collet additional attributes from the user and then invoke the IIDQA Get Quiz Node for another attempt to get a quiz for the user.
- LexisNexis IIDQA Quiz Collector Node. This node will display the quiz generated via the LexisNexis IIDQA Get Quiz Node. The user is expected to select the correct answers and click the submit button.
- LexisNexis IIDQA Quiz Decision Node to determine if the quiz answers collected from the user are valid and pass the test. When the decision node determines that the user did not fully pass the test, and the IIDQA policy allows for additional quiz questions, then the challenge outcome is triggered. The challenge outcome should loop back to a quiz collector to display the additional questions.
- Ping AIC message nodes display the results and/or error conditions.

To configure the authentication journey, perform the following to configure the server:

1. From a workstation, launch a browser and navigate to the admin console.
2. Login with administrator credentials for a user that has permission to configure journeys
3. Upon login, select the realm to configure the journey. For the purposes of this instruction the default realm of **alpha** is assumed.
4. On the main dashboard display, select **Journeys** on the left-hand side of the display.
5. On the **Journeys** display, click the **+New Journey** button.



6. On the **New Journey** display, enter information as shown followed by the **Save** button.



7. The result is the **Journeys > Registration-LNRS-IIDQA** display. This is the interface to build up the journey. At this point, the journey will be built by drag-n-drop of Components on the left side of the screen. Each node in the policy will then be configured.

8. Build the Register User Screen (e.g. Page Node), do the following:

- On the **Components Filter** on the left side of the interface, enter **page**. When the **Page Node** is displayed as a component, drag and drop the node into the journey.
- When the **Page Node** properties are displayed on the right side of the interface, enter the following property values:

Node name	Register User
Page Header	(en) Account Registration
Page Description	(en) Please enter the following information in order to create an account

- On the **Components Filter** on the left side of the interface, enter **platform**. When the **Platform Username** is displayed as a component, drag and drop the **Platform Username** into the journey into the **Register User** page node.
- On the **Components Filter** on the left side of the interface, enter **platform**. When the **Platform Password** is displayed as a component, drag and drop the **Platform Password** into the journey into the **Register User** page node.
- Select the **Platform Password** node to display the configuration properties on the right side of the interface. Enter the following:

Validate Password	Selected
Password Attribute	password

- On the **Components Filter** on the left side of the interface, enter **attribute**. When the **Attribute Collector** is displayed as a component, drag and drop it into the journey into the **Register User** page node.
- Select the **Attribute Collector** node to display the configuration properties on the right side of the interface. Enter the following Attributes to Collect (Order does matter):

givenName
sn
postalAddress
city
stateProvince
postalCode

> **Note:** The Attribute List defines a mapping of user parameters to InstantID Q&A API attributes. LexisNexis Risk Solutions Professional Services will assist with the definition of attributes to collect as part of the journey. The objective is to balance Personally Identifiable Information (PII) needed to match a physical data record within the InstantID Question and Answer (IIDQA) product.

9. Build the Persist Password State. This is done here since the PingAIC environment will lose the password from an original page node to collect the information. This script avoids a second password collection user interface to be displayed later in the journey. Do the following:

   - If the password-state script does not exist,
     - Be sure to save the current Journey
     - Create the script by selecting **Scripts** followed by **Auth Scripts** from the available capabilities in the PingAIC console. Select the **+ New Script** button and then select the **Journey Node Decision** script type.
     - Enter the following for the **New Journey Decision Node Script**

       Name: Persist Password State
       Description: <Optional Text Description>
       JavaScript:

```
outcome = "true";
nodeState.putShared("password", nodeState.get("password"));
var attributes = nodeState.get("objectAttributes");
if (attributes) {
    attributes.put("password", nodeState.get("password"));
    nodeState.putShared("objectAttributes", attributes);
}
```

     - Select Save and Close
     - Return to the Journey to continue editing by selecting Journeys followed by the Registration-IIDQA journey
   - On the **Components Filter** on the left side of the interface, enter **scripted**. When the **Scripted Decision** is displayed as a component, drag and drop it into the journey.
   - Select the **Scripted Decision** node component to display the configuration properties on the right side of the interface. Enter the following property values.

Node Name	Persist Password State
Script	<SELECT SCRIPT – password-state>
Outcomes	true
Base URL	https://h-api.online-metrix.net/

10. Build the GET QUIZ Screen, do the following:

    - On the **Components Filter** on the left side of the interface, enter **lexisnexis**. When the **LexisNexis InstantID Get Quiz** is displayed as a component, drag and drop it into the journey.
    - Select the **LexisNexis InstantID Get Quiz** Node component to display the configuration properties on the right side of the interface. Enter the following property values.

Node Name	GET QUIZ
Org ID	<ENTER ORG ID FROM DDP PORTAL>
API Key	<ENTER API KEY FROM DDP PORTAL>
Base URL	https://h-api.online-metrix.net/
Policy	<ENTER THE POLICY NAME AS CONFIGURED IN DDP PORTAL>
Attribute Source	Shared State

Attribute List	Defines the user parameter mapping from the Attribute Source to IIDQA attributes. For example, Key =account_first_name, Value =givenName, Key =account_last_name Value =sn Key=account_address_street1 Value=postalAddress Key=account_address_city Value=city Key=account_address_state Value=stateProvince Key =account_address_zip Value =postalCode

Note: The toggle for Attribute Source allows flexibility in the journey/tree. This determines where the IIDQA GET QUIZ node will inspect and gather user parameters to be mapped into the attributes of the IIDQA API Request to get a quiz. This can be configured for User Directory or from Shared State. User Directory is typically configured in an orchestration where IIDQA is used for Multi-Factor Authentication (MFA) since the information for the user should be in the directory. The Shared State specification is typically configured in an orchestration where IIDQA is used for identity proofing for use cases such as new account origination since the user account does not exist.

Note: The Attribute List defines a mapping of user parameters to InstantID Q&A API attributes. The user parameters will be fetched based on the Attribute Source.

InstantID Q&A must have a physical data record match in order to generate a quiz. The minimum parameters to send are first/last name and zip code. Based on the workflow, additional parameters may be needed such as address, data of birth or social security number. When designing the workflow, be sure to take into account the information needed and whether or not the Discovery Error outcome can be used to fetch additional information.

11. Build the IIDQA QUIZ COLLECTOR, do the following:

- The LexisNexis InstantID Quiz Collector Node may optionally be placed into a Page Node container for additional heading and messaging, or as a standalone node. This decision is up to the administrator. For the purposes of simplicity, this instruction will document the standalone configuration.
- On the **Components Filter** on the left side of the interface, enter **lexisnexis**. When the **LexisNexis InstantID Quiz Collector** is displayed as a component, drag and drop it into the journey.
- Select the **LexisNexis InstantID Quiz Collector** Node component to display the configuration properties on the right side of the interface. This node does not have any configuration parameters.

12. Build the IIDQA QUIZ DECISION, do the following:

    - On the **Components Filter** on the left side of the interface, enter **lexisnexis**. When the **LexisNexis InstantID Quiz Decision** is displayed as a component, drag and drop it into the journey.
    - Select the **LexisNexis InstantID Quiz Decision** Node component to display the configuration properties on the right side of the interface. Enter the following property values.

Node Name	QUIZ DECISION
Org ID	<ENTER ORG ID FROM DDP PORTAL>
API Key	<ENTER API KEY FROM DDP PORTAL>
Base URL	https://h-api.online-metrix.net/
Policy	<ENTER THE POLICY NAME AS CONFIGURED IN DDP PORTAL>
Store IIDQA API Response	Disabled

> **Note:** The Policy configured in the LexisNexis InstantID Quiz Decision node shall be the same as the LexisNexis InstantID Get Quiz. This is because DDP maintains state between issuance of the quiz and the submittal of quiz answers.

13. Build the IIDQA RETEST COLLECTOR, do the following:


    - The LexisNexis IIDQA Quiz Collector Node may optionally be placed into a Page Node container for additional heading and messaging, or as a standalone node. This decision is up to the administrator. In this case, the messaging should indicate that the user failed to answer all questions correctly and to answer some additional questions.
    - On the **Components Filter** on the left side of the interface, enter **lexisnexis**. When the **LexisNexis InstantID Quiz Collector** is displayed as a component, drag and drop it into the authentication tree.
    - Select the **LexisNexis InstantID Quiz Collector** Node component to display the configuration properties on the right side of the interface. This node does not have any configuration parameters.

14. Build Message Nodes for IIDQA Pass, IIDQA Fail, IIDQA API Error and Integration Error to support testing. This can be accomplished with Message Nodes. The nodes are meant to display outcomes to the user. These nodes are in support of testing and not necessary for a production deployment.

15. Build the Create Object node. On the **Components Filter** on the left side of the interface, enter **lexisnexis**. When the **LexisNexis InstantID Quiz Collector** is displayed as a component, drag and drop it into the authentication tree. Configure the **Identity Resource** to the appropriate realm where users are to be created. Add a failure message node as desired.

16. Link together the nodes of the journey.

- At this point you should have the following



Note that this drawing shows the additional steps of Creating the Object in the Identity store and failure condition from the creation operation. The message nodes and creation of object are depicted here to show a possible journey after Identity Proofing and Verification is complete. The steps to implement are the decision of the administrator.