

DSS 620

SND SND SET INPUT MODE	PIN NO.	PIN NO.	EROWN
GND .	2	2	
RET	2	1	
			BLACK
INPUT MODE		4	RED .
	В	8	BLACK
FET TEA	3	6	CRANGE
DUTPUT MODE	C .	5	BLACK
RET	4	8	YELLOW
FICE BUSS	D	7	BLACK
PLT	5	10	GREEN
LOAD	E .	9	PLACK
PET	6	15	FLUE
EUNEKA	F	11	HLACK
RST	7	14	VIOLET
TOG	H	13	SLACK
PET	8	16	GRAY
SCR DATO	J	15	BLACK
RET	9	18	BTIHW
SER DATO	K	17	ELACK
RET	10	50	BROWN
SERIAL IN BUSS	L	19	BLACK
PET	11	55	SBOMN
I SHOT BUSS	M	51	BLACK
SPARE	112	24	RED
SPARE	N	23	BLACK
RET	13	26	ORANGE
SN2	P	25	BLACK

COLOR
1811
ELLOW
SECON.
FEEN
LACK
THE
LACK
IOLET
LACK
LACK
THITE
LACK

Cable Configuration Scanner To Duplex



REV AUTH DATE APPD

Cable Configuration Scanner To Duplex

278

4.74

DSS 620

itese Unterlegen sind ausschließlich für ervice-Zwecke bestimmt, Jede andere

SIGNAL NAME	SCANNER PIN NO.	PERTERM PIN NO.	COLOR
GND .	A	1	BLACK
PET	2	4	RED
INPUT MODE	8	3	BLACK
RET	3	6	DRANGE
SOOM TURTUO	c	5	BLACK
RET	4	8	YELLOW
MRZ BUSS	0	7	BLACK
RET	5	10	GREEN
LOAD	E	9	BLACK
RET	6	12.	BLUE
EUREKA	F	11	BLACK
RET	7	14	VIOLET
TOG	н	13	BLACK
RET	8	16	GREY
SER DATO	2	15	BLACK
RET	9	18	WHITE
SER DATO	K	17	BLACK
RET	10	20	BROWN
SERIALIN BUSS	L	19	BLACK
RET	11	22	BROWN
SHOT BUSS	M	21	BLACK
SPARE	12	24	RED
SPARE	N	2.3	BLACK
RET	13	26	DRANGE
SNZ	P	25	BLACK
RET	- 14	88	YELLOW

SIGNAL NAME	SCANNER	PERTERM	COLOR
	PIN NO.	PIN NO.	BLACK
5N4	R	27	
RET	. 15	30	TREEN
SNI	5	2.9	BLACK
RET	16	32	BLUE
TERM Ø	T	31	BLACK
RET	17	34	VIOLET
TERM 1	U U	93	BLACK
RET	18	36	GREY
TERM 2	٧	35	BLACK,
RET	19	38	WHITE
TERM 3	W	37	BLACK

ole Configuration Scanner To Perterm



FEMALE MNPRSTOUWXYTEBEGFF SCANNER 2 6 10 14 18 22 26 30 34 18 PERTERM FEMALE

Cable Configuration Scanner To Perterm

280

4.74