



NOTES (UNLESS OTHERWISE SPECIFIED):

- ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 0.01 in MAX CHAMFER
- INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- PARTS TO BE BURR FREE

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FORMULA RACING AT UC DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FORMULA RACING AT UC DAVIS IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:	NAME		DATE		FORMULA RACING AT UC DAVIS	
		DIMENSIONS ARE IN INCHES TOLERANCES (UNLESS OTHERWISE SPECIFIED): FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1^\circ$ BEND $\pm 3^\circ$ TWO PLACE DECIMAL $\pm 0.01$ THREE PLACE DECIMAL $\pm 0.005$	DRAWN	AUSTIN M.		5/14/23		TITLE:  <b>Coolant Pump Bracket</b>
			CHECKED					
			ENG APPR.					
			MFG APPR.					
			Q.A.					
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5	COMMENTS:					
		MATERIAL						
		FINISH						
NEXT ASSY	USED ON							
APPLICATION		DO NOT SCALE DRAWING						

SIZE <b>C</b>	DWG. NO. EN-00088-AA-Davies Craig Pump Bracket	REV <b>A</b>
SCALE: 1:1		WEIGHT:
SHEET 1 OF 1		