



NOTES (UNLESS OTHERWISE SPECIFIED):

- 1. ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 2. 0.01 in MAX CHAMFER
- 3. INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- 4. PARTS TO BE BURR FREE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FORMULA RACING AT UC DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FORMULA RACING AT UC DAVIS IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS	
		DIMENSIONS ARE IN INCHES	DRAWN	CTANG	3/21/2023	TITLE:	
		TOLERANCES (UNLESS OTHERWISE SPECIFIED):	CHECKED			Adaptor, 90 degree 0.75-0.75 Elbow (SLA)	
		FRACTIONAL ± 1/32	ENG APPR.			SIZE	
		ANGULAR: MACH ± 1° BEND ± 3°	MFG APPR.			DWG. NO.	
		TWO PLACE DECIMAL ± 0.01	Q.A.			EN-50100-AA-Adaptor, 90 degree 0.75-0.75 Elbow (SLA)	
		THREE PLACE DECIMAL ± 0.005	COMMENTS:			REV	
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5				A	
		MATERIAL				SCALE: 4:1	
		High Temperature Resin				WEIGHT:	
		FINISH				SHEET 1 OF 1	
NEXT ASSY	USED ON	DO NOT SCALE DRAWING					
APPLICATION							