



NOTES (UNLESS OTHERWISE SPECIFIED):

- ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 0.01 in MAX CHAMFER
- INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- PARTS TO BE BURR FREE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
FORMULA RACING AT UC DAVIS. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
FORMULA RACING AT UC DAVIS IS
PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS	
		DIMENSIONS ARE IN INCHES TOLERANCES (UNLESS OTHERWISE SPECIFIED): FRACTIONAL: ± 1/32 ANGULAR: MACH: ± 1° BEND ± 3° TWO PLACE DECIMAL ±0.01 THREE PLACE DECIMAL ±0.005		DRAWN	CTANG	3/21/2023	TITLE: Adaptor, 110 degree 0.75-0.75 Elbow (SLA)
				CHECKED			
				ENG APPR.			
				MFG APPR.			
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5		Q.A.			SIZE C DWG. NO. EN-50101-AA-Adaptor, 110 degree 0.75-0.75 Elbow (SLA)
		MATERIAL High Temperature Resin		COMMENTS:			
		FINISH					REV
NEXT ASSY	USED ON						
APPLICATION		DO NOT SCALE DRAWING					
				SCALE: 4:1		WEIGHT:	SHEET 1 OF 1