



NOTES (UNLESS OTHERWISE SPECIFIED):

1. ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
2. 0.01 in MAX CHAMFER
3. INTERNAL AND EXTERNAL RADII 0.01 in MAX.
4. PARTS TO BE BURR FREE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FORMULA RACING AT UC DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FORMULA RACING AT UC DAVIS IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS		
		DIMENSIONS ARE IN INCHES TOLERANCES (UNLESS OTHERWISE SPECIFIED): FRACTIONAL ± 1/32 ANGULAR: MACH ± 1° BEND ± 3° TWO PLACE DECIMAL ±0.01 THREE PLACE DECIMAL ±0.005	DRAWN			TITLE: Drive Side Bracket		
			CHECKED					
			ENG APPR.					
			MFG APPR.					
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5	Q.A.			SIZE C DWG. NO. EN-10001-CA-Drive Side Bracket (DSB)		
		MATERIAL	COMMENTS:					
NEXT ASSY	USED ON	FINISH				REV		
APPLICATION		DO NOT SCALE DRAWING				SCALE: 1:2 WEIGHT:		SHEET 1 OF 1