



NOTES (UNLESS OTHERWISE SPECIFIED):

- 1. ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 2. 0.01 in MAX CHAMFER
- 3. INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- 4. PARTS TO BE BURR FREE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FORMULA RACING AT UC DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FORMULA RACING AT UC DAVIS IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS	
		DIMENSIONS ARE IN INCHES	DRAWN			TITLE: Adaptor, 0.625-0.75 Silicon Rubber Hose	
		TOLERANCES (UNLESS OTHERWISE SPECIFIED):	CHECKED				
		FRACTIONAL ± 1/32	ENG APPR.				
		ANGULAR: MACH ± 1° BEND ± 3°	MFG APPR.				
		TWO PLACE DECIMAL ± 0.01	Q.A.			REV A	
		THREE PLACE DECIMAL ± 0.005	COMMENTS:				
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5					
		MATERIAL				SIZE C	
		Silicon Rubber				DWG. NO. EN-00097-AA-Adaptor, 0.625-0.75 Silicon Rubber Hose	
		FINISH				SCALE: 3:1	
NEXT ASSY	USED ON	DO NOT SCALE DRAWING				WEIGHT: 0.05	SHEET 1 OF 1
APPLICATION							