



NOTES (UNLESS OTHERWISE SPECIFIED):

- 1. ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 2. 0.01 in MAX CHAMFER
- 3. INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- 4. PARTS TO BE BURR FREE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
FORMULA RACING AT UC DAVIS. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
FORMULA RACING AT UC DAVIS IS
PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS	
		DIMENSIONS ARE IN INCHES	DRAWN			TITLE:	
		TOLERANCES (UNLESS OTHERWISE SPECIFIED):	CHECKED				
		FRACTIONAL $\pm 1/32$	ENG APPR.				
		ANGULAR: MACH $\pm 1^\circ$ BEND $\pm 3^\circ$	MFG APPR.				
		TWO PLACE DECIMAL ± 0.01	Q.A.			SIZE DWG. NO. REV	
		THREE PLACE DECIMAL ± 0.005	COMMENTS:				
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5				BR-0000-AC-BPPS Linkage	
		MATERIAL					
		6061-T6 (SS)					
		FINISH				SCALE: 4:1 WEIGHT: 0.00 SHEET 1 OF 1	
NEXT ASSY	USED ON	DO NOT SCALE DRAWING					
APPLICATION							