



NOTES (UNLESS OTHERWISE SPECIFIED):

- 1. ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 2. 0.01 in MAX CHAMFER
- 3. INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- 4. PARTS TO BE BURR FREE

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
FORMULA RACING AT UC DAVIS. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
FORMULA RACING AT UC DAVIS IS  
PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS		
		DIMENSIONS ARE IN INCHES		DRAWN		TITLE: <b>FE10 Rear Toe Bracket</b>		
		TOLERANCES (UNLESS OTHERWISE SPECIFIED):		CHECKED				
		FRACTIONAL: ± 1/32		ENG APPR.				
		ANGULAR: MACH ± 1° BEND ± 3°		MFG APPR.				
		TWO PLACE DECIMAL ± 0.01		Q.A.				
		THREE PLACE DECIMAL ± 0.005		COMMENTS:		SIZE <b>C</b>		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5						
		MATERIAL <b>AISI 4130 Steel</b>						
		FINISH				DWG. NO. WT- <b>-AA-Rear Toe Bracket</b>		
NEXT ASSY		USED ON				REV <b>AA</b>		
APPLICATION		DO NOT SCALE DRAWING				SCALE: 2:1 WEIGHT: 0.13 SHEET 1 OF 1		