



NOTES (UNLESS OTHERWISE SPECIFIED):

- 1. ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 2. 0.01 in MAX CHAMFER
- 3. INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- 4. PARTS TO BE BURR FREE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
FORMULA RACING AT UC DAVIS. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
FORMULA RACING AT UC DAVIS IS
PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS		
		DIMENSIONS ARE IN INCHES	DRAWN			TITLE: FE10 Front Upright		
		TOLERANCES (UNLESS OTHERWISE SPECIFIED):	CHECKED					
		FRACTIONAL ± 1/32	ENG APPR.					
		ANGULAR: MACH ± 1° BEND ± 3°	MFG APPR.					
		TWO PLACE DECIMAL ± 0.01	Q.A.			SIZE DWG. NO. REV C WT- -AF-Front Upright AF		
		THREE PLACE DECIMAL ± 0.005	COMMENTS:					
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5				SCALE: 1:2 WEIGHT: 1.84 SHEET 1 OF 1		
		MATERIAL						
		6061-T6 (SS)						
		FINISH						
NEXT ASSY		USED ON						
APPLICATION		DO NOT SCALE DRAWING						