



NOTES (UNLESS OTHERWISE SPECIFIED):

- 1. ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 2. 0.01 in MAX CHAMFER
- 3. INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- 4. PARTS TO BE BURR FREE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FORMULA RACING AT UC DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FORMULA RACING AT UC DAVIS IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS		
		DIMENSIONS ARE IN INCHES TOLERANCES (UNLESS OTHERWISE SPECIFIED): FRACTIONAL ± 1/32 ANGULAR: MACH ± 1° BEND ± 3° TWO PLACE DECIMAL ±0.01 THREE PLACE DECIMAL ±0.005	DRAWN			TITLE:		
			CHECKED			PE Bottom		
			ENG APPR.					
			MFG APPR.					
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5	Q.A.					
		MATERIAL 5052-H32	COMMENTS:			SIZE C	DWG. NO. AC-20038-BA-PE Bottom	REV
NEXT ASSY	USED ON	FINISH						
APPLICATION		DO NOT SCALE DRAWING				SCALE: 1:2 WEIGHT: 0.36 SHEET 1 OF 1		