



NOTES (UNLESS OTHERWISE SPECIFIED):

- 1. ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 2. 0.01 in MAX CHAMFER
- 3. INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- 4. PARTS TO BE BURR FREE

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FORMULA RACING AT UC DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FORMULA RACING AT UC DAVIS IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS		
		DIMENSIONS ARE IN INCHES	DRAWN			TITLE: Accumulator Indicator Light Window		
		TOLERANCES (UNLESS OTHERWISE SPECIFIED):	CHECKED					
		FRACTIONAL ± 1/32	ENG APPR.					
		ANGULAR: MACH ± 1° BEND ± 3°	MFG APPR.					
		TWO PLACE DECIMAL ± 0.01	Q.A.			SIZE DWG. NO. REV ACC 046-AA-Accumulator Indicator Light Window		
		THREE PLACE DECIMAL ± 0.005	COMMENTS:					
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5						
		MATERIAL				SCALE: 2:1 WEIGHT: 0.008 SHEET 1 OF 1		
		FINISH						
NEXT ASSY	USED ON							
APPLICATION		DO NOT SCALE DRAWING						