



NOTES (UNLESS OTHERWISE SPECIFIED):

- ALL NON-DIMENSIONED PART FEATURES ARE TO BE TAKEN FROM THE SOLID MODEL.
- 0.01 in MAX CHAMFER
- INTERNAL AND EXTERNAL RADII 0.01 in MAX.
- PARTS TO BE BURR FREE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FORMULA RACING AT UC DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FORMULA RACING AT UC DAVIS IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	FORMULA RACING AT UC DAVIS		
		DIMENSIONS ARE IN INCHES	DRAWN			TITLE: Floor Insulation		
		TOLERANCES (UNLESS OTHERWISE SPECIFIED):	CHECKED					
		FRACTIONAL: $\pm 1/32$	ENG APPR.					
		ANGULAR: MACH $\pm 1^\circ$ BEND $\pm 3^\circ$	MFG APPR.					
		TWO PLACE DECIMAL ± 0.01	Q.A.			SIZE C DWG. NO. AC-20043-BC-PE Floor Insulation REV		
		THREE PLACE DECIMAL ± 0.005	COMMENTS:					
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5						
		MATERIAL				SCALE: 1:2 WEIGHT: 0.015 SHEET 1 OF 1		
		FINISH						
NEXT ASSY	USED ON	DO NOT SCALE DRAWING						
APPLICATION								