

Road vehicle descriptor

Information included in the Road Vehicle Descriptor (RVD) is supplied by the applicant for a vehicle type approval. This information is made available by the department for download to assist in defining the variants covered by the application or approval.

This downloaded version of the RVD is current on the date of the download identified below.

This information has not been verified or approved by the department. The department makes no statements or representations about the accuracy or completeness of this information.

Document Generated: 09/06/2024 16:31

General information

Vehicle type approval number:	VTA-044896 20230828
Make:	NISSAN
Model:	Y62 PATROL
Marketing designation:	Y62 Patrol
Category:	M - Passenger Vehicle

Secure vehicle identifier / vehicle plate details

Location:	On the lower part of the right hand side B-pillar
------------------	---

List of variant(s)

Variant information for Ti (Mid)

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	WAGON
NSW body code:	Station Wagon
Seating options:	8
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	1
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2703
Gross vehicle mass (kg):	3500
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5175
Vehicle width (mm):	1995
Vehicle height (mm):	1940
Wheelbase (mm):	3075
Running clearance (mm):	272

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - a	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - a	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - a	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim combination - a	Std Front and Rear (SB)

Suspension

Suspension name
Suspension configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)

Antilock brakes	Standard (S)
Power windows	Standard (S)
Power mirrors	Standard (S)
Driver's airbag	Standard (S)
Central airbag	Standard (S)
Central locking	Standard (S)
Side and Curtain Airbags	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)

Variant information for Ti-L (Upper)

Front 3/4 image:

Rear 3/4 image:

Variant details

Body style:	WAGON
NSW body code:	Station Wagon
Seating options:	7
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	1
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2729
Gross vehicle mass (kg):	3500
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	
B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5175
Vehicle width (mm):	1995
Vehicle height (mm):	1955
Wheelbase (mm):	3075
Running clearance (mm):	272

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - a	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - a	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - a	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim combination - a	Std Front and Rear (SB)

Suspension

Suspension name
Suspension configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Power windows	Standard (S)
Power mirrors	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Central airbag	Standard (S)
Central locking	Standard (S)
Side and Curtain Airbags	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)

Typical vehicle identification number (VIN) details

VIN:	JN1TANY62A0123456
Location:	12-N-18 (On the right side of front side member)

Engine specifications

Engine - a

Motive power:	Petrol (P)
Configuration:	V configuration 8 cylinders (V8)
Net engine power (kW):	298.00
Net engine power (rpm):	5800
Battery type:	
Battery capacity:	
Capacity (cc):	5,552.00
Alternative energy source:	
Storage system:	
Fuel injection type:	Direct Injection (DI)
Induction type:	Natural (N)
Stroke:	4.00000
Layout:	
Cylinders:	
Typical engine number:	VK56-123456@
Location:	1-J-7

Variant(s) this engine is applicable and the mass variation

Variant	Mass variation (kg) - positive or negative variation from tare weight	Mass variation amount
Ti (Mid)	Standard (S)	
Ti-L (Upper)	Standard (S)	

Service brake specifications

Brake System - a

Actuation type:	Hydraulic (H)
Power assisted:	Hydraulic Boost (HB)

Front

Type:	Disc Ventilated (DIV)
Diameter (mm):	358
Width (mm):	34

Rear

Type:	Disc Ventilated (DIV)
Diameter (mm):	350
Width (mm):	20

For which variant(s) is the service brake applicable and how is it available?

Variant	Variant availability type
Ti (Mid)	Standard (S)
Ti-L (Upper)	Standard (S)

Transmission data specifications

Transmission - a

Transmission type:	Automatic All WD (AAWD)
Forward gears:	7

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
Ti (Mid)	Standard (S)	
Ti-L (Upper)	Standard (S)	

Tyre and rim specifications

Tyre and Rim combination - a

Tyre designation:	265/70 R18
Rim size and profile:	18 x 8J
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	40
Front wheel track (mm):	1695
Rear wheel track (mm):	1695

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
Ti (Mid)	Std Front and Rear (SB)
Ti-L (Upper)	Std Front and Rear (SB)

Suspension data specifications

Suspension configuration - a

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	543	535
Vertical measurement of wheel centre to top of wheel arch opening at full bump	409	364
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	498	478

Variant(s) this suspension is applicable to, and how it is available

Variant
Ti (Mid)
Ti-L (Upper)

Standard equipment or options which may affect ADR compliance

Air conditioning

Variant	Variant availability type
Ti (Mid)	Standard (S)
Ti-L (Upper)	Standard (S)

Antilock brakes

Variant	Variant availability type
Ti (Mid)	Standard (S)
Ti-L (Upper)	Standard (S)

Power windows

Variant	Variant availability type
Ti (Mid)	Standard (S)
Ti-L (Upper)	Standard (S)

Power mirrors

Variant	Variant availability type
Ti (Mid)	Standard (S)
Ti-L (Upper)	Standard (S)

Driver's airbag

Variant	Variant availability type
Ti (Mid)	Standard (S)
Ti-L (Upper)	Standard (S)

Passenger's airbag

Variant	Variant availability type
Ti-L (Upper)	Standard (S)

Central airbag

Variant	Variant availability type
Ti (Mid)	Standard (S)
Ti-L (Upper)	Standard (S)

Central locking

Variant	Variant availability type
Ti (Mid)	Standard (S)
Ti-L (Upper)	Standard (S)

Side and Curtain Airbags

Variant	Variant availability type
Ti (Mid)	Standard (S)
Ti-L (Upper)	Standard (S)

Remarks

1) @ is a variable letter in the engine number