

Road vehicle descriptor

Information included in the Road Vehicle Descriptor (RVD) is supplied by the applicant for a vehicle type approval. This information is made available by the department for download to assist in defining the variants covered by the application or approval.

This downloaded version of the RVD is current on the date of the download identified below.

This information has not been verified or approved by the department. The department makes no statements or representations about the accuracy or completeness of this information.

Document Generated: 18/09/2025 12:55

General information

Vehicle type approval number:	VTA-047341 20250918
Make:	Toyota
Model:	Hilux 8GEN
Marketing designation:	Hilux
Category:	N - Goods Vehicles

Secure vehicle identifier / vehicle plate details

Location:	10-M-20
------------------	---------

List of variant(s)

Variant information for GUN125R-BTFLXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Single Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	2
Max. seating capacity (including driver):	
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1740
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
2GD-FTV	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
RC60F		

Tyre and Rim

Tyre and rim name	Variant availability type
225/70R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN126R-CTTSXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Extra Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	4
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1890
Gross vehicle mass (kg):	3100
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN126R-DTFHXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2045
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (F)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
RC61F		

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)
265/60R18	Opt Front and Rear (OB)

Suspension

Suspension name
GUN12#R-DT##XQ

Standard equipment or options

Name	Variant availability type
-------------	----------------------------------

Curtain Shield Airbags - Front Row	Standard (S)
Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0BA3CD#03123456
MR0JA3DC#03123456

Variant information for GUN126R-DTFSXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2040
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (F)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
RC61F		

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
GUN12#R-DT##XQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456
MR0KA3CD#03123456

Variant information for GUN126R-DTFSXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1925
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (F)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
RC61F		

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456
MR0KA3CD#03123456

Variant information for GUN126R-DTTHRQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2090
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (48V)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)
17" Front Disc I 15" Rear Disc	Optional (O)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)
265/60R18	Opt Front and Rear (OB)
265/60R18 Wide Track	Opt Front and Rear (OB)

Suspension

Suspension name
GUN126R-DTTHRQ
GUN126R-DTTHRQ (Wide Track)

GUN126R-DTTHRQ (Rugged)

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)
Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456
MR0KE3CD601234567

Variant information for GUN126R-DTTHRQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1960
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (48V)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/60R18	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456
MR0KE3CD601234567

Variant information for GUN126R-DTTHXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2050
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)
17" Front Disc I 15" Rear Disc	Optional (O)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)
265/60R18	Opt Front and Rear (OB)
265/60R18 Wide Track	Opt Front and Rear (OB)
265/65R17 Wide Track	Opt Front and Rear (OB)

Suspension

Suspension name
GUN12#R-DT##XQ

GUN1#6R-DTTHXQ (Wide Track)
GUN126R-DTTHXQ (Rugged)
GUN126R-DTTHXQ (GR-S)

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)
Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0BA3CD#03123456
MR0JA3DC#03123456

Variant information for GUN126R-DTTSRQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2085
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (48V)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
GUN12#R-DT##XQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456
MR0KE3CD601234567

Variant information for GUN126R-DTTSRQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1960
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (48V)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456
MR0KE3CD601234567

Variant information for GUN126R-DTTSXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2050
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
GUN12#R-DT##XQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456
MR0KA3CD#03123456

Variant information for GUN125R-CTTLXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Extra Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	4
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1890
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
2GD-FTV	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN126R-DTTSXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1925
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456
MR0KA3CD#03123456

Variant information for GUN135R-BTFLXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Single Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	2
Max. seating capacity (including driver):	
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1605
Gross vehicle mass (kg):	2900
Maximum towing mass (braked trailer) (kg):	2800
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
2GD-FTV	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
RC60		

Tyre and Rim

Tyre and rim name	Variant availability type
225/70R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0CB3DB#03123456
MR0JA3DC#03123456

Variant information for GUN135R-DTTLXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1915
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	2800
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
2GD-FTV	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60E		

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
GUN13#R-DTT#XQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN136R-CTTSXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Extra Cab Utility
NSW body code:	Utility
Seating options:	4
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1910
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	2800
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1860
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60E		

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
GUN136R-CTTSXQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN136R-DTTHXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1925
Gross vehicle mass (kg):	2980
Maximum towing mass (braked trailer) (kg):	2800
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)
17" Front Disc I 15" Rear Disc	Optional (O)

Transmission

Transmission name	Variant availability	Variant amount
AC60E		

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)
265/60R18	Opt Front and Rear (OB)
265/60R18 Wide Track	Opt Front and Rear (OB)

Suspension

Suspension name
GUN1#6R-DTTHXQ (Wide Track)
GUN13#R-DTT#XQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)
Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN136R-DTTSXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1915
Gross vehicle mass (kg):	2980
Maximum towing mass (braked trailer) (kg):	2800
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60E		

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
GUN13#R-DTT#XQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for TGN121R-BTMLKQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Single Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	2
Max. seating capacity (including driver):	
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1445
Gross vehicle mass (kg):	2700
Maximum towing mass (braked trailer) (kg):	2500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	174

Engine details

Engine name	Variant availability type	Mass variation amount
2TR-FE	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (1 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
R151		

Tyre and Rim

Tyre and rim name	Variant availability type
215/65R16	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for TGN121R-BTTLKQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Single Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	2
Max. seating capacity (including driver):	
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1460
Gross vehicle mass (kg):	2700
Maximum towing mass (braked trailer) (kg):	2500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	174

Engine details

Engine name	Variant availability type	Mass variation amount
2TR-FE	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (1 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60E		

Tyre and Rim

Tyre and rim name	Variant availability type
215/65R16	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for TGN121R-DTTLKQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1745
Gross vehicle mass (kg):	2780
Maximum towing mass (braked trailer) (kg):	2500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5330
Vehicle width (mm):	1800
Vehicle height (mm):	1750
Wheelbase (mm):	3085
Running clearance (mm):	174

Engine details

Engine name	Variant availability type	Mass variation amount
2TR-FE	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (1 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60E		

Tyre and Rim

Tyre and rim name	Variant availability type
215/65R16	Std Front and Rear (SB)

Suspension

Suspension name
TGN121R-DT#LKQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for TGN121R-DTMLKQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	2
Max. seating capacity (including driver):	
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1735
Gross vehicle mass (kg):	2780
Maximum towing mass (braked trailer) (kg):	2500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5330
Vehicle width (mm):	1800
Vehicle height (mm):	1750
Wheelbase (mm):	3085
Running clearance (mm):	174

Engine details

Engine name	Variant availability type	Mass variation amount
2TR-FE	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (1 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
R151		

Tyre and Rim

Tyre and rim name	Variant availability type
215/65R16	Std Front and Rear (SB)

Suspension

Suspension name
TGN121R-DT#LKQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN125R-DTFLXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2040
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
2GD-FTV	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
RC60F		

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
GUN12#R-DT##XQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN126R-DTTHXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1940
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/60R18	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0BA3CD#03123456
MR0JA3DC#03123456

Variant information for GUN125R-DTTLXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Utility
NSW body code:	Utility
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2050
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1865
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
2GD-FTV	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
GUN12#R-DT##XQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN125R-DTTLXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Double Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	5
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1905
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
2GD-FTV	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN126R-BTFSXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Single Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	2
Max. seating capacity (including driver):	
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1765
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (F)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
RC61F		

Tyre and Rim

Tyre and rim name	Variant availability type
225/70R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN126R-BTTSXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Single Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	2
Max. seating capacity (including driver):	
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1765
Gross vehicle mass (kg):	3050
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
225/70R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN126R-CTFSXQ3

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Extra Cab Chassis
NSW body code:	Cab and Chassis
Seating options:	4
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1875
Gross vehicle mass (kg):	3100
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (F)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
RC61F		

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)

Suspension

Suspension name
Cab-Chassis Variants

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)

Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Variant information for GUN126R-CTTHXQ

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	Extra Cab Utility
NSW body code:	Utility
Seating options:	4
Max. seating capacity (including driver):	
No. of doors side:	4
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	2025
Gross vehicle mass (kg):	3100
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	5325
Vehicle width (mm):	1855
Vehicle height (mm):	1860
Wheelbase (mm):	3085
Running clearance (mm):	216

Engine details

Engine name	Variant availability type	Mass variation amount
1GD-FTV (T)	Standard (S)	

Service Brake

Service brake name	Variant availability type
16" Front Disc (4 Piston) I Rear Drum	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
AC60F	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
265/65R17	Std Front and Rear (SB)
265/60R18	Opt Front and Rear (OB)

Suspension

Suspension name
GUN12#R-DT##XQ
GUN126R-CTTHXQ

Standard equipment or options

Name	Variant availability type
Curtain Shield Airbags - Front Row	Standard (S)
Curtain Shield Airbag - 2nd Row	Standard (S)
Driver's Knee Airbag	Standard (S)
Side Thorax Airbag - Front Row	Standard (S)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
MR0JA3DC#03123456

Typical vehicle identification number (VIN) details

VIN:	MR0AA3DD#03123456
Location:	12-D-4

VIN:	MR0AA3DD#03123456
Location:	12-D-4

VIN:	MR0AA3DD#03123456
Location:	12-D-4

VIN:	MR0AA3DD#03123456
Location:	12-D-4

VIN:	MR0BA3CC#03123456
Location:	12-D-4

VIN:	MR0BA3CC#03123456
Location:	12-D-4

VIN:	MR0BA3CC#03123456
Location:	12-D-4

VIN:	MR0BA3CC#03123456
Location:	12-D-4

VIN:	MR0BA3CD#03123456
Location:	12-D-4

VIN:	MR0BA3CD#03123456
Location:	12-D-4

Variant	
GUN126R-DTTHXQ3	
GUN126R-DTFHXQ	
GUN126R-DTTHXQ	

VIN:	MR0BA3CD#03123456
Location:	12-D-4

VIN:	MR0BA3CD#03123456
Location:	12-D-4

VIN:	MR0CB3DB#03123456
Location:	12-D-4

VIN:	MR0CB3DB#03123456
Location:	12-D-4

VIN:	MR0CB3DB#03123456
Location:	12-D-4

Variant	
GUN135R-BTFLXQ3	

VIN:	MR0CB3DB#03123456
Location:	12-D-4

VIN:	MR0CB3DD#03123456
Location:	12-D-4

VIN:	MR0CB3DD#03123456
Location:	12-D-4

VIN:	MR0CB3DD#03123456
Location:	12-D-4

VIN:	MR0CB3DD#03123456
Location:	12-D-4

VIN:	MR0CX3CB#03123456
Location:	12-D-4

VIN:	MR0CX3CB#03123456
Location:	12-D-4

VIN:	MR0CX3CB#03123456
Location:	12-D-4

VIN:	MR0CX3CB#03123456
Location:	12-D-4

VIN:	MR0CX3CD#03123456
Location:	12-D-4

VIN:	MR0CX3CD#03123456
Location:	12-D-4

VIN:	MR0CX3CD#03123456
Location:	12-D-4

VIN:	MR0CX3CD#03123456
Location:	12-D-4

VIN:	MR0DB3CB#03123456
Location:	12-D-4

VIN:	MR0DB3CB#03123456
Location:	12-D-4

VIN:	MR0DB3CB#03123456
Location:	12-D-4

VIN:	MR0DB3CB#03123456
Location:	12-D-4

VIN:	MR0DB3CC#03123456
Location:	12-D-4

VIN:	MR0DB3CC#03123456
Location:	12-D-4

VIN:	MR0DB3CC#03123456
Location:	12-D-4

VIN:	MR0DB3CC#03123456
Location:	12-D-4

VIN:	MR0DB3CD#03123456
Location:	12-D-4

VIN:	MR0DB3CD#03123456
Location:	12-D-4

VIN:	MR0DB3CD#03123456
Location:	12-D-4

VIN:	MR0DB3CD#03123456
Location:	12-D-4

VIN:	MR0JA3DC#03123456
Location:	12-D-4

Variant
GUN126R-DTTHXQ
GUN126R-DTTHXQ3
GUN126R-DTTSRQ
GUN136R-CTTSXQ
GUN125R-DTTLXQ3
GUN126R-CTFSXQ3
GUN126R-CTTSXQ3
GUN126R-DTFSXQ
GUN126R-DTFSXQ3
GUN125R-CTTLXQ3
GUN126R-DTTSXQ
GUN125R-DTFLXQ
GUN135R-DTTLXQ
GUN126R-DTFHXQ
TGN121R-DTMLKQ
GUN136R-DTTSXQ
GUN126R-BTTSXQ3
GUN126R-DTTSRQ3
GUN125R-BTFLXQ3
TGN121R-DTTLKQ
GUN125R-DTTLXQ
GUN126R-CTTHXQ
GUN126R-DTTSXQ3

GUN126R-BTFSXQ3
TGN121R-BTTLKQ3
GUN136R-DTTHXQ
GUN126R-DTTHRQ
GUN126R-DTTHRQ3
GUN135R-BTFLXQ3
TGN121R-BTMLKQ3

VIN:	MR0JA3DC#03123456
Location:	12-D-4

VIN:	MR0JA3DC#03123456
Location:	12-D-4

VIN:	MR0JA3DC#03123456
Location:	12-D-4

VIN:	MR0JA3DD#03123456
Location:	12-D-4

VIN:	MR0JA3DD#03123456
Location:	12-D-4

VIN:	MR0JA3DD#03123456
Location:	12-D-4

VIN:	MR0JA3DD#03123456
Location:	12-D-4

VIN:	MR0KA3CB#03123456
Location:	12-D-4

VIN:	MR0KA3CB#03123456
Location:	12-D-4

VIN:	MR0KA3CB#03123456
Location:	12-D-4

VIN:	MR0KA3CB#03123456
Location:	12-D-4

VIN:	MR0KA3CC#03123456
Location:	12-D-4

VIN:	MR0KA3CC#03123456
Location:	12-D-4

VIN:	MR0KA3CC#03123456
Location:	12-D-4

VIN:	MR0KA3CC#03123456
Location:	12-D-4

VIN:	MR0KA3CD#03123456
Location:	12-D-4

Variant
GUN126R-DTFSXQ3
GUN126R-DTTSXQ
GUN126R-DTTSXQ3
GUN126R-DTFSXQ

VIN:	MR0KE3CD601234567
Location:	12-D-4

Variant
GUN126R-DTTHRQ
GUN126R-DTTHRQ3
GUN126R-DTTSRQ
GUN126R-DTTSRQ3

Engine specifications

2GD-FTV

Motive power:	Diesel (D)
Configuration:	In line 4 cylinder (IL4)
Net engine power (kW):	110.00
Net engine power (rpm):	3400
Capacity (cc):	2,393.00
Fuel injection type:	Direct Injection (DI)
Induction type:	Turbo Charged (TC)
Typical engine number:	2GD 1234567
Location:	3-I-17

Variant(s) this engine is applicable and the mass variation

Variant	Mass variation (kg) - positive or negative variation from tare weight	Mass variation amount
GUN125R-BTFLXQ3	Standard (S)	
GUN125R-CTTLXQ3	Standard (S)	
GUN125R-DTFLXQ	Standard (S)	
GUN125R-DTTLXQ	Standard (S)	
GUN125R-DTTLXQ3	Standard (S)	
GUN135R-BTFLXQ3	Standard (S)	
GUN135R-DTTLXQ	Standard (S)	

1GD-FTV (F)

Motive power:	Diesel (D)
Configuration:	In line 4 cylinder (IL4)
Net engine power (kW):	150.00
Net engine power (rpm):	3400
Capacity (cc):	2,755.00
Fuel injection type:	Direct Injection (DI)
Induction type:	Turbo Charged (TC)
Typical engine number:	1GD 1234567
Location:	3-I-17

Variant(s) this engine is applicable and the mass variation

Variant	Mass variation (kg) - positive or negative variation from tare weight	Mass variation amount
GUN126R-BTFSXQ3	Standard (S)	
GUN126R-CTFSXQ3	Standard (S)	
GUN126R-DTFHXQ	Standard (S)	
GUN126R-DTFSXQ	Standard (S)	
GUN126R-DTFSXQ3	Standard (S)	

1GD-FTV (T)

Motive power:	Diesel (D)
Configuration:	In line 4 cylinder (IL4)
Net engine power (kW):	150.00
Net engine power (rpm):	3000
Capacity (cc):	2,755.00
Fuel injection type:	Direct Injection (DI)
Induction type:	Turbo Charged (TC)
Typical engine number:	1GD 1234567
Location:	3-I-17

Variant(s) this engine is applicable and the mass variation

Variant	Mass variation (kg) - positive or negative variation from tare weight	Mass variation amount
GUN126R-BTTSXQ3	Standard (S)	
GUN126R-CTTHXQ	Standard (S)	
GUN126R-CTTSXQ3	Standard (S)	
GUN126R-DTTHXQ	Standard (S)	
GUN126R-DTTSXQ	Standard (S)	
GUN126R-DTTSXQ3	Standard (S)	
GUN136R-CTTSXQ	Standard (S)	
GUN136R-DTTHXQ	Standard (S)	
GUN136R-DTTSXQ	Standard (S)	
GUN126R-DTTHXQ3	Standard (S)	

2TR-FE

Motive power:	Petrol (P)
Configuration:	In line 4 cylinder (IL4)
Net engine power (kW):	122.00
Net engine power (rpm):	5200
Capacity (cc):	2,694.00
Fuel injection type:	Multipoint injection (MPI)
Induction type:	Natural (N)
Typical engine number:	2TR 1234567
Location:	6-H-11

Variant(s) this engine is applicable and the mass variation

Variant	Mass variation (kg) - positive or negative variation from tare weight	Mass variation amount
TGN121R-BTMLKQ3	Standard (S)	
TGN121R-BTTLKQ3	Standard (S)	
TGN121R-DTTLKQ	Standard (S)	
TGN121R-DTMLKQ	Standard (S)	

1GD-FTV (48V)

Motive power:	Battery Plus Internal Combustion (BIC)
Configuration:	In line 4 cylinder (IL4)
Net engine power (kW):	150.00
Net engine power (rpm):	3000
Capacity (cc):	2,755.00
Fuel injection type:	Multipoint injection (MPI)
Induction type:	Turbo Charged (TC)
Typical engine number:	1GD 1234567
Location:	3-I-17

Variant(s) this engine is applicable and the mass variation

Variant	Mass variation (kg) - positive or negative variation from tare weight	Mass variation amount
GUN126R-DTTHRQ	Standard (S)	
GUN126R-DTTHRQ3	Standard (S)	
GUN126R-DTTSRQ	Standard (S)	
GUN126R-DTTSRQ3	Standard (S)	

Service brake specifications

16" Front Disc (1 Piston) I Rear Drum

Actuation type:	Hydraulic (H)
Power assisted:	Vacuum (VAC)

Front

Type:	Disc Ventilated (DIV)
Diameter (mm):	296
Width (mm):	30

Rear

Type:	Drum (DR)
Diameter (mm):	256
Width (mm):	74

For which variant(s) is the service brake applicable and how is it available?

Variant	Variant availability type
TGN121R-BTMLKQ3	Standard (S)
TGN121R-BTTLKQ3	Standard (S)
TGN121R-DTTLKQ	Standard (S)
TGN121R-DTMLKQ	Standard (S)

16" Front Disc (4 Piston) I Rear Drum

Actuation type:	Hydraulic (H)
Power assisted:	Vacuum (VAC)

Front

Type:	Disc Ventilated (DIV)
Diameter (mm):	319
Width (mm):	28

Rear

Type:	Drum (DR)
Diameter (mm):	297
Width (mm):	77

For which variant(s) is the service brake applicable and how is it available?

Variant	Variant availability type
GUN125R-BTFLXQ3	Standard (S)
GUN125R-CTTLXQ3	Standard (S)
GUN125R-DTFLXQ	Standard (S)
GUN125R-DTTLXQ	Standard (S)
GUN125R-DTTLXQ3	Standard (S)
GUN126R-BTFSXQ3	Standard (S)
GUN126R-BTTSXQ3	Standard (S)
GUN126R-CTFSXQ3	Standard (S)
GUN126R-CTTHXQ	Standard (S)
GUN126R-CTTSXQ3	Standard (S)
GUN126R-DTFHXQ	Standard (S)
GUN126R-DTFSXQ	Standard (S)
GUN126R-DTFSXQ3	Standard (S)
GUN126R-DTTHRQ	Standard (S)
GUN126R-DTTHRQ3	Standard (S)
GUN126R-DTTHXQ	Standard (S)
GUN126R-DTTSRQ	Standard (S)
GUN126R-DTTSRQ3	Standard (S)

GUN126R-DTTSXQ	Standard (S)
GUN126R-DTTSXQ3	Standard (S)
GUN135R-BTFLXQ3	Standard (S)
GUN135R-DTTLXQ	Standard (S)
GUN136R-CTTSXQ	Standard (S)
GUN136R-DTTHXQ	Standard (S)
GUN136R-DTTSXQ	Standard (S)
GUN126R-DTTHXQ3	Standard (S)

17" Front Disc I 15" Rear Disc

Actuation type:	Hydraulic (H)
Power assisted:	Vacuum (VAC)

Front

Type:	Disc Ventilated (DIV)
Diameter (mm):	338
Width (mm):	28

Rear

Type:	Disc Ventilated (DIV)
Diameter (mm):	312
Width (mm):	18

For which variant(s) is the service brake applicable and how is it available?

Variant	Variant availability type
GUN126R-DTTHRQ	Optional (O)
GUN126R-DTTHXQ	Optional (O)
GUN136R-DTTHXQ	Optional (O)

Transmission data specifications

R151

Transmission type:	Manual (M)
Forward gears:	5

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
TGN121R-BTMLKQ3		
TGN121R-DTMLKQ		

RC60

Transmission type:	Manual (M)
Forward gears:	6

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
GUN135R-BTFLXQ3		

RC61F

Transmission type:	Manual All WD (MAWD)
Forward gears:	6

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
GUN126R-BTFSXQ3		
GUN126R-CTFSXQ3		
GUN126R-DTFHXQ		
GUN126R-DTFSXQ		
GUN126R-DTFSXQ3		

RC60F

Transmission type:	Manual All WD (MAWD)
Forward gears:	6

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
GUN125R-BTFLXQ3		
GUN125R-DTFLXQ		

AC60E

Transmission type:	Automatic (A)
Forward gears:	6

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
GUN135R-DTTLXQ		
GUN136R-CTTSXQ		
GUN136R-DTTHXQ		
GUN136R-DTTSXQ		
TGN121R-BTTLKQ3		
TGN121R-DTTLKQ		

AC60F

Transmission type:	Automatic All WD (AAWD)
Forward gears:	6

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
GUN125R-CTTLXQ3	Standard (S)	
GUN125R-DTTLXQ	Standard (S)	
GUN125R-DTTLXQ3	Standard (S)	
GUN126R-BTTSXQ3	Standard (S)	
GUN126R-CTTHXQ	Standard (S)	
GUN126R-CTTSXQ3	Standard (S)	
GUN126R-DTTHRQ	Standard (S)	
GUN126R-DTTHRQ3	Standard (S)	
GUN126R-DTTHXQ	Standard (S)	
GUN126R-DTTSRQ	Standard (S)	
GUN126R-DTTSRQ3	Standard (S)	
GUN126R-DTTSXQ	Standard (S)	
GUN126R-DTTSXQ3	Standard (S)	
GUN126R-DTTHXQ3	Standard (S)	

Tyre and rim specifications

215/65R16

Tyre designation:	215/65R16C
Rim size and profile:	16X6J
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	45
Front wheel track (mm):	1510
Rear wheel track (mm):	1510

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
TGN121R-BTMLKQ3	Std Front and Rear (SB)
TGN121R-BTTLKQ3	Std Front and Rear (SB)
TGN121R-DTTLKQ	Std Front and Rear (SB)
TGN121R-DTMLKQ	Std Front and Rear (SB)

225/70R17

Tyre designation:	225/70R17C
Rim size and profile:	17x6J
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	50
Front wheel track (mm):	1495
Rear wheel track (mm):	1510

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
GUN125R-BTFLXQ3	Std Front and Rear (SB)
GUN126R-BTFSXQ3	Std Front and Rear (SB)
GUN126R-BTTSXQ3	Std Front and Rear (SB)
GUN135R-BTFLXQ3	Std Front and Rear (SB)

265/65R17

Tyre designation:	265/65R17
Rim size and profile:	17X7 1/2J
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	30
Front wheel track (mm):	1535
Rear wheel track (mm):	1550

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
GUN125R-CTTLXQ3	Std Front and Rear (SB)
GUN125R-DTFLXQ	Std Front and Rear (SB)
GUN125R-DTTLXQ	Std Front and Rear (SB)
GUN125R-DTTLXQ3	Std Front and Rear (SB)
GUN126R-CTFSXQ3	Std Front and Rear (SB)
GUN126R-CTTHXQ	Std Front and Rear (SB)
GUN126R-CTTSXQ3	Std Front and Rear (SB)
GUN126R-DTFHXQ	Std Front and Rear (SB)
GUN126R-DTFSXQ	Std Front and Rear (SB)
GUN126R-DTFSXQ3	Std Front and Rear (SB)
GUN126R-DTTHRQ	Std Front and Rear (SB)
GUN126R-DTTHXQ	Std Front and Rear (SB)
GUN126R-DTTSRQ	Std Front and Rear (SB)
GUN126R-DTTSRQ3	Std Front and Rear (SB)
GUN126R-DTTSXQ	Std Front and Rear (SB)
GUN126R-DTTSXQ3	Std Front and Rear (SB)
GUN135R-DTTLXQ	Std Front and Rear (SB)
GUN136R-CTTSXQ	Std Front and Rear (SB)
GUN136R-DTTHXQ	Std Front and Rear (SB)
GUN136R-DTTSXQ	Std Front and Rear (SB)

265/60R18

Tyre designation:	265/60R18
Rim size and profile:	18X7 1/2J
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	30
Front wheel track (mm):	1535
Rear wheel track (mm):	1550

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
GUN126R-CTTHXQ	Opt Front and Rear (OB)
GUN126R-DTFHXQ	Opt Front and Rear (OB)
GUN126R-DTTHRQ	Opt Front and Rear (OB)
GUN126R-DTTHRQ3	Std Front and Rear (SB)
GUN126R-DTTHXQ	Opt Front and Rear (OB)
GUN136R-DTTHXQ	Opt Front and Rear (OB)
GUN126R-DTTHXQ3	Std Front and Rear (SB)

265/60R18 Wide Track

Tyre designation:	265/60R18
Rim size and profile:	18X7 1/2J
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	30
Front wheel track (mm):	1670
Rear wheel track (mm):	1705

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
GUN126R-DTTHRQ	Opt Front and Rear (OB)
GUN126R-DTTHXQ	Opt Front and Rear (OB)
GUN136R-DTTHXQ	Opt Front and Rear (OB)

265/65R17 Wide Track

Tyre designation:	265/65R17
Rim size and profile:	17X7 1/2J
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	30
Front wheel track (mm):	1670
Rear wheel track (mm):	1705

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
GUN126R-DTTHXQ	Opt Front and Rear (OB)

Suspension data specifications

Cab-Chassis Variants

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	0	0
Vertical measurement of wheel centre to top of wheel arch opening at full bump	0	0
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	0	0

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN125R-BTFLXQ3
GUN125R-CTTLXQ3
GUN125R-DTTLXQ3
GUN126R-BTFSXQ3
GUN126R-BTTSXQ3
GUN126R-CTFSXQ3
GUN126R-CTTSXQ3
GUN126R-DTFSXQ3
GUN126R-DTTHRQ3
GUN126R-DTTSRQ3
GUN126R-DTTSXQ3
GUN135R-BTFLXQ3
TGN121R-BTMLKQ3
TGN121R-BTTLKQ3
GUN126R-DTTHXQ3

TGN121R-DT#LKQ

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	439	472
Vertical measurement of wheel centre to top of wheel arch opening at full bump	326	372
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	401	439

Variant(s) this suspension is applicable to, and how it is available

Variant
TGN121R-DTTLKQ
TGN121R-DTMLKQ

GUN12#R-DT##XQ

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	517	555
Vertical measurement of wheel centre to top of wheel arch opening at full bump	403	439
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	479	516

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN125R-DTFLXQ
GUN125R-DTTLXQ
GUN126R-CTTHXQ
GUN126R-DTFHXQ
GUN126R-DTFSXQ
GUN126R-DTTHXQ
GUN126R-DTTSRQ
GUN126R-DTTSXQ

GUN126R-CTTHXQ

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	517	554
Vertical measurement of wheel centre to top of wheel arch opening at full bump	404	430
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	479	513

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN126R-CTTHXQ

GUN1#6R-DTTHXQ (Wide Track)

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	533	585
Vertical measurement of wheel centre to top of wheel arch opening at full bump	425	470
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	497	547

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN126R-DTTHXQ
GUN136R-DTTHXQ

GUN126R-DTTHXQ (Rugged)

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	517	555
Vertical measurement of wheel centre to top of wheel arch opening at full bump	394	439
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	476	516

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN126R-DTTHXQ

GUN13#R-DTT#XQ

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	517	555
Vertical measurement of wheel centre to top of wheel arch opening at full bump	403	447
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	479	519

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN135R-DTTLXQ
GUN136R-DTTHXQ
GUN136R-DTTSXQ

GUN136R-CTTSXQ

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	517	554
Vertical measurement of wheel centre to top of wheel arch opening at full bump	404	437
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	479	515

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN136R-CTTSXQ

GUN126R-DTTHXQ (GR-S)

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	542	595
Vertical measurement of wheel centre to top of wheel arch opening at full bump	442	471
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	509	554

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN126R-DTTHXQ

GUN126R-DTTHRQ

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	517	533
Vertical measurement of wheel centre to top of wheel arch opening at full bump	403	417
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	479	494

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN126R-DTTHRQ

GUN126R-DTTHRQ (Wide Track)

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	517	533
Vertical measurement of wheel centre to top of wheel arch opening at full bump	409	418
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	481	495

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN126R-DTTHRQ

GUN126R-DTTHRQ (Rugged)

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	517	533
Vertical measurement of wheel centre to top of wheel arch opening at full bump	394	417
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	476	494

Variant(s) this suspension is applicable to, and how it is available

Variant
GUN126R-DTTHRQ

Standard equipment or options which may affect ADR compliance

Remarks

VARIANT INFORMATION_#_Height: GUN126R-CTTHXQ / GUN136R-CTTSXQ = 1810mm with Pole Antenna, 1860mm with Fin Antenna_ GUN126R-DTFHXQ / DTFSXQ / DTTSXQ / GUN136R-DTTSXQ = 1815mm with Pole Antenna, 1865mm with Fin Antenna_ GUN126R-DTTHXQ / DTTHRQ / GUN136R-DTTHXQ = 1815mm w/ Pole Antenna, 1865mm w/ Fin Antenna, 1830mm w/ Pole Antenna + Wide Track, 1880mm w/ Fin Antenna + Wide Track_ TGN121R-DTTLKQ = 1700mm w/ Pole Antenna, 1750mm w/ Fin Antenna_#_Width: GUN126R-DTTHXQ / DTFHXQ / DTTHRQ / GUN136R-DTTHXQ = 1855mm w/o MLM Overfender, 1900mm w/ MLM Overfender, 2020mm w/ MLM Wide Track_#_Tare Mass: GUN125R-CTTLXQ3 = 1880kg w/ 17" Alloy Wheel, 1890kg w/ 17" Steel Wheel_ GUN125R-DTTLXQ / GUN126R-DTTSXQ = 2040kg w/ 17" Alloy Wheel, 2050kg w/ 17" Steel Wheel_ GUN126R-CTFSXQ3 = 1865kg w/ 17" Alloy Wheel, 1875kg w/ 17" Steel Wheel_ GUN126R-CTTHXQ = 2015kg w/ 17" Alloy Wheel, 2025kg w/ 18" Alloy Wheel_ GUN126R-CTTSXQ3 = 1885kg w/ 17" Alloy Wheel, 1890kg w/ 17" Steel Wheel_ GUN126R-DTFSXQ = 2030kg w/ 17" Alloy Wheel, 2040kg w/ 17" Steel Wheel_ GUN126R-DTTSXQ3 / DTFSXQ3 = 1915kg w/ 17" Alloy Wheel, 1925kg w/ 17" Steel Wheel_ GUN126R-DTTHRQ = 2080kg w/ 17" Alloy Wheel, 2090kg w/ 18" Alloy Wheel, 2105kg w/ 18" MLM + Wide Track_ GUN126R-DTTHXQ = 2040kg w/ 17" Alloy Wheel, 2050kg w/ 18" Alloy Wheel, 2075kg w/ 18" MLM + Wide Track, 2080kg w/ 17" GR-S C1, 2090kg w/ 17" GR-S C2_ GUN135R-DTTLXQ = 1905kg w/ 17" Alloy Wheel, 1915kg w/ 17" Steel Wheel_ GUN136R-CTTSXQ = 1900kg w/ 17" Alloy Wheel, 1910kg w/ 17" Steel Wheel_ GUN136R-DTTSXQ = 1915kg w/ 17" Steel Wheel, 1905kg w/ 17" Alloy Wheel_ GUN136R-DTTHXQ = 1915kg w/ 17" Alloy Wheel, 1925kg w/ 18" Alloy Wheel, 1940kg w/ 18" MLM + Wide Track_#_GVM: GUN126R-DTTHXQ: 3050kg w/o GR-S C2, 3000kg w/ GR-S C2_#_Running Clearance: GUN126R-DTTHXQ / DTTHRQ / GUN136R-DTTHXQ = 174mm w 18" Alloy Wheel w/ Bullbar Package, 202mm w/ 18" Alloy Wheel with Wide Track, 216mm with 17" & 18" Alloy Wheel_#_ENGINE_1GD-FTV (T) = Net Engine Power (RPM): 3000 - 3400