

Road vehicle descriptor

Information included in the Road Vehicle Descriptor (RVD) is supplied by the applicant for a vehicle type approval. This information is made available by the department for download to assist in defining the variants covered by the application or approval.

This downloaded version of the RVD is current on the date of the download identified below.

This information has not been verified or approved by the department. The department makes no statements or representations about the accuracy or completeness of this information.

Document Generated: 16/04/2026 16:12

General information

Vehicle type approval number:	VTA-049434 20260414
Make:	SUZUKI
Model:	GJ
Marketing designation:	
Category:	M - Passenger Vehicle

Secure vehicle identifier / vehicle plate details

Location:	30-M-10
------------------	---------

List of variant(s)

Variant information for B74V

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	WAGON
NSW body code:	Off-Road Passenger Vehicle 4wd
Seating options:	4
Max. seating capacity (including driver):	
No. of doors side:	2
No. of doors rear:	1
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	1087
Gross vehicle mass (kg):	1450
Maximum towing mass (braked trailer) (kg):	1300
Maximum towing mass (non-braked trailer) (kg):	350
Gross combination mass (kg):	

B-Double capable:	☐
Road train capable:	☐

Major Dimensions

Vehicle length (mm):	3650
Vehicle width (mm):	1645
Vehicle height (mm):	1705
Wheelbase (mm):	2250
Running clearance (mm):	210

Engine details

Engine name	Variant availability type	Mass variation amount
K15B	Standard (S)	

Service Brake

Service brake name	Variant availability type
GJ20	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Part time 4WD 5MT	Standard (S)	
Part time 4WD 4AT	Heavier (+)	10

Tyre and Rim

Tyre and rim name	Variant availability type
195/80R15	Std Front and Rear (SB)
195/80R15	Opt Front and Rear (OB)

Suspension

Suspension name
GJ

Standard equipment or options

Name	Variant availability type
Side airbags	Standard (S)
Aluminum wheel	Optional (O)
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power mirrors	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
JSAGJB74V00123456

Typical vehicle identification number (VIN) details

VIN:	JSAGJB74V00123456
Location:	on the right side frame rear member
Variant	
B74V	

Engine specifications

K15B

Motive power:	Petrol (P)
Configuration:	In line 4 cylinder (IL4)
Net engine power (kW):	75.00
Net engine power (rpm):	6000
Capacity (cc):	1,462.00
Fuel injection type:	Multipoint injection (MPI)
Induction type:	Natural (N)
Typical engine number:	K15B-1234567
Location:	left side of cylinder block

Variant(s) this engine is applicable and the mass variation

Variant	Mass variation (kg) - positive or negative variation from tare weight	Mass variation amount
B74V	Standard (S)	

Service brake specifications

GJ20

Actuation type:	Hydraulic (H)
Power assisted:	Vacuum (VAC)

Front

Type:	Disc Non-ventilated (DIN)
Diameter (mm):	290
Width (mm):	10

Rear

Type:	Drum (DR)
Diameter (mm):	220
Width (mm):	39

For which variant(s) is the service brake applicable and how is it available?

Variant	Variant availability type
B74V	Standard (S)

Transmission data specifications

Part time 4WD 5MT

Transmission type:	Manual All WD (MAWD)
Forward gears:	5

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
B74V	Standard (S)	

Part time 4WD 4AT

Transmission type:	Automatic All WD (AAWD)
Forward gears:	4

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
B74V	Heavier (+)	10

Tyre and rim specifications

195/80R15

Tyre designation:	195/80R15
Rim size and profile:	15X5 1/2JJ
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	5
Front wheel track (mm):	1395
Rear wheel track (mm):	1405

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
B74V	Std Front and Rear (SB)

195/80R15

Tyre designation:	195/80R15
Rim size and profile:	15X5 1/2J
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	5
Front wheel track (mm):	1395
Rear wheel track (mm):	1405

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
B74V	Opt Front and Rear (OB)

Suspension data specifications

GJ

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	464	479
Vertical measurement of wheel centre to top of wheel arch opening at full bump	408	417
Minimum acceptable vertical measurement of wheel centre to top of wheel arch	445	458

Variant(s) this suspension is applicable to, and how it is available

Variant
B74V

Standard equipment or options which may affect ADR compliance

Remarks

Spare Tyre and Rim: same as Front/Rear Tyre and Rim.