

描述

因子研究

[纯文本] [预览](#)

☒ 丢弃旧的构建

策略Log Rotation

保持构建的天数5

如果非空，构建记录将保存此天数

保持构建的最大个数

如果非空，最多此数目的构建记录将被保存

高级...

☐ 参数化构建过程

☐ 关闭构建

☐ 在必要的时候并发构建

高级...

源码管理

☐ 无

☒ Git

Repositories

Repository URLhttp://zhuwenda@192.168.8.238/FMS/factor.git

Credentialsex-zhuwd@cmfchina.com/\*\*\*\*\*添加

高级...

Add Repository

Branches to build

Branch Specifier (blank for 'any')\*/master

Add Branch

源码库浏览器

(自动)

Additional Behaviours

新增

构建触发器

☐ 触发远程构建 (例如,使用脚本)

☒ Generic Webhook Trigger

Is triggered by HTTP requests to **http://JENKINS\_URL/generic-webhook-trigger/invoke**

There are example configurations in [the Git repository](#).

You can fiddle with JSONPath [here](#). You may also want to checkout the syntax [here](#).

You can fiddle with XPath [here](#). You may also want to checkout the syntax [here](#).

You can fiddle with regular expressions [here](#). You may also want to checkout the syntax [here](#).

If your job is **not parameterized**, then the resolved variables will just be contributed to the build. If your job is **parameterized**, and you resolve variables that have the same name as those parameters, then the plugin will populate the parameters when triggering job. That means you can, for example, use the parameters in combination with an SCM plugin, like GIT Plugin, to pick a branch.

General

源码管理

构建触发器

Optional filter

构建环境

构建

构建后操作

Header parameters

新增

If you want value of header **param1** to be contributed, you need to add "param1" here.

Request parameters

新增

If you want value of query parameter **param1** to be contributed, you need to add "param1" here.

Token

factor

Optional token. If it is specified then this job will can only be triggered if that token is supplied when invoking **http://JENKINS\_URL/generic-webhook-trigger/invoke**. It can be supplid as a:

- Query parameter **/invoke?token=TOKEN\_HERE**
- A token header **token: TOKEN\_HERE**
- A Authorization: Bearer header **Authorization: Bearer TOKEN\_HERE**

Cause

Generic Cause

This will be displayed in any triggered job. You can use the variables here to create a custom cause like "*\$name committed to \$branch*", if you have configured variables named **name** and **branch**.

Silent response

☐

Avoid responding with information about triggered jobs.

Print post content

☐

Print post content in job log.

Print contributed variables

☐

Print contributed variables in job log.

Optional filter

Expression

[Regular expression](#) to test on the evaluated text specified below. The regexp syntax is documented [here](#).

Text

admin

Text to test for the given [expression](#). You can use any combination of the variables you configured above.

This is an optional feature. If specified, this job will only trigger when given expression matches given text.

☐ 其他工程构建后触发



☐ 定时构建



☐ 轮询 SCM



构建环境

☐ Delete workspace before build starts



☐ Use secret text(s) or file(s)



☐ Provide Configuration files



☐ Send files or execute commands over SSH before the build starts



☐ Send files or execute commands over SSH after the build runs



☐ Abort the build if it's stuck

☐ Add timestamps to the Console Output

☐ Execute shell script on remote host using ssh



☐ Provide Node & npm bin/ folder to PATH

构建



调用顶层 Maven 目标



Maven 版本

maven-3.3.9



目标



## 执行 shell

命令

`docker build -t factor .`[查看 可用的环境变量列表](#)

高级...

## 执行 shell

命令

```
# 将镜像推送到远程仓库
registry=192.168.8.192:5000
namespace=fms
img_list="factor"
username=fms
password=Cmf_2011

docker login -u $username -p $password $registry
for item in $img_list;do
  docker tag $item $registry/$namespace/$item
  docker push $registry/$namespace/$item
done
```

[查看 可用的环境变量列表](#)

高级...

## Send files or execute commands over SSH

SSH Publishers

## SSH Server

Name

192.168.124.167

高级...

Transfers

## Transfer Set

Source files

Remove prefix

Remote directory

Exec command

`cd /root/fms && ./docker-compose-factor.sh`

All of the transfer fields (except for Exec timeout) support substitution of [Jenkins environment variables](#)

高级...

Add Transfer Set

Add Server

高级...

增加构建步骤

## 构建后操作

增加构建后操作步骤

General

源码管理

构建触发器

Optional filter

构建环境

构建

构建后操作