

gaussianKernel.m

```

1 function sim = gaussianKernel(x1, x2, sigma)
2 %RBFKERNEL returns a radial basis function kernel between x1 and x2
3 %   sim = gaussianKernel(x1, x2) returns a gaussian kernel between x1 and x2
4 %   and returns the value in sim
5
6 % Ensure that x1 and x2 are column vectors
7 x1 = x1(:); x2 = x2(:);
8
9 % You need to return the following variables correctly.
10 sim = 0;
11
12 sim = exp(-(sum((x1-x2).^2)/(2*sigma^2)));
13
14 end

```

dataset3Params.m

```

1 function [C, sigma] = dataset3Params(X, y, Xval, yval)
2 %DATASET3PARAMS returns your choice of C and sigma for Part 3 of the exercise
3 %where you select the optimal (C, sigma) learning parameters to use for SVM
4 %with RBF kernel
5
6 % You need to return the following variables correctly.
7 C = 1;
8 sigma = 0.3;
9
10 maxError = Inf;
11
12 % It would be nice if this didn't do function optimization by exhaustive search :-/
13 for currC = [0.01 0.03 0.1 0.3 1 3 10 30]
14     for currSigma = [0.01 0.03 0.1 0.3 1 3 10 30]
15         model = svmTrain(X, y, currC, @(x1, x2) gaussianKernel(x1, x2, currSigma));
16
17         predictions = svmPredict(model, Xval);
18         predictionError = mean(double(predictions ~= yval));
19
20         if predictionError < maxError
21             maxError = predictionError;
22             C = currC;
23             sigma = currSigma;
24         end
25     end
26 end
27
28 end

```

processEmail.m

```

1 function word_indices = processEmail(email_contents)
2 %Preprocesses the body of an email and returns a list of indices of the
3 %words contained in the email.
4
5 % Load Vocabulary
6 vocabList = getVocabList();
7
8 % Init return value
9 word_indices = [];

```

```

10
11 % ===== Preprocess Email =====
12
13 % Find the Headers ( \n\n and remove )
14 % Uncomment the following lines if you are working with raw emails with the
15 % full headers
16
17 % hdrstart = strfind(email_contents, ([char(10) char(10)]));
18 % email_contents = email_contents(hdrstart(1):end);
19
20 % Lower case
21 email_contents = lower(email_contents);
22
23 % Strip all HTML
24 % Looks for any expression that starts with < and ends with > and replace
25 % and does not have any < or > in the tag it with a space
26 email_contents = regexprep(email_contents, '<[^\>]+>', ' ');
27
28 % Handle Numbers
29 % Look for one or more characters between 0-9
30 email_contents = regexprep(email_contents, '[0-9]+', 'number');
31
32 % Handle URLs
33 % Look for strings starting with http:// or https://
34 email_contents = regexprep(email_contents, ...
35                             '(http|https)://[^\s]*', 'httpaddr');
36
37 % Handle Email Addresses
38 % Look for strings with @ in the middle
39 email_contents = regexprep(email_contents, '[^\s]+@[^\s]+', 'emailaddr');
40
41 % Handle $ sign
42 email_contents = regexprep(email_contents, '[$]+', 'dollar');
43
44
45 % ===== Tokenize Email =====
46
47 % Output the email to screen as well
48 fprintf('\n==== Processed Email ==== \n\n');
49
50 % Process file
51 l = 0;
52
53 while ~isempty(email_contents)
54
55     % Tokenize and also get rid of any punctuation
56     [str, email_contents] = ...
57         strtok(email_contents, ...
58             [' @$/#.-:&*+=[ ]?!(){},">_<;%' char(10) char(13)]);
59
60     % Remove any non alphanumeric characters
61     str = regexprep(str, '[^a-zA-Z0-9]', '');
62
63     % Stem the word
64     % (the porterStemmer sometimes has issues, so we use a try catch block)
65     try str = porterStemmer(strtrim(str));
66     catch str = ''; continue;

```

```

67     end;
68
69     % Skip the word if it is too short
70     if length(str) < 1
71         continue;
72     end
73
74     % Look up the word in the dictionary and add to word_indices if
75     % found
76     % =====
77     for i = 1:length(vocabList)
78         if(strcmp(str, vocabList{i}))
79             word_indices = [word_indices ; i];
80         end
81     end
82     % =====
83
84     % Print to screen, ensuring that the output lines are not too long
85     if (l + length(str) + 1) > 78
86         fprintf('\n');
87         l = 0;
88     end
89     fprintf('%s ', str);
90     l = l + length(str) + 1;
91
92 end
93
94 % Print footer
95 fprintf('\n\n=====\\n');
96
97 end

```

emailFeatures.m

```

1  function x = emailFeatures(word_indices)
2  %Takes in a word_indices vector and
3  %produces a feature vector from the word indices.
4
5  % Total number of words in the dictionary
6  n = 1899;
7
8  % You need to return the following variables correctly.
9  x = zeros(n, 1);
10
11  for i = 1:length(word_indices)
12      x(word_indices(i))=1;
13  end
14
15  end

```